

March 6, 1951

H. N. HENRIKSEN  
 DEVICE FOR SEWING MACHINES

2,544,425

Filed Feb. 17, 1948

Fig. 1.




Fig. 2.





Fig. 4.




Fig. 5.




Fig. 3.

Inventor:  
 H. N. Henriksen,  
 By  
 E. F. Hendricks  
 atty

## UNITED STATES PATENT OFFICE

2,544,425

## DEVICE FOR SEWING MACHINES

Henrik Nielsen Henriksen, Odense, Denmark

Application February 17, 1948, Serial No. 8,919  
In Sweden February 25, 1944Section 1, Public Law 690, August 8, 1946  
Patent expires February 25, 1964

2 Claims. (Cl. 112—236)

1

This invention relates to a device for sewing machines comprising a holder with a U-shaped hook which is fixed to the presser foot bar of a sewing machine and which U-shaped hook is adjusted in such a manner that the presser foot of the sewing machine is raised during a part of the movement of the needle-bar, so that the fabric to be sewn will thereby be released for a moment during each upward movement of the needle-bar. It is then possible to displace the fabric and easily and rapidly to effect darning by means of the sewing machine and furthermore to make elastic zigzag sewings or seams or other desired sewing operations which it is otherwise impossible to make by means of a sewing machine of the usual type.

The accompanying drawing illustrates an embodiment of the invention. Figs. 1 and 3 show a part of a sewing machine provided with a hook member according to the invention, in front and in rear elevation. Fig. 2 shows the machine in front elevation the hook member being in operative position, and Figs. 4 and 5 show in detail the hook member, as seen obliquely from above and obliquely from below.

1 designates a part of a sewing machine with a needle-bar 2 having a wing nut 3 and a clamping means 4 for holding a needle 5 which is moved by the needle-bar down through the machine table 6, and with a presser foot 7 arranged on a bar 8 of the known type.

According to the invention there is fixed to the presser foot a U-shaped holder 9 by means of a screw 11 (Fig. 3) arranged on the presser foot in the usual manner, which screw is first removed and, after the holder 9 has been mounted, is passed through a hole 10 in one end 19 of the holder (Figs. 4 and 5) and is then tightened and maintains the holder in the position shown in Figs. 1 to 3. In the other end 18 of the holder there is fixed a rivet 12 with a large inwardly directed head 13 below which there is tightly rotatably fixed an eye 14 formed on the bent end 15 of a U-shaped hook 16 having its free end 17 bent to serve as a finger grip for adjustment of the U-shaped hook 16.

When the U-shaped hook 16 is in the position shown in Figs. 1 and 3, the sewing machine can be used for ordinary sewing purposes. If the U-shaped hook 16 is swung down to the position shown in Fig. 2, the clamping means 4 will come into contact with the U-shaped hook 16 at every upwardly directed movement of the needle-bar 2, will enter one corner 20 and cause the U-shaped hook 16, the bar 8 and the presser foot

2

7 to partake in its movement, the presser foot being thereby raised from the table 6 when the needle 5 has left the table, so that it is possible to move the work (not shown) sideways, which is otherwise clamped under the presser foot. It is hereby possible to effect zigzag sewing operations or seams by means of the sewing machine, e. g. zigzag seams as running lines for elastics or elastic seams in underwear, mending across hole edges or similar work. The presser foot will fall down on the fabric and hold it when the needle again passes through the fabric. The U-shaped hook 16 may be turned more or less downwardly and be bent together or stretched out, since it is made of a resilient metal wire, and it is thus possible to regulate the distance to which the presser foot may be raised and the U-shaped hook can be arranged to fit different sizes and types of sewing machines.

The device may also be constructed in a manner other than that shown, without departing from the idea of invention. Thus the fitting may possibly be made adjustable so as to enable arrangement thereof on presser feet of different constructions or on the needle-bar. The U-shaped means may be made of several parts, adjustable in relation to each other, in order to abut against parts of the needle-bar or the presser foot for causing said presser foot to partake in the movement of the needle-bar during a certain part of the motion of the needle.

I claim:

1. A device for sewing machines having a needle-bar and presser foot on a presser foot bar comprising a U-shaped holder removably attached to said presser foot bar, said holder being attached to said bar by means of the screw attaching said presser foot to said bar, a rivet having an enlarged head attached to said holder on the side opposite the side attached to said presser bar, said enlarged head being arranged internally of said U-shaped holder, a U-shaped hook having an eye formed at one end thereof, said eye being tightly rotatably journaled on said rivet between a side of said holder and said enlarged head, said U-shaped hook member being adjustably rotatable to contact with said needle-bar whereby upon upward movement of said needle-bar said hook member will be contacted thereby and said presser foot bar and said presser foot will be raised with said needle-bar.

2. A device for sewing machines as claimed in claim 1, said U-shaped holder having a hole through a side thereof for insertion therethrough of the screw member securing the presser foot

3

to said presser foot bar, said U-shaped hook member having an end thereof outwardly bent, said bent end comprising a finger grip for adjustably moving said hook into and out of operative contacting position with said needle-bar.

HENRIK NIELSEN HENRIKSEN.

#### REFERENCES CITED

The following references are of record in the file of this patent:

5

Number  
1,102,433

Number  
28,670

4

#### UNITED STATES PATENTS

Number	Name	Date
1,102,433	Pettit	July 7, 1914

#### FOREIGN PATENTS

Number	Country	Date
28,670	Germany	Nov. 14, 1883

10