




(22) Date de dépôt/Filing Date: 2005/02/09
 (41) Mise à la disp. pub./Open to Public Insp.: 2005/08/25
 (62) Demande originale/Original Application: 2 552 352
 (30) Priorité/Priority: 2004/02/09 (US60/543,364)

(51) Cl.Int./Int.Cl. *B65D 81/34* (2006.01),
B65D 81/03 (2006.01), *H05B 6/74* (2006.01)
 (71) Demandeur/Applicant:
GRAPHIC PACKAGING INTERNATIONAL, INC., US
 (72) Inventeurs/Inventors:
COLE, LORIN R., US;
BOHRER, TIMOTHY H., US;
MIDDLETON, SCOTT W., US;
ROBISON, RICHARD G., US;
LAFFERTY, TERRENCE P., US;
O'HAGAN, BRIAN R., US;
WNEK, PATRICK H., US
 (74) Agent: MACRAE & CO.

(54) Titre : CONDITIONNEMENT DE CUISSON AU FOUR A MICRO-ONDES ET CONSTITUTION
 (54) Title: MICROWAVE COOKING PACKAGE AND METHODS OF MAKING THEREOF



(57) **Abrégé/Abstract:**

A microwave insulating material includes a dimensionally stable support, a patterned adhesive layer overlying at least a portion of the support, a polymer film layer overlying the patterned adhesive layer, and a plurality of expandable cells disposed between the support and the polymer film layer and defined by the patterned adhesive layer, wherein the expandable cells vary in size. A self-sealing microwave package includes a sheet of insulating material including a first surface, and a thermally activatable adhesive applied to at least a portion of the first surface.

ABSTRACT

A microwave insulating material includes a dimensionally stable support, a patterned adhesive layer overlying at least a portion of the support, a polymer film layer overlying the patterned adhesive layer, and a plurality of expandable cells disposed between the support and the polymer film layer and defined by the patterned adhesive layer, wherein the expandable cells vary in size. A self-sealing microwave package includes a sheet of insulating material including a first surface, and a thermally activatable adhesive applied to at least a portion of the first surface.

MICROWAVE COOKING PACKAGES AND METHODS OF MAKING THEREOF

This application is a division of Canadian Patent Application No.
5 2,552,352, filed February 9, 2005.

FIELD OF THE INVENTION

The present invention relates to the field of food preparation, and in particular, relates to materials and constructs that may be used to prepare foods
10 in a microwave oven.

BACKGROUND OF THE INVENTION

Microwave ovens commonly are used to cook food in a rapid and effective manner. To optimize the cooking performance of microwave ovens,
15 various food packaging arrangements have been developed to block, enhance, direct, and otherwise affect microwave interaction with food.

If browning or crisping of the exterior of the food item is desired, the food item is placed in a container that includes a susceptor. The susceptor typically includes a microwave energy interactive material, such as a metal,
20 that absorbs, reflects, and transmits microwave energy in varying proportions. The surface to be browned is placed proximate the susceptor. The susceptor absorbs the microwave energy, and transmits heat to the food item to promote surface browning and crisping. Further, some of the microwave energy is transmitted to the inside of the food item.

25 Numerous susceptor configurations, shapes, and sizes are known in the art. Depending on the susceptor arrangement, the time of exposure to microwave energy, the desired degree of browning and crisping, and other factors, the susceptor may be in intimate or proximate contact with the food item. Thus, a material or package including a susceptor may be used to cook a

food item, and to brown or crisp the surface of the food item in a way similar to conventional frying, baking, or grilling.

One particular food packaging arrangement that may employ susceptors involves closed cells formed between layers of packaging material. Upon exposure to microwave energy, the cells expand to form inflated cells that insulate the food item in the package from the microwave environment. One example of a microwave packaging material that provides inflatable cells is described in co-pending published PCT application PCT/US03/03779 titled “Insulating Microwave Interactive Packaging”, which is hereby incorporated by reference herein.

Despite these advances, numerous challenges in microwave cooking remain. For example, removal of large objects from a microwave oven, if not properly supported, can be difficult. If a flat tray supporting a pizza is grasped along only one side and lifted from the oven, the tray might bend and cause the pizza to slide off the tray. Additionally, many packages are fixed in shape and do not provide sufficient intimate or proximate contact with the food item to brown or crisp the surface of the food item. Some packages provide partitions to increase contact with the food item but, in many cases, the shape and size of the partitions are adapted to a standard or nominal food item size that does not accommodate any variation in the size of the food item. For example, if the cross sectional size of a portion of French fries varies, only a portion of the fries will contact the microwave interactive components of the package. Thus, there remains a need for improved microwave energy interactive packages.

25

SUMMARY OF THE INVENTION

The present invention generally relates to materials and packages, and methods of making such materials and packages, for use with microwaveable food items. In various aspects, an insulating material is used. In one aspect, the present invention involves a microwave sheet with a self-sealing feature to

provide a partially sealed food wrap after the sheet is exposed to microwave energy. In another aspect, the present invention involves a microwave sheet or package employing variably sized and variably expansive cells for use in shipping, microwave cooking, and other uses. In another aspect, the present invention is directed to a microwave tray with side walls that form upon exposure to microwave energy. The present invention also relates to an insulating microwave material or other microwave packaging material with an oxygen barrier. Further, the present invention relates to insulating microwave material or other microwave packaging material formed at least in part with a thermo-mechanical device. The present invention also includes a method of wrapping a food item in an insulating microwave material and, optionally, a protective overwrap. Finally, the present invention includes a package with a lid that can be tucked under the package during microwave cooking to provide additional insulation and heating.

15

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a cross-sectional view of an insulating microwave material that may be used in accordance with the present invention;

FIG. 1B is a perspective view of the insulating microwave material of **FIG. 1A**;

FIG. 1C is a perspective view of the insulating microwave material of **FIG. 1A** after exposure to microwave energy;

FIG. 1D is a cross-sectional view of an alternative insulating microwave material that may be used in accordance with the present invention;

FIG. 2 is a cross-sectional view of yet another alternative microwave insulating material in accordance with one aspect of the present invention, and that may be used in accordance with the present invention;

FIG. 3 is a cross-sectional view of still another alternative microwave insulating material in accordance with one aspect of the present invention, and that may be used in accordance with the present invention;

FIG. 4 is a perspective view of a sheet of microwave material having an activatable adhesive portion in accordance with the present invention;

FIG. 5 is a perspective view of the sheet of **FIG. 4** with a food item placed thereon;

FIG. 6 is a perspective view of the sheet of **FIG. 5** with a portion of the sheet folded over the food item;

FIG. 7 is a perspective view of the sheet of **FIG. 4** with a second portion of the sheet folded over so the first portion of the sheet, thereby forming a sleeve;

FIG. 8 is another perspective view of the sheet of **FIG. 7**;

FIG. 9 is a cross-sectional view of the sheet of **FIG. 8** taken along a line 9-9;

FIG. 10 is a perspective view of the sheet and food item of **FIG. 7** after exposure to microwave energy;

FIG. 11 is a cross-sectional view of the sheet of **FIG. 10** taken along a line 11-11;

FIG. 12 is a perspective view of a sheet of microwave material including an activatable adhesive portion in accordance with one aspect of the present invention, with a food item placed thereon;

FIG. 13 is a perspective view of the sheet of **FIG. 12** with a portion of the sheet folded over the food item;

FIG. 14 is a perspective view of the sheet of **FIG. 13** with a second portion of the sheet folded over the food item to form a pocket around the food item;

FIG. 15 is a perspective view of a sheet of microwave material including an activatable adhesive in accordance with the present invention, with a food item placed thereon;

FIG. 16 is a perspective view of the sheet of **FIG. 15** with a portion of the sheet folded over the food item;

FIG. 17 is a perspective view of the sheet of **FIG. 16** with a second portion of the sheet folded over the food item to form a pocket around the food item;

FIG. 18 is a top plan view of a package employing a plurality of variable arranged insulating expanding cell arrangements, in accordance with the present invention;

FIG. 19 is a cross-sectional view of the package of **FIG. 18** taken along a line 19-19;

FIG. 20 is a cross-sectional view of a package employing complimentary variably expanding cell arrangements, in accordance with the present invention;

FIG. 21 is a perspective view of the package of **FIG. 18**;

FIG. 22A is a perspective view of a package having an insulating material on at least a portion of the inside thereof, in a closed position;

FIG. 22B is a perspective view of a package having an insulating material on at least a portion of the inside thereof, in an open position;

FIG. 23 is a perspective view of an exemplary microwave tray having four self-forming walls in the non-folded position;

FIG. 24 is an exploded view of the tray of **FIG. 23**;

FIG. 25 is a cross-sectional view of the tray of **FIG. 23** before exposure to microwave energy;

FIG. 26 is a cross-sectional view of the tray of **FIG. 23** after exposure to microwave energy;

FIG. 27 is a perspective view of an alternative microwave tray structure defining four self-forming flaps in the non-folded position;

FIG. 28 is an exploded view of the tray of **FIG. 27**;

FIG. 29 is a cross-sectional view of the tray of **FIG. 27** before
5 exposure to microwave energy;

FIG. 30 is a cross-sectional view of the sheet of **FIG. 27** after exposure to microwave energy;

FIG. 31 is a cross-sectional view of an exemplary insulating microwave material with an oxygen barrier, in accordance with the present
10 invention;

FIG. 32 is a cross-sectional view of another exemplary insulating microwave material with an oxygen barrier, in accordance with the present invention;

FIG. 33 is a cross-sectional view of yet another exemplary insulating
15 microwave material with an oxygen barrier, in accordance with the present invention;

FIG. 34 is a cross-sectional view of the layers used to form an exemplary insulating microwave material;

FIG. 35 is a cross-sectional view of the layers of **FIG. 34** with a
20 plurality of thermo-mechanical devices arranged to define a pattern of bonds between the layers;

FIG. 36 is a cross-sectional view of the material and devices of **FIG. 35**, with the thermo-mechanical devices pressed into the layers to define closed cells;

FIG. 37 is a cross-sectional view of an insulating microwave material
25 after processing with a thermo-mechanical device;

FIG. 38 is a detail of a section of **FIG. 37** illustrating a bond between layers;

FIG. 39 is a cross-sectional view of a tool adapted to press form a container configuration, in an open position;

FIG. 40 is a cross-sectional view of the tool of **FIG. 39** in the closed position;

5 **FIG. 41** is a perspective view of the container formed by the tool of **FIG. 39** and **FIG. 40**;

FIG. 42 is a cross-sectional view of the container of **FIG. 41** taken along a line **42-42**;

FIG. 43 is an enlarged view of a portion of the container of **FIG. 42**;

10 **FIG. 44** is a perspective view of an alternative container shape formed with a tool with integrated thermo-mechanical bonding elements;

FIG. 45 is a perspective view of an exemplary process for forming an insulating microwave material sleeve around a food item in accordance with the present invention;

15 **FIG. 46** is a cross-sectional view of the heat seal and cut-off tool of **FIG. 45** taken along a line **46-46** in an open position;

FIG. 47 is a cross-sectional view of the heat seal and cut-off tool of **FIG. 45** taken along line **47-47** in an actuated position;

20 **FIG. 48** is a cross-sectional view of the wrapped food item of **FIG. 45** taken along a line **48-48**;

FIG. 49 is a cross-sectional view of a wrapped food item taken along line **49-49** of **FIG. 48**;

25 **FIG. 50** is a perspective view of a package with an underfolding insulating lid, in accordance with one aspect of the present invention, in a closed position;

FIG. 51 is another perspective view of the package of **FIG. 50** in an open position; and

FIG. 52 is another perspective view of the package of **FIGS. 50** and **51** with the lid folded under the tray.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates generally to various aspects of materials and packages for microwave cooking of food items, and methods of making such materials and packages. Although several different inventions, aspects, implementations, and embodiments of the various inventions are provided, numerous interrelationships between, combinations thereof, and modifications of the various inventions, aspects, implementations, and embodiments of the inventions are contemplated hereby.

According to various aspects of the present invention, an insulating material is used to form numerous constructs for microwave cooking and packaging of foods. As used herein, an “insulating microwave material” refers to any arrangement of layers, such as polyester layers, susceptor or “microwave interactive” layers, polymer layers, paper layers, continuous and discontinuous adhesive layers, and patterned adhesive layers, that provides an insulating effect. The sheet or package may include one or more susceptors, one or more expandable insulating cells, or a combination of susceptors and expandable insulating cells. Examples of materials that may be suitable, alone or in combination, include, but are not limited to, are QwikWave® Susceptor, QwikWave® Focus, Micro-Rite®, MicroFlex® Q, and QuiltWave™ susceptor, each of which is commercially available from Graphic Packaging International, Inc.

An exemplary insulating material **10** is depicted in **FIGS. 1A-1D**. In each of the examples shown herein, it should be understood that the layer widths are not necessarily shown in perspective. In some instances, for example, the adhesive layers are very thin with respect to other layers, but are nonetheless shown with some thickness for purposes of clearly illustrating the arrangement of layers.

Referring to **FIG. 1A**, the material **10** may be a combination of several different material layers. A susceptor, which typically includes a thin layer of microwave interactive material **14** on a first plastic film **16**, is bonded for example, by lamination with an adhesive **18**, to a dimensionally stable substrate **20**, for example, paper. The substrate **20** is bonded to a second plastic film **22** using a patterned adhesive **26** or other material, such that closed cells **28** are formed in the material **10**. The closed cells **28** are substantially resistant to vapor migration.

Optionally, an additional substrate layer **24** may be adhered by adhesive **29** or otherwise to the first plastic film **16** opposite the microwave interactive material **14**, as depicted in **FIG. 1D**. The additional substrate layer **24** may be a layer of paper or any other suitable material, and may be provided to shield the food item (not shown) from any flakes of susceptor film that craze and peel away from the substrate during heating. The insulating material **10** provides a substantially flat, multi-layered sheet **30**, as shown in **FIG. 1B**.

FIG. 1C depicts the exemplary insulating material **10** of **FIGS. 1A** and **1B** subjected to microwave energy from a microwave oven (not shown). As the susceptor film **12** heats upon impingement by microwave energy, water vapor and other gases normally held in the substrate **20**, for example, paper, and any air trapped in the thin space between the second plastic film **22** and the substrate **20** in the closed cells **28**, expand. The expansion of water vapor and air in the closed cells **28** applies pressure on the susceptor film **12** and the substrate **20** on one side and the second plastic film **22** on the other side of the closed cells **28**. Each side of the material **10** forming the closed cells **28** reacts simultaneously, but uniquely, to the heating and vapor expansion. The cells **28** expand or inflate to form a quilted top surface **32** of pillows separated by channels (not shown) in the susceptor film **12** and substrate **20** lamination, which lofts above a bottom surface **34** formed by the second plastic film **22**.

This expansion may occur within 1 to 15 seconds in an energized microwave oven, and in some instances, may occur within 2 to 10 seconds.

FIGS. 2 and 3 depict alternative exemplary microwave insulating material layer configurations that may be suitable for use with any of the various sheet, packaging, and other constructs of the present invention. Referring first to **FIG. 2**, an insulating microwave material **40** is shown with two symmetrical layer arrangements adhered together by a patterned adhesive layer. The first symmetrical layer arrangement, beginning at the top of the drawings, comprises a PET film layer **42**, a metal layer **44**, an adhesive layer **46**, and a paper or paperboard layer **48**. The metal layer **44** may comprise a metal, such as aluminum, deposited along a portion or all of the PET film layer **42**. The PET film **42** and metal layer **44** together define a susceptor. The adhesive layer **46** bonds the PET film **42** and the metal layer **44** to the paperboard layer **48**.

The second symmetrical layer arrangement, beginning at the bottom of the drawings, also comprises a PET film layer **50**, a metal layer **52**, an adhesive layer **54**, and a paper or paperboard layer **56**. If desired, the two symmetrical arrangements may be formed by folding one layer arrangement onto itself. The layers of the second symmetrical layer arrangement are bonded together in a similar manner as the layers of the first symmetrical arrangement. A patterned adhesive layer **58** is provided between the two paper layers **48** and **56**, and defines a pattern of closed cells **60** configured to expand when exposed to microwave energy. In one aspect, an insulating material **10** having two metal layers **44** and **52** according to the present invention generates more heat and greater cell loft.

Referring to **FIG. 3**, yet another insulating microwave material **40** is shown. The material **40** may include a PET film layer **42**, a metal layer **44**, an adhesive layer **46**, and a paper layer **48**. Additionally, the material **40** may include a clear PET film layer **50**, an adhesive **54**, and a paper layer **56**. The

layers are adhered or affixed by a patterned adhesive **58** defining a plurality of closed expandable cells **60**.

Use of any of the exemplary insulating materials to package and/or cook a food item provides several benefits before, during, and after heating in a microwave oven. First, the water vapor and air contained in the closed cells provides insulation between the food item and the interior surfaces of the microwave oven. The base of a microwave oven, for example, the glass tray found in most microwave ovens, acts as a large heat sink, absorbing much of the heat generated by the susceptor film or within the food item itself. The vapor pockets in the pillows formed by the present invention maybe used to insulate the food item and susceptor film from the microwave oven surfaces and the vented air in the microwave oven cavity, thereby increasing the amount of heat that stays within or is transferred to the food item.

Second, the formation of the pillows allows the material to conform more closely to the surface of the food item, placing the susceptor film in greater proximity to the food item. This enhances the ability of the susceptor film to brown and crisp the surface of the food item by conduction heating, in addition to some convection heating, of the food item.

Further, the insulating materials contemplated hereby may be desirable as a packaging material because it adds little bulk to the finished package, yet is transformed into a bulk insulating material without any consumer preparation before cooking.

I. Self-Sealing Microwave Sheet

According to one aspect of the present invention, a sheet of microwave packaging material is provided with an “activatable adhesive”. As used herein, the phrase “activatable adhesive” refers to any bonding agent or adhesive that bonds to itself or a material when exposed to microwave energy or heat. The food item is wrapped in the sheet and heated in a microwave oven, where it

self-seals during microwave heating to encompass all or a portion of the food item.

The type of activatable adhesive, the amount applied to the microwave sheet, and the coverage and positioning thereon may vary for a given application. Thus, the present invention contemplates numerous arrangements and configurations of the activatable adhesive on the microwave sheet as needed or desired. Where a stronger bond is desired, a particular adhesive may be selected and positioned accordingly. For a weaker bond, another particular adhesive may be selected and positioned accordingly. One example of an activatable adhesive that may be suitable for use with the present invention is amorphous polyethylene terephthalate ("APET"). For example, an APET layer may be co-extruded with a clear polyethylene terephthalate ("PET"). In one variation, the sheet or material includes a layer of DuPont MylarTM 850 PET with a heat-sealable APET layer. However, other activatable adhesives are contemplated by the present invention.

In one aspect, the activatable adhesive is not tacky or sticky before exposure to microwave energy or heat, making the sheet easier to handle. Alternatively, the adhesive may be somewhat tacky or sticky so that the user substantially can wrap the food item prior to exposure to microwave energy. Depending on the activatable adhesive employed and/or the amount of heat generated during cooking, some implementations of the invention may employ a susceptor layer under or adjacent the activatable adhesive to concentrate more heat in the area of the activatable adhesive and optimize bonding conditions.

In one aspect, a sheet or package arrangement with an activatable adhesive may include an insulating microwave material. For example, according to one aspect of the present invention, the self-sealing package includes an insulating material having expandable closed cells. Upon exposure to microwave energy, the cells expand to form inflated cells. While not

wishing to be bound by theory, it is believed that the inflated cells enhance the cooking efficiency of a microwave oven by reducing heat loss to the environment surrounding the package. For example, a microwave package, tray, or the like with insulating cells arranged between the food item and the glass tray in most microwave ovens is believed to reduce heat transfer between the food and the tray, allowing the food to heat more efficiently. Additionally, after cooking, a package with inflated cells may be comfortable to the touch, thereby allowing a user to comfortably grasp the package and remove it from the microwave oven. Optionally, the sheet is provided with a susceptor material. In one aspect, the susceptor material is positioned so that when the cells expand, the susceptor is are pressed against the food item in the package to enhance the heating, browning, and/or crisping thereof.

FIG. 4 is a perspective view of an exemplary microwave sheet **110** employing and defining an activatable adhesive region **112** on an insulating microwave material **114** according to the present invention. The shape and size of the sheet **110** and the location, size, and shape of the activatable adhesive region **112** may vary depending on the numerous factors, such as the shape and size of the food item (best seen in **FIGS. 5** and **6**) intended to be heated with the sheet **110**. The microwave sheet **110** defines one or more closed cells **116** that expand when exposed to microwave energy. The sheet **110** is provided in a rectangular shape, but any shape or size may be used as needed or desired. Additionally, the sheet **110** shown has square shaped insulating cells **116**, but other shapes are contemplated.

Turning to **FIG. 5**, a food item **118**, for example, a burrito, is placed on the sheet **110**. As shown in **FIGS. 6** and **7**, the user may center the food item **118** on the sheet **110**, wrap a first portion **120** (without activatable adhesive) of the sheet **110** over the food item **118** (**FIG. 6**), and then wrap a second portion **122** (with activatable adhesive) over the food item **118** (**FIG. 7**) so that at least a portion of the activatable adhesive **112** contacts the first portion **120** of the

sheet **110**. Folded in this manner, the sheet **110** forms a sleeve **124** around the food item **118**.

To assist the bonding and the formation of the sleeve **124**, the user may place the overlapping portions **120**, **122** of the sheet **110** under the food item **118** in a manner illustrated in **FIGS. 8** and **9** so that the wrapped sheet **110** is initially held together by the weight of the food item **118**. If desired, the sheet **110** may be provided with a tray **128** in which the wrapped food item **118** is placed for cooking.

The food item **118** wrapped in the sheet **110** then is placed in the microwave oven (not shown) and heated. During microwave heating, the microwave energy and/or the heat associated therewith activates the adhesive, thereby causing the overlapping edges of the sheet to adhere. In this manner, the sheet **110** generally forms a sleeve **124** with two open ends **130**, **132** around the food item **118**.

Additionally, exposure to microwave energy causes the cells **116** to expand, as shown in **FIGS. 10** and **11**. The expansion of the cells **116** during heating provides an insulating function, as discussed above. The insulation around the food item **118** provides more efficient heating by reducing heat loss to the surrounding microwave environment (e.g., the microwave tray and air). Additionally, the outer surface **134** of the self-formed sleeve **124** may be cooler to the touch than the food item within the sleeve **124**. As such, a user may grasp the formed sleeve **124** and remove the food item from the microwave oven. If desired, the user may eat the food item **118** directly from the formed sleeve **124**.

Further, where a susceptor material is used, the susceptor material is brought substantially into intimate and/or proximate contact with the food item **118** to brown or crisp the surface **136** thereof. Prior to cooking, some of the sheet **110** may not be in intimate contact with an irregularly shaped food item **118** wrapped therein. As such, only some portions of the food item will be

exposed to the susceptor material. The lofting or expansion of the cells **116** of the sheet **110** causes the susceptor layer to bulge against the food item, providing increased contact with the food item **118**, and thus more efficient heating, browning, and/or crisping thereof.

5 The exemplary sheet **110** depicted in **FIGS. 3-11** includes an activatable adhesive **112** that is positioned to facilitate self-formation of a sleeve **124** with two open ends **130, 132**. In contrast, **FIG. 12** shows another exemplary sheet **110** with insulating material **114** and activatable adhesive **112** provided along two adjacent edges **138, 140** of the sheet **110**. In this example,
10 the adhesive **112** is contiguously placed along a back edge **138** and a side edge **140** of the sheet **110**. The food item **118** is placed on the sheet **110** between the activatable adhesive regions **112a** and **112b**. In **FIG. 13**, the sheet **110** is wrapped over the food item **118**. In this example, a portion of the sheet **110** is folded over the food item so that the side edge **142** without adhesive first is
15 placed over the food item **118**. The back edge **138** is partially folded onto itself to engage the back activatable adhesive strip **112a**. **FIG. 14** depicts the sheet **110** with expanded cells **116** completely wrapped around the food item **118** after exposure to microwave energy. The overlapping edges are adhered to form a pocket **148** with one open end **152** (shown in hidden line) and one
20 closed end **146**. The self-forming pocket **148** provides the same advantages discussed in connection with **FIGS. 3-11** and further prevents excess juices, cheese, sauce, and the like and from dripping, provided that the pocket **148** is held with the open end **152** in a upward position during consumption of the food item **118**. The open end **152** also provides ventilation.

25 **FIGS. 15-17** illustrate a microwave sheet **110** in which the activatable adhesive **112** is provided along at least a portion of three adjacent edges **138, 140, 144** of the sheet **110**. In **FIG. 15**, a sheet **110** employing an insulating microwave material **114** and an adhesive strips **112a, 112b, and 112c** along a portion of the back edge **138**, a portion of the front edge **144**, and one of the

side edges 140, is shown. FIG. 16 illustrates the sheet 110 being folded over the food item 118. Folded in this manner, the adhesive 112c along the front edge 144 is aligned with itself or a portion of the front edge 144. Further, the adhesive 112a along the back edge 138 is also aligned with itself or a portion of the back edge 138. FIG. 17 illustrates the sheet 110 completely folded over the food item 118 and defining a sealed cooking vessel 150. The side edge 140 with adhesive is folded onto the corresponding opposite edge 142. The front edge 144 is bonded to itself and the back edge 138 also is bonded to itself to self form the vessel when exposed to heat or microwave energy. The embodiment of FIG. 17 may be further provided with one or more ventilation apertures, perforations, or holes (not shown) if needed or desired.

While various examples of self-sealing microwave sheets are shown and described herein, it should be understood that other arrangements and configurations are contemplated by the present invention. Thus, a microwave sheet may have a food contacting surface, a non-food contacting surface, or both, that is partially, substantially, or entirely covered by an activatable adhesive, for example, APET. In one aspect, the activatable adhesive, for example, APET, may cover substantially the food-contacting surface of the microwave sheet. In this manner, the food item may be placed on the sheet and the sheet folded over the food item a variety of possible ways to form a sleeve, a pocket, or some other container.

II. Heating and Shipping Microwave Interactive Sheet Employing Variably Sized and Variably Expansive Cells

Many food items are irregular in shape and small in size, making them difficult to insert into individual microwave susceptor sleeves for heating, browning, and crisping. Thus, according to another aspect of the present invention, a packaging material and package formed therefrom provides

improved contact between the material and multiple food items or a single food item having an irregular shape.

The material and package formed therefrom includes closed expandable cells that expand during exposure to microwave energy to conform to the shape and size of the food item. The cells may include one or more microwave interactive elements or susceptors. The cells expand upon exposure to microwave energy, thereby bringing the susceptor material into closer proximity to the surface of the food item. In one aspect, individual food items are wrapped or packaged in an insulating material, for example, a material having cells of varying sizes and configurations that may expand to differing degrees (termed herein “variably expanding cells” or “variable expanding cells”). The material may be any suitable expandable cell material as desired, and in some instances, may include any of the materials described herein, any of the materials described in PCT Application PCT/US03/03779, which is incorporated by reference herein, or any combination thereof. Optionally, the material may be used to form a package that provides support for and protection of fragile food items during shipping and handling prior to cooking.

The variably expanding cells and the non-uniform arrangements of the same provide several advantages over presently available microwave packaging materials. First, the cells provide insulation along the bottom and periphery of the food item, thereby preventing heat loss to the surrounding environment. Second, multiple cell arrangements may be used to form a sheet for use in a package, so that multiple food items can be cooked in the same package. Third, where a susceptor is included, the size, shape, and level of expansion may be customized to accommodate any food item, thereby providing increased proximity to the susceptor material and improved browning and crisping during microwave heating.

The size, shape, and configuration of the expanding cells may vary for a particular application. The cells may be arranged in any pattern, including rows, concentric circles, arrays of shapes or individual cells, or any other pattern as desired. Likewise, the difference in size between each of the expandable cells may vary for a particular application. In one aspect, one or more cells varies from about 5 to about 15% in expanded volume, as compared with the expanded volume of another cell. In another aspect, one or more cells varies from about 15 to about 25% in expanded volume when compared with the volume of another cell. In another aspect, one or more cells varies from about 25 to about 35%, from about 35 to about 45%, from about 45 to about 55%, from about 55 to about 65%, from about 65 to about 75%, from about 75 to about 85%, from about 85 to about 95%, from about 95 to about 105%, from about 105 to about 110%, from about 110 to about 115%, from about 115 to about 85%, from about 85 to about 100%, from about 100 to about 125%, from about 125 to about 150%, from about 150 to about 175%, from about 175 to about 200%, from about 200 to about 225%, from about 225 to about 250%, from about 250 to about 275%, from about 275 to about 300%, from about 300 to about 325%, from about 325 to about 350%, from about 350 to about 400%, from about 400 to about 450%, from about 450 to about 500%, from about 500 to about 600%, from about 600 to about 700%, from about 700 to about 800%, from about 800 to about 900%, from about 900 to about 1000%, or greater than 1000% in expanded volume, as compared with the expanded volume of another cell.

In another aspect, one or more cells varies from about 5 to about 15% in unexpanded surface area, as compared with the unexpanded surface area of another cell. In another aspect, one or more cells varies from about 15 to about 25% in unexpanded surface area when compared with the unexpanded surface area of another cell. In another aspect, one or more cells varies from about 25 to about 35%, from about 35 to about 45%, from about 45 to about 55%, from

about 55 to about 65%, from about 65 to about 75%, from about 75 to about 85%, from about 85 to about 95%, from about 95 to about 105%, from about 105 to about 110%, from about 110 to about 115%, from about 115 to about 85%, from about 85 to about 100%, from about 100 to about 125%, from about
5 125 to about 150%, from about 150 to about 175%, from about 175 to about 200%, from about 200 to about 225%, from about 225 to about 250%, from about 250 to about 275%, from about 275 to about 300%, from about 300 to about 325%, from about 325 to about 350%, from about 350 to about 400%, from about 400 to about 450%, from about 450 to about 500%, from about 500
10 to about 600%, from about 600 to about 700%, from about 700 to about 800%, from about 800 to about 900%, from about 900 to about 1000%, or greater than 1000% in unexpanded surface area, as compared with the unexpanded surface area of another cell.

In yet another aspect, cells may be provided around the periphery of the
15 food item so that during microwave heating, the cells expand along the periphery of the food item and brown the sides of the food item. In another aspect, cells are provided beneath the food product and around it. The cells positioned under the food item may expand to one height, and the cells adjacent the perimeter of the food item may expand to a second height that is
20 greater or less than the first height. In still another aspect, the cells may be arranged to form one or more cavities that can contain the individual food items. In this and other aspects, the susceptor material selectively is brought into proximate or intimate contact with the surface of the food item during expansion of the cells, thereby providing the desired degree of browning and
25 crisping.

Additional examples are provided in **FIGS. 18-22**. For convenience, food items and packages are described herein as having a top, bottom, and sides. In many instances, the top, bottom, and sides of a package or a food item are relative to a surface the food item is placed on and the perspective of

the viewer. It should be understood that reference to a top, bottom, or side is not meant to impart any particular limitation on the scope of the invention, but merely provide an easy way to refer to describe the features thereof.

Turning to **FIGS. 18-19**, a sheet **200** of insulating material **210** including variably expanding cells **212** is provided. The sheet **200** defines four arrangements **214** of variably expanding cells **212**. The sheet **200** may include the same arrangement of layers as shown in **FIGS. 1-3**, however, the adhesive pattern defining the expandable cells **212** is not uniform in shape. For each arrangement **214** of variably expansive cells **212**, a first set **216** of cells **212** collectively defining a somewhat circular shape is surrounded by a second set **218** of larger cells **212** collectively defining a somewhat ring shape. The cells **212** may be any shape as desired, such as oval, square, or hexagonal.

Each of the four arrangements **214** of cells **212** of **FIG. 18** may be used with a food item **220** that is circular, such as a pizza, pot pie, or any food item that is desirably browned and crisped on the bottom and sides thereof. To do so, the food item **220** is placed on the sheet **200** so that the bottom **224** of the food item **220** substantially is centered on the first set **216** of cells **212**. The periphery **226** of the food item **220** is then aligned with the inside edge **222** of the second set **218** of cells **212**. Four such food items **220** may be placed in each of the four arrangements **214** of variably expansive cells **212** and may, if desired, be used to form a package or other construct. When the sheet **200** or a package employing the sheet **200** is exposed to microwave energy, the first, inner set **216** of cells **212** lofts upward against the bottom **224** of the food item **220**. The outer set **218** of cells **212** lofts to a greater extent than the first set **216** of cells **212** against the periphery **226** of the food item **220**.

If desired, a package employing the sheet **200** with variable cells **212** includes a paperboard or other type cover **228**. The cover **228** may or may not include a microwave interactive material, such as a susceptor or antenna.

Further, vertical dividers (not shown) may be provided to maintain appropriate alignment of the food items with the cell arrangements.

In this and other aspects, the sheet may include microwave active elements or susceptors. The susceptors may be flat, continuous, or patterned, and/or deployed in combination with shielding or pseudo-shielding elements, such as thicker aluminum patches. Additionally, individual cells may be provided with patterned microwave interactive functionality or susceptors, which can aid further in providing custom heating, browning, and crisping of the food item. Likewise, the area between the cell arrangements may include one or more of any of such elements as needed or desired for proper heat distribution.

FIG. 20 depicts an exemplary package employing two sheets **200a**, **200b** of material **210**, each with the same variable cell arrangement **214** as that shown in **FIG. 18**. The food item **220** is placed on the first sheet **200a** in the same manner as discussed above with regards to **FIGS. 18** and **19**. The second sheet **200b** is placed over the food item **220** so that the generally circular shape of the first set **216b** of cells **212** is basically centered over the top surface **230** of the food item **220**, and the second set **218b** of cells **212** is arranged adjacent the periphery **226** of the food item **220**.

As shown in **FIG. 20**, upon exposure to microwave energy, the cells **212** on the first sheet **200a** loft upward in the same manner as discussed above with regard to **FIGS. 18** and **19**. As such, the first set **216a** of cells **212** engage the bottom **224** of the food item **220** and the second set **218a** of cells **212** bulge up against the outer periphery **226** of the food item **220**. The expanded cells **212** in the second sheet **200b** substantially are a mirror image of the first sheet **200a**, although other configurations are contemplated. The inner set **216b** of cells **212** expand downward to engage the top surface **230** of the food item **220** while the outer cells **218b** bulge downward to engage the outer periphery **226** of the food item **220**. The two sheets **200a** and **200b** thus

act in concert to completely or nearly completely surround the food item **220**. In this way, all or nearly all sides of the food item **220** are insulated by and in contact with the expanded cells **212**. Such a sheet or package may be used where browning of all surfaces of the food item is desirable.

5 Various package arrangements with variably-sized or variably-expandable cell sheets are contemplated by the present invention. In one aspect, an expandable cell sheet is disposed on the bottom and top panels of a folding carton. In another aspect, an expandable cell sheet is adhered to a pouch or sleeve. Further, a sheet with variable cells may be provided with an
10 activatable adhesive as described herein.

 According to another aspect of the present invention, a sheet or package with variable cell arrangements may be used to pack and transport food items. Some food items are quite fragile, especially in the frozen state, and can be damaged by the normal stresses of distribution, shipping, and
15 handling. It is known to provide thermoformed plastic trays with formed compartments to more securely hold the product. These trays are not typically capable, however, of providing susceptor functionality for microwave browning and crisping. Thus, according to this aspect, the sheet or package is exposed to microwave energy to expand the cells and hold the food items in
20 place during shipping. The sheet or package may be exposed with or without the food item or items therein, for a period of from 1 to about 15 seconds, for example, 2 to 10 seconds. In doing so, the cells expand and provide support and protection for the food item or items contained therein.

FIG. 21 illustrates an exemplary shipping and cooking package or
25 carton **250** in accordance with the present invention. The package **250** includes a sheet **200** with variable cells **212** adhered or otherwise inserted to the bottom portion **252** of a package **250**. Prior to loading the food items **220**, the package **250** including the sheet **200** is exposed briefly to microwave energy, which causes an initial expansion of the variable cells **212**. The food item (not

shown) then is placed therein as discussed above and the package **250** is closed with the food items (not shown) restrained and protected by the expanded variable cells **212**. If desired, the package **250** then may be exposed again to microwave energy to further expand the cells **212** and provide tighter
5 conformance to the shape of the food item (not shown). Alternatively, the food item may be placed in register on an unexpanded sheet or in a package, which then is briefly exposed to microwave energy to partially or completely expand the cells. Following heating by the user, the package **250** is opened and the undamaged and properly cooked individual food items (not shown) are
10 removed.

Another exemplary package is provided in **FIGS. 22A** and **22B**. The package **260** includes a tray **262** and a lid **264** including a tab **266**. Prior to being opened (**FIG. 22A**), the lid **264** covers the tray **262** and the food item (not shown) therein, and the tab **266** may be removably sealed to a front panel
15 **268** of the package **260**. When the food item (not shown) is ready to be heated, the package **260** is opened by pulling upward on the tab **266**. Vent holes **272** or other venting features (not shown) may be provided in the front panel **268** if needed or desired.

If desired, the lid may be pulled back along perforations (not shown)
20 located along or proximate edges **274a** and **274b**. The interior surface **276** of the lid **264** may include an insulating material **278**, with or without a susceptor layer, such as those described herein. The insulating material **278** may include an oxygen barrier layer, variably sized and/or variably expanding cells, partially expanded cells, or numerous other features disclosed herein or
25 contemplated hereby. To re-close the package **260** after being opened, the tab **266** may engage a corresponding slot **280** to secure the lid **264** in position. However, other means of securing the tab **266** are contemplated hereby.

If desired, additional insulating material **278** may be provided on one or more interior surfaces of the package, for example, on the bottom interior

surface **288** to enhance heating, browning, and crisping of the food product, or to provide further insulation between the food item and the bottom of the tray and the floor of the microwave oven.

A package in accordance with this aspect of the present invention may
 5 be suitable for the packaging, transportation, and cooking of numerous types of food items. For example, the package may be used for irregularly shaped items, such as French fries, and may incorporate other features disclosed herein, such as variably expanding cells, such as those discussed above, and pre-expanded cells, such as those discussed below.

10

III. Insulating Material and Tray with Self-Forming Walls Formed Therewith

According to another aspect of the present invention, a microwave tray
 15 is provided. The tray is flat initially, but upon exposure to microwave energy, one or more flaps or edges of the tray fold upward to form flaps substantially perpendicular to the tray. The flaps serve to strengthen and support the tray. Moreover, if combined with microwave active elements, the flaps may improve browning and crisping of the sides of a food item in the tray.

20 **FIGS. 23 and 24** depict an exemplary microwave tray **300** according to the present invention. The tray **300** includes a support **302** formed from paperboard, or other suitable material, having at least one layer of insulating material **304** partially adhered or affixed thereto. The insulating material **304** is positioned so that the susceptor film faces the food product (not shown) to
 25 be heated thereon. The tray **300** includes four self-forming flaps **306a**, **306b**, **306c**, and **306d** in the non-folded position. The flaps **306a**, **306b**, **306c**, and **306d** may be integral with the support **302** or may be adhered or joined thereto. The flaps **306a**, **306b**, **306c**, and **306d** may be defined by a cutout **318** in one or more corners **320** of the support **302**. In one aspect, the insulating
 30 material **304a**, **304b**, **304c**, and **304d** aligned with the flaps **306a**, **306b**, **306c**,

and **306d** is adhered thereto, and the remaining insulating material **304e** is disposed on, but not adhered or otherwise affixed to the support **302**.

FIG. 25 depicts the tray **300** of **FIG. 23** with a food item **312** placed thereon. Upon exposure to microwave energy, the insulating cells **310** expand, thereby contracting the overall surface area of the insulating material **304**. Since the insulating material **304** is adhered to only the flaps **306a**, **306b**, **306c**, and **306d** of the tray **300**, the contraction of the insulating material **304** draws the flaps **306a**, **306b** (not shown), **306c**, and **306d** (not shown) toward the food item **312**, as shown in **FIG. 26**. In this manner, the tray **300** features self-forming walls **324** upon exposure to microwave energy. The expanded cells **310** insulate the food item **312** from the microwave environment and, if used with a susceptor layer, brown and crisp the bottom **314** and sides **316** of the food item **312**.

To facilitate bending of the flaps **306a**, **306b**, **306c**, and **306d**, it is also possible to provide a score line **322**, depression, or perforation at the desired fold line. The walls **324** substantially are transverse to the support **302**, and serve to stiffen the tray **300** and minimize flexing thereof. Thus, upon removal of the tray **300** from the microwave oven, the food item is less likely to spill or fall from the tray **300**.

FIGS. 27 and **28** depict another exemplary tray **300** according to the present invention. The tray **300** includes a support **302** formed from paperboard, or other suitable material, having a first layer of insulating material **304** partially adhered or affixed thereto, and a second layer of insulating material **308** partially adhered or affixed to the first layer of insulating material **304**. The insulating material **308** is positioned so that the susceptor film faces the food product (not shown) to be heated thereon. The tray **300** includes four self-forming flaps **306a**, **306b**, **306c**, and **306d** in the non-folded position. The flaps **306a**, **306b**, **306c**, and **306d** may be integral with the support **302** or may be adhered or joined thereto. In one aspect, the

insulating material **304a**, **304b**, **304c**, and **304d** aligned with the flaps **306a**, **306b**, **306c**, and **306d** is adhered thereto, and the remaining insulating material **304e** is disposed on, but not adhered or otherwise affixed to the support **302**. Likewise, the insulating material **308a**, **308b**, **308c**, and **308d** aligned with the
 5 flaps **306a**, **306b**, **306c**, and **306d** is adhered to the corresponding portions **304a**, **304b**, **304c**, and **304d** of first layer of insulating material **304**, but is not adhered or otherwise affixed thereto.

FIG. 29 depicts the tray **300** of **FIG. 27** with a food item **312** placed thereon. Upon exposure to microwave energy, the insulating cells **310** expand,
 10 thereby contracting the overall surface area of the insulating material **304**. Since the insulating material **304** and **308** is adhered to only the flaps **306a**, **306b**, **306c**, and **306d** of the tray **300**, the contraction of the insulating material **304** and **308** draws the flaps **306a**, **306b** (not shown), **306c**, and **306d** (not shown) toward the food item **312**, as shown in **FIG. 30**. In this manner, the
 15 tray **300** features self-forming walls **324** upon exposure to microwave energy. The expanded cells **310** insulate the food item **312** from the microwave environment and, if used with a susceptor layer, brown and crisp the bottom **314** and sides **316** of the food item **312**.

As discussed above, to facilitate bending of the flaps **306a**, **306b**, **306c**,
 20 and **306d**, it is also possible to provide a score line **322**, depression, or perforation at the desired fold line. The walls **324** substantially are transverse to the support **302**, and serve to stiffen the tray **300** and minimize flexing thereof. Thus, upon removal of the tray **300** from the microwave oven, the food item is less likely to spill or fall from the tray **300**.

25

IV. Insulating Microwave Material with Oxygen Barrier

According to another aspect of the present invention, a microwaveable material with an oxygen barrier and a package formed therefrom is provided. Such a material or package may lengthen the shelf life of a food item placed in

the packaging. Moreover, the package may be used to contain and transport a food item. Numerous materials and packages having various layers and shapes are contemplated hereby.

Any suitable oxygen barrier material may be used in accordance with the present invention. Examples of materials that may be suitable include, but are not limited to, polyvinylidene chloride (PVdC), ethylene vinyl alcohol (EVOH), and DuPont DARTEK™ nylon 66 film may be applied in various manners including the various configurations discussed with regard to PVdC and EVOH. DuPont Dartek™ nylon 66 has a high melting point and good oxygen barrier properties.

The oxygen barrier material may be incorporated into any suitable insulating material including, but not limited to, those described herein. Typically, the insulating material has several layers. For example, the microwave insulating material may include an outer PET layer coated or otherwise provided with a metal layer (such as aluminum), and a paper or paperboard layer adhered to the PET layer, such that the metal layer is disposed between the PET layer and the paper layer. Typically, the food item is placed on the material adjacent the outer PET layer. The insulating material includes expandable cells defined by an arrangement or pattern of adhesive, such as in a grid pattern, between the paper layer and a second PET layer. As discussed in detail above, the cells expand upon exposure to microwave energy to provide an insulating feature and bring the susceptor in proximity to the food item.

The oxygen barrier material may be incorporated at any of numerous possible locations between layers of material. **FIGS. 31-33** illustrate various exemplary arrangements of an insulating material **500** with an oxygen barrier **502**. The exemplary insulating microwave material **500** includes a first PET layer **504** and a metal layer **506**, which together define a susceptor layer **508**. The susceptor layer **508** is adhered or affixed to a paper or paperboard layer

510 using an adhesive 518 or otherwise. The paper layer 510 is adhered in a pattern using an adhesive 516, or otherwise bonded, to a second PET layer 512, thereby defining closed expandable cells 514. In FIG. 31, an oxygen barrier layer 502 is applied between the paper layer 510 and the second PET layer 512. In FIG. 32, an oxygen barrier layer 502 is provided over the first PET layer 504. In FIG. 33, an oxygen barrier layer 502 is positioned between the first PET layer 504 and the paper layer 510. In another aspect (not shown), the oxygen barrier layer 502 may be provided on either or both sides of the paper layer 510. While various possible configurations are shown and described herein, it should be understood that other possible configurations and arrangements of layers are contemplated by the present invention.

An insulating microwave material with an oxygen barrier may be provided in a sealable package or construct. In such an exemplary construct, after the food item is inserted into the package, the package may be flushed with a gas or gas mixture, such as nitrogen and carbon dioxide, to displace the oxygen in the package, and sealed hermitically. The oxygen barrier helps to retard or eliminate the reentry of oxygen into the package. Such a package may help to reduce oxidation of and aerobic bacteria growth on a food item contained therein, and thus may reduce spoilage.

20

V. Formation of Insulating Microwave Structure using a Thermo-mechanical Device

Various aspects of the present invention disclosed herein or contemplated hereby involve use of an insulating material having expandable closed cells. According to another aspect of the present invention, the closed cells of the insulating material are formed by thermo-mechanically bonding one or more layers of the insulating material.

The thermo-mechanical bonds may be formed using a thermo-mechanical device, an impulse sealer, ultrasonic bonding device, heat bar, or

30

any similar device, or any combination thereof configured in the desired cell pattern. Typically, an impulse sealer includes a nichrome wire or bend that is pulsed electrically to form a seal. An ultrasonic bonding device uses high frequency vibration, typically in the ultrasonic region, to create a thermo-
 5 mechanical bond. In one aspect, the bonding device is pressed against or deployed adjacent to an arrangement of material layers to form a pattern of bonding between portions of the layers. The pattern of bonding defines a plurality of closed cells that expand when exposed to microwave energy, the heat generated thereby, and/or expansion of gases in the cells brought on by
 10 exposure to microwave energy.

FIG. 34 depicts the layers of an exemplary insulating material **600**. In this example, the first layer **602** is a PET film and the second layer **604** is metal, together defining a susceptor **606**. The third layer **608** is paper or paperboard, which may be adhered or affixed to the susceptor using adhesive
 15 or otherwise. One example of a paper that may be suitable is a dimensionally stable lightweight paper with some flexibility, such as paper with a basis weight of about 40 lb/ream. The fourth layer **610** is PET clear film with a heat-sealable amorphous PET (APET) coating **640** on one side, adjacent the paper layer **608**.

FIG. 35 depicts the material of **FIG. 34** with a plurality of bonding elements **612**. As used herein, the term “bonding elements” includes thermo-mechanical devices, impulse sealers, ultrasonic or sonic bonding elements, heated bars, or the like, that are capable of forming thermo-mechanical bonds between layers of PET susceptor film, clear film, and paper, or other layers of
 25 insulating microwave material. Turning to **FIG. 36**, the bonding elements **612** are depressed into the layers of material **600**. Where the bonding elements **612** contact the layers, a bond or seal **642** is formed by softening the APET between the layers of material. In the areas not bonded **644**, the layers of material define an open space **614** between the paper layer **608** and the PET

clear film layer **610**, as shown in **FIGS. 37** and **38**. Thus, in this aspect, closed cells are formed by selectively sealing the perimeter of the cells, rather than by applying an adhesive in a pattern, as discussed above.

FIGS. 39 and **40** depict a tool or die **620** comprising a plurality of bonding elements **612** used to press-form a container **632** including one or more closed cells (not shown) that expand when exposed to microwave energy. The tool **620** includes an upper punch or “male” section **622** that forms the inner section or concave portion of a container. The tool **620** further comprises a lower cavity or “female” section **624** that corresponds to the outer or convex portion of a container. Both the punch **622** and cavity **624** of the tool **620** include bonding elements **612**. The bonding elements **612** are arranged in alignment with one another, so that when the tool **620** is closed to form the container, bonding elements **612** in the upper punch section **622** align with bonding elements **612** in the lower cavity section **624**. Alternatively, the bonding elements **612** may be present in only the punch section **622** or cavity section **624** of the tool **620**, but not both. In yet another alternative, bonding elements **612** are employed in the punch section **622** and cavity section **624**, but not necessarily in alignment. The bonding elements **612** may be flush with the outer surface **628** of the punch **622** and the outer surface **630** of the cavity **624**, or the bonding elements **612** may be arranged to be slightly raised with respect to the outer surfaces **628** and **630** of the punch and cavity, respectively. The arrangement of bonding elements **612** and the configuration of a tool **620** will depend on various factors such as the shape of the container and the shape, size, number, and arrangement of insulating cells.

In one aspect, a container is formed from various layers of base material **600**, such as those shown in **FIG. 35**. To do so, the layers are arranged between the upper punch **622** and lower cavity **624**. The tool **620** then is closed, thereby forming the layers into an insulating material having

expandable cells. Simultaneously, the insulating material is formed into a container **632**.

In another aspect, a container is formed from a microwave insulating sheet having pre-formed expandable cells, such as those shown and described
 5 herein. The insulating material including the expandable cells is positioned between the upper punch **622** and lower cavity **624**. The tool then is closed, thereby forming the insulating material into a container.

FIGS. 41-43 illustrate an exemplary container **632** that may be formed according to the present invention. In the upper punch **622** and lower cavity
 10 **624** of the tool **620**, the bonding elements **612** define a grid pattern to form a pattern of closed cells **634** on the plate **632**. The cavity **624** is shaped to define the outer surface of the container **632**. The punch section **622** is shaped to define the inner surface of the container **632**.

FIG. 44 is an example of an alternative container **632** that may be
 15 formed in accordance with the present invention. In this example, the tool includes a generally square punch and cavity arrangement (not shown).

VI. Method of Packaging a Food Item

According to another aspect of the present invention, a method and
 20 process for wrapping a food item in a sleeve of insulating microwave material is provided. If desired, the wrapped food item further may be overwrapped with a printed film.

Turning to **FIG. 45**, an exemplary process according to the present invention is illustrated. A moving surface **700** includes one or more
 25 continuous belts **702** and **704** supported at each end by rollers **706**. A first continuous roll of insulating microwave material **708** is unwound onto the belt surface **700**. The food items **710** are placed on the insulating microwave material web **708**. A second continuous roll of insulating microwave material **712** is unwound over the food items **710** supported on the first continuous web

of material **708**. Thus, the insulating material is provided along the bottom and top surfaces of the food item **710**. In one aspect, the two webs of material **708** and **712** have a roughly equal width that is less than the width of the food item **710** (as measured transverse to the direction of conveyance). This dimensional relationship facilitates formation of a sleeve **714** having two open ends **716a** and **716b**, with a small portion of the ends **718a** and **718b** of the food item **710** exposed. It is possible, however, to provide any size webs of insulating microwave or other material. For example, it is possible to provide an arrangement to form a pocket with one open end, or to provide a pocket fully capable of enclosing the food item.

Turning to **FIGS. 46** and **47**, the wrapped food item **710** proceeds to an integrated heat seal and cut-off station **720**. The heat seal and cut-off tool **722** comprises an outer heat seal tool **724** and an inner blade **726** coaxially aligned therewith. The heat seal **724** and cut-off tool **726** are shown integrated. However, the heat seal and cut-off functions may be separated if desired. A plate **728** is provided to support the food item **710** during actuation of the heat seal and cut-off tool **722**. The food items **710** are moved incrementally over the flat plate **728** so that the leading edge **730** of the food item **710** is arranged adjacent, but not directly under the heat seal and cut-off tool **722**. As shown in **FIG. 45**, the webs of material **708** and **712** are suspended between adjacent food items **710**.

Referring now to **FIG. 47**, the heat seal and cut-off tool **722** is shown in the actuated position. When actuated, the heat seal portion **724** is pressed against the upper web of the material **712**, pushing it down against the lower web of material **708**. The heat seal tool **724** also presses down on the plate **728**. When engaged with the plate **728**, the heat seal tool **724** is energized to create a seal **732**, such as a thermo-mechanical bond, between the first web of insulating material **708** and second web of insulating material **712**. It is also

possible to provide an amorphous or activatable adhesive (not shown) in the region where the heat seal tool will create the seal between the webs.

In an alternative configuration (not shown), the plate **728** may be substituted by a second heat seal tool. In such a configuration, the second heat seal tool may oppose the first heat seal tool of the heat seal and cut-off tool, so that upon actuation, the two heat seal tools work in concert to form a seal between the first and second webs of insulating materials. In one aspect, the face of the heat sealing tool may be shaped to receive the blade, thereby preventing direct contact with the second heat sealing tool. For example, the face of the second heat sealing tool may be curved, notched, slotted, or otherwise configured to receive the portion of the blade that extends beyond the interface between the first and second heat sealing tools. If desired, the blade may travel from the heat seal and cutoff tool housing during actuation.

Referring again to **FIG. 46**, when the heat seal and cut-off tool **722** is in the upper position, the cut-off portion of the tool **726** may be withdrawn inside the tool **722**. In contrast, when the tool **722** is actuated, the blade **726** extends from the tool **722**. When the blade **726** is pressed down against the bonded webs **708** and **712**, as shown in **FIG. 47**, a line of separation **760** between food items **710** is formed. The line of separation **760** is located substantially along the centerline of the heat sealed area, so that the wrapping around each food item remains intact.

From **FIG. 47**, it can be seen that a first food item **710a** is located on the incoming portion **734** of the plate **728** at the end of the first belt **730**, and a second food item **710b** is located on the outgoing portion **736** of the plate **728** at the end of the second belt **704**. The first food item **710a** will proceed to the location of the second food item **710b** in the next movement of the belts **702** and **704**. The leading portion **740** of the webs **708** and **712** over the second food item **710b** was cut and heat sealed during the preceding actuation of the heat seal and cutoff tool **722**. In the actuation of the heat seal and cut-off tool

722 in the current position, the leading portion 742 of the webs 708 and 712 for the first food item 710a are heat sealed, and the trailing portion 744 of the webs 708 and 712 for the second food item 710b is heat sealed. When the blade 726 separates the webs 708 and 712, the first food item 710a is fully
 5 processed with a sleeve 714 of insulating microwave material. If desired, the food items 710 with insulating microwave material sleeves 714 may be sent along the second belt 704 to a wrapping station 746 (FIG. 45) for providing a form seal over wrap with a printed film. FIGS. 48 and 49 depict a food item 710 with a sleeve 714 and overwrap 748.

10

VII. Package With Reconfigurable Insulating Lid

In accordance with yet another aspect of the present invention shown in FIGS. 50-52, a package 800 having an insulating underfolding lid 802 is provided. The lid 802 includes a fold line 804 along one side 806, and a tab
 15 808 or other closure or sealing means along the opposing side 810. The lid 802 has an interior surface 820 that may include an insulating material 832, with or without a susceptor layer, such as those described herein. The insulating material may include an oxygen barrier layer, variably sized and/or variably expanding cells, partially expanded cells, or numerous other features
 20 disclosed herein or contemplated hereby.

Prior to being opened (FIG. 50), the lid 802 covers the tray 812 and the food item (not shown) therein, and the tab 808 may be removably sealed to the front panel 822 of the package 800. To re-close the package 800 after being
 25 opened, the tab 808 may engage a corresponding slot 816 to secure the lid 802 in position. However, other means of securing the tab 808 are contemplated hereby.

As shown in FIGS. 51 and 52, when the food item 814 is ready to be heated, the package 800 is opened, and the lid 802 is folded under the tray 812. The tab 808 engages a second slot (not shown) or other retaining structure

along the outside of the bottom surface **818**. By doing so, the lid **802** forms an insulating layer between the bottom **818** of the tray **812** and the floor or glass tray of a microwave (not shown). The additional insulation provided by the lid **802** enhances the cooking of the food item **814** in the tray **812** by preventing
5 heat loss to the surroundings.

If desired, additional insulating material **830** may be provided on one or more interior surfaces of the package to provide further insulation between the food item and the bottom of the tray and the floor of the microwave oven. Spacers along the lid surface that provide additional separation between the lid
10 and the bottom of the tray in the folded-under position also may be provided. Ventilation holes **824** also may be provided.

It will be readily understood by those persons skilled in the art that, in view of the above detailed description of the invention, the present invention is susceptible of broad utility and application. Many adaptations of the present
15 invention other than those herein described, as well as many variations, modifications, and equivalent arrangements will be apparent from or reasonably suggested by the present invention and the above detailed description thereof, without departing from the substance or scope of the present invention.

20 While the present invention is described herein in detail in relation to specific aspects, it is to be understood that this detailed description is only illustrative and exemplary of the present invention and is made merely for purposes of providing a full and enabling disclosure of the present invention. The detailed description set forth herein is not intended nor is to be construed
25 to limit the present invention or otherwise to exclude any such other embodiments, adaptations, variations, modifications, and equivalent arrangements of the present invention. Accordingly, all directional references (e.g., upper, lower, upward, downward, left, right, leftward, rightward, top, bottom, above, below, vertical, horizontal, clockwise, and counterclockwise)

are only used for identification purposes to aid the reader's understanding of the present invention, and do not create limitations, particularly as to the position, orientation, or use of the invention. Joinder references (e.g., attached, coupled, connected, and the like) are to be construed broadly and may include
5 intermediate members between a connection of elements and relative movement between elements. As such, such joinder references do not necessarily infer that two elements are directly connected and in fixed relation to each other. Accordingly, the present invention is limited solely by the claims appended hereto and the equivalents thereof.

WHAT IS CLAIMED IS:

1. A self-sealing microwave package comprising:
 - a flexible sheet having a first side and a second side opposite the first side, the sheet having an activatable adhesive region on at least one of the first side and the second side of the sheet, wherein the sheet includes
 - a susceptor film comprising a microwave energy interactive material supported on a first polymer film layer,
 - a moisture-containing layer superposed with the microwave energy interactive material, and
 - a second polymer film layer joined to the moisture-containing layer in a predetermined pattern, thereby forming at least one closed cell between the moisture-containing layer and the second polymer film layer, wherein the moisture-containing layer is positioned between the microwave energy interactive material and the second polymer film layer.

2. The package of claim 1, wherein
 - the first polymer film layer at least partially defines the first side of the sheet,
 - the second polymer film layer at least partially defines the second side of the sheet, and
 - the activatable adhesive region is on the first side of the sheet.

3. The package of claim 1, wherein
 - the first polymer film layer at least partially defines the first side of the sheet,
 - the second polymer film layer at least partially defines the second side of the sheet, and

the activatable adhesive region is on the second side of the sheet.

4. The package of claim 1, 2, or 3, wherein the activatable adhesive region comprises an adhesive that becomes tacky in response to thermal energy, microwave energy, or any combination thereof.
5. The package of claim 1, wherein
the second polymer film comprises coextruded layers of amorphous polyethylene terephthalate and polyethylene terephthalate, and
the activatable adhesive region comprises at least a portion of the layer of amorphous polyethylene terephthalate.
6. The package of any one of claims 1 to 5, wherein
the activatable adhesive region comprises an adhesive that is substantially non-tacky prior to heating the package in a microwave oven,
the sheet is adapted to enwrap a food item with at least a portion of the activatable adhesive region in a substantially contacting relationship with another portion of the sheet, and
upon heating the package in a microwave oven, the adhesive adheres to the other portion of the sheet.
7. The package of any one of claims 1 to 6, wherein
the sheet includes a first side portion, a second side portion, and a central portion between the first side portion and the second side portion,
the activatable adhesive region lies on the first side portion proximate an edge of the sheet,
the second side portion is adapted to be folded over the central portion,
and

the first side portion is adapted to be folded over the second side portion to form a sleeve.

8. The package of any one of claims 1 to 6, wherein
the activatable adhesive region is a first activatable adhesive region,
the sheet includes a first side portion including a first edge, a second side portion including a second edge opposite the first edge, a central portion between the first side portion and the second side portion, and a third edge extending across at least a portion of each of the first side portion, the second side portion, and the central portion,

the first activatable adhesive region lies on the first side portion proximate the first edge,

the sheet has a second activatable adhesive region on at least one of the first side portion, second side portion, and the central portion proximate the third edge,

the second side portion is adapted to be folded over the central portion, and

the first side portion is adapted to be folded over the second side portion to form a pouch including a substantially closed end proximate the third edge of the sheet.

9. The package of claim 8, wherein
the substantially closed end of the pouch is a first substantially closed end,

the sheet further includes a fourth edge extending across at least a portion of each of the first side portion, the second side portion, and the central portion opposite the third edge,

the sheet has a third activatable adhesive region on at least one of the first side portion, second side portion, and the central portion proximate the third edge, and

the pouch includes a second substantially closed end proximate the fourth edge of the sheet.

10. A self-sealing microwave package comprising:

a flexible sheet including a first surface, a second surface opposite the first surface, and a plurality of peripheral edges including a first edge and a second edge opposite the first edge;

an activatable adhesive overlying at least a portion of the first surface proximate the first edge, the activatable adhesive becoming tacky in response to heat,

wherein the sheet includes

a layer of microwave energy interactive material supported on a first polymer film layer,

a moisture-containing layer joined to the layer of microwave energy interactive material, and

a second polymer film layer joined to the moisture-containing layer in a patterned arrangement that defines a plurality of closed cells between the moisture-containing layer and the second polymer film layer, wherein the moisture-containing layer is positioned between the microwave energy interactive material and the second polymer film layer.

11. The package of claim 10, wherein the first polymer film layer at least partially defines the first surface of the sheet.

12. The package of claim 10, wherein the second polymer film layer at least partially defines the first surface of the sheet.
13. The package of claim 10, 11, or 12, wherein the activatable adhesive comprises amorphous polyethylene terephthalate.
14. The package of any one of claims 10 to 13, wherein the sheet is adapted to enwrap a food item with the activatable adhesive in an overlapping relationship with the second surface of the sheet.
15. The package of any one of claims 10 to 14, wherein the sheet is adapted to enwrap a food item with the activatable adhesive in an overlapping relationship with a portion of the second surface of the sheet proximate the second edge.
16. The package of claim 15, wherein the overlapping relationship defines a sleeve with a pair of open ends.
17. The package of any one of claims 10 to 16, wherein
the plurality of peripheral edges includes a third edge extending between the first edge and the second edge, and
the activatable adhesive further overlies at least a portion of the first surface proximate the third edge.
18. The package of claim 17, wherein the sheet is adapted to enwrap a food item with the activatable adhesive in an overlapping relationship with the second surface of the sheet.

19. The package of claim 18, wherein the overlapping relationship defines a pouch with a substantially closed end proximate the third edge of the sheet.
20. The package of claim 17, wherein
the plurality of peripheral edges includes a fourth edge extending between the first edge and the second edge opposite the third edge, and
the activatable adhesive further overlies at least a portion of the first surface proximate the fourth edge.
21. The package of claim 20, wherein the sheet is adapted to enwrap a food item with the activatable adhesive in an overlapping relationship with the second surface of the sheet.
22. The package of claim 21, wherein the overlapping relationship defines a pouch with a pair of substantially opposed, closed ends proximate the third edge and the fourth edge of the sheet.
23. A self-sealing microwave package comprising, in a layered configuration:
a first polymer film layer;
a layer of microwave energy interactive material;
a substantially continuous adhesive layer;
a moisture-containing layer;
a patterned adhesive layer; and
a second polymer film layer,
wherein
the patterned adhesive layer adjoins the moisture-containing layer and the second polymer film layer and defines a plurality of

substantially vapor-impermeable closed cells between the moisture-containing layer and the second polymer film layer,

at least some of the closed cells expand upon sufficient exposure of the package to microwave energy,

the first polymer film layer and the second polymer film layer respectively define a first surface and a second surface of the package,

an activatable adhesive overlies at least a portion of at least one of the first surface and the second surface, and

the tackiness of the activatable adhesive increases in response to heat.

24. The package of claim 23, wherein the activatable adhesive comprises amorphous polyethylene terephthalate.

25. The package of claim 23 or 24, wherein

the first surface is a food-contacting surface,

the activatable adhesive overlies at least a portion of the second surface,

and

the package is adapted to enwrap a food item with the activatable adhesive in an overlapping relationship with the first surface.

26. A self-sealing microwave packaging material comprising:

a flexible sheet having a first side and a second side opposite the first side, the sheet including a layer of microwave energy interactive material that converts at least a portion of impinging microwave energy into thermal energy; and

an activatable adhesive region on at least one of the first side and the second side of the sheet, the activatable adhesive region comprising an

adhesive material that is substantially non-tacky prior to being heated in a microwave oven,

wherein the sheet is adapted to enwrap a food item with at least a portion of the activatable adhesive region in a substantially contacting relationship with another portion of the sheet, such that upon sufficient heating in a microwave oven, the adhesive material adheres to the other portion of the sheet and maintains the microwave energy interactive material in proximity to the food item.

27. The packaging material of claim 26, wherein
the microwave energy interactive material is supported on a first polymer film layer, and

the sheet further includes

a moisture-containing layer joined to the microwave energy interactive material, and

a second polymer film layer joined to the moisture-containing layer in a predetermined pattern, thereby forming at least one closed cell between the moisture-containing layer and the second polymer film layer.

28. The packaging material of claim 27, wherein
the first polymer film layer at least partially defines the first side of the sheet,

the second polymer film layer at least partially defines the second side of the sheet, and

the activatable adhesive region is on the first side of the sheet.

29. The packaging material of claim 28, wherein the sheet is adapted to enwrap the food item with the activatable adhesive region in an overlapping relationship with the second side of the sheet.
30. The packaging material of claim 27, wherein
the first polymer film layer at least partially defines the first side of the sheet,
the second polymer film layer at least partially defines the second side of the sheet, and
the activatable adhesive region is on the second side of the sheet.
31. The packaging material of claim 30, wherein the sheet is adapted to enwrap the food item with the activatable adhesive region in an overlapping relationship with the first surface of the sheet.
32. The packaging material of claim 27, wherein
the second polymer film comprises coextruded layers of amorphous polyethylene terephthalate and polyethylene terephthalate, and
the activatable adhesive region comprises at least a portion of the layer of amorphous polyethylene terephthalate.
33. The packaging material of claim 26, wherein
the sheet includes a first side portion, a second side portion, and a central portion between the first side portion and the second side portion,
the activatable adhesive region is on the first side portion proximate an edge of the sheet,
the second side portion is adapted to be folded over the central portion,
and

the first side portion is adapted to be folded over the second side portion to form a sleeve.

34. The packaging material of claim 26, wherein
the activatable adhesive is a first activatable adhesive region,
the sheet includes a first side portion including a first edge, a second side portion including a second edge opposite the first edge, a central portion between the first side portion and the second side portion, and a third edge extending across at least a portion of each of the first side portion, the second side portion, and the central portion,

the first activatable adhesive region lies on the first side portion proximate the first edge,

the sheet has a second activatable adhesive region on at least one of the first side portion, second side portion, and the central portion proximate the third edge,

the second side portion is adapted to be folded over the central portion,
and

the first side portion is adapted to be folded over the second side portion to form a pouch including a substantially closed end proximate the third edge of the sheet.

35. The packaging material of claim 34, wherein
the substantially closed end of the pouch is a first substantially closed end,

the sheet further includes a fourth edge extending across at least a portion of each of the first side portion, the second side portion, and the central portion opposite the third edge,

the sheet has a third activatable adhesive region on at least one of the first side portion, second side portion, and the central portion proximate the third edge, and

the pouch includes a second substantially closed end proximate the fourth edge of the sheet.

36. The packaging material of any one of claims 26-35, wherein the adhesive material becomes tacky in response to thermal energy, microwave energy, or any combination thereof.

37. An insulating microwave material comprising:

a susceptor film comprising a layer of microwave energy interactive material supported on a first polymer film;

a dimensionally stable substrate joined to the layer of microwave energy interactive material; and

a second polymer film at least partially covered by a layer of amorphous polyethylene terephthalate,

wherein the amorphous polyethylene terephthalate is selectively bonded to the dimensionally stable substrate, thereby defining a plurality of substantially closed cells adjacent to the dimensionally stable substrate.

38. The insulating microwave material of claim 37, wherein the dimensionally stable substrate comprises a moisture-containing material.

39. The insulating microwave material of claim 38, wherein the moisture-containing material comprises paper or paperboard.

40. The insulating microwave material of 37, 38, or 39, wherein the microwave energy interactive material comprises aluminum.

41. The insulating microwave material of any one of claims 37 to 40, wherein at least one of the first polymer film and the second polymer film comprises polyethylene terephthalate.

42. The insulating microwave material of any one of claims 37 to 40, wherein the first polymer film and the second polymer film each comprise polyethylene terephthalate.

43. The insulating microwave material of any one of claims 37 to 42, wherein the closed cells are substantially resistant to vapor migration.

44. The insulating microwave material of any one of claims 37 to 43, wherein the closed cells inflate upon sufficient exposure to microwave energy.

45. The insulating microwave material of any one of claims 37 to 44, wherein the cells are approximately equal in size.

46. The insulating microwave material of any one of claims 37 to 44, wherein at least some of the expandable cells vary in size from at least some other of the expandable cells.

47. The insulating microwave material of any one of claims 37 to 46, further comprising an oxygen barrier layer.

48. The insulating microwave material of claim 47, wherein the oxygen barrier layer comprises polyvinylidene chloride, ethylene vinyl alcohol, nylon 66, or a combination thereof.

49. The insulating microwave material of claim 47 or 48, wherein the oxygen barrier layer is disposed between the dimensionally stable substrate and the second polymer film.

50. The insulating microwave material of claim 47 or 48, wherein the oxygen barrier layer is disposed between the layer of microwave energy interactive material and the dimensionally stable substrate.

51. The insulating microwave material of claim 47 or 48, wherein the oxygen barrier layer is superposed with the first polymer film distal the dimensionally stable substrate.

52. The insulating microwave material of claim 47 or 48, wherein the oxygen barrier layer is superposed with the second polymer film distal the dimensionally stable substrate.

53. An insulating microwave material comprising:

a susceptor film comprising a thin layer of microwave energy interactive material supported on a first polymer film;

a moisture-containing substrate joined to the layer of microwave energy interactive material; and

a second polymer film including a coating of amorphous polyethylene terephthalate on a first side of the second polymer film,

wherein

the first side of the second polymer film is in a facing relationship with the moisture-containing substrate,

the coating of amorphous polyethylene terephthalate is selectively bonded to the moisture-containing substrate to define a

plurality of closed cells between the moisture-containing substrate and the second polymer film, and

the closed cells are substantially resistant to vapor migration.

54. The insulating microwave material of claim 53, wherein the microwave energy interactive material comprises aluminum.

55. The insulating microwave material of claim 53 or 54, wherein at least one of the first polymer film and the second polymer film comprises polyethylene terephthalate.

56. The insulating microwave material of claim 53, 54, or 55, wherein the moisture-containing substrate releases water vapor upon sufficient exposure to microwave energy, thereby inflating the closed cells.

57. An insulating microwave material comprising:

a layer of microwave energy interactive material supported on a first polymer film;

a dimensionally stable substrate joined to the layer of microwave energy interactive material;

a second polymer film; and

a layer of amorphous polyethylene terephthalate overlying the second polymer film in a facing relationship with the dimensionally stable substrate,

wherein the layer of amorphous polyethylene terephthalate defines a plurality of bonded areas and unbonded areas between the dimensionally stable substrate and the second polymer film.

58. The insulating microwave material of claim 57, wherein the layer of microwave energy interactive material heats upon impingement of microwave energy.
59. The insulating microwave material of claim 57 or 58, wherein the layer of microwave energy interactive material comprises a metal.
60. The insulating microwave material of any of claim 57, 58, or 59, wherein at least one of the first polymer film and the second polymer film comprises polyethylene terephthalate.
61. The insulating microwave material of any one of claims 57 to 60, wherein the unbonded areas comprise a plurality of inflatable cells defined by the bonded areas.
62. The insulating microwave material of claim 61, wherein the inflatable cells are substantially resistant to vapor migration along the bonded areas.
63. The insulating microwave material of claim 61 or 62, wherein the dimensionally stable substrate contains moisture, and upon exposure to microwave energy, the dimensionally stable substrate releases water vapor, thereby inflating the inflatable cells.
64. The insulating microwave material of claim 56, 57, or 58, wherein at least some of the inflatable cells vary in size from at least some other of the inflatable cells.
65. A method of making an insulating microwave material, comprising:

joining a dimensionally stable substrate to a layer of microwave energy interactive material supported on a first polymer film, such that the microwave energy interactive material is disposed between the first polymer film and the dimensionally stable substrate;

providing a second polymer film including a first side, the second polymer film including a layer of amorphous polyethylene terephthalate overlying at least a portion of the first side;

arranging the dimensionally stable substrate in a superposed, facing relationship with the layer of amorphous polyethylene terephthalate; and

contacting the arranged layers with a thermo-mechanical bonding element in a patterned configuration, such that the amorphous polyethylene terephthalate is heated above a softening temperature and bonds to the dimensionally stable substrate in the patterned configuration,

wherein the patterned configuration of bonding defines a plurality of expandable insulating cells between the dimensionally stable substrate and the second polymer film.

66. The method of claim 65, further comprising selecting the patterned configuration of bonding to define at least some expandable insulating cells that vary in size from at least some other expandable insulating cells.

67. The method of claim 65 or 66, further comprising selecting the patterned configuration of bonding to define a plurality of expandable insulating cells arranged to form a periphery and a plurality of expandable insulating cells positioned within the periphery, wherein the expandable insulating cells that form the periphery differ in size from the expandable insulating cells within the periphery.

68. The method of claim 67, further comprising selecting the patterned configuration of bonding such that the expandable insulating cells that form the periphery are larger than the expandable insulating cells within the periphery.

69. A method of forming a microwave energy interactive insulating container, comprising:

providing a first polymer film, a layer of microwave energy interactive material, and a dimensionally stable substrate in a layered configuration with the microwave energy interactive material disposed between the first polymer film and the dimensionally stable substrate;

providing a second polymer film including a layer of amorphous polyethylene terephthalate overlying at least a portion of a first side of the second polymer film;

positioning the second polymer film adjacent to the dimensionally stable substrate with the layer of amorphous polyethylene terephthalate in a facing relationship with the dimensionally stable substrate to form an arrangement of layers;

placing the arrangement of layers between a punch section and a cavity section of a thermo-mechanical bonding device, wherein at least one of the punch section and the cavity section includes a bonding element; and

engaging the punch section and the cavity section with the arranged layers therebetween, thereby bringing the bonding element into contact with the arranged layers,

wherein bringing the bonding element into contact with the arranged layers causes the amorphous polyethylene terephthalate to adhere to the dimensionally stable substrate.

70. The method of claim 69, wherein adhering the amorphous polyethylene terephthalate to the dimensionally stable substrate defines a plurality of closed cells between the dimensionally stable substrate and the layer of amorphous polyethylene terephthalate.
71. The method of claim 70, wherein the closed cells are adapted to inflate in response to microwave energy.
72. The method of claim 69, wherein
the bonding element is a first bonding element of a plurality of bonding elements, and
the bonding elements are arranged to define a plurality of closed cells between the dimensionally stable substrate and the second polymer film.
73. The method of claim 72, wherein the bonding elements are arranged to define some closed cells that vary in size from at least some other closed cells.
74. The method of claim 69, wherein
the bonding element is a first bonding element of a plurality of bonding elements,
the punch section and the cavity section each include at least one bonding element of the plurality of bonding elements, and
the bonding elements in the punch section and the cavity section are in substantial alignment.
75. The method of claim 69, wherein
the bonding element is a first bonding element of a plurality of bonding elements,

the punch section and the cavity section each include at least one bonding element of the plurality of bonding elements, and

the bonding elements in the punch section and the cavity section are not in substantial alignment.

76. The method of claim 69, wherein only the punch section includes the bonding element.

77. The method of claim 69, wherein only the cavity section includes the bonding element.

78. The method of any one of claims 69 to 77, wherein the cavity section is shaped to define the outer surface of the container and the punch section is shaped to define the inner surface of the container.

79. A method of packaging a food item, comprising:

unwinding onto a moving belt a first web of insulating microwave material;

placing a food item having a leading edge onto the first web of insulating microwave material;

unwinding over the food item a second web of insulating microwave material;

advancing the leading edge of the food item to an integrated heat seal and cutoff tool including

a heat seal tool, and

a blade coaxially aligned with the heat seal tool; and

actuating the heat seal tool, thereby

bonding the second web of insulating microwave material to the first web of insulating microwave material, and

cutting through the first web of insulating microwave material and the second web of insulating microwave material.

80. The method of claim 79, wherein actuating the heat seal tool comprises bringing the heat seal tool into contact with the second web of insulating microwave material, thereby causing the second web of insulating microwave material to contact the first web of insulating microwave material, forming a thermo-mechanical bond between the first web of insulating microwave material and the second web of insulating microwave material, extending the blade toward the bonded first web of insulating microwave material and the second web of insulating microwave material, cutting the bonded first web of insulating microwave material and the second web of insulating microwave material, and withdrawing the blade into the heat seal tool.
81. The method of claim 79 or 80, wherein the integrated heat seal and cutoff tool further includes a plate supporting the first web of insulating microwave material, the plate being configured to receive the blade when the integrated heat seal and cutoff tool is actuated.
82. The method of claim 79 or 80, wherein the heat seal tool is a first heat seal tool, and the integrated heat seal and cutoff tool further comprises a second heat seal tool supporting the first web of insulating microwave material, the second heat seal tool being configured to receive the blade when the integrated heat seal and cutoff tool is actuated.




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5







FIG. 6






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22A




FIG. 22B




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG.39




FIG.40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52

