

(51) International Patent Classification:
G02B 6/44 (2006.01)(21) International Application Number:
PCT/US2009/004549(22) International Filing Date:
7 August 2009 (07.08.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/190,538 29 August 2008 (29.08.2008) US
61/197,068 23 October 2008 (23.10.2008) US
12/323,423 25 November 2008 (25.11.2008) US(71) Applicant (for all designated States except US): **CORNING CABLE SYSTEMS LLC** [US/US]; Intellectual Property Department, SP-TI-3-1, Corning, NY 14831 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **COOKE, Terry L.** [US/US]; 908 38th Avenue NE, Hickory, North Carolina 28601 (US). **KLAVUHN, Tory A.** [US/US]; 1670 Fairway Drive, Newton, North Carolina 28658 (US). **DEAN, JR., David L.** [US/US]; 2520 17th Street NE, Hickory, North Carolina 28601 (US). **GARCIA, Juan** [MX/MX];Narcisos 237 Col. Villa Florida, Tamaulipas, Reynosa, 88715 (MX). **MARIANO, Elmer** [MX/MX]; Las Moras # 239, Col. Lomas de Jarachina Nte., Tamaulipas, Reynosa, 88730 (MX). **LOPEZ, Manuel** [MX/MX]; Andador R # 813 Fracc. Las Fuentes, Secc., Lomas Tamaulipas, Reynosa, 88743 (MX). **GONZALEZ, Juan M.** [MX/MX]; Conquista Campesina Location, Rio Bravo (MX).(74) Agent: **VYNALEK, John H**; CORNING CABLE SYSTEMS LLC, Patent Department, SP-TI-3-1, Corning, New York 14831 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,

[Continued on next page]

(54) Title: REAR-INSTALLABLE FIBER OPTIC MODULES AND EQUIPMENT




FIG. 10

(57) Abstract: Fiber optic equipment that supports one or more rear-installable fiber optic modules is disclosed. The fiber optic equipment is comprised of a chassis defining a front end and a rear section. At least one guide system is disposed in the chassis and configured to receive at least one fiber optic module. The guide system may be provided in the form of a rail guide system. The at least one guide system receives the at least one fiber optic module from the rear section on the chassis and is configured to guide the fiber optic module toward the front end of the chassis. In this manner, a technician can make fiber optic connections to fiber optic modules and also install the fiber optic modules into the fiber optic equipment from the rear section of the chassis to reduce time and/or labor in making fiber optic connections.



TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

REAR-INSTALLABLE FIBER OPTIC MODULES AND EQUIPMENT

RELATED APPLICATIONS

[0001] The present application claims priority to U.S. Provisional Patent Application Serial No. 61/190,538 filed August 29, 2008, entitled "High Density Data Center Hardware, Assemblies and Components," which is incorporated herein by reference in its entirety.

[0002] The present application also claims priority to U.S. Provisional Patent Application Serial No. 61/197,068 filed October 23, 2008, entitled "High Density Data Center Hardware, Assemblies and Components," which is incorporated herein by reference in its entirety.

[0003] The present application also claims priority to U.S. Patent Application Serial No. 12/323,423, filed November 25, 2008, entitled "Rear-Installable Fiber Optic Modules and Equipment," which is incorporated herein by reference in its entirety.

[0004] The present application is related to co-pending U.S. Patent Application Serial No. 12/323,415, entitled "Independently Translatable Modules and Fiber Optic Equipment Trays in Fiber Optic Equipment," which is incorporated herein by reference in its entirety.

[0005] The present application is also related to co-pending U.S. Patent Application Serial No. 12/394,483, entitled "Rear-Slidable Extension in a Fiber Optic Equipment Tray," which is incorporated herein by reference in its entirety.

BACKGROUND

Field of the Disclosure

[0006] The technology of the disclosure relates to fiber optic modules provided in fiber optic equipment to support fiber optic connections.

Technical Background

[0007] Benefits of optical fiber use include extremely wide bandwidth and low noise operation. Because of these advantages, optical fiber is increasingly being used for a variety of applications, including but not limited to broadband voice, video, and data

transmission. Fiber optic networks employing optical fiber are being developed and used to deliver voice, video, and data transmissions to subscribers over both private and public networks. These fiber optic networks often include separated connection points at which it is necessary to link optical fibers in order to provide "live fiber" from one connection point to another connection point. In this regard, fiber optic equipment is located in data distribution centers or central offices to support interconnections.

[0008] The fiber optic equipment is customized based on the application need. The fiber optic equipment is typically included in housings that are mounted in equipment racks to maximize space. One example of such fiber optic equipment is a fiber optic module. A fiber optic module is designed to provide cable-to-cable fiber optic connections and manage the polarity of fiber optic cable connections. The fiber optic module is typically mounted to a chassis which is then mounted inside an equipment rack or housing. The chassis may be provided in the form of a tray that is extendable from the equipment rack like a drawer. This allows a technician access to fiber optic adapters disposed in the fiber optic module and any fiber optic cables connected to the fiber optic adapters without removing the fiber optic module from the equipment rack.

[0009] Even with advancements in access to fiber optic modules, the labor associated with installing fiber optic modules and making optical connections is significant. For example, for a field technician to install a new fiber optic module, the field technician typically loads trunk cables in the rear section of a fiber optic equipment rack. The field technician then feeds the connectorized fanout legs from the trunk cable to the front of the equipment rack. The field technician then walks around to the front of the equipment rack to connect the fanout legs to a fiber optic module. Because data distribution centers are typically large facilities with significant numbers of equipment racks, walking back and forth from the rear section to the front section of the equipment rack during an installation can take significant time. Alternatively, a second technician may work in tandem with the first technician, where the first technician manages loading of fiber optic cables in the rear section of the equipment rack. The second technician remains in the front of the rack to install the fiber optic modules and establish optical connections between the fiber optic cables and the fiber optic modules. In either scenario, fiber optic cables are installed in the rear section of the equipment rack and the fiber optic modules

and connections are installed from the front of the equipment rack thereby requiring extensive labor.

SUMMARY OF THE DETAILED DESCRIPTION

[0010] Embodiments disclosed in the detailed description include fiber optic equipment that supports one or more rear-installable fiber optic modules. The fiber optic modules are configured to support fiber optic connections. The fiber optic equipment is comprised of a chassis defining a front end and a rear section. At least one guide system is disposed in the chassis and configured to receive at least one fiber optic module. The guide system may be provided in the form of a rail guide system. The guide system receives a fiber optic module from the rear section of the chassis and is configured to guide the fiber optic module toward the front end of the chassis. In this manner, a technician can make fiber optic connections to fiber optic modules and also install the fiber optic modules into the fiber optic equipment from the rear section of the chassis to reduce time and/or labor in making fiber optic connections.

[0011] In some disclosed embodiments, the guide system is comprised of at least one tray guide that receives at least one fiber optic equipment tray. The tray guides are disposed in the chassis of the fiber optic equipment. The tray guides support fiber optic equipment trays within the fiber optic equipment. At least one module guide is disposed in the fiber optic equipment trays to support one or more fiber optic modules. In this manner, the fiber optic equipment tray can translate within the chassis to move the fiber optic modules supported by the fiber optic equipment tray about the chassis. The module guides also allow fiber optic modules to be rear-installable into the fiber optic equipment tray to be rear-installable in the fiber optic equipment. The tray guides disposed in the fiber optic equipment tray also allow the fiber optic modules disposed therein to be independently translated within the fiber optic equipment tray.

[0012] In other disclosed embodiments, the guide system is comprised of at least one module guide that receives at least one fiber optic module. The module guides are disposed in the chassis without intermediate fiber optic equipment trays. The module guides support one or more fiber optic modules. In this manner, the fiber optic modules translate within the chassis to move the fiber optic modules about the chassis. The

module rail guides also allow fiber optic modules to be rear-installable into the chassis to be rear-installable in the fiber optic equipment. Module guides disposed in the chassis also allow the fiber optic modules to be independently translated within the module guides within the chassis.

[0013] Additional features and advantages of the invention will be set forth in the detailed description which follows, and in part will be readily apparent to those skilled in the art from that description or recognized by practicing the invention as described herein, including the detailed description that follows, the claims, as well as the appended drawings.

[0014] It is to be understood that both the foregoing general description and the following detailed description present embodiments of the invention, and are intended to provide an overview or framework for understanding the nature and character of the invention as it is claimed. The accompanying drawings are included to provide a further understanding of the invention, and are incorporated into and constitute a part of this specification. The drawings illustrate various embodiments of the invention, and together with the description serve to explain the principles and operation of the invention.

BRIEF DESCRIPTION OF THE FIGURES

[0015] **FIG. 1** is a front perspective view of an exemplary fiber optic equipment rack with exemplary fiber optic equipment supporting rear-installable fiber optic modules according to one embodiment;

[0016] **FIG. 2A** is a rear perspective view of the fiber optic equipment supporting the rear-installable fiber optic modules of **FIG. 1**;

[0017] **FIG. 2B** is a perspective view of fiber optic equipment tray guides disposed in the fiber optic equipment of **FIG. 1**;

[0018] **FIG. 3** is a front perspective view of an individual fiber optic equipment tray in the fiber optic equipment of **FIG. 1** without rear-installable fiber optic modules installed in module guides disposed in the fiber optic equipment tray;

[0019] **FIG. 4** is a front perspective view of a fiber optic module that is rear-installable in the fiber optic equipment tray of **FIG. 3**;

[0020] FIG. 5 is a rear perspective close-up view of the rear-installable fiber optic module of FIG. 4 installed in the fiber optic equipment tray of FIG. 3;

[0021] FIG. 6 is a front perspective view of the fiber optic equipment tray of FIG. 3 with rear-installable fiber optic modules installed in the module guides;

[0022] FIG. 7 is a front perspective close-up view of the fiber optic equipment tray of FIG. 3 with rear-installable fiber optic modules installed in the module guides;

[0023] FIG. 8 is a front perspective view of a fiber optic equipment tray extended from the fiber optic equipment;

[0024] FIG. 9 is a front perspective view of a fiber routing guide tray of a fiber optic equipment tray lowered to obtain front access to the fiber optic modules supported in the fiber optic equipment tray;

[0025] FIG. 10 is a front perspective view of another exemplary fiber optic equipment supporting rear-installable fiber optic modules disposed in module guides;

[0026] FIG. 11 is a rear perspective view of the fiber optic equipment supporting the rear-installable fiber optic modules of FIG. 10;

[0027] FIG. 12 is a front perspective view of an individual fiber optic equipment tray in the fiber optic equipment of FIG. 10;

[0028] FIG. 13 is a rear perspective view of the rear-installable fiber optic module installed in the module guides disposed in the fiber optic equipment of FIG. 10;

[0029] FIG. 14 is a rear perspective close-up view of the rear-installable fiber optic module disposed within module guides in the fiber optic equipment of FIG. 10 and locked into the fiber optic equipment tray of FIG. 12 when the fiber optic module is pulled forward;

[0030] FIG. 15 is a rear perspective view of the fiber optic module in FIG. 14;

[0031] FIG. 16A is a perspective close-up view of a front locking latch in the fiber optic module of FIG. 15;

[0032] FIG. 16B is a perspective close-up view of a rear lock in the fiber optic module of FIG. 15;

[0033] FIG. 17 is a rear perspective close-up view of the rear-installable fiber optic modules installed in module guides;

[0034] FIG. 18 is a perspective view of the locking features to lock fiber optic modules to fiber optic equipment tray and the fiber optic equipment trays to the chassis of the fiber optic equipment of FIG. 10;

[0035] FIG. 19 is a front perspective view of the fiber optic equipment of FIG. 10 with rear-installable fiber optic modules disposed in the module guides;

[0036] FIG. 20 is a side cross-sectional view of the fiber optic equipment of FIG. 10 with rear-installable fiber optic modules disposed in the module guides and interlocked with the fiber optic equipment trays, with one fiber optic equipment tray extended forward;

[0037] FIG. 21 is a front perspective view of the fiber optic equipment of FIG. 20;

[0038] FIG. 22 is a front perspective view of another exemplary fiber optic equipment supporting rear-installable fiber optic modules;

[0039] FIG. 23 is a rear perspective view of the fiber optic equipment supporting the rear-installable fiber optic modules of FIG. 22;

[0040] FIG. 24A is a front view of a module guide supporting rear-installable fiber optic modules in the fiber optic equipment of FIG. 22;

[0041] FIG. 24B is a perspective view of the module guide illustrated in FIG. 24A;

[0042] FIG. 25 is a front perspective view of the fiber optic modules disposed in the module guides provided in the fiber optic equipment of FIG. 22;

[0043] FIGS. 26A and 26B are a front view of the fiber optic equipment of FIG. 22 with fiber optic modules installed in all module guides and a locking feature to prevent the fiber optic modules from being pulled forward beyond a front end of the fiber optic equipment;

[0044] FIG. 27 is a top view of a fiber optic module supported by module guides disposed in the fiber optic equipment of FIG. 22;

[0045] FIG. 28 is a front perspective view of another exemplary fiber optic equipment supporting rear-installable fiber optic modules;

[0046] FIG. 29 is a rear perspective view of the fiber optic equipment supporting the rear-installable fiber optic modules of FIG. 28;

[0047] FIG. 30 is a front perspective view of the fiber optic modules provided in the fiber optic equipment of FIG. 22;

[0048] FIG. 31 is another rear perspective view of the fiber optic equipment supporting the rear-installable fiber optic modules of FIG. 28;

[0049] FIG. 32 is another front perspective view of the fiber optic equipment supporting the rear-installable fiber optic modules of FIG. 28 with a fiber routing tray extended and tilted downward to provide access to certain fiber optic modules;

[0050] FIG. 33 is another front perspective view of the fiber optic equipment supporting the rear-installable fiber optic modules of FIG. 28 with the fiber routing tray extended and tilted downward;

[0051] FIG. 34 is a front perspective view of another exemplary fiber optic equipment supporting rear-installable fiber optic modules; and

[0052] FIG. 35 is another front perspective view of another exemplary fiber optic equipment supporting rear-installable fiber optic modules.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0053] Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings, in which some, but not all embodiments of the invention are shown. Indeed, the invention may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Whenever possible, like reference numbers will be used to refer to like components or parts.

[0054] Embodiments disclosed in the detailed description include fiber optic equipment that supports one or more rear-installable fiber optic modules. The fiber optic modules are configured to support fiber optic connections. The fiber optic equipment is comprised of a chassis defining a front end and a rear section. At least one guide system is disposed in the chassis and configured to receive at least one fiber optic module. The guide system may be provided in the form of a rail guide system. The guide system receives a fiber optic module from the rear section of the chassis and is configured to guide the fiber optic module toward the front end of the chassis. In this manner, a technician can make fiber optic connections to fiber optic modules and also install the

fiber optic modules into the fiber optic equipment from the rear section of the chassis to reduce time and/or labor in making fiber optic connections.

[0055] In some disclosed embodiments, the guide system is comprised of at least one tray guide that receives at least one fiber optic equipment tray. The tray guides are disposed in the chassis of the fiber optic equipment. The tray guides support fiber optic equipment trays within the fiber optic equipment. At least one module guide is disposed in the fiber optic equipment trays to support one or more fiber optic modules. In this manner, the fiber optic equipment tray can translate within the chassis to move the fiber optic modules supported by the fiber optic equipment tray about the chassis. The module guides also allow fiber optic modules to be rear-installable into the fiber optic equipment tray to be rear-installable in the fiber optic equipment. The tray guides disposed in the fiber optic equipment tray also allow the fiber optic modules disposed therein to be independently translated within the fiber optic equipment tray.

[0056] **FIG. 1** illustrates an exemplary fiber optic equipment **10** in this regard. The exemplary fiber optic equipment **10** may be provided at a data distribution center or central office to support cable-to-cable fiber optic connections and to manage a plurality of fiber optic cable connections. As will be described in greater detail below, the fiber optic equipment **10** has one or more fiber optic equipment trays that each support one or more rear-installable fiber optic modules. The fiber optic modules can be fiber optic adapter modules or any other type of fiber optic modules or fiber optic apparatuses, including those that support fiber optic connections. Both the fiber optic modules and the fiber optic equipment trays are rear-installable, meaning they can be installed from a rear section of the fiber optic equipment **10**. Further, both the fiber optic equipment trays and the fiber optic modules supported therein are independently translatable about the chassis for installation, access, and/or removal.

[0057] In this regard and as illustrated in **FIG. 1**, the fiber optic equipment **10** includes a fiber optic equipment chassis **12** ("chassis **12**"). The chassis **12** is shown as being installed in a fiber optic equipment rack **14**. The fiber optic equipment rack **14** contains two vertical rails **16A**, **16B** that extend vertically and include a series of apertures **18** for facilitating attachment of the fiber optic equipment **10** inside the fiber optic equipment rack **14**. The fiber optic equipment **10** is attached and supported by the

fiber optic equipment rack **14** in the form of shelves that are stacked on top of each other within the vertical rails **16A**, **16B**. As illustrated, the fiber optic equipment **10** is attached to the vertical rails **16A**, **16B**. The fiber optic equipment rack **14** may support 1U-sized shelves, with “U” equal a standard 1.75 inches in height. As will be discussed in greater detail later in this application, the fiber optic equipment **10** includes a plurality of extendable fiber optic equipment trays **20** that each carries one or more rear-installable fiber optic modules **22**. In this example, the fiber optic equipment **10** provides a density of 144 fibers, although it is not limited to this density. Further, as will also be described in more detail below, each fiber optic equipment tray **20** is independently translatable and accessible to access the fiber optic modules supported therein.

[0058] **FIG. 2A** illustrates a rear perspective view of the fiber optic equipment **10** illustrated in **FIG. 1**. The fiber optic equipment **10** is provided in the chassis **12** that defines a front end **24**, a rear section **26**, a first end **28**, and a second end **30**. The first end **28** of the chassis **12** is disposed on the opposite side of the second end **30** of the chassis **12**. A guide system in the form of a rail guide system **32** is provided to support the rear-installable fiber optic modules **22**. The rail guide system **32** comprises two tray rail guides **32A**, **32B** attached to the chassis **12** on the first end **28** and the second end **30**, respectively. The tray rail guides **32A**, **32B** are configured to support one or more fiber optic equipment trays that support the fiber optic modules **22**, which will be illustrated in **FIG. 3** and described below. The tray rail guides **32A**, **32B** allow each fiber optic equipment tray **20** installed therein to be translated about the chassis **12**. In this example, the chassis **12** supports three (3) fiber optic equipment trays **20** with each one stacked on top of each other. A tray cover **34** is disposed on top of the top fiber optic equipment tray **20** disposed in the chassis **12** and within the tray rail guides **32A**, **32B**. As will be discussed later in this application, each fiber optic equipment tray **20** contains a fiber routing tray **36** attached thereto to support routing of optical fibers connected to the fiber optic modules **22**. The fiber routing tray **36** can be extended and lowered as desired to obtain access to the fiber optic modules **22** from the front end **24** of the fiber optic equipment **10**.

[0059] **FIG. 2B** illustrates the tray rail guides **32A**, **32B** in more detail. As illustrated therein, the tray rail guides **32A**, **32B** form a series of channels **38A-38C**, wherein each

channel 38A-38C is configured to receive a fiber optic equipment tray 20. The tray rail guides 32A, 32B allow a plurality of fiber optic trays 20 arranged in a column format. The tray rail guides 32A, 32B comprise an end portion 40 by which the channels 38A-38C stop and the fiber optic equipment trays 20 cannot extend beyond. This end portion 40 is disposed in an orientation such that it is adjacent the rear section 26 of the fiber optic equipment 10. The tray rail guides 32A, 32B also contain an entry portion 42 through which the fiber optic equipment trays 20 can be inserted into the channels 38A-38C. Note that the entry portion 42 does not close off the channels 38A-38C such that the fiber optic equipment trays 20 can be extended beyond the entry portion 42 back towards the rear section 26 of the chassis 12. In this manner, the tray rail guides 32A, 32B support rear installation of fiber optic equipment trays 20 into the chassis 12 from the rear section 26.

[0060] FIG. 3 illustrates an individual fiber optic equipment tray 20 not disposed in the chassis 12 or contained within the tray rail guides 32A, 32B for further discussion and illustration. As illustrated therein, the fiber optic equipment tray 20 contains a main tray portion 44 and the fiber routing tray 36 attached thereto. The fiber routing tray 36 is attached to the main tray portion 44 via hinge mechanisms in the form of hinges 46A, 46B disposed on each end 48A, 48B of the main tray portion 44. The main tray portion 44 contains a plurality of module guides in the form of module rail guides 50 that support the fiber optic modules 22. More specifically, the fiber optic modules 22 contain rails (elements 52A, 52B in FIG. 4) that couple to tray channels 54 disposed within the module rail guides 50. The fiber optic modules 22 are disposed in a row arrangement if at least one intermediate module rail guide 50 is disposed in the fiber optic equipment tray 20. Providing a plurality of tray channels 54 in each module rail guide 50 allows a plurality of fiber optic modules 22 to be stacked on top of each other in a column arrangement. The fiber optic modules 22 can be moved within the module rail guides 50 in the fiber optic equipment tray 20 either towards the front end 24 of the chassis 12 or the rear section 26 or the chassis 12. The fiber optic equipment trays 20 can also be moved about the tray rail guides 32A, 32B. In this manner, the fiber optic equipment trays 20 can be translated independently of each other about the tray rail guides 32A,

32B, and each of the fiber optic modules **22** within a given fiber optic equipment tray **20** can be independently translated within their respective module rail guides **50**.

[0061] Note that in **FIG. 3**, the fiber optic equipment tray **20** contains five (5) module rail guides **50**, which means that the fiber optic equipment tray **20** can support four (4) individual fiber optic modules **22**. Four (4) fiber optic modules **22** can be installed in the fiber optic equipment tray **20** of **FIG. 3**, or less than four as desired or as required according to installation requirements. Also as shown in **FIG. 3** and as illustrated in more detail in **FIG. 4**, the module rail guides **50** are configured such that the tray channels **54** are open on a rear end **56** of the module rail guides **50**. This allows the fiber optic modules **22** to be rear-installable into the fiber optic equipment trays **20** from the rear section **26** of the chassis **12**. More specifically, the fiber optic equipment tray **20** is disposed in the chassis **12** such that the rear ends **56** of the module rail guides **50** are oriented towards the rear section **26** of the chassis **12**. Thus, as will be discussed in more detail below, the fiber optic modules **22** can be inserted into the rear ends **56** of the module rail guides **50** and pushed forward within the module rail guides **50** until the fiber optic modules **22** reach a front end **58** of each module rail guide **50**. A locking feature not illustrated in **FIG. 3**, but described later below in this application, can be provided to prevent the fiber optic module **22** from extending beyond the front end **58** of the module rail guides **50** unless a release is engaged. In this manner, the fiber optic modules **22** can be installed from the rear of the chassis **12**, but can also be extended and removed from the front end **24** of the chassis **12** as well.

[0062] Also as illustrated in **FIG. 3**, the fiber routing tray **36** is formed from sheet metal or other material that is bent on top of itself in a U-shape on a front end **60** of the fiber routing tray **36**. In this manner, optic fibers extending from the fiber optic modules **22** installed in the fiber optic equipment tray **20**, and in particular the module rail guides **50** disposed therein, can be routed underneath a lip section **23** contained in the fiber routing tray **36** and disposed to either end **48A**, **48B** of the fiber optic equipment tray **20** to be routed for connection to other fiber optic equipment.

[0063] **FIG. 4** illustrates an example of a fiber optic module **22** that is supported in the fiber optic equipment tray **20** in **FIGS. 1-3**. As illustrated therein, the fiber optic module **22** is comprised of a number of fiber optic adapters **64** disposed on a front end **66**

of the fiber optic module 22. In this example, the fiber optic adapters 64 accept duplex LC fiber optic connectors 68. However, any fiber optic connection type desired can be provided in the fiber optic modules 22. Fiber optic cables (not shown) extend from the fiber optic connectors 68 to establish fiber optic connections with other equipment. Another fiber optic adapter 70 is disposed on a rear end 72 of the fiber optic module 22. In this example, the fiber optic adapter 70 is an MTP fiber optic adapter equipped to establish connections to up to twelve (12) optical fibers. The fiber optic module 22 may also manage polarity between the fiber optic connectors 68 and the fiber optic adapters 64 disposed on the front end 66 of the fiber optic module 22 and the fiber optic adapter 70 disposed on the rear end 72 of the fiber optic module 22.

[0064] Module rails 52A, 52B are disposed on each side 74A, 74B of the fiber optic module 22. The module rails 52A, 52B are configured to be inserted within the tray channels 54 of the module rail guides 50 in the fiber optic equipment tray 20 as illustrated in FIG. 3. In this manner, when it is desired to install the fiber optic module 22 in the fiber optic equipment tray 20, the front end 66 of the fiber optic module 22 can be inserted from the rear section 26 of the chassis 12. More specifically, the front end 66 of the fiber optic module 22 is inserted into the tray channels 54 of the module rail guides 50 at their rear ends 56. In this manner, the fiber optic module 22 is rear-installable in the fiber optic equipment tray 20 and the chassis 12. The fiber optic module 22 can then be pushed forward within the tray channels 54 until the fiber optic module 22 reaches the front end 58 of the module rail guides 50. In this manner, a technician can install a fiber optic connection to the fiber optic adapter 70 disposed on the rear end 72 of the fiber optic module 22 and can then install the fiber optic module 22 from the rear section 26 of the chassis 12 into the fiber optic equipment tray 20.

[0065] In this regard, FIG. 5 illustrates a rear perspective view of the fiber optic modules 22 installed in the fiber optic equipment trays 20 and the module rail guides 50 disposed therein. As illustrated therein, when the fiber optic module 22 is installed in the tray channels 54 of the module rail guides 50 from the rear section 26 of the chassis 12, the module rails 52A, 52B of the fiber optic module 22 move towards the front end 24 within the tray channels 54. The fiber optic module 22 can be moved towards the front end 24 until the fiber optic modules 22 reach a stop or locking feature disposed in the

front end 24 as will described later in this application. A locking feature in the form of a locking latch 78 and a protrusion 80 (FIG. 4) engage a complementary protrusion disposed in the tray channel 54 such that the fiber optic module 22. The locking latch 78 is inwardly biased such that the fiber optic module 22 can be installed in the tray rail guides 32, but cannot be pulled back towards the rear section 26 of the chassis 12 until the locking latch 78 is disengaged to prevent the protrusion 80 from engaging with the module rail guides 50. The locking latch 78 is disengaged by pushing it inward towards the fiber optic module 22 to release the protrusion 80 from the tray channel 54.

[0066] If it is desired to remove the fiber optic module 22 from the fiber optic equipment tray 20, the fiber optic module 22 can be removed from either the rear section 26 of the chassis 12 or from the front end 24 of the chassis 12. To remove the fiber optic module 22 from the rear section 26 of the chassis 12, a pulling loop 76 disposed in the rear end 72 of the fiber optic module 22 can be pulled once the locking latch 78 is disengaged inward. The locking latch 78 controls the position of the protrusion 80 extending outward from the module rail 52A such that when the fiber optic module 22 is extended along a certain portion of the module rail guides 50, the protrusion 80 prevents the fiber optic module 22 from moving backwards along the tray channels 54 towards the rear section 26 of the chassis 12.

[0067] FIG. 6 illustrates the fiber optic equipment tray 20 of FIG. 3; however, with the rear-installable fiber optic modules 22 installed therein. The fiber optic modules 22 are installed in the module rail guides 50 disposed in the fiber optic equipment tray rails 82A, 82B. These fiber optic equipment tray rails 82A, 82B are configured to be disposed in the module rail guides 32A, 32B attached to the chassis 12 as illustrated in FIG. 2A such that the fiber optic equipment tray 20 is translatable with respect to the chassis 12.

[0068] FIG. 7 illustrates a front perspective view of the fiber optic equipment tray 20 in FIG. 6 in more detail. As illustrated therein, three (3) fiber optic equipment trays 20 are disposed within the tray rail guides 32A, 32B of the chassis 12. As illustrated therein, the hinges 46A, 46B that hingedly attach the fiber routing tray 36 to the fiber optic equipment trays 20 are provided in the form of position hinges 47. The position hinges 47 are configured to engage with the module rail guides 50 such that the fiber optic module 22 cannot be extended forward when the position hinges 47 are engaged. If it is

desired to access the fiber optic module 22, the pulling tab 25 attached to the fiber routing tray 36 can be pulled forward to cause the fiber optic equipment tray 20 to extend forward from the front end 24 of the chassis 12 as illustrated in FIG. 8. Thereafter, the fiber routing tray 36 can be tilted downward as illustrated in FIG. 9. When the fiber optic equipment tray 20 and its fiber routing tray 36 are tilted downward, the position hinges 47 on each side of the fiber optic equipment tray 20 are disengaged with the module rail guides 50 for that particular fiber optic equipment tray 20 such that the fiber optic modules 22 supported by that fiber optic equipment tray 20 can be removed from the front end 24 of the chassis 12. Also, by allowing the fiber routing tray 36 to be tilted downward, unobstructed access can be obtained to the fiber optic module adapter 70 and fiber optic connectors 68 for establishing or disconnecting fiber optic connections.

[0069] A plurality of fiber optic modules can also be disposed in a module guide system in the fiber optic equipment without need or requirement for an intermediate fiber optic equipment tray. In this manner, each of the fiber optic modules translates independently of other fiber optic modules disposed within the module guide system. In this regard, FIG. 10 illustrates another embodiment of fiber optic equipment 100. Fiber optic equipment 100 includes a module guide system disposed in a chassis 102 that supports rear-installable fiber optic modules. As will be described later in this application, the fiber optic equipment 100 provides an alternative guide system for rear-installable fiber optic modules. In FIG. 10, fiber optic modules 104 are supported within module rail guides 106 disposed in a chassis 102 of the fiber optic equipment 100. This is opposed to the fiber optic equipment 10 in FIGS. 1-9, wherein fiber optic modules are disposed in intermediate fiber optic equipment trays attached to a chassis. In this manner and as illustrated in FIG. 10, the fiber optic equipment 100 allows fiber optic modules 104 to be inserted into module rail guides 106 disposed in the chassis 102 and independently translated about the module rail guides 106.

[0070] Turning to FIG. 10, a plurality of rear installable fiber optic modules 104 are installed in the fiber optic equipment 100. The fiber optic modules 104 are supported by a plurality of module rail guides 106. Unlike the fiber optic equipment 10 of FIG. 1, the module rail guides 106 are attached directly to the chassis 102. Fiber optic equipment trays 108 are still provided to support the forward translation of the fiber optic modules

104 from the fiber optic equipment 100. As will be described later in this application, when the fiber optic modules 104 are installed from a rear section 110 of the chassis 102 into the module rail guides 106. The fiber optic modules 104 can then be moved forward within the module rail guides 106 to a front end 112 of the chassis 102. The fiber optic modules 104 will then engage with a latch (not shown) that will then attach the fiber optic modules 104 to fiber optic equipment trays 108. In this manner, when the fiber optic equipment tray 108 is pulled forward from the chassis 102, the fiber optic module 104 will also move outward with the fiber optic equipment tray 108 due to the interlock between the fiber optic modules 104 and the fiber optic equipment tray 108, although is still supported by the module rail guides 106. Thus, in the fiber optic equipment 100 in FIG. 10, the fiber optic equipment trays 108 are independently movable with respect to the chassis 102; however, the fiber optic modules 104 are not independently movable within the fiber optic equipment tray 108 like provided in the fiber optic equipment 10 of FIG. 1.

[0071] The chassis 102 also comprises a first end 114 and a second end 116, wherein the second end 116 is disposed on the opposite side from the first end 114. A plurality of module rail guides 106 are disposed within the chassis 102 between the first end 114 and the second end 116. A minimum of two (2) module rail guides 106 are required to support at least one (1) fiber optic module 104. However, as illustrated in FIG. 10, five (5) module rail guides 106 are provided to support four (4) fiber optic modules 104 per level. As will be described later in this application in more detail, the module rail guides 106 can contain a plurality of channels 118 to support more than one level or plane of fiber optic modules 104. In the example of the fiber optic equipment 100 in FIG. 10, three (3) levels of fiber optic modules 104 are provided; thus, three (3) channels 118 are provided in each module rail guide 106. The fiber optic equipment trays 108 each contain a routing tray 120 that can be pulled in order to remove a fiber optic equipment tray 108 from the chassis 102.

[0072] FIG. 11 illustrates a rear perspective view of the module rail guides 106 disposed within the chassis 102 and how the fiber optic module 104 is installed from the rear section 110 of the chassis 102. Further, FIG. 11 illustrates how the fiber optic equipment trays 108 are also supported by the module rail guides 106 and how the fiber

optic modules 104 attach to the fiber optic equipment trays 108 when pulled forward. As illustrated in FIG. 11, the module rail guides 106 are provided wherein a fiber optic module 104 can be inserted from the rear section 110 into the channels 118. The fiber optic module 104 can then be pushed forward with the module rail guides 106 towards the front end 112 of the chassis 102. The module rail guides 106 also contain a series of tray guides 122 disposed in the plane substantially orthogonal to the channels 118 to receive fiber optic equipment trays 108, although any orientation is possible.

[0073] As illustrated in FIG. 12, the fiber optic equipment tray 108 contains a series of elongated sections 124. The elongated sections 124 are configured to be inserted into the tray guides 122 disposed inside the module rail guides 106 along the longitudinal axis of the channels 118. Thus, as illustrated in FIGS. 13 and 14, when the fiber optic module 104 is pulled all the way forward along the module rail guide 106 to a front portion 126 of the fiber optic equipment tray 108, a locking feature in the form of a front module latch 128 interlocks with a detent feature 130 disposed adjacent the front end 112 of the chassis 102. The detent feature 130 is secured to the fiber optic equipment tray 108. In this manner, the fiber optic module 104 becomes interlocked with the fiber optic equipment tray 108 such that when the fiber optic equipment tray 108 is translated forward on the first end 114 of the chassis 102, the fiber optic module 104 travels forward with the fiber optic equipment tray 108. The elongated sections 124 and the fiber optic modules 104 interlocked with the fiber optic equipment tray 108 translate together about the tray guides 122 even though the fiber optic module 104 is still supported by the module rail guides 106. FIG 15 illustrates the fiber optic module 104 and more detail regarding the front module latch 128 in particular.

[0074] As illustrated in FIG. 15, the fiber optic module 104 is comprised of a plurality of fiber optic adapters 132 configured to support fiber optic connectors 134 on a front end 136 of the fiber optic module 104. A fiber optic adapter 138 is disposed on a rear end 140 of the fiber optic module 104. In this example of the fiber optic module 104 of FIG. 15, the fiber optic adapters 132 are duplex LC fiber optic adapters, and the fiber optic adapter 138 disposed in the rear end 140 of the fiber optic module 104 is an MTP fiber optic adapter, although any fiber connection type is possible. Fiber optic connections are established between the fiber optic connectors 134 and an MTP fiber

optic connector **142** connected to the MTP fiber optic adapter **138**. Optical fibers establishing connections between the fiber optic adapters **132**, **138** are provided inside the fiber optic module **104**.

[0075] The fiber optic module **104** also contains two (2) module rails **144A**, **144B** on a first side **146** and a second side **148**, respectively, of the fiber optic module **104**. The module rails **144A**, **144B** are configured to be inserted into the channels **118** of the module rail guides **106** such that the fiber optic module **104** can be translated within the module rail guides **106**. In this regard, because the channels **118** in the module rail guides **106** are open in the rear section **110**, as illustrated in **FIG. 11**, the fiber optic modules **104** are rear-installable into the fiber optic equipment **100**. The fiber optic module **104** can then be translated forward within the channels **118** until the front module latch **128** reaches the detent feature **130**. The front module latch **128** is biased inward such that when it reaches the detent feature **130**, the front module latch **128** flexes inward and is retained in the detent feature **130**. Once the front module latch **128** is retained in the detent feature **130**, the fiber optic module **104** cannot be pulled back towards the rear section **110** or towards the front end **112** independent of the fiber optic equipment tray **108** unless the front module latch **128** is released from the detent features **130**. In this manner, the front module latch **128** releasably retains the fiber optic module **104**.

[0076] **FIG. 16A** illustrates the front module latch **128** for the fiber optic module **104** in more detail. **FIG. 16B** illustrates a locking feature in the form of a rear module lock **150** that may be provided in the rear end **140** of the fiber optic module **104** to lock the fiber optic module **104** within the module rail guides **106**. In this manner, the fiber optic module **104** cannot be removed towards the rear section **110** of the fiber optic equipment **100** unless the rear module lock **150** is unlocked by pushing a rear module lock button **152** to the right as illustrated. When the rear module lock button **152** is moved to the right as illustrated, a latch **154** is disengaged from the channel **118** of the module rail guide **106** such that the fiber optic module **104** can be removed from the rear section **110**. The fiber optic module **104** may be removed from the rear section **110** by pulling on a pulling loop **156** (as shown in **FIG. 15**) attached to the rear end **140** of the fiber optic module **104**.

[0077] **FIGS. 17 and 18** illustrate the detent feature **130** and how the fiber optic equipment trays **108** are interlocked into the chassis **102**. As illustrated therein, the fiber optic equipment tray **108** contains an upwardly extending tab **158** that is secured to a bracket **160** wherein the bracket **160** is attached to the chassis **102**. The bracket **160** contains a series of apertures **162** that are adapted to receive flanges **164** from plungers **166**. Each fiber optic equipment tray **108** contains a plunger **166** disposed through the upwardly extending tab **158** that is adapted to engage with the aperture **162**. When it is desired to lock the fiber optic equipment tray **108** to the chassis **102**, the plunger **166** is engaged in the aperture **162**. As illustrated in **FIGS. 17 and 18**, three (3) apertures **162** are provided in the bracket **160** because three (3) fiber optic equipment trays **108** are provided. Each aperture **162** is designed to retain the upwardly extending tab **158** from a particular fiber optic equipment tray **108**. **FIG. 17** illustrates the bracket **160** disposed on the second end **116** of the chassis **102**. Although not shown, the bracket **160** is also disposed on the first end **114** of the chassis **102** as illustrated in **FIG. 10**. When it is desired to release the fiber optic equipment tray **108** from the chassis **102**, such as to pull it forward for access, the plunger **166** is pulled and disengaged from the corresponding aperture **162** in the bracket **160**. In this manner, each fiber optic equipment tray **108** is free to independently translate outwardly towards the front end **112** wherein the elongated sections **124** are moved forward about the tray guides **122** within the module rail guides **106**.

[0078] **FIG. 19** illustrates a front perspective view of the fiber optic equipment **100** and the fiber optic modules **104** locked into the fiber optic equipment trays **108** via the front module latch **128** engaging with the detent feature **130**. As illustrated therein, each of the fiber optic equipment trays **108** are secured to the chassis **102** via their plungers **166** being engaged with the bracket **160**. In order to disengage the fiber optic equipment tray **108** from the chassis **102**, the plunger **166** is pulled to disengage the plunger **166** from the aperture **162** in the bracket **160**. In this manner, the pulling force applied towards the front end **112** will translate the fiber optic equipment tray **108** forward. This is illustrated in **FIGS. 20 and 21**. **FIG. 20** is a side cross-sectional view of the fiber optic equipment **100** shown in perspective view in **FIG. 21** with a middle fiber optic equipment tray **108** extended. As illustrated therein, the middle fiber optic equipment

tray 108 is extended from the chassis 102. The plunger 166 for the middle fiber optic equipment tray 108 is disengaged from the bracket 160 and the aperture 162 therein.

[0079] FIG. 22 illustrates yet another example of fiber optic equipment 200 that also provides for rear-installable fiber optic modules. Like the fiber optic equipment 100 in FIGS. 10-21, each fiber optic module supported in the fiber optic equipment 200 of FIG. 22 is supported in module rails disposed in the chassis. The fiber optic modules are also independently translatable within the module rails.

[0080] As illustrated in FIG. 22, the fiber optic equipment 200 is provided, which includes a chassis 202 configured to hold one or more fiber optic modules 204. The fiber optic modules 204 are supported on a guide system in the form of module rail guides 206 that are disposed within and attached to the chassis 202 similar to the fiber optic equipment 100 in FIGS. 10-21. The module rail guides 206 are attached to the chassis 202. Only two module rail guides 206 are required to be provided on a first end 208 of the chassis 202 and a second end 210 of the chassis 202 such that a fiber optic module 204 can be installed in a rear section 212 of the chassis 202 and moved along the module rail guides 206 to a front end 214 of the chassis 202.

[0081] As will be described in further detail in this application, the module rail guides 206 contain one or more channels 216 (shown in FIGS. 24A and 24B) that are adapted to receive rails (element 215 in FIG. 25) disposed on each side of the fiber optic modules 204. The channels 216 are open in the rear section 212 such that the rails of the fiber optic module 204 can be inserted into the module rail guides 206 in the rear section 212 of the chassis 202 and moved forward within the module rail guides 206 until the fiber optic module 204 reaches the front end 214 of the chassis 202. This is further illustrated in FIG. 23. As illustrated therein, a fiber optic module 204 is shown as being inserted partially into the module rail guides 206. Module rails 215A, 215B are disposed on each side of the fiber optic module 204 such that the module rails 215A, 215B mate with the channels 216 in the module rail guides 206 so that the fiber optic module 204 may be slid from the rear section 212 to the front end 214 of the chassis 202.

[0082] FIGS. 24A and 24B illustrate more detail regarding the module rail guides 206 that are disposed in the fiber optic equipment 200 of FIGS. 22 and 23. As illustrated therein, a module rail guide 206 is disclosed that is provided between the first end 208

and the second end 210. For this type of module rail guide 206, the channels 216 are disposed on a first side 218 of the module rail guides 206. Channels 220 are also provided on a second side 224 of the module rail guides 206. In this manner, the module rail guide 206 can support rails of fiber optic modules 204 on each side. The module rail guide 206 illustrated in FIG. 24A would be provided as an intermediate module rail guide if more than one fiber optic module 204 in a given plane is supported by the fiber optic equipment 200. In this case, at least one intermediate module rail guide 206 is provided with channels 216, 220 disposed on each side 218, 224. As illustrated in FIG. 24A, the module rail guide 206 is attached to the chassis 202 such that when the module rails 215A, 215B of the fiber optic modules 204 are disposed within the channels 216, 220, the fiber optic modules 204 are supported by the chassis 202. Also, as will be described in greater detail below with regard to FIGS. 26A and 26B, the module rail guides 206 also contain a series of internal apertures 219 that support attaching module locks or stops to the chassis 202. The module locks or stops prevent the fiber optic modules 204 from translating beyond the front end 214 of the chassis 202.

[0083] FIG. 25 illustrates the rear-installable fiber optic module 204 that is adapted to be supported by the module rail guides 206 of the fiber optic equipment 200. As illustrated therein, module rails 215A, 215B are disposed on sides 226, 228, respectively, of the fiber optic module 204. These module rails 215A, 215B can be inserted into the module rail guides 206 to insert the fiber optic module 204 into the fiber optic equipment 200. Because the channels 220 in the module rail guides 206 are open in the rear section 212 of the chassis 202, the fiber optic modules 204 are rear-installable, meaning they can be installed from the rear section 212 of the chassis 202. The fiber optic module 204 contains a series of fiber optic adapters 230 disposed on a front end 232 of the fiber optic module 204. One or more fiber optic adapters 230 optically connected to the fiber optic adapters 230 are disposed on a rear end 234 of the fiber optic module 204. In this manner, connectorized fiber optic cables (not shown) connected to the fiber optic adapters 230 establish a fiber optic connection with fiber optic cables (not shown) installed in the fiber optic adapters 230 in the rear end 234 of the fiber optic module 204.

[0084] FIG. 26A illustrates a front view of the fiber optic equipment 200 with fiber optic modules 204 installed in the module rail guides 206 as previously described. To

prevent the fiber optic modules **204** from extending beyond the first end **208** of the chassis **202**, stop or lock features **236** are disposed between the rows of fiber optic modules **204** on the intermediate module rail guides **206**. **FIG. 26B** illustrates the stop or lock features **236** in more detail wherein front and rear perspective views are illustrated. The stop or lock features **236** contain a series of apertures **238** that align with the apertures **219** disposed in the module rail guides **206** as illustrated previously in **FIG. 24B**. A fastener (not shown) can be inserted into the apertures **238** to fasten the stop or lock features **236** to the module rail guides **206**. The stop features **236** contain opposing flared portions **240** on each side of the stop or lock feature **236** which contain platforms **242** of which the front end **232** of the fiber optic modules **204** abut against to prevent the fiber optic modules **204** from extending forward from the first end **208** of the chassis **202**.

[0085] **FIG. 27** illustrates a top view of the fiber optic equipment **200** with the fiber optic module **204** installed therein between two module rail guides **206**. As illustrated therein, the fiber optic module **204** is extended forward to the front end **214** of the chassis **202** wherein the front end **232** of the fiber optic module **204** abut against the platforms **242** in the stop or lock features **236** to prevent the fiber optic modules **204** from being extended beyond the front end **214** of the fiber optic equipment **200**.

[0086] **FIG. 28** illustrates yet another embodiment of fiber optic equipment that is configured to allow and support rear-installable fiber optic modules. As illustrated in **FIG. 28**, the fiber optic equipment **300** contains a chassis **302** that supports one or more fiber optic modules **304**. The fiber optic modules **304** are supported by a guide system in the form of module rail guides **306** that are attached to the chassis **302** such that each of the fiber optic modules **304** can translate about the module rail guides **306**. More specifically, the fiber optic modules **304** can be rear-installable from a rear section **308** of the chassis **302** into the module rail guides **306** and extended forward within the module rail guides **306** to a front end **310** of the chassis **302**.

[0087] **FIG. 29** illustrates a rear perspective view of the fiber optic equipment **300** illustrated in **FIG. 28** showing a series of rear-installable fiber optic modules **304** installed therein. It is noted that the module rail guides **306** can be provided that support more than one plane or row of fiber optic modules **304**. In such a case, a plurality of

channels will be provided in the module rail guides **306** to support more than one row of fiber optic modules **304**.

[0088] **FIG. 30** illustrates the fiber optic module **304** illustrated in **FIGS. 28 and 29** in more detail. As illustrated therein, the fiber optic module **304** contains module rails **312A, 312B** disposed on each side **314, 316** of the fiber optic module **304**. The module rails **312A, 312B** are adapted to be received into channels of the module rail guides **306** to support the fiber optic modules **304**. Each fiber optic module **304** is independently movable about the module rail guides **306**. Intermediate fiber optic equipment trays are not provided. The fiber optic module **304** contains a series of fiber optic adapters **318** disposed on a front end **320** of the fiber optic module **304**. A series of fiber optic connectors **322** may be connected to the fiber optic adapters **318** to establish fiber optic connections. A fiber optic adapter **324** is disposed in a rear end **326** of the fiber optic module **304** such that a fiber optic connector **322** connected to the fiber optic adapter **324** will establish an optical connection with optical fibers connected to the fiber optic connectors **322**. The fiber optic module **304** also contains a series of pulling loops **328A, 328B** disposed on each side of the fiber optic adapter **324** that may assist in removing the fiber optic module **304** from the rear section **308** of the fiber optic equipment **300**.

[0089] In order to install a fiber optic module **304** from the rear section **308** of the fiber optic equipment **300**, as illustrated in **FIG. 31**, hinged portions **330A, 330B** of the rear section **308** of the chassis **302** are pulled outward such that the module rail guides **306** are accessible to a technician. Thereafter, the fiber optic module **304** and its module rails **312A, 312B** are inserted into channels in the module rail guides **306** as illustrated in **FIG. 31**. The fiber optic module **304** is then pushed forward within the module rail guides **306** until the fiber optic module **304** reaches the front end **310** of the chassis **302**. Once the fiber optic modules **304** are installed as desired, the hinged portions **330A, 330B** are closed.

[0090] In order to access the fiber optic connectors **322** of the fiber optic modules **304**, a module guide tray **332**, which is hingedly attached via hinges to the module rail guides **306**, can be pulled forward and tilted downward as illustrated in **FIG. 32**. Each fiber optic module **304** has its own module guide tray **332** such that each fiber optic module **304** is individually accessible and independently movable about the module rail

guides 306. The module guide tray 332 may contain a series of fiber routing guides 336 that support routing of connectorized fiber optic cables (not shown) connected to the fiber optic adapters 318 of the fiber optic module 304. FIG. 33 illustrates a side perspective view illustrating more detail regarding the module guide tray 332. The module guide tray 332 is pulled forward and hingably tilted via hinge 334 downward to access the fiber optic adapters 318 of the fiber optic modules 304. The module guide tray 332 may contain a U-shaped flange 338 to allow optical fibers to be routed therein to either the left or right of the tray to the sides 340, 342 of the chassis 302. Further, a handle 344 may be provided and attached to the module guide tray 332 to allow for pulling and pushing for easy translation of the fiber optic module 304.

[0091] FIGS. 34 and 35 illustrate yet another embodiment of fiber optic equipment 400. In this embodiment, a module guide system is provided to allow fiber optic modules 402 to translate independently of each other about a chassis 404 outward in the Z-axis direction. As illustrated herein, two (2) fiber optic modules 402 are provided. Each fiber optic module 402 contains a series of fiber optic adapters 406 disposed in a front end 408 of the fiber optic module 402. A module rail guide 410 is disposed in the fiber optic equipment 400 for each fiber optic module 402. As illustrated in FIGS. 34 and 35, two fiber optic modules 402 are provided that expand the entire width of the chassis 404. Thus, no intermediate module rail guides 410 are necessary or provided in the fiber optic equipment 400. Only two (2) module rail guides 410 are disposed on a first end 412 and a second end 414 of the chassis 404, although intermediate module rail guides can be provided if the fiber optic equipment 400 is designed to support multiple fiber optic modules in a single level or plane. Each fiber optic module 402 comprises a module rail 416 that is configured to be disposed within a channel 420 of the module rail guides 410. In this manner, the fiber optic modules 402 may be rear-installable and may be independently movable from each other along their dedicated module rail 416 so they can be pulled out towards a front end 422 of the fiber optic equipment 400 and chassis 404. This is illustrated in FIGS. 34 and 35 wherein the bottom fiber optic module 402 is pulled forward along its module rail 416 to provide access. After any access desired is completed, the bottom fiber optic module 402 can be pushed back in along its module rail

216 into the chassis **404** such that the front end **422** of the fiber optic module **402** will be disposed within the front end **408** of the chassis **404**.

[0092] Many modifications and other embodiments of the invention set forth herein will come to mind to one skilled in the art to which the invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. These modifications include, but are not limited to, number or type of fiber optic modules, use of a fiber optic equipment tray, fiber optic connection type, number of fiber optic adapters, density, etc.

[0093] Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. It is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

What is claimed is:

1. A fiber optic apparatus, comprising:
a chassis defining a front end, a rear section, a first end, and a second end opposite the first end; and
at least one guide system disposed within the chassis and configured to receive at least one fiber optic module from the rear section of the chassis and guide the fiber optic module toward the front end of the chassis.
2. The fiber optic apparatus of claim 1, wherein the at least one guide system is a rail guide system.
3. The fiber optic apparatus of claim 1, further comprising at least one module locking feature disposed adjacent the front end of the chassis and configured to releasably retain the at least one fiber optic module.
4. The fiber optic apparatus of claim 1, further comprising at least one fiber routing tray attached to the at least one fiber optic module.
5. The fiber optic apparatus of claim 1, wherein the at least one guide system is comprised of at least one tray rail guide receiving at least one fiber optic equipment tray supporting the at least one fiber optic module.
6. The fiber optic apparatus of claim 5, wherein the at least one tray rail guide comprises a plurality of tray rail guides receiving a plurality of fiber optic equipment trays.
7. The fiber optic apparatus of claim 6, wherein each of the plurality of fiber optic equipment trays are independently translatable within the chassis.
8. The fiber optic apparatus of claim 5, further comprising at least one locking feature disposed adjacent the front end of the chassis and configured to releasably retain the at least one fiber optic equipment tray to the chassis.

9. The fiber optic apparatus of claim 5, further comprising at least one fiber routing tray attached to the at least one fiber optic equipment tray.
10. The fiber optic apparatus of claim 9, further comprising a plurality of fiber routing guides disposed in the at least one fiber routing tray.
11. The fiber optic apparatus of claim 5, further comprising at least one module guide disposed in the at least one fiber optic equipment tray receiving at least one fiber optic module.
12. The fiber optic apparatus of claim 11, wherein the at least one module guide comprises:
 - a first module guide disposed on a first end of the at least one fiber optic equipment tray;
 - a second module guide disposed on a second end of the at least one fiber optic equipment tray; and
 - at least one intermediate module guide disposed in the at least one fiber optic equipment tray between the first module guide and the second module guide.
13. The fiber optic apparatus of claim 11, wherein the at least one module guide comprises a plurality of module rail guides configured to receive at least one module rail disposed in each of the plurality of fiber optic modules.
14. The fiber optic apparatus of claim 13, wherein each of the plurality of fiber optic modules are independently translatable within the at least one fiber optic equipment tray.
15. The fiber optic apparatus of claim 1, wherein the at least one guide system is comprised of at least one module rail guide configured to receive the at least one fiber optic module.

16. The fiber optic apparatus of claim 15, wherein the at least one module rail guide comprises:

- a first module rail guide disposed on the first end of the chassis;
- a second module rail guide disposed on the second end of the chassis; and
- at least one intermediate module rail guide disposed in the chassis between the first module rail guide and the second module rail guide.

17. The fiber optic apparatus of claim 15, wherein the at least one module rail guide comprises a plurality of module rail guides configured to receive a plurality of fiber optic modules.

18. The fiber optic apparatus of claim 17, wherein each of the plurality of fiber optic modules are independently translatable within the chassis.

19. The fiber optic apparatus of claim 15, wherein the at least one module rail guide further comprises at least one fiber optic equipment tray guide receiving at least one fiber optic equipment tray.

20. The fiber optic apparatus of claim 19, further comprising at least one module locking feature disposed adjacent a front end of the at least one fiber optic equipment tray and configured to interlock the at least one fiber optic module to the at least one fiber optic equipment tray when the at least one fiber optic module is disposed adjacent the front end of the at least one fiber optic equipment tray.

21. The fiber optic apparatus of claim 20, wherein the at least one module locking feature is comprised of a detent feature attached to the at least one fiber optic equipment tray and configured to interlock with a module latch disposed in the at least one fiber optic module.

22. A fiber optic module, comprising:

- a housing having a front end, a rear end, and at least two sides disposed between the front end and the rear end;

at least one fiber optic adapter disposed in the front end;

at least one fiber optic adapter disposed in the rear end and optically connected to one or more of the at least one fiber optic adapters disposed in the front end; and

at least one rail disposed on a portion of one or more of the at least two sides configured to engage with a guide system of fiber optic equipment to move transversely within the guide system.

23. The fiber optic module of claim 22, wherein the at least one rail is comprised of a first rail disposed on a first side of the at least two sides, and a second rail disposed on a second side of the least two sides.

24. The fiber optic module of claim 22, further comprising a locking feature disposed on the housing and configured to engage with a locking mechanism disposed within the guide system.

25. The fiber optic module of claim 24, wherein the locking feature comprises an inwardly biased latch configured to engage with the locking mechanism when the housing is moved transversely within the guide system.

1/33




FIG. 1

2/33




FIG. 2A

FIG. 2B




FIG. 3

4/33




FIG. 4

5/33






FIG. 5

6/33



7/33



8/33





FIG. 8

9/33



10/33




FIG. 10

11/33





FIG. 11



13/33




FIG. 13

14/33









FIG. 14

15/33



16/33



17/33




FIG. 19

18/33




FIG. 20

19/33




FIG. 21

20/33





FIG. 22



22/33




FIG. 24A




FIG. 24B

23/33




FIG. 25




FIG. 26A




FIG. 26B

25/33




FIG. 27

26/33




FIG. 28

27/33




FIG. 29

28/33




FIG. 30

29/33




FIG. 31

30/33




FIG. 32

31/33





FIG. 33

32/33






FIG. 35