

(No Model.)

7 Sheets—Sheet 1.

J. C. BOWRING & A. NEWCOMB. HYDRAULIC PROPULSION OF VESSELS.

No. 454,151.

Patented June 16, 1891.

Fig. 1.





Fig. 2.



Witnesses.
Thomson Cross,
A. W. Weaver

Inventor
John Charles Bowring,
and Alfred Newcomb,
per Henry O. G. Attorney.


(No Model.)

7 Sheets—Sheet 2.

J. C. BOWRING & A. NEWCOMB.
HYDRAULIC PROPULSION OF VESSELS.

No. 454,151.

Patented June 16, 1891.



Witnesses:
Thomson Cross
A. P. Weaver

Inventors:
J. C. Boring and
Alfred Newcomb.
per Henry O'Bo
 Attorney.


(No Model.)

7 Sheets—Sheet 3.

J. C. BOWRING & A. NEWCOMB.
HYDRAULIC PROPULSION OF VESSELS.

No. 454,151.

Patented June 16, 1891.



(No Model.)

7 Sheets—Sheet 4.

J. C. BOWRING & A. NEWCOMB.
HYDRAULIC PROPULSION OF VESSELS.

No. 454,151.

Patented June 16, 1891.

Fig. 5.





Fig. 14.



Witnesses.
J. Thomson Cross
H. D. Weaver

Inventor.
J. C. Bowring and
Alfred Newcomb.
per Henry O. Th.
Atty.


(No Model.)

7 Sheets—Sheet 5.

J. C. BOWRING & A. NEWCOMB.
HYDRAULIC PROPULSION OF VESSELS.

No. 454,151.

Patented June 16, 1891.



(No Model.)

7 Sheets—Sheet 6.

J. C. BOWRING & A. NEWCOMB. HYDRAULIC PROPULSION OF VESSELS.

No. 454,151.

Patented June 16, 1891.




Fig. 9.




Fig. 10.




Fig. 11.




Fig. 8.




Fig. 7.

Witnesses.



J. Thomson Cross
A. V. Weaver

Inventors.
J. C. Bowring and
Alfred Newcomb.
 per *Murray O'Neil*
Atty.

J. C. BOWRING & A. NEWCOMB.
HYDRAULIC PROPULSION OF VESSELS.

No. 454,151.

Patented June 16, 1891.



Witnesses.
J. Thomson Cross.
A. D. Weaver.

Inventors:
J. C. Bowring and
Alfred Newcomb.
 per *Henry O. W.*
Atty.

UNITED STATES PATENT OFFICE.

JOHN CHARLES BOWRING AND ALFRED NEWCOMB, OF MELBOURNE,
VICTORIA.

HYDRAULIC PROPULSION OF VESSELS.

SPECIFICATION forming part of Letters Patent No. 454,151, dated June 16, 1891.

Application filed September 16, 1889. Serial No. 324,011. (No model.) Patented in Victoria June 14, 1889, No. 6,816.

To all whom it may concern:

Be it known that we, JOHN CHARLES BOWRING and ALFRED NEWCOMB, engineers, subjects of the Queen of Great Britain, residing at Melbourne, in the British Colony of Victoria, have invented new and useful Improvements in and Relating to the Hydraulic Propulsion of Vessels and in Apparatus Therefor, (for which we have obtained Letters Patent in the British Colony of Victoria, No. 6,816, bearing date June 14, 1889,) of which the following is a specification.

Our invention relates to the propulsion of floating craft by hydraulic power, and more particularly to that mode of propulsion in which water is drawn in at one end of the vessel and ejected at the other in an unbroken stream and under pressure; and it consists in structural features and combinations of co-operative elements, as will now be fully described, reference being had to the accompanying drawings, in which—

Figure 1 is a sectional side elevation, and Fig. 2, a plan of a vessel fitted with our improved apparatus for propelling it and for other purposes. In both these views the "pumping-engines," as they may be called, are drawn larger in proportion to the size of the vessel than would actually be the case in practice, while the boilers, on the other hand, are drawn smaller in proportion. This has been done the better to illustrate the construction of these pumping engines or apparatus. Fig. 3 is a front elevation, Fig. 4 a side elevation, and Fig. 5 a plan, of a vertical type of our apparatus, while Fig. 6 is a side elevation illustrating similar apparatus arranged horizontally. Fig. 7 is a detail-view of a certain valve-operating gear, hereinafter described. Fig. 8 is a plan of the end of the discharge-conduit, illustrating the steering devices and the valves connected therewith. Figs. 9 and 10 are respectively a side elevation and a sectional plan of a guard which is provided over the end of the orifice of the inlet-conduit for the purpose of preventing the entrance of any floating bodies, such as fish or logs of wood. Fig. 11 is a side elevation of a valve and raising-gear therefor, which we provide in the main conduits to enable water to be pumped out of the hold in the event of the ship

springing a leak. Figs. 12 and 13 are diagrammatic views illustrating the operation of our pumping engines or apparatus, and Fig. 14 is a detached side elevation of a portion of our improved apparatus, illustrating a modified construction of same.

Similar letters of reference indicate the same or corresponding parts throughout the figures.

The water of flotation is drawn in at the lowest possible point forward, as at A in Fig. 1, forcing such water in one unbroken stream in the form of a rope, as it were, through the vessel and eventually discharging it with augmented force through the tapering tube or conduit B at the stern. By constructing this tube B with a gradually-decreasing area in cross-section the pressure of the water therein will be increased and it will form what may be described as a "solid piston of water," which will act against the water of flotation in a very effective manner.

The conduit C, leading from the bows to the pump, and the conduit B, leading from said pump to the stern, are bolted or riveted to the ribs or framing of the vessel and constitute the keelson thereof, and by reason of their tubular form impart a strength and rigidity to the vessel, which have hitherto been unattainable.

The valves hereinbefore mentioned as being provided for the purpose of allowing the vessel to be pumped free of water in the event of a leak being sprung or a collision taking place are illustrated in position at D in Figs. 1 and 2. They may consist, as shown in detail in Fig. 11, of a simple disk-valve adapted to be raised or lowered by a screw-threaded rod *d*, passing up through a protecting tube or sleeve *d'* to the deck E of the vessel, where said rod may be rotated by means of a suitable key fitted over its squared end *d*², which is preferably let in flush with said deck, as shown. The water so pumped out of the vessel's hold would thus be employed for propelling her.

Over the orifice of the conduit C at the bows of the vessel we arrange a rolled-steel grating F, formed of bars *f*, Figs. 9 and 10, of triangular section, set with their apexes in the direction of the vessel's travel, so that they

will offer but very little resistance thereto. These bars are connected with a framing adapted to be moved vertically in the guides f' , secured on either side of the bows, in order that the grating may be drawn up out of the way when not required—as, for instance, when the vessel is going astern. The rod f^2 is provided for such raising and lowering purposes and is so arranged that by its means the grating F can readily be dropped into position over the orifice of the conduit C, in order to prevent large fish, floating logs, or other obstacles from being drawn therein.

The conduit B is connected at the stern of the vessel with two other shorter conduits G G, Figs. 2 and 8, which pass out at said stern on either side of the main conduit B, and are each provided with a suitable valve, such as $g g$, either of which may be opened as a passage for the outrushing water at the same time that the main conduit B is closed or partially so. These two valves $g g$ are preferably connected with some gearing or apparatus whereby they may be worked in unison—that is, they may be so arranged that when one of them is open, whether partially or entirely so, the other will be completely shut—thus enabling the vessel to be rapidly turned in either direction by simply regulating the flow of water therethrough.

In the vertical arrangement of our pumping apparatus (illustrated in Figs. 1 to 5) the steam-cylinder II is supported above the pump-cylinder I by standards $h h$, and its slide-valve h' is arranged to be operated by a small vertical donkey-engine J, whose slide-valve j is preferably worked by a tappet-lever j' , which is in its turn operated by the forked lever j^2 engaging with a pin j^3 , projecting from the cross-head i , which serves to connect the piston-rod h^2 of the steam-cylinder with the two piston-rods $i' i'$ of the pump-cylinder. By this means we obviate the employment of cranks and the necessity for working engines in pairs or triplets. We employ two piston-rods for the pump-cylinder in place of only one, as is ordinarily the case, in order to insure a steady movement of the pump-piston, and in order to render such piston still more smooth and regular in its operation we prefer to groove the inner walls of the pump-cylinder, as indicated at $i^* i^*$, Fig. 3, and to work the said piston-rods up and down in such grooves, the piston itself being of course constructed to correspond therewith.

In some convenient position—as, for instance, beneath the platform K, supporting the pumping-engines—we provide what will hereinafter be referred to as the “hydraulic chamber.” It is indicated by the letter L and is in communication with both conduits B and C, as well as with both the upper and lower portions of the pump-cylinder I. It may be of any convenient construction and may, for example, be either square, as illustrated in the majority of the figures, or may

be oval, as illustrated in Fig. 14, so as to better allow the flow of water therethrough. The opening l^2 , connecting this chamber L with the lower portion of the pump-cylinder, is provided with an outlet-valve l of any suitable construction, and the lower end of the pipe l' , connecting said chamber with the upper end of said cylinder, is similarly furnished with a corresponding valve l^2 . The ends of the two conduits B and C may the one be opened and the other closed, or both be partially opened by means of the double clack-valve $b c$, which is pivoted between a pair of lugs b' , projecting upwardly from the bottom of the chamber L in such a manner that said valve may be partially rotated upon its pivot, so as to throw it over from one side to the other in order to close one conduit and open the other, or (under some circumstances) to partially open both of these valves. This latter provision is made for the purpose of enabling the engines to be tested, so as to ascertain whether they are in proper working order before starting the vessel upon her voyage—that is, while she is stationary—as, for instance, when moored alongside a pier.

In any convenient position alongside the pump-cylinder I we arrange a condensing and receiving-chamber M, which is in communication with both the upper and lower ends of the pump-cylinder I through the two tubes v^2 and v^3 , whose ends are closed by inlet-valves v^4 and v^5 within said pump-cylinder. This condensing and receiving chamber M is also in communication with the two conduits B and C through the two branch tubes m and m' , whose ends where they project into the said condensing-chamber are either closed or opened by means of a double clack-valve $m^2 m^3$, which is similar in construction to the valve $b c$ in the hydraulic chamber L. This condensing and receiving chamber is capable of holding sufficient water to fill the pump-cylinder at any time and at any part of the stroke in order that the engines may start work immediately to propel the vessel either backward or forward.

The exhaust-pipe n passes from the exhaust-port of the steam-cylinder II down to the upper portion N of the condensing and receiving chamber. This upper portion is in communication with the lower portion of said chamber by a small snift-valve n' , which prevents the incoming water from rising in the exhaust-tube, while the steam is drawn off at each stroke into the receiving-chamber M and will be condensed in so effective a manner (owing to the immense volume of water passing through) that we shall be enabled to work our cylinders with steam at a very high pressure—in fact, at a pressure which will only be limited by considerations of safety.

An arm o upon a throttle-valve provided in the steam-pipe O is connected by rod o' with a short arm o^2 of the tappet-lever j' , so that said throttle-valve will be caused to work as

an expansion-valve, and will regulate the supply of steam to the cylinder II as its piston approaches either end of its stroke.

The two double clack-valves $b\ c$ and $m^2\ m^3$ are connected together and operated in unison by a rack m^* , Fig. 7, engaging with the teeth of two pinions m^4 and b^3 , keyed each upon one of the spindles of said valves in such a manner that when the inlet from the forward conduit C into the condensing and receiving chamber M is opened the conduit B will be in open communication with the hydraulic chamber L, and vice versa, as will hereinafter be explained.

Instead of employing clack-valves to close the various conduits, we may employ other suitable valves, such, for instance, as that illustrated in Fig. 14, which consists of a pair of stop-valves, connected the one to the other and operated by means of a pinion gearing with a rack formed upon the under side of their connecting-piece.

The horizontal arrangement of our pump-engine, illustrated in Fig. 6, is similar as regards the construction and operation of the various parts to the vertical type hereinbefore described. It will therefore, with the aid of the drawings, be readily understood from the description of the said vertical arrangement.

We provide against fire by connecting small pipes P, Fig. 1, to the conduits B and C, leading them into different parts of the vessel and providing them with rose or other jets p and with stop-cocks p' , whereby water may be pumped into the hold or wherever else the fire may have started.

The operation of our invention is as follows: If it be desired to drive the vessel ahead, the valves c and m^2 are closed and the valves b and m^3 are opened to passage of the water, which will be drawn through the conduit C into the condensing and receiving chamber M, and will from thence pass into either the upper or the lower part of the pump-cylinder I, according to whether the pump-piston is traveling up or down, and will finally be forced into the hydraulic chamber L, and from thence out through the conical discharge-conduit B at the stern of the vessel. This operation will be clearly understood by reference to Figs. 12 and 13, wherein the path of the water is clearly indicated by arrows in both the up and down stroke of the pump-piston, respectively. When it is required to reverse the motion of the vessel, it is only necessary to alter the positions of the two double clack-valves $b\ c$ and $m^2\ m^3$, so that the water will be drawn in through the conduit B and expelled through conduit C, thus reversing the travel of the vessel without stopping the engines for a single revolution. It will be readily understood that these facilities for reversal will be of very great practical utility in stopping the vessel quickly in the case of a collision or when some other similar danger appears to be imminent.

Having now particularly described and as-

certained the nature of our said invention and in what manner the same is to be performed, we declare that what we claim is—

1. In the propulsion of vessels by hydraulic power, the combination of a suction and force pipe having its inlet and outlet at the bow and stern, respectively, in substantially the same horizontal plane, a pump-cylinder and piston, a receiving-chamber and a delivery-chamber, connections provided with suitable check-valves between said chambers and the opposite ends of the pump-cylinder, and a valve mechanism in each of said chambers adapted to reverse the flow of water through said devices, for the purpose set forth.

2. In the propulsion of vessels by hydraulic power, a suction and force pipe having its inlets and outlets at the bow and stern, respectively, in substantially the same horizontal plane, the forcing end of said pipe being provided with a valved port opening into the hold of the vessel, in combination with a suction and force pump interposed in said pipe between the suction end thereof and said valved port, receiving and delivery chambers, both in communication with the suction and force pipe, connections provided with suitable check-valves between the chambers and both ends of the pump-cylinder, and a valve mechanism in each of said chambers adapted to reverse the flow of water through said devices, for the purpose set forth.

3. In the propulsion of vessels by hydraulic power, a suction and force pipe having its inlets and outlets at the bow and stern, respectively, in substantially the same horizontal plane, the forcing end of said pipe being provided with a valved port opening into the hold of the vessel, a stand-pipe connected with the suction and force pipe forward of said valved port, said pipe having valved branches provided with jet-nozzles extending to the various compartments of the vessel, in combination with a pump interposed in the suction and force pipe forward of the stand-pipe, receiving and delivery chambers both in communication with the suction and force pipe, and with both ends of the pump-cylinder, and a valve mechanism adapted to reverse the flow of water through the suction and force pipe, for the purpose set forth.

4. In the propulsion of vessels by hydraulic power, the combination of a suction and force pipe, a pump-cylinder interposed therein, receiving and delivery chambers in communication with the suction and force pipe, connections provided with suitable check-valves between said chambers and both ends of the pump-cylinder, a valve mechanism in each of said chambers operating to reverse the flow of water through said devices, a connection between said valve mechanisms, and a single operating-lever adapted to operate both valve mechanisms through the medium of said connection, for the purpose set forth.

5. In the propulsion of vessels by hydraulic power, the combination, with the receiving and

delivery chambers L and M for the pump, and the branched suction and force pipe entering both chambers at opposite ends, of a slide-valve in each of said chambers having a reciprocating motion in the plane of the oppositely-entering pipes and adapted to sever communication therewith, a shaft carrying cams in engagement with the slide-valves, and an operating-lever on said shaft, for the purpose set forth.

6. The combination, with a vessel having an opening in its bow, the receiving-chamber of the pump, and the suction-pipe, respectively connected with said receiving-chamber and the bow-opening of the vessel, of a grating arranged to cover said opening at the outside, said grating being composed of grate-bars of prismatic form in cross-section arranged with their apices in the direction of travel of the vessel, for the purpose set forth.

7. The combination, with a vessel having an opening in the bow, the receiving-chamber of the pump, and the suction-pipe, respectively connected with said chamber and opening, of a vertically-movable grate arranged to cover said opening on the outside, said grate having substantially the form of a basket composed of grate-bars of prismatic form in cross-section arranged with their apices in the direction of travel of the vessel, for the purpose set forth.

8. As a means for propelling vessels, a suction and force pump, a water-chamber in communication with the opposite ends of the pump-cylinder through the medium of valved communications, a suction-pipe having its inlet at the bows and its outlet within the water-chamber, a forcing-pipe having its outlet at the stern and its inlet also within the water-chamber, and a double valve interposed between the outlet of the suction-pipe and the inlet of the forcing-pipe and adapted to co-operate therewith and direct and control the flow of water therethrough, substantially as and for the purposes specified.

9. As a means for propelling vessels, a suction and force pump, a water-chamber in communication with the opposite ends of the pump-cylinder through the medium of valved communications, a suction-pipe having its

inlet at the bows and its outlet within the water-chamber, a forcing-pipe having its outlet at the stern and its inlet also within the water-chamber, and a double valve interposed between the outlet of the suction-pipe and the inlet of the forcing-pipe and adapted to co-operate therewith and direct and control the flow of water therethrough, an auxiliary water-chamber, valved connections between the same and the opposite ends of the pump-cylinder, the branches m' and m , connecting said auxiliary water-chamber with the suction and forcing pipes, respectively, and a double valve $m^3 m^2$, arranged within the auxiliary water-chamber and adapted to co-operate with said branches m' and m , to direct and control the flow of water therethrough, substantially as and for the purposes specified.

10. As a means for propelling vessels, a suction and force pump, a water-chamber in communication with the opposite ends of the pump-cylinder through the medium of valved connections, a suction-pipe having its inlet at the bows and its outlet within the water-chamber, a forcing-pipe provided with a valved port opening into the hold of the vessel, said pipe having its outlet at the stern and its inlet also within the water-chamber, and a double valve interposed between the outlet of the suction-pipe and the inlet of the forcing-pipe and adapted to co-operate therewith and direct and control the flow of water therethrough, an auxiliary water-chamber, valved connections between the same and the opposite ends of the pump-cylinder, the branches m' and m , connecting said auxiliary water-chamber with the suction and forcing pipes, respectively, and a double valve $m^3 m^2$, arranged within the auxiliary water-chamber and adapted to co-operate with said branches m' and m , to direct and control the flow of water therethrough, substantially as and for the purposes specified.

JOHN CHARLES BOWRING.
ALFRED NEWCOMB.

Witnesses:

WALTER SMYTHE BAYSTON,
WILLIAM GUEST HOLDEN.