



US 20210361284A1

(19) **United States**(12) **Patent Application Publication**
Shelton, IV et al.(10) **Pub. No.: US 2021/0361284 A1**(43) **Pub. Date: Nov. 25, 2021**(54) **SURGICAL END EFFECTORS WITH FIRING MEMBER AND CLOSURE LOCKING FEATURES**(71) Applicant: **Cilag GmbH International**, Zug (CH)(72) Inventors: **Frederick E. Shelton, IV**, Hillsboro, OH (US); **Jason L. Harris**, Lebanon, OH (US); **Gregory J. Bakos**, Mason, OH (US)(21) Appl. No.: **17/362,326**(22) Filed: **Jun. 29, 2021****Related U.S. Application Data**

(63) Continuation of application No. 16/281,675, filed on Feb. 21, 2019, now Pat. No. 11,129,611.

(60) Provisional application No. 62/807,310, filed on Feb. 19, 2019, provisional application No. 62/807,319, filed on Feb. 19, 2019, provisional application No. 62/807,309, filed on Feb. 19, 2019, provisional application No. 62/650,887, filed on Mar. 30, 2018, provisional application No. 62/649,302, filed on Mar. 28, 2018, provisional application No. 62/649,294, filed on Mar. 28, 2018, provisional application No. 62/649,300, filed on Mar. 28, 2018, provisional application No. 62/649,309, filed on Mar. 28, 2018, provisional application No. 62/649,310, filed on Mar. 28, 2018, provisional application No. 62/649,291, filed on Mar. 28, 2018, provisional application No. 62/649,296, filed on Mar. 28, 2018, provisional application No. 62/649,333, filed on Mar. 28, 2018, provisional application No. 62/649,327, filed on Mar. 28, 2018, provisional application No. 62/649,315,


filed on Mar. 28, 2018, provisional application No. 62/649,313, filed on Mar. 28, 2018, provisional application No. 62/649,320, filed on Mar. 28, 2018, provisional application No. 62/649,307, filed on Mar. 28, 2018, provisional application No. 62/649,323, filed on Mar. 28, 2018.

Publication Classification(51) **Int. Cl.****A61B 17/068** (2006.01)**A61B 17/072** (2006.01)**A61B 17/29** (2006.01)**A61B 17/34** (2006.01)**A61B 90/00** (2006.01)**A61F 2/82** (2006.01)(52) **U.S. Cl.**CPC **A61B 17/0682** (2013.01); **A61B 17/072** (2013.01); **A61B 17/07207** (2013.01); **A61B 34/30** (2016.02); **A61B 17/34** (2013.01); **A61B 90/39** (2016.02); **A61F 2/82** (2013.01); **A61B 17/29** (2013.01)

(57)

ABSTRACT

A surgical stapling instrument including a first jaw configured to removably support a surgical staple cartridge therein and a second jaw movable relative to the first jaw between an open position and a closed position. A firing member is configured to axially move between a starting and ending position upon application of a firing motion thereto. A firing member lockout interfaces with a camming assembly in the surgical staple cartridge to lockout the firing member unless the camming assembly is in an unfired position. A cartridge verification member is configured to move the camming assembly out of the unfired position to an intermediate position unless the cartridge verification member detects a verification feature on the surgical staple cartridge.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6








FIG. 8



၈၆



0101






FIG. 11






FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20



12345




FIG. 23





FIG. 24



ELIG 25




FIG. 27

FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 36




FIG. 33




FIG. 34







FIG. 37



38






FIG. 42

FIG. 41




FIG. 49




FIG. 43




FIG. 44

FIG. 50




FIG. 45






FIG. 47








FIG. 51






FIG. 53




FIG. 54

FIG. 58




FIG. 55




FIG. 56




FIG. 59




FIG. 60




FIG. 61

FIG. 62




FIG. 63




FIG. 64




FIG. 65





FIG. 66






FIG. 68




FIG. 69




FIG. 70




FIG. 71




Fig. 72




FIG. 73




FIG. 74





FIG. 75






FIG. 77




FIG. 78




FIG. 79






FIG. 80






FIG. 83




FIG. 84




FIG. 85













FIG. 86










၇၆၂








FIG. 98




FIG. 99




FIG. 100




FIG. 101




FIG. 103







FIG. 104








FIG. 108






FIG. 109



0
1
1
G.
E







FIG. 113

FIG. 112






FIG. 115




FIG. 116




FIG. 118




FIG. 117




FIG. 119




FIG. 120




FIG. 121




FIG. 122




FIG. 123




Figure 24




FIG. 125




FIG. 126

FIG. 127




FIG. 128






FIG. 129






FIG. 132




FIG. 133




FIG. 134




FIG. 135




FIG. 136




FIG. 137




FIG. 138




FIG. 139




FIG. 140




FIG. 141




FIG. 144




FIG. 145




FIG. 146






FIG. 148

FIG. 147






FIG. 151




FIG. 152




FIG. 153




FIG. 154




FIG. 155




FIG. 155A




FIG. 155B




FIG. 155C




FIG. 155D








FIG. 155E










FIG. 160




FIG. 161




FIG. 162




FIG. 163




FIG. 164




FIG. 165






FIG. 166

FIG. 167








Fig. 17




FIG. 172






FIG. 173






FIG. 176




FIG. 177





FIG. 178






FIG. 180

FIG. 181

SURGICAL END EFFECTORS WITH FIRING MEMBER AND CLOSURE LOCKING FEATURES

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority under 35 U.S.C. § 120 to U.S. patent application Ser. No. 16/281,675, entitled SURGICAL STAPLERS WITH ARRANGEMENTS FOR MAINTAINING A FIRING MEMBER THEREOF IN A LOCKED CONFIGURATION UNLESS A COMPATIBLE CARTRIDGE HAS BEEN INSTALLED THEREIN, filed Feb. 21, 2019, now U.S. Patent Application Publication No. 2019/0298354, the disclosure of which is herein incorporated by reference in its entirety.

[0002] U.S. patent application Ser. No. 16/281,675 claims the benefit of U.S. Provisional Patent Application Ser. No. 62/807,310, entitled METHODS FOR CONTROLLING A POWERED SURGICAL STAPLER THAT HAS SEPARATE ROTARY CLOSURE AND FIRING SYSTEMS, filed Feb. 19, 2019, of U.S. Provisional Patent Application Ser. No. 62/807,319, entitled SURGICAL STAPLING DEVICES WITH IMPROVED LOCKOUT SYSTEMS, filed Feb. 19, 2019, and of U.S. Provisional Patent Application Ser. No. 62/807,309, entitled SURGICAL STAPLING DEVICES WITH IMPROVED ROTARY DRIVEN CLOSURE SYSTEMS, filed Feb. 19, 2019, the disclosures of which are incorporated by reference herein in their entireties. U.S. patent application Ser. No. 16/281,675 claims the benefit of U.S. Provisional Patent Application Ser. No. 62/650,887, entitled SURGICAL SYSTEMS WITH OPTIMIZED SENSING CAPABILITIES, filed Mar. 30, 2018, the disclosure of which is incorporated by reference herein in its entirety. U.S. patent application Ser. No. 16/281,675 claims the benefit of U.S. Provisional Patent Application Ser. No. 62/649,302, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,294, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,300, entitled SURGICAL HUB SITUATIONAL AWARENESS, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,309, entitled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,310, entitled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,291, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,296, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,333, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,327, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEAS-

SURES, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,315, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,313, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,320, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, filed Mar. 28, 2018, of U.S. Provisional Patent Application Ser. No. 62/649,307, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, filed Mar. 28, 2018, and of U.S. Provisional Patent Application Ser. No. 62/649,323, entitled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, filed Mar. 28, 2018, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

[0003] The present invention relates to surgical instruments and, in various arrangements, to surgical stapling and cutting instruments and staple cartridges for use therewith that are designed to staple and cut tissue.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] Various features of the embodiments described herein, together with advantages thereof, may be understood in accordance with the following description taken in conjunction with the accompanying drawings as follows:

[0005] FIG. 1 is a perspective view of a powered surgical stapling system;

[0006] FIG. 2 is a perspective view of an interchangeable surgical shaft assembly of the powered surgical stapling system of FIG. 1;

[0007] FIG. 3 is an exploded assembly view of portions of a handle assembly of the powered surgical stapling system of FIG. 1;

[0008] FIG. 4 is an exploded assembly view of the interchangeable surgical shaft assembly of FIG. 2;

[0009] FIG. 5 is another partial exploded assembly view of a portion of the interchangeable surgical shaft assembly of FIG. 4;

[0010] FIG. 6 is a perspective view of another powered surgical stapling system;

[0011] FIG. 7 is an exploded assembly view of portion of a shaft assembly of the powered surgical stapling system of FIG. 6;

[0012] FIG. 8 is an exploded assembly view of portions of a handle assembly of the powered surgical stapling system of FIG. 6;

[0013] FIG. 9 is a side elevational view of another surgical end effector that may be employed with a rotary powered surgical stapling system;

[0014] FIG. 10 is an exploded assembly view of the surgical end effector of FIG. 9;

[0015] FIG. 11 is an exploded assembly view of a rotary powered firing member that may be employed with the surgical end effector of FIGS. 9 and 10;

[0016] FIG. 12 is a partial cross-sectional view of the surgical end effector of FIG. 9 illustrating initial insertion of a fresh, unfired surgical staple cartridge therein;

[0017] FIG. 13 is another partial cross-sectional view of the surgical end effector of FIG. 12, after the surgical staple cartridge has been operably installed therein;

[0018] FIG. 14 is an enlarged partial cross-sectional view illustrating a firing member and a camming assembly of the end effector of FIG. 13;

[0019] FIG. 15 is another partial cross-sectional view of the surgical end effector of FIG. 9, prior to insertion of a fresh surgical staple cartridge therein and with a firing member lockout assembly thereof in a locked position;

[0020] FIG. 16 is an enlarged partial cross-sectional view illustrating a firing member and lockout lugs of the end effector of FIG. 15, with a camming assembly and end effector channel omitted for clarity;

[0021] FIG. 17 is a side elevational view of another surgical end effector with an anvil thereof in an open position;

[0022] FIG. 18 is a partial bottom perspective view of the surgical end effector of FIG. 17;

[0023] FIG. 19 is a perspective view of a channel mount feature and anvil lockout spring of the surgical end effector of FIG. 17;

[0024] FIG. 20 is a partial bottom perspective view of the surgical end effector of FIG. 17 without a surgical staple cartridge installed therein and the anvil thereof in a locked position;

[0025] FIG. 21 is another partial bottom perspective view of the surgical end effector of FIG. 20 after a compatible surgical staple cartridge has been installed therein and the anvil lockout spring moved to an unlocked position;

[0026] FIG. 22 is a perspective view of a proximal end portion of the surgical staple cartridge depicted in FIG. 21;

[0027] FIG. 23 is a partial exploded assembly view of a surgical staple cartridge and a corresponding anvil and anvil lockout system of a surgical end effector;

[0028] FIG. 24 is a partial exploded assembly view of a surgical staple cartridge and a corresponding anvil and anvil lockout system of another surgical end effector;

[0029] FIG. 25 is a partial bottom view of a channel of another end effector with a compatible surgical staple cartridge loaded therein with portions of the compatible surgical staple cartridge omitted for clarity;

[0030] FIG. 26 is a side elevational view of a portion of the surgical end effector of FIG. 25, with portions of a channel, anvil and cartridge omitted for clarity;

[0031] FIG. 27 is a partial cross-sectional end view of the surgical end effector of FIGS. 25 and 26 with the anvil shown in a closed position on a compatible surgical staple cartridge;

[0032] FIG. 28 is another partial cross-sectional end view of the surgical end effector of FIGS. 25 and 26 with the anvil thereof shown in a locked open position;

[0033] FIG. 29 is a side elevational of an anvil lock of the surgical end effector of FIGS. 25 and 26 shown in a locked configuration and an unlocked configuration (in phantom lines);

[0034] FIG. 30 is a side elevational view of a portion of another surgical end effector, with portions of a channel, anvil and cartridge omitted for clarity;

[0035] FIG. 31 is a front elevational view of an anvil lock of the surgical end effector of FIG. 30;

[0036] FIG. 32 is a top view of the anvil lock of FIG. 31;

[0037] FIG. 33 is a cross-sectional side view of another surgical end effector with an anvil thereof in an open position and with a compatible surgical staple cartridge installed therein;

[0038] FIG. 34 is a partial perspective view of a proximal end of a compatible surgical staple cartridge of FIG. 33 in relation to a portion of an anvil lock feature of the surgical end effector of FIG. 33;

[0039] FIG. 35 is a top view of a portion of a channel of the surgical end effector of FIG. 33 and an outline of a compatible surgical staple cartridge of FIG. 33 being inserted therein;

[0040] FIG. 36 is another cross-sectional side view of the surgical end effector of FIG. 33, with the anvil thereof in an open position during initial installation of an incompatible surgical staple cartridge therein;

[0041] FIG. 37 is a cross-sectional side view of another surgical end effector with an anvil thereof in an open position during installation of a compatible surgical staple cartridge therein;

[0042] FIG. 38 is a cross-sectional side view of portions of another surgical end effector with an anvil thereof in an open position during installation of a compatible surgical staple cartridge therein;

[0043] FIG. 39 is a cross-sectional side view of portions of another surgical end effector with an anvil thereof in an open position during installation of a compatible surgical staple cartridge therein;

[0044] FIG. 40 is a cross-sectional side view of the end effector of FIG. 39 during installation of an incompatible cartridge therein;

[0045] FIG. 41 is a partial perspective view of a proximal end portion of an anvil;

[0046] FIG. 42 is a partial perspective view of a proximal end portion of another anvil;

[0047] FIG. 43 is a partial cross-sectional end view of portions of another surgical end effector;

[0048] FIG. 44 is a partial perspective view of a proximal end portion of the anvil of the surgical end effector of FIG. 43;

[0049] FIG. 45 is a partial cross-sectional perspective view of a portion of a channel and anvil lock of the surgical end effector of FIG. 43, with the anvil lock in a locked position;

[0050] FIG. 46 is a partial side elevational view of the surgical end effector of FIG. 43 with the anvil in an open position and the anvil lock thereof shown in a locked position in phantom lines;

[0051] FIG. 47 is another partial cross-sectional perspective view of a portion of the channel and anvil lock of the surgical end effector of FIG. 43, with the anvil lock in an unlocked position;

[0052] FIG. 48 is another partial side elevational view of the surgical end effector of FIG. 43 with the anvil in a closed position and the anvil lock thereof shown in the unlocked position in phantom lines;

[0053] FIG. 49 is a partial cross-sectional end view of portions of another surgical end effector;

[0054] FIG. 50 is a partial perspective view of a proximal end portion of the anvil of the surgical end effector of FIG. 49;

[0055] FIG. 51 is a partial cross-sectional side view of a portion of a channel and anvil lock of the surgical end effector of FIG. 49, with the anvil lock in a locked position;

[0056] FIG. 52 is a partial side elevational view of another surgical end effector with an anvil thereof in an open position and an anvil lock thereof shown in a locked position in phantom lines;

[0057] FIG. 53 is a side elevational view of a portion of the anvil of the surgical end effector of FIG. 52;

[0058] FIG. 54 is a partial perspective view of a portion of the anvil of FIG. 53;

[0059] FIG. 55 is a partial cross-sectional perspective view of a portion of a channel and anvil lock of the surgical end effector of FIG. 52 with the anvil lock in a locked position;

[0060] FIG. 56 is another partial cross-sectional perspective view of a portion of the channel and anvil lock of the surgical end effector of FIG. 52, with the anvil lock in an unlocked position;

[0061] FIG. 57 is a partial side elevational view of the surgical end effector of FIG. 52 with the anvil in a closed position and the anvil lock thereof shown in the unlocked position in phantom lines;

[0062] FIG. 58 is a partial perspective view of another anvil;

[0063] FIG. 59 is a partial cross-sectional perspective view of a portion of another channel that may be used in connection with the anvil of FIG. 58;

[0064] FIG. 60 is a side elevational view of a portion of another anvil;

[0065] FIG. 61 is a perspective view of a portion of the anvil of FIG. 60;

[0066] FIG. 62 is a perspective view of a portion of another anvil;

[0067] FIG. 63 is a side elevational view of another surgical end effector with an anvil thereof in an open position prior to installation of a surgical staple cartridge therein;

[0068] FIG. 64 is another side elevational view of the surgical end effector of FIG. 63 after a compatible surgical staple cartridge has been installed therein;

[0069] FIG. 65 is an end elevational view of an surgical end effector closure tube of the surgical end effector of FIG. 63 and with a closure lock thereof in a locked position;

[0070] FIG. 66 is another end elevational view of the surgical end effector closure tube and closure lock of FIG. 65, with the closure lock shown in an unlocked position;

[0071] FIG. 67 is a partial perspective view of a portion of a compatible surgical staple cartridge and the closure lock of the surgical end effector of FIG. 63;

[0072] FIG. 68 is a partial side elevational view of the surgical end effector of FIG. 63 with the anvil thereof in an open position and prior to installation of a surgical staple cartridge therein;

[0073] FIG. 69 is another partial side elevational view of the surgical end effector of FIG. 68 with the anvil thereof in an open position and during installation of a compatible surgical staple cartridge therein;

[0074] FIG. 70 is a partial side elevational view of the surgical end effector of FIG. 68 with the anvil thereof in an open position and during initial installation of a compatible surgical staple cartridge therein;

[0075] FIG. 71 is another partial side elevational view of the surgical end effector of FIG. 70 with the anvil thereof in an open position and after the compatible surgical staple cartridge has been operably seated therein;

[0076] FIG. 72 is a partial cross-sectional perspective view of a portion of the compatible surgical staple cartridge shown in FIGS. 70 and 71;

[0077] FIG. 73 is another partial side elevational view of the surgical end effector of FIG. 70 with the anvil thereof in an open position and during installation thereof of a surgical staple cartridge lacking a compatible camming assembly in a starting position;

[0078] FIG. 74 is a partial side elevational view of another surgical end effector with an anvil thereof in an open position and during initial installation of a compatible surgical staple cartridge therein;

[0079] FIG. 75 is another partial side elevational view of the surgical end effector of FIG. 74 with the anvil thereof in an open position and after the compatible surgical staple cartridge has been operably seated therein;

[0080] FIG. 76 is a perspective view of an anvil lock and channel mounting feature of the surgical end effector of FIGS. 74 and 75;

[0081] FIG. 77 is a perspective view of a portion of a surgical staple cartridge that is compatible with the surgical end effector of FIGS. 74 and 75;

[0082] FIG. 78 is another partial side elevational view of the surgical end effector of FIG. 74 with the anvil thereof in an open position and after an incompatible surgical staple cartridge has been seated therein;

[0083] FIG. 79 is a side elevational view of another surgical end effector with a compatible surgical staple cartridge loaded therein and an anvil thereof in an open position;

[0084] FIG. 80 is a top view of a portion of a surgical staple cartridge that is compatible with the surgical end effector of FIG. 79 with portions thereof omitted for clarity;

[0085] FIG. 81 is a partial cross-sectional side view of a portion of the surgical staple cartridge of FIG. 80 installed in the surgical end effector of FIG. 79 taken along line 81-81 in FIG. 80 showing the cartridge nose assembly in a locked position;

[0086] FIG. 82 is another partial cross-sectional side view of a portion of the surgical staple cartridge of FIG. 80 installed in the surgical end effector of FIG. 79 taken along line 82-82 in FIG. 80 showing the cartridge nose assembly in an unlocked position;

[0087] FIG. 83 is another partial cross-sectional side view of a portion of the surgical staple cartridge of FIG. 80 installed in the surgical end effector of FIG. 79 taken along line 83-83 in FIG. 80 showing the cartridge nose assembly in a locked position;

[0088] FIG. 84 is another partial cross-sectional side view of a portion of the surgical staple cartridge of FIG. 80 installed in the surgical end effector of FIG. 79 taken along line 84-84 in FIG. 80 showing the cartridge nose assembly in an unlocked position;

[0089] FIG. 85 is a partial cross-sectional view of a portion of a firing member and camming assembly of a surgical staple cartridge wherein the camming assembly is in a starting position and in unlocking engagement with a firing member lock on a firing member;

[0090] FIG. 86 is another partial cross-sectional view of a portion of a firing member of FIG. 85, with the firing member lock in a locked position;

[0091] FIG. 87 is a side elevational view of a portion of an anvil of another surgical end effector with the anvil in an

open position in relation to compatible surgical staple cartridge installed within a corresponding channel that has been omitted for clarity;

[0092] FIG. 88 is another side elevational view of the anvil and surgical staple cartridge of FIG. 87 during initial closure of the anvil;

[0093] FIG. 89 is another side elevational view of the anvil and surgical staple cartridge of FIG. 87 after the anvil has been moved to a closed position;

[0094] FIG. 90 is a perspective view of a portion of the compatible surgical staple cartridge depicted in FIGS. 87-89;

[0095] FIG. 91 is a partial bottom view of the anvil of FIGS. 87-89;

[0096] FIG. 92 is a perspective view of a portion of surgical staple cartridge that is incompatible with the anvil of FIGS. 87-89;

[0097] FIG. 93 is a side elevational view of the anvil of FIGS. 87-89 in an open position in relation to an incompatible surgical staple cartridge of FIG. 92 installed within a corresponding channel that has been omitted for clarity;

[0098] FIG. 94 is another side elevational view of the anvil and surgical staple cartridge of FIG. 93 during initial closure of the anvil;

[0099] FIG. 95 is another side elevational view of the anvil and surgical staple cartridge of FIG. 93 after the anvil has been moved to a closed position;

[0100] FIG. 96 is a partial cross-sectional side view of a portion of another surgical end effector with a compatible surgical staple cartridge loaded therein and an anvil thereof omitted for clarity;

[0101] FIG. 97 is a top view of a portion of the surgical staple cartridge and surgical end effector of FIG. 96;

[0102] FIG. 98 is a perspective view of a portion of proximal end of a compatible surgical staple cartridge depicted in FIG. 97;

[0103] FIG. 99 is another partial cross-sectional side view of a portion of the surgical end effector of FIG. 96 illustrating the installation of a compatible surgical staple cartridge therein;

[0104] FIG. 100 is another partial cross-sectional side view of a portion of the surgical end effector of FIG. 96 illustrating the installation of a compatible surgical staple cartridge therein;

[0105] FIG. 101 is a top view of the surgical end effector and compatible surgical staple cartridge of FIG. 98;

[0106] FIG. 102 is another partial cross-sectional side view of a portion of the surgical end effector of FIG. 96 illustrating the installation of an incompatible surgical staple cartridge therein;

[0107] FIG. 103 is another partial cross-sectional side view of a portion of the surgical end effector of FIG. 96 illustrating the installation of an incompatible surgical staple cartridge therein;

[0108] FIG. 104 is a top view of the surgical end effector and incompatible surgical staple cartridge of FIG. 103;

[0109] FIG. 105 is another partial cross-sectional side view of a portion of the surgical end effector of FIG. 96 illustrating the installation of an incompatible surgical staple cartridge therein;

[0110] FIG. 106 is a top view of the surgical end effector and incompatible surgical staple cartridge of FIG. 105;

[0111] FIG. 107 is a partial cross-sectional perspective view of portions of another surgical end effector with an incompatible surgical staple cartridge installed therein;

[0112] FIG. 108 is a partial top view of portions of the surgical end effector an incompatible surgical staple cartridge of FIG. 107;

[0113] FIG. 109 is another partial top view of the surgical end effector of FIG. 105, with a compatible surgical staple cartridge installed therein;

[0114] FIG. 110 is a partial cross-sectional perspective view of portions of another surgical end effector with a compatible surgical staple cartridge installed therein;

[0115] FIG. 111 is a partial exploded assembly view of portions of the surgical end effector of FIG. 110;

[0116] FIG. 112 is a partial cross-sectional end view of the surgical end effector and compatible surgical staple cartridge of FIG. 110;

[0117] FIG. 113 is another partial cross-sectional surgical end view of the end effector of FIG. 110 with an incompatible surgical staple cartridge installed therein;

[0118] FIG. 114 is another partial cross-sectional perspective view of portions of the surgical end effector of FIG. 110 with an incompatible surgical staple cartridge installed therein;

[0119] FIG. 115 is a top view of the surgical end effector and surgical staple cartridge of FIG. 114;

[0120] FIG. 116 is a top view of a portion of another surgical staple cartridge;

[0121] FIG. 117 is a partial cross-sectional perspective view of a portion of the surgical staple cartridge of FIG. 116 with a camming assembly thereof in a locked position;

[0122] FIG. 118 is another top view of the surgical staple cartridge of FIG. 116 interacting with a compatible actuator portion of a surgical end effector;

[0123] FIG. 119 is another partial cross-sectional perspective view of a portion of the surgical staple cartridge of FIG. 116 with the camming assembly thereof in an unlocked position;

[0124] FIG. 120 is a partial elevational view of a stapling instrument including a cartridge channel, a staple cartridge positioned in the cartridge channel, and a firing member in accordance with at least one embodiment illustrated with some components removed, wherein the firing member is in an unfired position;

[0125] FIG. 121 is a partial elevational view of the stapling instrument of FIG. 120 illustrating the firing member in a locked-out position;

[0126] FIG. 122 is a partial elevational view of a stapling instrument including a cartridge channel, a staple cartridge positioned in the cartridge channel, and a firing member in accordance with at least one embodiment illustrated with some components removed, wherein the firing member is in an unfired position;

[0127] FIG. 123 is a partial elevational view of the stapling instrument of FIG. 122 illustrating the firing member in an unlocked position;

[0128] FIG. 124 is a partial elevational view of the stapling instrument of FIG. 122 illustrating the firing member in a locked-out position;

[0129] FIG. 125 is a partial bottom view of the stapling instrument of FIG. 122 illustrating the firing member in an unfired position;

[0130] FIG. 126 is a partial perspective view of the staple cartridge of FIG. 122;

[0131] FIG. 127 is a partial perspective view of a staple cartridge in accordance with at least one embodiment;

[0132] FIG. 128 is a partial elevational view of a stapling instrument including a cartridge channel, a staple cartridge positioned in the cartridge channel, and a firing member in accordance with at least one embodiment illustrated with some components removed, wherein the firing member is in an unfired position;

[0133] FIG. 129 is a partial elevational view of the stapling instrument of FIG. 128 illustrating the firing member in an unlocked position;

[0134] FIG. 130 is a partial top view of the stapling instrument of FIG. 128 illustrated in the unfired position of FIG. 128;

[0135] FIG. 131 is a partial top view of the stapling instrument of FIG. 128 illustrated in the unlocked position of FIG. 129;

[0136] FIG. 132 is a partial perspective view of the staple cartridge of FIG. 128 in an unspent configuration;

[0137] FIG. 133 is a partial perspective view of the staple cartridge of FIG. 128 in a spent configuration;

[0138] FIG. 134 is a partial elevational view of a stapling instrument including a cartridge channel, a staple cartridge positioned in the cartridge channel, and a firing member in accordance with at least one embodiment illustrated with some components removed, wherein the firing member is in an unfired position;

[0139] FIG. 135 is a partial elevational view of the stapling instrument of FIG. 134 illustrating the firing member in a locked-out position;

[0140] FIG. 136 is a partial perspective view of a stapling instrument including a cartridge channel, a staple cartridge positioned in the cartridge channel, a firing member, and a firing member lock in accordance with at least one embodiment illustrated with some components removed, wherein the firing member has been unlocked by the staple cartridge;

[0141] FIG. 137 is a partial elevational view of the stapling instrument of FIG. 136 illustrated with an improper staple cartridge seated in the cartridge channel;

[0142] FIG. 138 is a partial cross-sectional plan view of the stapling instrument of FIG. 136 illustrated with an improper staple cartridge seated in the cartridge channel;

[0143] FIG. 139 is a partial cross-sectional plan view of the stapling instrument of FIG. 136 illustrating the firing member lock unlocked by the staple cartridge;

[0144] FIG. 140 is a partial cross-sectional view of a stapling instrument in accordance with at least one embodiment that has been unlocked by a staple cartridge;

[0145] FIG. 141 is a partial cross-sectional view of a stapling instrument in accordance with at least one embodiment that has been unlocked by a staple cartridge;

[0146] FIG. 142 is a partial perspective view of the staple cartridge of FIG. 140;

[0147] FIG. 143 is a partial perspective view of the staple cartridge of FIG. 141;

[0148] FIG. 144 is a partial cross-sectional perspective view of a staple cartridge pan in accordance with at least one embodiment;

[0149] FIG. 145 is a partial perspective view of a stapling instrument including a cartridge channel, a staple cartridge positioned in the cartridge channel, a firing member, and a firing member lock in accordance with at least one embodiment illustrated with some components removed, wherein the firing member is unlocked by the staple cartridge;

[0150] FIG. 146 is a partial perspective view of the stapling instrument of FIG. 145 illustrating a different staple cartridge positioned in the cartridge channel which does not unlock the firing member;

[0151] FIG. 147 is a partial perspective view of the stapling instrument of FIG. 145 illustrating the firing member in a locked configuration;

[0152] FIG. 148 is a partial perspective view of a stapling instrument configured to be unlocked by the different staple cartridge of FIG. 146;

[0153] FIG. 149 is a perspective view of a staple cartridge which is similar to the staple cartridge of FIG. 146 and configured to unlock the stapling instrument of FIG. 148;

[0154] FIG. 150 is a perspective view of a staple cartridge which is similar to the staple cartridge of FIG. 145 and configured to unlock the stapling instrument of FIG. 145;

[0155] FIG. 151 is a partial exploded view of a stapling instrument comprising a cartridge channel, a staple cartridge positioned in the cartridge channel, a firing member, an anvil, and a dual-purpose firing member/anvil lock in accordance with at least one embodiment illustrated with some components removed, wherein the stapling instrument is illustrated in a locked state;

[0156] FIG. 152 is a partial perspective view of the stapling instrument of FIG. 151 being unlocked by the insertion of the staple cartridge into the cartridge channel;

[0157] FIG. 153 is a partial cross-sectional view of the stapling instrument of FIG. 151 illustrating the stapling instrument in the locked state of FIG. 151;

[0158] FIG. 154 is a partial cross-sectional view of the stapling instrument of FIG. 151 illustrating the stapling instrument in the unlocked state of FIG. 152;

[0159] FIG. 155 is a perspective view of the firing member/anvil lock of FIG. 151;

[0160] FIG. 155A is a partial perspective view of a staple cartridge in accordance with at least one embodiment;

[0161] FIG. 155B is a partial perspective view of a staple cartridge in accordance with at least one embodiment;

[0162] FIG. 155C is a partial perspective view of a staple cartridge in accordance with at least one embodiment;

[0163] FIG. 155D is a partial perspective view of a staple cartridge in accordance with at least one embodiment;

[0164] FIG. 155E is a partial perspective view of a staple cartridge in accordance with at least one embodiment;

[0165] FIG. 156 is a partial cross-sectional view of a surgical stapling assembly comprising an anvil, a staple cartridge, a firing member, and a firing lockout;

[0166] FIG. 157 is a partial cross-sectional view of the firing member and the firing lockout of FIG. 156 illustrated in an unlocked configuration;

[0167] FIG. 158 is a partial cross-sectional view of the firing member and the firing lockout of FIG. 156 illustrated in a locked configuration;

[0168] FIG. 159 is a partial cross-sectional view of the surgical stapling assembly of FIG. 156, wherein the surgical stapling assembly further comprises an exterior access aperture configured to permit a user to artificially move the firing lockout into the unlocked configuration with a separate lockout key;

[0169] FIG. 160 is a perspective view of a lockout member of the firing lockout of FIG. 156;

[0170] FIG. 161 is a partial cross-sectional view of a surgical stapling assembly comprising a lockout and an

exterior access orifice configured to permit a user to artificially move the firing lockout into an unlocked configuration with a separate lockout key;

[0171] FIG. 162 is a bottom plan view of the surgical stapling assembly of FIG. 161;

[0172] FIG. 163 is a partial cross-sectional view of a surgical stapling assembly comprising a firing member, a cartridge channel, a staple cartridge configured to be installed into the cartridge channel, and a lockout, wherein the lockout is illustrated in an unengaged configuration;

[0173] FIG. 164 is a partial cross-sectional view of the surgical stapling assembly of FIG. 163, wherein the lockout is illustrated in an engaged configuration;

[0174] FIG. 165 comprises elevational views of two staple cartridges each comprising a different lockout key;

[0175] FIG. 166 is a graph depicting knife lift timing provided by each lockout key of the staple cartridges of FIG. 165;

[0176] FIG. 167 is a graph depicting knife lift displacement provided by each lockout key of the staple cartridges of FIG. 165;

[0177] FIG. 168 is a perspective view of a first staple cartridge for use with a surgical stapling system, wherein the first staple cartridge comprises a cartridge body, a pan, a sled, and a first lockout key;

[0178] FIG. 169 is a perspective view of a second staple cartridge for use with the surgical stapling system with which the first staple cartridge of FIG. 168 is to be used, wherein the second staple cartridge comprises a cartridge body, a pan, a sled, and a second lockout key;

[0179] FIG. 170 is an elevational view of a surgical stapling assembly comprising a firing member, a first jaw comprising a staple cartridge, a second jaw comprising an anvil movable relative to the first jaw, and a lockout;

[0180] FIG. 171 is a partial perspective view of the surgical stapling assembly of FIG. 170;

[0181] FIG. 172 is a partial elevational view of the surgical stapling assembly of FIG. 170 where the staple cartridge is not installed within the first jaw;

[0182] FIG. 173 is a partial elevational view of the surgical stapling assembly of FIG. 170 where the staple cartridge is installed within the first jaw;

[0183] FIG. 174 is a partial cross-sectional view of the surgical stapling assembly of FIG. 170 where the staple cartridge is installed within the first jaw and the firing member is in an unfired position;

[0184] FIG. 175 is a partial cross-sectional view of the surgical stapling assembly of FIG. 170 where the staple cartridge is installed within the first jaw and the firing member is in a partially fired position;

[0185] FIG. 176 is a partial cross-sectional view of the surgical stapling assembly of FIG. 170 where the staple cartridge is not installed within the first jaw and the firing member is in the unfired position;

[0186] FIG. 177 is a partial cross-sectional view of the surgical stapling assembly of FIG. 170 where the staple cartridge is not installed within the first jaw and the firing member is in a locked position;

[0187] FIG. 178 is a partial elevational view of the surgical stapling assembly of FIG. 170 where the staple cartridge is installed within the first jaw and the firing member is in the partially fired position, wherein some components are illustrated with hidden lines;

[0188] FIG. 179 is a perspective view of the staple cartridge of the surgical stapling assembly of FIG. 170 comprising a lockout key extending from a proximal end thereof;

[0189] FIG. 180 is a partial plan view of the staple cartridge of FIG. 179; and

[0190] FIG. 181 is a partial plan view of a second staple cartridge configured for use with a system including the staple cartridge of FIG. 179, wherein the second staple cartridge comprises a lockout key comprising a different configuration than the lockout key of the staple cartridge of FIG. 179.

[0191] Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate various embodiments of the invention, in one form, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION

[0192] Applicant of the present application owns the following U.S. patent applications that were filed on Feb. 21, 2019 and which are each herein incorporated by reference in their respective entireties:

[0193] U.S. patent application Ser. No. 16/281,658, entitled METHODS FOR CONTROLLING A POWERED SURGICAL STAPLER THAT HAS SEPARATE ROTARY CLOSURE AND FIRING SYSTEMS, now U.S. Patent Application Publication No. 2019/0298350;

[0194] U.S. patent application Ser. No. 16/281,670, entitled STAPLE CARTRIDGE COMPRISING A LOCKOUT KEY CONFIGURED TO LIFT A FIRING MEMBER, now U.S. Patent Application Publication No. 2019/0298340;

[0195] U.S. patent application Ser. No. 16/281,685, entitled SURGICAL INSTRUMENT COMPRISING CO-OPERATING LOCKOUT FEATURES, now U.S. Patent Application Publication No. 2019/0298341;

[0196] U.S. patent application Ser. No. 16/281,693, entitled SURGICAL STAPLING ASSEMBLY COMPRISING A LOCKOUT AND AN EXTERIOR ACCESS ORIFICE TO PERMIT ARTIFICIAL UNLOCKING OF THE LOCKOUT, now U.S. Patent Application Publication No. 2019/0298342;

[0197] U.S. patent application Ser. No. 16/281,704, entitled SURGICAL STAPLING DEVICES WITH FEATURES FOR BLOCKING ADVANCEMENT OF A CAMMING ASSEMBLY OF AN INCOMPATIBLE CARTRIDGE INSTALLED THEREIN, now U.S. Patent Application Publication No. 2019/0298356;

[0198] U.S. patent application Ser. No. 16/281,707, entitled STAPLING INSTRUMENT COMPRISING A DEACTIVATABLE LOCKOUT, now U.S. Patent Application Publication No. 2019/0298347;

[0199] U.S. patent application Ser. No. 16/281,741, entitled SURGICAL INSTRUMENT COMPRISING A JAW CLOSURE LOCKOUT, now U.S. Patent Application Publication No. 2019/0298357;

[0200] U.S. patent application Ser. No. 16/281,762, entitled SURGICAL STAPLING DEVICES WITH CARTRIDGE COMPATIBLE CLOSURE AND FIRING LOCKOUT ARRANGEMENTS, now U.S. Patent Application Publication No. 2019/0298343;

[0201] U.S. patent application Ser. No. 16/281,660, entitled SURGICAL STAPLE CARTRIDGE WITH FIR-

ING MEMBER DRIVEN CAMMING ASSEMBLY THAT HAS AN ONBOARD TISSUE CUTTING FEATURE, now U.S. Pat. No. 10,973,520;

[0202] U.S. patent application Ser. No. 16/281,666 entitled SURGICAL STAPLING DEVICES WITH IMPROVED ROTARY DRIVEN CLOSURE SYSTEMS, now U.S. Patent Application Publication No. 2019/0298352;

[0203] U.S. patent application Ser. No. 16/281,672, entitled SURGICAL STAPLING DEVICES WITH ASYMMETRIC CLOSURE FEATURES, now U.S. Patent Application Publication No. 2019/0298353;

[0204] U.S. patent application Ser. No. 16/281,678, entitled ROTARY DRIVEN FIRING MEMBERS WITH DIFFERENT ANVIL AND CHANNEL ENGAGEMENT FEATURES, now U.S. Patent Application Publication No. 2019/0298355; and

[0205] U.S. patent application Ser. No. 16/281,682, entitled SURGICAL STAPLING DEVICE WITH SEPARATE ROTARY DRIVEN CLOSURE AND FIRING SYSTEMS AND FIRING MEMBER THAT ENGAGES BOTH JAWS WHILE FIRING, now U.S. Patent Application Publication No. 2019/0298346.

[0206] Applicant of the present application owns the following U.S. Provisional patent applications that were filed on Feb. 19, 2019 and which are each herein incorporated by reference in their respective entireties:

[0207] U.S. Provisional Patent Application Ser. No. 62/807,310, entitled METHODS FOR CONTROLLING A POWERED SURGICAL STAPLER THAT HAS SEPARATE ROTARY CLOSURE AND FIRING SYSTEMS;

[0208] U.S. Provisional Patent Application Ser. No. 62/807,319, entitled SURGICAL STAPLING DEVICES WITH IMPROVED LOCKOUT SYSTEMS; and

[0209] U.S. Provisional Patent Application Ser. No. 62/807,309, entitled SURGICAL STAPLING DEVICES WITH IMPROVED ROTARY DRIVEN CLOSURE SYSTEMS.

[0210] Applicant of the present application owns the following U.S. Provisional patent applications, filed on Mar. 28, 2018, each of which is herein incorporated by reference in its entirety:

[0211] U.S. Provisional Patent Application Ser. No. 62/649,302, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;

[0212] U.S. Provisional Patent Application Ser. No. 62/649,294, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD;

[0213] U.S. Provisional Patent Application Ser. No. 62/649,300, entitled SURGICAL HUB SITUATIONAL AWARENESS;

[0214] U.S. Provisional Patent Application Ser. No. 62/649,309, entitled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;

[0215] U.S. Provisional Patent Application Ser. No. 62/649,310, entitled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS;

[0216] U.S. Provisional Patent Application Ser. No. 62/649,291, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;

[0217] U.S. Provisional Patent Application Ser. No. 62/649,296, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;

[0218] U.S. Provisional Patent Application Ser. No. 62/649,333, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;

[0219] U.S. Provisional Patent Application Ser. No. 62/649,327, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES;

[0220] U.S. Provisional Patent Application Ser. No. 62/649,315, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK;

[0221] U.S. Provisional Patent Application Ser. No. 62/649,313, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES;

[0222] U.S. Provisional Patent Application Ser. No. 62/649,320, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

[0223] U.S. Provisional Patent Application Ser. No. 62/649,307, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and

[0224] U.S. Provisional Patent Application Ser. No. 62/649,323, entitled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

[0225] Applicant of the present application owns the following U.S. Provisional patent application, filed on Mar. 30, 2018, which is herein incorporated by reference in its entirety:

[0226] U.S. Provisional Patent Application Ser. No. 62/650,887, entitled SURGICAL SYSTEMS WITH OPTIMIZED SENSING CAPABILITIES.

[0227] Applicant of the present application owns the following U.S. patent application, filed on Dec. 4, 2018, which is herein incorporated by reference in its entirety:

[0228] U.S. patent application Ser. No. 16/209,423, entitled METHOD OF COMPRESSING TISSUE WITHIN A STAPLING DEVICE AND SIMULTANEOUSLY DISPLAYING THE LOCATION OF THE TISSUE WITHIN THE JAWS, now U.S. Patent Application Publication No. 2019/0200981.

[0229] Applicant of the present application owns the following U.S. patent applications that were filed on Aug. 20, 2018 and which are each herein incorporated by reference in their respective entireties:

[0230] U.S. patent application Ser. No. 16/105,101, entitled METHOD FOR FABRICATING SURGICAL STAPLER ANVILS, now U.S. Patent Application Publication No. 2020/0054323;

[0231] U.S. patent application Ser. No. 16/105,183, entitled REINFORCED DEFORMABLE ANVIL TIP FOR SURGICAL STAPLER ANVIL, now U.S. Pat. No. 10,912,559;

[0232] U.S. patent application Ser. No. 16/105,150, entitled SURGICAL STAPLER ANVILS WITH STAPLE DIRECTING PROTRUSIONS AND TISSUE STABILITY FEATURES, now U.S. Patent Application Publication No. 2020/0054326;

[0233] U.S. patent application Ser. No. 16/105,098, entitled FABRICATING TECHNIQUES FOR SURGICAL STAPLER ANVILS, now U.S. Patent Application Publication No. 2020/0054322;

[0234] U.S. patent application Ser. No. 16/105,140, entitled SURGICAL STAPLER ANVILS WITH TISSUE STOP FEATURES CONFIGURED TO AVOID TISSUE PINCH, now U.S. Pat. No. 10,779,821;

[0235] U.S. patent application Ser. No. 16/105,081, entitled METHOD FOR OPERATING A POWERED ARTICULATABLE SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0054320;

[0236] U.S. patent application Ser. No. 16/105,094, entitled SURGICAL INSTRUMENTS WITH PROGRESSIVE JAW CLOSURE ARRANGEMENTS, now U.S. Patent Application Publication No. 2020/0054321;

[0237] U.S. patent application Ser. No. 16/105,097, entitled POWERED SURGICAL INSTRUMENTS WITH CLUTCHING ARRANGEMENTS TO CONVERT LINEAR DRIVE MOTIONS TO ROTARY DRIVE MOTIONS, now U.S. Patent Application Publication No. 2020/0054328;

[0238] U.S. patent application Ser. No. 16/105,104, entitled POWERED ARTICULATABLE SURGICAL INSTRUMENTS WITH CLUTCHING AND LOCKING ARRANGEMENTS FOR LINKING AN ARTICULATION DRIVE SYSTEM TO A FIRING DRIVE SYSTEM, now U.S. Pat. No. 10,842,492;

[0239] U.S. patent application Ser. No. 16/105,119, entitled ARTICULATABLE MOTOR POWERED SURGICAL INSTRUMENTS WITH DEDICATED ARTICULATION MOTOR ARRANGEMENTS, now U.S. Patent Application Publication No. 2020/0054330;

[0240] U.S. patent application Ser. No. 16/105,160, entitled SWITCHING ARRANGEMENTS FOR MOTOR POWERED ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,856,870; and

[0241] U.S. Design patent application Ser. No. 29/660,252, entitled SURGICAL INSTRUMENT ANVIL, now U.S. Design Pat. No. D914,878.

[0242] Applicant of the present application owns the following U.S. patent applications and U.S. patents that are each herein incorporated by reference in their respective entireties:

[0243] U.S. patent application Ser. No. 15/386,185, entitled SURGICAL STAPLING INSTRUMENTS AND REPLACEABLE TOOL ASSEMBLIES THEREOF, now U.S. Pat. No. 10,639,035;

[0244] U.S. patent application Ser. No. 15/386,230, entitled ARTICULATABLE SURGICAL STAPLING INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168649;

[0245] U.S. patent application Ser. No. 15/386,221, entitled LOCKOUT ARRANGEMENTS FOR SURGICAL END EFFECTORS, now U.S. Pat. No. 10,835,247;

[0246] U.S. patent application Ser. No. 15/386,209, entitled SURGICAL END EFFECTORS AND FIRING MEMBERS THEREOF, now U.S. Pat. No. 10,588,632;

[0247] U.S. patent application Ser. No. 15/386,198, entitled LOCKOUT ARRANGEMENTS FOR SURGICAL END EFFECTORS AND REPLACEABLE TOOL ASSEMBLIES, now U.S. Pat. No. 10,610,224;

[0248] U.S. patent application Ser. No. 15/386,240, entitled SURGICAL END EFFECTORS AND ADAPT-ABLE FIRING MEMBERS THEREFOR, now U.S. Pat. No. 10,973,516;

[0249] U.S. patent application Ser. No. 15/385,939, entitled STAPLE CARTRIDGES AND ARRANGEMENTS OF STAPLES AND STAPLE CAVITIES THEREIN, now U.S. Pat. No. 10,835,246;

[0250] U.S. patent application Ser. No. 15/385,941, entitled SURGICAL TOOL ASSEMBLIES WITH CLUTCHING ARRANGEMENTS FOR SHIFTING BETWEEN CLOSURE SYSTEMS WITH CLOSURE STROKE REDUCTION FEATURES AND ARTICULATION AND FIRING SYSTEMS, now U.S. Pat. No. 10,736,629;

[0251] U.S. patent application Ser. No. 15/385,943, entitled SURGICAL STAPLING INSTRUMENTS AND STAPLE-FORMING ANVILS, now U.S. Pat. No. 10,667,811;

[0252] U.S. patent application Ser. No. 15/385,950, entitled SURGICAL TOOL ASSEMBLIES WITH CLOSURE STROKE REDUCTION FEATURES, now U.S. Pat. No. 10,588,630;

[0253] U.S. patent application Ser. No. 15/385,945, entitled STAPLE CARTRIDGES AND ARRANGEMENTS OF STAPLES AND STAPLE CAVITIES THEREIN, now U.S. Pat. No. 10,893,864;

[0254] U.S. patent application Ser. No. 15/385,946, entitled SURGICAL STAPLING INSTRUMENTS AND STAPLE-FORMING ANVILS, now U.S. Patent Application Publication No. 2018/0168633;

[0255] U.S. patent application Ser. No. 15/385,951, entitled SURGICAL INSTRUMENTS WITH JAW OPENING FEATURES FOR INCREASING A JAW OPENING DISTANCE, now U.S. Pat. No. 10,568,626;

[0256] U.S. patent application Ser. No. 15/385,953, entitled METHODS OF STAPLING TISSUE, now U.S. Pat. No. 10,675,026;

[0257] U.S. patent application Ser. No. 15/385,954, entitled FIRING MEMBERS WITH NON-PARALLEL JAW ENGAGEMENT FEATURES FOR SURGICAL END EFFECTORS, now U.S. Pat. No. 10,624,635;

[0258] U.S. patent application Ser. No. 15/385,955, entitled SURGICAL END EFFECTORS WITH EXPAND-ABLE TISSUE STOP ARRANGEMENTS, now U.S. Pat. No. 10,813,638;

[0259] U.S. patent application Ser. No. 15/385,948, entitled SURGICAL STAPLING INSTRUMENTS AND STAPLE-FORMING ANVILS, now U.S. Patent Application Publication No. 2018/0168584;

[0260] U.S. patent application Ser. No. 15/385,956, entitled SURGICAL INSTRUMENTS WITH POSITIVE JAW OPENING FEATURES, now U.S. Pat. No. 10,588,631;

[0261] U.S. patent application Ser. No. 15/385,958, entitled SURGICAL INSTRUMENTS WITH LOCKOUT ARRANGEMENTS FOR PREVENTING FIRING SYSTEM ACTUATION UNLESS AN UNSPENT STAPLE CARTRIDGE IS PRESENT, now U.S. Pat. No. 10,639,034;

[0262] U.S. patent application Ser. No. 15/385,947, entitled STAPLE CARTRIDGES AND ARRANGEMENTS OF STAPLES AND STAPLE CAVITIES THEREIN, now U.S. Pat. No. 10,568,625;

[0263] U.S. patent application Ser. No. 15/385,896, entitled METHOD FOR RESETTING A FUSE OF A SURGICAL INSTRUMENT SHAFT, now U.S. Patent Application Publication No. 2018/0168597;

[0264] U.S. patent application Ser. No. 15/385,898, entitled STAPLE-FORMING POCKET ARRANGEMENT TO ACCOMMODATE DIFFERENT TYPES OF STAPLES, now U.S. Pat. No. 10,537,325;

[0265] U.S. patent application Ser. No. 15/385,899, entitled SURGICAL INSTRUMENT COMPRISING IMPROVED JAW CONTROL, now U.S. Pat. No. 10,758,229;

[0266] U.S. patent application Ser. No. 15/385,901, entitled STAPLE CARTRIDGE AND STAPLE CARTRIDGE CHANNEL COMPRISING WINDOWS DEFINED THEREIN, now U.S. Pat. No. 10,667,809;

[0267] U.S. patent application Ser. No. 15/385,902, entitled SURGICAL INSTRUMENT COMPRISING A CUTTING MEMBER, now U.S. Pat. No. 10,888,322;

[0268] U.S. patent application Ser. No. 15/385,904, entitled STAPLE FIRING MEMBER COMPRISING A MISSING CARTRIDGE AND/OR SPENT CARTRIDGE LOCKOUT, now U.S. Pat. No. 10,881,401;

[0269] U.S. patent application Ser. No. 15/385,905, entitled FIRING ASSEMBLY COMPRISING A LOCKOUT, now U.S. Pat. No. 10,695,055;

[0270] U.S. patent application Ser. No. 15/385,907, entitled SURGICAL INSTRUMENT SYSTEM COMPRISING AN END EFFECTOR LOCKOUT AND A FIRING ASSEMBLY LOCKOUT, now U.S. Patent Application Publication No. 2018/0168608;

[0271] U.S. patent application Ser. No. 15/385,908, entitled FIRING ASSEMBLY COMPRISING A FUSE, now U.S. Patent Application Publication No. 2018/0168609;

[0272] U.S. patent application Ser. No. 15/385,909, entitled FIRING ASSEMBLY COMPRISING A MULTIPLE FAILED-STATE FUSE, now U.S. Patent Application Publication No. 2018/0168610;

[0273] U.S. patent application Ser. No. 15/385,920, entitled STAPLE-FORMING POCKET ARRANGEMENTS, now U.S. Pat. No. 10,499,914;

[0274] U.S. patent application Ser. No. 15/385,913, entitled ANVIL ARRANGEMENTS FOR SURGICAL STAPLERS, now U.S. Patent Application Publication No. 2018/0168614;

[0275] U.S. patent application Ser. No. 15/385,914, entitled METHOD OF DEFORMING STAPLES FROM TWO DIFFERENT TYPES OF STAPLE CARTRIDGES WITH THE SAME SURGICAL STAPLING INSTRUMENT, now U.S. Patent Application Publication No. 2018/0168615;

[0276] U.S. patent application Ser. No. 15/385,893, entitled BILATERALLY ASYMMETRIC STAPLE-FORMING POCKET PAIRS, now U.S. Pat. No. 10,682,138;

[0277] U.S. patent application Ser. No. 15/385,929, entitled CLOSURE MEMBERS WITH CAM SURFACE ARRANGEMENTS FOR SURGICAL INSTRUMENTS WITH SEPARATE AND DISTINCT CLOSURE AND FIRING SYSTEMS, now U.S. Pat. No. 10,667,810;

[0278] U.S. patent application Ser. No. 15/385,911, entitled SURGICAL STAPLERS WITH INDEPENDENTLY ACTUATABLE CLOSING AND FIRING SYSTEMS, now U.S. Pat. No. 10,448,950;

[0279] U.S. patent application Ser. No. 15/385,927, entitled SURGICAL STAPLING INSTRUMENTS WITH SMART STAPLE CARTRIDGES, now U.S. Patent Application Publication No. 2018/0168625;

[0280] U.S. patent application Ser. No. 15/385,917, entitled STAPLE CARTRIDGE COMPRISING STAPLES WITH DIFFERENT CLAMPING BREADTHS, now U.S. Pat. No. 10,993,715;

[0281] U.S. patent application Ser. No. 15/385,900, entitled STAPLE-FORMING POCKET ARRANGEMENTS COMPRISING PRIMARY SIDEWALLS AND POCKET SIDEWALLS, now U.S. Pat. No. 10,898,186;

[0282] U.S. patent application Ser. No. 15/385,931, entitled NO-CARTRIDGE AND SPENT CARTRIDGE LOCKOUT ARRANGEMENTS FOR SURGICAL STAPLERS, now U.S. Pat. No. 10,980,536;

[0283] U.S. patent application Ser. No. 15/385,915, entitled FIRING MEMBER PIN ANGLE, now U.S. Pat. No. 10,779,823;

[0284] U.S. patent application Ser. No. 15/385,897, entitled STAPLE-FORMING POCKET ARRANGEMENTS COMPRISING ZONED FORMING SURFACE GROOVES, now U.S. Patent Application Publication No. 2018/0168598;

[0285] U.S. patent application Ser. No. 15/385,922, entitled SURGICAL INSTRUMENT WITH MULTIPLE FAILURE RESPONSE MODES, now U.S. Pat. No. 10,426,471;

[0286] U.S. patent application Ser. No. 15/385,924, entitled SURGICAL INSTRUMENT WITH PRIMARY AND SAFETY PROCESSORS, now U.S. Pat. No. 10,758,230;

[0287] U.S. patent application Ser. No. 15/385,910, entitled ANVIL HAVING A KNIFE SLOT WIDTH, now U.S. Pat. No. 10,485,543;

[0288] U.S. patent application Ser. No. 15/385,903, entitled CLOSURE MEMBER ARRANGEMENTS FOR SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,617,414;

[0289] U.S. patent application Ser. No. 15/385,906, entitled FIRING MEMBER PIN CONFIGURATIONS, now U.S. Pat. No. 10,856,868;

[0290] U.S. patent application Ser. No. 15/386,188, entitled STEPPED STAPLE CARTRIDGE WITH ASYMMETRICAL STAPLES, now U.S. Pat. No. 10,537,324;

[0291] U.S. patent application Ser. No. 15/386,192, entitled STEPPED STAPLE CARTRIDGE WITH TISSUE RETENTION AND GAP SETTING FEATURES, now U.S. Pat. No. 10,687,810;

[0292] U.S. patent application Ser. No. 15/386,206, entitled STAPLE CARTRIDGE WITH DEFORMABLE DRIVER RETENTION FEATURES, now U.S. Pat. No. 10,945,727;

[0293] U.S. patent application Ser. No. 15/386,226, entitled DURABILITY FEATURES FOR END EFFECTORS AND FIRING ASSEMBLIES OF SURGICAL STAPLING INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168648;

[0294] U.S. patent application Ser. No. 15/386,222, entitled SURGICAL STAPLING INSTRUMENTS HAVING END EFFECTORS WITH POSITIVE OPENING FEATURES, now U.S. Patent Application Publication No. 2018/0168647;

[0295] U.S. patent application Ser. No. 15/386,236, entitled CONNECTION PORTIONS FOR DEPOSABLE LOADING UNITS FOR SURGICAL STAPLING INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168650;

[0296] U.S. patent application Ser. No. 15/385,887, entitled METHOD FOR ATTACHING A SHAFT ASSEMBLY TO A SURGICAL INSTRUMENT AND, ALTERNATIVELY, TO A SURGICAL ROBOT, now U.S. Pat. No. 10,835,245;

[0297] U.S. patent application Ser. No. 15/385,889, entitled SHAFT ASSEMBLY COMPRISING A MANUALLY-OPERABLE RETRACTION SYSTEM FOR USE WITH A MOTORIZED SURGICAL INSTRUMENT SYSTEM, now U.S. Patent Application Publication No. 2018/0168590;

[0298] U.S. patent application Ser. No. 15/385,890, entitled SHAFT ASSEMBLY COMPRISING SEPARATELY ACTUATABLE AND RETRACTABLE SYSTEMS, now U.S. Pat. No. 10,675,025;

[0299] U.S. patent application Ser. No. 15/385,891, entitled SHAFT ASSEMBLY COMPRISING A CLUTCH CONFIGURED TO ADAPT THE OUTPUT OF A ROTARY FIRING MEMBER TO TWO DIFFERENT SYSTEMS, now U.S. Patent Application Publication No. 2018/0168592;

[0300] U.S. patent application Ser. No. 15/385,892, entitled SURGICAL SYSTEM COMPRISING A FIRING MEMBER ROTATABLE INTO AN ARTICULATION STATE TO ARTICULATE AN END EFFECTOR OF THE SURGICAL SYSTEM, now U.S. Pat. No. 10,918,385;

[0301] U.S. patent application Ser. No. 15/385,894, entitled SHAFT ASSEMBLY COMPRISING A LOCK-OUT, now U.S. Pat. No. 10,492,785;

[0302] U.S. patent application Ser. No. 15/385,895, entitled SHAFT ASSEMBLY COMPRISING FIRST AND SECOND ARTICULATION LOCKOUTS, now U.S. Pat. No. 10,542,982;

[0303] U.S. patent application Ser. No. 15/385,916, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168575;

[0304] U.S. patent application Ser. No. 15/385,918, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168618;

[0305] U.S. patent application Ser. No. 15/385,919, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168619;

[0306] U.S. patent application Ser. No. 15/385,921, entitled SURGICAL STAPLE CARTRIDGE WITH MOVABLE CAMMING MEMBER CONFIGURED TO DISENGAGE FIRING MEMBER LOCKOUT FEATURES, now U.S. Pat. No. 10,687,809;

[0307] U.S. patent application Ser. No. 15/385,923, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168623;

[0308] U.S. patent application Ser. No. 15/385,925, entitled JAW ACTUATED LOCK ARRANGEMENTS FOR PREVENTING ADVANCEMENT OF A FIRING MEMBER IN A SURGICAL END EFFECTOR UNLESS AN UNFIRED CARTRIDGE IS INSTALLED IN THE END EFFECTOR, now U.S. Pat. No. 10,517,595;

[0309] U.S. patent application Ser. No. 15/385,926, entitled AXIALLY MOVABLE CLOSURE SYSTEM ARRANGEMENTS FOR APPLYING CLOSURE MOTIONS TO JAWS OF SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168577;

[0310] U.S. patent application Ser. No. 15/385,928, entitled PROTECTIVE COVER ARRANGEMENTS FOR A JOINT INTERFACE BETWEEN A MOVABLE JAW

AND ACTUATOR SHAFT OF A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2018/0168578;

[0311] U.S. patent application Ser. No. 15/385,930, entitled SURGICAL END EFFECTOR WITH TWO SEPARATE COOPERATING OPENING FEATURES FOR OPENING AND CLOSING END EFFECTOR JAWS, now U.S. Patent Application Publication No. 2018/0168579;

[0312] U.S. patent application Ser. No. 15/385,932, entitled ARTICULATABLE SURGICAL END EFFECTOR WITH ASYMMETRIC SHAFT ARRANGEMENT, now U.S. Pat. No. 10,959,727;

[0313] U.S. patent application Ser. No. 15/385,933, entitled ARTICULATABLE SURGICAL INSTRUMENT WITH INDEPENDENT PIVOTABLE LINKAGE DISTAL OF AN ARTICULATION LOCK, now U.S. Pat. No. 10,603,036;

[0314] U.S. patent application Ser. No. 15/385,934, entitled ARTICULATION LOCK ARRANGEMENTS FOR LOCKING AN END EFFECTOR IN AN ARTICULATED POSITION IN RESPONSE TO ACTUATION OF A JAW CLOSURE SYSTEM, now U.S. Pat. No. 10,582,928;

[0315] U.S. patent application Ser. No. 15/385,935, entitled Laterally Actuable Articulation Lock Arrangements for Locking an End Effector of a Surgical Instrument in an Articulated Configuration, now U.S. Pat. No. 10,524,789;

[0316] U.S. patent application Ser. No. 15/385,936, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH ARTICULATION STROKE AMPLIFICATION FEATURES, now U.S. Pat. No. 10,517,596;

[0317] U.S. patent application Ser. No. 14/318,996, entitled FASTENER CARTRIDGES INCLUDING EXTENSIONS HAVING DIFFERENT CONFIGURATIONS, now U.S. Patent Application Publication No. 2015/0297228;

[0318] U.S. patent application Ser. No. 14/319,006, entitled FASTENER CARTRIDGE COMPRISING FASTENER CAVITIES INCLUDING FASTENER CONTROL FEATURES, now U.S. Pat. No. 10,010,324;

[0319] U.S. patent application Ser. No. 14/318,991, entitled SURGICAL FASTENER CARTRIDGES WITH DRIVER STABILIZING ARRANGEMENTS, now U.S. Pat. No. 9,833,241;

[0320] U.S. patent application Ser. No. 14/319,004, entitled SURGICAL END EFFECTORS WITH FIRING ELEMENT MONITORING ARRANGEMENTS, now U.S. Pat. No. 9,844,369;

[0321] U.S. patent application Ser. No. 14/319,008, entitled FASTENER CARTRIDGE COMPRISING NON-UNIFORM FASTENERS, now U.S. Patent Application Publication No. 2015/0297232;

[0322] U.S. patent application Ser. No. 14/318,997, entitled FASTENER CARTRIDGE COMPRISING DEPLOYABLE TISSUE ENGAGING MEMBERS, now U.S. Pat. No. 10,561,422;

[0323] U.S. patent application Ser. No. 14/319,002, entitled FASTENER CARTRIDGE COMPRISING TISSUE CONTROL FEATURES, now U.S. Pat. No. 9,877,721;

[0324] U.S. patent application Ser. No. 14/319,013, entitled FASTENER CARTRIDGE ASSEMBLIES AND STAPLE RETAINER COVER ARRANGEMENTS, now U.S. Patent Application Publication No. 2015/0297233; and

[0325] U.S. patent application Ser. No. 14/319,016, entitled FASTENER CARTRIDGE INCLUDING A LAYER ATTACHED THERETO, now U.S. Pat. No. 10,470,768.

[0326] Applicant of the present application owns the following U.S. patent applications that were filed on Jun. 24, 2016 and which are each herein incorporated by reference in their respective entireties:

[0327] U.S. patent application Ser. No. 15/191,775, entitled STAPLE CARTRIDGE COMPRISING WIRE STAPLES AND STAMPED STAPLES, now U.S. Pat. No. 11,000,278;

[0328] U.S. patent application Ser. No. 15/191,807, entitled STAPLING SYSTEM FOR USE WITH WIRE STAPLES AND STAMPED STAPLES, now U.S. Pat. No. 10,702,270;

[0329] U.S. patent application Ser. No. 15/191,834, entitled STAMPED STAPLES AND STAPLE CARTRIDGES USING THE SAME, now U.S. Pat. No. 10,542,979;

[0330] U.S. patent application Ser. No. 15/191,788, entitled STAPLE CARTRIDGE COMPRISING OVER-DRIVEN STAPLES, now U.S. Pat. No. 10,675,024; and

[0331] U.S. patent application Ser. No. 15/191,818, entitled STAPLE CARTRIDGE COMPRISING OFFSET LONGITUDINAL STAPLE ROWS, now U.S. Pat. No. 10,893,863.

[0332] Applicant of the present application owns the following U.S. patent applications that were filed on Jun. 24, 2016 and which are each herein incorporated by reference in their respective entireties:

[0333] U.S. Design patent application Ser. No. 29/569,218, entitled SURGICAL FASTENER, now U.S. Design Pat. No. D826,405;

[0334] U.S. Design patent application Ser. No. 29/569,227, entitled SURGICAL FASTENER, now U.S. Design Pat. No. D822,206;

[0335] U.S. Design patent application Ser. No. 29/569,259, entitled SURGICAL FASTENER CARTRIDGE, now U.S. Design Pat. No. D847,989; and

[0336] U.S. Design patent application Ser. No. 29/569,264, entitled SURGICAL FASTENER CARTRIDGE, now U.S. Design Pat. No. D850,617.

[0337] Applicant of the present application owns the following patent applications that were filed on Apr. 1, 2016 and which are each herein incorporated by reference in their respective entirety:

[0338] U.S. patent application Ser. No. 15/089,325, entitled METHOD FOR OPERATING A SURGICAL STAPLING SYSTEM, now U.S. Patent Application Publication No. 2017/0281171;

[0339] U.S. patent application Ser. No. 15/089,321, entitled MODULAR SURGICAL STAPLING SYSTEM COMPRISING A DISPLAY, now U.S. Pat. No. 10,271,851;

[0340] U.S. patent application Ser. No. 15/089,326, entitled SURGICAL STAPLING SYSTEM COMPRISING A DISPLAY INCLUDING A RE-ORIENTABLE DISPLAY FIELD, now U.S. Pat. No. 10,433,849;

[0341] U.S. patent application Ser. No. 15/089,263, entitled SURGICAL INSTRUMENT HANDLE ASSEMBLY WITH RECONFIGURABLE GRIP PORTION, now U.S. Pat. No. 10,307,159;

[0342] U.S. patent application Ser. No. 15/089,262, entitled ROTARY POWERED SURGICAL INSTRUMENT

WITH MANUALLY ACTUATABLE BAILOUT SYSTEM, now U.S. Pat. No. 10,357,246;

[0343] U.S. patent application Ser. No. 15/089,277, entitled SURGICAL CUTTING AND STAPLING END EFFECTOR WITH ANVIL CONCENTRIC DRIVE MEMBER, now U.S. Pat. No. 10,531,874;

[0344] U.S. patent application Ser. No. 15/089,296, entitled INTERCHANGEABLE SURGICAL TOOL ASSEMBLY WITH A SURGICAL END EFFECTOR THAT IS SELECTIVELY ROTATABLE ABOUT A SHAFT AXIS, now U.S. Pat. No. 10,413,293;

[0345] U.S. patent application Ser. No. 15/089,258, entitled SURGICAL STAPLING SYSTEM COMPRISING A SHIFTABLE TRANSMISSION, now U.S. Pat. No. 10,342,543;

[0346] U.S. patent application Ser. No. 15/089,278, entitled SURGICAL STAPLING SYSTEM CONFIGURED TO PROVIDE SELECTIVE CUTTING OF TISSUE, now U.S. Pat. No. 10,420,552;

[0347] U.S. patent application Ser. No. 15/089,284, entitled SURGICAL STAPLING SYSTEM COMPRISING A CONTOURABLE SHAFT, now U.S. Patent Application Publication No. 2017/0281186;

[0348] U.S. patent application Ser. No. 15/089,295, entitled SURGICAL STAPLING SYSTEM COMPRISING A TISSUE COMPRESSION LOCKOUT, now U.S. Pat. No. 10,856,867;

[0349] U.S. patent application Ser. No. 15/089,300, entitled SURGICAL STAPLING SYSTEM COMPRISING AN UNCLAMPING LOCKOUT, now U.S. Pat. No. 10,456,140;

[0350] U.S. patent application Ser. No. 15/089,196, entitled SURGICAL STAPLING SYSTEM COMPRISING A JAW CLOSURE LOCKOUT, now U.S. Pat. No. 10,568,632;

[0351] U.S. patent application Ser. No. 15/089,203, entitled SURGICAL STAPLING SYSTEM COMPRISING A JAW ATTACHMENT LOCKOUT, now U.S. Pat. No. 10,542,991;

[0352] U.S. patent application Ser. No. 15/089,210, entitled SURGICAL STAPLING SYSTEM COMPRISING A SPENT CARTRIDGE LOCKOUT, now U.S. Pat. No. 10,478,190;

[0353] U.S. patent application Ser. No. 15/089,324, entitled SURGICAL INSTRUMENT COMPRISING A SHIFTING MECHANISM, now U.S. Pat. No. 10,314,582;

[0354] U.S. patent application Ser. No. 15/089,335, entitled SURGICAL STAPLING INSTRUMENT COMPRISING MULTIPLE LOCKOUTS, now U.S. Pat. No. 10,485,542;

[0355] U.S. patent application Ser. No. 15/089,339, entitled SURGICAL STAPLING INSTRUMENT, now U.S. Patent Application Publication No. 2017/0281173;

[0356] U.S. patent application Ser. No. 15/089,253, entitled SURGICAL STAPLING SYSTEM CONFIGURED TO APPLY ANNULAR ROWS OF STAPLES HAVING DIFFERENT HEIGHTS, now U.S. Pat. No. 10,413,297;

[0357] U.S. patent application Ser. No. 15/089,304, entitled SURGICAL STAPLING SYSTEM COMPRISING A GROOVED FORMING POCKET, now U.S. Pat. No. 10,285,705;

[0358] U.S. patent application Ser. No. 15/089,331, entitled ANVIL MODIFICATION MEMBERS FOR SURGICAL STAPLERS, now U.S. Pat. No. 10,376,263;

[0359] U.S. patent application Ser. No. 15/089,336, entitled STAPLE CARTRIDGES WITH ATRAUMATIC FEATURES, now U.S. Pat. No. 10,709,446;

[0360] U.S. patent application Ser. No. 15/089,312, entitled CIRCULAR STAPLING SYSTEM COMPRISING AN INCISABLE TISSUE SUPPORT, now U.S. Patent Application Publication No. 2017/0281189;

[0361] U.S. patent application Ser. No. 15/089,309, entitled CIRCULAR STAPLING SYSTEM COMPRISING ROTARY FIRING SYSTEM, now U.S. Pat. No. 10,675,021; and

[0362] U.S. patent application Ser. No. 15/089,349, entitled CIRCULAR STAPLING SYSTEM COMPRISING LOAD CONTROL, now U.S. Pat. No. 10,682,136.

[0363] Applicant of the present application also owns the U.S. patent applications identified below which were filed on Dec. 31, 2015 which are each herein incorporated by reference in their respective entirety:

[0364] U.S. patent application Ser. No. 14/984,488, entitled MECHANISMS FOR COMPENSATING FOR BATTERY PACK FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,292,704;

[0365] U.S. patent application Ser. No. 14/984,525, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,368,865; and

[0366] U.S. patent application Ser. No. 14/984,552, entitled SURGICAL INSTRUMENTS WITH SEPARABLE MOTORS AND MOTOR CONTROL CIRCUITS, now U.S. Pat. No. 10,265,068.

[0367] Applicant of the present application also owns the U.S. patent applications identified below which were filed on Feb. 9, 2016 which are each herein incorporated by reference in their respective entirety:

[0368] U.S. patent application Ser. No. 15/019,220, entitled SURGICAL INSTRUMENT WITH ARTICULATING AND AXIALLY TRANSLATABLE END EFFECTOR, now U.S. Pat. No. 10,245,029;

[0369] U.S. patent application Ser. No. 15/019,228, entitled SURGICAL INSTRUMENTS WITH MULTIPLE LINK ARTICULATION ARRANGEMENTS, now U.S. Pat. No. 10,433,837;

[0370] U.S. patent application Ser. No. 15/019,196, entitled SURGICAL INSTRUMENT ARTICULATION MECHANISM WITH SLOTTED SECONDARY CONSTRAINT, now U.S. Pat. No. 10,413,291;

[0371] U.S. patent application Ser. No. 15/019,206, entitled SURGICAL INSTRUMENTS WITH AN END EFFECTOR THAT IS HIGHLY ARTICULATABLE RELATIVE TO AN ELONGATE SHAFT ASSEMBLY, now U.S. Pat. No. 10,653,413;

[0372] U.S. patent application Ser. No. 15/019,215, entitled SURGICAL INSTRUMENTS WITH NON-SYMMETRICAL ARTICULATION ARRANGEMENTS, now U.S. Patent Application Publication No. 2017/0224332;

[0373] U.S. patent application Ser. No. 15/019,227, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH SINGLE ARTICULATION LINK ARRANGEMENTS, now U.S.

[0374] Patent Application Publication No. 2017/0224334;

[0375] U.S. patent application Ser. No. 15/019,235, entitled SURGICAL INSTRUMENTS WITH TENSIONING ARRANGEMENTS FOR CABLE DRIVEN ARTICULATION SYSTEMS, now U.S. Pat. No. 10,245,030;

[0376] U.S. patent application Ser. No. 15/019,230, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH OFF-AXIS FIRING BEAM ARRANGEMENTS, now U.S. Pat. No. 10,588,625; and

[0377] U.S. patent application Ser. No. 15/019,245, entitled SURGICAL INSTRUMENTS WITH CLOSURE STROKE REDUCTION ARRANGEMENTS, now U.S. Pat. No. 10,470,764.

[0378] Applicant of the present application also owns the U.S. patent applications identified below which were filed on Feb. 12, 2016 which are each herein incorporated by reference in their respective entirety:

[0379] U.S. patent application Ser. No. 15/043,254, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,258,331;

[0380] U.S. patent application Ser. No. 15/043,259, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,448,948;

[0381] U.S. patent application Ser. No. 15/043,275, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2017/0231627; and

[0382] U.S. patent application Ser. No. 15/043,289, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2017/0231628.

[0383] Applicant of the present application owns the following patent applications that were filed on Jun. 18, 2015 and which are each herein incorporated by reference in their respective entirety:

[0384] U.S. patent application Ser. No. 14/742,925, entitled SURGICAL END EFFECTORS WITH POSITIVE JAW OPENING ARRANGEMENTS, now U.S. Pat. No. 10,182,818;

[0385] U.S. patent application Ser. No. 14/742,941, entitled SURGICAL END EFFECTORS WITH DUAL CAM ACTUATED JAW CLOSING FEATURES, now U.S. Pat. No. 10,052,102;

[0386] U.S. patent application Ser. No. 14/742,914, entitled MOVABLE FIRING BEAM SUPPORT ARRANGEMENTS FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,405,863

[0387] U.S. patent application Ser. No. 14/742,900, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH COMPOSITE FIRING BEAM STRUCTURES WITH CENTER FIRING SUPPORT MEMBER FOR ARTICULATION SUPPORT, now U.S. Pat. No. 10,335,149;

[0388] U.S. patent application Ser. No. 14/742,885, entitled DUAL ARTICULATION DRIVE SYSTEM ARRANGEMENTS FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,368,861; and

[0389] U.S. patent application Ser. No. 14/742,876, entitled PUSH/PULL ARTICULATION DRIVE SYSTEMS FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,178,992.

[0390] Applicant of the present application owns the following patent applications that were filed on Mar. 6, 2015 and which are each herein incorporated by reference in their respective entirety:

[0391] U.S. patent application Ser. No. 14/640,746, entitled POWERED SURGICAL INSTRUMENT, now U.S. Pat. No. 9,808,246;

[0392] U.S. patent application Ser. No. 14/640,795, entitled MULTIPLE LEVEL THRESHOLDS TO MODIFY OPERATION OF POWERED SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,441,279;

[0393] U.S. patent application Ser. No. 14/640,832, entitled ADAPTIVE TISSUE COMPRESSION TECHNIQUES TO ADJUST CLOSURE RATES FOR MULTIPLE TISSUE TYPES, now U.S. Pat. No. 10,687,806;

[0394] U.S. patent application Ser. No. 14/640,935, entitled OVERLAID MULTI SENSOR RADIO FREQUENCY (RF) ELECTRODE SYSTEM TO MEASURE TISSUE COMPRESSION, now U.S. Pat. No. 10,548,504;

[0395] U.S. patent application Ser. No. 14/640,831, entitled MONITORING SPEED CONTROL AND PRECISION INCREMENTING OF MOTOR FOR POWERED SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,895,148;

[0396] U.S. patent application Ser. No. 14/640,859, entitled TIME DEPENDENT EVALUATION OF SENSOR DATA TO DETERMINE STABILITY, CREEP, AND VISCOELASTIC ELEMENTS OF MEASURES, now U.S. Pat. No. 10,052,044;

[0397] U.S. patent application Ser. No. 14/640,817, entitled INTERACTIVE FEEDBACK SYSTEM FOR POWERED SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,924,961;

[0398] U.S. patent application Ser. No. 14/640,844, entitled CONTROL TECHNIQUES AND SUB-PROCESSOR CONTAINED WITHIN MODULAR SHAFT WITH SELECT CONTROL PROCESSING FROM HANDLE, now U.S. Pat. No. 10,045,776;

[0399] U.S. patent application Ser. No. 14/640,837, entitled SMART SENSORS WITH LOCAL SIGNAL PROCESSING, now U.S. Pat. No. 9,993,248;

[0400] U.S. patent application Ser. No. 14/640,765, entitled SYSTEM FOR DETECTING THE MIS-INSERTION OF A STAPLE CARTRIDGE INTO A SURGICAL STAPLER, now U.S. Pat. No. 10,617,412;

[0401] U.S. patent application Ser. No. 14/640,799, entitled SIGNAL AND POWER COMMUNICATION SYSTEM POSITIONED ON A ROTATABLE SHAFT, now U.S. Pat. No. 9,901,342; and

[0402] U.S. patent application Ser. No. 14/640,780, entitled SURGICAL INSTRUMENT COMPRISING A LOCKABLE BATTERY HOUSING, now U.S. Pat. No. 10,245,033.

[0403] Applicant of the present application owns the following patent applications that were filed on Feb. 27, 2015, and which are each herein incorporated by reference in their respective entirety:

[0404] U.S. patent application Ser. No. 14/633,576, entitled SURGICAL INSTRUMENT SYSTEM COMPRISING AN INSPECTION STATION, now U.S. Pat. No. 10,045,779;

[0405] U.S. patent application Ser. No. 14/633,546, entitled SURGICAL APPARATUS CONFIGURED TO ASSESS WHETHER A PERFORMANCE PARAMETER OF THE SURGICAL APPARATUS IS WITHIN AN ACCEPTABLE PERFORMANCE BAND, now U.S. Pat. No. 10,180,463;

[0406] U.S. patent application Ser. No. 14/633,560, entitled SURGICAL CHARGING SYSTEM THAT CHARGES AND/OR CONDITIONS ONE OR MORE BATTERIES, now U.S. Patent Application Publication No. 2016/0249910;

[0407] U.S. patent application Ser. No. 14/633,566, entitled CHARGING SYSTEM THAT ENABLES EMERGENCY RESOLUTIONS FOR CHARGING A BATTERY, now U.S. Pat. No. 10,182,816;

[0408] U.S. patent application Ser. No. 14/633,555, entitled SYSTEM FOR MONITORING WHETHER A SURGICAL INSTRUMENT NEEDS TO BE SERVICED, now U.S. Pat. No. 10,321,907;

[0409] U.S. patent application Ser. No. 14/633,542, entitled REINFORCED BATTERY FOR A SURGICAL INSTRUMENT, now U.S. Pat. No. 9,931,118;

[0410] U.S. patent application Ser. No. 14/633,548, entitled POWER ADAPTER FOR A SURGICAL INSTRUMENT, now U.S. Pat. No. 10,245,028;

[0411] U.S. patent application Ser. No. 14/633,526, entitled ADAPTABLE SURGICAL INSTRUMENT HANDLE, now U.S. Pat. No. 9,993,258;

[0412] U.S. patent application Ser. No. 14/633,541, entitled MODULAR STAPLING ASSEMBLY, now U.S. Pat. No. 9,993,258; and

[0413] U.S. patent application Ser. No. 14/633,562, entitled SURGICAL APPARATUS CONFIGURED TO TRACK AN END-OF-LIFE PARAMETER, now U.S. Pat. No. 10,159,483.

[0414] Applicant of the present application owns the following patent applications that were filed on Dec. 18, 2014 and which are each herein incorporated by reference in their respective entirety:

[0415] U.S. patent application Ser. No. 14/574,478, entitled SURGICAL INSTRUMENT SYSTEMS COMPRISING AN ARTICULATABLE END EFFECTOR AND MEANS FOR ADJUSTING THE FIRING STROKE OF A FIRING MEMBER, now U.S. Pat. No. 9,844,374;

[0416] U.S. patent application Ser. No. 14/574,483, entitled SURGICAL INSTRUMENT ASSEMBLY COMPRISING LOCKABLE SYSTEMS, now U.S. Pat. No. 10,188,385;

[0417] U.S. patent application Ser. No. 14/575,139, entitled DRIVE ARRANGEMENTS FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,844,375;

[0418] U.S. patent application Ser. No. 14/575,148, entitled LOCKING ARRANGEMENTS FOR DETACHABLE SHAFT ASSEMBLIES WITH ARTICULATABLE SURGICAL END EFFECTORS, now U.S. Pat. No. 10,085,748;

[0419] U.S. patent application Ser. No. 14/575,130, entitled SURGICAL INSTRUMENT WITH AN ANVIL THAT IS SELECTIVELY MOVABLE ABOUT A DISCRETE NON-MOVABLE AXIS RELATIVE TO A STAPLE CARTRIDGE, now U.S. Pat. No. 10,245,027;

[0420] U.S. patent application Ser. No. 14/575,143, entitled SURGICAL INSTRUMENTS WITH IMPROVED CLOSURE ARRANGEMENTS, now U.S. Pat. No. 10,004,501;

[0421] U.S. patent application Ser. No. 14/575,117, entitled SURGICAL INSTRUMENTS WITH ARTICU-

LATABLE END EFFECTORS AND MOVABLE FIRING BEAM SUPPORT ARRANGEMENTS, now U.S. Pat. No. 9,943,309;

[0422] U.S. patent application Ser. No. 14/575,154, entitled SURGICAL INSTRUMENTS WITH ARTICULATABLE END EFFECTORS AND IMPROVED FIRING BEAM SUPPORT ARRANGEMENTS, now U.S. Pat. No. 9,968,355;

[0423] U.S. patent application Ser. No. 14/574,493, entitled SURGICAL INSTRUMENT ASSEMBLY COMPRISING A FLEXIBLE ARTICULATION SYSTEM, now U.S. Pat. No. 9,987,000; and

[0424] U.S. patent application Ser. No. 14/574,500, entitled SURGICAL INSTRUMENT ASSEMBLY COMPRISING A LOCKABLE ARTICULATION SYSTEM, now U.S. Pat. No. 10,117,649.

[0425] Applicant of the present application owns the following patent applications that were filed on Mar. 1, 2013 and which are each herein incorporated by reference in their respective entirety:

[0426] U.S. patent application Ser. No. 13/782,295, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH CONDUCTIVE PATHWAYS FOR SIGNAL COMMUNICATION, now U.S. Pat. No. 9,700,309;

[0427] U.S. patent application Ser. No. 13/782,323, entitled ROTARY POWERED ARTICULATION JOINTS FOR SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,782,169;

[0428] U.S. patent application Ser. No. 13/782,338, entitled THUMBWHEEL SWITCH ARRANGEMENTS FOR SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2014/0249557;

[0429] U.S. patent application Ser. No. 13/782,499, entitled ELECTROMECHANICAL SURGICAL DEVICE WITH SIGNAL RELAY ARRANGEMENT, now U.S. Pat. No. 9,358,003;

[0430] U.S. patent application Ser. No. 13/782,460, entitled MULTIPLE PROCESSOR MOTOR CONTROL FOR MODULAR SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,554,794;

[0431] U.S. patent application Ser. No. 13/782,358, entitled JOYSTICK SWITCH ASSEMBLIES FOR SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,326,767;

[0432] U.S. patent application Ser. No. 13/782,481, entitled SENSOR STRAIGHTENED END EFFECTOR DURING REMOVAL THROUGH TROCAR, now U.S. Pat. No. 9,468,438;

[0433] U.S. patent application Ser. No. 13/782,518, entitled CONTROL METHODS FOR SURGICAL INSTRUMENTS WITH REMOVABLE IMPLEMENT PORTIONS, now U.S. Patent Application Publication No. 2014/0246475;

[0434] U.S. patent application Ser. No. 13/782,375, entitled ROTARY POWERED SURGICAL INSTRUMENTS WITH MULTIPLE DEGREES OF FREEDOM, now U.S. Pat. No. 9,398,911; and

[0435] U.S. patent application Ser. No. 13/782,536, entitled SURGICAL INSTRUMENT SOFT STOP, now U.S. Pat. No. 9,307,986.

[0436] Applicant of the present application also owns the following patent applications that were filed on Mar. 14, 2013 and which are each herein incorporated by reference in their respective entirety:

[0437] U.S. patent application Ser. No. 13/803,097, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING A FIRING DRIVE, now U.S. Pat. No. 9,687,230;

[0438] U.S. patent application Ser. No. 13/803,193, entitled CONTROL ARRANGEMENTS FOR A DRIVE MEMBER OF A SURGICAL INSTRUMENT, now U.S. Pat. No. 9,332,987;

[0439] U.S. patent application Ser. No. 13/803,053, entitled INTERCHANGEABLE SHAFT ASSEMBLIES FOR USE WITH A SURGICAL INSTRUMENT, now U.S. Pat. No. 9,883,860;

[0440] U.S. patent application Ser. No. 13/803,086, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING AN ARTICULATION LOCK, now U.S. Patent Application Publication No. 2014/0263541;

[0441] U.S. patent application Ser. No. 13/803,210, entitled SENSOR ARRANGEMENTS FOR ABSOLUTE POSITIONING SYSTEM FOR SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,808,244;

[0442] U.S. patent application Ser. No. 13/803,148, entitled MULTI-FUNCTION MOTOR FOR A SURGICAL INSTRUMENT, now U.S. Pat. No. 10,470,762;

[0443] U.S. patent application Ser. No. 13/803,066, entitled DRIVE SYSTEM LOCKOUT ARRANGEMENTS FOR MODULAR SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,629,623;

[0444] U.S. patent application Ser. No. 13/803,117, entitled ARTICULATION CONTROL SYSTEM FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,351,726;

[0445] U.S. patent application Ser. No. 13/803,130, entitled DRIVE TRAIN CONTROL ARRANGEMENTS FOR MODULAR SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,351,727; and

[0446] U.S. patent application Ser. No. 13/803,159, entitled METHOD AND SYSTEM FOR OPERATING A SURGICAL INSTRUMENT, now U.S. Pat. No. 9,888,919.

[0447] Applicant of the present application also owns the following patent application that was filed on Mar. 7, 2014 and is herein incorporated by reference in its entirety:

[0448] U.S. patent application Ser. No. 14/200,111, entitled CONTROL SYSTEMS FOR SURGICAL INSTRUMENTS, now U.S. Pat. No. 9,629,629.

[0449] Applicant of the present application also owns the following patent applications that were filed on Mar. 26, 2014 and are each herein incorporated by reference in their respective entirety:

[0450] U.S. patent application Ser. No. 14/226,106, entitled POWER MANAGEMENT CONTROL SYSTEMS FOR SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2015/0272582;

[0451] U.S. patent application Ser. No. 14/226,099, entitled STERILIZATION VERIFICATION CIRCUIT, now U.S. Pat. No. 9,826,977;

[0452] U.S. patent application Ser. No. 14/226,094, entitled VERIFICATION OF NUMBER OF BATTERY EXCHANGES/PROCEDURE COUNT, now U.S. Patent Application Publication No. 2015/0272580;

[0453] U.S. patent application Ser. No. 14/226,117, entitled POWER MANAGEMENT THROUGH SLEEP OPTIONS OF SEGMENTED CIRCUIT AND WAKE UP CONTROL, now U.S. Pat. No. 10,013,049;

[0454] U.S. patent application Ser. No. 14/226,075, entitled MODULAR POWERED SURGICAL INSTRUMENT WITH DETACHABLE SHAFT ASSEMBLIES, now U.S. Pat. No. 9,743,929;

[0455] U.S. patent application Ser. No. 14/226,093, entitled FEEDBACK ALGORITHMS FOR MANUAL BAILOUT SYSTEMS FOR SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,028,761;

[0456] U.S. patent application Ser. No. 14/226,116, entitled SURGICAL INSTRUMENT UTILIZING SENSOR ADAPTATION, now U.S. Patent Application Publication No. 2015/0272571;

[0457] U.S. patent application Ser. No. 14/226,071, entitled SURGICAL INSTRUMENT CONTROL CIRCUIT HAVING A SAFETY PROCESSOR, now U.S. Pat. No. 9,690,362;

[0458] U.S. patent application Ser. No. 14/226,097, entitled SURGICAL INSTRUMENT COMPRISING INTERACTIVE SYSTEMS, now U.S. Pat. No. 9,820,738;

[0459] U.S. patent application Ser. No. 14/226,126, entitled INTERFACE SYSTEMS FOR USE WITH SURGICAL INSTRUMENTS, now U.S. Pat. No. 10,004,497;

[0460] U.S. patent application Ser. No. 14/226,133, entitled MODULAR SURGICAL INSTRUMENT SYSTEM, now U.S. Patent Application Publication No. 2015/0272557;

[0461] U.S. patent application Ser. No. 14/226,081, entitled SYSTEMS AND METHODS FOR CONTROLLING A SEGMENTED CIRCUIT, now U.S. Pat. No. 9,804,618;

[0462] U.S. patent application Ser. No. 14/226,076, entitled POWER MANAGEMENT THROUGH SEGMENTED CIRCUIT AND VARIABLE VOLTAGE PROTECTION, now U.S. Pat. No. 9,733,663;

[0463] U.S. patent application Ser. No. 14/226,111, entitled SURGICAL STAPLING INSTRUMENT SYSTEM, now U.S. Pat. No. 9,750,499; and

[0464] U.S. patent application Ser. No. 14/226,125, entitled SURGICAL INSTRUMENT COMPRISING A ROTATABLE SHAFT, now U.S. Pat. No. 10,201,364.

[0465] Applicant of the present application also owns the following patent applications that were filed on Sep. 5, 2014 and which are each herein incorporated by reference in their respective entirety:

[0466] U.S. patent application Ser. No. 14/479,103, entitled CIRCUITRY AND SENSORS FOR POWERED MEDICAL DEVICE, now U.S. Pat. No. 10,111,679;

[0467] U.S. patent application Ser. No. 14/479,119, entitled ADJUNCT WITH INTEGRATED SENSORS TO QUANTIFY TISSUE COMPRESSION, now U.S. Pat. No. 9,724,094;

[0468] U.S. patent application Ser. No. 14/478,908, entitled MONITORING DEVICE DEGRADATION BASED ON COMPONENT EVALUATION, now U.S. Pat. No. 9,737,301;

[0469] U.S. patent application Ser. No. 14/478,895, entitled MULTIPLE SENSORS WITH ONE SENSOR AFFECTING A SECOND SENSOR'S OUTPUT OR INTERPRETATION, now U.S. Pat. No. 9,757,128;

[0470] U.S. patent application Ser. No. 14/479,110, entitled POLARITY OF HALL MAGNET TO IDENTIFY CARTRIDGE TYPE, now U.S. Pat. No. 10,016,199;

[0471] U.S. patent application Ser. No. 14/479,098, entitled SMART CARTRIDGE WAKE UP OPERATION AND DATA RETENTION, now U.S. Pat. No. 10,135,242;

[0472] U.S. patent application Ser. No. 14/479,115, entitled MULTIPLE MOTOR CONTROL FOR POWERED MEDICAL DEVICE, now U.S. Pat. No. 9,788,836; and

[0473] U.S. patent application Ser. No. 14/479,108, entitled LOCAL DISPLAY OF TISSUE PARAMETER STABILIZATION, now U.S. Patent Application Publication No. 2016/0066913.

[0474] Applicant of the present application also owns the following patent applications that were filed on Apr. 9, 2014 and which are each herein incorporated by reference in their respective entirety:

[0475] U.S. patent application Ser. No. 14/248,590, entitled MOTOR DRIVEN SURGICAL INSTRUMENTS WITH LOCKABLE DUAL DRIVE SHAFTS, now U.S. Pat. No. 9,826,976;

[0476] U.S. patent application Ser. No. 14/248,581, entitled SURGICAL INSTRUMENT COMPRISING A CLOSING DRIVE AND A FIRING DRIVE OPERATED FROM THE SAME ROTATABLE OUTPUT, now U.S. Pat. No. 9,649,110;

[0477] U.S. patent application Ser. No. 14/248,595, entitled SURGICAL SYSTEM COMPRISING FIRST AND SECOND DRIVE SYSTEMS, now U.S. Pat. No. 9,844,368;

[0478] U.S. patent application Ser. No. 14/248,588, entitled POWERED LINEAR SURGICAL STAPLER, now U.S. Pat. No. 10,405,857;

[0479] U.S. patent application Ser. No. 14/248,591, entitled SURGICAL INSTRUMENT COMPRISING A GAP SETTING SYSTEM, now U.S. Pat. No. 10,149,680;

[0480] U.S. patent application Ser. No. 14/248,584, entitled MODULAR MOTOR DRIVEN SURGICAL INSTRUMENTS WITH ALIGNMENT FEATURES FOR ALIGNING ROTARY DRIVE SHAFTS WITH SURGICAL END EFFECTOR SHAFTS, now U.S. Pat. No. 9,801,626;

[0481] U.S. patent application Ser. No. 14/248,587, entitled POWERED SURGICAL STAPLER, now U.S. Pat. No. 9,867,612;

[0482] U.S. patent application Ser. No. 14/248,586, entitled DRIVE SYSTEM DECOUPLING ARRANGEMENT FOR A SURGICAL INSTRUMENT, now U.S. Pat. No. 10,136,887; and

[0483] U.S. patent application Ser. No. 14/248,607, entitled MODULAR MOTOR DRIVEN SURGICAL INSTRUMENTS WITH STATUS INDICATION ARRANGEMENTS, now U.S. Pat. No. 9,814,460.

[0484] Applicant of the present application also owns the following patent applications that were filed on Apr. 16, 2013 and which are each herein incorporated by reference in their respective entirety:

[0485] U.S. Provisional Patent Application Ser. No. 61/812,365, entitled SURGICAL INSTRUMENT WITH MULTIPLE FUNCTIONS PERFORMED BY A SINGLE MOTOR;

[0486] U.S. Provisional Patent Application Ser. No. 61/812,376, entitled LINEAR CUTTER WITH POWER;

[0487] U.S. Provisional Patent Application Ser. No. 61/812,382, entitled LINEAR CUTTER WITH MOTOR AND PISTOL GRIP;

[0488] U.S. Provisional Patent Application Ser. No. 61/812,385, entitled SURGICAL INSTRUMENT

HANDLE WITH MULTIPLE ACTUATION MOTORS AND MOTOR CONTROL; and

[0489] U.S. Provisional Patent Application Ser. No. 61/812,372, entitled SURGICAL INSTRUMENT WITH MULTIPLE FUNCTIONS PERFORMED BY A SINGLE MOTOR.

[0490] Numerous specific details are set forth to provide a thorough understanding of the overall structure, function, manufacture, and use of the embodiments as described in the specification and illustrated in the accompanying drawings. Well-known operations, components, and elements have not been described in detail so as not to obscure the embodiments described in the specification. The reader will understand that the embodiments described and illustrated herein are non-limiting examples, and thus it can be appreciated that the specific structural and functional details disclosed herein may be representative and illustrative. Variations and changes thereto may be made without departing from the scope of the claims.

[0491] The terms “comprise” (and any form of comprise, such as “comprises” and “comprising”), “have” (and any form of have, such as “has” and “having”), “include” (and any form of include, such as “includes” and “including”) and “contain” (and any form of contain, such as “contains” and “containing”) are open-ended linking verbs. As a result, a surgical system, device, or apparatus that “comprises,” “has,” “includes” or “contains” one or more elements possesses those one or more elements, but is not limited to possessing only those one or more elements. Likewise, an element of a system, device, or apparatus that “comprises,” “has,” “includes” or “contains” one or more features possesses those one or more features, but is not limited to possessing only those one or more features.

[0492] The terms “proximal” and “distal” are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term “proximal” refers to the portion closest to the clinician and the term “distal” refers to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as “vertical”, “horizontal”, “up”, and “down” may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0493] Various exemplary devices and methods are provided for performing laparoscopic and minimally invasive surgical procedures. However, the reader will readily appreciate that the various methods and devices disclosed herein can be used in numerous surgical procedures and applications including, for example, in connection with open surgical procedures. As the present Detailed Description proceeds, the reader will further appreciate that the various instruments disclosed herein can be inserted into a body in any way, such as through a natural orifice, through an incision or puncture hole formed in tissue, etc. The working portions or end effector portions of the instruments can be inserted directly into a patient’s body or can be inserted through an access device that has a working channel through which the end effector and elongate shaft of a surgical instrument can be advanced.

[0494] A surgical stapling system can comprise a shaft and an end effector extending from the shaft. The end effector comprises a first jaw and a second jaw. The first jaw comprises a staple cartridge. The staple cartridge is insertable into and removable from the first jaw; however, other

embodiments are envisioned in which a staple cartridge is not removable from, or at least readily replaceable from, the first jaw. The second jaw comprises an anvil configured to deform staples ejected from the staple cartridge. The second jaw is pivotable relative to the first jaw about a closure axis; however, other embodiments are envisioned in which the first jaw is pivotable relative to the second jaw. The surgical stapling system further comprises an articulation joint configured to permit the end effector to be rotated, or articulated, relative to the shaft. The end effector is rotatable about an articulation axis extending through the articulation joint. Other embodiments are envisioned which do not include an articulation joint.

[0495] The staple cartridge comprises a cartridge body. The cartridge body includes a proximal end, a distal end, and a deck extending between the proximal end and the distal end. In use, the staple cartridge is positioned on a first side of the tissue to be stapled and the anvil is positioned on a second side of the tissue. The anvil is moved toward the staple cartridge to compress and clamp the tissue against the deck. Thereafter, staples removably stored in the cartridge body can be deployed into the tissue. The cartridge body includes staple cavities defined therein wherein staples are removably stored in the staple cavities. The staple cavities are arranged in six longitudinal rows. Three rows of staple cavities are positioned on a first side of a longitudinal slot and three rows of staple cavities are positioned on a second side of the longitudinal slot. Other arrangements of staple cavities and staples may be possible.

[0496] The staples are supported by staple drivers in the cartridge body. The drivers are movable between a first, or unfired position, and a second, or fired, position to eject the staples from the staple cavities. The drivers are retained in the cartridge body by a retainer which extends around the bottom of the cartridge body and includes resilient members configured to grip the cartridge body and hold the retainer to the cartridge body. The drivers are movable between their unfired positions and their fired positions by a sled. The sled is movable between a proximal position adjacent the proximal end and a distal position adjacent the distal end. The sled comprises a plurality of ramped surfaces configured to slide under the drivers and lift the drivers, and the staples supported thereon, toward the anvil.

[0497] Further to the above, the sled is moved distally by a firing member. The firing member is configured to contact the sled and push the sled toward the distal end. The longitudinal slot defined in the cartridge body is configured to receive the firing member. The anvil also includes a slot configured to receive the firing member. The firing member further comprises a first cam which engages the first jaw and a second cam which engages the second jaw. As the firing member is advanced distally, the first cam and the second cam can control the distance, or tissue gap, between the deck of the staple cartridge and the anvil. The firing member also comprises a knife configured to incise the tissue captured intermediate the staple cartridge and the anvil. It is desirable for the knife to be positioned at least partially proximal to the ramped surfaces such that the staples are ejected ahead of the knife.

[0498] FIG. 1 illustrates the surgical instrument 1010 that includes an interchangeable shaft assembly 1200 operably coupled to a housing 1012. FIG. 2 illustrates the interchangeable shaft assembly 1200 detached from the housing 1012 or handle 1014. As can be seen in FIG. 3, the handle

1014 may comprise a pair of interconnectable handle housing segments **1016** and **1018** that may be interconnected by screws, snap features, adhesive, etc. In the illustrated arrangement, the handle housing segments **1016**, **1018** cooperate to form a pistol grip portion **1019**. FIGS. 1 and 3 depict a motor-driven surgical cutting and fastening instrument **1010** that may or may not be reused. In the illustrated embodiment, the instrument **1010** includes a previous housing **1012** that comprises a handle **1014** that is configured to be grasped, manipulated and actuated by the clinician. The housing **1012** is configured for operable attachment to an interchangeable shaft assembly **1200** that has a surgical end effector **1300** operably coupled thereto that is configured to perform one or more surgical tasks or procedures. As the present Detailed Description proceeds, it will be understood that the various forms of interchangeable shaft assemblies disclosed herein may also be effectively employed in connection with robotically-controlled surgical systems. Thus, the term “housing” may also encompass a housing or similar portion of a robotic system that houses or otherwise operably supports at least one drive system that is configured to generate and apply at least one control motion which could be used to actuate the interchangeable shaft assemblies disclosed herein and their respective equivalents. In addition, various components may be “housed” or contained in the housing or various components may be “associated with” a housing. In such instances, the components may not be contained within the housing or supported directly by the housing. The term “frame” may refer to a portion of a handheld surgical instrument. The term “frame” may also represent a portion of a robotically controlled surgical instrument and/or a portion of the robotic system that may be used to operably control a surgical instrument. For example, the interchangeable shaft assemblies disclosed herein may be employed with various robotic systems, instruments, components and methods disclosed in U.S. Pat. No. 9,072,535, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, that is incorporated by reference herein in its entirety.

[0499] The previous housing **1012** depicted in FIG. 1 is shown in connection with an interchangeable shaft assembly **1200** (FIGS. 2, 4 and 5) that includes an end effector **1300** that comprises a surgical cutting and fastening device that is configured to operably support a surgical staple cartridge **4000** therein. The housing **1012** may be configured for use in connection with interchangeable shaft assemblies that include end effectors that are adapted to support different sizes and types of staple cartridges, have different shaft lengths, sizes, and types, etc. In addition, the housing **1012** may also be effectively employed with a variety of other interchangeable shaft assemblies including those assemblies that are configured to apply other motions and forms of energy such as, for example, radio frequency (RF) energy, ultrasonic energy and/or motion to end effector arrangements adapted for use in connection with various surgical applications and procedures. Furthermore, the end effectors, shaft assemblies, handles, surgical instruments, and/or surgical instrument systems can utilize any suitable fastener, that can be gripped and manipulated by the clinician. As will be discussed in further detail below, the handle **1014** operably supports a plurality of drive systems therein that are configured to generate and apply various control motions to

corresponding portions of the interchangeable shaft assembly that is operably attached thereto.

[0500] Referring now to FIG. 3, the handle **1014** may further include a frame **1020** that operably supports a plurality of drive systems. For example, the frame **1020** can operably support a “first” or closure drive system, generally designated as **1030**, which may be employed to apply closing and opening motions to the interchangeable shaft assembly **1200** that is operably attached or coupled thereto. In at least one form, the closure drive system **1030** may include an actuator in the form of a closure trigger **1032** that is pivotally supported by the frame **1020**. More specifically, as illustrated in FIG. 3, the closure trigger **1032** is pivotally coupled to the handle **1014** by a pin **1033**. Such arrangement enables the closure trigger **1032** to be manipulated by a clinician such that when the clinician grips the pistol grip portion **1019** of the handle **1014**, the closure trigger **1032** may be easily pivoted from a starting or “unactuated” position to an “actuated” position and more particularly to a fully compressed or fully actuated position. The closure trigger **1032** may be biased into the unactuated position by spring or other biasing arrangement (not shown). In various forms, the closure drive system **1030** further includes a closure linkage assembly **1034** that is pivotally coupled to the closure trigger **1032**. As can be seen in FIG. 3, the closure linkage assembly **1034** may include a first closure link **1036** and a second closure link **1038** that are pivotally coupled to the closure trigger **1032** by a pin **1035**. The second closure link **1038** may also be referred to herein as an “attachment member” and include a transverse attachment pin **1037**.

[0501] Still referring to FIG. 3, it can be observed that the first closure link **1036** may have a locking wall or end **1039** thereon that is configured to cooperate with a closure release assembly **1060** that is pivotally coupled to the frame **1020**. In at least one form, the closure release assembly **1060** may comprise a release button assembly **1062** that has a distally protruding locking pawl **1064** formed thereon. The release button assembly **1062** may be pivoted in a counterclockwise direction by a release spring (not shown). As the clinician depresses the closure trigger **1032** from its unactuated position towards the pistol grip portion **1019** of the handle **1014**, the first closure link **1036** pivots upward to a point wherein the locking pawl **1064** drops into retaining engagement with the locking wall **1039** on the first closure link **1036** thereby preventing the closure trigger **1032** from returning to the unactuated position. Thus, the closure release assembly **1060** serves to lock the closure trigger **1032** in the fully actuated position. When the clinician desires to unlock the closure trigger **1032** to permit it to be biased to the unactuated position, the clinician simply pivots the release button assembly **1062** such that the locking pawl **1064** is moved out of engagement with the locking wall **1039** on the first closure link **1036**. When the locking pawl **1064** has been moved out of engagement with the first closure link **1036**, the closure trigger **1032** may pivot back to the unactuated position. Other closure trigger locking and release arrangements may also be employed.

[0502] An arm **1061** may extend from the release button assembly **1062**. A magnetic element **1063**, such as a permanent magnet, for example, may be mounted to the arm **1061**. When the release button assembly **1062** is rotated from its first position to its second position, the magnetic element **1063** can move toward a circuit board **1100**. The circuit

board **1100** can include at least one sensor that is configured to detect the movement of the magnetic element **1063**. In at least one embodiment, for example, a “Hall Effect” sensor (not shown) can be mounted to the bottom surface of the circuit board **1100**. The Hall Effect sensor can be configured to detect changes in a magnetic field surrounding the Hall Effect sensor caused by the movement of the magnetic element **1063**. The Hall Effect sensor can be in signal communication with a microcontroller, for example, which can determine whether the release button assembly **1062** is in its first position, which is associated with the unactuated position of the closure trigger **1032** and the open configuration of the end effector, its second position, which is associated with the actuated position of the closure trigger **1032** and the closed configuration of the end effector, and/or any position between the first position and the second position.

[0503] In at least one form, the handle **1014** and the frame **1020** may operably support another drive system referred to herein as a firing drive system **1080** that is configured to apply firing motions to corresponding portions of the interchangeable shaft assembly attached thereto. The firing drive system **1080** may also be referred to herein as a “second drive system”. The firing drive system **1080** may employ an electric motor **1082** that is located in the pistol grip portion **1019** of the handle **1014**. In various forms, the motor **1082** may be a DC brushed driving motor having a maximum rotation of, approximately, 25,000 RPM, for example. In other arrangements, the motor may include a brushless motor, a cordless motor, a synchronous motor, a stepper motor, or any other suitable electric motor. The motor **1082** may be powered by a power source **1090** that in one form may comprise a removable power pack **1092**. As can be seen in FIG. 3, for example, the power pack **1092** may comprise a proximal housing portion **1094** that is configured for attachment to a distal housing portion **1096**. The proximal housing portion **1094** and the distal housing portion **1096** are configured to operably support a plurality of batteries **1098** therein. Batteries **1098** may each comprise, for example, a Lithium Ion (“LI”) or other suitable battery. The distal housing portion **1096** is configured for removable operable attachment to the circuit board **1100** which is also operably coupled to the motor **1082**. A number of batteries **1098** may be connected in series may be used as the power source for the surgical instrument **1010**. In addition, the power source **1090** may be replaceable and/or rechargeable.

[0504] As outlined above with respect to other various forms, the electric motor **1082** can include a rotatable shaft (not shown) that operably interfaces with a gear reducer assembly **1084** that is mounted in meshing engagement with a set, or rack, of drive teeth **1122** on a longitudinally-movable drive member **1120**. In use, a voltage polarity provided by the power source **1090** can operate the electric motor **1082** in a clockwise direction wherein the voltage polarity applied to the electric motor by the battery can be reversed in order to operate the electric motor **1082** in a counter-clockwise direction. When the electric motor **1082** is rotated in one direction, the drive member **1120** will be axially driven in the distal direction “DD”. When the motor **82** is driven in the opposite rotary direction, the drive member **1120** will be axially driven in a proximal direction “PD”. The handle **1014** can include a switch which can be configured to reverse the polarity applied to the electric motor **1082** by the power source **1090**. As with the other

forms described herein, the handle **1014** can also include a sensor that is configured to detect the position of the drive member **1120** and/or the direction in which the drive member **1120** is being moved.

[0505] Actuation of the motor **1082** can be controlled by a firing trigger **1130** that is pivotally supported on the handle **1014**. The firing trigger **1130** may be pivoted between an unactuated position and an actuated position. The firing trigger **1130** may be biased into the unactuated position by a spring **1132** or other biasing arrangement such that when the clinician releases the firing trigger **1130**, it may be pivoted or otherwise returned to the unactuated position by the spring **1132** or biasing arrangement. In at least one form, the firing trigger **1130** can be positioned “outboard” of the closure trigger **1032** as was discussed above. In at least one form, a firing trigger safety button **1134** may be pivotally mounted to the closure trigger **1032** by the pin **1035**. The safety button **1134** may be positioned between the firing trigger **1130** and the closure trigger **1032** and have a pivot arm **1136** protruding therefrom. See FIG. 3. When the closure trigger **1032** is in the unactuated position, the safety button **1134** is contained in the handle **1014** where the clinician cannot readily access it and move it between a safety position preventing actuation of the firing trigger **1130** and a firing position wherein the firing trigger **1130** may be fired. As the clinician depresses the closure trigger **1032**, the safety button **1134** and the firing trigger **1130** pivot down wherein they can then be manipulated by the clinician.

[0506] As indicated above, in at least one form, the longitudinally movable drive member **1120** has a rack of teeth **1122** formed thereon for meshing engagement with a corresponding drive gear **1086** of the gear reducer assembly **1084**. At least one form also includes a manually-actuatable “bailout” assembly **1140** that is configured to enable the clinician to manually retract the longitudinally movable drive member **1120** should the motor **1082** become disabled. The bailout assembly **1140** may include a lever or bailout handle assembly **1142** that is configured to be manually pivoted into ratcheting engagement with teeth **1124** also provided in the drive member **1120**. Thus, the clinician can manually retract the drive member **1120** by using the bailout handle assembly **1142** to ratchet the drive member **1120** in the proximal direction “PD”. U.S. Pat. No. 8,608,045, entitled POWERED SURGICAL CUTTING AND STAPLING APPARATUS WITH MANUALLY RETRACTABLE FIRING SYSTEM, discloses bailout arrangements and other components, arrangements and systems that may also be employed with the various instruments disclosed herein. U.S. Pat. No. 8,608,045, is hereby incorporated by reference herein in its entirety.

[0507] Turning now to FIGS. 2 and 5, the interchangeable shaft assembly **1200** includes a surgical end effector **1300** that comprises an elongate channel **1310** that is configured to operably support a staple cartridge **4000** therein. The end effector **1300** may further include an anvil **2000** that is pivotally supported relative to the elongate channel **1310**. The interchangeable shaft assembly **1200** may further include an articulation joint **3020** and an articulation lock **2140** which can be configured to releasably hold the end effector **1300** in a desired position relative to a shaft axis SA. Examples of various features of at least one form of the end effector **1300**, the articulation joint **3020** and articulation locks may be found in U.S. patent application Ser. No. 13/803,086, filed Mar. 14, 2013, entitled ARTICULAT-

ABLE SURGICAL INSTRUMENT COMPRISING AN ARTICULATION LOCK, now U.S. Patent Application Publication No. 2014/0263541. The entire disclosure of U.S. patent application Ser. No. 13/803,086, filed Mar. 14, 2013, entitled ARTICULABLE SURGICAL INSTRUMENT COMPRISING AN ARTICULATION LOCK, now U.S. Patent Application Publication No. 2014/0263541, is hereby incorporated by reference herein. As can be seen in FIG. 4, the interchangeable shaft assembly 1200 can further include a proximal housing or nozzle 1201 comprised of nozzle portions 1202 and 1203.

[0508] The interchangeable shaft assembly 1200 can further include a closure system or closure member assembly 3000 which can be utilized to close and/or open the anvil 2000 of the end effector 1300. The shaft assembly 1200 can include a spine 1210 that is configured to, one, slidably support a firing member therein and, two, slidably support the closure member assembly 3000 which extends around the spine 1210. As can be seen in FIG. 5, a distal end 1212 of spine 1210 terminates in an upper lug mount feature 1270 and in a lower lug mount feature 1280. The upper lug mount feature 1270 is formed with a lug slot 1272 therein that is adapted to mountingly support an upper mounting link 1274 therein. Similarly, the lower lug mount feature 1280 is formed with a lug slot 1282 therein that is adapted to mountingly support a lower mounting link 1284 therein. The upper mounting link 1274 includes a pivot socket 1276 therein that is adapted to rotatably receive therein a pivot pin 1292 that is formed on a channel cap or anvil retainer 1290 that is attached to a proximal end portion 1312 of the elongate channel 1310. The lower mounting link 1284 includes lower pivot pin 1286 that adapted to be received within a pivot hole 1314 formed in the proximal end portion 1312 of the elongate channel 1310. See FIG. 5. The lower pivot pin 1286 is vertically aligned with the pivot socket 1276 to define an articulation axis AA about which the surgical end effector 1300 may articulate relative to the shaft axis SA. See FIG. 2.

[0509] In the illustrated example, the surgical end effector 1300 is selectively articulatable about the articulation axis AA by an articulation system 2100. In one form, the articulation system 2100 includes proximal articulation driver 2102 that is pivotally coupled to an articulation link 2120. As can be most particularly seen in FIG. 5, an offset attachment lug 2114 is formed on a distal end 2110 of the proximal articulation driver 2102. A pivot hole 2116 is formed in the offset attachment lug 2114 and is configured to pivotally receive therein a proximal link pin 2124 formed on the proximal end 2122 of the articulation link 2120. A distal end 2126 of the articulation link 2120 includes a pivot hole 2128 that is configured to pivotally receive therein a channel pin 1317 formed on the proximal end portion 1312 of the elongate channel 1310. Thus, axial movement of proximal articulation driver 2102 will thereby apply articulation motions to the elongate channel 1310 to thereby cause the surgical end effector 1300 to articulate about the articulation axis AA relative to the spine 1210. Further details concerning the construction and operation of the articulation system 2100 may be found in various references incorporated by reference herein including U.S. patent application Ser. No. 15/635,631, filed Jun. 28, 2017, entitled SURGICAL INSTRUMENT WITH AXIALLY MOVABLE CLOSURE MEMBER, now U.S. Pat. No. 10,639,037, the entire disclosure of which is hereby incorporated by reference

herein. In various circumstances, the proximal articulation driver 2102 can be held in position by an articulation lock 2140 when the proximal articulation driver 2102 is not being moved in the proximal or distal directions. Additional details regarding an example of an articulation lock 2140 may be found in U.S. patent application Ser. No. 15/635,631, now U.S. Pat. No. 10,639,037, as well as in other references incorporated by reference herein.

[0510] In various circumstances, the spine 1210 can comprise a proximal end 1211 which is rotatably supported in a chassis 1240. In one arrangement, for example, the proximal end 1211 of the spine 1210 has a thread 1214 formed thereon for threaded attachment to a spine bearing 1216 configured to be supported within the chassis 1240. See FIG. 4. Such an arrangement facilitates rotatable attachment of the spine 1210 to the chassis 1240 such that the spine 1210 may be selectively rotated about a shaft axis SA relative to the chassis 1240.

[0511] Referring primarily to FIG. 4, the interchangeable shaft assembly 1200 includes a closure shuttle 1250 that is slidably supported within the chassis 1240 such that it may be axially moved relative thereto. The closure shuttle 1250 includes a pair of proximally-protruding hooks 1252 that are configured for attachment to the attachment pin 1037 (FIG. 3) that is attached to the second closure link 1038 as will be discussed in further detail below. In at least one example, the closure member assembly 3000 comprises a proximal closure member segment 3010 that has a proximal end 3012 that is coupled to the closure shuttle 1250 for relative rotation thereto. For example, a U shaped connector 1263 is inserted into an annular slot 3014 in the proximal end 3012 of the proximal closure member segment 3010 and is retained within vertical slots 1253 in the closure shuttle 1250. Such an arrangement serves to attach the proximal closure member segment 3010 to the closure shuttle 1250 for axial travel therewith while enabling the proximal closure member segment 3010 to rotate relative to the closure shuttle 1250 about the shaft axis SA. A closure spring 1268 is journaled on the proximal closure member segment 3010 and serves to bias the proximal closure member segment 3010 in the proximal direction "PD" which can serve to pivot the closure trigger 1032 into the unactuated position when the shaft assembly is operably coupled to the handle 1014.

[0512] In at least one form, the interchangeable shaft assembly 1200 may further include an articulation joint 3020. Other interchangeable shaft assemblies, however, may not be capable of articulation. As can be seen in FIG. 5, for example, a distal closure member or distal closure tube segment 3030 is coupled to the distal end of the proximal closure member segment 3010. The articulation joint 3020 includes a double pivot closure sleeve assembly 3022. According to various forms, the double pivot closure sleeve assembly 3022 includes an end effector closure tube 3050 having upper and lower distally projecting tangs 3052, 3054. An upper double pivot link 3056 includes upwardly projecting distal and proximal pivot pins that engage respectively an upper distal pin hole in the upper proximally projecting tang 3052 and an upper proximal pin hole in an upper distally projecting tang 3032 on the distal closure tube segment 3030. A lower double pivot link 3058 includes upwardly projecting distal and proximal pivot pins that engage respectively a lower distal pin hole in the lower proximally projecting tang 3054 and a lower proximal pin

hole in the lower distally projecting tang **3034**. See FIGS. **4** and **5**. As will be discussed in further detail below, the closure member assembly **3000** is translated distally (direction “DD”) to close the anvil **2000**, for example, in response to the actuation of the closure trigger **1032**. The anvil **2000** is opened by proximally translating the closure member assembly **3000** which causes the end effector closure tube **3050** to interact with the anvil **2000** and pivot it to an open position.

[0513] As was also indicated above, the interchangeable shaft assembly **1200** further includes a firing member **1900** that is supported for axial travel within the spine **1210**. The firing member **1900** includes an intermediate firing shaft portion **1222** that is configured for attachment to a distal cutting portion or knife bar **1910**. The intermediate firing shaft portion **1222** may include a longitudinal slot **1223** in the distal end thereof which can be configured to receive a tab **1912** on the proximal end of the distal knife bar **1910**. The longitudinal slot **1223** and the proximal end tab **1912** can be sized and configured to permit relative movement therebetween and can comprise a slip joint **1914**. The slip joint **1914** can permit the intermediate firing shaft portion **1222** of the firing member **1900** to be moved to articulate the end effector **1300** without moving, or at least substantially moving, the knife bar **1910**. Once the end effector **1300** has been suitably oriented, the intermediate firing shaft portion **1222** can be advanced distally until a proximal sidewall of the longitudinal slot **1223** comes into contact with the tab **1912** in order to advance the knife bar **1910** and fire the staple cartridge **4000** positioned within the channel **1310**. The knife bar **1910** includes a knife portion **1920** that includes a blade or tissue cutting edge **1922** and includes an upper anvil engagement tab **1924** and lower channel engagement tabs **1926**. Various firing member configurations and operations are disclosed in various other references incorporated herein by reference.

[0514] As can be seen in FIG. **4**, the shaft assembly **1200** further includes a switch drum **1500** that is rotatably received on proximal closure member segment **3010**. The switch drum **1500** comprises a hollow shaft segment **1502** that has a shaft boss formed thereon for receive an outwardly protruding actuation pin therein. In various circumstances, the actuation pin extends through a longitudinal slot provided in the lock sleeve to facilitate axial movement of the lock sleeve when it is engaged with the articulation driver. A rotary torsion spring **1420** is configured to engage the boss on the switch drum **1500** and a portion of the nozzle housing **1203** to apply a biasing force to the switch drum **1500**. The switch drum **1500** can further comprise at least partially circumferential openings **1506** defined therein which can be configured to receive circumferential mounts extending from the nozzle portions **1202**, **1203** and permit relative rotation, but not translation, between the switch drum **1500** and the nozzle **1201**. The mounts also extend through openings **3011** in the proximal closure member segment **3010** to be seated in recesses **1219** in the spine **1210**. Rotation of the switch drum **1500** about the shaft axis SA will ultimately result in the rotation of the actuation pin and the lock sleeve between its engaged and disengaged positions. In one arrangement, the rotation of the switch drum **1500** may be linked to the axial advancement of the closure tube or closure member. Thus, in essence, actuation of the closure system may operably engage and disengage the articulation drive system with the firing drive system in the

various manners described in further detail in U.S. patent application Ser. No. 13/803,086, now U.S. Patent Application Publication No. 2014/0263541, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING AN ARTICULATION LOCK and U.S. Pat. No. 9,913,642, entitled SURGICAL INSTRUMENT COMPRISING A SENSOR SYSTEM, the entire disclosures of each being hereby incorporated by reference herein. For example, when the closure member segment **3010** is in its proximal-most position corresponding to a “jaws open” position, the closure member segment **3010** will have positioned the switch drum **1500** so as to link the articulation system with the firing drive system. When, the closure tube has been moved to its distal position corresponding to a “jaws closed” position, the closure tube has rotated the switch drum **1500** to a position wherein the articulation system is delinked from the firing drive system.

[0515] As also illustrated in FIG. **4**, the shaft assembly **1200** can comprise a slip ring assembly **1600** which can be configured to conduct electrical power to and/or from the end effector **1300** and/or communicate signals to and/or from the end effector **1300**, for example. The slip ring assembly **1600** can comprise a proximal connector flange **1604** that is mounted to a chassis flange **1242** that extends from the chassis **1240** and a distal connector flange that is positioned within a slot defined in the shaft housings. The proximal connector flange **1604** can comprise a first face and the distal connector flange can comprise a second face which is positioned adjacent to and movable relative to the first face. The distal connector flange can rotate relative to the proximal connector flange **1604** about the shaft axis SA. The proximal connector flange **1604** can comprise a plurality of concentric, or at least substantially concentric, conductors defined in the first face thereof. A connector can be mounted on the proximal side of the connector flange and may have a plurality of contacts wherein each contact corresponds to and is in electrical contact with one of the conductors. Such an arrangement permits relative rotation between the proximal connector flange **1604** and the distal connector flange while maintaining electrical contact therebetween. The proximal connector flange **1604** can include an electrical connector **1606** which can place the conductors in signal communication with a shaft circuit board **1610** mounted to the shaft chassis **1240**, for example. In at least one instance, a wiring harness comprising a plurality of conductors can extend between the electrical connector **1606** and the shaft circuit board **1610**. The electrical connector **1606** may extend proximally through a connector opening **1243** defined in the chassis flange **1242**. See FIG. **4**. Further details regarding slip ring assembly **1600** may be found in U.S. patent application Ser. No. 13/803,086, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING AN ARTICULATION LOCK, now U.S. Patent Application Publication No. 2014/0263541, U.S. patent application Ser. No. 13/800,067, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, filed on Mar. 13, 2013, now U.S. Patent Application Publication No. 2014/0263552, and U.S. Pat. No. 9,345,481, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, for example. U.S. patent application Ser. No. 13/803,086, now U.S. Patent Application Publication No. 2014/0263541, U.S. patent application Ser. No. 13/800,067, now U.S. Patent Application Publication No. 2014/0263552,

and U.S. Pat. No. 9,345,481 are each hereby incorporated by reference herein in their respective entireties.

[0516] As discussed above, the shaft assembly 1200 can include a proximal portion which is fixably mounted to the handle 1014 and a distal portion which is rotatable about a longitudinal axis. The rotatable distal shaft portion can be rotated relative to the proximal portion about the slip ring assembly 1600, as discussed above. The distal connector flange of the slip ring assembly 1600 can be positioned within the rotatable distal shaft portion. Moreover, further to the above, the switch drum 1500 can also be positioned within the rotatable distal shaft portion. When the rotatable distal shaft portion is rotated, the distal connector flange and the switch drum 1500 can be rotated synchronously with one another. In addition, the switch drum 1500 can be rotated between a first position and a second position relative to the distal connector flange. When the switch drum 1500 is in its first position, the articulation drive system may be operably disengaged from the firing drive system and, thus, the operation of the firing drive system may not articulate the end effector 1300 of the shaft assembly 1200. When the switch drum 1500 is in its second position, the articulation drive system may be operably engaged with the firing drive system and, thus, the operation of the firing drive system may articulate the end effector 1300 of the shaft assembly 1200. When the switch drum 1500 is moved between its first position and its second position, the switch drum 1500 is moved relative to distal connector flange. In various instances, the shaft assembly 1200 can comprise at least one sensor configured to detect the position of the switch drum 1500.

[0517] Referring again to FIG. 4, the chassis 1240 includes at least one, and preferably two, tapered attachment portions 1244 formed thereon that are adapted to be received within corresponding dovetail slots 1702 formed within a distal attachment flange portion 1700 of the frame 1020. See FIG. 3. Each dovetail slot 1702 may be tapered or, stated another way, be somewhat V-shaped to seatingly receive the attachment portions 1244 therein. As can be further seen in FIG. 4, a shaft attachment lug 1226 is formed on the proximal end of the intermediate firing shaft portion 1222. As will be discussed in further detail below, when the interchangeable shaft assembly 1200 is coupled to the handle 1014, the shaft attachment lug 1226 is received in a firing shaft attachment cradle 1126 formed in a distal end 1125 of the longitudinal drive member 1120. See FIG. 3.

[0518] Various shaft assembly embodiments employ a latch system 1710 for removably coupling the shaft assembly 1200 to the housing 1012 and more specifically to the frame 1020. As can be seen in FIG. 4, for example, in at least one form, the latch system 1710 includes a lock member or lock yoke 1712 that is movably coupled to the chassis 1240. In the illustrated embodiment, for example, the lock yoke 1712 has a U-shape with two spaced downwardly extending legs 1714. The legs 1714 each have a pivot lug 1715 formed thereon that are adapted to be received in corresponding holes 1245 formed in the chassis 1240. Such arrangement facilitates pivotal attachment of the lock yoke 1712 to the chassis 1240. The lock yoke 1712 may include two proximally protruding lock lugs 1716 that are configured for releasable engagement with corresponding lock detents or grooves 1704 in the distal attachment flange portion 1700 of the frame 1020. See FIG. 3. In various forms, the lock yoke 1712 is biased in the proximal direction by spring or biasing

member (not shown). Actuation of the lock yoke 1712 may be accomplished by a latch button 1722 that is slidably mounted on a latch actuator assembly 1720 that is mounted to the chassis 1240. The latch button 1722 may be biased in a proximal direction relative to the lock yoke 1712. As will be discussed in further detail below, the lock yoke 1712 may be moved to an unlocked position by biasing the latch button in the distal direction which also causes the lock yoke 1712 to pivot out of retaining engagement with the distal attachment flange portion 1700 of the frame 1020. When the lock yoke 1712 is in “retaining engagement” with the distal attachment flange portion 1700 of the frame 1020, the lock lugs 1716 are retainingly seated within the corresponding lock detents or grooves 1704 in the distal attachment flange portion 1700.

[0519] When employing an interchangeable shaft assembly that includes an end effector of the type described herein that is adapted to cut and fasten tissue, as well as other types of end effectors, it may be desirable to prevent inadvertent detachment of the interchangeable shaft assembly from the housing during actuation of the end effector. For example, in use the clinician may actuate the closure trigger 1032 to grasp and manipulate the target tissue into a desired position. Once the target tissue is positioned within the end effector 1300 in a desired orientation, the clinician may then fully actuate the closure trigger 1032 to close the anvil 2000 and clamp the target tissue in position for cutting and stapling. In that instance, the first drive system 1030 has been fully actuated. After the target tissue has been clamped in the end effector 1300, it may be desirable to prevent the inadvertent detachment of the shaft assembly 1200 from the housing 1012. One form of the latch system 1710 is configured to prevent such inadvertent detachment.

[0520] As can be most particularly seen in FIG. 4, the lock yoke 1712 includes at least one and preferably two lock hooks 1718 that are adapted to contact corresponding lock lug portions 1256 that are formed on the closure shuttle 1250. When the closure shuttle 1250 is in an unactuated position (i.e., the first drive system 1030 is unactuated and the anvil 2000 is open), the lock yoke 1712 may be pivoted in a distal direction to unlock the interchangeable shaft assembly 1200 from the housing 1012. When in that position, the lock hooks 1718 do not contact the lock lug portions 1256 on the closure shuttle 1250. However, when the closure shuttle 1250 is moved to an actuated position (i.e., the first drive system 1030 is actuated and the anvil 2000 is in the closed position), the lock yoke 1712 is prevented from being pivoted to an unlocked position. Stated another way, if the clinician were to attempt to pivot the lock yoke 1712 to an unlocked position or, for example, the lock yoke 1712 was inadvertently bumped or contacted in a manner that might otherwise cause it to pivot distally, the lock hooks 1718 on the lock yoke 1712 will contact the lock lug portions 1256 on the closure shuttle 1250 and prevent movement of the lock yoke 1712 to an unlocked position.

[0521] Attachment of the interchangeable shaft assembly 1200 to the handle 1014 will now be described. To commence the coupling process, the clinician may position the chassis 1240 of the interchangeable shaft assembly 1200 above or adjacent to the distal attachment flange portion 1700 of the frame 1020 such that the tapered attachment portions 1244 formed on the chassis 1240 are aligned with the dovetail slots 1702 in the frame 1020. The clinician may then move the shaft assembly 1200 along an installation axis

that is perpendicular to the shaft axis SA to seat the attachment portions **1244** in “operable engagement” with the corresponding dovetail receiving slots **1702**. In doing so, the shaft attachment lug **1226** on the intermediate firing shaft portion **1222** will also be seated in the cradle **1126** in the longitudinally movable drive member **1120** and the portions of the pin **1037** on the second closure link **1038** will be seated in the corresponding hooks **1252** in the closure shuttle **1250**. As used herein, the term “operable engagement” in the context of two components means that the two components are sufficiently engaged with each other so that upon application of an actuation motion thereto, the components may carry out their intended action, function and/or procedure.

[0522] At least five systems of the interchangeable shaft assembly **1200** can be operably coupled with at least five corresponding systems of the handle **1014**. A first system can comprise a frame system which couples and/or aligns the frame or spine of the shaft assembly **1200** with the frame **1020** of the handle **1014**. Another system can comprise a closure drive system **1030** which can operably connect the closure trigger **1032** of the handle **1014** and the closure tube **1260** and the anvil **2000** of the shaft assembly **1200**. As outlined above, the closure shuttle **1250** of the shaft assembly **1200** can be engaged with the pin **1037** on the second closure link **1038**. Another system can comprise the firing drive system **1080** which can operably connect the firing trigger **1130** of the handle **1014** with the intermediate firing shaft portion **1222** of the shaft assembly **1200**. As outlined above, the shaft attachment lug **1226** can be operably connected with the cradle **1126** of the longitudinal drive member **1120**. Another system can comprise an electrical system which can signal to a controller in the handle **1014**, such as microcontroller, for example, that a shaft assembly, such as shaft assembly **1200**, for example, has been operably engaged with the handle **1014** and/or, two, conduct power and/or communication signals between the shaft assembly **1200** and the handle **1014**. For instance, the shaft assembly **1200** can include an electrical connector **1810** that is operably mounted to the shaft circuit board **1610**. The electrical connector **1810** is configured for mating engagement with a corresponding electrical connector **1800** on the handle control board **1100**. Further details regarding the circuitry and control systems may be found in U.S. patent application Ser. No. 13/803,086, now U.S. Patent Application Publication No. 2014/0263541, and U.S. patent application Ser. No. 14/226,142, now U.S. Pat. No. 9,913,642, the entire disclosures of each which were previously incorporated by reference herein. The fifth system may consist of the latching system for releasably locking the shaft assembly **1200** to the handle **1014**.

[0523] The anvil **2000** in the illustrated example includes an anvil body **2002** that terminates in an anvil mounting portion **2010**. The anvil mounting portion **2010** is movably or pivotally supported on the elongate channel **1310** for selective pivotal travel relative thereto about a fixed anvil pivot axis PA that is transverse to the shaft axis SA. In the illustrated arrangement, a pivot member or anvil trunnion **2012** extends laterally out of each lateral side of the anvil mounting portion **2010** to be received in a corresponding trunnion cradle **1316** formed in the upstanding walls **1315** of the proximal end portion **1312** of the elongate channel **1310**. The anvil trunnions **2012** are pivotally retained in their corresponding trunnion cradle **1316** by the channel cap or anvil retainer **1290**. The channel cap or anvil retainer **1290**

includes a pair of attachment lugs that are configured to be retainingly received within corresponding lug grooves or notches formed in the upstanding walls **1315** of the proximal end portion **1312** of the elongate channel **1310**. See FIG. 5.

[0524] Still referring to FIG. 5, in at least one arrangement, the distal closure member or end effector closure tube **3050** employs two axially offset, proximal and distal positive jaw opening features **3060** and **3062**. The positive jaw opening features **3060**, **3062** are configured to interact with corresponding relieved areas and stepped portions formed on the anvil mounting portion **2010** as described in further detail in U.S. patent application Ser. No. 15/635,631, entitled SURGICAL INSTRUMENT WITH AXIALLY MOVABLE CLOSURE MEMBER, now U.S. Pat. No. 10,639,037, the entire disclosure which has been herein incorporated by reference. Other jaw opening arrangements may be employed.

[0525] FIGS. 6-8 depict a previous surgical cutting and fastening instrument **5010** that is configured to generate rotary drive motions for operating a surgical end effector **5012**. The endoscopic surgical instrument **5010** comprises a handle **5006**, a shaft **5008**, and an articulating surgical end effector **5012** pivotally connected to the shaft **5008** at an articulation pivot **5014**. An articulation control **5016** may be provided adjacent to the handle **5006** to effect rotation of the end effector **5012** about the articulation pivot **5014**. It will be appreciated that various embodiments may include a non-pivoting end effector, and therefore may not have an articulation pivot **5014** or articulation control **5016**.

[0526] The handle **5006** of the instrument **5010** may include a closure trigger **5018** and a firing trigger **5020** for actuating the end effector **5012**. It will be appreciated that instruments having end effectors directed to different surgical tasks may have different numbers or types of triggers or other suitable controls for operating the end effector **5012**. In one embodiment, a clinician or operator of the instrument **5010** may articulate the end effector **5012** relative to the shaft **5008** by utilizing the articulation control **5016**, as described in more detail in pending U.S. Pat. No. 7,670,334, entitled SURGICAL INSTRUMENT HAVING AN ARTICULATING END EFFECTOR, the entire disclosure of which is incorporated herein by reference. The end effector **5012** includes in this example, among other things, a staple channel **5022** and a pivotally translatable clamping member, such as an anvil **5024**, which are maintained at a spacing that assures effective stapling and severing of tissue clamped in the end effector **5012**. The handle **5006** includes a pistol grip **5026** toward which the closure trigger **5018** is pivotally drawn by the clinician to cause clamping or closing of the anvil **5024** towards the staple channel **5022** of the end effector **5012** to thereby clamp tissue positioned between the anvil **5024** and channel **5022**.

[0527] In the arrangement depicted in FIG. 7, the end effector **5012** includes, in addition to the previously-mentioned channel **5022** and anvil **5024**, a cutting instrument **5032**, a sled **5033**, a staple cartridge **5034** that is removably seated in the channel **5022**, and a helical screw shaft **5036**. The cutting instrument **5032** may be, for example, a knife. The anvil **5024** includes pivot pins **5025** that are movably supported in corresponding slots in the channel **5022**. In one arrangement, the anvil **5024** includes a tab **5027** at its proximate end that is inserted into a component of the mechanical closure system (described further below) to open and close the anvil **5024**.

[0528] Still referring to FIG. 7, the shaft 5008 includes a proximal closure tube 5040 and a distal closure tube 5042 pivotably linked by a pivot link 5044. The distal closure tube 5042 includes an opening 5045 into which the tab 5027 on the anvil 5024 is inserted in order to open and close the anvil 5024, as further described below. Disposed inside the closure tubes 5040, 5042 may be a proximate spine tube 5046. Disposed inside the proximate spine tube 5046 may be a main rotational (or proximate) drive shaft 5048 that communicates with a secondary (or distal) drive shaft 5050 via a bevel gear assembly 5052a-c. The secondary drive shaft 5050 is connected to a drive gear 5054 that engages a proximate drive gear 5056 of the helical screw shaft 5036. The vertical bevel gear 5052b may sit and pivot in an opening 5057 in the distal end of the proximate spine tube 5046. A distal spine tube 5058 may be used to enclose the secondary drive shaft 5050 and the drive gears 5054, 5056. Collectively, the main drive shaft 5048, the secondary drive shaft 5050, and the articulation assembly (e.g., the bevel gear assembly 5052a-c) are sometimes referred to herein as the “main drive shaft assembly.”

[0529] A bearing 5038, positioned at a distal end of the staple channel 5022, receives the helical screw shaft 5036, allowing the helical screw shaft 5036 to freely rotate with respect to the channel 5022. The helical screw shaft 5036 may interface a threaded opening (not shown) of the knife 5032 such that rotation of the helical screw shaft 5036 causes the knife 5032 to translate distally or proximally (depending on the direction of the rotation) through the staple channel 5022.

[0530] Turning next to FIG. 8, the handle 5006 includes exterior lower side pieces 5059, 5060 and nozzle pieces 5061, 5062 that fit together to form, in general, the exterior of the handle 5006. A battery 5064, such as a Li ion battery, may be provided in the pistol grip 5026 of the handle 5006. The battery 5064 powers a motor 5065 disposed in an upper portion of the pistol grip portion 5026 of the handle 5006. The motor 5065 may drive a 90° bevel gear assembly 5066 comprising a first bevel gear 5068 and a second bevel gear 5070. The bevel gear assembly 5066 may drive a planetary gear assembly 5072. The planetary gear assembly 5072 may include a pinion gear 5074 connected to a drive shaft 5076. The pinion gear 5074 may drive a mating ring gear 5078 that drives a helical gear drum 5080 via a drive shaft. A ring 5084 may be threaded on the helical gear drum 5080. Thus, when the motor 5065 rotates, the ring 5084 is caused to travel along the helical gear drum 5080 by means of the interposed bevel gear assembly 5066, planetary gear assembly 5072 and ring gear 5078.

[0531] The handle 5006 may include a middle handle piece 5104 adjacent to the upper portion of the firing trigger 5020. The handle 5006 also may comprise a bias spring 5112 connected between posts on the middle handle piece 5104 and the firing trigger 5020. The bias spring 5112 may bias the firing trigger 5020 to its fully open position. In that way, when the operator releases the firing trigger 5020, the bias spring 5112 will pull the firing trigger 5020 to its open position. The distal end of the helical gear drum 5080 includes a distal drive shaft 5120 that drives a ring gear 5122, which mates with a pinion gear 5124. The pinion gear 5124 is connected to the main drive shaft 5048 of the main drive shaft assembly. In that way, rotation of the motor 5065 causes the main drive shaft assembly to rotate, which causes actuation of the end effector 5012. The ring 5084 threaded

on the helical gear drum 5080 may include a post 5086 that is disposed within a slot 5088 of a slotted arm 5090. The slotted arm 5090 has an opening 5092 in its opposite end 5094 that receives a pivot pin 5096 that is connected between the handle exterior side pieces 5059, 5060. The pivot pin 5096 is also disposed through an opening 5100 in the firing trigger 5020 and an opening 5102 in the middle handle piece 5104.

[0532] The middle handle piece 5104 includes a backside shoulder 5106 that engages the slotted arm 5090. The middle handle piece 5104 also has a forward motion stop 5107 that engages the firing trigger 5020. The movement of the slotted arm 5090 is controlled by rotation of the motor 5065. When the slotted arm 5090 rotates counter clockwise as the ring 5084 travels from the proximate end of the helical gear drum 5080 to the distal end, the middle handle piece 5104 will be free to rotate counter clockwise. Thus, as the user draws in the firing trigger 5020, the firing trigger 5020 will engage the forward motion stop 5107 of the middle handle piece 5104, causing the middle handle piece 5104 to rotate counter clockwise. Due to the backside shoulder 5106 engaging the slotted arm 5090, however, the middle handle piece 5104 will only be able to rotate counter clockwise as far as the slotted arm 5090 permits. In that way, if the motor 5065 should stop rotating for some reason, the slotted arm 5090 will stop rotating, and the user will not be able to further draw in the firing trigger 5020 because the middle handle piece 5104 will not be free to rotate counter clockwise due to the slotted arm 5090.

[0533] Components of an exemplary closure system for closing (or clamping) the anvil 5024 of the end effector 5012 by retracting the closure trigger 5018 are also shown in FIG. 8. In the illustrated embodiment, the closure system includes a yoke 5250 connected to the closure trigger 5018. A pivot pin 5252 is inserted through aligned openings in both the closure trigger 5018 and the yoke 5250 such that they both rotate about the same point. The distal end of the yoke 5250 is connected, via a pin 5254, to a first closure bracket 5256. The first closure bracket 5256 connects to a second closure bracket 5258. Collectively, the closure brackets 5256, 5258 define an opening in which the proximate end of the proximal closure tube 5040 (see FIG. 7) is seated and held such that longitudinal movement of the closure brackets 5256, 5258 causes longitudinal motion by the proximal closure tube 5040. The instrument 5010 also includes a closure drive shaft 5260 disposed inside the proximal closure tube 5040. The closure drive shaft 5260 may include a window 5261 into which a post 5263 on one of the handle exterior pieces, such as exterior lower side piece 5059 in the illustrated embodiment, is disposed to fixedly connect the closure drive shaft 5260 to the handle 5006. In that way, the proximal closure tube 5040 is capable of moving longitudinally relative to the closure drive shaft 5260. The closure drive shaft 5260 may also include a distal collar 5267 that fits into a cavity in proximate spine tube 5046 and is retained therein by a cap.

[0534] In operation, when the yoke 5250 rotates due to retraction of the closure trigger 5018, the closure brackets 5256, 5258 cause the proximal closure tube 5040 to move distally (i.e., away from the handle end of the instrument 5010), which causes the distal closure tube 5042 to move distally, which causes the anvil 5024 to rotate about the pivot pins 5025 into the clamped or closed position. When the closure trigger 5018 is unlocked from the locked position,

the proximal closure tube **5040** is caused to slide proximally, which causes the distal closure tube **5042** to slide proximally, which, by virtue of the tab **5027** being inserted in the opening **5045** of the distal closure tube **5042**, causes the anvil **5024** to pivot about the pivot pins **5025** into the open or unclamped position. In that way, by retracting and locking the closure trigger **5018**, an operator may clamp tissue between the anvil **5024** and channel **5022**, and may unclamp the tissue following the cutting/stapling operation by unlocking the closure trigger **5018** from the locked position. Further details concerning the construction and operation of the existing surgical instrument **5010** may be found in U.S. Pat. No. 7,845,537, entitled SURGICAL INSTRUMENT HAVING RECORDING CAPABILITIES, the entire disclosure of which is hereby incorporated by reference herein. Other rotary drive arrangements configured for use with various forms of robotic systems are disclosed in U.S. Pat. No. 10,213,201, entitled STAPLING END EFFECTOR CONFIGURED TO COMPENSATE FOR AN UNEVEN GAP BETWEEN A FIRST JAW AND A SECOND JAW, the entire disclosure of which is hereby incorporated by reference herein.

[0535] FIGS. 9-16 depict a surgical end effector **20012** that may be used for example in connection with the powered surgical instrument **5010** described above. The surgical end effector **20012** may also be effectively employed with various other rotary powered or robotically powered surgical systems which are disclosed in the various references incorporated herein by reference. Those components shown in FIGS. 9-16 that are identical to the components of the powered surgical instrument **5010** have been labeled with like component numbers. In the illustrated example, the surgical end effector **20012** comprises an elongate channel **20020** that is configured to operably support a surgical staple cartridge **20040** therein. The elongate channel **20020** is similar to channel **5022** described above, except for the noted differences. Turning to FIG. 10, the elongate channel **20020** comprises a pair of spaced upstanding walls **20022** and a bottom **20024**. A helical screw shaft **5036** is supported in the channel **20020** by a bearing **5038** which enables the helical screw shaft **5036** to freely rotate with respect to the channel **20020**. The surgical end effector **20012** further comprises an anvil **5024** that has pivot pins or trunnions **5025** that are received in corresponding slots **20026** provided in the upstanding channel walls **20022**.

[0536] In the illustrated arrangement, the staple cartridge **20040** includes an elongate cartridge body **20042** that is sized to be removably seated in the elongate channel **20020**. The cartridge body **20042** includes a cartridge slot **20050** that extends from a proximal end portion **20046** to a distal end portion **20044** of the cartridge body **20042**. The cartridge body **20042** further comprises a cartridge deck surface **20043** that confronts a staple-forming undersurface **5029** of the anvil **5024** when the cartridge **20040** is seated in the channel **20020** and the anvil **5024** is pivoted to a closed position. Also in the illustrated example, three lines of surgical staple pockets **20052** are formed on each side of the cartridge slot **20050** and open through the cartridge deck surface **20043**. Each staple pocket **20052** may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon.

[0537] Still referring to FIG. 10, the staple cartridge **20040** further includes a camming assembly **20060** that comprises a camming assembly body **20062** that has a passage **20064**

therethrough that is configured to straddle the helical screw shaft **5036** without affecting the rotation thereof. In other embodiments, the camming assembly **20060** may have a series of internal threads (not shown) that are configured to threadably engage the helical screw shaft **5036** to be driven thereby. In such arrangements, for example, the helical screw shaft **5036** may be provided with an unthreaded portion that corresponds to a starting position of the camming assembly **20060**. Such camming assembly arrangements are further described in various references that have been herein incorporated by reference. In the illustrated example, the camming assembly **20060** is driven distally through the cartridge body **20042** by a firing member **20120**.

[0538] As can further be seen in FIG. 10, the camming assembly body **20062** includes a series of cam members **20066** that are aligned with corresponding staple drivers supported in lines within the staple cartridge body **20042**. In the illustrated example, the camming assembly **20060** includes an onboard tissue cutting member or blade **20068**. The tissue cutting member **20068** extends above the deck surface **20043** so that as the camming assembly **20060** is driven distally, the tissue cutting member **20068** cuts the tissue that is clamped between the anvil **5024** and the staple cartridge **20040**. When the staple cartridge is “fresh” or new (i.e., the cartridge has never been fired and contains staples or fasteners therein ready to be fired), the camming assembly **20060** is in a starting position within the cartridge **20040**. When the camming assembly **20060** is in the starting position, the tissue cutting member **20068** is located within a garage portion **20048** formed on the proximal end portion **20046** of the cartridge body **20042** to prevent injury when handling the fresh cartridge **20040**. In one aspect, the cam members **20066** extend distally beyond the tissue cutting member **20068** such that the staples or fasteners are deployed through the tissue before the tissue cutting member **20068** cuts through the tissue. Thus, the clamped tissue is stapled and thereafter cut as the firing member **20120** and camming assembly **20060** are driven distally. Once the firing member **20120** and the camming assembly **20060** have been driven into their distal-most ending positions, the firing member **20120** may be retracted back to its starting position by rotating the helical screw shaft **5036** in a reverse rotary direction while the camming assembly **20060** remains in its ending position. In at least one arrangement, the tissue cutting member **20068** is movable from a deployed cutting position to a storage position wherein the tissue cutting member **20068** is stored below the cartridge deck surface **20043** to prevent injury when handling the fired or spent cartridge **20040**. For example, a retraction member (not shown) may be strategically located in the distal end **20044** of the cartridge body **20042** to contact and move the tissue cutting member **20068** from the deployed position to the storage position when a portion of the tissue cutting member **20068** is brought into contact with the retraction member.

[0539] FIG. 11 depicts one form of a firing member **20120**. As can be seen in FIG. 11, the firing member **20120** comprises a body portion **20122** that includes two downwardly extending hollow mounting portions **20124** that are unthreaded and spaced from each other to receive a threaded drive nut **20130** therebetween. The threaded drive nut **20130** is configured to threadably engage the helical screw shaft **5036**. The drive nut **20130** includes a vertical tab portion **20131** that is sized to extend through an axial slot **20025** (FIG. 10) in the bottom **20024** of the elongate channel

20020. Two laterally extending retention flanges **20134** are formed on the threaded drive nut **20130** and are configured to engage the bottom **20024** of the elongate channel **20020**. In addition, two laterally extending anvil engagement tabs **20126** are formed on the top of the firing member body **20122** and are configured to engage corresponding ledges **20102** formed in the anvil **5024** as the firing member **20120** is axially moved within the surgical end effector **20012**.

[0540] As can also be seen in FIG. 11, the firing member **20120** may also be equipped with an onboard firing member lockout assembly **20140** that comprises a lockout member **20142** that is pivotally coupled to the firing member body **20122**. The lockout member **20142** includes a sled latch **20148** that is configured to be engaged by the camming assembly **20060** when the camming assembly **20060** is in an unfired position. As can be seen in FIGS. 12 and 13, the camming assembly **20060** includes a firing member ledge **20061** configured to engage the sled latch **20148** on the lockout member **20142**. A lockout spring **20150** is mounted in the elongate channel **20020** and is configured to bias the lockout member **20142** downward such that if the camming assembly **20060** is not in its unfired starting position, the lockout member **20142** contacts lockout lugs **20028** that are formed on portions of the inside surface of each upstanding sidewall **20022** of the elongate channel **20020**. See FIG. 15. When in that position, should the user inadvertently attempt to distally advance the firing member **20120**, the lockout member **20142** contacts the lockout lugs **20028** on the channel **20020** to prevent the distal advancement of the firing member **20120**.

[0541] FIG. 12 illustrates the initial insertion of a fresh unfired surgical staple cartridge **20040** into the channel **20020**. As can be seen in FIG. 12, the camming assembly **20060** is in a starting position and the proximal end portion **20046** of the surgical staple cartridge **20040** is inserted at an angle relative to the channel **20020** and then pushed in the proximal direction PD until the firing member ledge **20061** on the camming assembly **20060** unlockingly engages the sled latch portion **20148** of the lockout member **20142**. FIGS. 13 and 14 illustrate the surgical staple cartridge **20040** in a properly installed position. As can be seen in FIG. 13, the firing member lockout assembly **20140** is in an unlocked position. Rotary actuation of the helical screw shaft **5036** in a first rotary direction will cause the firing member **20120** to move distally in the distal direction DD. As the firing member **20120** moves distally, the camming assembly **20060** is also driven distally thereby. The cam members **20066** cam the drivers stored in the cartridge **20040** upward in the cartridge body **20042**. As the drivers are cammed upwardly, the staples or fasteners supported thereon are driven through the tissue that has been clamped between the anvil **5024** and the cartridge **20040** and into forming contact with the staple-forming undersurface **5029** on the anvil **5024**. The stapled tissue is then cut by the tissue cutting member **20068**. Once the firing member **20120** has been driven to its distalmost position in the cartridge **20040**, the helical screw shaft **5036** may be rotated in a second opposite rotary direction to retract the firing member **20120** back to its beginning position. The camming assembly **20060** remains in the distal end portion **20044** of the cartridge body **20042**. The spent cartridge **20040** may then be removed from the channel **20020**.

[0542] FIG. 14 illustrates the end effector **20012** after the spent cartridge has been removed from the channel **20020**.

As can be seen in FIG. 14, the spring **20150** biases the lockout member **20142** of the firing member lockout assembly **20140** into locking engagement with the lockout lugs **20028** in the channel **20020**. Should the user attempt to fire the surgical end effector **20012** (distally advance the firing member **20120**), the lockout member **20142** will prevent the firing member **20120** from moving distally. Likewise, should the user attempt to reuse the spent cartridge, because the camming assembly **20060** is not in the starting position, the firing member lockout assembly **20140** will prevent the distal advancement of the firing member **20120**.

[0543] In the illustrated arrangement, the lockout member **20142** is pivotally coupled to the firing member body **20122** by pivot pins **20143** that are received in a hole **20123** extending through the firing member body **20122**. See FIGS. 14 and 16. In at least one arrangement, the pivot pins **20143** are sized relative to the holes **20123** in the firing member body **20122** to facilitate free pivotal travel of the lockout member **20142** and to account for tolerance differences of the components. As can be seen in FIG. 14, the firing member **20120** includes a proximally-facing, firing surface **20145** that is configured to abut a distal-facing bearing surface **20125** on the firing member body **20122** when the firing member lockout assembly **20140** is in the unlocked position. Thus, when the firing member **20120** is advanced distally, the resistive forces encountered by the camming assembly **20060** during its distal movement are directly applied to the distal-facing bearing surface **20125** on the firing member body **20122**. Such arrangement may prevent the transfer of these resistive forces back to the pivot pins **20143**, which might cause the pivot pins **20143** to fail under such load. Similarly, as can be seen in FIG. 16, the proximally-facing angled bearing surface **20145** of the firing member **20120** is configured to abut the distal-facing bearing surface **20125** on the firing member body **20122** when the firing member lockout assembly **20140** is in the locked position. Such arrangement may prevent the transfer of the resistive locking forces resulting from the locking engagement of the lockout member **20142** with the lock lugs **20028** back to the pivot pins **20143**, which might cause the pivot pins **20143** to fail under such load. The loose fit between the pins **20143** and the hole **20123** in the firing member body **20122** facilitate some translation of the lockout member **20142** when under load to facilitate transfer of the loads into the firing member body **20122** and not to the pins **20143** themselves.

[0544] In another arrangement, or in addition to the foregoing described lockout member **20142** arrangement, the amount of current being drawn by the motor used to apply the rotary motions to the helical screw shaft **5036** is monitored. Once the current increases beyond a predetermined threshold, a control circuit for the surgical instrument or robotic system, etc., may stop the motor to prevent any further rotation of the helical screw shaft **5036** and movement of the firing member **20120** to prevent damage to the above-described components.

[0545] Some previous firing member lockout arrangements that are configured to prevent advancement of a firing member of the end effector unless a fresh unfired staple cartridge has been properly installed in the surgical end effector, require the user to actively retract the firing member back to its proximal-most beginning position before the anvil is permitted to open. If the user attempts to open the anvil before the firing member is moved back to its proximal-most

position, the may not understand why the anvil cannot come open. The above-described arrangement may prevent such confusion.

[0546] FIGS. 17-21 depict a surgical end effector 20300 that may be used for example in connection with the powered surgical instrument 1010 described above. The surgical end effector 20300 may also be effectively employed with various other robotically powered surgical systems which are disclosed in the various references incorporated herein by reference. Those components shown in FIGS. 17-21 that are identical to the components of surgical instrument 1010 have been labeled with like component numbers. Those construction and function of those components of surgical instrument 1010 that are not necessary to understand the operation of the surgical end effector 20300 will not be repeated herein for the sake of brevity.

[0547] Referring to FIGS. 17-21, the surgical end effector 20300 comprises an elongate channel 20310 that is configured to operably support a surgical staple cartridge 20600 therein. In the illustrated example, the elongate channel 20310 comprises a channel bottom 20312 and a pair of upstanding sidewalls 20314. The channel 20310 is coupled to the elongate shaft assembly 1200 (FIG. 5) by a channel mount feature 20340 which may facilitate articulation thereof about articulation joint 3020 (FIG. 5). As can be seen in FIG. 19, in one arrangement for example, the channel mount feature 20340 comprises a body portion 20342 that consists of an upstanding support 20344 that has a slot 20346 extending therethrough to receive the firing member beam 1900 (FIG. 5) therethrough. The channel mount feature 20340 may be movably or pivotally mounted to a proximal end 20316 of the channel 20310 by a channel mount feature, or channel pin 20320. In particular, the channel mount feature 20320 further includes a transverse pin opening 20348 that is configured to be coaxially aligned with holes 20318 in the sidewalls 20314 of the channel 20310 to receive the channel pin 20320 therethrough.

[0548] As described above, the shaft assembly 1200 includes a spine 1210 that terminates in an upper lug mount feature 1270 and in a lower lug mount feature 1280. See FIG. 5. The upper lug mount feature 1270 is formed with a lug slot 1272 therein that is adapted to mountingly support an upper mounting link 1274 therein. Similarly, the lower lug mount feature 1280 is formed with a lug slot 1282 therein that is adapted to mountingly support a lower mounting link 1284 therein. The upper mounting link 1274 includes a pivot socket 1276 therein that is adapted to rotatably receive therein a pivot pin 1292 that is formed on a channel cap or anvil retainer 1290 that is attached to the proximal end portion 20316 of the elongate channel 20310. As can be seen in FIG. 19, the channel mount feature 20340 further includes a shaft mount flange 20350 that extends proximally therefrom. In one arrangement for example, the shaft mount flange 20350 has a centrally disposed pivot hole 20352 therethrough that may pivotally receive the lower pivot pin 1286 on the lower mounting link 1284 of the lower lug mount feature 1280 (FIG. 5). The lower pivot pin 1286 is vertically aligned with the pivot socket 1276 to define an articulation axis AA about which the surgical end effector 20300 may articulate relative to the spine 1210. In one arrangement, the proximal articulation driver 2102 (FIG. 5) may be directly coupled to an articulation lug 20354 formed on the shaft mount flange 20350. In other arrangements, the proximal articulation driver 2102 may be attached to one or

more articulation links that are attached to the shaft mount flange 20350. In either case, axial movement of the proximal articulation driver 2102 in the above-described manner will cause the channel mount feature to pivot about the articulation axis relative to the spine 1210 (FIG. 5) to articulate the end effector 20300 about the articulation axis AA.

[0549] The surgical end effector 20300 further comprises an anvil 20400 that is very similar to anvil 2000 described above, except for the differences discussed below. The anvil 20400 includes an elongate anvil body portion 20402 that has a staple-forming undersurface 20404 and an anvil mounting portion 20410 that is configured to interact with the end effector closure tube 3050 (FIG. 5) in the manner described above. The anvil 20400 is pivotally mounted on the elongate channel 20310 by a pair of laterally extending anvil pins or trunnions 20412 that are received in corresponding elongate trunnion slots 20322 formed in the upstanding channel walls 20314. Axial movement of the end effector closure tube 3050 in a distal direction will cause the anvil 20400 to pivot to a closed position about a pivot axis defined by the anvil trunnions 20412 and movement of the end effector closure tube 3050 in a proximal direction will cause the anvil to pivot to an open position relative to the elongate channel 20310.

[0550] FIG. 22 illustrates one form of a staple cartridge 20600 that may be used in connection with the surgical end effector 20300. In at least one arrangement, the surgical staple cartridge 20600 comprises an elongate cartridge body 20602 that is sized to be removably seated in the elongate channel 20310. The cartridge body 20602 includes a cartridge slot 20608 that extends from a proximal end portion 20604 to a distal end portion 20606 (FIG. 17) of the cartridge body 20602. The cartridge body 20602 further comprises a cartridge deck surface 20610 that confronts the staple-forming undersurface 20404 of the anvil 20400 when the cartridge 20600 is seated in the channel 20310 and the anvil 20400 is pivoted to a closed position. Also in the illustrated example, three lines of surgical staple pockets 20612 are formed on each side of the cartridge slot 20608 and open through the cartridge deck surface 20610. Each staple pocket 20612 may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body 20602 is molded from a polymer material with the staple pockets 20612 molded or machined therein. In one arrangement, the staple pockets 20612 also open through a bottom of the cartridge body 20602 to facilitate installation of the drivers and fasteners into their respective pockets 20612. Once the drivers and fasteners are inserted into their respective staple pockets 20612, a cartridge pan 20620 is attached to the bottom of the cartridge body 20602. In one form, the cartridge pan 20620 is fabricated from a metal material and includes a bottom 20622 that spans across the bottom of the cartridge body 20602 and two upstanding sidewalls 20624 that correspond to each side of the cartridge body 20602. The cartridge pan 20620 may be removably affixed to the cartridge body 20602 by a series of hooks 20626 that are formed on the sidewalls 20624 and configured to hookingly engage corresponding portions of the cartridge body 20602. See FIG. 22. When installed, the cartridge pan 20620 may, among other things, prevent the drivers and fasteners from falling out of the bottom of the cartridge body 20602 during handling and installation of the cartridge 20600 into the elongate channel 20310.

[0551] As was discussed above in connection with cartridge 20040, cartridge 20600 operably supports a camming assembly therein. The camming assembly comprises a series of spaced cam members that are configured to move axially within corresponding cam slots 20609 formed on each side of the cartridge slot 20608 in the cartridge body 20602. The cam slots 20609 are aligned with corresponding lines of drivers in the cartridge body 20602 to facilitate camming contact with a corresponding cam member as the camming assembly is driven through the staple cartridge 20600 from a beginning position within the proximal end portion 20604 of the cartridge body 20602 to an ending position within the distal end portion 20606.

[0552] The example illustrated in FIGS. 20 and 21 also employs a firing member 20500 that is attached to a distal end of the firing member beam 1900 and is configured to operably interface with the camming assembly in the staple cartridge 20600 to driven the camming assembly from its starting position to its ending position within the cartridge 20600. In at least one arrangement, the firing member 20500 is configured to interact with a camming assembly (not shown) in a staple cartridge 20600 that has been properly installed in the elongate channel 20310. For example, the firing member 20500 includes a firing member body 20502 that has a tissue cutting surface or blade 20504 formed thereon or attached thereto. The firing member body 20502 is sized to axially move within an axial anvil slot (not shown) in the anvil 20400 as well as the cartridge slot 20608 in the cartridge body 20602 and a channel slot (not shown) in the elongate channel 20310. A lower foot assembly 20506 that comprises a pair of laterally extending lower flanges 20508 extends from a bottom end of the firing member body 20502 to slidably engage corresponding channel ledges (not shown) that are formed on each side of the channel slot. An upper foot (not shown) that comprises two laterally extending anvil tabs may be formed on an upper end of the firing member body 20502 and is configured to slidably engage anvil ledges (not shown) that are formed on each side of the anvil slot. In at least one arrangement, the firing member 20500 further includes a pair of central tabs 20510 that extend laterally from each side of the firing member body 20502.

[0553] Still referring to FIGS. 20 and 21, in one arrangement, the firing member body 20502 is configured with a proximally extending spring tail 20512 that may be configured to operably interface with a firing member lockout spring 20520 that is mounted in the elongate channel 20310 and is configured to bias the firing member 20500 downward (arrow DN) in the elongate channel 20310 into a locked position. When in the locked position, the firing member foot 20506 and/or the central tabs 20510 are misaligned with corresponding passages in the channel 20310 and as such, should the user attempt to distally advance the firing member 20500 when in that locked out state, the firing member 20500 would not move distally due to such misalignment. That is, the foot 20506 and/or central tabs 20510 contact portions of the elongate channel to thereby prevent the distal advancement of the firing member 20500. In one arrangement, a sled latch 20514 is formed on the firing member body 20502 and is configured to be engaged by a corresponding portion formed on a camming assembly that is operably supported in the surgical staple cartridge 20600. When a fresh unfired staple cartridge 20600 with the camming assembly thereof in its starting position has been

operably installed in the elongate channel 20310, a portion of the camming assembly engages the sled latch 20514 on the firing member body 20502 and moves the firing member 20500 upward (arrow UP in FIG. 20) into an unlocked position wherein the lower foot assembly 20506 and/or the central tabs 20510 are aligned with their respective passages in the channel 20310 to permit the firing member 20500 to axially advance therein. As the user distally advances the firing member 20500 into the cartridge 20600, the firing member 20500 also drives the camming assembly therein which cams the drivers upward to drive the staples or fasteners supported thereon into forming contact with the underside of the anvil. The tissue cutting member 20504 on the firing member 20500 then cuts through the stapled tissue. Once the firing member 20500 has been driven to its distal-most position corresponding to the ending position of the camming assembly, the firing member 20500 is retracted back to its proximal-most position, leaving the camming assembly in the distal end 20606 of the cartridge 20600. When the firing member 20500 returns to its proximal-most beginning position, the firing member lockout spring 20520 once again biases the firing member 20500 back into its locked position. Thus, should the user inadvertently try to reuse the spent cartridge 20600, the camming assembly is not in its starting position which is required to unlock the firing member 20500.

[0554] The surgical end effector 20300 may also employ a closure lockout system 20700 for preventing the anvil 20400 from being moved from an open position to a closed (clamped) position unless a corresponding compatible surgical staple cartridge 20600 has been operably installed in the elongate channel 20310. In the illustrated example, the closure lockout system 20700 comprises an anvil lock 20702 that is configured to move between an anvil locked position and an anvil unlocked position in response to installation of a staple cartridge 20600 therein. FIG. 19 illustrates one form of an anvil lock 20702. The anvil lock 20702 may be fabricated from spring steel or other suitable metal and include a proximal biasing arm 20704 that may be configured to be seated in a transverse spring mounting slot 20343 provided in the body portion 20342 of the channel mount feature 20340. The anvil lock 20702 further includes a distally extending body portion 20706 that has a downwardly extending mounting tab 20708 and an upwardly extending anvil lockout tab 20710 protruding therefrom. As can be seen in FIGS. 17, 18, and 20 the mounting tab 20708 extends into a clearance window 20319 that is formed in the elongate channel 20310.

[0555] FIG. 19 illustrates the surgical end effector 20300 without a surgical staple cartridge installed therein. As can be seen in FIG. 19, the proximal biasing arm 20704 has biased the anvil lock 20702 in the distal "anvil locked" position. When in this position, the anvil lockout tab 20710 is aligned with a portion of an anvil lock lug 20414 that is formed on the anvil mounting portion 20410 of the anvil 20400. Should the user attempt to close the anvil 20400, the anvil lock lug 20414 will contact the anvil lockout tab 20710 to thereby prevent any further travel of the anvil 20400 in the closure direction.

[0556] Returning to FIG. 21, in at least one arrangement, the staple cartridge 20600 includes an anvil unlocking feature or tab 20630 that protrudes proximally from the cartridge body 20602 and is aligned to unlockingly engage an actuation tab 20712 that is formed on the distal end of the

anvil lock 20702 when the cartridge 20600 has been operably installed in the elongate channel 20310. FIG. 20 depicts the surgical staple cartridge 20600 operably installed in the elongate channel 20310. As can be seen in FIG. 21, the anvil unlocking tab 20630 on the staple cartridge body 20602 has contacted the actuation tab 20712 of the anvil lockout 20702 and biased the anvil lockout 20702 in the proximal direction PD to an unlocked position, wherein the anvil lockout tab 20710 is no longer aligned with the anvil lock lug 20414 on the anvil 20400. When in that position, the user may pivot the anvil 20400 to a closed position. Should the user attempt to install an inappropriate cartridge that lacks the anvil unlocking tab 20630 or similar feature designed to unlocking engage the anvil lockout 20702, the user will be unable to close the anvil 20400 to complete the surgical stapling procedure.

[0557] FIG. 23 illustrates an alternative closure lockout system 20700' for preventing an anvil 20400' of a surgical end effector 20300' from being moved from an open position to a closed (clamped) position unless a corresponding proper surgical staple cartridge 20600' has been operably installed in the corresponding elongate channel (not shown). The surgical end effector 20300' is substantially identical to surgical end effector 20300 described above, except for the differences discussed below. The closure lockout system 20700' comprises an anvil lockout 20702' that is substantially identical to anvil lockout 20702 described above, except for the following differences. For example, the anvil lockout 20702 may be fabricated from spring steel or other suitable metal and include a distally extending body portion 20706' that has a spring portion 20707' formed therein. A proximal end of the anvil lockout 20702' has an anchor tab 20703' formed thereon that serves to couple the anvil lockout 20702' to the channel mount feature 20340 (FIG. 19). Additionally, the body portion 20706' includes a downwardly extending mounting tab 20708' and an upwardly extending anvil lockout tab 20710' that protrudes therefrom. An actuation tab 20712' is formed on the distal end of the body portion 20706'.

[0558] The surgical staple cartridge 20600' is similar to the surgical staple cartridge 20600 described above and includes a cartridge body 20602' that is sized to be removably seated in the elongate channel 20310. The cartridge body 20602' includes a cartridge slot 20608' that extends from a proximal end portion 20604' to a distal end portion of the cartridge body 20602'. The cartridge body 20602' further comprises a cartridge deck surface 20610' and three lines of surgical staple pockets 20612' located on each side of the cartridge slot 20608'. As can be seen in FIG. 23, the staple pockets 20612', as well as the staples or fasteners therein (not shown) are aligned on pocket axes PA' that are parallel to the cartridge slot 20608'. Thus, the staples/fasteners are applied in lines that are approximately parallel to the cartridge slot 20608' and the tissue cutline. Like surgical staple cartridge 20600, surgical staple cartridge 20600' includes a cartridge pan 20624' and an anvil unlocking feature or tab 20630' that protrudes proximally from the cartridge body 20602'.

[0559] Still referring to FIG. 23, the anvil 20400' is similar to anvil 20400, except for the differences discussed below. The anvil 20400' includes an elongate anvil body portion 20402' and an anvil mounting portion 20410' that is configured to interact with the end effector closure tube 3050 (FIG. 5) in the manner described above. The anvil body portion 20402' includes a staple-forming undersurface 20404' that is

bisected by an anvil slot 20405' that is configured to accommodate passage of the firing member 20500 therethrough. As can be seen in FIG. 23, the staple-forming undersurface 20404' comprises three lines of staple-forming pockets 20407' that are arranged on forming pocket axes FPA that are a parallel with the anvil slot 20405'. When the anvil 20400' is moved to a closed position, the anvil slot 20405' is vertically aligned with the cartridge slot 20608' to permit passage of the firing member 20500 therethrough. The lines of staple-forming pockets 20407' are aligned with the staple pockets 20612' such that as the staples are driven from the cartridge 20600', they contact a corresponding pair of staple-forming pockets 20407' to be crimped. Thus, the array of staple-forming pockets in the anvil 20400' must correspond to the array of staple pockets 20612' in the cartridge 20600' to ensure that the staples are properly formed. As can be further seen in FIG. 23, in this arrangement, the anvil 20400' includes a downwardly extending anvil lock lug 20414' that is formed distal to the anvil mounting portion 20410' but is otherwise configured to contact the anvil lockout tab 20710' when the anvil lockout 20702' is in the locked position (e.g., no cartridge has been inserted into the channel 20310 or an improper cartridge has been seated in the channel 20310). When the cartridge 20600' has been properly seated in the elongate channel 20310, the anvil unlocking feature 20630' thereon contacts the actuation tab 20712' on the anvil lockout 20702' to bias the lockout 20702' proximally into the unlocked position wherein the anvil lockout tab 20710' is out of locking alignment with the anvil lock lug 20414' to permit the anvil 20400' to be pivoted to the closed position.

[0560] FIG. 24 illustrates an alternative closure lockout system 20700" for preventing an anvil 20400" of another surgical end effector 20300" from being moved from an open position to a closed (clamped) position unless a compatible surgical staple cartridge 20600" has been operably installed in the elongate channel 20310. The surgical end effector 20300" is substantially identical to surgical end effector 20300 described above, except for the differences discussed below. The closure lockout system 20700" comprises an anvil lockout 20702" that is substantially identical to anvil lockout 20702 described above, except for the following differences. For example, the anvil lockout 20702" may be fabricated from spring steel or other suitable metal and include a distally extending body portion 20706" that has a spring portion 20707" formed therein. A proximal end of the anvil lockout 20702" has an anchor tab 20703" formed thereon that serves to couple the anvil lockout 20702" to the channel mount feature 20340 (FIG. 19). Additionally, the body portion 20706" includes a downwardly extending mounting tab 20708" and an upwardly extending anvil lockout tab 20710" that protrudes therefrom. An actuation tab 20712" is formed on the distal end of the body portion 20706".

[0561] The surgical staple cartridge 20600" is similar to the surgical staple cartridge 20600 described above and includes a cartridge body 20602" that is sized to be removably seated in the elongate channel 20310. The cartridge body 20602" includes a cartridge slot 20608" that extends from a proximal end portion 20604" to a distal end portion of the cartridge body 20602". The cartridge body 20602" further comprises a cartridge deck surface 20610" and two lines of surgical staple pockets 20612" located on each side of the cartridge slot 20608". As can be seen in FIG. 24, the staple pockets 20612", as well as the staples or fasteners

therein (not shown), are aligned on pocket axes PA" that are transverse to the cartridge slot 20608". Thus, the staples/fasteners are applied in lines that are approximately transverse to the cartridge slot 20608" and the tissue cutline. Such arrangements of fasteners create "flexible" or "stretchable" staple lines. Further details regarding cartridges for developing flexible or stretchable lines of staples may be found in U.S. patent application Ser. No. 14/498,121, entitled FASTENER CARTRIDGE FOR CREATING A FLEXIBLE STAPLE LINE, now U.S. Pat. No. 9,801,627, the entire disclosure of which is hereby incorporated by reference herein. Like surgical staple cartridge 20600, surgical staple cartridge 20600" includes a cartridge pan 20624" and an anvil unlocking feature or tab 20630" that protrudes proximally from the cartridge body 20602'.

[0562] Still referring to FIG. 24, the anvil 20400" is similar to anvil 20400, except for the differences discussed below. The anvil 20400" includes an elongate anvil body portion 20402" and an anvil mounting portion 20410" that is configured to interact with the end effector closure tube 3050 (FIG. 5) in the manner described above. The anvil body portion 20402" includes a staple-forming undersurface 20404" that is bisected by an anvil slot 20405" that is configured to accommodate passage of the firing member 20500 therethrough. As can be seen in FIG. 24, the staple-forming undersurface 20404" comprises lines of staple-forming pockets 20407" that are arranged on forming pocket axes FPA that are transverse to the anvil slot 20405". When the anvil 20400" is moved to a closed position, the anvil slot 20405" is vertically aligned with the cartridge slot 20608" to permit passage of the firing member 20500 therethrough. The lines of staple-forming pockets 20407" are aligned with the staple pockets 20612" such that as the staples are driven from the surgical staple cartridge 20600", they contact a corresponding pair of forming pockets 20407" to be crimped. Thus, the array of staple-forming pockets 20407" in the anvil 20400" must correspond to the array of staple pockets 20612" in the cartridge 20600" to ensure that the staples are properly formed. As can be further seen in FIG. 24, in this arrangement, the anvil 20400" includes a downwardly extending anvil lock lug 20414" that is formed or attached to the anvil mounting portion 20410" and is configured to contact the anvil lockout tab 20710" when the anvil lockout 20702" is in the locked position (e.g., no cartridge has been inserted into the channel 20310 or an improper cartridge is inserted in the channel 20310). When the cartridge 20600" has been properly seated in the elongate channel 20310, the anvil unlocking feature 20630" thereon contacts the actuation tab 20712" on the anvil lockout 20702" to bias the anvil lockout 20702" proximally into the unlocked position wherein the anvil lockout tab 20710" is out of locking alignment with the anvil lock lug 20414" to permit the anvil 20400" to be pivoted close.

[0563] As was discussed above, various surgical staple cartridges may have different arrays of and/or orientations of staples/fasteners therein. The sizes of the staples or fasteners, as well as the number of fasteners may vary from cartridge type to cartridge type depending upon a particular surgical procedure or application. To ensure that the staples are properly crimped or formed, the surgical staple cartridges must be used in connection with corresponding anvils that have the proper array of staple-forming pockets therein. Should a "non-compatible" cartridge be loaded into an end effector that has an anvil that is mismatched to the

cartridge, the staples may not be properly formed during the firing process which could lead to catastrophic results. For example, the surgical staple cartridge 20600' depicted in FIG. 23 is matched to or "compatible with" the anvil 20400' shown in FIG. 23. The surgical staple cartridge 20600" shown in FIG. 24 is matched to or compatible with the anvil 20400" shown in FIG. 24. However, the surgical staple cartridge 20600" of FIG. 24 is incompatible with the anvil 20400' shown in FIG. 23, for example.

[0564] The closure lockout systems employed in the examples described above may avoid the activation of a mismatched cartridge that has otherwise been loaded into the end effector. For example, the anvil unlocking feature or tab 20630' on the staple cartridge 20600' is located on the left side of the cartridge slot 20608' and is positioned to contact the actuator tab 20712' on the anvil lockout spring 20707' when the cartridge 20600' is properly loaded in the channel 20310 of end effector 20300'. Conversely, the anvil unlocking feature or tab 20630" on the cartridge 20600" is located on the right side of the cartridge slot 20608" and aligned to contact the actuator tab 20712" on the anvil lockout 20702" when the cartridge 20600" is properly loaded in the channel 20310. Should the user load cartridge 20600" into the channel 20310 of the end effector 20300', anvil unlocking feature or tab 20630" on the staple cartridge 20600" will not contact the he actuator tab 20712' on the anvil lockout 20702' to move it into the unlocked position and the user will be unable to pivot the anvil 20400' closed. Likewise, should the user load cartridge 20600' into the channel of the end effector 20300", anvil unlocking feature or tab 20630' on the staple cartridge 20600' will not contact the he actuator tab 20712" on the anvil lockout 20702" to move it into the unlocked position and the user will be unable to pivot the anvil 20400" closed. If the user unwittingly loads another cartridge that lacks the proper anvil unlocking feature or tab that corresponds to the anvil lockout in the end effector, the user will be unable to close the anvil. The location, shape, length, etc. of the anvil unlocking feature(s) or tab(s) on a surgical staple cartridge may vary from cartridge type to cartridge type and be interrelated to the actuator member (size, location, shape, number, etc.) on the correspond anvil lockout located in a corresponding surgical end effector. For example, the anvil unlocking feature or tab may be integrally formed on the cartridge body, be machined or molded into the cartridge body, be attached to the cartridge body, be attached to or integrally formed on the camming assembly of the cartridge or comprise a portion of the cartridge pan, for example. All such variations are contemplated herein and are intended to be encompassed by the appended claims.

[0565] FIGS. 25-29 illustrate a surgical end effector 21300 that is very similar to the surgical end effectors 20300, 20300', 20300" described above, except for the differences discussed below. In this embodiment, for example, the end effector 21300 comprises an elongate channel 21310 that is configured to operably support a surgical staple cartridge 21600 therein. In the illustrated example, the elongate channel 21310 comprises a channel bottom 21312 and a pair of upstanding sidewalls 21314. Although not shown, the channel 21310 may be coupled to the elongate shaft assembly 1200 (FIG. 5) by a channel mount feature 20340 (described above) which may facilitate articulation thereof about articulation joint 3020 (FIG. 5). The surgical end effector 21300 further comprises an anvil 21400 that may be very similar to anvil 20400 described above, except for the

differences discussed below. The anvil **21400** includes an elongate anvil body portion **21402** that has a staple-forming undersurface and an anvil mounting portion **21410** that is configured to interact with an end effector closure tube **3050** (FIG. 5) in the manner described above. The anvil **21400** is pivotally mounted on the elongate channel **21310** by a pair of laterally extending anvil pins or trunnions **21412** that are received in corresponding elongate trunnion slots **21320** that are formed in the upstanding channel walls **21314**. Axial movement of the end effector closure tube **3050** in a distal direction will cause the anvil **21400** to translate distally until the trunnions **21412** contact the distal ends of their respective trunnion slots **21320** and pivot to a closed position. Conversely, movement of the end effector closure tube **3050** in a proximal direction will cause the anvil **21400** to pivot to an open position relative to the elongate channel **21310**.

[0566] The end effector **21300** is configured to operably support a surgical staple cartridge **21600** that may be substantially the same as the surgical staple cartridge **20600**, except that the anvil unlocking feature or tab **21630** comprises a portion of the cartridge pan **21620**. The anvil unlocking feature **21630** is configured to operably interact with an axially movable anvil lock **21702** that is supported by the channel **21310**. Turning to FIG. 27, the anvil lock **21702** is supported for axial movement between a distal locked position and a proximal locked position by a guide block **21720** that is attached to a portion of the channel **21310**. In one example, anvil lock **21702** may be formed from metal and the guide block **21720** may be fabricated from 40% carbon filled Nylon 6/6 and be attached to the sidewall of **21314** of the channel **21310** by appropriate adhesive or other fastening means. The guide block **21720** may define a guide channel **21722** that is configured to support a locking tab portion **21710** of the anvil lock **21702**. The anvil lock **21702** additionally comprises a vertical body portion **21706** that has an actuation tab **21712** formed on a distal end thereof. The anvil lock **21702** is biased to a distal locked position by an extension spring **21730** that is attached to the anvil lock **21702** and the channel sidewall **21314**. When no cartridge is present, the extension spring **21730** biases the anvil lock **21702** into a distal locked position wherein the locking tab portion **21710** contacts a portion of the anvil **21400** to prevent the anvil **21400** from pivoting to a closed position. When a proper or compatible cartridge **21600** is loaded into the elongate channel **21310**, the unlocking feature or tab **21630** of the cartridge pan **21620** contacts the actuation tab **21712** on the anvil lock **21702** to move the anvil lock **21702** proximally into an unlocked position wherein the locking tab portion **21710** of the anvil lock **21702** no longer prevents pivotal motion of the anvil **21400**. As can be seen in FIG. 25, the anvil unlocking feature **21630** of the surgical staple cartridge **21600** is “asymmetric” in design. That is, the anvil unlocking feature **21630** is only located on one side of a proximal end of the cartridge **21600**. FIG. 25 illustrates an old relief area **21315** that is present in previous channel arrangements and new relief areas **21317**, **21319** that are provided in the channel **21310** to accommodate cartridge **21600** therein.

[0567] FIG. 30 illustrates portions of a surgical end effector **21300'** that is identical to end effector **21300**, except that the end effector **21300'** employs an anvil lock **21702'** as depicted in FIGS. 31 and 32. In one example, the anvil lock **21702'** may be fabricated from 40% carbon filled Nylon 6/6 and include a vertical body portion **21706'** that has a locking

portion **21710'** formed on the upper end thereof. An actuation tab **21712'** is formed on a distal end and a gusset **21714'** is also employed to provide additional support to the actuation tab **21712'**. As discussed above, when a proper or compatible surgical staple cartridge **21600** is loaded into the elongate channel **21310**, the unlocking feature or tab **21630** of the cartridge pan **21620** contacts the actuation tab **21712'** on the anvil lock **21702'** to move the anvil lock **21702'** proximally into an unlocked position wherein the locking portion **21710'** of the anvil lock **21702'** no longer prevents pivotal motion of the anvil **21400**.

[0568] FIG. 33 illustrates another surgical end effector **22300** that employs an anvil lockout system **22700**. The end effector **22300** is similar to the end effector **20300** described above, except for the noted differences. In this embodiment, the end effector **22300** comprises an elongate channel **22310** that is configured to operably support a surgical staple cartridge **22600** therein. In the illustrated example, the elongate channel **22310** comprises a channel bottom **22312** and a pair of upstanding sidewalls **22314**. Although not shown, the channel **22310** may be coupled to the elongate shaft assembly **1200** (FIG. 5) by a channel mount feature **20340** (described above) which may facilitate articulation thereof about articulation joint **3020** (FIG. 5). The surgical end effector **22300** further comprises an anvil **22400** that is very similar to anvil **20400** described above, except for the differences discussed below. The anvil **22400** includes an elongate anvil body portion **22402** and an anvil mounting portion **22410** that is configured to interact with an end effector closure tube **3050** (FIG. 5) in the manner described above. The anvil **22400** is pivotally mounted on the elongate channel **22310** by a pair of laterally extending anvil pins or trunnions **22412** that are received in corresponding elongate trunnion slots **22320** formed in the upstanding channel sidewalls **22314**. Axial movement of the end effector closure tube **3050** in a distal direction will cause the anvil trunnions **22412** to translate distally up the trunnion slots **22320** to pivot the anvil **22400** to a closed position. Conversely, movement of the end effector closure tube **3050** in a proximal direction will cause the anvil **22400** to pivot to an open position relative to the elongate channel **22310**.

[0569] The end effector **22300** is configured to operably support a surgical staple cartridge **22600** that may be substantially the same as the surgical staple cartridge **20600**, except that the anvil unlocking feature or tab **22630** is formed on a right side of a proximal end proximal end portion **22604** of the cartridge body **22602** and has a contoured proximal end surface **22632**. In the illustrated example, the contoured proximal end surface **22632** has an arcuate shape. The anvil unlocking feature **22630** is configured to operably interact with an axially movable anvil lock **22702** of the anvil lockout system **22700** that is supported by the channel **22310**. In the illustrated example, the anvil lock **22702** is supported for axial movement between a distal locked position and a proximal unlocked position within a proximal end portion **22316** of the elongate channel **22310**. In the illustrated example, the anvil lock **22702** comprises an elongate body portion **22706** that has an anvil lock tab **22710** formed on a proximal end thereof and configured to lockingly interact with a lock lug **22413** formed on the anvil mounting portion **22410** of the anvil **22400**. See FIG. 33. An actuation tab **22712** is formed on a distal end of the body portion **22706**. The actuation tab **22712** has a contoured actuation surface **22714** formed therein that is configured to

substantially match or mate with the contoured proximal end surface **22632** on the anvil unlocking feature **22630**. See FIG. **34**.

[0570] In at least one arrangement, a spring or biasing member **22730** (leaf spring, coil spring, etc.) may be attached to or mounted within the channel **22310** and configured to bias the anvil lock **22702** in the distal direction DD to the locked position wherein the anvil lock tab **22710** thereon is in blocking alignment with the lock lug **22413** on the anvil mounting portion **22410** to prevent closing of the anvil **22400**. When a proper or compatible surgical staple cartridge **22600** is operably loaded into the channel **22310**, the anvil unlocking feature or tab **22630** is brought into engagement with the contoured surface **22714** on the actuation tab **22712** of the anvil lock **22702**. The surgical staple cartridge **22600** is then moved proximally to seat the cartridge **22600** within the channel **22310**. As the surgical staple cartridge **22600** is moved proximally, the anvil unlocking feature **22630** contacts the actuation tab **22712** of the anvil lock **22702** and biases the anvil lock **22702** proximally into the unlocked position wherein the anvil lock tab **22710** thereon is moved out of blocking alignment with the lock lug **22413** on the anvil mounting portion **22410** to permit the anvil **22400** to pivot closed. When the surgical staple cartridge **22600** is removed from the channel **22310**, the spring **22730** biases the anvil lock **22702** distally back to the locked position. FIG. **35** illustrates that the contoured proximal end **22632** of the anvil unlocking feature **22630** formed on a right side of the proximal end portion **22604** of the cartridge body **22602** and the matching contoured surface **22714** on the actuation tab **22712** of the anvil lock **22702** enable the cartridge **22600** to facilitate unlocking interaction between the unlocking feature **22630** and actuation tab **22712** even when the cartridge is installed at an installation angle IA relative to the central axis EA of the end effector **22300**. See FIG. **35**.

[0571] FIG. **36** illustrates the attempted use of an incompatible cartridge **22600X** that lacks an unlocking feature to move the anvil lock **22702** from the locked position to the unlocked position. As can be seen in FIG. **36**, the lockout tab **22710** is in blocking alignment with the lock lug **22413** on the anvil **22400** to thereby prevent the anvil **22400** from being closed even after the cartridge **22600X** has been seated in the channel **22310**.

[0572] FIG. **37** illustrates another surgical end effector **22300'** that is substantially identical to surgical end effector **22300** described above, except for the noted differences. The end effector **22300'** is configured to operably support a staple cartridge **22600'** that is substantially the same as cartridge **20600** and includes an anvil unlocking feature or tab **22630'** that has a contoured proximal end surface **22632'**. In the illustrated example, the anvil lock **22702'** comprises an elongate body portion **22706'** that has an anvil lock tab **22710'** formed on a proximal end **22711'** thereof and configured to lockingly interact with a lock lug **22413'** formed on the anvil mounting portion **22410** of the anvil **22400**. A distal end **22712'** of the anvil lock **22702'** includes a contoured actuation surface **22714'** formed therein that is configured to substantially match or mate with the contoured proximal end surface **22632'** on the anvil unlocking feature **22630'** in the manners described above. A spring or biasing member **22730'** (leaf spring, coil spring, etc.) may be attached to or mounted within the channel **22310'** and configured to bias the anvil lock **22702'** in the distal direc-

tion DD to the locked position wherein the anvil lock tab **22710'** thereon is in blocking alignment with the lock lug **22413'** on the anvil mounting portion **22410** to prevent closing of the anvil **22400**.

[0573] When a proper or compatible surgical staple cartridge **22600'** is operably loaded into the channel **22310'**, the anvil unlocking feature or tab **22630'** is brought into engagement with the contoured surface **22714'** of the anvil lock **22702'**. The cartridge **22600'** is then moved proximally in a proximal direction PD to seat the cartridge **22600'** within the channel **22310'**. As the cartridge **22600'** is moved proximally, the anvil unlocking feature **22630'** contacts the distal end of the anvil lock **22702'** and biases the anvil lock **22702'** proximally into the unlocked position wherein the anvil lock tab **22710'** thereon is moved out of blocking alignment with the lock lug **22413'** on the anvil mounting portion **22410** to permit the anvil **22400** to pivot closed. When the cartridge **22600'** is removed from the channel **22310'**, the spring **22730'** biases the anvil lock **22702'** distally back to the locked position. As can be seen in FIG. **37**, when compared to anvil lock **22702** described above, the anvil lock **22702'** has a more robust body portion **22706'**. In at least one example, a clearance notch **22709'** is provided in the body portion **22706'** to provide sufficient clearance for the lock lug **22413'** when the anvil **22400** is pivoted to the closed position. In addition, a channel stop **22313'** is formed on a bottom **22312'** of the channel **22310'** and is configured for contact with the proximal end **22711'** of the anvil lock **22702'** when the anvil lock **22702'** is in the unlocked position to prevent the anvil lock **22702'** from moving any further proximally to ensure that the lock lug **22413'** remains aligned with the clearance notch **22709'** in the anvil lock **22702'** during closing of the anvil **22400**.

[0574] FIG. **38** illustrates another surgical end effector **22300"** that is substantially identical to surgical end effector **22300** described above, except for the noted differences. The end effector **22300"** comprises an elongate channel **22310"** that includes an anvil **22400"** that is pivotally supported thereon. The channel **22310"** is configured to operably support a surgical staple cartridge **22600** that is compatible with the staple-forming undersurface of the anvil **22400"** and employs an anvil locking system **22700"** that is configured to prevent closure of the anvil **22400"** unless a surgical staple cartridge **22600** has been operably installed in the end effector **22300"**. In the illustrated example, the anvil locking system **22700"** includes an anvil lock **22702"** that comprises a body portion **22706"** that has a distal end portion **22712"** that is higher than a proximal portion of the body **22706"**. When the anvil lock **22702"** is in its distal-most locked position, a portion of the anvil **22400"** contacts the higher distal end portion **22712"** to prevent the anvil **22400"** from being closed. The distal end portion **22712"** of the anvil lock **22702"** includes a contoured actuation surface **22714"** that is configured to substantially match or mate with the contoured proximal end surface **22632** on the anvil unlocking feature **22630** formed on the cartridge **22600** in the manners described above. A spring or biasing member **22730"** (leaf spring, coil spring, etc.) may be attached to or mounted within the channel **22310"** and be configured to bias the anvil lock **22702"** in the distal direction DD to the locked position wherein the distal end portion **22712"** is in blocking alignment with corresponding portion of the anvil **22400"** to prevent closing of the anvil **22400"**.

[0575] When a proper or compatible surgical staple cartridge 22600 is operably loaded into the channel 22310", the anvil unlocking feature 22630 on the cartridge 22600 is brought into engagement with the contoured surface 22714" on the distal end 22712" of the anvil lock 22702". The cartridge 22600 is then moved proximally to seat the cartridge 22600 within the channel 22310". As the cartridge 22600 is moved proximally, the anvil unlocking feature 22630 contacts the distal end 22712" of the anvil lock 22702" and biases the anvil lock 22702" proximally into the unlocked position wherein the distal end portion 22712" is moved out of blocking alignment with the corresponding portion of the anvil 22400" to permit the anvil 22400" to pivot to a closed position. When the cartridge 22600 is removed from the channel 22310", the spring 22730" biases the anvil lock 22702" distally back to the locked position. As can also be seen in FIG. 38, a channel stop 22313" is formed on a bottom 22312" of the channel 22310" and is configured for contact with a proximal end 22711" of the anvil lock 22702" to prevent the cartridge 22600 from being inserted too far proximally into the end effector 22300".

[0576] FIGS. 39 and 40 illustrate another surgical end effector 23300 that is similar to the other surgical end effectors described herein with the exception of the various differences noted below. The end effector 23300 comprises an elongate channel 23310 that includes an anvil 23400 that is pivotally supported thereon. The channel 23310 is configured to operably support a surgical staple cartridge 22600 that is compatible to the staple-forming undersurface of the anvil 23400 and employs an anvil locking system 23700 that is configured to prevent closure of the anvil 23400 unless a cartridge 22600 has been operably installed in the end effector 23300. In the illustrated example, anvil locking system 23700 comprises an anvil lock 23702 comprising a body portion 23706 that has a distal end portion 23712. The distal end portion 23712 of the anvil lock 23702 includes a contoured actuation surface 23714 that is configured to substantially match or mate with the contoured proximal end surface 22632 on the anvil unlocking feature 22630 that is formed on the cartridge 22600 in the manners described above. A spring or biasing member 23730 is mounted within the channel 23310 and is configured to bias the anvil lock 23702 in the distal direction DD to a "locked" position.

[0577] In the illustrated example, the anvil 23400 includes an elongate anvil body 23402 that an anvil mounting portion 23410 that is configured to interact with the end effector closure tube 3050 (FIG. 5) in the manner described above. The anvil 23400 is pivotally mounted on the elongate channel 22310 by a pair of laterally extending trunnion formations 23412 that are received in corresponding trunnion slots 23320 formed in upstanding sidewalls of the channel 23310. At least one trunnion formation 23412 comprises a laterally protruding actuator lobe 23414 that defines an actuator ledge 23416. A trunnion pin 23418 protrudes outwardly from the actuator lobe 23414 and is sized to translate and pivot within a corresponding trunnion slot 23320.

[0578] As can be seen in FIG. 39, at least one trunnion slot 23320 comprises an arcuate actuation portion 23322 and a locking offset portion 23324 that is formed at a proximal end 23321 of the trunnion slot 23320. FIG. 39 illustrates insertion of a cartridge 22600 into the elongate channel 23310. To install a cartridge 22600 into the elongate channel 23310, the anvil 23400 is first moved to an open position. This may be

accomplished by actuating the closure system to move the end effector closure tube 3050 (FIG. 5) in a proximal direction PD. As the closure tube 3050 is moved proximally, it interacts with an opening tab 23411 formed on the anvil mounting portion 23410. As the closure tube 3050 interacts with the anvil mounting portion 23410, the anvil 23400 translates proximally and starts to pivot open which results in the trunnion formation 23412 translating down the arcuate actuation portion 23322 of the corresponding trunnion slot 23320 and into the proximal end 23321 of the trunnion slots 23320 when the anvil 23400 reaches its fully open position.

[0579] During installation of a proper or compatible surgical staple cartridge 22600 into the channel 23310, the anvil unlocking feature or tab 22630 is brought into engagement with the contoured surface 23714 on the distal end 23712 of the anvil lock 23702. The cartridge 22600 is then moved proximally to seat the cartridge 22600 within the channel 23310. As the cartridge 22600 is moved proximally, the anvil unlocking feature 22630 contacts the distal end 23712 of the anvil lock 23702 and biases the anvil lock 23702 proximally an unlocking distance UD to bring a proximal end 23710 of the anvil lock body 23706 into engagement with actuator lobe 23414 on at least one trunnion formation 23412 to move the trunnion formation 23412 into a position wherein the trunnion formation 23412 can translate up the arcuate actuation portion 23322 of the corresponding trunnion slot 23320 when a closing motion is applied to the anvil mounting portion 23410. Stated another way, the proximal end 23710 of the anvil lock 23702 prevents the trunnion formation 23412 from entering the locking offset portion 23324 formed at the proximal end 23321 of the trunnion slot 23320 to enable the trunnion formation 23412 to progress into the arcuate actuation portion 23322 of the trunnion slot 23320.

[0580] FIG. 40 illustrates an attempted insertion of an incompatible cartridge 22600X that lacks the requisite unlocking feature or tab 22630 to move the anvil lock 23702 out of the distal locked position. If the user nonetheless seats the incompatible cartridge 22600X in the channel 23310 and then attempts to close the anvil 23400, the anvil locking system 23700 will prevent closure of the anvil 23400. For example, to close the anvil 23400, the closure system is activated to move the closure tube (or other closure member) distally into operably contact with the anvil mounting portion 23410 of the anvil 23400 to apply closure motions thereto. The initial application of closure motions to the anvil mounting portion 23410 causes the anvil mounting portion 23410 to move downwardly (arrow DL in FIG. 40) which results in the anvil trunnion formations 23412 entering the locking offset portions 23324 formed in the trunnion slots 23320. Thus, the anvil trunnion formations 23412 cannot translate into the arcuate actuation portion 23322 of the corresponding trunnion slot 23320 during the application of the closure motion to the anvil 23400 and the anvil 23400 is then prevented from closing.

[0581] FIG. 41 illustrates a portion of an alternative anvil 23400' that comprises an anvil mounting portion 23410' that has trunnion formations 23412' formed thereon. Each trunnion formation 23412' comprises a laterally protruding actuator lobe 23414' that defines an actuator ledge 23416' that is configured to interact with an anvil locking system 23700 in the manner described above. As can be seen in FIG. 41, the actuator ledge 23416' is vertically offset (distance OD) from a bottom surface 23415' of the anvil mounting

portion **23410'**. A trunnion pin **23418'** protrudes outwardly from the actuator lobe **23414'** and is sized to translate and pivot within a corresponding trunnion slot **23320**. In this example, the trunnion pin **23418'** has a trunnion pin diameter TRD that is approximately equal to the width LW of the actuator lobe **23414'**.

[0582] FIG. 42 illustrates a portion of an alternative anvil **23400"** that comprises an anvil mounting portion **23410"** that has trunnion formations **23412"** formed thereon. Each trunnion formation **23412"** comprises a laterally protruding actuator lobe **23414"** that defines an actuator ledge **23416"** that is configured to interact with an anvil locking system **23700** in the manner described above. As can be seen in FIG. 42, the actuator ledge **23416"** is coextensive with (e.g., not offset from) a bottom edge **23415"** of the anvil mounting portion **23410"**. A trunnion pin **23418"** protrudes outwardly from the actuator lobe **23414"** and is sized to translate and pivot within a corresponding trunnion slot **23320**. In this example, the trunnion pin **23418"** has a trunnion pin diameter TRD' that is approximately equal to the width LW' of the actuator lobe **23414'**.

[0583] FIG. 43 is a partial cross-sectional end elevational view of a surgical end effector **24100** that comprises an anvil **24400** that is pivotally supported on an elongate channel **24310**. The anvil **24400** comprises an anvil mounting portion **24410** that has trunnion formations **24412** formed thereon. Each trunnion formation **24412** comprises a laterally protruding actuator lobe **24414** that defines a bottom lobe surface **24416** that is configured to interact with an anvil locking system **24700** in the manner described above. As can be seen in FIG. 44, the bottom lobe surface **24416** is vertically offset (distance OD₁) from a bottom surface **24415** of the anvil mounting portion **24410**. A trunnion pin **24418** protrudes outwardly from the actuator lobe **24414** and is sized to translate and pivot within a corresponding trunnion slot **24320** formed in the elongate channel **24310**. In this example, the trunnion pin **24418** has a trunnion pin diameter TRD₁ that is approximately equal to the width LW₁ of the actuator lobe **24414**.

[0584] Channel **20310** comprises a channel bottom **24312** and a pair of upstanding sidewalls **24314**. The channel **24310** may be coupled to an elongate shaft assembly **1200** (FIG. 5) by a channel mount feature **20340** which may facilitate articulation thereof about articulation joint **3020** (FIG. 5). FIG. 45 illustrates a portion of a proximal end **24316** of the channel **24310**. In one example, each channel wall **24314** has a trunnion slot **24320** formed therein. In the illustrated arrangement, a lobe ledge **24340** is formed in each channel wall **24314** such that a top surface **24342** of the lobe ledge **24340** is coextensive with a bottom surface **24321** of the corresponding trunnion slot **24320**. Each trunnion **24418** is received within a corresponding trunnion slot **24320** and is free to rotate and translate therein.

[0585] Still referring to FIG. 45, a portion of an anvil lock **24702** of the anvil locking system **24700** is shown. The anvil lock **24702** operates in the same manner as the anvil lock **20702** described above and includes a lockout body **24706** that has an actuator tab (not shown) that is formed on a distal end thereof that is configured to be contacted by an unlocking feature that protrudes proximally from a compatible cartridge. The anvil lock **24702** may be fabricated from spring steel or other suitable metal and include a proximal biasing arm **24704** that may be configured to be seated in a transverse spring mounting slot (not shown) that is provided

in the body portion of a channel mount feature (not shown). The anvil lock **24702** further includes an upwardly extending anvil lockout tab **24710** that protrudes therefrom that is configured to extend above the corresponding lobe ledge **24340** and contact a corresponding lobe **24414** as will be described below.

[0586] FIGS. 45 and 46 illustrate the anvil lock **24702** in the locked position wherein the anvil **24400** is pivoted to an open position. This may occur when no cartridge has been inserted into the channel **24310** or a non-compatible cartridge (e.g. a cartridge that lacks, among other things, the proper anvil unlocking feature that is necessary to bias the anvil lock spring proximally) has been inserted into the channel **24310**. Should the user unwittingly attempt to close the anvil **24400** when the anvil lock **24702** is in the distal locked position shown in FIGS. 45 and 46, the corresponding lobe **24414** will contact the anvil lockout tab **24710** and prevent the anvil **24400** from pivoting to the closed position. FIGS. 47 and 48 illustrate the position of the anvil lock **24702** in the proximal unlocked position wherein the anvil lockout tab **24710** is positioned proximal to the lobe **24414** to permit the lobe **24414** to pivot to the closed position.

[0587] FIG. 49 is a partial cross-sectional end elevational view of a surgical end effector **24100'** that comprises an anvil **24400'** that is pivotally supported on an elongate channel **24310'**. The anvil **24400'** comprises an anvil mounting portion **24410'** that has trunnion formations **24412'** formed thereon. Each trunnion formation **24412'** comprises a laterally protruding actuator lobe **24414'** that defines a bottom lobe surface **24416'** that is configured to interact with an anvil locking system **24700'** in the manner described above. As can be seen in FIG. 50, the bottom lobe surface **24416'** is coextensive with a bottom surface **24415'** of the anvil mounting portion **24410'**. A trunnion pin **24418'** protrudes outwardly from the actuator lobe **24414'** and is sized to translate and pivot within a corresponding trunnion slot **24320'** formed in the elongate channel **24310'**. In this example, the trunnion pin **24418'** has a trunnion pin diameter TRD₂ that is smaller than the width LW₂ of the actuator lobe **24414'**.

[0588] Channel **20310'** comprises a channel bottom **24312'** and a pair of upstanding sidewalls **24314'**. The channel **24310'** may be coupled to an elongate shaft assembly **1200** (FIG. 5) by a channel mount feature **20340** which may facilitate articulation thereof about articulation joint **3020** (FIG. 5). FIG. 51 illustrates a portion of a proximal end **24316'** of the channel **24310'**. In one example, each channel wall **24314'** has a trunnion slot **24320'** formed therein. In the illustrated arrangement, a lobe ledge **24340'** is formed in each channel wall **24314'** such that a top surface **24342'** of the lobe ledge **24340'** is offset vertically from a bottom surface **24321'** of the corresponding trunnion slot **24320'** an offset distance OSD. Offset distance OSD may be approximately equal to a distance TSD between the trunnion pin **24418'** and the bottom lobe surface **24416'**. See FIG. 50. Each trunnion pin **24418'** is received within a corresponding trunnion slot **24320'** and is free to rotate and translate therein.

[0589] Still referring to FIG. 51, a portion of an anvil lock **24702'** of the anvil locking system **24700'** is shown. The anvil lock **24702'** operates in the same manner as the anvil lock **20702** described above and includes a lockout body **24706'** that has an actuator tab (not shown) formed on a distal end thereof that is configured to be contacted by an

unlocking feature that protrudes proximally from a compatible cartridge. The anvil lock **24702'** may be fabricated from spring steel or other suitable metal and include a proximal biasing arm **24704'** that may be configured to be seated in a transverse spring mounting slot (not shown) provided in the body portion of a channel mount feature (not shown). The anvil lock **24702'** further includes an upwardly extending anvil lockout tab **24710'** that protrudes therefrom that is configured to extend above the corresponding lobe ledge **24340'** and contact a corresponding lobe **24414'** as was described above.

[0590] FIG. 51 illustrates the anvil lock **24702'** in the locked position wherein the anvil **24400** is pivoted to an open position. This may occur when no cartridge has been inserted into the channel or a non-compatible cartridge (e.g., a cartridge that lacks, among other things, the proper anvil unlocking feature that is required to bias the anvil lock spring proximally) has been inserted into the channel **24310'**. Should the user unwittingly attempt to close the anvil **24400'** when the anvil lock **24702'** is in the distal locked position shown in FIG. 45, the corresponding lobe **24414'** will contact the anvil lockout tab **24710'** and prevent the anvil **24400'** from pivoting to the closed position. Once a compatible surgical staple cartridge has been loaded into the end effector **24100'**, the anvil lock **24702'** will be biased to the unlocked position (see e.g., FIG. 47) and the anvil **24400'** will be free to pivot to the closed position.

[0591] FIG. 52 depicts a portion of a surgical end effector **24100"** that comprises an anvil **24400"** that is pivotally supported on an elongate channel **24310"**. The anvil **24400"** comprises an anvil mounting portion **24410"** that has trunnion formations **24412"** formed thereon. As can be seen in FIGS. 53 and 54, each trunnion formation **24412"** comprises a laterally protruding actuator lobe **24414"** that defines a bottom lobe surface **24416"** that is configured to interact with an anvil locking system **24700"** in the manner described above. As can be seen in FIG. 53, the actuator lobe **24414"**, as well as the bottom lobe surface **24416"** of the actuator lobe **24414"**, are located at an angle relative to an end effector axis EA as well as a bottom edge **24419"** of the anvil mounting portion **24410"** and/or the bottom **24312"** of the channel **24310"**. As further illustrated in FIG. 53, the bottom lobe surface **24416"** is parallel to a lobe axis LBA that is located at a lobe angle LA relative to the end effector axis EA. A trunnion pin **24418"** protrudes outwardly from the actuator lobe **24414"** and is sized to translate and pivot within a corresponding trunnion slot **24320"** that is formed in the elongate channel **24310"**. See FIG. 55. In this example, the trunnion pin **24418"** has a trunnion pin diameter TRD₃ that is equal to the width LW₃ of the actuator lobe **24414"**.

[0592] Referring to FIG. 55, the channel **24310"** comprises a channel bottom **24312"** and a pair of upstanding sidewalls **24314"**. The channel **24310"** may be coupled to an elongate shaft assembly **1200** (FIG. 5) by a channel mount feature **20340** which may facilitate articulation thereof about articulation joint **3020** (FIG. 5) in the various manners described herein. FIG. 55 illustrates a portion of a proximal end **24316"** of the channel **24310"**. In one example, each channel wall **24314"** has a trunnion slot **24320"** formed therein. In the illustrated arrangement, a lobe ledge **24340"** is formed in each channel wall **24314"** such that a proximal surface portion **24344"** of a top surface **24342"** of the lobe ledge **24340"** is coextensive with a bottom surface **24321"** of

the corresponding trunnion slot **24320"**. In the illustrated arrangement, the bottom surface **24321"** of the trunnion slot **24320"** is approximately parallel to the end effector axis EA and/or the bottom **24312"** of the channel **24310"**. As can be seen in FIG. 56, a ramped portion **24346"** of the top surface **24342"** extends distally from the proximal surface portion **24344"** at an angle TSA and terminates in a horizontal distal surface portion **24348"**. In one arrangement, for example, the distal surface portion **24348"** is approximately parallel with the end effector axis EA and/or the bottom **24312"** of the channel **24310"** and the angle TSA=angle LA. However, angle TSA may be different from angle LA in other embodiments. Each trunnion **24418"** is received within a corresponding trunnion slot **24320"** and is free to rotate and translate therein.

[0593] Referring to FIGS. 55 and 56, a portion of an anvil lock **24702"** of the anvil locking system **24700"** is shown. The anvil lock **24702"** operates in the same manner as the anvil lock **20702** described above and includes a lockout body **24706"** that has an actuator tab (not shown) formed on a distal end thereof that is configured to be contacted by an unlocking feature that protrudes proximally from a compatible surgical staple cartridge. The anvil lock **24702"** may be fabricated from spring steel or other suitable metal and include a proximal biasing arm **24704"** that may be configured to be seated in a transverse spring mounting slot (not shown) that is provided in the body portion of a channel mount feature (not shown). The anvil lock **24702"** further includes an upwardly extending anvil lockout tab **24710"** that protrudes therefrom and is configured to extend above the distal surface portion **24348"** of the corresponding lobe ledge **24340"** and be even or level with the proximal surface portion **24344"** of the lobe ledge **24340"**.

[0594] FIG. 55 illustrates the anvil lock **24702'** in the distal, locked position with the anvil **24400"** pivoted to an open position. This may occur when no surgical staple cartridge has been inserted into the channel **24310"** or a non-compatible surgical staple cartridge (e.g., a surgical staple cartridge that lacks, among other things, a proper anvil unlocking feature required to bias the anvil lock **24702"** proximally) has been inserted into the channel **24310"**. When the anvil lock **24702"** is in that position, the anvil trunnions **24418"** are located in the proximal end of their respective trunnion slot **24320"** and the bottom lobe surface **24416"** of at least one lobe **24414"** is resting on the proximal surface portion **24344"** of the corresponding lobe ledge **24340"** as well as on the anvil lockout tab **24710"**. Should the user unwittingly attempt to close the anvil **24400"** when the anvil lock **24702"** is in the distal, locked position shown in FIGS. 52 and 55, the anvil lockout tab **24710"** will prevent the lobe **24414"** from pivoting downward onto the ramp surface portion **24346"** of the lobe ledge **24340"** which prevents the anvil **24400"** from pivoting to the closed position. See FIG. 52. Once a compatible surgical staple cartridge has been loaded into the end effector **24100"**, the anvil lockout feature thereon will bias the anvil lock **24702"** proximally into to the unlocked position. See FIGS. 56 and 57. When the anvil lock **24702"** is in the proximal unlocked position, the anvil lock out tab **24710"** is locked proximal to the ramp surface **24346"** on the lobe ledge **24340"** to thereby permit the lobe **24414"** to pivot downwardly thereon which results in the closure of the anvil **24400"**.

[0595] FIG. 58 depicts a proximal portion of another anvil 24400' that is configured to be pivotally supported in an elongate channel 24310' that is similar to channel 24310 except for the differences discussed below. The anvil 24400' comprises an anvil mounting portion 24410' that has trunnion formations 24412' formed thereon. Each trunnion formation 24412' comprises a laterally protruding actuator lobe 24414' that defines a bottom lobe surface 24416' that is configured to interact with an anvil locking system 24700' in the manner described above. The actuator lobe 24414' as well as the bottom lobe surface 24416' of the actuator lobe 24414' are located at an angle that is the same as the angle LA described above with respect to actuator lobe 24414'. A trunnion pin 24418' protrudes outwardly from the actuator lobe 24414' and is sized to translate and pivot within a corresponding trunnion slot 24320' that is formed in the elongate channel 24310'. See FIG. 59. In this example, the trunnion pin 24418' has a trunnion pin diameter TRD_A that is equal to the width LW₄ of the actuator lobe 24414'.

[0596] As can be seen in FIG. 59, the channel 24310' comprises a channel bottom 24312' and a pair of upstanding sidewalls 24314'. The channel 24310' may be coupled to an elongate shaft assembly 1200 (FIG. 5) by a channel mount feature 20340 which may facilitate articulation thereof about articulation joint 3020 (FIG. 5). FIG. 59 illustrates a portion of a proximal end 24316' of the channel 24310'. In one example, each channel wall 24314' has a trunnion slot 24320' formed therein. In the illustrated arrangement, a lobe ledge 24340' is formed in each channel wall 24314' such that a top surface 24342' of the lobe ledge 24340' is offset vertically from a bottom surface 24321' of the corresponding trunnion slot 24320' an offset distance OSD₁. Offset distance OSD₁ may be approximately equal to a distance between the trunnion 24418' and the bottom lobe surface 24416'. In the illustrated arrangement, the top surface 24342' of the lobe ledge 24340' is identical to the top surface 24342' of the lobe ledge 24340' and includes a proximal portion 24344' that is parallel to the bottom surface 24321' of the trunnion slot 24320' as well as a ramped surface 24346' and a distal surface 24348'.

[0597] The anvil locking system 24700' works in the same manner to prevent the anvil 24400' from closing. When no cartridge is present in the channel 24310' or a non-compatible cartridge (e.g. a cartridge that lacks the proper anvil unlocking feature to bias the anvil lock spring proximally) has been inserted into the channel 24310' the anvil lock tab 24710' is in its distal-most locked position preventing the corresponding actuator lobe 24414' from pivoting down onto the ramp surface 24346' thereby retaining the anvil 24400' in the open position. Once a compatible surgical staple cartridge has been loaded into the end effector 24100', the anvil lockout feature thereon will bias the anvil lock 24702' proximally into the unlocked position. When the anvil lock 24702' is in the proximal, unlocked position, the anvil lock out tab 24710' is locked proximal to the ramp surface 24346' on the lobe ledge 24340' to thereby permit the lobe 24414' to pivot downwardly thereon which results in the closure of the anvil 24400'.

[0598] FIGS. 60 and 61 illustrate another anvil 24400_A that is identical in construction and operation to anvil 24400 described above, except that the trunnion formation 24412_A is offset vertically from a bottom edge 24415_A of an anvil mounting portion 24410_A of the anvil 24400_A. FIG. 62

illustrates another anvil 24400_B that is identical in construction and operation to anvil 24400' described above, except that the trunnion formation 24412_B is offset vertically from a bottom edge 24415_B of an anvil mounting portion 24410_B of the anvil 24400_B.

[0599] The examples depicted in FIGS. 41-62 employ trunnion formations that comprise various shapes and configurations of lobe structures that serve to interact with an anvil lock feature such that the interaction between the anvil lock feature and the corresponding lobe structure serves to facilitate positioning of the anvil trunnions within their respective trunnion slots. This positioning of the lobe structures permits the anvil to close upon application of closure motions thereto when a compatible surgical staple cartridge has been loaded into the end effector. In instances wherein an incompatible surgical staple cartridge has been loaded into the end effector, the anvil lock feature will retain the corresponding trunnion formation in a position wherein the anvil will be unable to close even upon application of a closure motion thereto. Thus, the initial positions of the trunnion formations prevent closure, but loading of a proper or compatible surgical staple cartridge into the channel changes positions of the trunnion formations to allow closure to occur. The various lobe features described herein are also generally more robust than previous trunnion arrangements which may lead to improved anvil reliability.

[0600] FIGS. 63-69 depict a surgical end effector 25300 that may be used for example in connection with the powered surgical instrument 1010 described above. The surgical end effector 25300 comprises an anvil 25400 that is pivotally supported on an elongate channel 25310 that is configured to operably support a surgical staple cartridge 25600. The anvil 25400 is movable between an open position and a closed position through interaction with an axially movable closure member in the various manners disclosed herein. In the illustrated example, the anvil 25400 comprises an anvil body 25402 and an anvil mounting portion 25410. The anvil mounting portion 25410 comprises a pair of laterally extending trunnions 25412 that are operably received within corresponding trunnion slots provided in upstanding sidewalls 25314 of the channel 25310 in the various manners disclosed herein. As was discussed above with respect to end effector 1300, anvil 25400 may be pivoted between an open and a closed position by interaction with an end effector closure tube 3050 in the various manners described herein. For example, the end effector closure tube 3050 may be axially moved by actuation of a closure trigger 1032 of the surgical instrument 1010. In other arrangements, the end effector 25300 and shaft assembly to which it is attached may operably interface with a robotic system as is described in detail in many of the references which have been incorporated herein by reference. In such applications, the end effector closure tube 3050 may be axially advanced and retracted through actuation of a closure control system of the robotic system.

[0601] In the illustrated arrangement, distal movement of the end effector closure tube 3050 causes a distal end 3051 of the end effector closure tube 3050 to operably interact with a camming surface 25411 that is formed on the anvil mounting portion 25410 to cam the anvil 25400 to a closed position. When the end effector closure tube 3050 is axially retracted in the proximal direction, the end effector closure tube 3050 may be configured to interact with various formations, ledges or tabs to apply an opening motion to the

anvil **25400**. Further details may be found in various other references which have been herein incorporated by reference.

[0602] The elongate channel **25310** may be coupled to an elongate shaft assembly **1200** (FIG. 5) by a channel mount feature **20340** which may facilitate articulation thereof about articulation joint **3020** (FIG. 5) in the various manners described herein. The illustrated example also includes a firing member **20500** (FIG. 20) that is attached to a distal end of a firing member beam **1900** (FIG. 5) and is configured to operably interface with a camming assembly in a surgical staple cartridge **25600** that has been loaded into the channel **25310**. To ensure that a compatible surgical staple cartridge **25600** has been loaded into the end effector **25300** prior to closure of the anvil **25400**, the end effector employs a closure lockout system **25700**. In the illustrated example, the closure lockout system **25700** is configured to prevent a distal movement of the end effector closure tube **3050** unless a compatible cartridge **25600** has been properly seated within the channel **25310**. In one example, the closure lockout system **25700** comprises a closure lock **25702** that is configured to move between a locked position and an unlocked position in response to installation of a compatible surgical staple cartridge **25600** therein. FIGS. 65-69 illustrate one form of a closure lock **25702** that may be fabricated from spring steel or other suitable metal and include a body portion **25706** that is pivotally pinned to the body portion **20342** of the channel mount feature **20340** by a pivot pin **25709** that extends through a pivot hole **25707** in the body portion **25706**. The closure lock **25702** further includes a proximal biasing arm **25704** that may be configured to be seated in a slot (not shown) that is provided in the body portion **20342** of the channel mount feature **20340**. Such arrangement serves to bias the closure lock **25702** downward within the channel **25310**.

[0603] As can be most particularly seen in FIGS. 65 and 66, in the illustrated example, the closure lock **25702** further includes a blocking feature **25710** that protrudes from a bottom of the body portion **25706** and extends laterally outward. As illustrated in FIG. 65, when the closure lock **25702** is in the locked position, the blocking feature **25710** is positioned to block the distal advancement of the end effector closure tube **3050**. When the closure lock **25702** is in the unlocked position as shown in FIG. 66, the blocking feature **25710** is moved away from the blocking position to permit the distal advancement of the end effector closure tube **3050**.

[0604] Turning to FIG. 67, the closure lock **25702** further includes an actuator portion **25712** that extends proximally to be engaged by a closure unlocking feature **25630** formed on a proximal end **25604** of a compatible surgical staple cartridge **25600**. In at least one arrangement, the surgical staple cartridge **25600** comprises an elongate cartridge body **25602** that is sized to be removably seated in the elongate channel **25310**. The cartridge body **25602** includes a cartridge slot **25608** that extends from the proximal end portion **25604** to a distal end portion **25606** (FIG. 64) of the cartridge body **25602**. The cartridge body **25602** further comprises a cartridge deck surface **25610** that confronts a staple-forming undersurface **25404** of the anvil **25400** when the cartridge **25600** is seated in the channel **25310** and the anvil **25400** is pivoted to a closed position. Although not shown in FIG. 67, the surgical staple cartridge **25600** may have a plurality of (usually three) lines of surgical staple

pockets on each side of the cartridge slot **25608** that open through the cartridge deck surface **25610**. Each staple pocket may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body **25602** is molded from a polymer material with the staple pockets molded or machined therein. In one arrangement, the staple pockets also open through a bottom of the cartridge body **25602** to facilitate installation of the drivers and fasteners into their respective pockets. Once the drivers and fasteners are inserted into their respective staple pockets, a cartridge pan **25620** is attached to the bottom of the cartridge body **25602**. When installed, the cartridge pan **25620** may, among other things, prevent the drivers and fasteners from falling out of the bottom of the cartridge body **25602** during handling and installation of the cartridge **25600** into the elongate channel **25310**. As was discussed above in connection with cartridge **20040**, cartridge **25600** operably supports a camming assembly therein. The camming assembly comprises a series of spaced cam members that are configured to move axially within corresponding cam slots **25609** formed on each side of the cartridge slot **25608** in the cartridge body **25602**. The cam slots **25609** are aligned with corresponding lines of drivers in the cartridge body **25602** to facilitate camming contact with a corresponding cam member as the camming assembly is driven through the staple cartridge **25600** from a beginning position within the proximal end portion **25604** of the cartridge body **25602** to an ending position within the distal end portion **25606**.

[0605] FIGS. 63 and 68 illustrate the surgical end effector **25300** without a surgical staple cartridge installed therein. As can be seen in FIG. 68, the proximal biasing arm **25704** has biased the closure lock **25702** downward in the channel **25310** which results in the blocking feature **25710** moving into blocking alignment with the distal end **3051** of the end effector closure tube **3050** (locked position). Should the user activate the closure system to move the end effector closure tube **3050** distally, the blocking feature **25710** will block the distal advancement of the end effector closure tube **3050** thereby preventing an application of closure motions to the anvil **25400**. Returning to FIG. 67, in at least one arrangement, the staple cartridge **25600** includes an anvil unlocking feature or tab **25630** that protrudes proximally from the cartridge body **25602** and is aligned to unlockingly engage the actuation tab **25712** that is formed on the distal end of the closure lock **25702** when the cartridge **25600** has been operably installed in the elongate channel **25310**. In one example, the unlocking feature **25630** has a somewhat ramped surface **25632** that is configured to operably interact with an angled surface **25713** on the actuation tab **25712** so that the when the ramped surface **25632** and the angled surface **25713** are brought into engagement, the closure lock **25702** is pivoted in an upward direction. When the closure lock **25702** is pivoted upward into the unlocked position, the blocking feature **25710** is no longer in blocking alignment with the end effector closure tube **3050**. See FIG. 66.

[0606] FIGS. 64 and 69 depict the surgical end effector **25300** with a compatible surgical staple cartridge **25600** operably installed in the elongate channel **25310**. As can be seen in FIG. 69, the ramped surface **25632** on the unlocking feature **25630** on the staple cartridge body **25602** has contacted the angled surface **25713** (shown in FIG. 68) on the actuation tab **25712** on the closure lock **25702** to bias the closure lock **25702** into the unlocked position. When in that

position, the user may distally advance the end effector closure tube 3050 distally to apply closing motions to the anvil 25400. Should the user attempt to install an inappropriate cartridge that lacks the unlocking feature 25630 in an appropriate position or similar feature designed to unlocking engage the closure lock 25702, the user will be unable to distally advance the end effector closure tube 3050 to close the anvil 25400.

[0607] FIGS. 70 and 71 illustrate a surgical end effector 25300' that comprises an anvil 25400' that is pivotally supported on a channel 25310' and is substantially identical to end effector 25300 described above except that the closure locking system 25700' employs a different closure lock 25702' that is configured to interact with an unlocking feature provided on a camming assembly 25650' within a surgical staple cartridge 25600'. As can be seen in FIGS. 70 and 71, the closure lock 25702' comprises an elongate body 25706' that has a tapered actuator tab portion 25712' on its distal end. The body 25706' is pivotally attached to the channel mount feature 20340 and a proximal biasing arm 25704' biases the closure lock 25702' within the channel 25310'.

[0608] FIG. 72 illustrates a surgical staple cartridge 25600' that comprises an elongate cartridge body 25602' that is sized to be removably seated in the elongate channel 25310'. The cartridge body 25602' includes a cartridge slot 25608' that extends from a proximal end portion 25604' to a distal end portion of the cartridge body 25602'. The cartridge body 25602' further comprises a cartridge deck surface 25610' that confronts a staple-forming undersurface 25404' of the anvil 25400' when the cartridge 25600' is seated in the channel 25310' and the anvil 25400' is pivoted to a closed position. Although not shown in FIG. 72, the surgical staple cartridge 25600' may have a plurality of (usually three) lines of surgical staple pockets on each side of the cartridge slot 25608' that open through the cartridge deck surface 25610'. Each staple pocket may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body 25602' is molded from a polymer material with the staple pockets molded or machined therein. In one arrangement, the staple pockets also open through a bottom of the cartridge body 25602' to facilitate installation of the drivers and fasteners into their respective pockets. Once the drivers and fasteners are inserted into their respective staple pockets, a cartridge pan 25620' is attached to the bottom of the cartridge body 25602'. When installed, the cartridge pan 25620' may, among other things, prevent the drivers and fasteners from falling out of the bottom of the cartridge body 25602' during handling and installation of the cartridge 25600' into the elongate channel 25310'. A camming assembly 25650' is operably supported in the cartridge body 25602'. In at least one arrangement, the camming assembly 25650' comprises a series of spaced cam members 25652' that are configured to move axially within corresponding cam slots 25609' that are formed on each side of the cartridge slot 25608' in the cartridge body 25602'. The cam slots 25609' are aligned with corresponding lines of drivers in the cartridge body 25602' to facilitate camming contact with a corresponding cam member 25652' as the camming assembly 25650' is driven through the staple cartridge 25600' from a beginning position within the proximal end portion 25604' of the cartridge body 25602' to an ending position within the distal end portion. In at least one

example, the camming assembly 25650' includes a closure unlocking feature or tab 25660' that protrudes proximally from the camming assembly 25650' and is aligned to unlockingly engage the actuation tab 25712' that is formed on the distal end of the closure lock 25702' when the cartridge 25600' has been operably installed in the elongate channel 25310' and the camming assembly 25650' is in its unfired beginning position within the cartridge 25600'.

[0609] Returning to FIG. 71, in one example, the unlocking feature 25660' has a tapered nose portion 25662' that is configured to operably interact with the actuation tab 25712' so that when the tapered nose portion 25662' is brought into engagement with the actuation tab 25712', the closure lock 25702' is pivoted upward. When the closure lock 25702' is pivoted upward into the unlocked position, a blocking feature 25710' on the closure lock 25702' is no longer in blocking alignment with the end effector closure tube 3050.

[0610] As can be seen in FIG. 72, the cartridge body 25602' may further include a locking safety 25670' that protrudes proximally from a proximal end of the cartridge body 25602' and adjacent to the tapered nose portion 25662'. An upper surface 25672' of the locking safety 25670' is angled to match the tapered nose portion 25662' but when the camming assembly 25650' is in its proximal-most beginning position, the tapered nose portion 25662' protrudes proximally beyond the end of the locking safety 25670'.

[0611] FIG. 70 illustrates an initial insertion of an unfired compatible surgical staple cartridge 25600' into the channel 25310'. As can be seen in FIG. 70 the tapered nose portion 25662' has made initial contact with the actuator tab portion 25712' on the closure lock 25702'. The closure lock 25702' remains biased downward to a locked position wherein the blocking feature 25710' of the closure lock 25702' is in blocking alignment with the distal end 3051 of the end effector closure tube 3050. As the cartridge 25600' is further advanced proximally into a seated position within the channel 25310', the tapered nose portion 25662' on the camming assembly 25650' lifts the actuation tab 25712' upward above the angled upper surface 25672' of the locking safety 25670' to enable the closure lock 25702' to pivot into the unlocked position wherein the blocking feature 25710' is no longer in blocking alignment with the distal end 3051 of the end effector closure tube 3050. When in that position, the user may advance the end effector closure tube 3050 distally to apply closing motions to the anvil 25400'. Thus, in this embodiment, the closure locking system 25700' is actuated by the camming assembly 25650', but only when the camming assembly 25650' is in an unfired beginning position.

[0612] FIG. 73 illustrates insertion of a staple cartridge 25600X wherein the camming assembly thereof is not in a proximal-most unfired position. This may occur when the user attempts to use the staple cartridge 25600X that has been previously used, for example. Because the camming assembly is not in its unfired beginning position, the tapered nose portion is absent to begin to bias the closure lock 25702' into an upward position above the closure safety 25670'. When the cartridge 25600X is fully seated in the channel 25310', the action tab 25712' of the closure lock 25702' is positioned under a lower lock surface 25674'. The closure lock 25702' remains in the locked position wherein the blocking feature 25710' thereof is in blocking alignment with the distal end 3051 of the end effector closure tube 3050. Should the user unwittingly attempt to distally advance the end effector closure tube 3050 to close the anvil

25400', the distal end **3051** will contact the blocking feature **25710'** and the closure safety **25670'** will further prevent the closure lock **25702'** from pivoting upwardly to an unlocked position under the closure load.

[0613] FIGS. 74 and 75 illustrate a surgical end effector **25300** that comprises an anvil **25400** that is pivotally supported on a channel **25310** and is substantially identical to end effector **25300'** described above. End effector **25300** employs a closure locking system **25700** that comprises a closure lock **25702**. As can be seen in FIG. 76, the closure lock **25702** comprises an elongate body **25706** that has an actuator tab portion **25712** on its distal end. The body **25706** includes a lower spring arm **25720** that is mounted within the channel **25310**. The lower spring arm **25720** is mounted so as to apply a downwardly biasing force to the closure lock **25702** which will be discussed below. As will also be discussed in further detail below, the closure lock **25702** further includes a vertically extending anvil locking tab **25710** that is configured to lockingly interact with a lock lug **25414** that is formed on an anvil mounting portion **25410** of the anvil **25400**. In addition, the closure lock **25702** comprises a proximal biasing spring **25704** which serves to bias the closure lock **25702** in the distal direction DD (FIG. 76). As can be seen in FIG. 74, the elongate channel **25310** may be coupled to an elongate shaft assembly **1200** (FIG. 5) by a channel mount feature **20340** which may facilitate articulation thereof about articulation joint **3020** (FIG. 5) in the various manners described herein. As can be seen in FIG. 76, the proximal biasing spring **25704** is configured to be seated within the transverse slot **20343** in the body portion **20342** of the channel mount feature **20340**.

[0614] Similar to the closure of anvil **25400'** discussed above, distal movement of an end effector closure tube causes a distal end of the end effector closure tube to operably interact with a camming surface **25411** formed on an anvil mounting portion **25410** of the anvil **25400** to cam the anvil **25400** to a closed position. When the end effector closure tube is axially retracted in the proximal direction, the end effector closure tube may be configured to interact with various formations, ledges or tabs to apply an opening motion to the anvil **25400**. Further details may be found in various other references which have been herein incorporated by reference.

[0615] FIG. 77 illustrates a surgical staple cartridge **25600** that comprises an elongate cartridge body **25602** that is sized to be removably seated in the elongate channel **25310**. The cartridge body **25602** includes a cartridge slot **25608** that extends from a proximal end portion **25604** to a distal end portion of the cartridge body **25602**. The cartridge body **25602** further comprises a cartridge deck surface **25610** that confronts a staple-forming undersurface **25404** of the anvil **25400** when the cartridge **25600** is seated in the channel **25310** and the anvil **25400** is pivoted to a closed position. Although not shown in FIG. 77, the surgical staple cartridge **25600** may have a plurality of (usually three) lines of surgical staple pockets on each side of the cartridge slot **25608** that open through the cartridge deck surface **25610**. Each staple pocket may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body **25602** is molded from a polymer material with the staple pockets molded or machined therein. In one arrangement, the staple pockets also open through a bottom of the cartridge body **25602** to

facilitate installation of the drivers and fasteners into their respective pockets. A camming assembly **25650** is operably supported in the cartridge body **25602**. In at least one arrangement, the camming assembly **25650** comprises a series of spaced cam members **25652** that are configured to move axially within corresponding cam slots **25609** that are formed on each side of the cartridge slot **25608** in the cartridge body **25602**. The cam slots **25609** are aligned with corresponding lines of drivers in the cartridge body **25602** to facilitate camming contact with a corresponding cam member **25652** as the camming assembly **25650** is driven through the staple cartridge **25600** from a beginning position within the proximal end portion **25604** of the cartridge body **25602** to an ending position within the distal end portion. In at least one example, the camming assembly **25650** includes a closure unlocking feature or tab **25660** that protrudes proximally from the camming assembly **25650** and is aligned to unlockingly engage the actuation tab **25712** that is formed on the distal end of the closure lock **25702** when the surgical staple cartridge **25600** has been operably installed in the elongate channel **25310** and the camming assembly **25650** is in its unfired beginning position within the cartridge **25600**.

[0616] Returning to FIG. 77, in one example, the unlocking feature **25660** has a tapered nose portion **25662** that is configured to operably interact with the actuation tab **25712** so that when the tapered nose portion **25662** is brought into engagement with the actuation tab **25712**, the closure lock **25702** is moved upward against a downward biasing force established by the lower spring **25720**. When the closure lock **25702** is pivoted upward into the unlocked position, the anvil locking tab **25710** on the closure lock **25702** is no longer in blocking alignment with the lock lug **25414** on the anvil mounting portion **24410**.

[0617] FIG. 74 illustrates an initial insertion of an unfired compatible surgical staple cartridge **25600** into the channel **25310**. As can be seen in FIG. 74, the tapered nose portion **25662** of the camming assembly **25650** has not yet interacted with the actuator tab portion **25712** on the closure lock **25702**. The closure lock **25702** remains biased downward to a locked position wherein the anvil locking tab **25710** of the closure lock **25702** is in blocking alignment with the lock lug **25414** on the anvil mounting portion **25410** of the anvil **25400**. As the surgical staple cartridge **25600** is further advanced proximally into a seated position within the channel **25310**, the tapered nose portion **25662** on the camming assembly **25650** contacts the actuation tab **25712** and biases the closure lock **25702** upward to an unlocked position wherein the anvil locking tab **25710** is no longer aligned with the anvil lock lug **25414**. When in that position, the user may close the anvil **25400** by distally advancing the end effector closure tube to apply closing motions to the anvil **25400**. Thus, in this embodiment, the closure locking system **25700** is actuated by the camming assembly **25650**, but only when the camming assembly **25650** is in an unfired beginning position. Once the surgical staple cartridge **25600** has been removed from the channel **25310**, the lower spring **25720** on the closure lock **25702** will bias the closure lock **25702** downwardly back into its locked position wherein the anvil locking tab **25710** is in blocking alignment with the lock lug **25414** on the anvil **25400**.

[0618] FIG. 78 illustrates insertion of a staple cartridge **25600X** that has a camming assembly therein that is not in

a proximal-most unfired position. Because the camming assembly is not in its unfired, beginning position, the tapered nose portion is absent to bias the closure lock **25702** upward into the unlocked position. The closure lock **25702** remains in the locked position wherein the anvil locking tab **25710** thereof is in blocking alignment with the anvil lock lug **25414** on the anvil **25400**. Should the user unwittingly attempt to close the anvil **25400**, the anvil lock lug **25414** will contact the anvil locking tab **25710** on the closure lock **25702** and prevent the anvil **25400** from pivoting to the closed position.

[0619] FIGS. 79-83 illustrate an alternative cartridge nose assembly **25800** that may be employed with any of the cartridges and channel arrangements disclosed herein to provide another mechanism for ensuring that a surgical staple cartridge that is inserted into the end effector channel is compatible with the end effector and to provide the user with another visual indicator that the cartridge has been fired. For example, the cartridge nose assembly **25800** may be employed with the cartridge **25600** and the channel **25310** of the end effector **25300** (FIG. 64). In the illustrated arrangement, cartridge nose assembly **25800** comprises a nose assembly body **25802** that is movably coupled to a distal end **25606** of the cartridge body **25602**. As can be seen in FIGS. 81 and 82, the distal end portion **25606** of the cartridge body **25602** comprises a distally extending tapered portion **25605** that is adapted to be received within complementary shaped nose notch **25804** in the nose assembly body **25802**. In addition, the nose assembly body **25802** is configured with axial alignment features (not shown) that may be slidably supported in axial grooves **25607** provided in the distal end portion **25606** of the cartridge body **25602**.

[0620] As can be seen in FIGS. 83 and 84, a nose retainer latch arm **25810** extends proximally from an upper portion of the nose assembly body **25802** into a latch cavity **25680** formed in the cartridge body **25602**. The nose assembly body **25802** is axially movable from a locked position shown in FIGS. 81 and 83 to an unlocked position shown in FIGS. 82 and 84. When the nose assembly body **25802** is in the unlocked position, a retention latch **25812** that is formed on a proximal end of the retainer latch arm **25810** engages a retention lug **25682** that is formed on the distal end portion **25606** of the cartridge body **25602** to retain the cartridge nose assembly **25800** on the distal end **25606** of the cartridge body **25602**.

[0621] Referring now to FIGS. 81 and 82, the nose assembly body **25802** further comprises proximally extending nose tab portions **25820** that are sized to frictionally engage corresponding distal extending channel ledges **25317** formed on a distal end **25315** of the channel **25310** to retain the nose assembly **25800** in the proximally forward "locked position". As can be seen in FIGS. 83 and 84, the nose assembly body **25802** may further include an integral spring arm **25830** that is configured to interact with a spring lug **25684** that is formed on the distally extending tapered portion **25605** of the cartridge body **25602**. The spring arm **25830** applies a distal biasing force BF to the cartridge nose assembly **25800** to increase the frictional force between the nose tab portions **25820** and the channel ledges **25317** to retain the cartridge nose assembly **25800** in the locked position.

[0622] In operation, the cartridge nose assembly **25800** is in the locked position when the cartridge **25600** is in its unfired state and is ready to be installed in the channel

25310. To install the unfired cartridge **25600** into the end effector **25300**, the cartridge body **25602** is placed in the channel **25310** and then advanced proximally therein to engage the channel ledges **25317** with the nose tab portions **25820** as shown in FIGS. 81 and 82. As discussed above, when the cartridge **25600** is unfired, the camming assembly **25650** is in its proximal-most beginning position. During the firing process, the camming assembly **25650** is driven in the cartridge body **25602** to its distal-most position therein. When the camming assembly **25650** reaches its distal-most position, a central body portion **25651** of the camming assembly **25650** contacts the cartridge nose assembly **25800** with a sufficient amount of force to overcome the frictional forces FF retaining the cartridge nose assembly **25800** in the locked position and moves the cartridge nose assembly **25800** axially into the unlocked position. In the alternative, the user may disengage the cartridge nose assembly **25800** by pulling it distally to the unlocked position. Once the cartridge nose assembly **25800** is moved to the unlocked position, the cartridge **25600** may be removed from the elongate channel **25310**. In addition, the distally extending cartridge nose assembly **25800** may provide the user with a visual indication that the cartridge has been fired (spent).

[0623] FIGS. 85 and 86 illustrate a portion of a surgical end effector **26300** that employs a firing member **26120** that may be configured to be distally advanced by a rotary powered firing system or an axial powered (non-rotary powered) firing system. In particular, the firing member **26120** may be employed in connection with any of the various end effector arrangements and firing drive system configurations disclosed herein, as well as in connection with those end effector and firing drive system configurations described in the various references incorporated by reference herein.

[0624] As can be seen in FIGS. 85 and 86, the firing member **26120** comprises a firing member body **26122** that includes a firing member lockout system **26140** that comprises a firing member lockout **26142** that is pivotally attached to the firing member body **26122**. The firing member lockout **26142** comprises a lockout body **26144** that comprises a pair of legs **26146** that straddle the firing member body **26122** and are pivotally attached thereto. The lockout body **26144** further includes a sled latch **26148** that is configured for contact with a camming sled or camming assembly **26650** that is operably supported in a staple cartridge (not shown). FIG. 85 illustrates the firing member **26120** in a proximal-most starting position. As can be seen in FIGS. 85 and 86, a firing lockout hole **26315** is provided through a bottom portion **26312** of an elongate channel **26310** of the end effector **26300**. A lockout spring **26150** is mounted in the elongate channel **26310** and is configured to bias the firing member lockout **26142** downward such that, if a fresh unfired staple cartridge has not been properly loaded into the elongate channel **26310**, a distal edge **26149** of the lockout body **26144** engages an angled distal edge **26317** of the firing lockout hole **26315**. When in that position, should the user inadvertently attempt to distally advance the firing member **26120**, the firing member lockout **26142** prevents the distal advancement of the firing member **26120** as shown in FIG. 86.

[0625] A fresh, unfired surgical staple cartridge contains a camming assembly **26650** that is located in a starting or unfired position that is proximal to the lines of staple drivers that are supported in the cartridge body. As used herein, the

terms “fresh, unfired” means that the staple cartridge has all of its intended staples or fasteners in their respective unfired positions and the camming assembly is in a proximal unfired starting position. When a fresh, unfired surgical staple cartridge has been properly seated within the elongate channel **26310**, a proximally extending unlocking portion **26653** on the camming assembly **26650** engages the sled latch **26148** on the firing member lockout **26142** to pivot the firing member lockout **26142** into an unlocked position wherein the firing member lockout **26142** does not extend into the firing lockout hole **26315** in the elongate channel **26310**. FIG. **85** illustrates a camming assembly **26650** in the starting position and the firing member **26120** is free to be advanced distally by actuating the firing drive system.

[**0626**] At the completion of the firing process, the camming assembly **26650** may remain at the distal end of the staple cartridge (i.e., in a “fired” position”) while the firing member **26120** is retracted back to its starting position wherein the anvil may be opened and the spent cartridge removed from the channel **26310**. Thus, once a surgical staple cartridge has been spent (e.g., completely fired) the camming assembly **26650** is not returned to its starting position. As such, if the spent cartridge were to be inadvertently re-installed in the end effector **26300**, the camming assembly **26650** is not in a starting position wherein the camming assembly **26650** can unlock the firing member lockout **26142**. Thus, the firing member lockout system **26140** may also be referred to herein as a “spent cartridge lockout system”.

[**0627**] FIGS. **87-90** illustrate an anvil **26400** that is configured to be pivotally supported on the channel **26310** or a similar channel of the various types disclosed herein. In FIGS. **87-89**, the channel has been omitted for clarity. In the illustrated arrangement, the anvil **26400** includes a cartridge verification system **26440** that may be configured to prevent firing of an incompatible cartridge that has been otherwise seated in the cartridge. The anvil **26400** and cartridge verification system **26440** may be used in connection with a surgical end effector **26300** that employs a firing member **26120** that is equipped with an onboard firing member lockout system **26140** that is configured to prevent the distal advancement of the firing member **26120** unless the firing member lockout **26142** has been moved to an unlocked position through interaction with a corresponding camming assembly located in the surgical staple cartridge. The cartridge verification system **26440** may also be used in connection with surgical end effectors that employ an axially advanced (non-rotary) firing member that is otherwise equipped with a firing member lockout system that is similar to the firing member lockout system **26140**.

[**0628**] FIG. **90** illustrates a portion of a surgical staple cartridge **26600** that is compatible with the surgical end effector **26300**. In at least one arrangement, the surgical staple cartridge **26600** comprises an elongate cartridge body **26602** that is sized to be removably seated in the elongate channel of the end effector **26300**. The cartridge body **26602** includes a cartridge slot **26608** that extends from a proximal end portion **26604** to a distal end portion of the cartridge body **26602**. The cartridge body **26602** further comprises a cartridge deck surface **26610** that confronts a staple-forming undersurface **26404** of the anvil **26400** when the cartridge **26600** is seated in the channel and the anvil **26400** is pivoted to a closed position. Although not shown in FIG. **90**, the surgical staple cartridge **26600** may have a plurality of

(usually three) lines of surgical staple pockets on each side of the cartridge slot **26608** that open through the cartridge deck surface **26610**. Each staple pocket may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body **26602** is molded from a polymer material with the staple pockets molded or machined therein. In one arrangement, the staple pockets also open through a bottom of the cartridge body **26602** to facilitate installation of the drivers and fasteners into their respective pockets. Once the drivers and fasteners are inserted into their respective staple pockets, a cartridge pan **26620** is attached to the bottom of the cartridge body **26602**. When installed, the cartridge pan **26620** may, among other things, prevent the drivers and fasteners from falling out of the bottom of the cartridge body **26602** during handling and installation of the cartridge **26600** into the elongate channel **26310**.

[**0629**] In the illustrated arrangement, the cartridge **26600** operably supports a camming assembly **26650** therein. The camming assembly **26650** comprises a central body portion **26652** and a series of spaced cam members **26654** that are configured to move axially within corresponding cam slots **26609** formed on each side of the cartridge slot **26608** in the cartridge body **26602**. The cam slots **26609** are aligned with corresponding lines of drivers in the cartridge body **26602** to facilitate camming contact with a corresponding cam member **26654** as the camming assembly **26650** is driven through the staple cartridge **26600** from a beginning position within the proximal end portion **26604** of the cartridge body **26602** to an ending position within the distal end portion of the cartridge body **26602**. The central body portion **26652** includes the proximally extending unlocking portion **26653** that is configured to engage the sled latch **26148** on the firing member lock **26142** when the cartridge **26600** has been properly loaded into the channel **26310**. As can be seen in FIG. **90**, when the camming assembly **26650** is in its proximal-most starting position wherein the unlocking portion **26653** can move the firing member lockout **26142** to the unlocked position, each of the cam members **26654** may protrude proximally out of their respective cam slots **26609**.

[**0630**] Referring now to FIGS. **87** and **91**, in the illustrated arrangement, the cartridge verification system **26440** comprises a cartridge verification member or shuttle member **26442** that is attached to an underside of an anvil mounting portion **26410** of the anvil **26400**. The cartridge verification member **26442** may be of one-piece construction and include a pair of downwardly extending shuttle legs **26444** that are bifurcated by a firing member slot **26447** (FIG. **91**) to facilitate passage of the firing member **26120** therebetween. In other arrangements, the cartridge verification member **26442** may be of two-piece construction which consists of two separate downwardly extending shuttle legs **26444** that are separated from each other by a space **26448** that is configured to accommodate passage of the firing member body **26122** therethrough. In either case, the shuttle member **26442** may be fabricated from a compliant polymer or rubber material and be attached to the underside of the anvil mounting portion **26410** by appropriate adhesive of fastener arrangements.

[**0631**] In the illustrated example, each shuttle leg **26444** includes a distally protruding sled actuator arm **26446**. Returning to FIG. **90**, the cartridge body **26602** includes two proximally protruding verification features or cartridge key

portions **26630** that are configured to unlockingly engage the sled actuator arm **26446** on a corresponding shuttle leg **26444** when the cartridge **26600** is operably seated in the channel **26310**. As will be discussed further below, if the verification features **26630** are not present to contact the corresponding sled actuator arm **26446**, the sled actuator arms **26446** would otherwise contact the protruding cam members **26654** and push or urge the camming assembly **26650** distally into a position wherein the unlocking portion **26653** on the camming assembly **26650** is no longer in unlocking engagement with the sled latch **26148** on the firing member lock **26142**.

[0632] Interaction between the cartridge verification system **26440** and cartridge **26600** may be understood from reference to FIGS. **87-92**. FIG. **87** illustrates initial installation of a compatible surgical staple cartridge **26600** into the end effector **26300**. Although the channel has been omitted from the drawings, the anvil **26400** is shown in a fully open position. In the illustrated example, the anvil **26400** is movably journaled on the channel such that upon application of an initial closure motion thereto from a closure member arrangement of many of the various closure systems described herein, the anvil **26400** pivots to a partially closed position or intermediate position shown in FIG. **88**. When in that position, each sled actuator arm **26446** is confrontingly aligned with the corresponding verification feature **26630** on the cartridge body **26602**. Further application of the closure motion to the anvil **26400** may also cause the anvil **26400** to translate distally into a closed position. When the anvil **26400** moves distally, the verification features **26630** block the distal movement of the corresponding compliant sled actuator arms **26446** to prevent the sled actuator arm **26446** from contacting the proximally protruding cam members **26654**. Thus, the camming assembly **26650** remains in its starting position wherein the unlocking portion **26653** on the camming assembly **26650** remains in unlocking engagement with the sled latch **26148** on the firing member lock **26142**. Thus, the firing member **26120** is free to move distally through the cartridge **26600** upon actuation of the firing drive system.

[0633] FIG. **92** illustrates a cartridge **26600X** that may be very similar to cartridge **26600** but is “incompatible” with the surgical end effector **26300**. For example, the cartridge **26600X** lacks the verification features or key portions **26630** of the cartridge **26600**. In addition, to lacking the verification features or keys **26630**, the cartridge **26600X** may also differ from the cartridge **26600** in the numbers, sizes, locations, etc. of the fasteners contained therein, notwithstanding the fact that the cartridge **26600X** may have a camming assembly **26650** that is identical in construction and use as the camming assembly **26650** employed in cartridges **26600**.

[0634] FIGS. **93-95** illustrate insertion of an incompatible cartridge **26600X** into the surgical end effector **26300**. FIG. **93** illustrates initial installation of an incompatible surgical staple cartridge **26600X** into the end effector **26300**. Although the channel has been omitted from the drawings, the anvil **26400** is shown in a fully open position. FIG. **94** illustrates the anvil **26400** in an intermediate position upon application of an initial closure motion thereto. When in that position, each sled actuator arm **26446** is confrontingly aligned with corresponding cam members **26654** that protrude proximally out of their respective cam slots **26609**. Further application of the closure motion to the anvil **26400**

may cause the anvil **26400** to translate distally into a final closed position. When the anvil **26400** moves distally, the sled actuator arms **26446** contact the proximally protruding cam members **26654** and move the camming assembly **26650** distally to a point wherein the unlocking portion **26653** thereon is no longer in engagement with the sled latch **26148** on the firing member lock **26142**. Thus, the firing member lockout **26142** remains in locking engagement with the elongate channel **26310** of the end effector **26300** to prevent the distal advancement of the firing member **26120** upon actuation of the firing drive system.

[0635] FIGS. **96-98** illustrate another cartridge verification system **26440'** that may be employed with an end effector **26300'** that employs a firing member **20500** that is axially advanced by a firing member beam **1900** in the various manners discussed herein. As was discussed above, the firing member **20500** comprises a firing member body **20502** that is configured to axially pass through vertically aligned slots in the anvil (not shown), a staple cartridge **26600'**, and the elongate channel **26310'**. A lower foot assembly **20506** that comprises a pair of laterally extending lower flanges extends from a bottom end of the firing member body **20502** to slidably engage corresponding channel ledges that are formed on each side of the channel slot. An upper foot that comprises two laterally extending anvil tabs **20507** may be formed on an upper end of the firing member body **20502** and is configured to slidably engage anvil ledges (not shown) that are formed on each side of the anvil slot. In at least one arrangement, the firing member **20500** further includes a pair of central tabs (not shown) that extend laterally from each side of the firing member body **20502**.

[0636] The firing member body **20502** is also configured with a proximally extending spring tail **20512** that may be configured to operably interface with a firing member lockout spring (not shown) that is mounted in the elongate channel **26310'** and is configured to bias the firing member **20500** downward in the elongate channel **26310'** into a locked position. When in the locked position, the firing member foot **20506** and/or the central tabs are misaligned with corresponding passages in the channel **26310'** and as such, should the user attempt to distally advance the firing member **20500** when in that locked out state, the firing member **20500** would not move distally due to such misalignment. That is, the foot **20506** and/or central tabs contact portions of the elongate channel **26310'** to thereby prevent the distal advancement of the firing member **20500**. In one arrangement, a sled latch **20514** is formed on the firing member body **20502** and is configured to be engaged by a proximally extending unlocking portion **26653'** on a camming assembly **26650'** that is operably supported in a proximal-most unfired or starting position within a compatible cartridge **26600'** that has been operably seated in the channel **26310'**. When a fresh, unfired staple cartridge **26600'** with the camming assembly **26650'** thereof in its unfired position has been operably installed in the elongate channel **26310'**, the unlocking portion **26653'** on the camming assembly **26650'** engages the sled latch **20514** on the firing member body **20502** and moves the firing member **20500** upward into an unlocked position wherein the lower foot assembly **20506** and/or the central tabs are aligned with their respective passages in the channel **26310'** to permit the firing member **20500** to axially advance therein. As the user distally advances the firing member **20500** into the cartridge

26600', the firing member **20500** also drives the camming assembly **20650'** therein which cams the drivers upward to drive the staples or fasteners supported thereon into forming contact with the underside of the anvil. The tissue cutting member **20504** on the firing member **20500** then cuts through the stapled tissue. Once the firing member **20500** has been driven to its distal-most position corresponding to the ending position of the camming assembly **26650'**, the firing member **20500** is retracted back to its proximal-most position, leaving the camming assembly **26650'** in the distal end of the cartridge **26600'**. When the firing member **20500** returns to its proximal-most beginning position, the lock spring once again biases the firing member **20500** back into its locked position. Thus, should the user inadvertently try to reuse the spent cartridge, the camming assembly **26650'** is not in its starting position which is required to unlock the firing member **20500**. Thus, this firing member lockout arrangement may also be referred to herein as a "spent cartridge lockout arrangement".

[0637] In the arrangement depicted in FIGS. 96 and 97, the cartridge verification system **26440'** comprises an axially movable, cartridge verification member or seating shuttle **26442'** that is supported within the channel **26310'** for axial movement from a distal-most cartridge engagement position to a proximal verification location within the channel **26310'**. A shuttle spring **26449'** is mounted within the channel **26310'** and serves to bias the cartridge verification member or seating shuttle **26442'** into the distal-most cartridge engagement position. As can be seen in FIGS. 96 and 97, the cartridge verification member or shuttle **26442'** further includes a pair of distally protruding sled actuator arms **26446'**. The sled actuator arms **26446'** are positioned to contact corresponding cam members on a camming assembly of a non-compliant cartridge as will be discussed below.

[0638] FIG. 98 illustrates a proximal end portion **26604'** of the surgical staple cartridge **26600'** that is compatible with the surgical end effector **26300'**. In at least one arrangement, the surgical staple cartridge **26600'** comprises an elongate cartridge body **26602'** that is sized to be removably seated in the elongate channel **26310'**. The cartridge body **26602'** includes a cartridge slot **26608'** that extends from the proximal end portion **26604'** to a distal end portion of the cartridge body **26602'**. The cartridge body **26602'** further comprises a cartridge deck surface **26610'** that confronts a staple-forming undersurface of the anvil when the cartridge **26600'** is seated in the channel **26310'** and the anvil is pivoted to a closed position. Although not shown in FIG. 98, the surgical staple cartridge **26600'** may have a plurality of (usually three) lines of surgical staple pockets on each side of the cartridge slot **26608'** that open through the cartridge deck surface **26610'**. Each staple pocket may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body **26602'** is molded from a polymer material with the staple pockets molded or machined therein. In one arrangement, the staple pockets also open through a bottom of the cartridge body **26602'** to facilitate installation of the drivers and fasteners into their respective pockets. Once the drivers and fasteners are inserted into their respective staple pockets, a cartridge pan **26620'** is attached to the bottom of the cartridge body **26602'**. When installed, the cartridge pan **26620'** may, among other things, prevent the drivers and fasteners from

falling out of the bottom of the cartridge body **26602'** during handling and installation of the cartridge **26600'** into the elongate channel **26310'**.

[0639] In the illustrated arrangement, cartridge **26600'** operably supports a camming assembly **26650'** therein. The camming assembly **26650'** comprises a central body portion **26652'** and a series of spaced cam members **26654'** that are configured to move axially within corresponding cam slots **26609'** formed on each side of the cartridge slot **26608'** in the cartridge body **26602'**. The cam slots **26609'** are aligned with corresponding lines of drivers in the cartridge body **26602'** to facilitate camming contact with a corresponding cam member **26654'** as the camming assembly **26650'** is driven through the staple cartridge **26600'** from a beginning position within the proximal end portion **26604'** of the cartridge body **26602'** to an ending position within the distal end portion of the cartridge body **26602'**. The central body portion **26652'** includes the proximally extending unlocking portion **26653'** that is configured to engage the sled latch **20514** on the firing member **20500** when the cartridge **26600'** has been properly loaded into the channel **26310'**.

[0640] The compatible cartridge **26600'** further includes proximally protruding verification features or key formations **26630'** that are configured to engage the sled actuator arms **26446'** when the cartridge **26600'** is operably seated in the channel **26310'**. In the illustrated arrangement, the cartridge body **26602'** additionally has two side verification features or cartridge key formations **26632'** that are also configured to engage the cartridge verification member or shuttle **26442'**. As will be discussed further below, if the verification formations **26630'**, **26632'** are not present to contact the corresponding sled actuator arm **26446'** and the cartridge verification member or shuttle **26442'**, the sled actuator arms **26446'** would otherwise contact the protruding cam members **26654'** and push or urge the camming assembly **26650'** distally into a position wherein the unlocking portion **26653'** on the camming assembly **26650'** is no longer in unlocking engagement with the sled latch **20514** on the firing member **20500**.

[0641] Turning now to FIGS. 99-101, in the illustrated arrangement, the verification features or key formations **26630'**, **26632'** each have an angled lower alignment surface **26634'** thereon that facilitate initial insertion of the cartridge **26600'** into the channel **26310'** at a first position angle FPA wherein the angled lower alignment surfaces **26634'** avoid abutting contact with the sled actuator arms **26446'**. The surfaces **26634'** may be referred to herein as secondary surfaces. Once the user has positioned the surgical staple cartridge **26600'** in the first installation position, the cartridge **26600'** is then pivoted downward into the channel **26310'** into position 2 wherein vertical abutment surfaces **26636'** (secondary surfaces) on the verification features or cartridge key formations **26630'**, **26632'** abut the corresponding vertical abutment surfaces **26641'** and **26647'** (primary surfaces) on the cartridge verification member or shuttle **26442'**. The user may then advance the cartridge **26600'** proximally into position 3 within the elongate channel **26310'**.

[0642] FIG. 102 illustrates insertion of an incompatible cartridge **26600X'** into the surgical end effector **26300'**. In this example, the incompatible cartridge **26600X'** lacks the verification features or cartridge key formations **26630'**, **26632'** that were provided on the compatible cartridge **26600'** to engage the cartridge verification member or shuttle

26442'. Thus, as the cartridge **26600X'** is seated in the channel **26310'**, the sled actuator arms **26446'** contact the protruding cam members **26654'** and push or urge the camming assembly **26650'** distally into a position wherein the unlocking portion **26653'** on the camming assembly **26650'** is not in unlocking engagement with the sled latch **20514** on the firing member **20500**. Thus, the firing member **20500** remains locked in position and the user would be unable to distally advance the firing member **20500** into the incompatible cartridge **26600X'**.

[**0643**] FIGS. **103** and **104** illustrate insertion of the incompatible cartridge **26600X'** into the end effector **26300'** wherein the incompatible cartridge **26600X'** has been initially inserted too far proximally into the channel **26310'** such that the distal end of the firing member **20500** has contacted and pushed the camming assembly **26650'** or "sled" too far distally within the cartridge **26600X'** so as to be in the appropriate position to unlockingly engage the sled latch **20514** portion of the firing member **20500** after the cartridge **26600X'** has ultimately been seated in the channel **26310'** in a proper position. Likewise, when the incompatible cartridge **26600X'** is initially inserted in a diagonal position 1 as was described above and then moved to positions 2 and 3, the firing member **20500** may bump the camming assembly **26650'** or sled distally out of the firing member unlocking position such that once properly seated, the camming assembly **26650'** would fail to unlock the firing member **20500**. See FIGS. **105** and **106**.

[**0644**] FIGS. **107-109** illustrate another cartridge verification system **26440"** that may be employed with an end effector **26300"** that employs a firing member **20500** that is axially advanced by a firing member beam **1900** in the various manners discussed herein. As was discussed above, the firing member **20500** comprises a firing member body **20502** that is configured to axially pass through vertically aligned slots in the anvil (not shown), a staple cartridge, and the elongate channel **26310"**. A lower foot assembly (not shown) that comprises a pair of laterally extending lower flanges extends from a bottom end of the firing member body **20502** to slidably engage corresponding channel ledges that are formed on each side of the channel slot. An upper foot **20507** that comprises two laterally extending anvil tabs **20509** may be formed on an upper end of the firing member body **20502** and is configured to slidably engage anvil ledges (not shown) that are formed on each side of the anvil slot. In at least one arrangement, the firing member **20500** further includes a pair of central tabs **20510** that extend laterally from each side of the firing member body **20502**.

[**0645**] The firing member body **20502** is also configured with a proximally extending spring tail (not shown) that may be configured to operably interface with a firing member lockout spring (not shown) that is mounted in the elongate channel **26310"** and is configured to bias the firing member **20500** downward in the elongate channel **26310"** into a locked position. When in the locked position, the firing member foot and/or the central tabs **20510** are misaligned with corresponding passages in the channel **26310"** and as such, should the user attempt to distally advance the firing member **20500** when in this locked out state, the firing member **20500** would not move distally due to such misalignment. That is, the foot and/or central tabs **20510** contact portions of the elongate channel **26310"** to thereby prevent the distal advancement of the firing member **20500**. In one

arrangement, a sled latch **20514** is formed on the firing member body **20502** and is configured to be engaged by a proximally extending unlocking portion on a camming assembly that is operably supported in a proximal-most starting position within a compatible cartridge that has been operably seated in the channel **26310"**.

[**0646**] When a fresh, unfired compatible staple cartridge with the camming assembly thereof in its starting (unfired) position has been operably installed in the elongate channel **26310"**, an unlocking portion on the camming assembly engages the sled latch **20514** on the firing member body **20502** and moves the firing member **20500** upward into an unlocked position wherein the lower foot assembly and/or the central tabs **20510** are aligned with their respective passages in the channel **26310"** to permit the firing member **20500** to axially advance therein. As the user distally advances the firing member **20500** into the cartridge, the firing member **20500** also drives the camming assembly therein which cams the drivers upward to drive the staples or fasteners supported thereon into forming contact with the underside of the anvil. A tissue cutting member **20504** on the firing member **20500** then cuts through the stapled tissue. Once the firing member **20500** has been driven to its distal-most position corresponding to the ending position of the camming assembly, the firing member **20500** is retracted back to its proximal-most position, leaving the camming assembly in the distal end (fired position) of the cartridge. When the firing member **20500** returns to its proximal-most beginning position, the lock spring once again biases the firing member **20500** back into its locked position. Thus, should the user inadvertently try to reuse the spent cartridge, the camming assembly is not in its starting position which is required to unlock the firing member **20500**. Such firing member locking system may also be referred to herein as a "spent cartridge lockout system".

[**0647**] In the arrangement depicted in FIGS. **107-109**, the cartridge verification system **26440"** comprises an axially movable, cartridge verification shuttle **26442"** that is supported within the channel **26310"** for axial movement from a distal-most cartridge engagement position to a proximal verification location within the channel **26310"**. A shuttle spring **26449"** is mounted within the channel **26310"** and serves to bias the cartridge verification shuttle **26442"** into the distal-most cartridge engagement position. As can be seen in FIGS. **107** and **108**, the cartridge verification shuttle **26442"** further includes distally extending shuttle base members **26644"** and pair of laterally movable shuttle drive arms **26450"**. Each shuttle drive arm **26450"** has a drive latch feature **26452"** thereon that has an angled proximal drive surface **26454"** and an angled distal drive surface **26456"** that converge together to form a point **26548"**. The shuttle drive arms **26450"** are biased laterally inward into a driving position by the shuttle spring **26449"**. When the shuttle drive arms **26450"** are in the driving position, the angled proximal drive surfaces **26454"** are in driving engagement with the central tabs **20510** on the firing member **20500** as shown in FIGS. **107** and **108**. When the shuttle drive arms **26450"** are in that position, distal advancement of the firing member **20500** will cause the seating shuttle **26442"** to move distally therewith.

[**0648**] FIG. **109** illustrates a proximal end portion **26604"** of a surgical staple cartridge **26600"** that is compatible with the surgical end effector **26300"** and seated within the channel **26310"**. In at least one arrangement, the surgical

staple cartridge **26600**" comprises an elongate cartridge body **26602**" that is sized to be removably seated in the elongate channel **26310**". The cartridge body **26602**" includes a cartridge slot **26608**" that extends from the proximal end portion **26604**" to a distal end portion of the cartridge body **26602**". The cartridge **26600**" operably supports a camming assembly **26650**" therein. The camming assembly **26650**" comprises a central body portion **26652**" and a series of spaced cam members **26654**" that are configured to move axially within corresponding cam slots **26609**" formed on each side of the cartridge slot **26608**" in the cartridge body **26602**". The cam slots **26609**" are aligned with corresponding lines of drivers in the cartridge body **26602**" to facilitate camming contact with a corresponding cam member **26654**" as the camming assembly **26650**" is driven through the staple cartridge **26600**" from a beginning position within the proximal end portion **26604**" of the cartridge body **26602**" to an ending position within the distal end portion of the cartridge body **26602**". The central body portion **26652**" includes the proximally extending unlocking portion **26653**" that is configured to engage the sled latch **20514** on the firing member **20500** when the cartridge **26600**" has been properly loaded into the channel **26310**".

[0649] The compatible cartridge **26600**" further includes proximally protruding unlocking features or cartridge key formations **26630**" that are configured to engage the shuttle drive arms **26450**" when the cartridge **26600**" is operably seated in the channel **26310**". As can be seen in FIG. 109, during the distal advancement of the firing member **20500**, the verification shuttle **26442**" is driven distally until each shuttle drive arm **26450**" contacts a corresponding cartridge key formation **26630**" which causes the shuttle drive arms **26450**" to bias laterally outward. As the firing member **20500** continues to move distally, the drive latch features **26452**" on the shuttle drive arms **26450**" disengage from the corresponding central tabs **20510** on the firing member body **20502** to permit the firing member **20500** to move distally without driving the verification shuttle **26442**" distally. Thus, in such case, the verification shuttle **26442**" has not moved sufficiently distally so as to move the camming assembly **26650**" out of unlocking engagement with the sled latch **20514** on the firing member **20500**. Therefore, the firing member **20500** may be driven distally through the compatible cartridge **26600**" to drive the fasteners therefrom and to cut the tissue that has been clamped in the end effector **26300**". When the firing member **20500** is retracted back into its starting position, a tapered surface **20511** on each central tab **20510** contacts the angled distal drive surface **26456**" on the corresponding drive latch feature **26452**" to bias the shuttle arms **26450**" laterally to permit the central tabs **20510** to reengage the angled proximal drive surfaces **26454**" so that the verification shuttle **26442**" can once again be driven distally with the firing member **20500**.

[0650] FIGS. 107 and 108 illustrate an incompatible cartridge **26600X**" loaded into the surgical end effector **26300**". As can be seen in those Figures, the incompatible cartridge **26600X**" lacks the proximally protruding unlocking features or cartridge key formations **26630**" that are provided on the compatible cartridge **26600**". Thus, when the firing member **20500** is distally advanced, the cartridge verification shuttle **26442**" also moves distally with the firing member **20500**. As the cartridge verification shuttle **26442**" moves distally, the distal ends **26645**" of the distally extending shuttle base members **26644**" contact the camming assembly **26650**" and

move the camming assembly **26650**" out of unlocking engagement with the sled latch **20514** on the firing member **20500**. When the unlocking portion **26653**" of the camming assembly **26650**" disengages the sled latch **20514**, the firing member body **20502** will drop into locking engagement with the elongate channel **26310**" thereby preventing further distal advancement of the firing member **20500**.

[0651] As can be further seen in FIGS. 108 and 109, in the illustrated arrangement, a lateral stiffener member **26470**" protrudes laterally outward from each shuttle arm **26450**". When the firing member **20500** and the verification shuttle **26442**" are located in their respective proximal-most starting positions, each lateral stiffener member **26470**" is laterally aligned with a corresponding channel notch **26472**" provided in each channel sidewall **26314**" to provide clearance for the shuttle arms **26450**" to move laterally when a compatible cartridge **26600**" has been properly loaded into the end effector **26300**". However, when an incompatible cartridge **26600X**" has been loaded into the end effector **26300**" and the user begins to advance the firing member **20500** as well as the verification shuttle **26442**" distally, the lateral stiffener members **26470**" are no longer aligned with the channel notches **26472**" in the channel sidewalls **26314**" as can be seen in FIG. 108. In such instance, the lateral stiffener members **26470**" prevent the shuttle arms **26450**" from biasing laterally outward out of engagement with the central tabs **20510** that extend laterally from each side of the firing member body **20502**.

[0652] The cartridge verification systems described herein may address various problems that may, from time-to-time, be encountered when using an end effector that is capable of initially accepting a variety of cartridges wherein some of the cartridges are not otherwise particularly compatible with the end effector. For example, a cartridge may operably fit into the channel of the end effector, but the cartridge may lack proper fastener configurations that are compatible with the forming pockets on the end effector anvil. The incompatible cartridge may not have the proper numbers and forms of staples, etc. The cartridge may not have a camming assembly that is compatible with the firing member lockout arrangement employed by the end effector. Some cartridges may have an appropriate camming assembly, but the camming assembly may at some point have moved to a marginal unlocking position wherein the camming assembly may or may not unlockingly engage the firing member lockout arrangement. At least some of the cartridge verification systems may address that issue. The cartridge verification systems disclosed herein may also provide the ability to differentiate between an old obsolete cartridge and a newer more appropriate cartridge that has, for example, features that are better paired to the end effector components. The cartridge verification systems may also ensure that a cartridge is properly seated in the end effector channel and minimize any misalignment of the cartridge in the channel wherein the proximal end of the cartridge is positioned relative to the firing member in an undesirable position wherein the central tabs on the firing member may get under the cartridge pan rather than on top of it as desired. Such misalignment may result in the damage and bending of the cartridge pan which could lead to premature locking of the firing member.

[0653] FIGS. 110-115 illustrate another cartridge verification system **27440** that may be employed with an end effector **27300** that employs a firing member **20500** (de-

scribed above) that is axially advanced by a firing member beam 1900 in the various manners discussed herein. In the illustrated arrangement, the cartridge verification system 27440 comprises an axially movable cartridge verification member or shuttle 27442 that is supported within a channel 27310 of the end effector 27300 for axial movement from a distal-most cartridge engagement position to a proximal verification location within the channel 27310. The cartridge verification member or shuttle 27442 may be fabricated from spring steel and include an elongate body 27444 that has a blocking hook 27446 that is formed on a distal end 27445 of the elongate body 27444. See FIG. 111. The cartridge verification member or shuttle 27442 further includes an actuator portion 27448 that is formed on a proximal end 27447 of the elongate body 27444.

[0654] Still referring to FIG. 111, the cartridge verification member or shuttle 27442 is configured to axially move within a shuttle track 27360 that is formed in a channel bottom 27312 of the channel 27310. As can be seen in FIG. 111, the shuttle track 27360 comprises a curved transverse portion 27362 that extends transversely relative to a channel slot 27313 that is centrally disposed in the channel bottom 27312 to accommodate axial passage of the firing member 20500 therethrough. The transverse curved portion 27362 of the shuttle track 27360 terminates in a ramped track portion 27364 that is located on another side of the channel slot 27313. As can be seen in FIG. 111, the ramped track portion 27364 has an angled bottom surface 27366. A proximal end 27370 of the shuttle track 27360 abuts an axial spring cavity 27380 that is configured to support a shuttle spring 27382 that is journaled on a spring retainer pin 27449 that protrudes proximally from the actuator portion 27448 of the cartridge verification member or shuttle 27442. The shuttle spring 27382 serves to bias the verification shuttle 27442 into a distal-most, locked position wherein the cartridge verification member or shuttle 27442 blocks distal advancement of a camming assembly 27650 and the firing member 20500.

[0655] FIG. 110 illustrates a proximal end portion 27604 of a surgical staple cartridge 27600 that is compatible with the surgical end effector 27300. In at least one arrangement, the surgical staple cartridge 27600 comprises an elongate cartridge body 27602 that is sized to be removably seated in the elongate channel 27310. The cartridge body 27602 includes a cartridge slot 27608 that extends from the proximal end portion 27604 to a distal end portion of the cartridge body 27602. The cartridge body 27602 further comprises a cartridge deck surface 27610 that confronts a staple-forming undersurface of the anvil when the cartridge 27600 is seated in the channel 27310 and the anvil is pivoted to a closed position. Although not shown in FIG. 110, the surgical staple cartridge 27600 may have a plurality of (usually three) lines of surgical staple pockets on each side of the cartridge slot 27608 that open through the cartridge deck surface 27610. Each staple pocket may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body 27602 is molded from a polymer material with the staple pockets molded or machined therein. In one arrangement, the staple pockets also open through a bottom of the cartridge body 27602 to facilitate installation of the drivers and fasteners into their respective pockets. Once the drivers and fasteners are inserted into their respective staple pockets, a cartridge pan 27620 is attached to the bottom of the cartridge body 27602. When installed, the cartridge pan

27620 may, among other things, prevent the drivers and fasteners from falling out of the bottom of the cartridge body 27602 during handling and installation of the cartridge 27600 into the elongate channel 27310.

[0656] In the illustrated arrangement, cartridge 27600 operably supports a camming assembly 27650 therein. The camming assembly 27650 comprises a central body portion 27652 and a series of spaced cam members 27654 that are configured to move axially within corresponding cam slots 27609 formed on each side of the cartridge slot 27608 in the cartridge body 27602. The cam slots 27609 are aligned with corresponding lines of drivers in the cartridge body 27602 to facilitate camming contact with a corresponding cam member 27654 as the camming assembly 27650 is driven through the staple cartridge 27600 from a beginning position within the proximal end portion 27604 of the cartridge body 27602 to an ending position within the distal end portion of the cartridge body 27602. The central body portion 27652 includes a proximally extending unlocking portion 27653 that is configured to engage the sled latch 20514 on the firing member 20500 when the cartridge 27600 has been properly loaded into the channel 27310.

[0657] The compatible cartridge 27600 further includes a proximally protruding verification feature or cartridge key formation 27630 that is configured to engage the sled actuator 27448 when the cartridge 27600 is operably seated in the channel 27310. The verification feature 27630 biases the cartridge verification member or shuttle 27442 into the proximal-most, unlocked position wherein the camming assembly 27650 and the firing member 20500 may be distally displaced through the cartridge 27600. When the cartridge verification member or shuttle 27442 is in the unlocked position, the blocking hook 27446 that is formed on the distal end 27445 of the elongate body 27444 of the cartridge verification member or shuttle 27442 is retracted into the curved transverse portion 27362 of the shuttle track 27360 and does not extend across the channel slot 27313 in the channel bottom 27312. When the blocking hook 27446 is not extending across the channel slot 27313, the firing member 20500 and the camming assembly 27650 can be advanced into the cartridge 27310".

[0658] FIGS. 114 and 115 illustrate the surgical end effector 27300 with an incompatible cartridge 27600X installed therein. In this example, the incompatible cartridge 27600X lacks the verification feature or cartridge key formation 27630 that was provided on the compatible cartridge 27600 to engage the actuator portion 27448 of the cartridge verification member or shuttle 27442. Thus, the shuttle spring 27382 has biased the cartridge verification member or shuttle 27442 distally into its locked position wherein the blocking hook 27446 that is formed on the distal end 27445 of the elongate body 27444 of the cartridge verification member or shuttle 27442 extends transversely across the channel slot 27313 and into the ramped track portion 27364. As the blocking hook 27446 enters the ramped track portion 27364, the angled bottom surface 27366 causes the blocking hook 27446 to move upward into a position wherein the blocking hook 27446 blocks the distal advancement of the camming assembly 27650 and the firing member 20500. Thus, when in that position, should the user unwittingly attempt to distally advance the firing member 20500, the blocking hook 27446 will block the distal advancement of the camming assembly 27650 and the firing member 20500.

[0659] In at least one arrangement as shown in FIG. 115, the portion of the blocking hook 27446 that transversely spans the channel slot 27313 may be reinforced with an additional reinforcement block portion 27450 that is attached thereto. That is the portion of the blocking hook 27446 that is reinforced has a cross-sectional thickness that is greater than a cross-sectional thickness of the remaining body portions of the cartridge verification member or shuttle 26442. Alternative arrangements are contemplated for use with those end effectors disclosed herein that employ an axially movable closure member for moving the anvil to a closed position such as, for example, an end effector closure tube. In such end effector arrangements, for example, the end effector closure tube may be configured to bias the verification shuttle to the locked, blocking position when the closure member is actuated to close the anvil. The cartridge verification system 27440 may also be effectively employed with surgical end effectors that have rotary powered firing member arrangements with firing member lockout systems of the types disclosed herein.

[0660] FIGS. 116-119 illustrate an alternative surgical staple cartridge 28600 that may be employed in connection with various end effector arrangements disclosed herein. In the illustrated arrangement, the surgical staple cartridge 28600 comprises an elongate cartridge body 28602 that is sized to be removably seated in the elongate channel of the end effector. As can be seen in FIG. 117, the cartridge body 28602 includes a cartridge slot 28608 that extends from a proximal end portion 28604 of the cartridge body 28602 to a distal end portion of the cartridge body 28602. The cartridge body 28602 further comprises a cartridge deck surface 28610 that confronts a staple-forming undersurface of the anvil when the cartridge 28600 is seated in the channel and the anvil is pivoted to a closed position. Although not shown in FIG. 117, the surgical staple cartridge 28600 may have a plurality of (usually three) lines of surgical staple pockets on each side of the cartridge slot 28608 that open through the cartridge deck surface 28610. Each staple pocket may have a staple driver (not shown) associated therewith that supports a surgical staple or fastener (not shown) thereon. In at least one example, the cartridge body 28602 is molded from a polymer material with the staple pockets molded or machined therein. In one arrangement, the staple pockets also open through a bottom of the cartridge body 28602 to facilitate installation of the drivers and fasteners into their respective pockets. Once the drivers and fasteners are inserted into their respective staple pockets, a cartridge pan 28620 is attached to the bottom of the cartridge body 28602. When installed, the cartridge pan 28620 may, among other things, prevent the drivers and fasteners from falling out of the bottom of the cartridge body 28602 during handling and installation of the cartridge 28600 into the elongate channel.

[0661] In the illustrated arrangement, cartridge 28600 operably supports a camming assembly 28650 therein. The camming assembly 28650 comprises a central body portion 28652 and a series of spaced cam members 28654, 28654' that are configured to move axially within corresponding cam slots 28609 formed on each side of the cartridge slot 28608 in the cartridge body 28602. The cam slots 28609 are aligned with corresponding lines of drivers in the cartridge body 28602 to facilitate camming contact with a corresponding cam member 28654, 28654' as the camming assembly 28650 is driven through the staple cartridge 28600 from a

beginning position within the proximal end portion 28604 of the cartridge body 28602 to an ending position within the distal end portion of the cartridge body 28602.

[0662] Still referring to FIG. 117, the cartridge 28600 is equipped with a camming assembly locking system 28440 that is configured to retain the camming assembly 28650 in its starting position unless the cartridge 28600 has been loaded into a compatible end effector. In the illustrated arrangement for example, the camming assembly locking system 28440 comprises a laterally displaceable lock feature 28442 that comprises an actuator portion 28444 and a locking tab 28446. As can be seen in FIG. 117, the locking tab 28446 is configured to be received within a lock cavity 28655 provided in a corresponding cam member 28654' when the camming assembly 28650 is in a locked position. See FIGS. 116 and 117. The actuator portion 28444 is configured to be contacted by an actuator lug or other portion of the end effector anvil when the anvil is moved to a closed position. For example, an actuator lug 28411 may be formed on an anvil mounting portion of any of the various anvils disclosed herein and be configured to laterally bias the actuator portion 28444 laterally into an unlocked position when the anvil is moved to a closed position. When the actuator portion 28444 is in an unlocked position, the locking tab 28446 is moved laterally out of the lock cavity 28655 in the cam member 28654' and the cam assembly 28650 may then be distally advanced through the cartridge 28600 when the firing drive system is activated as described herein. See FIGS. 118 and 119.

[0663] In various instances, a surgical stapling instrument comprises a cartridge jaw configured to receive a replaceable staple cartridge. The stapling instrument further comprises a staple firing system configured to eject, or fire, staples from the staple cartridge and an anvil comprising forming surfaces, or pockets, configured to deform the staples. The staple firing system comprises a tissue cutting knife which is moved from a proximal end of the staple cartridge toward a distal end during a staple firing stroke. During the staple firing stroke, the tissue cutting knife abuts and pushes a sled in the staple cartridge which drives the staples toward and against the anvil. As the staples are deformed against the anvil, the staples are implanted in the tissue in longitudinal rows and the tissue cutting knife incises the tissue between two of the longitudinal staple rows. After the staple firing stroke has been completed, and/or after a sufficient length of the staple firing stroke has been completed, the tissue cutting knife is retracted proximally. However, the cartridge sled is not retracted proximally with the tissue cutting knife. Instead, the cartridge sled is left behind at the distal-most position in which it was pushed by the tissue cutting knife. After a staple cartridge has been fired, or at least partially fired, it is removed from the cartridge jaw and then replaced with another replaceable staple cartridge, if desired. At such point, the stapling instrument can be re-used to continue stapling and incising the patient tissue. In some instances, however, a previously-fired staple cartridge can be accidentally loaded into the cartridge jaw. If the tissue cutting knife were to be advanced distally within such a previously-fired staple cartridge, the stapling instrument would cut the patient tissue without stapling it. The stapling instrument would similarly cut the patient tissue without stapling it if the tissue cutting knife were advanced distally through a staple firing stroke without a staple cartridge positioned in the cartridge jaw at all. To

this end, the stapling instrument comprises one or more lockouts which prevents this from happening, as discussed in greater detail below.

[0664] The disclosures of U.S. Patent Application Publication No. 2004/0232200, entitled SURGICAL STAPLING INSTRUMENT HAVING A SPENT CARTRIDGE LOCKOUT, filed on May 20, 2003, which issued on Jan. 24, 2006 as U.S. Pat. No. 6,988,649, U.S. Patent Application Publication No. 2004/0232199, entitled SURGICAL STAPLING INSTRUMENT HAVING A FIRING LOCKOUT FOR AN UNCLOSED ANVIL, which issued on Dec. 5, 2006 as U.S. Pat. No. 7,143,923, U.S. Patent Application Publication No. 2004/0232197, entitled SURGICAL STAPLING INSTRUMENT INCORPORATING AN E-BEAM FIRING MECHANISM, filed on May 20, 2003, which issued on Dec. 27, 2005 as U.S. Pat. No. 6,978,921, U.S. Patent Application Publication No. 2004/0232196, entitled SURGICAL STAPLING INSTRUMENT HAVING SEPARATE DISTINCT CLOSING AND FIRING SYSTEMS, filed on May 20, 2003, U.S. Patent Application Publication No. 2004/0232195, entitled SURGICAL STAPLING INSTRUMENT HAVING A SINGLE LOCKOUT MECHANISM FOR PREVENTION OF FIRING, filed on May 20, 2003, which issued on May 16, 2006 as U.S. Pat. No. 7,044,352, and U.S. Patent Application Publication No. 2018/0085123, entitled ARTICULATING SURGICAL STAPLING INSTRUMENT INCORPORATING A TWO-PIECE E-BEAM FIRING MECHANISM, filed on Aug. 17, 2017, which issued on May 21, 2019 as U.S. Pat. No. 10,292,707, are incorporated by reference in their entireties.

[0665] Referring to FIG. 120, a surgical stapling instrument 30000 comprises a cartridge jaw, or channel, 30010 and a staple cartridge 30020 seated in the cartridge jaw 30010. The staple cartridge 30020 comprises a cartridge body 30022, staple cavities defined in the cartridge body 30022, and staples removably stored in the staple cavities. The staple cartridge 30020 further comprises a sled 30030 and staple drivers which are driven by the sled 30030 to eject the staples from the staple cavities as the sled 30030 is advanced distally during a staple firing stroke. The stapling instrument 30000 further comprises a firing member 30040 which is configured to engage the sled 30030 and push the sled 30030 distally, as discussed in greater detail below.

[0666] Further to the above, the firing member 30040 comprises a cutting portion 30042 including a tissue knife 30044. The cutting portion 30042 further comprises a distal nose 30043 which is configured to sit on a shoulder 30033 defined on the sled 30030 when the sled 30030 is in its unfired position in the staple cartridge 30020 and the firing member 30040 is moved distally from its unfired position illustrated in FIG. 120. Once the distal nose 30043 is on the sled shoulder 30033, the firing member 30040 can be advanced distally to perform the staple firing stroke. Notably, the cutting portion 30042 further comprises a first camming member 30046 configured to engage a cam surface of the channel 30010 and a second camming member 30048 configured to engage a cam surface on the anvil of the stapling instrument 30000 which co-operate to position the anvil and the staple cartridge 30020 relative to one another. That said, embodiments are envisioned without one or both of the camming members 30046 and 30048.

[0667] Referring to FIG. 121, the firing member 30040 is biased toward the channel 30010 by a spring and, if the sled 30030 is not in its unfired position when the firing member

30040 is advanced distally to start the staple firing stroke, the distal nose 30043 of the cutting portion 30042 will miss, or not land on, the shoulder 30033 and the cutting portion 30042 will dive downwardly toward the channel 30010 instead. The cutting portion 30042 comprises lockout pins 30045 extending laterally therefrom which enter a lockout window, or recess, 30012 defined in the channel 30010 when the distal nose 30043 does not land on the shoulder 30033 of the sled 30030. In such instances, the firing member 30040 is permitted to travel distally within the lockout window 30012; however, the distal end of the lockout window 30012 comprises a lockout shoulder 30015 which is contacted by the lockout pins 30045 to stop the distal advancement of the firing member 30040. In such instances, as a result, the firing member 30040 is locked out and prevented from performing its staple firing stroke. Had the sled 30030 been in its unfired position, however, the interaction between the distal nose 30043 of the cutting portion 30042 and the shoulder 30033 of the sled 30030 would have prevented the firing member 30040 from diving into the lockout window 30012 and the staple firing stroke could have been performed.

[0668] Further to the above, the firing member 30040 would dive into the lockout window 30012 if the firing member 30040 were advanced distally without a staple cartridge positioned in and/or a staple cartridge properly seated in the cartridge channel 30010. In view of the above, the surgical instrument 30000 comprises a lockout which prevents the staple firing stroke if the staple cartridge in the surgical instrument 30000 is missing, improperly seated, and/or has been at least partially spent. That said, various instances can arise where a staple cartridge has not been fired, i.e., all of its staples are still positioned in their staple cavities, and, yet, the distal nose 30043 of the cutting portion 30042 can miss the shoulder 30033 of the sled 30030 owing to various manufacturing tolerances, for instance. Such instances would cause the firing member 30040 to be locked out unnecessarily and require a clinician to replace the staple cartridge with another staple cartridge. Such instances may not happen that often, but if they do they are inconvenient to the clinician.

[0669] A surgical instrument 30100 is illustrated in FIG. 122 and includes an improvement which can reduce the possibility of the distal nose 30043 of the cutting portion 30042 missing the shoulder 30033 of the sled 30030. The surgical instrument 30100 is similar to the surgical instrument 30000 in many respects but includes a staple cartridge 30120 instead of the staple cartridge 30020. The staple cartridge 30120 comprises a cartridge body 30122, staple cavities defined in the cartridge body 30122, and staples removably stored in the staple cavities. Referring to FIG. 123, the staple cartridge 30120 further comprises a sled 30030 which, similar to the above, is movable distally from an unfired position during a staple firing stroke if the distal nose 30043 of the cutting portion 30042 catches the shoulder 30033 of the sled 30030. If not, referring to FIG. 124, the cutting portion 30042 is pushed into the lockout window 30012 defined in the cartridge channel 30010 when the firing member 30040 is advanced distally.

[0670] Referring to FIGS. 125 and 126, the cartridge body 30122 comprises proximal ramps 30126 configured to lift the firing member 30040 upwardly when the firing member 30040 is advanced distally. More specifically, the lockout pins 30045 extending laterally from the firing member

30040 contact ramp surfaces **30127** defined on the proximal ramps **30126** which guide the cutting portion **30042** away from the lockout window **30012** when the firing member **30040** is advanced distally. They do so, further to the above, against the biasing force of the spring pushing the firing member **30040** toward the cartridge channel **30010**. The lifting of the firing member **30040** in this manner increases the probability that the nose **30043** of the firing member **30040** will land on the shoulder **30033** of the sled **30030**—even if the sled **30030** has been accidentally pushed slightly distally from its unfired position. Thus, the possibility of an unfired staple cartridge becoming unintentionally locked out is reduced. If the staple cartridge **30120** has been at least partially fired, however, the nose **30043** will miss the shoulder **30033** and the lockout pins **30045** will fall through a window **30125** defined between the proximal ramps **30126** and into the lockout window **30012**. Thus, as above, the surgical instrument **30100** will be locked out if an at least partially spent staple cartridge **30120** is seated in the cartridge channel **30010**. Moreover, as above, the surgical instrument **30100** will be locked out if a staple cartridge is missing from the cartridge channel **30010** and the staple firing stroke is initiated as the firing member **30040** will immediately enter the lockout window **30012** owing to the absence of the proximal ramps **30126**.

[0671] Notably, further to the above, the ramps **30126** are positioned proximally with respect to the shoulder **30033** of the sled **30030**. As such, the firing member **30040** must consecutively pass the missing cartridge/improper cartridge lockout provided by the ramps **30126** and the spent cartridge lockout provided by the sled **30030** as the firing member **30040** is moved distally to perform the staple firing stroke. Moreover, the ramps **30126** lift the firing member **30040** to a proper height to be supported by the sled **30030**. Ultimately, the ramps **30126** of the cartridge body **30122** and the shoulder **30033** of the sled **30030** work together to defeat the lockouts of the stapling instrument **30100**.

[0672] A staple cartridge **30220** is illustrated in FIG. 127 in accordance with at least one alternative embodiment. The staple cartridge **30220** comprises a cartridge body **30222** which is similar to the cartridge body **30122** in many respects. That said, the cartridge body **30222** comprises proximal ramps **30226** which extend further proximally than the proximal ramps **30126**. As such, the firing member **30040** will be lifted earlier in its staple firing stroke when a staple cartridge **30220** is used. In various instances, the staple cartridge **30220** can include a larger drop window **30225** than the drop window **30125**. Moreover, the proximal ramps **30226** comprise ramp surfaces **30227** which are shorter than the ramp surfaces **30127**. In such instances, the firing member **30040** will not be lifted as high when a staple cartridge **30220** is used as compared to when a staple cartridge **30120** is used. In any event, such parameters can be used to hone an appropriate lifting motion for the firing member **30040**.

[0673] As discussed above, the lockout pins **30045** of the firing member **30040** are configured to contact the ramps **30226** which lift the firing member **30040** such that the firing member **30040** can land on the shoulder **30033** of the sled **30030** if the sled **30030** is properly positioned in the staple cartridge **30220**. That said, alternative embodiments are envisioned in which ramps can lift any suitable portion of a staple firing member onto the shoulder **30033** of the sled **30030**. For instance, the firing member **30040** can comprise

laminar bars attached to the cutting portion **30042** which contact the ramps **30226** and cause the firing member **30040** to be lifted upwardly when the staple firing stroke is initiated.

[0674] Referring again to FIG. 127, the staple cartridge **30220** comprises a pan **30024** at least partially extending under the cartridge body **30222**. The pan **30024** is configured to prevent the staple drivers and/or staples within the cartridge body **30222** from falling out of the bottom of the cartridge body **30222**. The pan **30024** comprises latches **30021** engaged with slots defined in the cartridge body **30222**. The pan **30024** further comprises windows **30029** defined therein which, in co-operation with projections extending from the cartridge body **30222**, align the pan **30024** with the cartridge body **30222**. In addition to or in lieu of the above, the lift ramps **30226**, for example, can extend from the pan **30024**.

[0675] A surgical stapling instrument **30300** is illustrated in FIG. 128. The stapling instrument **30300** is similar to the stapling instrument **30200** in many respects. That said, the stapling instrument **30300** comprises a staple cartridge **30320** instead of the staple cartridge **30220**. The staple cartridge **30320** comprises a cartridge body **30322**, staple cavities defined in the cartridge body **30322**, and staples removably stored in the staple cavities. The cartridge body **30322** further comprises a longitudinal slot **30023** defined therein which is configured to receive the firing member **30040** and, in addition, a proximal ramp **30327** extending in front of the longitudinal slot **30023** which lofts the firing member **30040** onto the sled **30030** if the sled **30030** is in, or at least nearly in, its unfired position, as illustrated in FIG. 129. If the sled **30030** has been at least partially advanced through its staple firing stroke, the shoulder **30033** will not catch the nose **30043** of the firing member **30040** and the cutting portion **30042** will fall through a window defined between ramp supports **30326** and into the lockout window **30012**.

[0676] Referring to FIGS. 130 and 132, the ramp **30327** also comprises a gate configured to pivot out of the way of the firing member **30040** when a sufficient pushing force is applied to the firing member **30040**. The ramp **30327** comprises a first end rotatably mounted to one of the ramp supports **30326** and a second end releasably attached to the other ramp support **30326**. Referring to FIGS. 131 and 133, the second end of the ramp **30327** is configured to release from its ramp support **30326** after the firing member **30040** has been lofted upwardly such that, once the ramp **30327** gives way, the nose **30043** of the firing member **30040** falls on the shoulder **30033** of the sled **30030**—if the sled **30030** is in its unfired position, or at least close to its unfired position. At such point, the ramp **30327** no longer impedes the distal movement of the firing member **30040** and the firing member **30040** can be advanced distally through the longitudinal slot **30023**. The ramp **30327** remains displaced to the side throughout the staple firing stroke and after the firing member **30040** has been retracted back into its unfired position. As such, the displaced ramp **30327** cannot lift the firing member **30040** if the firing member **30040** were to be advanced distally once again. In such instances, the lockout pins **30045** of the cutting portion **30042** would be pushed into the lockout window **30012** by the spring acting against the firing member **30040** if the firing member **30040** were advanced distally before the spent staple cartridge **30320** is replaced. Thus, the ramp **30327** acts as a spent cartridge

lockout. In at least one alternative embodiment, the ramp **30327** is configured to break away from the cartridge body **30322** to release the firing member **30040**.

[0677] Moreover, further to the above, the lockout arrangement of the stapling instrument **30300** also acts as an improper/incompatible cartridge lockout. If an improper, or incompatible, staple cartridge not having the ramp **30327**, or another suitably configured ramp, were to be seated in the cartridge channel **30010**, the firing member **30040** would not be lofted onto a sled of the improper staple cartridge and, instead, the lockout pins **30045** would be forced into the lockout window **30012** thereby locking out the staple firing system. In such instances, the firing member **30040** can be retracted back into its unfired position and the improper/incompatible staple cartridge can be replaced with a proper/compatible staple cartridge. The accidental swapping of an improper staple cartridge for a proper staple cartridge can happen in an operating room where certain staple cartridges are meant to be only used with certain stapling instruments, among other instances.

[0678] As discussed above, the ramp **30327** extends behind the sled **30030**. As a result, the ramp **30327** can protect the sled **30030** from being bumped distally accidentally. In various instances, the staple cartridge **30320** is loaded into the stapling instrument **30300** by inserting the proximal end of the staple cartridge **30320** into the cartridge channel **30010** first and then seating the staple cartridge **30320** in the cartridge channel **30010**. As such, the possibility exists that the sled **30030** will contact the cartridge channel **30010**, for example, and be pushed distally within the staple cartridge **30320** from its proximal unfired position. In such instances, the sled **30030** may no longer be positioned to defeat the staple firing lockout of the stapling instrument **30300** when the staple firing stroke is initiated and, thus, the stapling firing lockout will treat this staple cartridge **30320** as being spent and it must be replaced to use the stapling instrument **30300**. The ramp **30327** can prevent this as it extends proximally behind the sled **30030** and can prevent the sled **30030** from being bumped distally within the staple cartridge **30320** when the staple cartridge **30320** is being installed.

[0679] As discussed above, the sled **30030**, when properly positioned in the staple cartridge, defeats the staple firing lockout of the stapling instrument such that the staple firing stroke can be completed. In use, the firing member **30040** is advanced distally, at least partially, to assess whether or not the sled **30030** is properly positioned and that the staple firing lockout has been defeated. More specifically, the firing member **30040** is advanced distally until the firing member **30040** is supported by the sled **30030** to perform the staple firing stroke—if the sled **30030** is properly positioned in the staple cartridge **30320**—or contact the lockout shoulder **30015** if the sled **30030** is not properly positioned in the staple cartridge **30320** or the staple cartridge **30320** is missing from the cartridge channel **30010**. If the firing member **30040** contacts the lockout shoulder **30015**, the firing member **30040** may need to be retracted to be able to insert an unspent staple cartridge **30320** into the cartridge channel **30010** and/or retracted to start another staple firing stroke. With this in mind, the surgical instrument **30400** of FIGS. 134 and 135 is configured to limit the travel of a firing member such that the firing member can be stopped before

it reaches the lockout shoulder **30015** if the staple cartridge is missing from the cartridge channel, as discussed in greater detail below.

[0680] The firing member **30440** of the surgical instrument **30400**, further to the above, is similar to the firing member **30040** in many respects but comprises a cutting member **30442** including secondary lockout pins **30449** extending laterally therefrom. If the staple cartridge **30320** is not positioned in the cartridge channel **30410** of the stapling instrument **30400**, the cutting member **30442** will immediately enter the lockout window **30012** when the firing member **30440** is advanced distally and the secondary lockout pins **30449** will quickly contact a secondary lockout shoulder **30419** in the lockout window **30012**. Thus, if a staple cartridge **30320** is not present in the cartridge channel **30410**, the firing member **30440** will not have to travel distally until it contacts the lockout shoulder **30015**. In such instances, the distance in which the firing member **30440** needs to be retracted is at least reduced. In certain instances, the secondary lockout shoulder **30419** is positioned such that the cutting member **30442** does not need to be retracted at all. In such instances, as a result, an unspent staple cartridge **30320** can be inserted into the channel **30410** and the staple firing stroke can be completed without having to retract the firing member **30440**.

[0681] Further to the above, the interaction between the lockout pins **30449** and the lockout shoulder **30419** provides a missing cartridge lockout. If the staple cartridge **30320** is seated in the cartridge channel **30410**, the cutting member **30442** engages the ramp **30327** of the staple cartridge **30320** which lifts the lockout pins **30449** over the lockout shoulder **30419**. Stated another way, the presence of the staple cartridge **30320** in the cartridge channel **30010** defeats the secondary staple firing lockout. That said, the sled **30030** of the staple cartridge **30320** must be properly positioned in the staple cartridge **30320** in order for the staple firing stroke to be completed as the nose **30043** of the cutting member **30442** must still land on the shoulder **30033** of the sled **30030** in order for the lockout pins **30045** to be lifted over the lockout shoulder **30015**, as described above. Stated another way, the presence of the sled **30030** in the staple cartridge **30320** in its unfired position defeats the primary firing lockout and the presence of the staple cartridge **30320** in the cartridge channel **30410** defeats the secondary firing lockout. Thus, the stapling instrument **30400** comprises a primary missing cartridge lockout and a secondary missing cartridge lockout, where the primary missing cartridge lockout also serves as a spent cartridge lockout.

[0682] A surgical stapling instrument **30500** is illustrated in FIG. 136. The stapling instrument **30500** is similar to the stapling instrument **30000** in many respects. Among other things, the stapling instrument **30500** comprises a cartridge channel **30510**, a staple cartridge **30520** removably positionable in the cartridge channel **30510**, a firing member **30040**, and a staple firing lockout **30514**. The staple firing lockout **30514** comprises a resilient metal spring, for example, mounted in the cartridge channel **30510**. That said, the staple firing lockout **30514** can be comprised of any suitable material. The staple firing lockout **30514** comprises a base mounted in the cartridge channel **30510** and flexible lock arms **30516** extending from the base. Each flexible lock arm **30516** moves independently of the other and comprises a lock window **30515** defined therein which is configured to receive and releasably capture a lockout pin **30045** extend-

ing from the firing member **30040**. The flexible lock arms **30516** are configured such that they extend inwardly toward and/or against the side of the firing member **30040** and are, thus, biased to capture the lockout pins **30045**. When one or both of the lockout pins **30045** are captured in a lock window **30515**, the staple firing member **30040** is prevented from being advanced distally through a staple firing stroke.

[0683] Further to the above, the staple cartridge **30520** comprises a cartridge body **30522**, staple cavities defined in the cartridge body **30522**, and staples removably stored in the staple cavities. The staple cartridge **30520** further comprises a pan **30024** attached to the cartridge body **30522** and a sled configured to travel distally within the staple cartridge **30520** to eject the staples from the staple cavities during a staple firing stroke. Similar to the above, the firing member **30040** is configured to push the sled distally to perform the staple firing stroke once the firing member **30040** has been unlocked. To this end, referring to FIGS. **136** and **139**, the cartridge body **30522** comprises projections, or keys, **30526** extending proximally therefrom which are configured to engage the lock arms **30516** when the staple cartridge **30520** is seated in the cartridge channel **30510**. Notably, the ends of the lock arms **30516** flare outwardly such that, when the projections **30526** contact the lock arms **30516**, the lock arms **30516** aren't trapped between the projections **30526** and the firing member **30040**. As a result, the projections **30526** flex the lock arms **30516** laterally outwardly such that the lockout pins **30045** extending from the firing member **30040** are no longer positioned in the lockout windows **30515** of the firing lockout **30514** when the staple cartridge **30520** is seated in the cartridge channel **30510**. Thus, the act of seating the staple cartridge **30520** in the cartridge channel **30510** unlocks the stapling instrument **30500**.

[0684] If a staple cartridge **30520** is not seated in the cartridge channel **30510**, as discussed above, the firing member **30040** remains locked by the firing lockout **30514** and the stapling instrument **30500** cannot be used to staple the patient's tissue. If a staple cartridge is seated in the cartridge channel **30510** that does not have the projections, or keys, **30526**, such as the staple cartridge **30020**, for example, it will not unlock the firing lockout **30514**, as illustrated in FIGS. **137** and **138**, and, as a result, the stapling instrument **30500** cannot be used to staple the patient's tissue. As depicted in FIGS. **137** and **138**, the proximal end of the cartridge body **30022** does not engage, and/or sufficiently displace, the lock arms **30516**. Thus, in this instance, the staple cartridge **30020** would be an improper staple cartridge as it does not unlock the staple firing drive of the stapling instrument **30500** and, correspondingly, the staple cartridge **30520** would be a proper staple cartridge as it can unlock the staple firing drive of the stapling instrument **30500**. As such, the firing lockout **30514** is both a missing cartridge lockout and an improper cartridge lockout. The stapling instrument **30500** can further comprise a spent cartridge lockout. In the event that an improper staple cartridge is seated in the stapling instrument **30500** and the stapling instrument **30500** cannot be fired, the improper staple cartridge can be removed and a proper staple cartridge, i.e., a staple cartridge **30520**, can be seated in the stapling instrument **30500** to unlock the staple firing drive.

[0685] As discussed above in connection with the stapling instrument **30000**, referring again to FIG. **121**, the lockout pins **30045** of the firing member **30040** engage the lock shoulder **30015** if the sled **30030** is not in its proper position

in the staple cartridge **30020**. As also discussed above, the firing member **30040** of the stapling instrument **30000** is advanced distally before engaging the lock shoulder **30015** and, thus, has time to accelerate before contacting the lock shoulder **30015**. As such, the firing member **30040** of the stapling instrument **30000** can impact the lock shoulder **30015** with significant speed and energy. As such, the lock shoulder **30015** is robustly designed to absorb this impact; however, there exists a possibility that the firing member **30040** can plow or blow through the lock shoulder **30015** thereby unintentionally defeating the staple firing lockout of the stapling instrument **30000**. The lockout **30514** of FIGS. **136** and **137** can reduce, if not eliminate, these potential problems. For instance, the lock windows **30515** of the firing lockout **30514** are sized and configured to prevent little, if any, proximal and distal translation of the staple firing member **30040** while the lock arms **30516** are engaged with the lockout pins **30045** and, thus, the staple firing member **30040** has little, if any, time to accelerate before being stopped by the distal ends of the lock windows **30515**. Moreover, once the lockout pins **30045** engage the distal ends of the lock windows **30515**, the lock arms **30516** are placed in tension and, as a result, are capable of handling significant loads before failing, if they fail at all.

[0686] As discussed above, both lock arms **30516** are disengaged from the firing member **30040** by the cartridge body **30522** when the staple cartridge **30520** is seated in the stapling instrument **30500**. That said, alternative embodiments are envisioned in which a first component of a staple cartridge unlocks a first lock arm **30516** and a second component of the staple cartridge unlocks a second lock arm **30516** when the staple cartridge is seated in the stapling instrument **30500**. For instance, a cartridge body of the staple cartridge can unlock the first lock arm **30516** and a sled of the staple cartridge can unlock the second lock arm **30516**.

[0687] A surgical stapling instrument **30600** is illustrated in FIG. **140** and a surgical stapling instrument **30700** is illustrated in FIG. **141**. The stapling instruments **30600** and **30700** are similar to the stapling instrument **30500** in many respects. Referring to FIG. **140**, the stapling instrument **30600** comprises a cartridge channel **30610**, a staple cartridge **30620** removably positionable in the cartridge channel **30610**, and a staple firing lockout **30614** mounted to the cartridge channel **30610** which prevents the firing member **30040** from being advanced through a staple firing stroke unless the staple cartridge **30620** is seated in the cartridge channel **30610**. Similarly, referring to FIG. **141**, the stapling instrument **30700** comprises a cartridge channel **30710**, a staple cartridge **30720** removably positionable in the cartridge channel **30710**, and a staple firing lockout **30714** mounted to the cartridge channel **30710** which prevents the firing member **30040** from being advanced through a staple firing stroke unless the staple cartridge **30720** is seated in the cartridge channel **30710**. Notably, however, seating the staple cartridge **30720** in the stapling instrument **30600** does not unlock the staple firing system of the stapling instrument **30600** and, likewise, seating the staple cartridge **30620** in the stapling instrument **30700** does not unlock the staple firing system of the stapling instrument **30700**. Thus, the stapling instruments **30600** and **30700** can be used in the same operating room at the same time without the possibility

of being used with the wrong staple cartridge, despite the fact that the staple cartridges **30620** and **30720** may be confusingly similar.

[0688] Referring to FIG. 142, further to the above, the staple cartridge **30620** further comprises a cartridge body **30622** including a proximal end **30626** that is angled such that the center of the cartridge body **30622**, i.e., the portion closest to the longitudinal slot **30023**, extends further proximally than the lateral sides of the cartridge body **30622**. The staple cartridge **30620** further comprises a sled **30630**, which is similar to the sled **30030** in many respects, that comprises a proximal end **30636** having a profile that matches, or at least substantially matches, the profile of the proximal end **30626** of the cartridge body **30622**. Referring again to FIG. 140, the firing lockout **30614** is similar to the firing lockout **30514**. Among other things, the firing lockout **30614** comprises lock arms **30616** which releasably hold the firing member **30040** in its unfired position until the lock arms **30616** are displaced laterally by the proximal end of the cartridge body **30622** and/or the proximal end of the sled **30630** to release the lockout pins **30045** from lock windows defined in the lock arms **30616**. If the staple cartridge **30620** is removed from the cartridge channel **30610**, the lock arms **30616** resiliently return to their locked position.

[0689] Referring to FIG. 143, further to the above, the staple cartridge **30700** further comprises a cartridge body **30722** including a proximal end **30726** that is angled such that the lateral sides of the cartridge body **30722**, i.e., the portions furthest away from the longitudinal slot **30023**, extend further proximally than the center of the cartridge body **30722**. The staple cartridge **30720** further comprises a sled **30730**, which is similar to the sled **30030** in many respects, that comprises a proximal end **30736** having a profile that matches, or at least substantially matches, the profile of the proximal end **30726** of the cartridge body **30722**. Referring again to FIG. 141, the firing lockout **30714** is similar to the firing lockout **30514**. Among other things, the firing lockout **30714** comprises lock arms **30716** which releasably hold the firing member **30040** in its unfired position until the lock arms **30716** are displaced laterally by the proximal end of the cartridge body **30722** and/or the proximal end of the sled **30730** to release the lockout pins **30045** from lock windows defined in the lock arms **30716**. If the staple cartridge **30720** is removed from the cartridge channel **30710**, the lock arms **30716** resiliently return to their locked position.

[0690] Notably, further to the above, the proximal end of the staple cartridge **30620** would not displace, or at least sufficiently displace, the lock arms **30716** of the firing lockout **30714** to disengage the firing lockout **30714** from the firing member **30040** if the staple cartridge **30620** were to be seated in the stapling instrument **30700**. Moreover, the proximal end of the staple cartridge **30720** would not displace, or at least sufficiently displace, the lock arms **30616** of the firing lockout **30614** to disengage the firing lockout **30614** from the firing member **30040** if the staple cartridge **30720** were to be seated in the stapling instrument **30600**. Thus, the staple cartridges **30620** and **30720** each comprise unique keying features which unlock their respective, or proper, stapling instruments.

[0691] In various instances, further to the above, the cartridge body and/or sled of a staple cartridge, or staple cartridge type, can comprise one or more unique keying features which can only unlock its respective stapling instru-

ment. In certain instances, the pan extending under the cartridge body can comprise a proximal feature, or key, configured to unlock the staple firing drive of its stapling instrument. Referring to FIG. 144, a cartridge pan **30824**, which is similar to the pan **30024** in many respects, comprises a proximal projection, or key, **30826** configured to unlock the staple firing drive of a stapling instrument. The projection **30826** is comprised of folded sheet metal to form a tubular structure, for example. The tubular structure is strengthened by a nested interconnection including a tab **30827** and a slot **30828**.

[0692] A surgical stapling instrument **30900** is illustrated in FIGS. 145 and 147 and a surgical stapling instrument **31000** is illustrated in FIG. 148. The stapling instruments **30900** and **31000** are similar to the stapling instrument **30500** in many respects. Referring to FIG. 145, the stapling instrument **30900** comprises a cartridge channel **30910**, a staple cartridge **30920** removably positionable in the cartridge channel **30910**, and a staple firing lockout **30914** mounted to the cartridge channel **30910** which prevents the firing member **30040** from being advanced through a staple firing stroke unless the staple cartridge **30920** is seated in the cartridge channel **30910**. Similarly, referring to FIG. 148, the stapling instrument **31000** comprises a cartridge channel, a staple cartridge **31020** removably positionable in the cartridge channel, and a staple firing lockout **31014** mounted to the cartridge channel which prevents the firing member **30040** from being advanced through a staple firing stroke unless the staple cartridge **31020** is seated in the cartridge channel.

[0693] Notably, the staple firing lockout **30914** comprises only one lock arm **30916** which extends alongside the right side of the firing member **30040**. That said, the one lock arm **30916** comprises a lock window defined therein which is configured to capture and suitably hold a lockout pin **30045** of the firing member **30040** to hold the firing member **30040** in its unfired position, as illustrated in FIG. 147, until the staple cartridge **30920** is seated in the cartridge channel **30910**, as illustrated in FIG. 145. More specifically, the cartridge body **30922** of the staple cartridge **30920** comprises a proximal projection, or key, **30926** extending from the right side of the cartridge body **30922** that engages the lock arm **30916** and flexes the lock arm **30916** laterally outwardly when the staple cartridge **30920** is seated in the cartridge channel **30910**. Notably, the cartridge body **30922** does not comprise a projection, or key, **30926** extending from the left side of the cartridge body **30922**.

[0694] Also, notably, the staple firing lockout **31014** comprises only one lock arm **31016** which extends alongside the left side of the firing member **30040**. That said, the one lock arm **31016** comprises a lock window defined therein which is configured to capture and suitably hold a lockout pin **30045** of the firing member **30040** to hold the firing member **30040** in its unfired position, as illustrated in FIG. 148, until the staple cartridge **31020** is seated in the cartridge channel of the stapling instrument **31000**. More specifically, the cartridge body **31022** of the staple cartridge **31020** comprises a proximal projection, or key, **31026** extending from the left side of the cartridge body **31022** that engages the lock arm **31016** and flexes the lock arm **31016** laterally outwardly when the staple cartridge **31020** is seated in the stapling instrument **31000**. Notably, the cartridge body **31022** does not comprise a projection, or key, **31026** extending from the right side of the cartridge body **31022**.

[0695] Owing to the asymmetry of the cartridge bodies 30922 and 31022 and the corresponding asymmetry of the staple firing lockouts 30914 and 31014, seating the staple cartridge 31020 in the stapling instrument 30900 does not unlock the staple firing system of the stapling instrument 30900 and, likewise, seating the staple cartridge 30920 in the stapling instrument 31000 does not unlock the staple firing system of the stapling instrument 31000. Thus, the stapling instruments 30900 and 31000 can be used in the same operating room at the same time without the possibility of being used with the wrong staple cartridge despite the fact that the staple cartridges 30920 and 31020 may be confusingly similar. In some instances, the staple pattern produced by the staple cartridge 30920 is different than the staple pattern produced by the staple cartridge 31020 and, as a result, the anvil of the stapling instrument 30900 will have a different forming pocket arrangement than the anvil of the stapling instrument 31000. In such instances, the asymmetrical key/firing lockout arrangements disclosed herein can prevent a mismatch between the arrangement of the staple cavities and the arrangement of the staple forming pockets.

[0696] Referring to FIGS. 149 and 150, a staple cartridge 31120 comprises a cartridge body 31122 including parallel longitudinal rows of staple cavities while a staple cartridge 31220 comprises a cartridge body 31222 including rows of staple cavities oriented in transverse directions. Similar to the above, referring to FIG. 149, the proximal end of the cartridge body 31122 comprises keys 31126 extending from the left side of the cartridge body 31122—but not the right, or opposite, side of the cartridge body 31122—and the proximal end of the cartridge body 31222, referring to FIG. 150, comprises keys 31226 extending from the right side of the cartridge body 31222—but not the left side of the cartridge body 31222. The staple cartridge 31120 (FIG. 149) is used with a first stapling instrument having parallel longitudinal rows of anvil staple forming pockets and a left-side staple firing lockout, such as the firing lockout 31014 (FIG. 148), for example. The staple cartridge 31220 (FIG. 150) is used with a second stapling instrument having longitudinal rows of transverse staple forming pockets and a right-side staple firing lockout, such as the firing lockout 30914 (FIG. 147), for example. The staple cartridge 31220 does not unlock the first stapling instrument and, similarly, the staple cartridge 31120 does not unlock the second stapling instrument. As such, the keys 31126 of the staple cartridge 31120 cannot unlock a stapling instrument having staple forming pockets which extend in transverse directions and, correspondingly, the keys 31226 of the staple cartridge 31220 cannot unlock a stapling instrument having staple forming pockets which extend in parallel longitudinal rows.

[0697] Notably, the staple cartridge 31120 and the staple cartridge 31220 are substantially the same length and have substantially the same shape. Moreover, the staple cartridges 31120 and 31220 are both configured to produce staple lines in the patient tissue which are approximately 60 mm in length. However, the staple cartridges 31120 and 31220 could both be configured to produce staple lines which are approximately 30 mm in length or 45 mm in length, for example. Moreover, it is entirely possible that the cartridge body 31122 and the cartridge body 31222 have the same color. In various instances, a commercial supplier may color-code the cartridge bodies of the staple cartridges that they sell to indicate the size of the staples stored therein. For instance, the cartridge bodies containing unformed staples

having an approximately 4 mm unformed height are green, for example. The cartridge bodies containing unformed staples having an approximately 2.5 mm unformed height could be white, for example. Thus, it is entirely possible that the staple cartridges 31120 and 31220 have the same color. As such, it is possible that a clinician could grab one staple cartridge when they intended to grab the other and install the staple cartridge in the wrong stapling instrument. The improvements disclosed herein account for such possibilities and lockout the stapling instrument in such instances.

[0698] A surgical instrument 30800 is illustrated in FIGS. 151-155. Referring primarily to FIGS. 153 and 154, the surgical instrument 30800 comprises a cartridge channel 30810, a staple cartridge 30820 removably positioned in the cartridge channel 30810, a firing member 30040, and a lockout 30814 mounted to the cartridge channel 30810. The lockout 30814 comprises a leaf spring 30816 including a proximal end anchored in an aperture defined in the cartridge channel 30810 and a distal end which is movable relative to the fixed proximal end. Referring primarily to FIGS. 153 and 155, the lockout 30814 further comprises a lockout box 30815 configured to capture one of the lockout pins 30045 extending from the cutting portion 30042 of the firing member 30040 and hold the firing member 30040 in an unfired position when the staple cartridge 30820 is not seated in the cartridge channel 30810. The lockout box 30815 comprises a distal wall configured to prevent the firing member 30040 from being advanced distally, a proximal wall configured to prevent the firing member 30040 from being retracted proximally, and a bottom wall connecting the proximal wall and the distal wall of the lockout box 30815. The top of the lockout box 30815, however, is open but could be closed.

[0699] The staple cartridge 30820 comprises a cartridge body 30822, a sled, and a pan 30824 attached to and extending under the cartridge body 30822. Further to the above, the pan 30824 comprises a proximal projection 30826 configured to engage the leaf spring 30816 of the lockout 30814 when the staple cartridge 30820 is seated in the cartridge channel 30810, as illustrated in FIGS. 152 and 154. When the projection 30826 contacts the leaf spring 30816, the leaf spring 30816 flexes laterally such that the lockout pin 30045 is no longer captured in the lockout box 30815 of the lockout 30814. At such point, the firing member 30040 has been unlocked and the firing member 30040 can be advanced distally to perform a staple firing stroke. Referring primarily to FIG. 154, the distal, or free, end of the leaf spring 30816 extends into a window 30819 defined in the cartridge channel 30810. The window 30819 provides clearance for the leaf spring 30816 when the leaf spring 30816 is flexed by the staple cartridge 30820. Also, a bottom sidewall of the window 30819 supports the distal end of the leaf spring 30816 such that the distal end is at least simply supported. In any event, the lockout 30814 provides a missing cartridge lockout and an improper cartridge lockout for staple cartridges, such as the staple cartridge 30020, that do not have an appropriate key for unlocking the stapling instrument 30800.

[0700] As discussed above, the lockout 30814 is moved from a locked position (FIGS. 152 and 153) to an unlocked position (FIG. 154) when the staple cartridge 30820 is seated in the cartridge channel 30810 of the stapling instrument 30800. This deflection is seen in FIG. 155 which illustrates the lockout 30814 in its locked position in solid and its

unlocked position in phantom. In instances where an improper or incompatible staple cartridge, i.e., a staple cartridge not having a suitable key, is seated in the cartridge channel **30810**, the leaf spring **30816** will not be deflected, or at least suitably deflected, to unlock the firing member **30040**. Notably, the lockout **30814** further comprises a tab **30817** extending from the leaf spring **30816** such that the tab **30817** moves laterally with the leaf spring **30816** when the lockout **30814** is deflected. When the lockout **30814** is in its locked position, as illustrated in FIG. **153**, the tab **30817** prevents the anvil of the surgical instrument **30800**, i.e., the anvil **30050**, from being moved into a closed, or fully-clamped, position, as described in greater detail below.

[0701] The anvil **30050** is rotatably coupled to the cartridge channel **30810** about pivot pins **30051** mounted in apertures defined in the cartridge channel **30810**. When the anvil **30050** is rotated toward the cartridge channel **30810** by a closure system of the surgical instrument **30800**, and the staple cartridge **30820** is not seated in the cartridge channel **30810**, a bottom surface **30057** of the anvil **30050** contacts the tab **30817** and the anvil **30050** is blocked from being moved into its closed or fully-clamped position. When the staple cartridge **30820** is seated in the cartridge channel **30810**, however, the tab **30817** is displaced laterally such that, when the anvil **30050** is closed, the anvil **30050** does not contact the tab **30817** and the anvil **30050** can be moved into its closed or fully-clamped position. Thus, the lockout **30814** also comprises an anvil closure lockout as the lockout **30814** prevents the anvil **30050** from being closed when the staple cartridge **30820** is not seated in the cartridge channel **30810**. In such instances, the clinician will become quickly aware that an improper staple cartridge is positioned in the cartridge channel **30810** and/or that a staple cartridge is missing altogether as they won't be able to close the anvil **30050**. Because the anvil **30050** can't be closed onto the tissue, the staple firing stroke of the stapling instrument **30800** would also be prevented in such instances. In alternative embodiments where the staple cartridge jaw is rotatable instead of the anvil, such a lockout could be used to prevent the staple cartridge jaw from being rotated into a closed or fully-clamped position if an improper staple cartridge is positioned in the staple cartridge jaw or a staple cartridge is missing from the cartridge jaw altogether.

[0702] As discussed above, the lockout **30814** is configured to resist the closure of the anvil **30050**. To this end, further to the above, the proximal end of the lockout **30814** is fixedly supported in the cartridge channel **30810** and the distal end of the lockout **30814** is simply supported by the sidewalls of the window **30819**. This is the case when the lockout **30814** is in both of its locked (FIG. **153**) and unlocked (FIG. **154**) configurations. As such, the lockout **30814** can act as a beam supported at both ends and is well-suited to withstand the clamping load applied by the anvil **30050**. Similarly, the tab **30817** extending from the lockout **30814** is also supported by the cartridge channel **30810**. More specifically, the tab **30817** is slidably supported in a slot **30818** defined in the cartridge channel **30810** when the lockout **30814** is in both of its locked (FIG. **153**) and unlocked (FIG. **154**) configurations. As such, the lockout **30814** can act as a beam supported at both ends and an intermediate position and is well-suited to withstand the clamping load applied by the anvil **30050**. That said, any suitable support arrangement could be used.

[0703] As discussed above, the lockout **30814** is configured to prevent the anvil **30050** of the stapling instrument **30800** from being moved into a closed, or fully-clamped, position when the staple cartridge **30820** is not seated in the cartridge channel **30810**. That said, the lockout **30814** is configured to prevent the anvil **30050** from being substantially closed at all when the staple cartridge **30820** is not seated in the cartridge channel **30810**. In such instances, the anvil **30050** can be moved slightly toward the cartridge channel **30810**; however, the anvil **30050** is noticeably open when the anvil **30050** contacts the tab **30817** of the lockout **30814**. In various alternative embodiments, the anvil **30050** is prevented from moving at all until the staple cartridge **30820** is seated in the cartridge channel **30810**. In either event, the stapling instrument **30800** is not insertable into a patient through a trocar when the anvil **30050** is locked out. More specifically, a trocar comprises an inner passageway, or cannula, that is sized and configured to closely receive a surgical instrument therein and, when the anvil **30050** is locked out as described above, the distance between the anvil **30050** and the cartridge channel **30810** is too large for the stapling instrument **30800** to fit through the inner passageway. As a result, in such instances, the clinician using the stapling instrument **30800** will become aware that an improper staple cartridge is positioned in the stapling instrument **30800** before the stapling instrument **30800** is inserted into the patient.

[0704] A staple cartridge **31520** is illustrated in FIG. **155A**. The staple cartridge **31520** comprises a cartridge body **31522** and a pan **31524** attached to the cartridge body **31522**. The pan **31524** comprises lock arms **31521** engaged with lateral channels defined in the cartridge body **31522** which hold the pan **31524** to the cartridge body **31522**. The pan **31524** is comprised of stamped metal, such as stainless steel, for example. The pan **31524** comprises two lateral sides—one on each side of the longitudinal slot **30023**. Each lateral side of the pan **31524** extends along a lateral side of the cartridge body **31522** and under a portion of the cartridge body **31522**. Each lateral side of the pan **31524** further comprises a proximal end **31527** that wraps around the proximal end of the cartridge body **31522**. The proximal ends **31527** extend orthogonally, or at least substantially orthogonally, to the lateral sides of the pan **31524**. Each proximal end **31527** comprises a tab which is folded to form a proximally-extending key **31526**. Similar to the above, the keys **31526** are configured to unlock a staple firing system of a stapling instrument when the staple cartridge **31520** is seated in the stapling instrument.

[0705] Further to the above, each key **31526** comprises a rounded proximal end created by folding over the tabs outwardly such that the ends of the tab are brought back into contact with the proximal end **31527**. As a result, the keys **31526** are sturdy and deflection of the keys **31526** is prevented, or at least substantially reduced. As such, the keys **31526** will reliably deflect the firing system locks to unlock the firing system when the staple cartridge **31520** is seated in the stapling instrument. Each proximal end **31527** further comprises one or more retention teeth **31529** which extend into slots **31528** defined in the proximal end **31527**. The slots **31528** facilitate the folding of the proximal ends **31527** and also prevent, or at least limit, movement and/or deflection within the keys **31526**. The teeth **31529** bite into the proximal end **31527** and hold the key **31526** in its folded configuration.

[0706] A staple cartridge 31620 is illustrated in FIG. 155B. The staple cartridge 31620 comprises a cartridge body 31522 and a pan 31624 attached to the cartridge body 31522. The pan 31624 comprises lock arms 31621 engaged with lateral channels defined in the cartridge body 31522 which hold the pan 31624 to the cartridge body 31522. The pan 31624 is comprised of stamped metal, such as stainless steel, for example. The pan 31624 comprises two lateral sides—one on each side of the longitudinal slot 30023. Each lateral side of the pan 31624 extends along a lateral side of the cartridge body 31522 and under a portion of the cartridge body 31522. Each lateral side of the pan 31624 further comprises a proximal end that wraps downwardly around the proximal end of the cartridge body 31522. The proximal ends extend orthogonally, or at least substantially orthogonally, to the lateral sides of the pan 31624. Each proximal end comprises a tab which is folded to form a proximally-extending key 31626. Similar to the above, the keys 31626 are configured to unlock a staple firing system of a stapling instrument when the staple cartridge 31620 is seated in the stapling instrument.

[0707] Further to the above, each key 31626 comprises a laterally-facing U-shaped channel. More specifically, each key 31626 comprises an inner base 31627, a laterally-extending top side 31628 extending from the inner base 31627, and a laterally-extending bottom side 31629 extending from the opposite side of the inner base 31627. The U-shaped configuration of the keys 31626 prevents the keys 31626 from buckling under a longitudinal load and/or deflecting under a laterally-directed torque. Notably, the keys 31626 are folded from tabs extending from the pan 31624 in such a manner so as to create clearance gaps 31625 under the keys 31626. The clearance gaps 31625 are sized and configured to permit the locking pins of a firing member to pass under the keys 31626 during a staple firing stroke of the firing member.

[0708] A staple cartridge 31720 is illustrated in FIG. 155C. The staple cartridge 31720 comprises a cartridge body 31522 and a pan 31724 attached to the cartridge body 31522. The pan 31724 comprises lock arms 31721 and 31721' engaged with lateral channels defined in the cartridge body 31522 which hold the pan 31724 to the cartridge body 31522. The pan 31724 is comprised of stamped metal, such as stainless steel, for example. The pan 31724 comprises two lateral sides—one on each side of the longitudinal slot 30023. Each lateral side of the pan 31724 extends along a lateral side of the cartridge body 31522 and under a portion of the cartridge body 31522. One lateral side of the pan 31724 further comprises a proximal end 31727 that wraps downwardly around the proximal end of the cartridge body 31522. The proximal end 31727 extends orthogonally, or at least substantially orthogonally, to the lateral side of the pan 31724. The proximal end 31727 comprises a tab which is folded to form a proximally-extending key 31726. Similar to the above, the key 31726 is configured to unlock a staple firing system of a stapling instrument when the staple cartridge 31720 is seated in the stapling instrument.

[0709] Further to the above, the lateral side of the pan 31724 comprises an arcuate or circular cut-out and the proximal end 31727 comprises an arcuate or circular projection 31723 that is bent around the side of the cartridge body 31522 into the circular cut-out. The projection 31723 is closely received in the cut-out such that the proximal end 31727 of the pan 31724 is greatly stiffened or strengthened

by this arrangement. The key 31726 comprises an L-shaped tab bent proximally from the pan 31724. The key 31726 comprises a shoulder 31728 bent upwardly from the proximal end 31727 to create this L-shaped configuration. The shoulder 31728 comprises at least one notch, or strain relief, 31729 configured to facilitate the bending of the key 31726. The L-shaped configuration of the key 31726 prevents the key 31726 from buckling under a longitudinal load and/or deflecting under a laterally-directed torque. Notably, the key 31726 is folded from a tab extending from the pan 31724 in such a manner so as to create a clearance gap 31725 under the key 31726. The clearance gap 31725 is sized and configured to permit the locking pin of a firing member to pass under the key 31726 during a staple firing stroke of the firing member.

[0710] A staple cartridge 31920 is illustrated in FIG. 155E. The staple cartridge 31920 comprises a cartridge body 31522 and a pan 31924 attached to the cartridge body 31522. The pan 31924 comprises lock arms 31921 engaged with lateral channels defined in the cartridge body 31522 which hold the pan 31924 to the cartridge body 31522. The pan 31924 is comprised of stamped metal, such as stainless steel, for example. The pan 31924 comprises two lateral sides—one on each side of the longitudinal slot 30023. Each lateral side of the pan 31924 extends along a lateral side of the cartridge body 31522 and under a portion of the cartridge body 31522. One lateral side of the pan 31924 further comprises a proximal end 31927 that wraps around the proximal end of the cartridge body 31522. The proximal end 31927 extends orthogonally, or at least substantially orthogonally, to the lateral side of the pan 31924. The proximal end 31927 comprises a tab which is folded to form a proximally-extending key 31926. Similar to the above, the key 31926 is configured to unlock a staple firing system of a stapling instrument when the staple cartridge 31920 is seated in the stapling instrument.

[0711] Further to the above, the key 31926 comprises an L-shaped tab bent proximally from the pan 31924. The key 31926 comprises a shoulder 31928 bent upwardly from the proximal end 31927 to create this L-shaped configuration. The L-shaped configuration of the key 31926 prevents the key 31926 from buckling under a longitudinal load and/or deflecting under a laterally-directed torque. Moreover, a free edge of the shoulder 31928 is welded, soldered, and/or brazed to the proximal end 31927 in order to strengthen the key 31926. That said, any suitable number of welds 31929 can be used to secure or strengthen the key 31926. Notably, the key 31926 is folded from a tab extending from the pan 31924 in such a manner so as to create a clearance gap 31925 under the key 31926. The clearance gap 31925 is sized and configured to permit the locking pin of a firing member to pass under the key 31926 during a staple firing stroke of the firing member.

[0712] A staple cartridge 31820 is illustrated in FIG. 155D. The staple cartridge 31820 comprises a cartridge body 31522 and a pan 31824 attached to the cartridge body 31522. The pan 31824 comprises lock arms 31821 engaged with lateral channels defined in the cartridge body 31522 which hold the pan 31824 to the cartridge body 31522. The pan 31824 is comprised of stamped metal, such as stainless steel, for example. The pan 31824 comprises two lateral sides—one on each side of the longitudinal slot 30023. Each lateral side of the pan 31824 extends along a lateral side of the cartridge body 31522 and under a portion of the cartridge

body **31522**. One lateral side of the pan **31824** further comprises a proximal end **31827** that wraps around the proximal end of the cartridge body **31522**. The proximal end **31827** extends orthogonally, or at least substantially orthogonally, to the lateral side of the pan **31824**. The proximal end **31827** comprises a tab which is folded to form a proximally-extending key **31826**. Similar to the above, the key **31826** is configured to unlock a staple firing system of a stapling instrument when the staple cartridge **31820** is seated in the stapling instrument.

[0713] Further to the above, the key **31826** comprises a rounded proximal end created by folding over the tab outwardly such that the end of the tab is brought back into contact with the proximal end **31827**. As a result, the key **31826** is sturdy and deflection of the key **31826** is prevented, or at least substantially reduced. As such, the key **31826** will reliably deflect the firing system locks to unlock the firing system when the staple cartridge **31820** is seated in the stapling instrument. The proximal end **31827** further comprises one or more retention teeth **31829** which extend into slots **31828** defined in the proximal end **31827**. The slots **31828** facilitate the folding of the proximal end **31827** and also prevent, or at least limit, movement and/or deflection within the key **31826**. The teeth **31829** bite into the proximal end **31827** and hold the key **31826** in its folded configuration. Notably, the key **31826** is folded from a tab extending from the pan **31824** in such a manner so as to create a clearance gap **31825** under the key **31826**. The clearance gap **31825** is sized and configured to permit the locking pin of a firing member to pass under the key **31826** during a staple firing stroke of the firing member.

[0714] Many of the lockouts disclosed herein are defeated when a compatible or proper staple cartridge is seated in the stapling instrument. When seated, a staple cartridge is locked into position within the stapling instrument. In such instances, there is little, if any, relative movement possible between the staple cartridge and the stapling instrument until the staple cartridge is uninstalled from the stapling instrument.

[0715] In various instances, a surgical stapling assembly comprises a shaft and an end effector extending distally from the shaft including a first jaw and a second jaw rotatable relative to the first jaw. The surgical stapling assembly may comprise a lockout member configured to prevent the inadvertent firing of the surgical stapling assembly and/or the clamping of the surgical stapling assembly until a lockout key unlocks the lockout member. The lockout key may be a part of a staple cartridge configured to be installed in one of the first jaw and the second jaw, for example. Particularly, the lockout key may be a part of a sled of the staple cartridge such that the staple cartridge can unlock the lockout member when the sled is in its unfired position indicating that the staple cartridge is unspent when the staple cartridge is installed within the surgical stapling assembly. In at least one instance, further action may be required to unlock the lockout with the lockout key. For example, an end effector may be required to attain a fully clamped configuration before the lockout key can unlock the lockout member. One example of a lockout can be found in U.S. Patent Application Publication No. 2016/0249921 entitled SURGICAL APPARATUS WITH CONDUCTOR STRAIN RELIEF, now U.S. Pat. No. 10,085,749, the entire disclosure of which is hereby incorporated by reference herein.

[0716] In at least one instance, surgical stapling assemblies, such as the one described above, may be used with a surgical robot. The surgical stapling assemblies can be configured to be attached to robotic systems and operated by way of robotic arms of the robotic systems. These robotic systems allow for surgeons to be outside of a sterile field within which the patient is present. In at least one instance, a technician and/or another surgeon, for example, may be located within the bounds of the sterile field to monitor the interface between the tools and the patient. This technician and/or surgeon may attach and detach instruments to the robotic arms during a surgical procedure. In some instances, it may be advantageous to be able to actively bypass the lockout member of a surgical stapling assembly. Providing this ability can enable a surgeon or technician to manually defeat a lockout means of a staple cartridge when the lockout means, for whatever reason, cannot be automatically defeated. Providing this ability may also enable a surgeon to test the operability of the lockout member to ensure that the lockout member is functional prior to using the surgical stapling assembly. In an instance where a surgeon wants to manually override the lockout member to fire a staple cartridge, a surgeon or clinician may know that the installed staple cartridge is a proper unfired staple cartridge and may want to fire the staple cartridge regardless of the fact that the lockout member was not actually defeated. In at least one instance, the clinician may want remove that lockout member from the firing sequence and prevent it from being a part of the firing stroke. Moreover, providing direct access to the lockout member within the end effector itself for manual unlocking can provide an advantage with or without a system that automatically defeats the lockout member. Direct access to the lockout member within the end effector can eliminate additional components that otherwise may be present in a system utilizing an unlocking mechanism to unlock the lockout member that is further upstream of the lockout member. Using an unlocking mechanism further upstream to the lockout member within the shaft of the surgical instrument, for example, can introduce additional components that might jam or fail during the application of an unlocking actuation.

[0717] FIGS. 156-160 depict a surgical stapling assembly **41000** configured to clamp, staple, and cut the tissue of a patient. The surgical stapling assembly **41000** is configured to be attached to, detached from, and operated by a surgical robot and/or a surgical instrument handle. The surgical stapling assembly **41000** comprises a shaft **41100**, a first jaw **41200** pivotably supported within the shaft **41100**, and a second jaw **41300** attached to the shaft **41100**. The first jaw **41200** is movable between an unclamped configuration and a clamped configuration to clamp and unclamp tissue positioned between the first jaw **41200** and the second jaw **41300**. The surgical stapling assembly **41000** further comprises a staple cartridge **41230** comprising a plurality of staples removably stored therein. The staple cartridge **41230** is configured to be installed into the first jaw **41200** and replaced with other staple cartridges. The surgical stapling assembly **41000** further comprises a firing member **41400** extending through the shaft **41100** that is configured to move the first jaw **41200** relative to the second jaw **41300** between the unclamped configuration and the clamped configuration, deploy staples from the staple cartridge **41230**, and cut tissue during a firing stroke with a knife, or blade, **41422**. The firing member **41400** is configured to be actuated by a drive

system of a surgical robot and/or a surgical instrument handle. Embodiments are envisioned where the firing member **41400** is driven with a rotary drive shaft. Embodiments are also envisioned where the jaw configured to receive the staple cartridge is fixed to the shaft and the jaw containing the anvil is movable between a clamped configuration and an unclamped configuration.

[0718] The surgical stapling assembly **41000** further comprises a lockout **41500** (FIG. 160) configured to prevent the firing member **41400** from moving distally past a specific position unless a proper unspent staple cartridge is installed within the first jaw **41200** and the first jaw **41200** is in a fully clamped configuration. In at least one instance, the firing member **41400** is permitted to move a first distance between a home position and the specific position regardless of the condition of the lockout **41500** to permit clamping and unclamping of tissue, as discussed in greater detail below. The lockout **41500** is biased toward a locked configuration where the firing member **41400** is prevented from moving distally beyond the specific position. The lockout **41500** is movable into an unlocked configuration where the firing member **41400** is permitted to move distally beyond the specific position to deploy staples from the staple cartridge **41230**. Discussed in greater detail below, the surgical stapling assembly **41000** further comprises a direct access orifice defined therein configured to allow a clinician to manually, or artificially, unlock the lockout **41500**, i.e., move the lockout **41500** into the unlocked configuration.

[0719] The first jaw **41200** comprises a channel **41210** configured to receive the staple cartridge **41230** therein. The staple cartridge **41230** is configured to be installed within the channel **41210** and readily replaced with another staple cartridge. The staple cartridge **41230** further comprises a sled **41235** movable between an unfired position and a fired position to eject the staples from the staple cartridge **41230** as the sled **41235** is pushed distally through a cartridge body **41232** of the staple cartridge **41230** by the firing member **41400**. The second jaw **41300** comprises an anvil **41320** comprising a staple-forming surface **41310** configured to form the staples ejected from the staple cartridge **41230**.

[0720] The first jaw **41200** is movable relative to the second jaw **41300** between an unclamped configuration and a clamped configuration by the firing member **41400**. Embodiments are envisioned where the second jaw **41300** is movable relative to the first jaw **41200**. To clamp tissue, the firing member **41400** is moved distally a first distance from a home position to cam the first jaw **41200** into a clamped configuration. Referring to FIG. 159, the firing member **41400** comprises anvil-camming portions **41423** configured to engage a ramp **41332** of an anvil channel **41330** defined within the second jaw **41300** and channel-camming portions **41424** configured to engage a ramp **41222** of a bottom surface **41220** of the first jaw **41200**. The anvil-camming portions **41423** and the channel-camming portions **41424** extend laterally from a distal portion **41420** of the firing member **41400** and are configured to control the distance between the first jaw **41200** and the second jaw **41300** as the distal portion **41420** of the firing member moves through its firing stroke. During the first distance discussed above, the anvil-camming portions **41423** and the channel-camming portions **41424** engage the first and second jaws **41200**, **41300** and cam the first jaw **41200** into a clamped configuration. Further distal movement of the distal portion **41420** of the firing member **41400** holds the first and second jaws

41200, **41300** relative to each other during the firing stroke and pushes the sled **41235** distally to eject staples stored within the staple cartridge **41230**.

[0721] The surgical stapling assembly **41000** further comprises a lockout **41500** configured to prevent the firing member from being advanced distally beyond the first distance unless a proper unspent staple cartridge is installed within the first jaw **41200** and the first jaw **41200** is fully clamped. The lockout **41500** comprises a lockout member **41510** pivotably supported within the shaft **41100** and movable between an unlocked configuration (FIG. 157) where the firing member **41400** is permitted to move beyond the first distance to complete the firing stroke and a locked configuration (FIG. 158) where the firing member **41400** is prevented from moving beyond the first distance. The lockout member **41510** is biased into the locked configuration by a spring **41520**. A proper unspent staple cartridge installed within the channel **41210** can overcome the bias provided by the spring **41520** when the first jaw **41200** is moved into the clamped configuration.

[0722] To unlock the lockout **41500**, the first jaw **41200** must be moved into its clamped configuration to present the sled **41235** to engage and unlock the lockout member **41510**. The sled **41235** cannot defeat the lockout **41500** when the first jaw **41200** is not in its clamped configuration. Embodiments are envisioned where the cartridge jaw is not pivotable but, rather, the anvil jaw is pivotable. In such embodiments, mere insertion of the staple cartridge presents the sled **41235** to defeat the lockout **41500**. In such embodiments, the lockout **41500** can be defeated prior to the application of any clamping motions to the anvil jaw.

[0723] To unlock the lockout **41500**, as discussed above, a proper unspent staple cartridge must be installed in the first jaw **41200** of the surgical stapling assembly **41000**. The staple cartridge **41230** comprises a sled **41235** comprising a lockout key **41237** extending proximally therefrom. The lockout key **41237** is configured to move the lockout member **41510** into the unlocked configuration when the sled **41235** is in an unfired position and the first jaw **41200** is moved into the clamped configuration. To unlock the lockout, the lockout key **41237** pivots the lockout member **41510** into the unlocked configuration by moving a lockout ledge, or leg, **41511** of the lockout member **41510** away from a lockout notch **41412** defined in a firing shaft, or bar, **41410** of the firing member **41400** which would otherwise prevent distal movement of the firing member **41400** beyond an initial distance used for clamping when the first jaw **41200** is moved into the clamped configuration. The lockout member **41510** comprises a pair of arms **41512** extending distally from the lockout ledge **41511** which are configured to straddle the firing member **41400** as the firing member **41400** moves through its firing stroke.

[0724] FIG. 157 illustrates the lockout key **41237** engaged with distal ends **41516** of the arms **41512** on a distal end **41515** of the lockout member **41510**. As illustrated in FIG. 157, the lockout member **41510** has pivoted relative to the shaft **41100** about nubs **41513** (FIG. 160) of the lockout member **41510** into the unlocked configuration. When the lockout member **41510** is in the unlocked configuration, the lockout notch **41412** of the firing shaft **41410** will clear the lockout ledge **41511** of the lockout member **41510** thereby permitting the firing member **41400** to move distally through the staple cartridge **41230**. Referring to FIG. 158, if the lockout key **41237** is not present upon clamping the first jaw

41200 into the clamped configuration, the lockout member **41510** remains biased in the locked configuration by way of the spring **41520** (FIG. 159) pushing against the tabs **41514** (FIG. 160) of the lockout member **41510** where the lockout ledge **41511** engages the notch **41412** of the firing shaft **41410** to block distal movement of the firing member **41400** beyond the initial distance used for clamping.

[0725] As discussed above, the surgical stapling assembly **41000** further comprises a direct access orifice **41425** defined therein configured to allow a clinician to artificially move the lockout member **41510** into the unlocked configuration. The orifice **41425** can be positioned in any suitable component such that a tool **41590** can access the lockout member **41510** through the orifice **41425** to move the lockout member **41510** into the unlocked configuration. The orifice **41425** is defined in the channel-camming portions **41424** of the distal portion **41420** of the firing member **41400**. The orifice **41425** may comprise access slits defined in the channel-camming portions **41424**, for example. In at least one instance, the orifice **41425** is defined in the shaft **41100** and/or a component thereof. Nonetheless, the lockout member **41510** is directly accessible through the orifice **41425**. The tool **41590** comprises a hook portion **41591** configured to be inserted through the orifice **41425** and an opening **41517** defined between the arms **41512** of the lockout member **41510** to hook, or latch, onto an upper side of the ledge **41511** to pull the ledge **41511** and thus pivot the lockout member **41510** into the unlocked configuration overcoming the spring bias which encourages the lockout member **41510** into the locked configuration. The orifice **41425** can be configured such that commonly-avoidable tools, such as a screwdriver, for example, do not fit within the orifice, or exterior access aperture, **41425**. Portions of the lockout member **41510** are illustrated in phantom in the unlocked configuration where tool **41590** has positioned the lockout member **41510** into the unlocked configuration. Arms **41512'** and ledge **41511'** are phantom versions of the arms **41512** and ledge **41511** of the lockout member **41510** illustrated in the unlocked configuration.

[0726] Once the lockout member **41510** is manually, or artificially, defeated to move the lockout **41500** into the unlocked configuration, the firing member **41400** is permitted to move distally past an unfired location and into the staple cartridge **41230**. The unfired location is defined as the position after clamping but before firing. Once the firing member **41400** is advanced distally past its unfired position, the tool **41590** can be disengaged from the lockout member **41510** and removed from the orifice **41425** to allow the lockout **41500** to resume normal operation. For instance, the lockout member **41510** will pivot into the locked configuration when the firing member **41400** returns to the unfired location after having at least partially fired a staple cartridge. During the firing stroke, the lockout member **41510** is accessible with the tool **41590** through a secondary access aperture **41160** defined between a proximal end of the channel **41210** and a distal end of the shaft **41100**. That said, the lockout member **41510** will remain defeated during the staple firing stroke. In at least one instance, the direct access orifice is positioned within the shaft **41100**, for example, and can provide access to the lockout member **41510** during the firing stroke of the firing member **41400**. In at least one instance, the secondary access aperture **41160** comprises the primary lockout access aperture.

[0727] The lockout **41500** can be positioned in any suitable location. In at least one instance, the lockout **41500** may be positioned proximal to the distal portion **41420** of the firing member **41400** when the firing member **41400** is in its proximal most position (such as the position illustrated in FIG. 159). In such an instance, the access aperture may be defined in a shaft housing, or frame, of the surgical stapling assembly **41000**. In at least one instance, the access aperture is defined in the channel **41210**.

[0728] In at least one instance, the tool **41590** can be inserted through the direct access aperture **41425** to unlock the lockout **41500** prior to the insertion of the staple cartridge **41230** into the channel **41210**. Moving the lockout **41500** to its unlocked configuration prior to the insertion of a staple cartridge can aid the staple cartridge installation by preventing the lockout **41500** from engaging the staple cartridge during installation. Some lockouts disable improper staple cartridges by bumping a sled of the staple cartridge from its unfired, firable position to an unfired, unfirable position which can cause the staple cartridge to become instantly spent. Moreover, such lockouts may bump a sled of a proper staple cartridge during installation of the proper staple cartridge. Unlocking the lockout **41500** prior to installation of the staple cartridge can ensure that the proper staple cartridge is not disabled accidentally during installation.

[0729] FIGS. 161 and 162 depict a surgical stapling assembly **42000** for use in clamping, stapling, and cutting the tissue of a patient. The surgical stapling assembly **42000** is similar to other stapling assemblies described herein in many respects. The surgical stapling assembly **42000** comprises a firing assembly **42100** and a cartridge channel **42200** configured to receive a staple cartridge therein. The firing assembly **42100** is configured to push a sled of a proper unspent staple cartridge installed within the cartridge channel **42200** to deploy the staples of the staple cartridge and cut the stapled tissue. The surgical stapling assembly **42000** further comprises a lockout **42300** configured to prevent the firing assembly **42100** from being advanced through an improper staple cartridge. The lockout **42300** comprises a spring **42310** which biases the lockout **42300** toward a locked configuration. The lockout **42300** is configured to be pushed proximally by a proper unspent staple cartridge to unlock the firing assembly **42100**. Notably, the lockout **42300** is configured such that lockout **42300** does not accidentally push the sled of the proper staple cartridge into a position which would induce a lockout condition for the firing assembly **42100**. The lockout **42300** can employ any suitable lockout method. The firing assembly **42100** is similar to other firing assemblies described herein.

[0730] The surgical stapling assembly **42000** further comprises a direct access cutout, or aperture, **42210** defined in the bottom of the cartridge channel **42200** at a proximal end of a longitudinal slot **42230** defined in the cartridge channel **42200**. The firing assembly **42100** is movable through the slot **42230** of the cartridge channel **42200** during a staple firing stroke. The direct access cutout **42210** allows for a tool to be inserted within the surgical stapling assembly **42000** to access the lockout **42300** directly. The tool can be inserted through the direct access cutout **42210** to move the lockout **42300** into an unlocked configuration (FIG. 162). Unlocking the lockout **42300** in this manner can be referred to as artificially unlocking the lockout **42300** because an unspent staple cartridge has not automatically unlocked the lockout

42300 for whatever reason. The direct access cutout **42210** comprises a proximal end **42211** and a distal end **42213** comprising a wider cutout portion than the proximal end **42211**. The wider cutout portion of the distal end **42213** can aid in the proper insertion of the tool into the channel **42200**. For example, the tool can comprise a lock-engaging portion that fits in the distal end **42213** but not the proximal end **42211** thereby eliminating the possibility of mis-inserting the tool in the proximal end **42211**. Moreover, the lockout **42300**, and its position relative to other components of the surgical stapling assembly **42000**, is also directly visible through the direct access cutout **42210**. Nonetheless, a tool can be inserted through the cutout **42210** to pull and/or push the lockout **42300** proximally to overcome the spring bias and move the lockout **42300** into the unlocked configuration. The tool can also be removed and disengaged from the lockout **42300** such that the lockout **42300** can resume normal operation. Moreover, providing the ability to manually move the lockout **42300** may allow a clinician to move the lockout **42300** away from its locked position before installing a staple cartridge into the cartridge channel **42200** to prevent the lockout **42300** from moving a sled of the staple cartridge that is being installed into the cartridge channel **42200** prematurely.

[0731] FIGS. 163 and 164 depict a surgical stapling assembly **43000** comprising a firing assembly **43100**, a frame **43400** that supports the firing assembly **43100** therein, a cartridge channel **43300** pivotably attached to the frame **43400**, and a lockout key mechanism **43500** configured to defeat a lockout of the surgical stapling assembly **43000**. The surgical stapling assembly **43000** can comprise any suitable lockout; however, a diving knife lockout where the firing assembly **43100** falls into a locking recess in the absence of a proper unspent staple cartridge being positioned in the cartridge channel **43300** is described below.

[0732] The firing assembly **43100** comprises a firing shaft **43110** and a firing member **43120** attached to the distal end of the firing shaft **43110**. Although a linear firing shaft is illustrated, the firing assembly **43100** may be configured with a rotary drive shaft. The firing shaft **43110** is configured to be actuated by a firing driver of a surgical instrument handle and/or a surgical robot, for example. Any suitable drive mechanism may be used. The firing member **43120** comprises anvil-camming pins **43122** and channel camming pins **43123** extending laterally therefrom. The pins **43122**, **43123** are configured to control the clamping pressure on the tissue captured within the surgical stapling assembly **43000** during a firing stroke. The firing member **43120** further comprises a cutting edge **43121** configured to cut the clamped tissue. The firing member **43120** further comprises a ledge, or distal nose, **43124** configured to engage and/or rest on top of a sled of an unfired proper staple cartridge such that the firing member **43120** does not fall into the lockout recess.

[0733] The firing assembly **43100** further comprises an extension **43111** configured to be biased downwardly toward the channel **43300** by a spring member mounted within the frame **43400**. Discussed in greater detail below, the downward bias of the extension **43111** encourages the firing assembly **43100** toward its locked out condition. The downward bias is overcome when an unspent proper staple cartridge is installed within the cartridge channel **43300**.

[0734] The lockout key mechanism **43500** comprises a spring **43530**, a wedge **43520** slidably supported within the

frame **43400**, and a lifter spring **43510** comprising a proximal end **43511** mounted to the frame **43400**. The wedge **43520** comprises a ramp **43521** on which a distal end **43512** of the lifter spring **43510** rests. When a staple cartridge is inserted into the cartridge channel **43300**, the staple cartridge **43200** pushes the wedge **43520** proximally. Proximal movement of the wedge **43520** causes the lifter spring **43510** to lift the firing member **43120** to defeat a first stage of the lockout. The lifter spring **43510** comprises a notch **43513** defined on the distal end **43512** configured to engage lifter pins **43125** extending laterally from the firing member **43120** when the lifter spring **43510** is lifted by the wedge **43520** of the staple cartridge **43200**.

[0735] Once the first stage of the lockout has been overcome, the firing assembly **43100** is advanced distally to assess the second stage of the lockout. This second stage of the lockout is defeated when the sled of the staple cartridge **43200** is in its proximal unfired position. Similar to the above, the firing shaft **43110** can be lifted onto the sled by the staple cartridge **43200** as the firing shaft **43110** is advanced distally.

[0736] To cause the nose **43124** of the firing member **43120** to land on an unfired sled of the staple cartridge **43200** to defeat the second stage of the lockout and prevent the firing member **43120** from falling into the lockout recess, a cartridge body key **43211** is provided on a proximal end **43201** of the cartridge body **43210**. Referring now to FIG. 164, as the staple cartridge **43200** is installed in the cartridge channel **43300**, the cartridge body key **43211** pushes the wedge **43520** proximally and overcomes the spring bias provided by the spring **43530**. As the wedge **43520** is pushed proximally, the wedge **43520** lifts the lifter spring **43510**. At this point, the notch **43513** can grab the lifter pins **43125** and lift the firing assembly **43100**. Lifting the firing assembly **43100** in this manner can be referred to as defeating the first stage of the lockout. Notably, a staple cartridge without the proper cartridge lockout key may be able to be installed in the cartridge channel **43300** but will not be able to lift the firing assembly **43100**. Once the staple cartridge **43200** is installed in the cartridge channel **43300** and the firing assembly **43100** is lifted, the firing assembly **43100** can be advanced distally such that the notch **43513** can hold the firing assembly **43100** at the proper height and for the proper distance so that the nose **43124** can land on the unfired sled in the staple cartridge **43200** thereby avoiding the lockout recess. Landing the nose **43124** on the unfired sled can be referred to as defeating the second stage of the lockout. If the sled in the staple cartridge **43200** is not in its unfired position, the firing assembly **43100** will fall into the lockout recess and not be able to be advanced distally beyond its locked configuration. In at least one instance, the cartridge body key **43211** extends proximally from a cartridge body pan **43220** of the staple cartridge **43200**.

[0737] FIG. 165 depicts a first staple cartridge **43610** comprising a proximal end **43611** and a lockout key **43613** extending from the proximal end **43611**. The lockout key **43613** comprises a first profile. FIG. 165 depicts a second staple cartridge **43620** comprising a proximal end **43621** and a lockout key **43623** extending from the proximal end **43621**. The lockout key **43623** comprises a second profile that is different than the first profile of the lockout key **43613**. The first staple cartridge **43610** is configured to unlock only the stapling instruments it is compatible with

and the second staple cartridge **43620** is configured to unlock only the stapling instruments it is compatible with.

[0738] Referring back to the lockout key mechanism **43500** in FIGS. **163** and **164**, cartridges using different key profiles can be used to ensure that the firing member is lifted at the appropriate location and with the appropriate height. Lifting the firing member at different locations, referring to FIG. **165**, causes different lift timings of the firing member. This can be used to ensure that an improper staple cartridge can not unlock a non-compatible instrument. FIGS. **166** and **167** contain graphs illustrating the different lift timings **43610'**, **43620'** and displacements **43610"**, **43620"** provided by the cartridges **43610**, **43620**. The staple cartridge **43610** is configured to lift the firing member earlier than the staple cartridge **43620**. In a compatible surgical instrument, the first staple cartridge **43610** will cause a wedge, for example, such as the wedge described herein, to lift the firing member at the appropriate time and location such that the firing member will land on an unfired sled of the first staple cartridge **43610** so as to defeat the lockout and enable the firing member to be advanced distally to perform a staple firing stroke. In an incompatible surgical instrument, the first staple cartridge **43610** will cause a wedge, for example, to lift the firing member at the incorrect time and location causing the firing member to fall before reaching the sled or causing the firing member to bump the sled distally before being lifted onto the sled. Both situations involving installing an incompatible cartridge and instrument will cause the firing member to enter a locked out condition upon an attempt to move the firing member through a firing stroke. The second staple cartridge **43620** works in a similar manner. That said, the second staple cartridge **43620** cannot unlock an instrument compatible with the first staple cartridge **43610**, and vice versa.

[0739] FIGS. **168** and **169** depict a system **44000** comprising a first cartridge **44100** (FIG. **168**) and a second cartridge **44200** (FIG. **169**). The first staple cartridge **44100** comprises a cartridge body **44110** comprising a proximal end **44111**, a distal end **44112**, and a plurality of staple cavities **44114** arranged in rows extending between the proximal end **44111** and the distal end **44112**. The first staple cartridge **44100** further comprises a cartridge pan **44130** configured to hold staples in the cartridge body **44110**, and a sled **44120** configured to deploy the staples from the cartridge body **44110**. The cartridge body **44110** further comprises a longitudinal slot **44113** defined therein configured to receive a firing member of a surgical stapling assembly. The longitudinal slot **44113** defines a first lateral side and a second lateral side labeled "A" and "B" respectively. The cartridge body **44110** further comprises a lockout key **44116** extending from a proximal face **44115** of the first lateral side "A" of the cartridge body **44110**.

[0740] The second staple cartridge **44200** comprises a cartridge body **44210** comprising a proximal end **44211**, a distal end **44212**, and a plurality of staple cavities **44214** arranged in rows extending between the proximal end **44211** and the distal end **44212**. The second staple cartridge **44200** further comprises a cartridge pan **44230** configured to hold staples in the cartridge body **44210**, and a sled **44220** configured to deploy the staples from the cartridge body **44210**. The cartridge body **44210** further comprises a longitudinal slot **44213** defined therein configured to receive a firing member of a surgical stapling assembly. The longitudinal slot **44213** defines a first lateral side and a second

lateral side labeled "A" and "B" respectively. The cartridge body **44210** further comprises a lockout key **44216** extending from a proximal face **44215** of the second lateral side "B" of the cartridge body **44210**.

[0741] The staple cavities **44114** comprise three rows on each side of the longitudinal slot **44113**. Each row defines a row axis with which each staple cavity in that row is aligned. In other words, the proximal end and the distal end of each cavity in a single row is aligned with the row axis of that row. The staple cavities **44214** comprise three rows on each side of the longitudinal slot **44213**. Each row defines a row axis with which each staple cavity in that row is transversely aligned. Each side of the staple cartridge **44200** comprises an outer row of staple cavities **44214**, an inner row of staple cavities **44214**, and a middle row of staple cavities **44214** positioned between the outer row of staple cavities **44214** and the inner row of staple cavities **44214**. The staple cavities **44214** of the middle row define cavity axes that are transverse to cavity axes defined by the staple cavities **44214** in the inner row and the staple cavities **44214** in the outer row.

[0742] The system **44000** provides a way to prevent an improper staple cartridge from being used with a surgical stapling assembly by providing the lockout keys of each cartridge on different sides of the staple cartridge. Providing the lockout keys on different sides of the staple cartridge prevents the use of a stapling assembly comprising corresponding staple-forming pockets for the first staple cartridge **44100** with the second staple cartridge **44200** and the use of a stapling assembly comprising corresponding staple-forming pockets for the second staple cartridge **44200** with the first staple cartridge **44100**. Thus, the first staple cartridge **44100** will not be able to unlock a firing lockout of a surgical stapling assembly meant for the second staple cartridge **44200** and the second staple cartridge **44200** will not be able to unlock a firing lockout of a surgical stapling assembly meant for the first staple cartridge **44100**. This prevents improper cartridge installation which may result in deploying staples against an anvil with non-corresponding staple-forming pockets.

[0743] FIGS. **170-179** depict a surgical stapling assembly **45000** configured to clamp, staple, and cut the tissue of a patient. The surgical stapling assembly **45000** can be used with a surgical robot and/or a surgical instrument handle. The surgical stapling assembly **45000** comprises a first jaw **45200**, a second jaw **45400** movable relative to the first jaw **45200** between an unclamped configuration and a clamped configuration, and a firing assembly **45500**. The surgical stapling assembly **45000** further comprises a replaceable staple cartridge **45300** comprising a plurality of staples removably stored therein which are configured to be deployed by the firing assembly **45500**. The first jaw **45200** comprises a channel **45210** configured to receive the replaceable staple cartridge **45300**. The second jaw **45400** comprises an anvil **45410** comprising a staple-forming surface **45415** configured to form the staples deployed from the staple cartridge **45300**. The first jaw **45200** further comprises pin apertures **45212** (FIG. **171**) in which pivot pins **45413** of the second jaw **45400** are received to permit the second jaw **45400** to pivot relative to the first jaw **45200**. Embodiments are envisioned where the fixed jaw comprises the anvil and the movable jaw comprises the channel and the staple cartridge.

[0744] To clamp tissue with the surgical stapling assembly 45000, the second jaw 45400 comprises a camming surface 45412 formed on a proximal end 45411 thereof which is configured to be engaged by a closure member. The closure member comprises a closure tube, for example, but can comprise any other suitable configuration. The closure member is configured to cam the second jaw 45400 from the unclamped configuration to the clamped configuration toward the channel 45210 by engaging and sliding along the camming surface 45412. To unclamp the surgical stapling assembly 45000, the closure member is retracted proximally. A spring may be provided to bias the second jaw 45400 into the unclamped configuration as the closure member disengages the camming surface 45412.

[0745] To staple and cut tissue with the surgical stapling assembly 45000, a proper unspent staple cartridge must be installed within the surgical stapling assembly 45000. When a proper unspent staple cartridge is installed within the channel 45210, the firing assembly 45500 can be actuated through the staple cartridge 45300 to push a sled 45340 of the staple cartridge 45300 distally from an unfired position to a fired position to deploy the staples stored within the staple cartridge 45300 during a staple firing stroke. As the firing assembly 45500 is moved through the staple firing stroke, a cutting edge 45523 of the firing assembly cuts the tissue clamped between the first jaw 45200 and the second jaw 45400. In at least one instance, the cutting edge 45523 trails behind the staple deployment to prevent tissue from being cut before the tissue is stapled.

[0746] Referring primarily to FIGS. 172-175, the firing assembly 45500 comprises a firing member 45520 comprising the cutting edge 45523, anvil-camming portions 45521 and channel-camming portions 45522 configured to control the distance between the first jaw 45200 and the second jaw 45400 during the staple firing stroke, and laterally-extending portions 45525 positioned between the anvil-camming portions 45521 and the channel-camming portions 45522 configured to fall into a lockout as discussed in greater detail below. The firing member 45520 further comprises a tail 45526 extending proximally therefrom which is configured to interface with a spring 45240 mounted in the shaft as discussed in greater detail below.

[0747] To prevent the firing assembly 45500 from being advanced through an improper and/or spent staple cartridge, the surgical stapling assembly 45000 further comprises a lockout system. The surgical stapling assembly 45000 comprises a diving-knife lockout such as those disclosed herein where the firing assembly 45500 falls into a lockout pocket if a proper unspent staple cartridge is not installed within the surgical stapling assembly 45000. A proper unspent staple cartridge, such as the staple cartridge 45300, is configured to prevent the firing assembly 45500 from falling into the lockout pocket by lifting the firing assembly 45500 when the staple cartridge 45300 is unspent. In such instances, a distal end of the firing assembly will land on an unfired sled of the staple cartridge 45300. The firing assembly 45500 may then be advanced through the staple cartridge 45300.

[0748] The staple cartridge 45300 includes a lockout key 45330 to lift the firing assembly 45500 to the proper height and proper distance to get the firing assembly 45500 to land on an unfired sled and defeat the lockout of the surgical stapling assembly 45000. The staple cartridge 45300 further comprises a cartridge body 45310 comprising a proximal end 45301 comprising a proximal face 45313 and a longi-

tudinal slot 45311 configured to receive the firing assembly 45500 during the staple firing stroke. The lockout key 45330 extends proximally from the proximal face 45313 of the cartridge body 45310 and comprises a pair of protrusions defining a proximal longitudinal slot portion 45333 of the longitudinal slot 45311. The proximal longitudinal slot portion 45333 is configured to straddle the firing member 45520 when the staple cartridge 45300 is installed in the channel 45210. Each protrusion of the lockout key 45330 comprises a ramped surface, or portion, 45331 and a non-ramped portion, or surface, 45332. The staple cartridge 45300 further comprises a pan 45320 configured to hold the staples within the cartridge body 45310. The pan 45320 is configured to clip onto a deck 45312 of the cartridge body 45310. The pan 45320 may be removably affixed to the cartridge body 45310 by a series of hooks 45321 that are formed on the sidewalls of the cartridge pan 45320 and configured to hookingly engage corresponding portions of the cartridge body 45310. In at least one instance, the pan can comprise the lockout key.

[0749] The firing assembly 45500 comprises a firing shaft 45510 configured to transfer firing motions to the firing member 45520. The firing member 45520 is attached to a distal end 45513 of the firing shaft 45510. The firing member 45520 is biased downwardly by the spring 45420 mounted in the shaft. More specifically, the spring 45420 pushes the tail 45526 of the firing member 45520 downwardly to bias the firing member 45520 unless the firing member 45520 is lifted upwardly away from the firing lockout. To lift the firing assembly 45500, the surgical stapling assembly 45000 comprises a floating pin 45600 positioned behind the firing member 45520 of the firing assembly 45500. The floating pin 45600 is supported within a slot, or channel, 45213 defined in the sides of the staple cartridge channel 45210. The floating pin 45600 is configured to move vertically within the slot 45213 by the ramped surfaces 45331. More specifically, the floating pin 45600 is pushed upwardly by the lockout key 45330 into the staple cartridge channel 45210 which, in turn, contacts the bottom edge of the firing member 45520 and pushes the firing member 45520 upwardly. Thus, the floating pin 45600 keeps the firing member 45520 from diving into the firing lockout when the staple cartridge 45300 is seated in the staple cartridge channel 45210. As such, the lockout key 45330 overcomes the downward spring bias applied to the firing member 45520 by the spring 45240.

[0750] Once the staple cartridge 45300 is fully installed and the firing assembly 45500 is lifted to the position illustrated in FIG. 174, the firing assembly 45500 can then be advanced distally toward the sled 45340 of the staple cartridge 45300. Thus, with the proper lockout key, the first stage of the lockout is defeated. If the sled 45340 is in its unfired position, a distal nose, or shelf, 45524 of the firing member 45520 will land on a corresponding platform 45341 of the sled 45340 and avoid the lockout discussed above. Landing the distal nose 45524 of the firing member 45520 on the platform 45341 of the sled 45340 when the sled 45340 is in its unfired position defeats a second stage of the lockout. As the firing assembly 45500 is advanced distally, the bottom surface 45511 rides over the floating pin 45600 and the height of the firing assembly 45500 is governed by the engagement between the floating pin 45600, the bottom surface 45511 of the firing shaft 45510, and the lockout key 45600.

[0751] Because the height of the firing assembly 45500 is governed by the engagement between the floating pin 45600, the bottom surface 45511 of the firing shaft 45510, and the lockout key 45600, the firing shaft 45510 is configured such that the firing assembly 45500 may still fall into the lockout when the sled 45340 of the staple cartridge 45300 is not in its unfired position. Referring to FIGS. 176 and 177, the bottom surface 45511 comprises a notch 45515 defined proximal to the distal end 45513 of the firing shaft 45510. The notch 45515 is configured such that the firing shaft 45510 will fall into the lockout if the sled 45340 is not present in its unfired position. FIG. 176 illustrates the staple cartridge 45300 installed within the channel 45210; however, the sled 45340 is not present in its unfired position. Thus, turning to FIG. 177, the firing shaft 45510 is not sufficiently lifted upwardly by the floating pin 45600 to lift the firing shaft 45510 out of the lockout. Instead, the firing shaft 45510 is pulled down by the spring 45240 as the firing assembly 45500 is advanced distally owing to the floating pin 45600 fitting in the notch 45515. To perform a staple firing stroke, the improper cartridge must be removed and replaced with a proper unfired staple cartridge.

[0752] If a staple cartridge is installed in the surgical stapling assembly that does not have a proper lockout key, the floating pin 45600 will remain in its lower most position illustrated in FIG. 172. If an attempt is made to advance the firing assembly 45500 distally, the firing assembly 45500 will be unable to overcome the first stage of the lockout.

[0753] FIG. 180 depicts the staple cartridge 45300 discussed above. FIG. 181 depicts a second staple cartridge 45900 comprising a cartridge body 45910 and a pan 45920 configured to hold a plurality of staples in the staple cartridge 45900. The cartridge body 45910 further comprises a lockout key 45930 extending proximally from a proximal face 45913 of the cartridge body 45910. As can be seen from FIGS. 180 and 181, the staple cartridge 45300 and the second staple cartridge 45900 comprise similar features; however, they comprise lockout keys having different configurations. The lockout key 45330 of the staple cartridge 45300 comprises a first length 45338 and a first height 45339 while the lockout key 45930 of the second staple cartridge 45900 comprises a second length 45938 and a second height 45939 which are different than the first length 45338 and the first height 45339, respectively. The staple cartridges 45300, 45900 are part of a system in which the staple cartridge 45300 can only unlock a first instrument but not a second instrument while the second staple cartridge 45900 can only unlock the second instrument and not the first instrument. The lockout key 45930 comprises a ramped surface 45931 and a flat surface 45932 which have different dimensions than the surfaces 45331, 45332 of the lockout key 45330. The lockout key 45330 of the staple cartridge 45300 is shown in phantom lines in FIG. 181 for comparison purposes.

[0754] Differing lockout key configurations between similar looking cartridges, for example, can prevent a clinician from inserting and using an incompatible cartridge in a second instrument. In this instance, the lockout keys 45330, 45930 will cause a firing assembly of an instrument to lift to different heights and at different times during the firing stroke of the firing assembly. Referring back to the floating pin 45600, if the second staple cartridge 45900 is installed in the surgical stapling assembly 45000, the firing assembly 45500 will be lifted by the floating pin 45600 at a height

which is less than a height at which the firing assembly 45500 will be lifted by the floating pin 45600 if the staple cartridge 45300 is installed. This will cause the firing assembly 45500 to not be able to land on the sled platform of the second staple cartridge and, instead, will become locked out. This will prevent the use of an improper staple cartridge within a stapling instrument.

[0755] The instrument with which the second staple cartridge 45900 may be used can comprise a similar floating pin system as discussed above; however, this floating pin may be located in a different position relative to the second staple cartridge 45900 such that the lockout key 45930 can lift the firing member of this instrument to the appropriate height and at the appropriate time to land on the sled of the second staple cartridge 45900 to bypass the lockout of the instrument. In at least one instance, the lockout keys described herein comprise cartridge body fins, for example.

[0756] Various aspects of the subject matter described herein are set out in the following examples.

[0757] Example 1—A surgical stapling instrument configured for use with a surgical staple cartridge containing a plurality of surgical staples configured to be ejected therefrom by a camming assembly supported therein as the camming assembly is moved from an unfired position therein to a fired position. The surgical stapling instrument comprising a first jaw configured to removably support the surgical staple cartridge therein, a second jaw movable relative to the first jaw between an open position and a closed position, a firing member configured to axially move between a starting position and an ending position upon application of a firing motion thereto, a firing member lockout, and a cartridge verification member. The firing member lockout is configured to interface with the camming assembly of the surgical staple cartridge supported in the first jaw. The firing member lockout is further configured to prevent the firing member from moving out of the starting position upon application of the firing motion to the firing member unless the camming assembly is in the unfired position within the surgical staple cartridge. The cartridge verification member is configured to move the camming assembly out of the unfired position to an intermediate position unless the cartridge verification member detects a verification feature on the surgical staple cartridge.

[0758] Example 2—The surgical stapling instrument of Example 1, wherein the cartridge verification member is coupled to the second jaw.

[0759] Example 3—The surgical stapling instrument of Examples 1 or 2, wherein the cartridge verification member is configured to detect the verification feature when the second jaw is moved to the closed position.

[0760] Example 4—The surgical stapling instrument of Examples 1, 2, or 3, wherein the verification feature protrudes from a proximal end of the surgical staple cartridge.

[0761] Example 5—The surgical stapling instrument of Examples 1, 2, 3, or 4, wherein the cartridge verification member comprises a compliant portion configured to interact with the camming assembly and the verification feature.

[0762] Example 6—The surgical stapling instrument of Examples 1, 2, 3, 4, or 5, wherein the surgical staple cartridge comprises a cartridge body and wherein the verification feature comprises a cartridge body extension extending proximally from a proximal end of the cartridge body.

[0763] Example 7—The surgical stapling instrument of Examples 1, 2, 3, 4, 5, or 6, wherein the cartridge verification member is movably supported within the first jaw and is configured to move between an actuated position wherein the cartridge verification member is configured to move the camming assembly from the unfired position to the intermediate position and a cartridge verification position.

[0764] Example 8—The surgical stapling instrument of Example 7, further comprising a verification biaser for biasing the cartridge verification member into the actuated position unless the cartridge verification member is contacted by the verification feature of the cartridge to move the surgical staple cartridge verification member to the cartridge verification position.

[0765] Example 9—The surgical stapling instrument of Examples 1, 2, 3, 4, 5, 6, 7, or 8, wherein the camming assembly includes a plurality of cam members and wherein the cartridge verification member comprises a plurality of displacement arms corresponding to at least two of the cam members.

[0766] Example 10—The surgical stapling instrument of Examples 1, 2, 3, 4, 5, 6, 7, 8, or 9, wherein the surgical staple cartridge comprises four verification members.

[0767] Example 11—The surgical stapling instrument of Examples 1, 2, 3, 4, 5, 6, 7, 8, 9, or 10, wherein the cartridge verification member has at least one primary verification surface thereon configured to interface with a corresponding secondary verification surface on the verification feature to facilitate operable seating of the staple cartridge in the first jaw.

[0768] Example 12—A surgical stapling instrument configured for use with a surgical staple cartridge containing a plurality of surgical staples configured to be ejected therefrom by a camming assembly supported therein as the camming assembly is moved from an unfired position therein to a fired position. The surgical stapling instrument comprising a channel configured to removably support the surgical staple cartridge therein, an anvil movable relative to the channel between an open position and a closed position, a firing member configured to axially move between a starting position and an ending position upon application of a firing motion thereto, a firing member lockout, and a cartridge verification member. The firing member lockout is movable between a locked position wherein the firing member lockout prevents the firing member from moving from the starting position upon application of the firing motion thereto and an unlocked position wherein the firing member is permitted to move from the starting position to the ending position upon the application of the firing motion thereto. The firing member lockout comprising a latch portion configured to unlockingly engage an unlocking portion of the camming assembly when the camming assembly is in the unfired position to move the firing member lockout from the locked position to the unlocked position. The cartridge verification member is movably supported in the channel and configured to move the camming assembly out of the unfired position and out of unlocking engagement with the latch portion of the firing member to an intermediate position unless the cartridge verification member detects a verification feature on the surgical staple cartridge.

[0769] Example 13—The surgical stapling instrument of Example 12, wherein the surgical staple cartridge comprises a cartridge body and wherein the verification feature com-

prises a cartridge body extension extending proximally from a proximal end of the cartridge body.

[0770] Example 14—The surgical stapling instrument of Examples 12 or 13, wherein the cartridge verification member is movable within the channel between an actuated position wherein the cartridge verification member moves the camming assembly from the unfired position to the intermediate position and a cartridge verification position.

[0771] Example 15—The surgical stapling instrument of Example 14, further comprising a verification biaser for biasing the cartridge verification member into the actuated position unless the cartridge verification member is contacted by the verification feature of the surgical staple cartridge to move the cartridge verification member to the cartridge verification position.

[0772] Example 16—A surgical staple cartridge configured to be installed in a surgical stapling instrument. The surgical stapling instrument includes a firing member, a firing member lockout, and a cartridge verification member. The surgical staple cartridge comprises a cartridge body, a plurality of staples removably stored within the cartridge body, a camming assembly, and at least one verification feature. The cartridge body is configured to be operably supported in the surgical stapling instrument and comprises a proximal end, a distal end, and a cartridge slot extending from the proximal end to the distal end to accommodate axial passage of the firing member therethrough. The camming assembly is configured to deploy the staples from the cartridge body as the camming assembly moves from an unfired position adjacent the proximal end of the cartridge body to a fired position. The camming assembly is further configured to move the firing member lockout from a locked position wherein the firing member cannot be moved distally through the cartridge body to an unlocked position wherein the firing member may be axially moved through the cartridge body. The at least one verification feature is configured to operably interface with the cartridge verification member such that when the cartridge body is operably supported in the surgical stapling instrument, the verification feature prevents the cartridge verification member from moving the camming assembly from the unfired position to an intermediate position wherein the camming assembly disengages from the firing member lockout to permit the firing member lockout to be biased into the locked position to prevent the firing member from being moved distally through the cartridge body upon application of a firing motion to the firing member.

[0773] Example 17—The surgical staple cartridge of Example 16, wherein the at least one verification feature comprises at least one cartridge body extension extending proximally from the proximal end of the cartridge body and in actuation alignment with a corresponding portion of the cartridge verification member.

[0774] Example 18—The surgical staple cartridge of Example 16, wherein the at least one verification feature comprises four cartridge body extensions extending proximally from the proximal end of the cartridge body wherein each cartridge body extension is in actuation alignment with a corresponding portion of the cartridge verification member.

[0775] Example 19—The surgical staple cartridge of Examples 16, 17, or 18, wherein the camming assembly further comprises a camming assembly body supported in the cartridge slot for axial travel therein and at least one cam

member on each lateral side of the camming assembly body and movably supported in a corresponding cam member axial slot in the cartridge body on each side of the cartridge slot and wherein the cartridge verification member comprises an actuator arm corresponding to each cam member axial slot and configured to extend therein.

[0776] Example 20—The surgical staple cartridge of Examples 16, 17, 18, or 19, wherein the at least one verification feature comprises at least one secondary verification surface thereon configured to interface with a corresponding primary surface on the cartridge verification member to facilitate operable seating of the surgical staple cartridge in the surgical stapling instrument.

[0777] Example 21—A surgical stapling assembly configured to receive any of the staple cartridges selected from the group of staple cartridges comprising a compatible staple cartridge and an incompatible staple cartridge. The compatible staple cartridge comprises a cartridge body comprising a longitudinal slot, a plurality of staples stored within the cartridge body, a camming assembly configured to eject the staples from the cartridge body, and a cartridge verification feature. The camming assembly is movable between an unfired position and a fired position. The incompatible staple cartridge comprises another cartridge body comprising another longitudinal slot, another plurality of other staples stored within the another cartridge body, and another camming assembly configured to eject the other staples from the another cartridge body. The another camming assembly is movable between an another unfired position and another fired position. The surgical stapling assembly comprises a first jaw configured to operably support any one of the group of staple cartridges therein, a second jaw movable relative to the first jaw, a firing member configured to axially move between a starting position and an ending position upon application of a firing motion thereto, a firing member lockout, and a cartridge verification member. The firing member lockout is movable from a first locked position wherein the firing member lockout prevents the firing member from moving out of the starting position to an unlocked position wherein the firing member is distally movable from the starting position upon application of the firing motion to the firing member. Upon installation of the compatible cartridge into the first jaw with the camming assembly thereof in the unfired position, the camming assembly engages the firing member lockout to move the firing member lockout to the unlocked position. Upon installation of the incompatible staple cartridge in the first jaw with the another camming assembly thereof in the another unfired position, the another camming assembly is configured to engage the firing member lockout to move the firing member lockout to the unlocked position. When the incompatible staple cartridge is installed in the first jaw, the cartridge verification member moves the another camming assembly out of engagement with the firing member lockout to permit the firing member lockout to be biased into the locked position by a firing member spring. When the compatible cartridge is installed in the first jaw, the cartridge verification feature thereon prevents the cartridge verification member from moving the camming assembly thereof out of engagement with the firing member lockout.

[0778] Many of the surgical instrument systems described herein are motivated by an electric motor; however, the surgical instrument systems described herein can be motivated in any suitable manner. In various instances, the

surgical instrument systems described herein can be motivated by a manually-operated trigger, for example. In certain instances, the motors disclosed herein may comprise a portion or portions of a robotically controlled system. Moreover, any of the end effectors and/or tool assemblies disclosed herein can be utilized with a robotic surgical instrument system. U.S. patent application Ser. No. 13/118,241, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, now U.S. Pat. No. 9,072,535, for example, discloses several examples of a robotic surgical instrument system in greater detail.

[0779] The surgical instrument systems described herein have been described in connection with the deployment and deformation of staples; however, the embodiments described herein are not so limited. Various embodiments are envisioned which deploy fasteners other than staples, such as clamps or tacks, for example. Moreover, various embodiments are envisioned which utilize any suitable means for sealing tissue. For instance, an end effector in accordance with various embodiments can comprise electrodes configured to heat and seal the tissue. Also, for instance, an end effector in accordance with certain embodiments can apply vibrational energy to seal the tissue.

[0780] The entire disclosures of:

[0781] U.S. Pat. No. 5,403,312, entitled ELECTROSURGICAL HEMOSTATIC DEVICE, which issued on Apr. 4, 1995;

[0782] U.S. Pat. No. 7,000,818, entitled SURGICAL STAPLING INSTRUMENT HAVING SEPARATE DISTINCT CLOSING AND FIRING SYSTEMS, which issued on Feb. 21, 2006;

[0783] U.S. Pat. No. 7,422,139, entitled MOTOR-DRIVEN SURGICAL CUTTING AND FASTENING INSTRUMENT WITH TACTILE POSITION FEEDBACK, which issued on Sep. 9, 2008;

[0784] U.S. Pat. No. 7,464,849, entitled ELECTRO-MECHANICAL SURGICAL INSTRUMENT WITH CLOSURE SYSTEM AND ANVIL ALIGNMENT COMPONENTS, which issued on Dec. 16, 2008;

[0785] U.S. Pat. No. 7,670,334, entitled SURGICAL INSTRUMENT HAVING AN ARTICULATING END EFFECTOR, which issued on Mar. 2, 2010;

[0786] U.S. Pat. No. 7,753,245, entitled SURGICAL STAPLING INSTRUMENTS, which issued on Jul. 13, 2010;

[0787] U.S. Pat. No. 8,393,514, entitled SELECTIVELY ORIENTABLE IMPLANTABLE FASTENER CARTRIDGE, which issued on Mar. 12, 2013;

[0788] U.S. patent application Ser. No. 11/343,803, entitled SURGICAL INSTRUMENT HAVING RECORDING CAPABILITIES, now U.S. Pat. No. 7,845,537;

[0789] U.S. patent application Ser. No. 12/031,573, entitled SURGICAL CUTTING AND FASTENING INSTRUMENT HAVING RF ELECTRODES, filed Feb. 14, 2008;

[0790] U.S. patent application Ser. No. 12/031,873, entitled END EFFECTORS FOR A SURGICAL CUTTING AND STAPLING INSTRUMENT, filed Feb. 15, 2008, now U.S. Pat. No. 7,980,443;

[0791] U.S. patent application Ser. No. 12/235,782, entitled MOTOR-DRIVEN SURGICAL CUTTING INSTRUMENT, now U.S. Pat. No. 8,210,411;

[0792] U.S. patent application Ser. No. 12/235,972, entitled MOTORIZED SURGICAL INSTRUMENT, now U.S. Pat. No. 9,050,083.

[0793] U.S. patent application Ser. No. 12/249,117, entitled POWERED SURGICAL CUTTING AND STAPLING APPARATUS WITH MANUALLY RETRACTABLE FIRING SYSTEM, now U.S. Pat. No. 8,608,045;

[0794] U.S. patent application Ser. No. 12/647,100, entitled MOTOR-DRIVEN SURGICAL CUTTING INSTRUMENT WITH ELECTRIC ACTUATOR DIRECTIONAL CONTROL ASSEMBLY, filed Dec. 24, 2009, now U.S. Pat. No. 8,220,688;

[0795] U.S. patent application Ser. No. 12/893,461, entitled STAPLE CARTRIDGE, filed Sep. 29, 2012, now U.S. Pat. No. 8,733,613;

[0796] U.S. patent application Ser. No. 13/036,647, entitled SURGICAL STAPLING INSTRUMENT, filed Feb. 28, 2011, now U.S. Pat. No. 8,561,870;

[0797] U.S. patent application Ser. No. 13/118,241, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, now U.S. Pat. No. 9,072,535;

[0798] U.S. patent application Ser. No. 13/524,049, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING A FIRING DRIVE, filed on Jun. 15, 2012, now U.S. Pat. No. 9,101,358;

[0799] U.S. patent application Ser. No. 13/800,025, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, filed on Mar. 13, 2013, now U.S. Pat. No. 9,345,481;

[0800] U.S. patent application Ser. No. 13/800,067, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, filed on Mar. 13, 2013, now U.S. Patent Application Publication No. 2014/0263552;

[0801] U.S. Patent Application Publication No. 2007/0175955, entitled SURGICAL CUTTING AND FASTENING INSTRUMENT WITH CLOSURE TRIGGER LOCKING MECHANISM, filed Jan. 31, 2006; and

[0802] U.S. Patent Application Publication No. 2010/0264194, entitled SURGICAL STAPLING INSTRUMENT WITH AN ARTICULATABLE END EFFECTOR, filed Apr. 22, 2010, now U.S. Pat. No. 8,308,040, are hereby incorporated by reference herein.

[0803] Although various devices have been described herein in connection with certain embodiments, modifications and variations to those embodiments may be implemented. Particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Thus, the particular features, structures, or characteristics illustrated or described in connection with one embodiment may be combined in whole or in part, with the features, structures or characteristics of one or more other embodiments without limitation. Also, where materials are disclosed for certain components, other materials may be used. Furthermore, according to various embodiments, a single component may be replaced by multiple components, and multiple components may be replaced by a single component, to perform a given function or functions. The foregoing description and following claims are intended to cover all such modification and variations.

[0804] The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, a device can be reconditioned for reuse after at least one use. Reconditioning

can include any combination of the steps including, but not limited to, the disassembly of the device, followed by cleaning or replacement of particular pieces of the device, and subsequent reassembly of the device. In particular, a reconditioning facility and/or surgical team can disassemble a device and, after cleaning and/or replacing particular parts of the device, the device can be reassembled for subsequent use. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

[0805] The devices disclosed herein may be processed before surgery. First, a new or used instrument may be obtained and, when necessary, cleaned. The instrument may then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK bag. The container and instrument may then be placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, and/or high-energy electrons. The radiation may kill bacteria on the instrument and in the container. The sterilized instrument may then be stored in the sterile container. The sealed container may keep the instrument sterile until it is opened in a medical facility. A device may also be sterilized using any other technique known in the art, including but not limited to beta radiation, gamma radiation, ethylene oxide, plasma peroxide, and/or steam.

[0806] While this invention has been described as having exemplary designs, the present invention may be further modified within the spirit and scope of the disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles.

1-21. (canceled)

22. A surgical end effector, comprising:

- a first jaw configured to operably support a staple cartridge therein;
- a second jaw supported relative to said first jaw for movement between an open position and a closed position about a jaw axis;
- a firing member movable between a beginning position and an ending position in said surgical end effector;
- a firing member lock system configured to distinguish between an unfired compatible cartridge, a fired compatible cartridge, and an incompatible cartridge, wherein said firing member lock system is configured to prevent said firing member from moving from said beginning position to said ending position when one of said fired compatible cartridge and said incompatible cartridge is seated in said first jaw, and wherein said firing member lock system is configured to permit said firing member to move from said beginning position to said ending position when said unfired compatible cartridge is seated in said first jaw; and
- a closure lock laterally movable in an unblocking direction that is parallel to the jaw axis between a blocking position in which said closure lock blocks said second jaw from moving from said open position to said closed position and an unblocking position in which said second jaw is permitted to move from said open position to said closed position when one of said unfired compatible cartridge and said fired compatible cartridge is seated in said first jaw, and wherein said

closure lock is retained in said blocking position when said incompatible cartridge is seated in said first jaw.

23. The surgical end effector of claim **22**, wherein said unfired compatible cartridge comprises:

- a compatible cartridge body configured to be seated in said first jaw, wherein said compatible cartridge body comprises a compatible proximal end and a compatible distal end;
- a plurality of surgical staples stored in said compatible cartridge body;
- a camming member in an unfired position and configured to eject said surgical staples from said compatible cartridge body when said camming member is distally moved from said unfired position; and
- a closure unlocking feature protruding from said compatible proximal end of said compatible cartridge body, wherein said closure unlocking feature is configured to laterally move said closure lock from said blocking position to said unblocking position when said unfired compatible cartridge is seated in said first jaw.

24. The surgical end effector of claim **23**, wherein said fired compatible cartridge comprises another compatible cartridge body configured to be seated in said first jaw, wherein said another compatible cartridge body comprises another compatible proximal end and another compatible distal end;

- another camming member supported in said another compatible cartridge body in a fired position; and
- another closure unlocking feature protruding from said another compatible proximal end, wherein said another closure unlocking feature is configured to laterally move said closure lock from said blocking position to said unblocking position when said fired compatible cartridge is seated in said first jaw.

25. The surgical end effector of claim **24** wherein said incompatible cartridge comprises a cartridge body configured to be seated in said first jaw, wherein said cartridge body lacks means for moving said closure lock from said blocking position to said unblocking position when said cartridge body is seated in said first jaw.

26. The surgical end effector of claim **23**, wherein said firing member lock system comprises a lock latch pivotally coupled to said firing member, wherein said lock latch is movable between a locked position in which said firing member is prevented from moving distally from said beginning position, and an unlocked position in which said firing member is distally movable from said beginning position, and wherein said camming member is configured to move said lock latch from said locked position to said unlocked position when said camming member is in said unfired position.

27. The surgical end effector of claim **26**, wherein said firing member lock system further comprises a lock member, wherein said lock member is laterally movable between another locked position in which said lock member retains said firing member in said beginning position and another unlocked position, wherein said unfired compatible cartridge further comprises a firing system unlocking feature protruding from said compatible proximal end, wherein said firing system unlocking feature is configured to laterally move said lock member from said another locked position to said another unlocked position when said unfired compatible cartridge is seated in said first jaw, and wherein said fired compatible cartridge further comprises another firing system

unlocking feature protruding from said another compatible proximal end, wherein said another firing system unlocking feature is configured to laterally move said lock member from said another locked position to said another unlocked position when said fired compatible cartridge is seated in said first jaw.

28. A surgical end effector, comprising:

- a first jaw configured to operably support a surgical cartridge therein;
- a second jaw supported relative to said first jaw for movement between an open position and a closed position, wherein said second jaw is configured to support a surgical cartridge selected from the group of surgical cartridges consisting of a compatible cartridge, an unfired compatible cartridge, a fired compatible cartridge, an unfired incompatible cartridge, and a fired incompatible cartridge;
- a firing member movable between a beginning position and an ending position in said surgical end effector;
- a first firing member lock configured to prevent said firing member from being movable from said beginning position to said ending position unless said unfired compatible cartridge is seated in said first jaw;
- a second firing member lock configured to prevent said firing member from being movable from said beginning position to said ending position unless one of said compatible cartridge, said unfired compatible cartridge, and said fired compatible cartridge is seated in said first jaw; and
- a closure lock laterally movable between a blocking position in which said closure lock blocks said second jaw from moving from said open position to said closed position and an unblocking position in which said second jaw is permitted to move from said open position to said closed position when one of said compatible cartridge, said unfired compatible cartridge, and said fired compatible cartridge is seated in said first jaw.

29. The surgical end effector of claim **28**, wherein said first firing member lock prevents said firing member from being movable from said beginning position when said first firing member lock is in a first locked position, wherein said first firing member lock permits said firing member to move from said beginning position when said first firing member lock is in a first unlocked position, wherein said second firing member lock prevents said firing member from being movable from said beginning position when said second firing member lock is in a second locked position and said second firing member lock permits said firing member to move from said beginning position when said second firing member lock is in a second unlocked position.

30. The surgical end effector of claim **29**, wherein said compatible cartridge comprises:

- a first compatible cartridge body configured to be seated in said first jaw, wherein said first compatible cartridge body comprises a first compatible proximal end and a first compatible distal end;
- a first compatible unlocking feature protruding from said first compatible proximal end and configured to laterally move said second firing member lock from said second locked position to said second unlocked position when said first compatible cartridge body is seated in said first jaw; and

a first compatible closure unlocking feature configured to laterally move said closure lock from said blocking position to said unblocking position when said first compatible cartridge body is seated in said first jaw.

31. The surgical end effector of claim **29**, wherein said unfired compatible cartridge comprises:

- a second compatible cartridge body configured to be seated in said first jaw, wherein said second compatible cartridge body comprises a second compatible proximal end and a second compatible distal end;
- a second compatible unlocking feature protruding from said second compatible proximal end and configured to laterally move said second firing member lock from said second locked position to said second unlocked position when said unfired compatible cartridge is seated in said first jaw;
- a plurality of surgical staples stored in said second compatible cartridge body;
- a camming member movably supported in said second compatible cartridge body in an unactuated position, wherein said camming member is configured to eject said surgical staples from said second compatible cartridge body when said camming member is moved from said unactuated position to an actuated position, and wherein when in said unactuated position, said camming member is configured to move said first firing member lock from said first locked position to said first unlocked position when said unfired compatible cartridge is seated in said first jaw; and
- a second compatible closure unlocking feature configured to laterally move said closure lock from said blocking position to said unblocking position when said unfired compatible cartridge is seated in said first jaw.

32. The surgical end effector of claim **29**, wherein said fired compatible cartridge comprises:

- a third compatible cartridge body configured to be seated in said first jaw, wherein said third compatible cartridge body comprises a third compatible proximal end and a third compatible distal end;
- a third compatible unlocking feature protruding from said third compatible proximal end and configured to laterally move said second firing member lock from said second locked position to said second unlocked position when said fired compatible cartridge is seated in said first jaw;
- a camming member in said third compatible cartridge body in an actuated position in which said camming member is unable to move said first firing member lock from said first locked position; and
- a third compatible closure unlocking feature configured to laterally move said closure lock from said blocking position to said unblocking position when said fired compatible cartridge is seated in said first jaw.

33. The surgical end effector of claim **29**, wherein said unfired incompatible cartridge comprises:

- an incompatible cartridge body configured to be seated in said first jaw, wherein said incompatible cartridge body comprises an incompatible proximal end and an incompatible distal end, wherein said cartridge body lacks at least one of:
 - a feature configured to move said second firing member lock from said second locked position to said second unlocked position when said unfired incompatible cartridge is seated in said first jaw; and
 - another feature configured to move said closure lock from said blocking position to said unblocking position when said unfired incompatible cartridge is seated in said first jaw, and wherein said unfired incompatible cartridge further comprises:
- a plurality of surgical staples stored in said incompatible cartridge body; and
- a camming member movably supported in said incompatible cartridge body in an unactuated position, wherein said camming member is configured to eject said surgical staples from said incompatible cartridge body when said camming member is moved from said unactuated position to an actuated position.

34. The surgical end effector of claim **33**, wherein said camming member is configured to move said first firing member lock from said first locked position to said second locked position when said camming member is in said unactuated position and said unfired incompatible cartridge is seated in said first jaw.

35. The surgical end effector of claim **29**, wherein said fired incompatible cartridge comprises:

- an incompatible cartridge body configured to be seated in said first jaw, wherein said incompatible cartridge body comprises an incompatible proximal end and an incompatible distal end, and wherein said incompatible cartridge body lacks at least one of:
 - a feature configured to move said second firing member lock from said second locked position to said second unlocked position when said fired incompatible cartridge is seated in said first jaw; and
 - another feature configured to move said closure lock from said blocking position to said unblocking position when said fired incompatible cartridge is seated in said first jaw, and wherein said fired incompatible cartridge further comprises:
- a camming member in an actuated position, wherein said camming member is configured to eject staples stored in said incompatible cartridge body when said camming member is moved from an unactuated position to said actuated position.

* * * * *