



US010896540B2

(12) **United States Patent**  
**Freund et al.**

(10) **Patent No.:** **US 10,896,540 B2**

(45) **Date of Patent:** **\*Jan. 19, 2021**

(54) **SYSTEMS AND METHODS FOR RAPID THREE-DIMENSIONAL MODELING WITH REAL FAÇADE TEXTURE**

(71) Applicants: **Pictometry International Corp.**, Rochester, NY (US); **Idan Computers Engineering (1979) Ltd.**, Azor (IL)

(72) Inventors: **Joseph G. Freund**, Rishon le-Zion (IL); **Ran Gal**, Rishon le-Zion (IL)

(73) Assignee: **Pictometry International Corp.**, Rochester, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/799,034**

(22) Filed: **Feb. 24, 2020**

(65) **Prior Publication Data**  
US 2020/0193702 A1 Jun. 18, 2020

**Related U.S. Application Data**

(63) Continuation of application No. 16/298,774, filed on Mar. 11, 2019, now Pat. No. 10,573,069, which is a (Continued)

(51) **Int. Cl.**  
**G06T 17/05** (2011.01)  
**G06T 11/00** (2006.01)  
**G06T 15/04** (2011.01)

(52) **U.S. Cl.**  
CPC ..... **G06T 17/05** (2013.01); **G06T 11/001** (2013.01); **G06T 15/04** (2013.01)

(58) **Field of Classification Search**  
CPC ..... **G06T 15/04**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,273,876 A 2/1942 Lutz et al.  
3,153,784 A 10/1964 Petrides et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

AT 331204 T 7/2006  
BR 0316110 9/2005  
(Continued)

OTHER PUBLICATIONS

Ackermann, Prospects of Kinematic GPS Aerial Triangulation, ITC Journal, 1992.

(Continued)


*Primary Examiner* — Phi Hoang

(74) *Attorney, Agent, or Firm* — Dunlap Coddling, P.C.

(57) **ABSTRACT**

Computer systems and methods are described for automatically generating a 3D model, including, with computer processor(s), obtaining geo-referenced images representing the geographic location of a structure containing one or more real façade texture of the structure; locating a geographical position of real façade texture(s) of the structure; selecting base oblique image(s) from the images by analyzing image raster content of the real façade texture depicted in the images with selection logic; analyzing the real façade texture to locate a geographical position of at least one occlusion using pixel pattern recognition of the real façade texture; locating oblique image(s) having an unoccluded image characteristic of the occlusion in the real façade texture; applying the real façade texture to wire-frame data of the structure to create a 3D model of the structure; and applying the unoccluded image characteristic to the real façade texture to remove the occlusion from the real façade texture.

**19 Claims, 9 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/977,848, filed on May 11, 2018, now Pat. No. 10,229,532, which is a continuation of application No. 15/830,823, filed on Dec. 4, 2017, now Pat. No. 9,972,126, which is a continuation of application No. 15/374,358, filed on Dec. 9, 2016, now Pat. No. 9,836,882, which is a continuation of application No. 15/056,598, filed on Feb. 29, 2016, now Pat. No. 9,520,000, which is a continuation of application No. 14/633,285, filed on Feb. 27, 2015, now Pat. No. 9,275,496, which is a continuation of application No. 14/152,638, filed on Jan. 10, 2014, now Pat. No. 8,970,615, which is a continuation of application No. 13/903,683, filed on May 28, 2013, now Pat. No. 8,648,872, which is a continuation of application No. 11/998,974, filed on Dec. 3, 2007, now Pat. No. 8,531,472.

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

3,594,556	A	7/1971	Edwards	5,200,793	A	4/1993	Ulich et al.
3,614,410	A	10/1971	Bailey	5,210,586	A	5/1993	Grage et al.
3,621,326	A	11/1971	Hobrough	5,231,435	A	7/1993	Blakely
3,661,061	A	5/1972	Tokarz	5,247,356	A	9/1993	Ciampa
3,716,669	A	2/1973	Watanabe et al.	5,251,037	A	10/1993	Busenberg
3,725,563	A	4/1973	Woycechowsky	5,265,173	A	11/1993	Griffin et al.
3,864,513	A	2/1975	Halajian et al.	5,267,042	A	11/1993	Tsuchiya et al.
3,866,602	A	2/1975	Furihata	5,270,756	A	12/1993	Busenberg
3,877,799	A	4/1975	O'Donnell	5,296,884	A	3/1994	Honda et al.
4,015,080	A	3/1977	Moore-Searson	5,335,072	A	8/1994	Tanaka et al.
4,044,879	A	8/1977	Stahl	5,342,999	A	8/1994	Frei et al.
4,184,711	A	1/1980	Wakimoto	5,345,086	A	9/1994	Bertram
4,240,108	A	12/1980	Levy	5,353,055	A	10/1994	Hiramatsu
4,281,354	A	7/1981	Conte	5,369,443	A	11/1994	Woodham
4,344,683	A	8/1982	Stemme	5,402,170	A	3/1995	Parulski et al.
4,360,876	A	11/1982	Girault et al.	5,414,462	A	5/1995	Veatch
4,382,678	A	5/1983	Thompson et al.	5,467,271	A	11/1995	Abel et al.
4,387,056	A	6/1983	Stowe	5,481,479	A	1/1996	Wight et al.
4,396,942	A	8/1983	Gates	5,486,948	A	1/1996	Imai et al.
4,463,380	A	7/1984	Hooks	5,506,644	A	4/1996	Suzuki et al.
4,489,322	A	12/1984	Zulch et al.	5,508,736	A	4/1996	Cooper
4,490,742	A	12/1984	Wurtzinger	5,555,018	A	9/1996	von Braun
4,491,399	A	1/1985	Bell	5,604,534	A	2/1997	Hedges et al.
4,495,500	A	1/1985	Vickers	5,617,224	A	4/1997	Ichikawa et al.
4,527,055	A	7/1985	Harkless et al.	5,633,946	A	5/1997	Lachinski et al.
4,543,603	A	9/1985	Laures	5,668,593	A	9/1997	Lareau et al.
4,586,138	A	4/1986	Mullenhoff et al.	5,677,515	A	10/1997	Selk et al.
4,635,136	A	1/1987	Ciampa et al.	5,798,786	A	8/1998	Lareau et al.
4,653,136	A	3/1987	Denison	5,835,133	A	11/1998	Moreton et al.
4,653,316	A	3/1987	Fukuhara	5,841,574	A	11/1998	Willey
4,673,988	A	6/1987	Jansson et al.	5,844,602	A	12/1998	Lareau et al.
4,686,474	A	8/1987	Olsen et al.	5,852,753	A	12/1998	Lo et al.
4,688,092	A	8/1987	Kamel et al.	5,894,323	A	4/1999	Kain et al.
4,689,748	A	8/1987	Hofmann	5,899,945	A	5/1999	Baylocq et al.
4,707,698	A	11/1987	Constant et al.	5,963,664	A	10/1999	Kumar et al.
4,758,850	A	7/1988	Archdale et al.	6,037,945	A	3/2000	Loveland
4,805,033	A	2/1989	Nishikawa	6,088,055	A	7/2000	Lareau et al.
4,807,024	A	2/1989	Mclairin et al.	6,094,215	A	7/2000	Sundahl et al.
4,814,711	A	3/1989	Olsen et al.	6,097,854	A	8/2000	Szeliski et al.
4,814,896	A	3/1989	Heitzman et al.	6,108,032	A	8/2000	Hoagland
4,843,463	A	6/1989	Michetti	6,130,705	A	10/2000	Lareau et al.
4,899,296	A	2/1990	Khattak	6,157,747	A	12/2000	Szeliski et al.
4,906,198	A	3/1990	Cosimano et al.	6,167,300	A	12/2000	Cherepenin et al.
4,953,227	A	8/1990	Katsuma et al.	6,222,583	B1	4/2001	Matsumura et al.
4,956,872	A	9/1990	Kimura	6,236,886	B1	5/2001	Cherepenin et al.
5,034,812	A	7/1991	Rawlings	6,256,057	B1	7/2001	Mathews et al.
5,086,314	A	2/1992	Aoki et al.	6,373,522	B2	4/2002	Mathews et al.
5,121,222	A	6/1992	Endoh et al.	6,421,610	B1	7/2002	Carroll et al.
5,138,444	A	8/1992	Hiramatsu	6,434,280	B1	8/2002	Peleg et al.
5,155,597	A	10/1992	Lareau et al.	6,597,818	B2	7/2003	Kumar et al.
5,164,825	A	11/1992	Kobayashi et al.	6,639,596	B1	10/2003	Shum et al.
5,166,789	A	11/1992	Myrick	6,711,475	B2	3/2004	Murphy
5,191,174	A	3/1993	Chang et al.	6,731,329	B1	5/2004	Feist et al.
				6,747,686	B1	6/2004	Bennett
				6,810,383	B1	10/2004	Loveland
				6,816,819	B1	11/2004	Loveland
				6,826,539	B2	11/2004	Loveland
				6,829,584	B2	12/2004	Loveland
				6,834,128	B1	12/2004	Altunbasak et al.
				6,876,763	B2	4/2005	Sorek et al.
				7,009,638	B2	3/2006	Gruber et al.
				7,018,050	B2	3/2006	Ulichney et al.
				7,046,401	B2	5/2006	Dufaux et al.
				7,061,650	B2	6/2006	Walmsley et al.
				7,065,260	B2	6/2006	Zhang et al.
				7,123,382	B2	10/2006	Walmsley et al.
				7,127,348	B2	10/2006	Smitherman et al.
				7,133,551	B2	11/2006	Chen
				7,142,984	B2	11/2006	Rahmes et al.
				7,184,072	B1	2/2007	Loewen et al.
				7,233,691	B2	6/2007	Setterholm
				7,262,790	B2	8/2007	Bakewell
				7,348,895	B2	3/2008	Lagassey
				7,376,284	B2	5/2008	Tao
				7,509,241	B2	3/2009	Guo
				7,728,833	B2	6/2010	Verma
				7,832,267	B2	11/2010	Woro
				7,844,499	B2	11/2010	Yahiro
				8,078,396	B2	12/2011	Meadow

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,078,436	B2	12/2011	Pershing
8,145,578	B2	3/2012	Pershing
8,170,840	B2	5/2012	Pershing
8,209,152	B2	6/2012	Pershing
8,705,843	B2	4/2014	Lieckfeldt
2002/0041328	A1	4/2002	LeCompte et al.
2002/0041717	A1	4/2002	Murata et al.
2002/0114536	A1	8/2002	Xiong et al.
2003/0014224	A1	1/2003	Guo et al.
2003/0043824	A1	3/2003	Remboski et al.
2003/0088362	A1	5/2003	Meier et al.
2003/0164962	A1	9/2003	Nims et al.
2003/0214585	A1	11/2003	Bakewell
2004/0105090	A1	6/2004	Schultz et al.
2004/0167709	A1	8/2004	Smitherman et al.
2005/0073241	A1	4/2005	Yamauchi et al.
2005/0088251	A1	4/2005	Matsumoto
2005/0169521	A1	8/2005	Hel-Or
2005/0209774	A1	9/2005	Finlay
2005/0265631	A1	12/2005	Mai et al.
2006/0011026	A1	1/2006	Dickey
2006/0028550	A1	2/2006	Palmer et al.
2006/0061566	A1	3/2006	Verma et al.
2006/0092043	A1	5/2006	Lagassey
2006/0238383	A1	10/2006	Kimchi et al.
2006/0250515	A1	11/2006	Koseki et al.
2007/0024612	A1	2/2007	Balfour
2007/0046448	A1	3/2007	Smitherman
2007/0237420	A1	10/2007	Steadly et al.
2008/0120031	A1	5/2008	Rosenfeld et al.
2008/0123994	A1	5/2008	Schultz et al.
2008/0158256	A1	7/2008	Russell et al.
2008/0221843	A1	9/2008	Shenkar et al.
2009/0110267	A1	4/2009	Zakhor et al.
2009/0177458	A1	7/2009	Hochart et al.
2009/0208095	A1	8/2009	Zebedin
2009/0304227	A1	12/2009	Kennedy et al.
2010/0204974	A1	8/2010	Israelsen et al.
2010/0241406	A1	9/2010	Rahmes et al.
2010/0296693	A1	11/2010	Thornberry et al.
2011/0033110	A1	2/2011	Shimamura et al.
2013/0246204	A1	9/2013	Thornberry et al.
2015/0213590	A1	7/2015	Brown et al.

## FOREIGN PATENT DOCUMENTS

CA	2402234	9/2000
CA	2505566	5/2004
CN	1735897	A 2/2006
DE	60017384	T 3/2006
DE	60306301	T 11/2006
DK	1418402	T 10/2006
EP	1010966	2/1999
EP	1180967	2/2002
EP	1418402	5/2004
EP	1696204	8/2006
ES	2266704	T 3/2007
JP	2003/317089	A 11/2003
MX	PA05004987	2/2006
WO	WO99/18732	4/1999
WO	WO/2000/053090	9/2000
WO	WO/2004/044692	5/2004
WO	WO/2005/088251	9/2005
WO	WO/2008/028040	3/2008

## OTHER PUBLICATIONS

Ciampa, John A., "Pictometry Digital Video Mapping", SPIE, vol. 2598, pp. 140-148, 1995.

Ciampa, J. A., "Oversee, Presented at Reconstruction After Urban earthquakes, Buffalo, NY, 1989.

Dunford et al., "Remote Sensing for Rural Development Planning in Africa, The Journal for the International Institute for Aerial Survey and Earth Sciences, 2:99-108, 1983.

Gagnon, P.A., Agnard, J. P., Nolette, C., & Boulianne, M., "A Micro-Computer based General Photogrammetric System", Photogrammetric Engineering and Remote Sensing, vol. 56, No. 5., pp. 623-625, 1990.

Konecny, G., "Issues of Digital Mapping", Leibniz University Hannover, Germany, GIS Ostrava 2008, Ostrava 27.—30.1.2008, pp. 1-8.

Konecny, G., "Analytical Aerial Triangulation with Convergent Photography", Department of Surveying Engineering, University of New Brunswick, pp. 37-57, 1966.

Konecny, G., "Interior Orientation and Convergent Photography", Photogrammetric Engineering, pp. 625-634, 1965.

Graham, Lee A., "Airborne Video for Near-Real-Time Vegetation Mapping", Journal of Forestry, 8:28-32, 1993.

Graham, Horita TRG-50 SMPTE Time-Code Reader, Generator, Window Inserter, 1990.

Hess, L.L., et al., "Geocoded Digital Videography for Validation of Land Cover Mapping in the Amazon Basin", International Journal of Remote Sensing, vol. 23, No. 7, pp. 1527-1555, 2002.

Hinthorne, J., et al., "Image Processing in The Grass GIS", Geoscience and Remote Sensing Symposium, 4:2227-2229, 1991.

Imhof, Ralph K., "Mapping from Oblique Photographs", Manual of Photogrammetry, Chapter 18, 1966.

Jensen, John R., Introductory Digital Image Processing: A Remote Sensing Perspective, Prentice-Hall, 1986; 399 pages.

Lapine, Lewis A., "Practical Photogrammetric Control by Kinematic GPS", GPS World, 1(3):44-49, 1990.

Lapine, Lewis A., Airborne Kinematic GPS Positioning for Photogrammetry—The Determination of the Camera Exposure Station, Silver Spring, MD, 11 pages, at least as early as 2000.

Linden et al., Airborne Video Automated Processing, US Forest Service Internal report, Fort Collins, CO, 1993.

Myhre, Dick, "Airborne Video System Users Guide", USDA Forest Service, Forest Pest Management Applications Group, published by Management Assistance Corporation of America, 6 pages, 1992.

Myhre et al., "An Airborne Video System Developed Within Forest Pest Management—Status and Activities", 10 pages, 1992.

Myhre et al., "Airborne Videography—A Potential Tool for Resource Managers"—Proceedings: Resource Technology 90, 2nd International Symposium on Advanced Technology in Natural Resource Management, 5 pages, 1990.

Myhre et al., Aerial Photography for Forest Pest Management, Proceedings of Second Forest Service Remote Sensing Applications Conference, Slidell, Louisiana, 153-162, 1988.

Myhre et al., "Airborne Video Technology", Forest Pest Management/Methods Application Group, Fort Collins, CO, pp. 1-6, at least as early as Jul. 30, 2006.

Norton-Griffiths et al., 1982. "Sample surveys from light aircraft combining visual observations and very large scale color photography". University of Arizona Remote Sensing Newsletter 82-2:1-4.

Norton-Griffiths et al., "Aerial Point Sampling for Land Use Surveys", Journal of Biogeography, 15:149-156, 1988.

Novak, Rectification of Digital Imagery, Photogrammetric Engineering and Remote Sensing, 339-344, 1992.

Slaymaker, Dana M., "Point Sampling Surveys with GPS-logged Aerial Videography", Gap Bulletin No. 5, University of Idaho, <http://www.gap.uidaho.edu/Bulletins/5/PSSwGPS.html>, 1996.

Slaymaker, et al., "Madagascar Protected Areas Mapped with GPS-logged Aerial Video and 35mm Air Photos", Earth Observation magazine, vol. 9, No. 1, [http://www.eonline.com/Common/Archives/2000jan/00jan\\_tableofcontents.html](http://www.eonline.com/Common/Archives/2000jan/00jan_tableofcontents.html), pp. 1-4, 2000.

Slaymaker, et al., "Cost-effective Determination of Biomass from Aerial Images", Lecture Notes in Computer Science, 1737:67-76, <http://portal.acm.org/citation.cfm?id=648004.743267&coll=GUIDE&dl=>, 1999.

Slaymaker, et al., "A System for Real-time Generation of Georeferenced Terrain Models", 4232A-08, SPIE Enabling Technologies for Law Enforcement Boston, MA, <ftp://vis-ftp.cs.umass.edu/Papers/schultz/spie2000.pdf>, 2000.

Slaymaker, et al., "Integrating Small Format Aerial Photography, Videography, and a Laser Profiler for Environmental Monitoring", In ISPRS WG III/1 Workshop on Integrated Sensor Calibration and Orientation, Portland, Maine, 1999.

(56)

## References Cited

## OTHER PUBLICATIONS

- Slaymaker, et al., "Calculating Forest Biomass With Small Format Aerial Photography, Videography and a Profiling Laser", In Proceedings of the 17th Biennial Workshop on Color Photography and Videography in Resource Assessment, Reno, NV, 1999.
- Slaymaker et al., Mapping Deciduous Forests in Southern New England using Aerial Videography and Hyperclustered Multi-Temporal Landsat TM Imagery, Department of Forestry and Wildlife Management, University of Massachusetts, 1996.
- Star et al., "Geographic Information Systems an Introduction", Prentice-Hall, 1990.
- Tomasi et al., "Shape and Motion from Image Streams: a Factorization Method"—Full Report on the Orthographic Case, pp. 9795-9802, 1992.
- Warren, Fire Mapping with the Fire Mousetrap, Aviation and Fire Management, Advanced Electronics System Development Group, USDA Forest Service, 1986.
- Welch, R., "Desktop Mapping with Personal Computers", Photogrammetric Engineering and Remote Sensing, 1651-1662, 1989.
- Westervelt, James, "Introduction to GRASS 4", pp. 1-25, 1991.
- "RGB Spectrum Videographics Report, vol. 4, No. 1, McDonnell Douglas Integrates RGB Spectrum Systems in Helicopter Simulators", pp. 1-6, 1995.
- RGB "Computer Wall", RGB Spectrum, 4 pages, 1995.
- "The First Scan Converter with Digital Video Output", Introducing . . . The RGB/Videolink 1700D-1, RGB Spectrum, 2 pages, 1995.
- Erdas Field Guide, Version 7.4, A Manual for a commercial image processing system, 1990.
- "Image Measurement and Aerial Photography", Magazine for all branches of Photogrammetry and its fringe areas, Organ of the German Photogrammetry Association, Berlin-Wilmersdorf, No. 1, 1958.
- "Airvideo Analysis", Microimages, Inc., Lincoln, NE, 1 page, Dec. 1992.
- Zhu, Zhigang, Hanson, Allen R., "Mosaic-Based 3D Scene Representation and Rendering", Image Processing, 2005, ICIP 2005, IEEE International Conference on 1(2005).
- Mostafa, et al., "Direct Positioning and Orientation Systems How do they Work? What is the Attainable Accuracy?", Proceeding, American Society of Photogrammetry and Remote Sensing Annual Meeting, St. Louis, MO, Apr. 24-27, 2001.
- "POS AV" georeferenced by APPLANIX aided inertial technology, [http://www.applanix.com/products/posav\\_index.php](http://www.applanix.com/products/posav_index.php).
- Mostafa, et al., "Ground Accuracy from Directly Georeferenced Imagery", Published in GIM International vol. 14 N. Dec. 12, 2000.
- Mostafa, et al., "Airborne Direct Georeferencing of Frame Imagery: An Error Budget", The 3<sup>rd</sup> International Symposium on Mobile Mapping Technology, Cairo, Egypt, Jan. 3-5, 2001.
- Mostafa, M.R. and Hutton, J., "Airborne Kinematic Positioning and Attitude Determination Without Base Stations", Proceedings, International Symposium on Kinematic Systems in Geodesy, Geomatics, and Navigation (KIS 2001) Banff, Alberta, Canada, Jun. 4-8, 2001.
- Mostafa, et al., "Airborne DGPS Without Dedicated Base Stations for Mapping Applications", Proceedings of ION-GPS 2001, Salt Lake City, Utah, USA, Sep. 11-14.
- Mostafa, "ISAT Direct Exterior Orientation QA/QC Strategy Using POS Data", Proceedings of OEEPE Workshop: Integrated Sensor Orientation, Hanover, Germany, Sep. 17-18, 2001.
- Mostafa, "Camera/IMU Bore-sight Calibration: New Advances and Performance Analysis", Proceedings of the ASPRS Annual Meeting, Washington, D.C., Apr. 21-26, 2002.
- Hiatt, "Sensor Integration Aids Mapping at Ground Zero", Photogrammetric Engineering and Remote Sensing, Sep. 2002, p. 877-878.
- Mostafa, "Precision Aircraft GPS Positioning Using CORS", Photogrammetric Engineering and Remote Sensing, Nov. 2002, p. 1125-1126.
- Mostafa, et al., System Performance Analysis of INS/DGPS Integrated System for Mobile Mapping System (MMS), Department of Geomatics Engineering, University of Calgary, Commission VI, WG VI/4, Mar. 2004.
- Artes F., & Hutton, J., "GPS and Inertial Navigation Delivering", Sep. 2005, GEOconnexion International Magazine, p. 52-53, Sep. 2005.
- "POS AV" APPLANIX, Product Outline, [airborne@applanix.com](mailto:airborne@applanix.com), 3 pages, Mar. 28, 2007.
- POSTrack, "Factsheet", APPLANIX, Ontario, Canada, [www.applanix.com](http://www.applanix.com), Mar. 2007.
- POS AV "Digital Frame Camera Applications", 3001 Inc., Brochure, 2007.
- POS AV "Digital Scanner Applications", Earthdata Brochure, Mar. 2007.
- POS AV "Film Camera Applications" AeroMap Brochure, Mar. 2007.
- POS AV "LIDAR Applications" MD Atlantic Brochure, Mar. 2007.
- POS AV "OEM System Specifications", 2005.
- POS AV "Synthetic Aperture Radar Applications", Overview, Orbisat Brochure, Mar. 2007.
- "POSTrack V5 Specifications" 2005.
- "Remote Sensing for Resource Inventory Planning and Monitoring", Proceeding of the Second Forest Service Remote Sensing Applications Conference—Slidell, Louisiana and NSTL, Mississippi, Apr. 11-15, 1988.
- "Protecting Natural Resources with Remote Sensing", Proceeding of the Third Forest Service Remote Sensing Applications Conference—Apr. 9-13, 1990.
- Heipke, et al., "Test Goals and Test Set Up for the OEEPE Test—Integrated Sensor Orientation", 1999.
- Kumar, et al., "Registration of Video to Georeferenced Imagery", Sarnoff Corporation, CN5300, Princeton, NJ, 1998.
- McConnel, Proceedings Aerial Pest Detection and Monitoring Workshop—1994.pdf, USDA Forest Service Forest Pest Management, Northern Region, Intermountain region, Forest Insects and Diseases, Pacific Northwest Region.
- "Standards for Digital Orthophotos", National Mapping Program Technical Instructions, US Department of the Interior, Dec. 1996.
- Tao, "Mobile Mapping Technology for Road Network Data Acquisition", Journal of Geospatial Engineering, vol. 2, No. 2, pp. 1-13, 2000.
- "Mobile Mapping Systems Lesson 4", Lesson 4 SURE 382 Geographic Information Systems II, pp. 1-29, Jul. 2, 2006.
- Konecny, G., "Mechanische Radialtriangulation mit Konvergentaufnahmen", BILDMESSUNG und LUFTBILDWESEN, 1958, Nr. 1.
- Myhre, "ASPRS/ACSM/RT 92" Technical papers, Washington, D.C., vol. 5 Resource Technology 92, Aug. 3-8, 1992.
- Rattigan, "Towns get new view from above," *The Boston Globe*, Sep. 5, 2002.
- Mostafa, et al., "Digital image georeferencing from a multiple camera system by GPS/INS," *ISP RS Journal of Photogrammetry & Remote Sensing*, 56(1): 1-12, Jun. 2001.
- Dillow, "Grin, or bare it, for aerial shot," *Orange County Register* (California), Feb. 25, 2001.
- Anonymous, "Live automatic coordinates for aerial images," *Advanced imaging*, 12(6):51, Jun. 1997.
- Anonymous, "Pictometry and US Geological Survey announce—Cooperative Research and Development Agreement," Press Release published Oct. 20, 1999.
- Miller, "Digital software gives small Arlington the Big Picture," *Government Computer News/State & Local*, 7(12), Dec. 2001.
- Garrett, "Pictometry: Aerial photography on steroids," *Law Enforcement Technology* 29(7):114-116, Jul. 2002.
- Weaver, "County gets an eyeful," *The Post-Standard* (Syracuse, NY), May 18, 2002.
- Reed, "Firm gets latitude to map O.C. in 3D," *Orange County Register* (California), Sep. 27, 2000.
- Reyes, "Orange County freezes ambitious aerial photography project," *Los Angeles Times*, Oct. 16, 2000.
- Aerowest Pricelist of Geodata as of Oct. 21, 2005 and translations to English 3 pages.
- [www.archive.org](http://www.archive.org) Web site showing archive of German AeroDach Web Site <http://www.aerodach.de> from Jun. 13, 2004 (retrieved Sep. 20, 2012) and translations to English 4 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

AeroDach® Online Roof Evaluation Standard Delivery Format and 3D Data File: Document Version 01.00.2002 with publication in 2002, 13 pages.

Noronha et al., "Detection and Modeling of Building from Multiple Aerial Images," Institute for Robotics and Intelligent Systems, University of Southern California, Nov. 27, 2001, 32 pages.

Applicad Reports dated Nov. 25, 1999-Mar. 9, 2005, 50 pages.

Applicad Online Product Bulletin archive from Jan. 7, 2003, 4 pages.

Applicad Sorcerer Guide, Version 3, Sep. 8, 1999, 142 pages.

Xactimate Claims Estimating Software archive from Feb. 12, 2010, 8 pages.

Bignone et al, Automatic Extraction of Generic House Roofs from High Resolution Aerial Imagery, Communication Technology Laboratory, Swiss Federal Institute of Technology ETH, CH-8092 Zurich, Switzerland, 12 pages, 1996.

Geospan 2007 Job proposal.

Greening et al., Commercial Applications of GPS-Assisted Photogrammetry, Presented at GIS/LIS Annual Conference and Exposition, Phoenix, AZ, Oct. 1994.

Applanix Corp, Robust, Precise Position and Orientation Solutions, POS/AV & POS/DG Installation & Operation Manual, Redefining the way you survey, May 19, 1999, Ontario, Canada.

Applanix Corp, Robust, Precise Position and Orientation Solutions, POS/AV V4 Ethernet & Disk Logging ICD, Redefining the way you survey, Revision 3, Apr. 18, 2001, Ontario, Canada.

PCT/US08/85410 International Search Report dated Feb. 3, 2009.  
PCT/US09/052776 International Search Report dated Mar. 15, 2010.


Mikhail, Edward M., "Multi-source Feature Extraction and Visualization in Urban Environment," International Archives of Photogrammetry and Remote Sensing, vol. XXXIII, Part B3. Amsterdam 2000.  
PCT/US08/85410 International Search Report dated Jun. 8, 2010.

Rasmussen et al., "Spatiotemporal inpainting for Recovering Texture Maps of Partially Occluded Building Facades", IEEE International Conference, vol. 3, Sep. 2005.

USPTO, Office Action regarding U.S. Appl. No. 13/689,006, dated Feb. 17, 2016.

Fuji, Kensaku; Arikawa, Tomohiko; "Urban Object Reconstruction Using Airborne Laser Elevation Image and Aerial Image", IEEE Transactions on GeoScience and Remote Sensing, vol. 40, No. 10, IEEE, Oct. 2002, Abstract.

USPTO, Office Action dated Aug. 20, 2015 regarding U.S. Appl. No. 13/689,006.



*Fig. 1*



Fig. 2



Fig. 3




Fig. 4





Fig. 5



***Fig. 6***






Fig. 7



**Fig. 8**



**Fig. 9**

**SYSTEMS AND METHODS FOR RAPID  
THREE-DIMENSIONAL MODELING WITH  
REAL FAÇADE TEXTURE**

INCORPORATION BY REFERENCE OF  
RELATED APPLICATIONS

The present patent application is a continuation of, and claims priority to, U.S. Ser. No. 16/298,774 filed Mar. 11, 2019; which is a continuation of U.S. Ser. No. 15/977,848 filed May 11, 2018, which issued Mar. 12, 2019 as U.S. Pat. No. 10,229,532; which is a continuation of U.S. Ser. No. 15/830,823 filed Dec. 4, 2017, which issued May 15, 2018 as U.S. Pat. No. 9,972,126; which is a continuation of U.S. Ser. No. 15/374,358 filed Dec. 9, 2016, which issued Dec. 5, 2017 as U.S. Pat. No. 9,836,882; which is a continuation of U.S. Ser. No. 15/056,598 filed Feb. 29, 2016, which issued Dec. 13, 2016 as U.S. Pat. No. 9,520,000; which is a continuation of U.S. Ser. No. 14/633,285 filed Feb. 27, 2015, which issued Mar. 1, 2016 as U.S. Pat. No. 9,275,496; which is a continuation of U.S. Ser. No. 14/152,638, filed Jan. 10, 2014, which issued Mar. 3, 2015, as U.S. Pat. No. 8,970,615; which is a continuation of U.S. Ser. No. 13/903,683, filed May 28, 2013, which issued Feb. 11, 2014 as U.S. Pat. No. 8,648,872; which is a continuation of U.S. Ser. No. 11/998,974, filed Dec. 3, 2007 which issued Sep. 10, 2013, as U.S. Pat. No. 8,531,472, the entire contents of all of which are hereby incorporated herein by reference in their entirety.

BACKGROUND OF THE INVENTION

Technology advancements within the three-dimensional modeling industry are providing avenues for physical simulation of real-life and hypothetical situations on computer systems. These models can provide valuable information for strategic and tactical planning. For example, three-dimensional models of city streets can provide first responders information regarding current city developments including entryway locations, building recognition, and the like. This information is valuable in reducing response time during emergency conditions. Further, emergency personal can train for emergency situations through simulated scenarios provided by or with the three-dimensional models.

Currently within the art, oblique images obtained from aerial photographs are used to provide close-to-accurate representations of each building's surface within the three-dimensional model. However, generally, it is difficult to obtain these oblique images with unobstructed views of the building's surface. For instance, most buildings in downtown regions of a major metropolitan city are close in proximity to one another. It becomes burdensome and time consuming to capture aerial images of each building without an obstruction, such as a neighboring building. Further, finding a single image without obstructions from the thousands of aerial images obtained, would be extremely time consuming and cost-prohibitive and may require three-dimensional modeling of all obstructing structures.

Some three-dimensional models edit the obstructed portion of the oblique image by approximating the building's surface using other portions of the same building. Although this method does provide a representation of the building within the three-dimensional model, the representation goes on the assumption that all portions of the building are created equal. However, this assumption is problematic as an obstructed area may have uniquely placed doorways and/or windows that may be ignored by the approximation.

Alternatively, a user can manually manipulate two or more oblique images to form a single image having an unobstructed view of the façade. This type of manual manipulation is slow and tedious, and requires experience and expertise in the modeling field.

BRIEF SUMMARY OF THE INVENTION

In one embodiment, the present invention is related to a method of automatically generating a three-dimensional model of a structure. The three-dimensional model of the structure preferably includes real façade textures obtained from geo-referenced oblique images. The geographical position of the real façade texture is provided using wire-frame data. A base oblique image is selected from geo-referenced oblique images using the geographical positions obtained from the wire-frame data. The base oblique image is selected from the geo-referenced oblique images based on analysis of the image raster content of the real façade texture, and the real façade texture of the base oblique image is then applied to the three-dimensional model.

In one version, the real façade texture is analyzed to locate at least one occlusion. Occlusions can include obstructions in the view of the real façade texture such as an overlapping building, image distortions within the base oblique images, and/or the like. Occlusions may be located using pattern recognition, contrast, and/or the like. Unoccluded image characteristics of the real façade texture are provided by at least one geo-referenced oblique image. The unoccluded image characteristics of the occlusion are applied to the real façade texture to form a mosaic image.

In another version, the real façade texture is analyzed and corrected for misalignment. Misalignment may be corrected by shrinking and/or stretching the real façade texture, extracting portions of the real façade texture, and/or the like. For example, the outer boundaries of the real façade texture may be extracted using discontinuities in depth, discontinuities in surface orientation, variations in scene illumination, and/or the like.

In another version, the wire-frame data of the three-dimensional model is analyzed to locate the geographical position of a roof of the structure. Images containing the roof are provided and a base image is selected and applied to the three-dimensional model. The images may be nadir images or oblique images. Selection of the base image is based on the image raster content, for example, a base image may be preferred in which the image raster content contains a greater proportion of pixels associated with the roof as compared with other base images.

In another embodiment, the present invention is related to a method of automatically generating a three-dimensional model having structures with real façade textures. The real façade textures are obtained from geo-referenced aerial oblique images. Wire-frame data is analyzed to locate geographical positions of the real façade textures of the structures within a geographical area. An oblique image showing the real façade texture is selected. Where present, at least one incorrect area within at least a portion of the real façade texture may be identified. The incorrect area within the portion of the real façade texture is automatically corrected.

BRIEF DESCRIPTION OF THE SEVERAL  
VIEWS OF THE DRAWING

So the above-recited features and advantages of the present invention may be understood in detail, a more particular description of the invention, briefly summarized

above, may be had by reference to the embodiments thereof that are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only typical embodiments of this invention and are therefore not to be considered limiting in scope, for the invention may admit to other equally-effective embodiments.

FIG. 1 is a block diagram of one embodiment of the rapid three-dimensional modeler system having real-façade textures obtained from geo-referenced images in accordance with the present invention.

FIG. 2 is a pictorial representation of a three-dimensional model having real façade textures.

FIG. 3 is a pictorial representation of wire-frame data providing a geographical position of a real façade texture of a structure.

FIG. 4 is a pictorial representation of terrain data providing a geographical position of a real façade texture of a structure.

FIG. 5 is a pictorial representation of an exemplary oblique image obtained from an aerial camera, the oblique image displaying a real façade texture of a structure.

FIG. 6 is an exemplary function flow chart of a method for generating a three-dimensional model of a structure including real façade textures obtained from geo-referenced images.

FIG. 7 is a schematic block diagram of the formation of a mosaic image from a base image and a geo-referenced image including an unoccluded image characteristic.

FIG. 8 is a schematic block diagram of the formation of a mosaic image from a base image and a geo-referenced image including an unoccluded image characteristic, the base image and the geo-referenced image having different views.

FIG. 9 is a schematic diagram of an exemplary embodiment of a system for providing three-dimensional models having real façade textures in accordance with the present invention.

#### DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Embodiments of the invention are shown in the above-identified Figures and described in detail below. In describing the embodiments, like or identical reference numerals are used to identify common or similar elements. The Figures are not necessarily to scale and certain features and certain views of the Figures may be shown exaggerated in scale or in schematic in the interest of clarity and conciseness.

Referring now to the drawings and in particular to FIGS. 1 and 2, shown therein and designated by a reference numeral 10 is an exemplary system for rapidly creating a three-dimensional model 12 of a structure 14 including real façade textures 16. The system 10 provides real façade textures 16 obtained from geo-referenced images 18. The three-dimensional model 12, including the real façade textures 16, provides an accurate representation of a geographic area. An exemplary three-dimensional model 12 is shown in FIG. 2 and preferably includes structures such as buildings, thoroughfares, and other associated fixtures. Such features provide real-life representation of the geographical area useful in strategic planning, tactical planning, tactical debriefing, simulation, real-time simulation, first response actions, engineering designs, and/or the like. Although the geographic area applies to physical characteristics of an area, it is not limited to the topographical features of the Earth's surface. For example, the system and methods

described herein may apply to rapid three-dimensional modeling techniques for medical imaging.

Generally, the system 10 identifies a geographical position 22 of at least one real façade texture 16 of the structure 14. The system 10 locates geo-referenced images 18 containing the real façade texture 16 and selects a base image 19 (See FIG. 7) having optimal image characteristics of the real façade texture 16. This base image 19 provides at least one real façade texture applied to the structure 14 forming the three-dimensional model 12.

The system 10 identifies the geographical position 22 of the real façade textures 16 within the geo-referenced images 18. In one embodiment, the system 10 uses wire-frame data 20 of the structure 14 to provide the geographical position 22 through the identification of boundaries (17a, 17b, 17c, 17d . . . ) of the real façade texture 16, as best illustrated in FIG. 3. Although the wire-frame data 20 of FIG. 3 illustrates boundaries 17a-17d of the real façade texture 16 as a rectangle, it will be appreciated by one skilled in the art, the boundaries 17a-17d may comprise a circle, square, triangle, or any fanciful shape. Alternatively, an edge-detection algorithm may be used to locate the geographical position 22 of the real façade texture 16 within the wire-frame data. Preferably, wire-frame data 20 is obtained from publicly available information of buildings, structures, elevations and the like. For example, publicly available wire-frame data 20 commonly stored as \*.shp files may be used. Alternatively, wire-frame data 20 of the structure 14 may be created based on the particular application of the present invention using techniques commonly known within the art.

The system 10 may also use terrain data 24 to provide the geographical position 22 of the real façade texture 16. For example, the system may identify boundaries (17a, 17b, 17c, 17d . . . ) of the real façade texture 16 as illustrated in FIG. 4. Although FIG. 4 illustrates boundaries 17a-17d of the real façade texture 16 as a rectangle, it will be appreciated by one skilled in the art, the boundaries 17a-17d may comprise a circle, square, triangle, or any fanciful shape. Alternatively, an edge-detection algorithm may be used to locate the geographical position 22 of the real façade texture 16 within the terrain data 24. Terrain data may include Digital Terrain Models (DTMs), Digital Elevation Models (DEMs), and/or the like. Generally, terrain data 24 is comprised of sets of universal terrain map coordinates identifying location and elevation of geographical regions. The coordinate system may be any coordinate system including latitude and longitude or any other geographical coordinate system suitable for use with the present invention. Preferably, the terrain data 24 is a publicly available Digital Terrain Model. Alternatively, terrain data 24 for a geographical area may be extracted or created from publicly available contour images, and/or may be created for the specific application intended.

The geo-referenced image 18 providing the real façade texture 16, as illustrated in FIG. 5, may use any color space and be stored in any industry supported file format, such as TIFF, JPEG, GIF, BMP, ECW, and/or the like. Additionally, the geo-referenced images preferably contain or are referenced to or coordinated with information regarding the location and orientation of the camera, focal length, the physical size of the sensor, and/or the like.

The geo-referenced images 18 are preferably nadir images and/or oblique images. Nadir images, as described herein, provide vertical or orthogonal views of the geographic area. Nadir images may be an image captured from an overhead position, a position above the structure 14, or at a right angle or an angle near to a right angle to the structure 14. For example, the image may be taken from an overhead position

as related to the structure **14** at an eighty-seven degree angle or similar angle close to a ninety-degree angle. A nadir image may be rectified to fit an associated wire-frame, DTM, DEM, and/or the like. Rectifying a nadir image may entail mapping the pixels to the coordinates of the wire-

frame, DTM, DEM, and/or the like. As nadir images typically do not express the details and characteristics of structures and objects, in the currently preferred embodiment, oblique images will typically, but not exclusively, be used for the purposes of the present invention. Oblique images, as described herein, are images taken at an angle other than that of the nadir perspective or images derived from the nadir perspective. Oblique images provide a perspective line of sight that generally reveals information not visible from an orthogonal or orthophoto view. For example, an oblique image may have an angle to the structure **14** in the range of about zero degrees to about eighty-nine degrees.

Referring to FIGS. **1** and **6**, the first step **50** in generating a three-dimensional model having real façade textures **16** is to obtain a relevant geographic location of the structure **14**. Once the geographic location is determined, a set of geo-referenced images **18** representing the location are obtained, which is the second step **52**. The geo-referenced images **18** may be obtained as discussed above or in any other suitable fashion. The relevant geographical location **22** may be determined internally, calculating a position based upon a mathematical formula, or through an external entity, for example, by a database or user. Preferably, a user indicates an initial geographic location, for example, such that subsequent locations may be mathematically calculated using image boundaries.

The third step **54** is to locate the geographical position **22** of at least one real façade texture **16** of the structure **14**. Wire-frame data **20** and/or terrain data **24** may be used to locate the geographical position **22** coordinating to the structure **14** as previously discussed herein.

The fourth step **56** is to select a base image **19** containing the real façade texture **16** from the geo-referenced images **18**. The base image **19** is preferably selected as one that accurately represents the real façade texture **16** and may be automatically selected by the system **10** or selected or determined by the user from a limited selection of geo-referenced images **18** provided by the system **10**.

The base image **19** containing the real façade texture **16** is selected from the geo-referenced images **18** of the structure **14** based upon a factorial analysis of the image raster content of each geo-referenced image **18** of the structure **14**. The factorial analysis may include a weighted determination based on the resolution of the image, colour depth of the image, proportional size of the real façade texture, contrast, time of day the image was captured, time of year the image was captured and/or the like. Foliage may also play a role in the factorial analysis. For example, the base image **19** may be selected based on the contrast in lighting conditions. Contrast may be measured as a histogram and provide information regarding shadows within the image. Such information is relevant in constructing replications of large geographical areas, as the three-dimensional model **12** would generally include real façade textures **16** representing the same approximate time of day and/or time of year.

The fifth step is to apply or relate the real façade texture **16** of the base image **19** to the three-dimensional model **12**. The three-dimensional model **12** may comprise base factors such as wire-frame data **20** and/or terrain data **24**. For example, the real façade texture **16** of the base image **19** may be applied to the wire-frame of the structure **14**. The system

**10** may automatically rotate, stretch, or shrink the real façade texture **16** to align with edges of the wire-frame data **20**. Additionally, the system **10** may provide for user evaluation and/or manipulation of the real façade texture **16**.

Alternatively, wire-frame data **20** and/or terrain data **24** may provide a coordinate system for the three-dimensional model **12** such that the real façade texture **16** is geographically positioned within the three-dimensional model according to the corresponding coordinates of the wire-frame data **20** and/or terrain data **24**. Additionally, the real façade texture **16** may be applied to form the entire three-dimensional model **12** or, alternatively, at least a portion of the three-dimensional model **12**. Multiple base images **19** with multiple real façade textures **16** may form the three-dimensional model **12**.

In another embodiment, the real façade texture may be further processed to correct occlusions **70**, as illustrated in FIGS. **7** and **8**. Generally, it is difficult to provide the real façade texture **16** of the base image **19** of the structure **14** without occlusions **70** such as overlapping structures, visual distortions, and/or the like. For example, FIG. **7** illustrates the real façade texture **16** blocked by an overlapping structure **71**. This blocked overlapping structure **71** causes an occlusion **70** within the real façade texture **16**. Multiple geo-referenced images **18** may not be able to provide the real façade texture **16** without the blocked overlapping structure **71**. Therefore, methods are provided to correct for the occlusion **70** within the real façade texture **16**.

To correct for the occlusion **70** within the real façade texture **16**, the base image **19** is analyzed to locate a geographical position **72** of the occlusion **70**. For example, the geographical position **72** may be identified using boundaries (**74a**, **74b**, **74c**, **74d** . . . ). Although the boundaries **74a-74d** are illustrated as a rectangle, it will be appreciated by one skilled in the art, the boundaries **74a-74d** may comprise a circle, square, triangle, or any fanciful shape. Additionally, an edge-detection algorithm may be used to identify the geographical position of the occlusion **70**.

Once the geographical position **72** of the occlusion **70** is located, the geo-referenced images **18** of the structure **14** are analyzed to locate at least one image **76** having an unoccluded image characteristic **78**. As illustrated in FIG. **7**, the geo-referenced images **18** of the structure **14** correcting for the occlusion **70** are not required to be the same view as the base image **19**.

The unoccluded image characteristic is applied to the real façade texture **16** forming a mosaic image **80**. For example, pixels of the unoccluded image characteristic **78** may replace pixels of the occlusion **70** of the real façade texture **16**. The mosaic image **80** may include several unoccluded image characteristics **78** in addition to the real façade texture **16** of the base image **19**.

Storage of the mosaic image **80** may be problematic if the file size of the mosaic image **80** is extremely large. Thus, it may be beneficial to use an algorithm for storing the mosaic image **80**. For example, a rectangular area of the mosaic image **80** can be extracted and all information outside of the rectangular space cropped and removed. However, the geo-referencing information of the area would still be maintained within the mosaic image **80**.

Occlusions **70** are not limited to blocked areas on the real façade texture **16** but can also include misalignment of the real façade texture **16** when applied to the three-dimensional model **12** and/or undesirable background images within the real façade texture **16**. Occlusions **70**, misalignments, and background images may be identified using pattern recognition, contrast, and/or the like. For example, pattern rec-

ognition technically can be used to analyze each pixel or a group of pixels to determine whether the pixel belongs to the real façade texture **16** or is part of the occlusion **70**. The three-dimensional geometry of the surrounding buildings may also be a key factor.

Additionally, the real façade texture **16** may be optimized for depth complexity. Methods for optimizing depth complexity involve the system **10** first determining whether overlapping elements within the real façade texture **16** are occlusions **70** or desirable features of the real façade texture **16**. If the system **10** determines the overlapping elements are desirable features of the real façade texture **16**, the system **10** applies the real façade texture **16** of the overlapping structures to the three-dimensional model. For example, the system **10** may detect a small roof structure that is overlapping a large roof structure. The system **10** will assume that the small roof structure is an element on top of the large roof structure and considered desirably within the real façade texture **16**. The system will apply the real façade texture **16** of the overlapping structures to the three-dimensional model **12**. Depth complexity analyses the geometry of overlapping 3D structures, such as a small room on a large roof. Usually, walls are represented by vertical rectangles, from the top of the roof to the terrain. In this case, walls of the small room are created only to the large roof and not to the terrain.

The formation of the three-dimensional model **12** with real façade textures **16** may be a continuous or intermittent process. Preferably, the formation of the three-dimensional model **12** is automatically performed by the system **10** to facilitate rapid modeling of an area. Using the methods as described herein, the system **10** determines the geographic location of an area of interest and retrieves the appropriate wire-frame data **20** and/or terrain data **24** associated with the area. The system **10** automatically locates and identifies structures **14** within the area based upon the wire-frame data **20** and/or terrain data **24** provided. Geo-referenced images **18** of the area are located by the system **10** using the wire-frame data **20** and/or terrain data **24**. The base oblique image **19** of the structure **14** is automatically selected by the system **10** based on the image raster content of each of the geo-referenced images **18**. If the base oblique image **19** contains more than one structure **14**, the system **10** may locate each real façade texture **16** independently or together. Once the real façade texture **16** is located, the system **10** may fix any occlusions if necessary and apply the real façade texture to the three-dimensional model **12**.

Generally, the system **10** is a computer system that is able to embody and/or execute the logic of the processes described herein. The logic embodied may be executed on any appropriate hardware such as, for example, a dedicated system or systems, personal computer system, distributed processing computer system, and/or the like.

Referring now to FIG. 9, the system **10** is preferably distributed, and includes a host system **112**, communicating with one or more user devices **114** via a network **116**. The network **116** can be the Internet or other network. In either case, the host system **112** typically includes one or more servers **118** configured to communicate with the network **116** via one or more gateways **120**. When the network **116** is the Internet, the primary user interface of the system **10** is delivered through a series of web pages, but the primary user interface can be replaced by another type of interface, such as a Windows-based application. This method is also used when deploying the system **10** in a stand-alone environment, such as a kiosk.

The network **116** can be almost any type of network, although Internet and Internet 2 networks are preferred

because of the wide support of their underlying technologies. One embodiment of the network **116** exists in an Internet environment, which means a TCP/IP-based network. It is conceivable that in the near future, the preferred or other embodiments, may wish to use more advanced networking topologies.

The servers **118** can be networked with a LAN **130**. The gateway **120** is an entity responsible for providing access between the LAN **130** and the network **116**. The gateway **120** can also be used as a security means to protect the LAN **130** from attack from external networks such as the network **116**.

The LAN **130** network can be based on TCP/IP network such as the Internet, or it can be based on another underlying network transport technology. The preferred embodiment uses an Ethernet network with TCP/IP because of the availability and acceptance of underlying technologies, but other embodiments may use other types of networks such as Fibre Channel, SCSI, Gigabit Ethernet, etc.

As discussed above, in one embodiment, the host system **112** includes the servers **118**. The configuration of the server hardware will depend upon the requirements and needs of the particular embodiment of the system **10**. Typical embodiments, including the preferred embodiment, will include multiple servers **118** with load balancing to increase stability and availability. It is envisioned that the servers **118** will include database servers and application/web servers. The database servers are preferably separated from the application/web servers to improve availability and to provide the database servers with improved hardware and storage.

The user devices **114** can be any number and type of device. Generally, user devices **114** involve a user **32**, using a computer **34** with a display **36**, keyboard **38**, and mouse **40**. It is contemplated user devices **114** may include a touch screen element on the display in addition to or in lieu of the keyboard **38** and/or mouse **40**.

Typically, the user device **114** uses a type of software called a "browser" as indicated by reference numeral **42** to render HTML/XHTML content that is generated when requesting resources from a source, such as the host system **112**. In the preferred embodiment, the system **10** is designed to be compatible with major Web Browser vendors (Microsoft Internet Explorer, Netscape Navigator, and Opera). Other embodiments may wish to focus on one particular browser depending upon the common user base using the system **10**. It should be noted, user devices **114** may interact with the system **10** through any suitable functional software, such as a program specifically designed for the individual embodiments of the system **10**.

The user devices **114** can also be implemented as a portable device such as a laptop computer **150** (or handheld computer); a cellular telephone **152** with a micro or embedded Web Browser; a Portable Digital Assistant **154** (PDA) capable of wireless network access; a pen-based or tablet computer **156**, and/or the like. In another embodiment, the user device **114** may be a cable box **60** or other similar device for viewing through a display **62** or television. Current embodiments of the system **10** can also be modified to use any of these or similar future developed devices.

The system **10** is designed to provide flexibility in its deployment. Depending upon the requirements of the particular embodiment, the engine may be designed to work in almost any environment such as a desktop application, a web application, a series of web services designed to communicate with an external application, and/or the like.

The hardware and system software are designed with two key concerns: flexibility and scalability. Although some specifics for software and hardware components are described herein, it will be understood that a wide array of different components may be substituted. For example, different database vendors may be used, SML-based document stores may be used, and/or the like.

When the system 10 is used to execute the logic of the processes described herein, such computer(s) and/or execution may be conducted at a same geographical location or multiple geographic locations. Furthermore, the execution of the logic may be conducted continuously or at multiple discrete times.

The system 10 includes one or more computer readable medium storing instructions for displaying a pixel representation of one or more of the images described herein including the geo-referenced images 18, the base oblique images 19, wire frame data 20, terrain data 24, the three-dimensional model 12, and the like. The computer readable medium may be part of the host system 112, the user devices 114, or combination thereof. Additionally, the system 10 uses one or more databases or servers 118 to store the images in an organized format. For example, the geo-referenced images 18 of the structure 14 may be sorted and stored by the direction showing the particular real façade texture 16.

The system 10 may also include instructions for (1) displaying pixel representations of the images as described above; (2) selecting the geographical location of interest; (3) altering and/or editing images; and (4) other similar tasks. The instructions typically run on a combination of the user devices 114 and the host system 112.

Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it will be obvious to those skilled in the art that certain changes and modifications may be practiced without departing from the spirit and scope thereof, as described in this specification and as defined in the appended claims below.

What is claimed is:

1. A computer system for automatically generating a three-dimensional model, comprising:

one or more computer processor; and,

one or more non-transitory computer readable medium accessible by the one or more computer processor and storing instructions that when executed by the one or more computer processor cause the one or more computer processor to:

obtain, using a geographical location of a structure, multiple geo-referenced images representing the geographic location of a structure within an area of interest and containing one or more real façade texture of the structure;

locate a geographical position of one or more real façade texture of the structure;

select one or more base oblique image from the multiple geo-referenced images by analyzing image raster content of the real façade texture depicted in the multiple geo-referenced images with selection logic;

analyze the real façade texture depicted within the base oblique image to locate a geographical position of at least one occlusion using pixel pattern recognition of the real façade texture to locate the occlusion;

locate at least one oblique image having an unoccluded image characteristic of the occlusion in the real façade texture from the multiple geo-referenced images;

apply the real façade texture of the one or more base oblique image to wire-frame data of the structure to create a three-dimensional model of the structure; and

apply the unoccluded image characteristic to the real façade texture to remove the occlusion from the real façade texture.

2. The computer system of claim 1, wherein locating the geographical position of one or more real façade texture of the structure comprises locating the geographical position of at least one real façade texture of the structure utilizing the wire-frame data of the structure.

3. The computer system of claim 1, wherein the geo-referenced images are geo-referenced solved images.

4. The computer system of claim 1, further comprising instructions that when executed by the one or more computer processor cause the one or more computer processor to extract the real façade texture from the base oblique image, the real façade texture having geo-referenced information.

5. The computer system of claim 1, wherein the real façade texture includes overlapping structures having a geometry, and wherein the instructions, when executed by the one or more computer processor cause the one or more computer processor to analyze the geometry of the overlapping structures to determine whether the overlapping structures are occlusions or desirable features of the real façade texture.

6. The computer system of claim 5, wherein a first overlapping structure of the overlapping structures is a roof structure.

7. The computer system of claim 5, wherein the one or more non-transitory computer readable medium stores instructions that when executed by the one or more computer processor further causes the one or more computer processor to:

apply the real façade texture of the overlapping structures that are determined to be desirable features to the three-dimensional model.

8. The computer system of claim 1, wherein analyzing image raster content of the real façade texture depicted in the multiple geo-referenced images further comprises analyzing image characteristics of the real façade texture contained in the image raster content.

9. The computer system of claim 1, wherein analyzing image raster content of the real façade texture depicted in the multiple geo-referenced images further comprises analyzing multiple characteristics of the real façade texture in the image raster content of multiple geo-referenced images.

10. The computer system of claim 9, wherein locating a geographical position of one or more real façade texture of the structure comprises locating the geographical position of at least one real façade texture of the structure utilizing the wire-frame data of the structure.

11. A method for automatically generating a three-dimensional model, comprising:

obtaining, with one or more computer processor, using a geographical location of a structure, multiple geo-referenced images representing the geographic location of a structure within an area of interest and containing one or more real façade texture of the structure;

locating, with the one or more computer processor, a geographical position of one or more real façade texture of the structure;

selecting, with the one or more computer processor, one or more base oblique image from the multiple geo-referenced images by analyzing image raster content of

**11**

the real façade texture depicted in the multiple geo-referenced images with selection logic; and, analyzing, with the one or more computer processor, the real façade texture depicted within the base oblique image to locate a geographical position of at least one occlusion using pixel pattern recognition of the real façade texture to locate the occlusion;

locating, with the one or more computer processor, at least one oblique image having an unoccluded image characteristic of the occlusion in the real façade texture from the multiple geo-referenced images;

applying, with the one or more computer processor, the real façade texture of the one or more base oblique image to wire-frame data of the structure to create a three-dimensional model; and

applying, with the one or more computer processor, the unoccluded image characteristic to the real façade texture to remove the occlusion from the real façade texture.

**12.** The method of claim **11**, wherein locating a geographical position of one or more real façade texture of the structure comprises locating the geographical position of at least one real façade texture of the structure utilizing the wire-frame data of the structure.

**13.** The method of claim **11**, wherein the real façade texture includes overlapping structures having a geometry, and further comprising, analyzing, using the one or more computer processor, the geometry of the overlapping structures to determine whether the overlapping structures are occlusions or desirable features of the real façade texture.

**12**

**14.** The method of claim **13**, further comprising: applying, using the one or more computer processor, the real façade texture of the overlapping structures that are determined to be desirable features to the three-dimensional model.

**15.** The method of claim **11**, wherein analyzing image raster content of the real façade texture depicted in the multiple geo-referenced images further comprises analyzing image characteristics of the real façade texture contained in the image raster content.

**16.** The method of claim **11**, wherein analyzing image raster content of the real façade texture depicted in the multiple geo-referenced images further comprises analyzing the real façade texture formed by the image raster content of multiple geo-referenced images.

**17.** The method of claim **16**, wherein locating a geographical position of one or more real façade texture of the structure comprises locating the geographical position of at least one real façade texture of the structure utilizing the wire-frame data of the structure.

**18.** The method of claim **11**, wherein analyzing image raster content of the real façade texture depicted in the multiple geo-referenced images further comprises analyzing multiple characteristics of the real façade texture in the image raster content of multiple geo-referenced images.

**19.** The method of claim **18**, wherein locating a geographical position of one or more real façade texture of the structure comprises locating the geographical position of at least one real façade texture of the structure utilizing the wire-frame data of the structure.

\* \* \* \* \*