




(86) Date de dépôt PCT/PCT Filing Date: 2000/01/28
 (87) Date publication PCT/PCT Publication Date: 2000/09/08
 (45) Date de délivrance/Issue Date: 2005/01/25
 (85) Entrée phase nationale/National Entry: 2000/10/30
 (86) N° demande PCT/PCT Application No.: US 2000/002107
 (87) N° publication PCT/PCT Publication No.: 2000/051516
 (30) Priorité/Priority: 1999/03/01 (09/258,931) US

(51) Cl.Int.⁷/Int.Cl.⁷ A61C 5/02
 (72) Inventeurs/Inventors:
 COHEN, BRETT I., US;
 MUSIKANT, BARRY L., US
 (73) Propriétaire/Owner:
 ESSENTIAL DENTAL SYSTEMS, INC., US
 (74) Agent: R. WILLIAM WRAY & ASSOCIATES

(54) Titre : INSTRUMENTS ENDODONTIQUES NON CIRCULAIRES
 (54) Title: NON CIRCULAR ENDODONTIC INSTRUMENTS



(57) **Abrégé/Abstract:**

A non-circular endodontic instrument (110) is provided for reduced stress to the tooth, and to the cutting instrument during the removal of dentin from a root canal. The non-circular endodontic instrument (110) includes at least one area of non-contact (140), i.e., one portion of the instrument does not contact and does not cut the dentin material. The non-contact area (140) extends the length of the endodontic instrument (110), about a portion of the circumference of the instrument, and interrupts a generally circular cutting face (120) of the instrument. This non-contact area (140) reduces stress, provides a place for debris to gather during cutting so as to not interfere with the cutting face (120), and serves to direct the debris out of the root canal. The endodontic instrument (110) can be D-shaped in cross-section. It could have circumferential opposing non-contact, areas and/or can be elliptical in cross-sectional shape.


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61C 5/02	A1	(11) International Publication Number: WO 00/51516 (43) International Publication Date: 8 September 2000 (08.09.00)
(21) International Application Number: PCT/US00/02107 (22) International Filing Date: 28 January 2000 (28.01.00) (30) Priority Data: 09/258,931 1 March 1999 (01.03.99) US (71) Applicant: ESSENTIAL DENTAL SYSTEMS, INC. [US/US]; 89 Leuning Street, South Hackensack, NJ 07606 (US). (72) Inventors: COHEN, Brett, I.; 11 Kevin Court, Nanuet, NY 10954 (US). MUSIKANT, Barry, L.; 124 Churchill Road, Tenafly, NJ 07606 (US). (74) Agent: FRISCIA, Michael, R.; Wolff & Samson, 5 Becker Farm Road, Roseland, NJ 07068-1776 (US).	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	

(54) Title: NON CIRCULAR ENDODONTIC INSTRUMENTS**(57) Abstract**

A non-circular endodontic instrument (110) is provided for reduced stress to the tooth, and to the cutting instrument during the removal of dentin from a root canal. The non-circular endodontic instrument (110) includes at least one area of non-contact (140), i.e., one portion of the instrument does not contact, and does not cut the dentin material. The non-contact area (140) extends the length of the endodontic instrument (110), about a portion of the circumference of the instrument, and interrupts a generally circular cutting face (120) of the instrument. This non-contact area (140) reduces stress, provides a place for debris to gather during cutting so as to not interfere with the cutting face (120), and serves to direct the debris out of the root canal. The endodontic instrument (110) can be D-shaped in cross-section. It could have circumferential opposing non-contact, areas and/or can be elliptical in cross-sectional shape.



NON CIRCULAR ENDODONTIC INSTRUMENTS

SPECIFICATION

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

This invention relates to endodontic instruments having non-circular cross sections, and more specifically, to endodontic instruments for removing pulp tissue and widening root canals, which include cutting surfaces and non-contact surfaces spaced circumferentially about the instruments for decreasing stress and permitting debris to be directed away from the cutting surfaces of the instruments.

RELATED ART

When a diseased root canal (diseased pulp tissue) is found in the root canal of a patient's tooth, a dentist removes the pulp tissue in order to get access to the most apical end of the tooth where bacteria is normally found. Usually a series of files or reamers (hand instruments or rotary instruments) which have a circular cross section are used to both remove the pulp tissue and to widen the root canal. After the tissue is removed, irrigation solutions like Sodium Hypochlorite (NaOCl) are used to kill any remaining bacteria. Then the root canal is filled with gutta-percha and adhesive and sealed-off with such root canal preparations as the one sold by Essential Dental Systems, Inc. under the trademark EZ-Fill. Lastly, a crown could be fitted to the tooth.

The traditional endodontic instrument used to remove pulp tissue or dentin, in the root canal is circular in cross section. As the instrument engages the dentin, it creates a contact surface extending 360 degrees about the narrowest part of the canal. This complete circumferential contact creates resistance to the rotation of the instrument as it removes dentin. The resistance is transferred to both the instrument and the tooth in the form of stress. The greater the resistance, the greater the stress. Because the tooth is much thicker than the reamer or file, it has a minimum chance of distorting or fracturing. The reamer or file, which can be hand or rotary driven however, can easily distort by unwinding when engagement along the shank produces excessive torque generated by

either hand or motor powered rotation. In fact, if rotation with excessive torque continues, the stainless steel reamer can unwind and then fracture. Ni-Ti (Nickel-Titanium) alloy instruments will generally fracture much more abruptly given the same amount torque because the Ni-Ti alloy is more flexible but failure can occur quickly and unpredictably.

One way to reduce the chances of excessive engagement is by using a sequence of ever thickening instruments that remove the dentin in a gradual fashion. In theory, each preceding reamer or file widens the canal enough to allow the incremental removal of dentin with the subsequent reamer or file never creating sufficient engagement for distortion during rotation. This technique is known as step-back because the wider reamers or files are also taken to a shallower depth to further minimize stress and distortion to the instrument.

Another technique employed in endodontics is called crown-down. It employs wider instruments first to open up the coronal aspects of the canal, and subsequently thinner reamers and files are placed more and more apically. Both techniques attempt to reduce the amount of torque generated by limiting the degree of dentin engagement that the reamers and files encounter, to prevent excessive engagement of dentin which leads to distortion and potential fracture of the instruments.

However, the efforts by others in the past have not resulted in an endodontic instrument which reduces in stress in operation based on the geometry of the cutting surfaces of the instrument in relation to non-contact areas positioned circumferentially about the instrument.

Accordingly, what is desirable, and has not heretofore been developed, is the provision of an endodontic instrument which does not make full engagement with the dentin in a root canal during use so that stress is minimized and debris can be directed away from the cutting surfaces of the instrument.

Past efforts in this area, which have not been completely successful in providing stress-reducing endodontic instruments, include the following:

Heath, et al., U.S. Patent No. 5,464,362, discloses a method for fabricating an endodontic instrument by a machining operation wherein a wire-like rod, composed of titanium alloy, is created with a high degree of flexibility, high resistance to torsional

breakage, and sharp cutting edges along the working length. Said cutting edges having either a triangular or helical cross-section.

Weissman, U.S. Patent No. 4,990,088, discloses a multi-functional dental tool having a first pointed end with a first shank cutting section and second, minor diameter shank section for reaming or drilling. Located immediately adjacent to the uppermost second section is a divergent counterbore section. Surrounding the maximum diameter of the counterbore section is an annular cleaner grinding surface and there above a top cutting section extending a relatively short distance above the grinding surface. The cutting portions of the tool include a lower drilling end, a counterbore portion, a larger routing section, and a top cutting section. The tool can be formed having a cross section of various regular polygons as desired, the apices of the polygons providing the cutting edges. The invention further discloses a combination dental tool wherein the shape of a lateral cross section of the first shank is a square or an equilateral polygon.

Arpaio, Jr. et al, U. S. Patent No. 4,934,934, discloses a dental instrument adapted to be used as a dental file and reamer for removing dead or damaged tissue from the root canal of a tooth. The instrument is formed, having at least two helical flutes defining at least two continuous helical cutting edges. A helical peripheral end extends between the helical flutes at the periphery of the shank. The invention discloses an instrument having three or four continuous helical flutes and having helical cutting edges at the periphery of said working portion of said shank equally spaced about the circumference of said shank. The cross-sectional shape of one embodiment is triangular.

Martin, U.S. Patent No. 4,661,061, discloses a dental instrument for performing root canal work. The end or working portion of the instrument is connected to the instrument shaft and is provided with four faces of like size, shape, and orientation, forming a generally square shaped cross-section. The four faces are joined to one another by four edges which meet at a point and are curved in an unbroken line toward each other, whereby when the canal is being rasped the debris is forced out of the canal away from the instrument end.

Leonard, U.S. Patent No. 4,634,378, discloses a dental drill having a triple helicoidal flute and progressive pitch so that the free spaces between the cutting lips increase progressively as they move away from the top of the drill towards the shank. The flutes have cutting lips along peripheral edges thereof for drilling dental canals, and triple flutes at each cross-section of the drill.

Groves, et al., U.S. Patent No. 4,260,379, discloses an endodontic instrument, whereby the file or reamer portion is manufactured by twisting an elongated tapered parallelogram ground bar. The resulting twisted configuration provides a file with a major diameter approximately corresponding to the long diagonal of the parallelogram and a minor diameter corresponding to the short diagonal of the parallelogram. The spiral edges defining the large diameter sections provide the cutting edges whereas the second set of alternating edges defining the reduced diameter sections provide a retaining and debris removal function during operation of the instrument. The result is an endodontic instrument with increased strength and stiffness compared to traditional endodontic instruments.

Daniel, U.S. Patent No. 1,527,845, discloses an improved toothpick with a finger grip element of compressible material anchored to the stock by an attached wired element. The toothpick has a flattened end which can be used as a scraper.

Fowler, U.S. Patent No. 1,067,015, discloses a dental broach which is constructed of flexible steel in order to serve as a nerve extractor and reamer, whereby such construction minimizes the risk of the broach binding or breaking in a root canal. The broach consists essentially of a round, spring-tempered wire. The broach is flattened at one end to form a generally rectangular cross-section, and placed in a suitable holder and by any suitable means turned or rotated to twist the flattened portion while forming a continuous double coil or spiral having continuous longitudinal reaming or cutting edges. This produces an extracting and reaming surface which has a screw-like action when the broach is rotated in a clockwise direction, thus adapting the broach for use in penetrating and cleaning out very small canals without the pressure usually required from conventional broaches.

None of the previous efforts, taken either alone or in combination, teach or suggest the provision of endodontic instrument having a non-circular cross section which

WO 00/51516

PCT/US00/02107

5

includes one or more cutting surfaces and one or more non-contact areas positioned circumferentially about the instrument for reducing stress during the removal of dentin from a root canal, and for directing debris away from the cutting surfaces of the instrument.

OBJECTS AND SUMMARY OF THE INVENTION

It is a primary object of the present invention to provide an endodontic instrument that reduces stress during removal of dentin from a root canal.

It is another object of the present invention to provide an endodontic instrument having a non-circular cross section for reducing stress during removal of dentin material from a root canal.

It is an additional object of the present invention to provide an endodontic instrument having a non-contact area which does not make contact with a tooth and thus reduces stress, during the removal of dentin material from a root canal.

It is an additional object of the present invention to provide an endodontic instrument having a non-circular cross section which provides for a location for debris to collect away from cutting areas.

It is an additional object of the present invention to provide an endodontic instrument having a cutting face that extends only partially circumferentially about the endodontic instrument.

It is another object of the present invention to provide an endodontic instrument having a non-circular cross-section including a generally circular portion truncated by a flat area.

It is an additional object of the present invention to provide a non-circular endodontic instrument having an elliptical cross-section.

It is still even another object of the present invention to provide an endodontic instrument having two cutting areas on opposing sides of the instrument and two non-contact areas, positioned between the cutting areas, on opposing sides of the instrument.

These and other objects of the present invention are achieved by providing an endodontic instrument having a non-circular cross section. Preferably, the endodontic instrument of the present invention includes a non-contact area extending the length of the endodontic instrument which interrupts the generally circular cutting face of the instrument. The non-contact area does not make contact with the tooth during removal of dentin material and therefor decreases stress to the tooth and the endodontic instrument. The non-contact area also provides a place for debris to gather during cutting so as not to interfere with the cutting face, and serves to direct the debris out of the root canal.

In a preferred embodiment, the endodontic instrument of the present invention provides for a cutting surface or face that is generally circular in cross-section and extends about a portion the circumference of the instrument, but is interrupted, at one circumferential location, by a non-contact face, which extends the length of the instrument. The instrument can have more than one non-contact area and/or more than one cutting surface. The cutting surface includes helically extending cutting blades as is known in the art. The relative size of the cutting face (faces) versus the non-contact face (faces) can be varied as desired.

In another embodiment, the endodontic instrument comprises two generally curved cutting faces positioned in a circumferentially opposing relationship along the length of the instrument, and two non-contact faces positioned between the cutting faces.

In yet another embodiment, the instrument can be generally elliptical in cross-sectional shape.

Importantly, the present invention provides for reduced stress to the tooth and to the cutting instrument during the removal of dentin from a root canal, and does so by providing at least one area of non-contact, i.e. one portion of the instrument does not contact and does not cut the dentin material, but is recessed back from the general cross-sectional shape of the device to reduce stress to the tooth, maintain debris away from the cutting face of the device and to reduce instrument failure.

BRIEF DESCRIPTION OF THE DRAWINGS

Other important objects and features of the invention will be apparent from the following Detailed Description of the Invention taken in connection with the accompanying drawings in which:

FIG. 1 is a perspective view of a prior art endodontic instrument.

FIG. 2 is a cross-sectional view of the device shown in **FIG. 1** taken along the lines 2-2.

FIG. 3 is a perspective view of an endodontic instrument of the present invention having a cutting surface and a non-contact area.

FIG. 4 is a cross-sectional view of the device shown in **FIG. 1** taken along the line 4-4.

FIG. 5 is a view of the endodontic shown in **FIG. 3** having a larger non-contact area.

FIG. 6 is a cross-sectional view of the device shown in **FIG. 5** taken along the line 6-6.

FIG. 7 is a perspective view of another embodiment of an endodontic instrument according to the present invention having two cutting surfaces and two non-contact areas.

FIG. 8 is a cross-sectional view of the device shown in **FIG. 7** taken along line 8-8.

FIG. 9 is a perspective view of another embodiment of an endodontic instrument according to the present invention having an elliptical cross-sectional shape.

FIG. 10 is a cross-section view of the device of **FIG. 9** taken along line 10-10.

DETAILED DESCRIPTION OF THE INVENTION

Referring to **FIG. 1**, an endodontic instrument according to prior art is shown. The endodontic instrument is generally indicated at **10**, and has a cutting surface **20** comprising cutting blades **30**. The endodontic instrument **10** extends from an upper end **12** to a pointed lower end **14**. Cutting blades **30** extend helically along the instrument **10** from the upper end **12** to the lower end **14**.

Referring to **FIG. 2**, which is a cross-section of taken along the line 2-2 of **FIG. 1**, the endodontic instrument **10** is shown to include a cutting surface **20**. The cutting blades **30** extend to a depth indicated by broken line **32**. As can be seen, the cutting surface **20** extends entirely circumferentially around the instrument **10**, and the instrument is generally circular in cross-section. In use, the instrument **10** engages the root canal at all aspects around the circumference of the instrument resulting in maximum stress to the tooth (not shown) and the instrument **10** during use.

Referring now to **FIG. 3**, an endodontic instrument according to the present invention is shown at **110**. The instrument **110** includes an upper end **112** which tapers down along a length to a generally pointed lower end **114**. The device includes a cutting surface **120** comprised of cutting blades **130** which extend helically along the cutting surface **120**. The cutting surface **120** extends along the length of the instrument **110** about a portion of the circumference of the instrument **110**. A non-contact area **140** also extends along the length of the instrument **110** about a portion of the circumference of the instrument **110**.

Referring to **FIG. 4**, which is a cross-sectional view of the instrument **110** taken along the line 4-4, it can be seen that the cutting blades **130** extend interiorly of the cutting surface **120** of the instrument **110** to depth indicated by broken line **132**. **FIG. 4** also clearly shows the non-contact area **140** defining a portion of the cross-section of the instrument **110**, resulting in an overall non-circular cross-section for the instrument **110**. The non-contact area **140** is interconnected with the cutting face **120** at juncture points **142** and **144**. It can be seen that the instrument **110** is non-circular in cross-section, having generally, a D-shape.

In use, when the instrument **110** is inserted into a canal (not shown) and rotated, the cutting surface **120** with the cutting blades **130** engages the canal and removes dentin

therefrom. The non-contact area **140** of instrument **110** does contact the canal area and thus reduces the stress caused by the engagement of the cutting face **120** with the canal.

The non-contact area **140** also provides an area for debris to gather and be maintained out of the way of cutting face **120**. Cutting is performed by the cutting blades **130** on cutting face **120**. The resultant shape of the cut is circular in cross-section because the instrument **110** is axially rotated.

Referring to **FIG. 5**, a device similar to that of **FIG. 3** is shown, except that the non-contact area **140** is of a greater dimension, and consequently the cutting face **120** is of a smaller dimension. Such an instrument **110** would serve to reduce stress to a larger extent based on the fact that the non-contact area is larger. **FIG. 6** is a cross-sectional view of the instrument **110** shown in **FIG. 5** taken along line 6-6. Accordingly, it should be pointed out that the relative sizes of the contact surfaces **120** and non-contact area **140** can be varied as desired to produce a desired result. Further, it should be pointed out that the cutting surface **120** can employ any known cutting means, including helical cutting blades **130**, or any other known cutting means.

Referring to **FIG. 7**, another embodiment of the endodontic instrument of the present invention is shown where the endodontic instrument, generally indicated at **310**, includes two cutting faces **320** extending along the length of the instrument **310** at opposite circumferential sides of the device. The cutting faces **320** include cutting blades **330** extending helically along the cutting faces **320**. Two non-contact areas **340** comprising flat surfaces without cutting blades, extend along the length of the instrument **310** at opposite circumferential sides of device, interconnecting with the cutting faces at juncture edges **342** and **344**.

This arrangement of cutting faces **320** and non-contact faces **340** of instrument **310** can be clearly seen in **FIG. 8**, which is a cross-sectional view along line 8-8, of the instrument **310** shown in **FIG. 7**. As can be seen, cutting faces **320** are found on opposite sides of the circumference of the instrument **310**. Likewise, non-contact areas **340** are positioned on opposite sides of the circumference of the instrument **310**. The non-contact areas **340** are positioned between the cutting surfaces **320**. The cutting surfaces **320** have helical cutting blades **330**, which extend inwardly from the surfaces of the cutting face **320** to broken line **332**. Alternatively, the cutting face **320** can utilize any cutting means

known in the art.

Importantly, the instrument **310** has a non-circular cross-section shape including cutting surfaces **320** and non-contact surfaces **340**. The non-contact surfaces **340** serve to reduce stress during use, and also serve to maintain cut debris out of the way of cutting surfaces **320**. It should be pointed out that other geometric arrangements of cutting surfaces and non-contact surfaces positioned along an endodontic instrument, resulting in an instrument having non-circular cross-section, are considered within the scope of the present invention.

Referring now to **FIGS. 9** and **10**, another embodiment of the instrument of the present invention is shown having an elliptical shape. The instrument, generally indicated at **410**, includes an upper end **412** and a lower end **414** and a length tapering from the upper end **412** to lower end **414**. The instrument **410** includes ends A and sides B. The end portions A comprise the cutting faces **420**, and the long side portions B comprise the non-contact areas **440**. Cutting blades **430** extend about the instrument **410**. The cutting blades extend into the instrument to a depth shown by phantom line **432**. As the endodontic instrument **410** is rotated, it will remove dentin in a circular cross-sectional shape, but during use, only the edge portions A comprising the cutting faces **420** will engage the canal and the long side areas B comprising non-contact areas **440** will not engage the canal, thereby reducing stress and directing debris away from the cutting faces **420**. Again, the instrument is non-circular in cross-section. It should be noted that the specific cross-section geometry can be varied as desired in accordance with the present invention.

Having thus described the invention in detail, it is to be understood that the foregoing description is not intended to limit the spirit and scope thereof. What is desired to be protected by Letters Patent is set forth in the appended claims.

CLAIMSWhat is claimed is:

1. An endodontic instrument comprising:
 - an upper end;
 - a pointed lower end;
 - a length extending from near the upper end to the pointed lower end, the length tapering from the upper end to the lower end;
 - a non-circular circumference;
 - a cutting surface extending along the length of the instrument about a first portion of the circumference; and
 - a flat non-contact area extending uninterrupted along the length of the instrument to the pointed end about a second portion of the circumference.
2. The instrument of claim 1 wherein the circumferential shape of the cutting surface is generally circular.
3. The instrument of claim 2 wherein the cross-section of the instrument is D-shaped.
4. The instrument of claim 3 wherein the cutting surface includes cutting blades.
5. The instrument of claim 4 wherein the cutting blades helically extend along the cutting surface.
6. An endodontic instrument comprising:
 - an upper end;
 - a pointed lower end;
 - a length extending from near the upper end to the lower end and tapering therealong; and
 - a non-circular circumferential cross-section including at least one flat non-contact area extending uninterrupted along the length to the pointed lower end.
7. The instrument of claim 6 wherein the cross-section comprises a generally circular portion, with cutting blades, and said flat portion interrupting the generally circular portion.
8. The instrument of claim 7 wherein the cross-section comprises opposing generally circular portions with cutting blades and opposing flat portions positioned between the generally circular portions.

9. **A non-circular endodontic instrument comprising:**
a length tapering from near an upper end to a pointed lower end, the length having a non-circular circumferential cross-section;
a cutting surface extending along the length about a portion of the circumferential cross-section, the cutting surface having helical cutting blades extending therealong;
a flat non-contact area extending uninterrupted along the length to the pointed lower end about a portion of the circumferential cross-section;
the cutting surface being generally circular in circumferential cross-section;
the non-contact area being linear in circumferential cross-section;
whereby the instrument is insertable into a root canal and rotatable therein to remove dentin by rotational contact of the cutting surface with a portion of the root canal wall, while the non-contact area remains away from the root canal wall thereby providing an area for debris to accumulate away from the cutting surface.
10. **The instrument of claim 9 wherein the cross-section of the instrument is D-shaped.**
11. **The instrument of claim 9 wherein the device further comprises a second cutting area and a second flat non-contact area.**
12. **The instrument of claim 11 wherein the second cutting surface is positioned opposite the cutting surface about the circumferential cross-section.**
13. **The instrument of claim 12 wherein the second flat non-contact area is positioned opposite the flat non-contact area about the circumference.**
14. **The instrument of claim 1 wherein the flat non-contact area has a taper corresponding to the taper of the length.**
15. **The instrument of claim 1 wherein the flat non-contact area extends to the center axis of the instrument.**

FIG. 1
(PRIOR ART)




FIG. 3




FIG. 5




FIG. 2
(PRIOR ART)




FIG. 4




FIG. 6




FIG. 7




FIG. 9




FIG. 8




FIG. 10

