



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number: **0 437 507 B1**

EUROPEAN PATENT SPECIFICATION

④ Date of publication of patent specification: 19.01.94 ⑤ Int. Cl. 5: **G03B 13/12**

⑥ Application number: **89911660.2**

⑦ Date of filing: **04.10.89**

⑧ International application number:
PCT/US89/04344

⑨ International publication number:
WO 90/04199 (19.04.90 90/09)

⑩ CAMERA VIEW FINDER.

⑪ Priority: **07.10.88 US 255187**

⑫ Date of publication of application:
24.07.91 Bulletin 91/30

⑬ Publication of the grant of the patent:
19.01.94 Bulletin 94/03

⑭ Designated Contracting States:
DE FR GB

⑮ References cited:
GB-A- 1 509 882
US-E- 30 231

PATENT ABSTRACTS OF JAPAN, vol. 6, no.
217 (P-152)(1095), 30 October 1982 ; & JP-
A-57122422

⑯ Proprietor: **EASTMAN KODAK COMPANY**
343 State Street
Rochester, New York 14650-2201(US)

⑰ Inventor: **GATES, Richard, Allen**
169 Sherwood Drive
Hilton, NY 14468(US)
Inventor: **STONEHAM, Jeffrey, Richard**
776 Stony Point Road
Spencerport, NY 14559(US)

⑱ Representative: **Blickle, K. Werner, Dipl.-Ing. et**
al
KODAK AKTIENGESELLSCHAFT
Patentabteilung
D-70323 Stuttgart (DE)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

CROSS-REFERENCE TO RELATED APPLICATIONS

Reference is made to commonly assigned European application now published under No. EP-A-0 363 850 "Camera view finder".

TECHNICAL FIELD

The present invention relates to view finder devices for use in cameras and more particularly to an improved view finder device in which a plurality of lenses can be selectively positioned in a viewing position.

BACKGROUND ART

Mechanisms are known which change the magnification of a view finder in cameras having more than one photographic lens and in cameras for producing special effects such as pseudo tele or pseudo pan. However, in general, such mechanisms are complicated and capable of providing only two levels of magnification.

In copending application EP-A-0 363 850 referenced above, a view finder is disclosed which comprises three lenses mounted for pivotal movement about three separate axes respectively. Cam means are provided for moving the respective lenses between a common viewing position and separate folded positions.

DISCLOSURE OF THE INVENTION

The invention discloses an apparatus for selectively positioning one of three lenses into an optical path, said apparatus is defined in claim 1.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and advantages of the invention will become apparent from the following description taken in connection with the accompanying drawings wherein:

FIG. 1 is a partially exploded perspective view of a view finder device in accordance with the invention; and

FIGS. 2, 3 and 4 are plan views of the apparatus shown in FIG. 1 showing the parts in three different positions.

BEST MODE FOR CARRYING OUT THE INVENTION

Referring to the drawings, there is shown a view finder device for a photographic camera. To

simplify the disclosure, camera parts not necessary for an understanding of the invention have been omitted. For example, the eye lens and front element are not shown and the disclosure is limited to apparatus for moving the movable lens element.

Referring to FIG. 1 of the drawings, there is shown a view finder 10 comprising three lenses (tele, pan and normal) mounted in frames 20, 22 and 24 respectively. Each of the frames 20, 22 and 24 are of rectangular configuration and mounted for rectilinear movement in a supporting structure 26.

The supporting structure 26 which would be part of a camera housing (not shown) comprises a bottom supporting plate 28 and a box-like structure 30 formed on one end of the plate 28. A viewing window 32 framed in the structure defines a viewing axis with which the lens frames 20, 22 and 24 are selectively aligned.

The lens frame 20 (tele) is mounted for rectilinear sliding movement in supporting structure 26. The bottom segment of the frame is provided with a pair of spaced pins 34 (one of which is visible in FIG. 1) and the upper segment is provided with a pair of spaced pins 38 and 40. The bottom pins are positioned in a bottom track 42 and the upper pins are received in an upper track 44. Both tracks comprise slots formed in rails extending from surfaces of supporting structure 26. The upper pin 38 extends beyond the upper end of track 44 to serve as a cam pin as will later be described. A flange 46 extending perpendicular from the left end of frame 20 functions as a cam for displacing frame 22 as will be described below.

Frame 22 (pan) similar to frame 20 includes a pair of bottom pins (not shown) received by a lower track (not shown) and a pair of upper pins 54 and 56 received by a track 58. A spring 59 connected between the right end of frame 22 and a fixed surface of structure 26 serves to bias frame 22 to the right.

Frame 24 (normal) similarly comprises a pair of lower pins 60 received by a track 64 and a pair of upper pins 66 and 68 received by an upper track 70. The pin 66 extends above the end of track 70 and functions as a cam pin as will be described below. The frame 24 is supported to engage and displace frame 22 to the left against the bias of spring 59 as discussed below.

The three frames are thus mounted for rectilinear movement in respective parallel planes by means of the described pins and tracks. The cam means for positioning the frames includes a pivotal lever 72 supported by a pivot pin 74 fixed to housing 26 adjacent to slot 44. The lever 72 has an elongated slot 76 in one end which receives pin 66 of frame 24 and has a cam pin 78 extending outward from its opposite end.

A second pivotal lever 80 is pivotally mounted at one end of the upper wall of structure 30 by means of a pin 82 and has a slot 84 in its opposite end which receives cam pin 38 of frame 20. A cam pin 86 extends upward from the central portion of lever 80.

The cam means further includes a plate 88 slideably mounted for rectilinear movement on the structure 26. The plate 88 is received in slots 90 and 92 defined by respective guides 94 and 96 attached to the structure 26. The plate 88 is movable rectilinearly relative to the structure 26 in the direction indicated.

The plate 88 is provided with two cam slots 98 and 100 for positioning the frames 20, 22 and 24. Each slot includes a elongated straight portion (a) and a cam portion (b) extending at right angles to portion (a). The slot 98 receives cam pin 86 of lever 80 and slot 100 receives cam pin 78 of lever 72.

In operation, the parts will assume the positions shown in FIGS. 1 and 2 when the pan lens frame 22 is aligned with the viewing window 32. In this condition, frames 20 and 24 will be displaced to the right of the viewing axis as shown and pins 38 and 66 will be near the ends of their respective slots 84 and 76.

If plate 88 is moved to the left from the central position shown in FIGS. 1 and 2 to the position shown in FIG. 3, pin 86 will be displaced into the cam portion (b) of slot 98 and lever 80 will be pivoted counterclockwise causing pin 38 to displace frame 20 to the left into the viewing position. The flange 46 will engage frame 22 and move it out at the viewing position against the bias of spring 59. Pin 78 will ride in the straight portion (a) of slot 100 and no movement of frame 24 will occur.

If the plate 88 is returned to the position shown in FIGS. 1 and 2 from the position shown in FIG. 3, the parts will move in the opposite direction. In this case, spring 59 will position frame 22 back into the viewing position.

If the plate 88 is moved to the right from the position shown in FIGS. 1 and 2 to the position shown in FIG. 4, pin 78 will be moved into the cam portion (b) of slot 100 to pivot lever 72 counterclockwise. Such motion will cause lens frame 24 to be moved to the left into the viewing position. In this case, lens frame 24 will engage lens frame 22 and move it to the left out of the viewing position. No movement of lens frame 20 will occur because pin 86 will ride in the straight portion (a) of slot 98. Upon return of the plate to the position shown in FIGS. 1 and 2, the spring 59 will again return frame 22 to the viewing position.

It will now be apparent that the disclosed embodiment of the invention enables three lenses to

be selectively positioned in a viewing position using simple rectilinear movements effected by a unique cam means. In addition, the assembly is compact and will have little effect on camera size.

While the invention has been shown and described with reference to a preferred embodiment thereof, it will be apparent that various changes may be made without departing from the scope of the invention as defined by the appended claims.

Claims

1. Apparatus for selectively positioning one of three lenses into an optical path, said apparatus comprising:
 - first, second and third lens frames (20, 22, 24) each arranged to support a lens;
 - means (26, 28, 46, 64) for guiding and supporting said frames (20, 22, 24) in positions substantially parallel to one another and for enabling rectilinear movement of each frame (20, 22, 24) between a respective first position, where it is out of the optical path, and a respective second position, where it is in the optical path; and means for moving said lens frames between their first and second positions, such that only one frame (20, 22, 24) can ever be in its second position, one of the frames (22) being urged by resilient means (59) to stay in its second position, but being pushed to its first position by either of the other two frames (20, 24) when either one of the latter is moved to its second position; said apparatus being characterized in that said moving means comprises:
 - first cam means (38, 66) extending from said other two frames (20, 24);
 - two pivotable levers (72, 80) each having cam slots (76, 84) engaging said first cam means (38, 66);
 - second cam means (78, 86) extending from each of said levers; and a translatable cam element having cam slots engaging said second cam means (78, 86) extending from each of said levers (76, 84), the position of said translatable cam element determining the position occupied by said other two lens frames.
2. Apparatus as claimed in Claim 1 wherein said first (38, 66) and said second (78, 86) cam means comprises cam pins extending from said two frames (20, 24) and said two pivotable levers (76, 84) respectively.
3. Apparatus as claimed in Claim 1 or 2 wherein said means for simultaneously moving comprises a slidable plate (88) having two cam

slots (98, 100) for receiving said second cam means (78, 86) extending from each of said levers (76, 84) respectively.

4. Apparatus as claimed in Claim 3 wherein said plate (88) has a central position, wherein one of said frames is in the optical path, and is moveable in one direction to a second position, to position another frame in the optical path and, and in the opposite direction to a third position to position still another of said frames in the optical path.

5. Apparatus as claimed in Claim 4 wherein said frames (20, 22, 24) are positioned in substantially parallel planes and said supporting means (26, 28) comprise a track like structure for moveably supporting said frames in said parallel planes.

Patentansprüche

1. Vorrichtung zum wahlweisen Positionieren einer von drei Linsen in einem optischen Strahlengang mit
einer ersten, einer zweiten und einer dritten jeweils zum Lagern einer Linse vorgesehenen Linsenhalterung (20, 22, 24),
Mitteln (26, 28, 46, 64), die die Halterungen (20, 22, 24) führen und im wesentlichen parallel zueinander halten und eine geradlinige Bewegung einer jeden Halterung (20, 22, 24) zwischen einer ersten Stellung, in der sie sich außerhalb des optischen Strahlengangs befindet, und einer zweiten Stellung, in der sie sich innerhalb des optischen Strahlengangs befindet, ermöglichen, sowie Mitteln, die die Linsenhalterungen zwischen ihrer ersten und zweiten Stellung derart bewegen, daß sich immer nur eine Halterung (20, 22, 24) in der zweiten Stellung befinden kann, wobei eine der Halterungen (22) durch Federmittel (59) in die zweite Stellung vorgespannt ist, jedoch von einer der beiden anderen Halterungen (20, 24) in die erste Stellung schiebbar ist, wenn eine dieser anderen Halterungen in ihre zweite Stellung bewegt wird, **dadurch gekennzeichnet, daß**

die Bewegungsmittel erste aus den beiden Halterungen (20, 24) herausragende Steuermittel (38, 66) umfassen sowie zwei Schwenkhebel (72, 80) aufweisen, die jeweils mit den ersten Steuermitteln (38, 66) in Eingriff stehende Führungsschlitze (76, 84) enthalten, und zweite aus je einem der Hebel herausragende Steuermittel (78, 86) aufweisen, und daß ein translatorisch bewegbares Steuerelement vorgesehen ist, das Führungsschlitze enthält, die

mit den jeweils aus den Hebeln (76, 84) herausragenden zweiten Steuermitteln (78, 86) in Eingriff gehalten sind, wobei die Stellung des translatorisch bewegbaren Steuerelements die jeweils von den beiden anderen Linsenhalterungen eingenommene Stellung bestimmt.

2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die ersten (38, 66) und zweiten (78, 86) Steuermittel jeweils Steuerstifte aufweisen, die aus den beiden Halterungen (20, 24) bzw. aus den beiden Schwenkhebeln (76, 84) herausragen.

3. Vorrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die eine Simultanbewegung bewirkenden Mittel aus einer verschiebbaren Platte (88) mit zwei Führungsschlitzen (98, 100) bestehen, in die die aus jedem der Hebel (76 bzw. 84) herausragenden zweiten Steuermittel (78, 86) eingreifen.

4. Vorrichtung nach Anspruch 3, dadurch gekennzeichnet, daß die Platte (88) eine mittlere Stellung besitzt, in der sich eine der Halterungen im optischen Strahlengang befindet und in einer Richtung in eine zweite Stellung bewegbar ist, in der sie eine andere Halterung im optischen Strahlengang positioniert, und daß sie in der entgegengesetzten Richtung in eine dritte Stellung bewegbar ist, in der sie wiederum eine andere Halterung im optischen Strahlengang positioniert.

5. Vorrichtung nach Anspruch 4, dadurch gekennzeichnet, daß die Halterungen (20, 22, 24) in im wesentlichen parallel verlaufenden Ebenen angeordnet sind und die Führungs- und Haltemittel (26, 28) ein schienentartiges Teil umfassen, auf dem die Halterungen in den parallel verlaufenden Ebenen bewegbar gelagert sind.

Revendications

1. Dispositif pour disposer à volonté l'une de trois lentilles sur un trajet optique, dispositif comprenant :

un premier, un second et un troisième barillets (20, 22, 24), chacun agencé de manière à supporter une lentille,

un moyen (26, 28, 46, 64) pour guider et supporter lesdits barillets (20, 22, 24) dans des positions pratiquement parallèles les unes aux autres afin de permettre des déplacements rectilignes de chaque barillet (20, 22, 24) entre une première position respective, où le barillet correspondant n'est pas sur ledit trajet optique, et une seconde position respective, où ledit

barillet correspondant est situé sur ledit trajet optique ; et un moyen pour déplacer lesdits barillets entre leur première et seconde positions, de manière que seul l'un des barillets (20, 22, 24) puisse être disposé dans sa seconde position, l'un desdits barillets (22) étant sollicité pour des moyens déformables (59) pour rester dans sa seconde position, mais étant poussé dans sa première position par l'un quelconque des deux autres barillets (20, 24) lorsque l'un quelconque d'entre eux est disposé dans sa seconde position ; ledit dispositif étant caractérisé en ce que le moyen pour déplacer lesdits barillets comprend :

un premier agencement servant de came (38, 66) s'étendant à partir desdits deux autres barillets (20, 24), deux leviers (72, 80) articulés, chacun muni de fentes (76, 84) servant de came et venant en prise avec ledit premier agencement (38, 66) ;

un second agencement servant de came (78, 86) s'étendant à partir de chacun desdits leviers articulés ; et un organe à mouvement de translation servant de came et possédant des fentes servant de cames venant en prise avec ledit second agencement servant de came (78, 86) et s'étendant à partir de chacun desdits leviers (76, 84), la position dudit organe déterminant la position occupée par lesdits deux autres barillets.


2. Dispositif selon la revendication 1, dans lequel le premier (38, 66) et le second (78, 86) agencements servant de came comprennent des tétons débordant lesdits deux autres barillets (20, 24) et lesdits deux leviers articulés (76, 84) respectivement.

3. Dispositif selon l'une des revendications 1 ou 2, dans lequel le moyen pour déplacer comprend une plaque (88) coulissante présentant deux fentes (98, 100) servant de came et agencées pour recevoir ledit second agencement (78, 86) servant de came et s'étendant à partir desdits leviers (76, 84) respectivement.

4. Dispositif selon la revendication 3, dans lequel la plaque (88) occupe une position centrale dans laquelle l'un des barillets est situé sur le trajet optique et, peut être déplacée dans une première direction vers une seconde position de manière à disposer un autre barillet sur le trajet optique et, peut être déplacée dans une seconde direction opposée à la première direction vers une troisième position pour disposer encore un autre barillet sur le trajet optique.

5. Dispositif selon la revendication 4, dans lequel les barillets (20, 22, 24) sont situés dans des plans pratiquement parallèles et le moyen pour supporter lesdits barillets (26, 28) comprend une structure analogue à une piste pour supporter lesdits barillets de manière mobile dans lesdits plans parallèles.

FIG. 1






FIG. 2




FIG. 3




FIG. 4

REGISTER ENTRY FOR EP0437507

European Application No EP89911660.2 filing date 04.10.1989

Priority claimed:

07.10.1988 in United States of America - doc: 255187

PCT EUROPEAN PHASE

PCT Application PCT/US89/04344 Publication No WO90/04199 on 19.04.1990

Designated States DE FR GB

Title CAMERA VIEW FINDER.

Applicant/Proprietor

EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York 14650, United States of America [ADP No. 56832066001]

Inventors

ALLEN RICHARD GATES, 169 Sherwood Drive, Hilton, NY 14468, United States of America [ADP No. 58757154001]

RICHARD JEFFREY STONEHAM, 776 Stony Point Road, Spencerport, NY 14559, United States of America [ADP No. 58757360001]

Classified to

G03B

Address for Service

P A C BARON, KODAK LIMITED, Patent Department, Headstone Drive, HARROW, Middlesex, HA1 4TY, United Kingdom [ADP No. 00026443002]

EPO Representative

DIPL.-ING. K. WERNER BLICKLE, KODAK AKTIENGESELLSCHAFT Postfach 600345, W-7000 Stuttgart-Wangen 60, Federal Republic of Germany [ADP No. 50936814001]

Publication No EP0437507 dated 24.07.1991

Publication in English

Examination requested 04.04.1991

Patent Granted with effect from 19.01.1994 (Section 25(1)) with title CAMERA VIEW FINDER.

17.12.1993 Notification from EPO of change of Applicant/Proprietor details from

EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York 14650, United States of America [ADP No. 56832066001]

to

EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York 14650-2201, United States of America [ADP No. 56832066001]

Entry Type 25.14 Staff ID. RD06 Auth ID. EPT

REGISTER ENTRY FOR EP0437507 (Cont.)

TIMED: 09/02/94 11:32:42

PAGE: 2

17.12.1993 Notification from EPO of change of EPO Representative details from
DIPL.-ING. K. WERNER BLICKLE, KODAK AKTIENGESELLSCHAFT Postfach
600345, W-7000 Stuttgart-Wangen 60, Federal Republic of Germany
[ADP No. 50936814001]

to

DIPL.-ING. K. WERNER BLICKLE, KODAK AKTIENGESELLSCHAFT,
Patentabteilung, D-70323 Stuttgart, Federal Republic of Germany
[ADP No. 50936814001]

Entry Type 25.14 Staff ID. RD06 Auth ID. EPT

**** END OF REGISTER ENTRY ****

OA80-01
EP

OPTICS - PATENTS

09/02/94 11:33:38
PAGE: 1

RENEWAL DETAILS

PUBLICATION NUMBER

EP0437507

PROPRIETOR(S)

EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York
14650-2201, United States of America

DATE FILED

04.10.1989 ✓

DATE GRANTED

19.01.1994 ✓

DATE NEXT RENEWAL DUE

04.10.1994

DATE NOT IN FORCE

DATE OF LAST RENEWAL

YEAR OF LAST RENEWAL

00

STATUS

PATENT IN FORCE ✓