




(86) **Date de dépôt PCT/PCT Filing Date:** 2011/08/23  
 (87) **Date publication PCT/PCT Publication Date:** 2012/03/01  
 (45) **Date de délivrance/Issue Date:** 2017/11/28  
 (85) **Entrée phase nationale/National Entry:** 2013/02/21  
 (86) **N° demande PCT/PCT Application No.:** NZ 2011/000165  
 (87) **N° publication PCT/PCT Publication No.:** 2012/026831  
 (30) **Priorité/Priority:** 2010/08/25 (US61/376,894)

(51) **Cl.Int./Int.Cl. A41C 3/00** (2006.01)  
 (72) **Inventeur/Inventor:**  
 SHEARER, RICHARD HEUGHAN, NZ  
 (73) **Propriétaire/Owner:**  
 QP HOLDINGS LIMITED, NZ  
 (74) **Agent:** HILL & SCHUMACHER

(54) **Titre : UN SOUTIEN-GORGE**  
 (54) **Title: A BRA**



(57) **Abrégé/Abstract:**

A sport motion control bra having a pair of partial cups which locate, support and shape the lower periphery of the breasts of a user so as to effectively restrict the motion of the breasts relative to the body of a user during sporting activities and one or more side

**(57) Abrégé(suite)/Abstract(continued):**

straps which connect to wings extending from each cup so as to, in use, support and locate the sides of the cups. A sport impact protection and motion control bra including a pair of cups dimensioned to encompass the majority of the breasts of a user. The cups are configured to effectively transfer local impact force through the cup to be dissipated through the bra and surrounding breast tissue and restrict motion of the breasts relative to the body of a user. The lower edge of each cup may include an inflexion section extending between the torso and breast sections of the bra.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
1 March 2012 (01.03.2012)(10) International Publication Number  
**WO 2012/026831 A3**(51) International Patent Classification:  
*A41C 3/00* (2006.01)(21) International Application Number:  
PCT/NZ2011/000165(22) International Filing Date:  
23 August 2011 (23.08.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
61/376,894 25 August 2010 (25.08.2010) US(71) Applicant (for all designated States except US): **QP HOLDINGS LIMITED** [NZ/NZ]; c/- Busing Russell + Co Limited, 369 Devon Street East, New Plymouth (NZ).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SHEARER, Richard Heughan** [NZ/NZ]; 13a Shearer Drive, Oakura, Taranaki (NZ).(74) Agents: **ELLIS | TERRY** et al.; PO Box 10 932, The Terrace, Wellington 6143 (NZ).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: A SPORTS MOTION CONTROL BRA




Figure 1

(57) Abstract: A sport motion control bra having a pair of partial cups which locate, support and shape the lower periphery of the breasts of a user so as to effectively restrict the motion of the breasts relative to the body of a user during sporting activities and one or more side straps which connect to wings extending from each cup so as to, in use, support and locate the sides of the cups. A sport impact protection and motion control bra including a pair of cups dimensioned to encompass the majority of the breasts of a user. The cups are configured to effectively transfer local impact force through the cup to be dissipated through the bra and surrounding breast tissue and restrict motion of the breasts relative to the body of a user. The lower edge of each cup may include an inflexion section extending between the torso and breast sections of the bra.

**WO 2012/026831 A3**



---

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

**(88) Date of publication of the international search report:**  
19 April 2012

**A BRA****FIELD OF THE INVENTION**

- 5 This invention relates to a bra. More particularly, although not exclusively, the invention relates to a sport motion control and/or impact protection bra.

**BACKGROUND OF THE INVENTION**

- 10 A wide range of bras have been produced for general use, typically with the aim of providing a basic level of support and to achieve aesthetic outcomes in relation to breast form and the appearance of the bra itself. Such "general use" bras typically provide sub-optimal impact protection and breast motion control.

15

**Static Support and Shaping**

- With a traditional fabric bra, support is provided by positioning of the breast relative to the body of the wearer and influencing the shape of the breast through the application of a flexible boundary in the form of a flexible fabric cup. Positioning of the breast above its natural position is termed uplift. With a traditional fabric bra uplift is often achieved by tensioning of the shoulder strap of the bra. An alternate mechanism for uplift is to provide inserts in the lower portion of the bra cup that displace the breast.

25

- With a traditional fabric bra uplift is achieved by tensioning the fabric of the cup between its lower edge (often the location of an underwire) and the shoulder strap, to a position where there is no overlap of the breast tissue with the torso of the wearer.

30

With a traditional fabric bra the resulting shape of the breast is a function of the volume and geometry of the breast, the degree of uplift / material tension and the shape and construction of the flexible fabric cup. As the optimum position of the breast varies between individuals the degree of uplift required and the resulting shape is likely to be different for each wearer of a particular  
5 bra. This contributes to significant industry-wide challenges of fit and bra choice.

### **Motion Control**

10

Control of motion of the breasts during activity is important. Motion of the breasts relative to the body can cause breast pain and longer term can lead to deterioration of the natural support mechanisms for the breasts. These factors can have a negative impact on the participation of women in sports and other  
15 activities.

With a traditional fabric bra motion control of the breast during activity is achieved through provision of a flexible boundary in the form of a fabric cup. Typically improved motion control is achieved through compression (where  
20 the breast is compressed against the torso) or encapsulation (where the breast is held by an inelastic cup form). Of these mechanisms encapsulation is generally preferred as it does not affect the mobility and ability to breathe of the wearer.

25 A further element that is typically used to provide location and motion control of the breast is an underwire which forms a rigid narrow boundary around the lower periphery of the fabric cup.

The motion control performance of a traditional fabric bra is limited by the  
30 shape and positioning of the breast relative the body of the wearer and the

construction of the bra. As a flexible cup cannot maintain geometry of the breast, movement of the breast mass can occur within the cup itself. The motion-control performance of the bra is subject to the same vagaries as outlined for static support.

5

### **Impact Protection**

The participation of women in activities where there is a probability of physical impact on the breast, such as soccer, is increasing. Physical impact  
10 on the breast can cause short-term pain and bruising which may have an impact on participation and confidence.

With a traditional fabric bra the breasts are provided minimal protection against physical impacts and associated pain and bruising often experienced  
15 during sporting activity.

In summary traditional fabric bras do not perform at an optimum level for a broad variety of wearers. This can result in breast compression, discomfort, pain, undesirably and unconstrained motion, undue load on the shoulders.  
20 Such bras also provide little impact protection and limited motion control (typically only about 50% over all three dimensions compared to a no-bra condition). Underwire bras provide location of the bra around the lower periphery of the breast but do not significantly contribute to breast support, uplift, motion control or shaping.

25

Some bras have been developed that have removable cups or cup inserts. Bras including removable cups are inconvenient and difficult to integrate into the bra structure and provide sub-optimal performance. Multiple material structures are complex and expensive to construct.

30

Specific impact protection and/or sports bras can provide good protection and motion control but are typically rigid, bulky, unfashionable, inhibit movement and/or restrict breathing. In sports such as soccer a combination of impact and motion control may be required whereas in other activities one  
5 or other may suffice.

**US2061268** discloses a moulded full-cup structure which holds a breast in a preferred shape.

10 **GB496777** discloses a chest and part-cup cantilever structure comprising of a laminate of fabric and polymer.

**GB590284** discloses a plastic shaped cup reinforcing element.

15 **US2429680** discloses an independent pallet / shelf comprising a single piece part-cup and underband structure.

**US3225768** discloses a method of laminating a plastic breast form to fabric to create a 3-d shaped article of clothing.

20

**US6431946** discloses an underwire structure that extends into the cup of the bra.

**US6439959** discloses a multiple-piece or single piece plastic form structure  
25 for a bra made of soft, flexible foam.

**US6447365** discloses a rigid underwire structure that is incorporated into a soft polymer structure that extends into and outside the cup of the bra.

**US6966815** discloses a stiffening element that is incorporated into the underband of a bra.

**US7234994** discloses a u-shaped hard underwire rolled into a soft plastic  
5 body.

**GB2456897** discloses a flexible lower bra cup that extends past the conventional underwire and into the underband.

10 **WO2009/101287** discloses a laminated stiffening structure in the form of fingers and peripheral which operates to contain the cup of a bra.

None of the above patents address the issues of effective motion control or impact protection for a sports bra.

15

The following physical impact bras are also known:

**US4607640** discloses a bra having removable elements.

20 **US5022887** discloses a bra having two overlapping cups that are held away from the breasts.

**US6083080** discloses a laminated full-cup protective bra with layers of neoprene on the inside and outside of the polyethylene protector.

25

Whilst providing some impact protection the designs lack either comfort, mobility or effective motion control

It would be desirable to provide a bra providing good impact protection  
30 and/or motion control that is comfortable, compact, flexible and allows

relatively free movement or to at least provide the public with a useful choice.

#### EXEMPLARY EMBODIMENTS

5

According to one exemplary embodiment there is provided a sport motion control bra including:

- 10 a. a pair of partial cups which locate, support and shape the lower periphery of breasts of a user so as to effectively restrict the motion of the breasts relative to the body of a user during sporting activities; and
- b. one or more side straps which connect to wings extending from each cup so as to, in use, support and locate the sides of the cups.

15 According to another exemplary embodiment there is provided a sport impact protection and motion control bra including:

- 20 a. a pair of cups each having side wings extending from the outer side of each cup and tabs extending from the top of each cup, the cups being dimensioned to encompass the majority of the breasts of a user and to effectively transfer local impact force through the cup to be dissipated through the bra and surrounding breast tissue and restrict motion of the breasts relative to the body of a user;
- b. one or more side straps which connect to the wings so as to, in use, anchor the sides of the cups to the torso of a user; and
- 25 c. shoulder straps connected to the top tabs.

According to a further exemplary embodiment there is provided a sport impact protection bra including:

- 30 a. a pair of cups each having side wings extending from the outer side of each cup and tabs extending from the top of each cup, the

cups being dimensioned to encompass the majority of the breasts of a user and to effectively transfer local impact force through the cup to be dissipated through the bra and surrounding breast tissue;

- 5           b. one or more side straps which connect to the wings so as to, in use, anchor the sides of the cups to the torso of a user; and
- c. shoulder straps connected to the top tabs.

The lower edge of each cup preferably includes an inflexion section extending between the torso and breast sections of the bra.

10

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings which are incorporated in and constitute part of the specification, illustrate embodiments of the invention and, together with  
15 the general description of the invention given above, and the detailed description of embodiments given below, serve to explain the principles of the invention.

- 20           **Figure 1**     shows a bra including full cups;
- Figure 2**     shows a cup of the bra shown in figure 1;
- Figure 3**     shows another view of a cup of the bra shown in figure 1;
- 25           **Figure 4**     illustrates the uplift generated by the cup of the bra shown in figures 1 to 3 and location of the breast by providing an area of inflexion;
- Figure 5**     illustrates the limited location from a cup without an area of  
30           inflexion;

- Figure 6** shows a bra including full cups according to a second embodiment;
- 5 **Figure 7** shows a side view of a cup of the type shown in figures 1 to 3;
- Figure 8** shows a side view of a cup of the type shown in figure 6;
- Figure 9** shows a bra including a partial cup;
- 10 **Figure 10** shows the partial cup of the bra shown in figure 9; and
- Figure 11** shows a bra including a partial cup according to another embodiment.

15

#### **DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION**

The present invention is primarily directed to sport motion control and sport impact protection bras. A sport motion control bra is a bra that significantly  
20 constrains the motion of breasts as a sum of its three dimensional movement (e.g. motion control as a sum of three dimensional movement reduced in the order of 80% compared to a no-bra condition). A sport impact protection bra is one capable of effectively dissipating local impact forces outside the local  
25 impact area (e.g. of the order of 75% of local impact force dissipated outside the local impact area).

Referring to figures 1 to 5 a sport impact and motion control bra according to a first embodiment is shown. Bra 1 includes a pair of full cups 2 and 3 supported by a fabric body 4. Side straps 5 connect at the back and shoulder

straps 6 and 7 extend from tabs 10 to connect around the neck or at the back to secure the bra to a user.

Cups 2 and 3 may be formed of a material that has sufficient rigidity to  
5 impose a desired shape on the breast of a user and distribute impact force but which is flexible enough to provide freedom of movement. The cups may suitably be formed by injection moulding using a material such as low density polyethylene. Alternatively they may be of a composite construction. The cups may decrease in thickness towards all or part of the periphery to  
10 provide greater flexibility at the perimeter. Alternatively or additionally "fingers" may be provided about all or part of the periphery in the form of spaced apart finger sections. Foam cushioning, such as shape memory foam, may be provided within the cups. The bra may be formed as an integrated article with the parts glued, stitched or ultrasonically welded together etc.

15

Cup 2 (as per cup 3 also) is shown to include a wing 8 which extends to an area under the arm of a user and acts as a cantilever to support cup 2. This provides an effective "armature" as traditionally provided in prior art designs by an underwire etc. The lower edge of cup 2 includes an inflexion region  
20 9 where a reverse curve serves to lift the lower part of the breast 11 and provide an anchor along the adjacent area of the torso of a user to support the cup (as compared to a cup 12 without inflexion about breast 13 as shown in figure 5). This inflexion provides shape and location to the breasts and avoids overlap of the breast onto the torso. It also provides a location on the  
25 chest wall for cantilever support. In addition, the approximate orthogonal inflexion of the 'wing' provides support for the cup but also provides a cantilever for sideways motion of the breast relative to the body.

The cup shape imposes a shape on the breast that better positions the mass of  
30 the breast to reduce motion. In this way an ideal shape may be imposed

rather than shape being the result of individual anatomy and the flexible nature of the fabric cup.

The cups 2 and 3 are chiral (left and right handed) to impose an ideal shape  
5 on each breast. The configuration transfers the load of 'uplift' to the wing 8 acting as a cantilever (i.e. to the chest band rather than principally to the shoulder straps 6 and 7). The load on the shoulder straps 6 and 7 is between the shoulders and the upper edge of the cups to prevent spillover of the breast over the cups.

10

In effect the insert is taking the bulk of the static load and limits the sideways and downward motion of the breast during exercise. The shoulder load is related to the tension between the top of the insert and the shoulder strap rather than the underwire and the shoulder strap. Thus stresses on the  
15 shoulders should be less to achieve the same degree of static uplift. Sideways motion is also reduced due to the anchoring via wing 8.

Referring to figure 6 an alternative full cup bra embodiment 14 is shown. In this case the cups 15 and 16 do not include the wings 8 of the previous  
20 embodiments. The side profiles of the two cup designs are compared in figures 7 and 8.

Referring now to figures 9 and 10 a partial cup embodiment is shown. Bra  
17 has partial cups 18 and 19 supporting the lower periphery of a user's  
25 breasts. These partial cups are integrated into the fabric body 20 of the bra 17 as per the previous embodiments. As in the previous embodiments the partial cups have an inflexion region along their lower edges which assists in lifting the breasts and imposing a desired shape on the breasts. The cups are shaped to locate the breasts in an optimized position and support and shape  
30 the lower periphery of the breasts of a user so as to effectively locate, shape

and restrict the motion of the breasts relative to the body of a user during sporting activities. An underband 21 is provided to anchor the bottom of the bra to the torso of a user. It has been surprisingly found that by providing a partial under breast support to only about 20% of the volume of the breast  
5 that the sum of motion of the breasts in all three dimensions can be reduced by about 80% compared to a no-bra situation.

As in the previous embodiments wings 22 act as a cantilever to anchor the partial cups and inhibit motion. Due to this anchoring effect with underband  
10 21 combined with the inflexion region the partial cups can provide support and motion control without placing undue load on straps 23 and 24.

Figure 11 shows a further partial cup embodiment in which the partial cups 26 and 27 of bra 25 do not include wings.

15

There is thus provided sports motion and/or impact control bras that provide improved comfort, mobility and protection whilst maintaining desirable aesthetics and usability. By imposing a desired shape on the breast and providing appropriate support improved motion control can be achieved and  
20 harmonic motion inhibited (unconstrained breasts naturally move in a figure of 8 pattern during exercise). By maintaining the center of gravity of the breasts closer to the body rotational forces on the breasts may be reduced. The design provides impact protection without unduly inhibiting motion and comfort. By providing effective anchoring of the cups and shaping of the  
25 breasts the shoulder load may be reduced. The bras may be easily and cost effectively be constructed as integrated articles and are easy to use as they require no separate inserts.

While the present invention has been illustrated by the description of the  
30 embodiments thereof, and while the embodiments have been described in

detail, it is not the intention of the Applicant to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details, representative apparatus and method, and illustrative examples shown and described. Accordingly, departures may be made from such details without departure from the spirit or scope of the Applicant's general inventive concept.

**Claims**

1. A bra including:
  - a. a fabric bra body;
  - b. a pair of molded partial cups incorporated into the fabric bra body and positioned so as to, in use, support breasts of a user, each cup including:
    - i. a molded main breast engaging section having:
      - a. a top edge,
      - b. a bottom edge,
      - c. an inside edge, wherein the inside edge of each cup faces each other; and
      - d. an outside edge;
    - ii. a molded non-breast engaging extension integrally formed with the molded main breast engaging section and extending from the outside edge of the molded main breast engaging section to an area under an arm of the user; and
    - iii. a tab extending from the top edge of each cup;
  - c. at least one side strap which connects to respective extensions so as to, in use, anchor sides of the cups to a torso of the user; and
  - d. at least one shoulder strap connected to each tab.

2. The bra as claimed in claim 1 wherein the bottom edge of each cup has an inflexion region at the bottom edge of each cup configured to provide support for each partial cup from a user's chest.
3. The bra as claimed in claim 1 or 2 wherein each molded cup is configured to provide uplift such that overlap of a breast with the torso is avoided.
4. The bra as claimed in any one of claims 1 to 3 wherein the cups have foam cushioning on interior faces of the cups.
5. The bra as claimed in claim 4 wherein the foam is shape memory foam.
6. The bra as claimed in any one of claims 1 to 5 wherein the cups of the bra are shaped for left and right breasts of the user.
7. The bra as claimed in any one of claims 1 to 6 wherein a thickness of each cup is reduced towards all or some edges of each cup.
8. The bra as claimed in any one of claims 1 to 7 wherein each cup has fingers extending about all or some edges of each cup.

9. The bra as claimed in any one of claims 1 to 8 wherein the cups are injection molded.
10. The bra as claimed in any one of claims 1 to 9 wherein the cups are formed of low density polyethylene.
11. The bra as claimed in any one of claims 1 to 10 wherein the bra is of an integral unitary construction.
12. A sports bra including:
- a. a fabric bra body;
  - b. a pair of molded partial cups incorporated into the bra body and positioned so as to, in use, support the breasts of a user, each cup including:
    - i. a molded main breast engaging section having:
      - a. a top edge,
      - b. a bottom edge,
      - c. an inside edge, wherein the inside edges of the cups face each other; and
      - d. an outside edge;

ii. a molded non-breast engaging extension integrally formed with the main breast engaging section and extending from the outside edge of the molded main breast engaging section to an area under an arm of a user; and

iii. an inflexion region at the bottom edge of each cup configured to provide support for each partial cup from the chest; and

c. at least one side strap which connects to respective extensions so as to, in use, anchor the cups to a user's torso.

13. The bra as claimed in claim 12 wherein each molded cup is configured to provide uplift such that overlap of the breast with the torso is avoided.

14. The bra as claimed in claim 12 or 13 wherein the cups have foam cushioning on interior faces of the cups.

15. The bra as claimed in claim 14 wherein the foam is shape memory foam.

16. The bra as claimed in any one of claims 12 to 15 wherein the pair of cups of the bra are shaped for a user's left and right breasts.

17. The bra as claimed in any one of claims 12 to 16 wherein each cup has a thickness that reduces towards all or some edges of each cup.
18. The bra as claimed in any one of claims 12 to 17 wherein each cup has fingers extending about all or some edges of each cup.
19. The bra as claimed in any one of claims 12 to 18 wherein the cups are injection molded.
20. The bra as claimed in any one of claims 12 to 19 wherein the cups are formed of low density polyethylene.
21. The bra as claimed in any one of claims 12 to 20 wherein the bra is of an integral unitary construction.
22. A sports bra including:
  - a. a fabric bra body;
  - b. a pair of molded partial cups incorporated into the bra body and positioned so as to, in use, support the breasts of a user, each cup including:
    - i. a molded main breast engaging section having:
      - a. a top edge,

- b. a bottom edge,
  - c. an inside edge, wherein the inside edges of the cups face each other; and
  - d. an outside edge;
- ii. a molded non-breast engaging extension integrally formed with the main breast engaging section and extending from the outside edge of the molded main breast engaging section to an area under an arm of a user; and
  - iii. fingers extending about all or some edges of each cup; and
- c. at least one side strap which connects to respective extensions so as to, in use, anchor the cups to the torso of a user.

23. The bra as claimed in claim 22 wherein each molded cup is configured to provide uplift such that overlap of the breast with the torso is avoided.

24. The bra as claimed in claim 22 or 23 wherein the cups have foam cushioning on interior faces of the cups.

25. The bra as claimed in claim 24 wherein the foam is shape memory foam.

26. The bra as claimed in any one of claims 22 to 25 wherein the pair of cups of the bra are shaped for a user's left and right breasts.

27. The bra as claimed in any one of claims 22 to 26 wherein each cup has a thickness that reduces towards all or some edges of each cup.
28. The bra as claimed in any one of claims 22 to 27 wherein the cups are injection molded.
29. The bra as claimed in any one of claims 22 to 28 wherein the cups are formed of low density polyethylene.
30. The bra as claimed in any one of claims 22 to 29 wherein the bra is of an integral unitary construction.
31. A sports bra including:
- a. a fabric bra body;
  - b. a pair of molded partial cups formed of low density polyethylene incorporated into the bra body and positioned so as to, in use, support the breasts of a user, each cup including:
    - i. a molded main breast engaging section having:
      - a. a top edge,
      - b. a bottom edge,

c. an inside edge, wherein the inside edges of the cups face each other; and

d. an outside edge; and

ii. a molded non-breast engaging extension integrally formed with the main breast engaging section and extending from the outside edge of the molded main breast engaging section to an area under an arm of a user; and

c. at least one side strap which connects to respective extensions so as to, in use, anchor the cups to a user's torso.

32. The bra as claimed in claim 31 wherein the bottom edge of each cup has an inflexion region at the bottom edge of each cup configured to provide support for each partial cup from a user's chest.

33. The bra as claimed in claim 32 wherein each molded cup is configured to provide uplift such that overlap of the breast with the torso is avoided.

34. The bra as claimed in any one of claims 31 to 33 wherein the cups have foam cushioning on interior faces of the cups.

35. The bra as claimed in claim 34 wherein the foam is shape memory foam.

36. The bra as claimed in any one of claims 31 to 35 wherein the pair of cups of the bra are shaped for a user's left and right breasts.

37. The bra as claimed in any one of claims 31 to 36 wherein the thickness of each cup is reduced towards all or some edges of each cup.

38. The bra as claimed in any one of claims 31 to 37 wherein the cups are injection molded.

39. The bra as claimed in any one of claims claim 31 to 38 wherein the bra is of an integral unitary construction.




Figure 1

P




Figure 2

*Handwritten mark*




Figure 3




Figure 4




Figure 5




Figure 6

70




Figure 8




Figure 7

*R*




Figure 9






Figure 10






Figure 11

