



US006986701B2

(12) **United States Patent**
Halley et al.

(10) **Patent No.:** **US 6,986,701 B2**
(45) **Date of Patent:** **Jan. 17, 2006**

(54) **POLISHING PAD WITH BUILT-IN OPTICAL SENSOR**

(75) Inventors: **David G. Halley**, San Luis Obispo, CA (US); **Gregory L. Barbour**, San Luis Obispo, CA (US); **Ben Smedley**, San Luis Obispo, CA (US); **Stephen H. Wolf**, Los Osos, CA (US)

(73) Assignee: **Strasbaugh**, San Luis Obispo, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/850,346**

(22) Filed: **May 20, 2004**

(65) **Prior Publication Data**

US 2005/0009449 A1 Jan. 13, 2005

Related U.S. Application Data

(63) Continuation of application No. 09/970,252, filed on Sep. 29, 2001, now Pat. No. 6,739,945.

(60) Provisional application No. 60/236,575, filed on Sep. 29, 2000.

(51) **Int. Cl.**
B24B 49/12 (2006.01)

(52) **U.S. Cl.** **451/6; 451/526**

(58) **Field of Classification Search** **451/6, 451/5, 8, 287, 288, 41, 526**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,081,796 A 1/1992 Schultz 51/165.74

5,433,651 A	7/1995	Lustig et al.	451/6
5,643,046 A	7/1997	Katakabe et al.	451/6
5,838,447 A	11/1998	Hiyama et al.	356/381
5,893,796 A	4/1999	Birang et al.	451/526
5,949,927 A	9/1999	Tang	385/12
6,010,538 A	1/2000	Sun et al.	756/345
6,045,439 A	4/2000	Birang et al.	451/526
6,068,539 A	5/2000	Bajaj et al.	451/6
6,106,662 A	8/2000	Bibby, Jr. et al.	156/345
6,146,242 A	11/2000	Truer et al.	451/6
6,190,234 B1	2/2001	Swedek et al.	451/6

FOREIGN PATENT DOCUMENTS

EP	0325753	8/1989
JP	3-234467	10/1991


Primary Examiner—Robert A. Rose

(74) *Attorney, Agent, or Firm*—K. David Crockett, Esq.; Crockett & Crockett

(57) **ABSTRACT**

An optical sensor that includes a light source and a detector is located within a cavity in a polishing pad so as to face the surface that is being polished. Light from the light source is reflected from the surface being polished and the detector detects the reflected light. The electrical signal produced by the detector is conducted to a hub located at the central aperture of the polishing pad. The disposable polishing pad is removably connected, both mechanically and electrically to the hub. The hub contains electronic circuitry that is concerned with supplying power to the optical sensor and with transmitting the electrical signal to a non-rotating station. Several techniques are described for accomplishing these tasks. The system permits continuous monitoring of an optical characteristic of a surface that is being polished, even while the polishing machine is in operation, and permits the end point of the polishing process to be determined.

4 Claims, 10 Drawing Sheets






Fig. 1




Fig. 2




Fig. 4




Fig. 3





Fig. 5

Fig. 8






Fig. 11




Fig. 12

Fig. 13





Fig. 14






FIG. 15

POLISHING PAD WITH BUILT-IN OPTICAL SENSOR

This application is a continuation of U.S. application Ser. No. 09/970,252 filed Sep. 29, 2001, now U.S. Pat. No. 6,739,945, which claims priority to U.S. provisional application 60/236,575 filed Sep. 29, 2000.

FIELD OF THE INVENTIONS

The present invention is in the field of semiconductor wafer processing, and more specifically relates to a disposable polishing pad for use in chemical mechanical polishing. The polishing pad contains an optical sensor for monitoring the condition of the surface being polished while the polishing operation is taking place, thus permitting determination of the endpoint of the process.

BACKGROUND OF THE INVENTIONS

In U.S. Pat. No. 5,893,796 issued Apr. 13, 1999 and in continuation Pat. No. 6,045,439 issued Apr. 4, 2000, Birang et al. show a number of designs for a window installed in a polishing pad. The wafer to be polished is on top of the polishing pad, and the polishing pad rests upon a rigid platen so that the polishing occurs on the lower surface of the wafer. That surface is monitored during the polishing process by an interferometer that is located below the rigid platen. The interferometer directs a laser beam upward, and in order for it to reach the lower surface of the wafer, it must pass through an aperture in the platen and then continue upward through the polishing pad. To prevent the accumulation of slurry above the aperture in the platen, a window is provided in the polishing pad. Regardless of how the window is formed, it is clear that the interferometer sensor is always located below the platen and is never located in the polishing pad.

In U.S. Pat. No. 5,949,927 issued Sep. 7, 1999 to Tang, there are described a number of techniques for monitoring polished surfaces during the polishing process. In one embodiment Tang refers to a fiber-optic ribbon embedded in a polishing pad. This ribbon is merely a conductor of light. The light source and the detector that do the sensing are located outside of the pad. Nowhere does Tang suggest including a light source and a detector inside the polishing pad. In some of Tang's embodiments, fiber-optic decouplers are used to transfer the light in the optical fibers from a rotating component to a stationary component. In other embodiments, the optical signal is detected onboard a rotating component, and the resulting electrical signal is transferred to a stationary component through electrical slip rings. There is no suggestion in the Tang patent of transmitting the electrical signal to a stationary component by means of radio waves, acoustical waves, a modulated light beam, or by magnetic induction.

In another optical end-point sensing system, described in U.S. Pat. No. 5,081,796 issued Jan. 21, 1992 to Schultz there is described a method in which, after partial polishing, the wafer is moved to a position at which part of the wafer overhangs the edge of the platen. The wear on this overhanging part is measured by interferometry to determine whether the polishing process should be continued.

In earlier attempts to mount the sensor in the polishing pad, an aperture was formed in the polishing pad and the optical sensor was bonded into position within the aperture by means of an adhesive. However, subsequent tests revealed that the use of an adhesive could not be depended

upon to prevent the polishing slurry, which may contain reactive chemicals, from entering the optical sensor and from penetrating through the polishing pad to the supporting table.

In conclusion, although several techniques are known in the art for monitoring the polished surface during the polishing process, none of these techniques is entirely satisfactory. The fiber optic bundles described by Tang are expensive and potentially fragile; and the use of an interferometer located below the platen, as used by Birang et al., requires making an aperture through the platen that supports the polishing pad. Accordingly, the present inventor set out to devise a monitoring system that would be economical and robust, taking advantage of recent advances in the miniaturization of certain components.

SUMMARY

The disposable polishing pad described below is composed of foamed urethane. It contains an optical sensor for monitoring, in situ, an optical characteristic of a wafer surface being polished. The real-time data derived from the optical sensor enables, among other things, the end-point of the process to be determined without disengaging the wafer for off-line testing. This greatly increases the efficiency of the polishing process.

The wafers to be polished are composite structures that include strata of different materials. Typically, the outermost stratum is polished away until its interface with an underlying stratum has been reached. At that point it is said that the end point of the polishing operation has been reached. The polishing pad and accompanying optics and electronics is able to detect transitions from an oxide layer to a silicon layer as well as transitions from a metal to an oxide, or other material.

The polishing pad described involves modifying a conventional polishing pad by embedding within it an optical sensor and other components. The unmodified polishing pads are widely available commercially, and the Model IC 1000 made by the Rodel Company of Newark, N.J., is a typical unmodified pad. Pads manufactured by the Thomas West Company may also be used.

The optical sensor senses an optical characteristic of the surface that is being polished. Typically, the optical characteristic of the surface is its reflectivity. However, other optical characteristics of the surface can also be sensed, including its polarization, its absorptivity, and its photoluminescence (if any). Techniques for sensing these various characteristics are well known in the optical arts, and typically they involve little more than adding a polarizer or a spectral filter to the optical system. For this reason, in the following discussion the more general term "optical characteristic" is used.

In addition to the optics the disposable pad provides an apparatus for supplying electrical power to the optical sensor in the polishing pad.

The disposable polishing pad also provides an apparatus for supplying electrical power for use in transmitting an electrical signal representing the optical characteristic from the rotating polishing pad to an adjacent non-rotating receiver. The pad is removably connectable to a non-disposable hub that contains power and signal processing circuitry.

An optical sensor that includes a light source and a detector is disposed within a blind hole in the polishing pad so as to face the surface that is being polished. Light from the light source is reflected from the surface being polished

3

and the detector detects the reflected light. The detector produces an electrical signal related to the intensity of the light reflected back onto the detector.

The electrical signal produced by the detector is conducted radially inward from the location of the detector to the central aperture of the polishing pad by a thin conductor concealed between the layers of the polishing pad.

The disposable polishing pad is removably connected, both mechanically and electrically, to a hub that rotates with the polishing pad. The hub contains electronic circuitry that is concerned with supplying power to the optical sensor and with transmitting the electrical signal produced by the detector to non-rotating parts of the system. Because of the expense of these electronic circuits, the hub is not considered to be disposable. After the polishing pad has been worn out from use, it is disposed of, along with the optical sensor and the thin conductor.

Electrical power for operating the electronic circuits within the hub and for powering the light source of the optical sensor may be provided by several techniques. In one embodiment, the secondary winding of a transformer is included within the rotating hub and a primary winding is located on an adjacent non-rotating part of the polishing machine. In another embodiment, a solar cell or photovoltaic array is mounted on the rotating hub and is illuminated by a light source mounted on a non-rotating portion of the machine. In another embodiment, electrical power is derived from a battery located within the hub. In yet another embodiment, electrical conductors in the rotating polishing pad or in the rotating hub pass through the magnetic fields of permanent magnets mounted on adjacent non-rotating portions of the polishing machine, to constitute a magneto.

The electrical signal representing an optical characteristic of the surface being polished is transmitted from the rotating hub to an adjacent stationary portion of the polishing machine by any of several techniques. In one embodiment, the electrical signal to be transmitted is used to frequency modulate a light beam that is received by a detector located on adjacent non-rotating structure. In other embodiments, the signal is transmitted by a radio link or an acoustical link. In yet another embodiment, the signal is applied to the primary winding of a transformer on the rotating hub and received by a secondary winding of the transformer located on an adjacent non-rotating portion of the polishing machine. This transformer may be the same transformer used for coupling electrical power into the hub, or it can be a different transformer.

There must be a viable optical path between the top of the sensor and the lower side of the wafer. However, a void would not be acceptable, because it would quickly become filled with polishing slurry, thereby rendering it incapable of serving as an optical medium. In addition, a void would present a large mechanical discontinuity in the otherwise homogenous and uniformly resilient polishing pad. Further, the components of the optical sensor must not come into direct mechanical contact with the wafer that is being polished, to avoid scratching the surface of the wafer.

To overcome this problem, the optical sensor is embedded into the polishing pad using techniques described in detail below. These techniques have been successful in overcoming the disadvantages described above.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a top view of a chemical mechanical planarization machine polishing wafers using a polishing pad embedded with optical sensors.

4

FIG. 2 is an exploded view in perspective showing the general arrangement of the elements of the hub and optical assembly as placed in a polishing pad.

FIG. 3 is a front top perspective view of the optical sensor.

FIG. 4 is a side elevational diagram showing an optical sensor without a prism.

FIG. 5 illustrates an electronics hub using an inductive coupler.

FIG. 6 is a diagram showing a cross sectional view of an hub using a light emitting means to transfer signals to a non-rotating hub.

FIG. 7 is a diagram showing a cross sectional view of a hub utilizing radio emitting means to transfer signals to a non-rotating hub.

FIG. 8 is a diagram showing a cross sectional view of a hub utilizing sound waves to transfer signals to a non-rotating hub.

FIG. 9 shows a snap ring disposed in the polishing pad.

FIG. 10 is a top view of the snap ring, with a contact pad and conducting ribbon disposed on the bottom of the snap ring.

FIG. 11 shows a medial cross section of the optical sensor embedded into the polishing pad.

FIG. 12 shows a medial cross section of the injection molding process used to embed the optical sensor shown in FIG. 13.

FIG. 13 shows a medial cross section of the optical sensor and hub assembly embedded in a single injection molded pad.

FIG. 14 shows a medial cross section of the injection molding process used to embed both the optical sensor and the hub assembly.

FIG. 15 shows the polishing pad installed in a CMP system.

DETAILED DESCRIPTION OF THE INVENTIONS

FIG. 1 is an overhead view of a chemical mechanical system 1 with the optical port 2 cut into the polishing pad 3. The wafer 4 (or other work piece requiring planarization or polishing) is held by the polishing head 5 and suspended over the polishing pad 3 from a translation arm 6. Other systems may use several polishing heads that hold several wafers, and separate translation arms on opposite sides (left and right) of the polishing pad.

The slurry used in the polishing process is injected onto the surface of the polishing pad through slurry injection tube 7. The suspension arm 8 connects to the non-rotating hub 9 that suspends over the electronic assembly hub 10. The electronics assembly hub 10 is removably attached to the polishing pad 3 by means of twist lock, detents, snap rings, screws, threaded segments, or any releasable mating mechanism. The hub 10 is attached to an electrical conducting assembly located within the pad where the hub attaches. The electrical conducting assembly can be either a single contact or a plurality of contacts attached to a thin, electrically conducting ribbon 11, also known as a flex circuit or ribbon cable. The ribbon 11 electrically connects an optical sensing mechanism, located within the optical port 2 and embedded in the pad 3, to the electronics in the electronics hub 10. The ribbon 11 may also comprise individual wires or a thin cable.

The window rotates with the polishing pad, which itself rotates on a process drive table, or platen 18, in the direction of arrow 12. The polishing heads rotate about their respective spindles 13 in the direction of arrows 14. The polishing heads themselves are translated back and forth over the

5

surface of the polishing pad by the translating spindle 15, as indicated by arrow 16. Thus, the optical window 2 passes under the polishing heads while the polishing heads are both rotating and translating, swiping a complex path across the wafer surface on each rotation of the polishing pad/platen assembly.

The optical port 2 and the electrical conducting assembly (see FIG. 10) always remain on the same radial line 17 as the pad rotates. However, the radial line translates in a circular path as pad 3 rotates about the hub 9. Note that the conducting ribbon 11 lies along the radial line 17 and moves with it.

As shown in FIG. 2, the polishing pad 3 has a circular shape and a central circular aperture 23. A blind hole 24 is formed in the polishing pad, and the hole opens upwardly so as to face the surface that is being polished. An optical sensor 25 is placed in the blind hole 24 and a conductor ribbon 11, which extends from the optical sensor 25 to the central aperture 23, is embedded within the polishing pad 3.

When the polishing pad 3 is to be used, an electronics hub is inserted from above into the central aperture 23 and secured there by screwing a base 26, which lies below the polishing pad 3, onto a threaded portion of the hub 10. As seen in FIG. 5, the polishing pad 3 is thus clamped between portions of the hub and portions of the base 26. During the grinding process, the polishing pad 3, the hub 10 and the base 26 rotate together about a central vertical axis 28.

The non-rotating hub 9 of the polishing machine is located adjacent and above the hub 10. The non-rotating hub 9 is fixed during operation to the suspension arm 8.

FIG. 3 shows the optical sensor 25 in greater detail. The optical sensor 25 includes a light source 35, a detector 36, a reflective surface 37 (which could be a prism, mirror, or other reflective optical component), and the conductor ribbon 11. The conductor ribbon 11 includes a number of generally parallel conductors laminated together for the purpose of supplying electrical power to the light source 35 and for conducting the electrical output signal of the detector 36 to the central aperture 23. Preferably, the light source 35 and the detector 36 are a matched pair. In general, the light source 35 is a light emitting diode and the detector 36 is a photodiode. The central axis of the beam of light emitted by the light source 35 is directed horizontally initially, but upon reaching the reflective surface 37 the light is redirected upward so as to strike and reflect from the surface that is being polished. The reflected light also is redirected by the reflective surface 37 so that the reflected light falls on the detector 36, which produces an electrical signal in relation to the intensity of the light falling on it. The arrangement shown in FIG. 3 was chosen to minimize the height of the sensor. The reflective surface 37 may be omitted and instead the arrangement shown in side view in FIG. 4 may be used.

The optical components and the end of the conductor ribbon 11 are encapsulated in the form of a thin disk 38 that is sized to fit snugly within the blind hole 24 of FIG. 2. Note that in the arrangements of FIGS. 3 and 4 baffles may be used to reduce the amount of non-reflective light reaching the detector 36. Included within the conductor ribbon 11 are three conductors: a power conductor 39, a signal conductor 40, and one or more return or ground conductors 41.

FIG. 5 illustrates an electronics hub using an inductive coupler. The power conductor 39 terminates adjacent the central aperture 23 of the polishing pad 3 at a power plug 46, and the signal conductor 40 likewise terminates at a signal plug 49. When the hub 10 is inserted into the central aperture 23, the power plug 46 makes electrical contact with the power jack 50, and the signal plug 49 makes electrical

6

contact with the signal jack 51. An O-ring seal 52 prevents the liquids used in the polishing process from reaching the plugs and jacks. A ring seal 53 is provided in the base 26 to further insure that the electronic circuits within the hub remain uncontaminated.

An electrical signal produced by the detector and related to the optical characteristic is carried by the conductor 54 from the signal jack 51 to a signal processing circuit 55, that produces in response to the electrical signal a processed signal on the conductor 56 representing the optical characteristic. The processed signal on the conductor 56 is then applied to a transmitter 57.

The process by which the signal is passed from the rotating hub 10 to the non-rotating hub 9 is referred to as inductive coupling, or RF coupling. The overall assembly may be referred to as an inductive coupler or an RF coupler.

The transmitter 57 applies a time-varying electrical current to the primary winding 58 of a transformer that produces a varying magnetic field 59 representative of the processed signal. The magnetic field 59 extends upward through the top of the hub 10 and is intercepted by a secondary winding 60 of the transformer which is located on an adjacent non-rotating portion 9 of the polishing machine, or on some other non-rotating object. The varying magnetic field 59 induces a current in the secondary winding 60 that is applied to a receiver 61 that produces on the terminal 62 a signal representative of the optical characteristic. This signal is then available for use by external circuitry for such purposes as monitoring the progress of the polishing operation or determining whether the end point of the polishing process has been reached.

A similar technique may be used to transfer electrical power from the adjacent non-rotating portion 9 of the polishing machine to the rotating hub 10. A prime power source 63 on the non-rotating portion 9 applies an electrical current to the primary winding 64 of a transformer that produces a magnetic field 65 that extends downward through the top of the hub 10 and is intercepted by a secondary winding 66 in which the varying magnetic field induces an electrical current that is applied to a power receiver circuitry 67. The power receiver 67 applies electrical power on the conductor 68 to the power jack 50, from which it is conducted through the power plug 46 and the power conductor 46 to the light source. The power receiver 67 also supplies electrical power to the signal processing circuit 55 through the conductor 69, and to the transmitter 57 through the conductor 70. Thus, power for operation of the LED may also be provided by inductive coupling.

The winding 58 is the same winding as winding 66, and winding 60 is the same winding as winding 64. Alternatively, the windings may be different. The superimposed power and signal components are at different frequency ranges and are separated by filtering.

FIGS. 6 through 8 show other techniques used to transfer signals from the rotating hub 10 to a non-rotating hub 9 of the polishing machine, and to transfer electrical power from the non-rotating portion 9 into the rotating hub 10.

FIG. 6 shows the transmitter 57 further includes a modulator 75 that applies to a light emitting diode or laser diode 76 a frequency modulated current representative of the processed signal that represents the optical characteristic. The light-emitting diode 76 emits light waves 77 that are focused by a lens 78 onto a photodiode detector 79. The detector 79 converts the light waves 77 into an electrical signal that is demodulated in the receiver 80 to produce on the terminal 62 an electrical signal representative of the optical characteristic.

The prime source of electrical power is a battery **81** that supplies power to a power distribution circuit **82** that, in turn, distributes electrical power to the power jack **50**, to the signal processing circuit **55**, and to the transmitter circuit **57**. In FIG. **7** the transmitter **57** is a radio transmitter having an antenna **87** that transmits radio waves **88** through the top of the hub **9**. The radio waves **88** are intercepted by the antenna **89** and demodulated by the receiver **90** to produce an electrical signal on the terminal **62** that is representative of the optical characteristic.

Electrical power is generated by a magneto consisting of a permanent magnet **91** located in the non-rotating portion **29** and an inductor **92** in which the magnetic field of the permanent magnet **91** induces a current as the inductor **92** rotates past the permanent magnet **91**. The induced current is rectified and filtered by the power circuit **93** and then distributed by a power distribution circuit **94**.

In FIG. **8**, the transmitter **57** further includes a power amplifier **100** that drives a loudspeaker **101** that produces sound waves **102**. The sound waves **102** are picked up by a microphone **103** located in the non-rotating portion **29** of the polishing machine. The microphone **103** produces an electrical signal that is applied to the receiver **104** which, in turn, produces an electrical signal on the terminal **62** that is representative of the optical characteristic.

Electrical power is generated in the rotating hub **9** by a solar cell or solar panel **105** in response to light **106** applied to the solar panel **105** by a light source **107** located in the non-rotating portion **29**. The electrical output of the solar panel **105** is converted to an appropriate voltage by the converter **108**, if necessary, and applied to the power distribution circuit **94**.

FIGS. **9** through **16** show the hub insertion assembly and the optical-electrical insertion assembly **25**. They also disclose methods of sealing a snap ring (to releasably attach the electronics hub) and a optical-electrical assemblies into the polishing pad. The polishing pads **3** shown in these Figures are typical polishing pads available in the industry, such as the model IC 1000 produced by Rodel Co. The model comprises two 0.045 inch thick layers of foamed urethane bonded face to face by a 0.007 inch thick layer of adhesive. However, each has been modified to allow for a conducting ribbon **11**, a snap ring **114**, and an optical assembly **25** to be placed into the pad.

FIG. **9** shows a cross section of a molded insert, comprising a snap ring, **114** used to fix the electronics hub **10** into the center aperture of the polishing pad **3**. The snap ring **114** is placed inside the center aperture **23** of the polishing pad **3**. An inwardly extending flange **115**, or collar, is cut out of the snap ring **114** so that the electronics hub **10** will snap securely into place. A guide pin hole **116** receives an electronics hub guide pin **117** to help assure proper alignment of the electronics hub **10**. The snap ring is sealed inside of the polishing pad **3** by means of an adhesive or by a liquid urethane which subsequently dries and solidifies. The electronics hub **10** has a flange or ridge **118** disposed around its bottom section **119**. This flange **118** is sized to provide a releasable fit with the molded insert snap ring **114**.

The electrically conducting ribbon **11** conveys electrical signals and power between the optical assembly **25** and the electronics hub **10**. The terminus of ribbon **11** is disposed on a contact pad **126** in the bottom of the hub-receiving aperture **120**. The contact pad is provided with contacts for establishing electrical contact with matching contacts **122** disposed on the hub **10**. The contacts **122** are preferably spring loaded or biased contacts (such as pogo pins). The contacts

may be provided in redundant groups. As shown, three contacts are provided in the group visible in this view.

The snap ring assembly **114** is preferably isoplanar with the polishing pad **3** such that multiple pads may be easily stacked on top of each other.

FIG. **10** shows a top view of the snap ring **114**. The circular lip of the snap ring **115**, the guide pin hole **116**, and the electrically conducting ribbon **11** are the same as shown in FIG. **9**. Also shown in this Figure are three electrical contacts disposed on the contact pad **126**. Specifically, the three contacts are used for power conduction (contact **123**), signal conduction (contact **124**), and common ground (contact **125**), all of which lie on the contact pad **126**. The contact pad **127** is disposed on the bottom inside surface of the snap ring assembly.

The electronics hub will snap into place inside the lip **115** of the snap ring **114**. Proper alignment of the contacts of the hub with the contacts of the contact pad **127** is assured by the guide pin **116**. Thus, the contacts of the hub establish electrical contact with contacts **123**, **124**, and **125** of the contact pad **126** when the hub is secured in the snap ring.

FIGS. **11** and **12** show cross sections of the optical sensor **25** and a method of securing the optical sensor **25** in the optical port **2** into the polishing pad **3**. An aperture, or hole, **143** is produced in the polishing pad. The aperture **143** must be large enough to accommodate the optical sensor **25**. The optical assembly **25** is placed into an optical assembly puck so that it may be easily disposed into the aperture. Portions of the aperture adjacent to the upper surface **144** and lower surface **145** of the polishing pad **3** extend a short distance radially outwardly from the aperture. This creates a spool-shaped void with the boundaries of the pad.

A channel is produced in the underside of the upper layer **147** to accommodate the conducting ribbon **11** used to convey electrical power and signals from the electronics hub **10** to the optical sensor **25**. The conducting ribbon **11** may intrude into the space generally occupied by the layer of adhesive **148**, which secures the upper layer **147** of the polishing pad to the lower layer **149** of the polishing pad. Alternatively the conducting ribbon **11** may lie above or beneath the adhesive layer **148**.

After the aperture **143** has been formed in the polishing pad **3**, the optical sensor **25** and its conductor ribbon **11** are inserted into their respective places, where they are supported and held in place by spacers composed of urethane or by portions of the upper layer **147** and lower layer **149**.

Thereafter, the assembly is placed into a fixture that includes flat, non-stick surfaces **155** and **156**. The non-stick surfaces **155** and **156** are brought into contact with the upper pad surface **144** and lower pad surface **145** and pressed together.

Next, a liquid urethane is injected by syringe **157** through a passage **158** in the lower mold plate **159** and into the void immediately surrounding the optical sensor **25** until the injected urethane begins to emerge through the vent passage **160** of upper mold plate **161**. During the injection, it is helpful to tilt the assembly slightly in the clockwise direction so that the liquid is injected at the lowest point of the void and the vent passage **160** is at the highest point. Tilting the assembly in this manner prevents air from becoming trapped in the void.

The injected urethane **162** directly above the optical sensor **25** serves as a window through which the optical sensor **25** can view the underside of the wafer, which is placed on top of the upper layer **147**. The liquid urethane is a type of urethane that is optically transparent when it has cured. Because it is chemically similar to the urethane of the

polishing pad **3**, it forms a durable, liquid-proof bond with the material of the polishing pad **3**.

The snap-ring assembly can be inserted into the pad, as shown in FIG. **9**, or formed or integrally with the pad with injection molding processes. As shown in FIGS. **13** and **14**, the polishing pad **3**, including the upper pad layer **147**, lower pad layer **149** and adhesive layer **148**, has been punched and cut to provide voids **168** for the optical sensor, ribbon cable and the electrode pad. The ribbon cable **11**, contact pad, and optical sensor **25** are placed in the corresponding voids in the pad, and a snap ring hub mold is inserted into the hub aperture. The electrode pad may be glued with a weak pressure sensitive adhesive (sticky glue) to the snap ring mold **169**.

As shown in FIG. **13**, an upper mold base **172** and a lower mold base **173** are pressed against the polishing pad's upper layer **147** and lower **149** layer, respectively. Urethane or other injectable plastic is then injected through the injection port **174**, and the urethane fills the voids. When the void between the plates is filled, the liquid urethane **162** will exit through the exit vent **175**, signaling that the injection process is complete. As shown in FIG. **14**, the injected urethane **176** forms the snap ring assembly and fills the ribbon cable channel and the optical sensor assembly aperture. The injected urethane seals and connects the entire length of void between the snap ring **114** and the optics insert **25**, and it locks the ribbon cable and the sensor assembly into place within the pad.

This process can be accomplished using a snap ring insert as shown in FIGS. **9** and **10** by sizing the hub aperture in the pad slightly larger than the snap ring insert, and using the injected urethane to fix the snap ring insert to the pad.

FIG. **15** shows a detailed view of the overall polishing pad **3** installed in a CMP system, using the pad design shown in FIGS. **13** and **14**. The pad comprises the upper pad layer **147**, lower pad layer **149**, adhesive layer **148**, injected urethane **176**, electrically conductive ribbon **11**, optical sensor **25**, described in the previous Figures. The pad is placed on the platen **18**. The electronics hub **10** is inserted in to the snap ring, so that the pogo pin electrical contacts **137** are in contact with the electrodes of the electrode pad. The non-rotating receiving hub **9** is suspended from the suspension arm **8** over the rotating electronics hub **10**. The electronics in the rotating electronics hub may be the electronics shown in FIGS. **5** through **8**, inside the box numbered as item **10** in those drawings, and the non-rotating receiving hub **9** will house the corresponding electronics in the boxes marked as items **9**. After extended use, the pad will be exhausted and may be removed and discarded. A new pad may be placed on the platen, and the rotating hub may be inserted into the snap ring of the new pad.

It should be noted that the various inventions may be employed in various combinations. For example, the releasable hub embodiments, described in connection with inductive couplers and other non-contacting couplers, can also be employed with slip rings and other contacting couplers. While urethane has been discussed as the material to be used as for injection and use as the injected sealant, other materials may be used, so long as they provide substantial

adhesion and sealing between the several inserts and the pad. Additionally, while the pad construction has been discussed in relation to optical sensors, electrical sensors, heat sensors, impedance sensors and other sensors may be used instead, and the benefits of the molding and releasable hub still achieved. Thus, while the preferred embodiments of the devices and methods have been described in reference to the environment in which they were developed, they are merely illustrative of the principles of the inventions. Other embodiments and configurations may be devised without departing from the spirit of the inventions and the scope of the appended claims.

We claim:

1. A polishing pad assembly for use in a CMP process using a sensor assembly to detect the progress of the CMP process, said polishing pad assembly comprising:

- a pad having a center;
- a releasable mating structure disposed at the center of the pad, said releasable mating structure having a first set of electrical contacts disposed thereon;
- sensor assembly disposed within the pad, said sensor assembly radially spaced from the center of the pad; and

- an electrical conductor connecting the sensor assembly to the releasable rotating mating structure; and

- a hub adapted to be releasably attached to the releasable mating structure, said hub having a second set of electrical contacts disposed thereon such that insertion of the hub into the releasable fitting results in electrical contact between the first set of electrical contacts and the second set of electrical contacts;

- wherein the releasable mating structure further comprises a snap ring assembly disposed in the center of the polishing pad, said snap ring assembly having snap ring and a hub receiving aperture, said hub, receiving aperture having a bottom;

- a contact pad disposed on the bottom of the hub receiving aperture, wherein the first set of electrical contacts are disposed on the contact pad, and wherein said contacts face towards the hub receiving aperture; and

- the electrical conductor electrically connects the sensor assembly to the plurality of electrical contacts on the bottom of the snap ring.

2. The polishing pad of claim **1** wherein the top surface of the snap ring and the top surface of the pad are substantially co-planar and wherein the bottom surface of the snap ring and the bottom surface of the pad are substantially co-planar.

3. The polishing pad of claim **1** where the removably attachable hub is an electronics hub holding electronics.

4. The polishing pad of claim **1** wherein the first set of contacts comprises a signal contact, a power contact, and a ground contact, and the removably attached hub is an electronics hub holding electronics for processing a signal received from the signal contact, for transferring power to the power contact, and for connecting a common ground to the ground contact.

* * * * *