

W. H. BARNARD.
Lamp-Chimney.

No. 165,912.

Patented July 27, 1875.

FIG. I.




FIG. III.




FIG. II.




FIG. V.





FIG. IV.



WITNESSES:

J. S. Coombs
W. H. Norris

INVENTOR

William H. Barnard

By James L. Norris.
Atty.

UNITED STATES PATENT OFFICE.

WILLIAM H. BARNARD, OF SEDALIA, MISSOURI.

IMPROVEMENT IN LAMP-CHIMNEYS.

Specification forming part of Letters Patent No. **165,912**, dated July 27, 1875; application filed January 4, 1875.

To all whom it may concern:

Be it known that I, WILLIAM H. BARNARD, of Sedalia, in the county of Pettis and State of Missouri, have invented certain new and useful Improvements in Lamp-Chimneys, of which the following is a specification:

My invention relates to certain improvements in that class of lamp-chimneys which are constructed of two longitudinal sections, united at their edges, and properly bound or clasped together, for the purpose of allowing for the expansion and contraction of the glass when subjected to sudden changes of temperature, and preventing the chimney from cracking or breaking.

The object of my invention is to secure a more perfect joint at the point of union of the two sections, and provide a more secure and reliable device for binding the two sections together, than has been heretofore accomplished in the chimneys of this class, as ordinarily constructed; and my invention consists in constructing a chimney of two longitudinal sections or parts, as usual, each section having a longitudinal flange on its edges, which unite and form a longitudinal projection or edge on the outside of the chimney when the sections are bound together.

By this construction a broad face is obtained along the edges of each section, which form, when properly ground and placed together, a perfect joint.

In the drawings, Figure 1 is a perspective view of my improved lamp-chimney; Fig. 2, a similar view of the same with the end ferrules removed. Figs. 3 and 4 are detached views of the top and bottom ferrules, respectively; and Fig. 5 is a section on line *xx* of Fig. 1.

The letters A A represent the sections composing the chimney. Along the edges of each section, on the outside, a longitudinal flange, *d*, is formed. The faces of these flanges

are accurately ground, so as to form a perfectly tight joint when the sections are joined together. The flanges do not extend quite to the end of the sections, but terminate a short distance from said ends, in order to allow the sections to set into the annular ferrules which bind them together. These annular ferrules are represented by the letters B B. They are constructed so as to grasp the edges of the sections at their ends, both on the inside and outside, and thus firmly bind them together.

It will be seen that by the above-described construction of the sections a broad face will be formed along the edges of the sections at the point of union, which will allow said edges to be readily and accurately ground, forming a perfect joint throughout the entire length of the sections, which it has hitherto been found impossible to obtain.

The annular ferrules, by grasping both the outside and inside of the chimney, will prevent any slipping of the sections, and thus necessarily bind them in place.

The chimneys thus constructed are admirably adapted for packing for transportation, as the sections will nest together, occupying but little room.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

A lamp-chimney constructed of two sections, each of which is provided with laterally-projecting flanges, substantially as described, whereby, when the sections are placed together, a longitudinal projection is formed and a perfect joint secured, as set forth.

In testimony that I claim the foregoing I have hereunto set my hand and seal.

WILLIAM H. BARNARD. [L. S.]

Witnesses:

J. HALL BROWNE,
J. S. JACKSON.