## **PCT**

#### WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

C08J 7/12, 7/04 // A61L 33/00

A1

(11) International Publication Number: WO 92/07023

(43) International Publication Date: 30 April 1992 (30.04.92)

(21) International Application Number: PCT/SE91/00702 (81) D
(22) International Filing Date: 18 October 1991 (18.10.91)

(30) Priority data: 9003364-8 22

22 October 1990 (22.10.90) SE

(71) Applicant: BEROL NOBEL AB [SE/SE]; S-444 85 Stenungsund (SE).

(72) Inventors: BRINK, Carina; Slätvarsgatan 65, S-421 79 VA Frölunda (SE). HOLMBERG, Krister; Dalgångsgatan 17, S-431 39 Mölndal (SE). ÖSTERBERG, Eva; Storskiftegatan 67, S-442 53 Kungälv (SE).

(74) Agent: ANDERSSON, Rolf; Berol Nobel AB, S-444 85 Stenungsund (SE).

(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent).

**Published** 

With international search report.

(54) Title: HYDROPHILISED SOLID SURFACE, METHOD FOR THE PRODUCTION THEREOF, AND AGENT THEREFOR

#### (57) Abstract

A hydrophilised solid surface having a biopolymer-repellent hydrophilic outer layer is produced by causing a solid surface with anionic groups capable of reacting with amino groups, to react with a polyethylene imine which is partly substituted by hydrophilic nonionic polymer chains having a molecular weight of 400-200,000. In this manner, it is possible to obtain a solid surface having a hydrophilic outer layer consisting of nonionic polymer chains which at one end are covalently bonded to a polyethylene imine which in turn is bonded to the solid surface via anionic groups capable of reacting with the amino groups in the polyethylene imine, the weight of the nonionic polymer chains being at least 50 % of the weight of the polyethylene imine. Such hydrophilised solid surfaces exhibit low spontaneous adsorption of biomolecules.

#### + DESIGNATIONS OF "SU"

Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

ΑT	Austria	ES	Spain	MG	Madagascar
AU	Australia	Fl	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	. NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	İtaly	RO	Romania
CF	Central African Republic	JР	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic	SE	Swcden
CH	Switzerland		of Korea	SN	Senegal
Cl	Côte d'ivoire	KR	Republic of Korea	su+	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TG	Togo
DΕ	Germany	LU	Luxembourg	US	United States of Americ
DK	Denmark	MC	Monaco		_ : :== = :==== = : : : : : : : : : : :

1

# HYDROPHILISED SOLID SURFACE, METHOD FOR THE PRODUCTION THEREOF, AND AGENT THEREFOR

The present invention relates to a hydrophilised sur-5 face having a high density of hydrophilic polymer chains, whereby biofouling is notably reduced.

Biofouling, i.e. the undesired adsorption of proteins and other biopolymers, is a well-known problem in many biotechnical and medicotechnical contexts. A primary adhe10 sion of soluble polymers frequently causes cells, cell debris, bacteria, virus etc. to be bonded to the surface, resulting in the clogging of membranes for e.g. ultra- and microfiltration, impaired performance of chromatographic columns, bacterial infections in conjunction with the use of catheters, etc.

It is generally assumed that the adhesion of cells and lower organisms is always preceded by the adsorption of biopolymers, primarily proteins, and by minimising the protein bond to a surface it would thus be possible to avoid biofouling.

The basic problem is the same for all surfaces, both organic and inorganic, even though it may be more pronounced for some materials than for others. A general rule is that the adsorption of polymers to solid surfaces from aqueous solutions is controlled by hydrophobic interactions and electrostatic forces of attraction.

One way, and a very interesting one, to prevent biofouling, is to coat the surface with a film of a hydrophilic uncharged material. Examples of such materials are

30 polysaccharides, such as dextran, and polyethylene glycol
derivatives. To prevent the far-reaching hydrophobic
forces of attraction, the layer should not be too thin,
preferably not below 10 nm. Furthermore, it has proved to
be advantageous if the material contains blocks having a

35 high mobility out to the bulk phase. In respect of protein
repellency, polyethylene glycols thus are anchored far
more effectively at one end to a polymer matrix than are

2

polyethylene glycols having both ends bonded to the matrix.

One way of attaching polyethylene glycol tails to a solid polymer surface is to first subject the surface to 5 so-called acidic etching, then to adsorb a cationic polymer, polyethylene imine, to the surface, and finally to react a reactive polyethylene glycol derivative to available amino groups in the polyethylene imine layer. This technique is described in "Prog. Colloid Polym. Sci.", 74, 10 113-119 (1987). The acidic etching which is carried out in potassium permanganate in concentrated sulphuric acid, results in the formation of carboxylic acid and sulphonic acid groups as well as sulphuric acid esters on the surface. To this highly negatively charged polymer surface, the cationic polyethylene imine is extremely strongly bonded by electrostatic forces. Besides, it is likely that salt formations between amino groups in the polyethylene imine and carboxylated sulphonate groups on the surface are gradually transformed into amide bonds upon drying, 20 whereby an even more stable anchoring of the polyethylene imine to the surface is obtained.

Even though hydrophilised surfaces produced by the technique described in the above paper give an improved repellency of biopolymers, the adsorption thereof is still unacceptably high for most applications.

According to the present invention, it has now proved possible to obtain an even stronger bond of hydrophilic polymer chains to the solid surface than is obtainable with the method previously described in which polyethylene 30 glycol is bonded to a surface made amino-functional by adsorption of polyethylene imine. As a consequence of the more efficient grafting of hydrophilic polymer chains, the method of the present invention gives a far better protein repellency from the surface so that biofouling is effectively prevented. According to the invention, a solid surface having a hydrophilic outer layer of hydrophilic polymer chains is produced by causing a solid surface with

3

anionic groups capable of reacting with amino groups, to react with a polyethylene imine, the amino groups of which are partly substituted by hydrophilic nonionic polymer chains, the weight of the hydrophilic polymer chains being 5 at least 50% of the weight of the polyethylene imine. Preferably, the polymer chains have such a molecular weight and are present in such numbers that the hydrophilic outer chain has a thickness of at least 100 Å. The surprising effect is believed to be due to the fact that it is diffi-10 cult to bond hydrophilic polymers in a closely packed arrangement to a surface since the individual hydrophilic polymer molecules repel each other. The same repellency occurs when polyethylene imine is reacted with hydrophilic polymers in solution. However, by first producing a poly-15 ethylene imine compound with hydrophilic polymer tails in solution and then allowing this graft copolymer to adsorb to the negatively charged surface, the hydrophilic polymer chains will be forced over to the water side. The density and the thickness of the hydrophilic layer formed by the 20 hydrophilic polymer chains is increased considerably as compared to prior art technique. With this approach, the method of the invention is a method by which hydrophilic polymer chains are more closely packed on the surface than is energetically advantageous with respect to the interaction between the repellent hydrophilic polymer chains. However, this interaction is counterbalanced in that the electrostatically attraction between the polyethylene imine and the surface is energetically stronger than the repellency between the hydrophilic polymer chains when these are compelled to pack themselves more closely.

The polyethylene imine with the hydrophilic polymer chains consists of a polyethylene imine skeleton having a molecular weight of 10,000-1,000,000, preferably from 50,000 to 500,000, which to at least 90% by weight is 35 built up of the units  $-C_2H_4NH-$ ,  $-C_2H_4N<$  and  $-C_2H_4NH_2$  in which preferably less than 20% of the reactive hydrogens of the imino and amino groups are substituted by hydro-

30

4

philic polymer chains and, optionally, other substituents, such as alkyl groups, hydroxyl group-containing groups, amide-containing groups, or functional groups utilised upon grafting of the hydrophilic polymer chains. The 5 hydrophilic polymer chains suitably derive from nonionic polymers, such polyethylene glycol or randomly distributed or block-distributed polyalkylene glycols between ethylene oxide and alkylene oxides having 3-4 carbon atoms, or tetrahydrofuran. Other groups of suitable polymers are 10 adducts of ethylene oxide, optionally in combination with higher alkylene oxides or tetrahydrofuran, with a dihydroxy or polyhydroxy compound, such as glycerol and pentaerythritol. Polysaccharides, such as dextran and starch; cellulose ethers, such as methyl cellulose, methyl hydroxypropyl cel-15 lulose, or ethyl hydroxyethyl cellulose; and polyvinyl alcohol are other suitable hydrophilic polymers. The hydrophilic polymer chains are water-soluble, and their molecular weight usually is from 400 to 200,000, preferably from 1,000 to 100,000.

20 According to the invention, the polyethylene imine with grafted hydrophilic polymer chains can be produced by causing the polyethylene imine to react with a reactive hydrophilic polymer in a water-based solution. The ratio of reactive amino groups in the polyethylene imine to 25 reactive end groups in the hydrophilic polymer is adjusted such that the hydrophilic polymer is preferably bonded via its one end only. Examples of reactive hydrophilic polymer derivatives are such derivatives as contain epoxides, aldehydes, sulphonic acid esters, such as tresylate, mesy-30 late and tosylate, cyanuric chlorides, carbonyl imidazoles and active carboxylic acid esters. After the reaction between the hydrophilic polymer derivative and the polyethylene imine has been terminated, remaining reactive groups at the ends of the hydrophilic polymer chains can 35 be removed by reaction with, for example, 2-mercaptoethanol and 2-aminoethanol. A different way of attaching hydrophilic polymer chains to the polyethylene imine is to

5

provide the latter with reactive groups capable of reacting with the hydroxyl groups of the hydrophilic polymer.

Another alternative way of attaching hydrophilic polymer chains to the polyethylene imine is to add ethylene oxide to the latter, optionally in combination with propylene or butylene oxide or tetrahydrofuran.

The resulting water-soluble polyethylene imine derivative is then caused to adsorb to a negatively charged solid surface. Examples of suitable surfaces are those which have a natural negative net charge, such as silica and glass, or those in which the negative charges have been generated by chemical or physical means. Negative charges can be induced on organic polymer surfaces, for example by acidic etching, i.e. a treatment with potassium permanganate in concentrated sulphuric acid, or by plasma-or radiation-induced grafting of, for example, acrylic acid or methacrylic acid. Examples of organic polymers suitable for this purpose are polystyrene, polyvinyl chloride, polyethylene, polymethyl methacrylate, polycarbonate, polysulfone and cellulose acetate. The invention will be further illustrated by the following Examples.

#### Example 1

was washed in 70% ethanol for 3 min. in an ultrasonic bath. The surface of the sample was air-dried and then oxidised for 30 sec. in KMnO<sub>4</sub>/H<sub>2</sub>SO<sub>4</sub> so that carboxylic acid and sulphonic acid groups were formed. The polystyrene plate was thoroughly rinsed in water. 5 g of a polyethylene glycol diepoxide of molecular weight 4,000 was dissolved in 45 ml carbonate buffer of pH 9.5, whereupon 0.43 g polyethylene imine (Polymin SN) of molecular weight 500,000 was added, and the mixture was allowed to react for 3 h at 45°C under agitation. The polystyrene plate thus treated was placed in the solution containing the polyethylene imine derivative which was adsorbed to the oxidised polystyrene surface for 2 h at 40°C.

6

For comparison, a polystyrene plate activated in the above manner was coated with the polyethylene imine from a 10% solution for 2 h at 40°C and pH 9.5. The resulting polyethylene imine-coated polystyrene surface was then repeatedly rinsed with water and allowed to react with a 10% solution of the polyethylene glycol-diepoxide for 20 h at 40°C and pH 9.5.

The thickness of the nonionic hydrophilic layer was evaluated by ellipsometry, the dimensions of both the polyethylene glycol-polyethylene imine layer and of the polyethylene imine layer alone being determined. The thickness of the polyethylene glycol layer was obtained by subtracting the latter value from the former.

The hydrophilisation effect was evaluated also by protein adsorption measurements by so-called ELISA technique. The amount of adsorbed protein is proportional to the adsorbency at 490 nm.

Table 1

10

35

20	Product	Layer thick- ness (nm)	OD 495 nm	Weight ratio
	110000	ness (Im)	OD 493 1III	PEG/PEI,%
	Untreated polystyrene	1.254	-	-
25	Polystyrene hydro- philised according to the invention	0.107	42	87
	Polystyrene hydro- philised according to the comparison	0.500	1.6	13

30 PEG = polyethylene glycol; PEI = polyethylene imine

The above results show that the polyethylene glycol layer on the surface treated according to the invention reaches far into the aqueous phase, whereas only a thin layer in which the chains presumably are lying against the solid surface, is formed on the comparison product. The Table also shows that the hydrophilised surface according

7

to the invention has a far higher protein repellency than the comparison product.

#### Example 2

5

Pieces of LD polyethylene, PVC and polystyrene were cleaned in 70% ethanol and sulphated with  ${\rm KMnO_4/H_2SO_4}$ according to Example 1. A branched polyethylene glycol was produced by adding 320 mol ethylene oxide to di-trimethylol propane and made reactive by reaction with cya-10 nuric chloride. 5 g of the resulting product was dissolved in 45 ml carbonate buffer (pH 9.5), 0.12 g polyethylene imine was added, and the mixture was allowed to react for 3 h at 45°C. Then the resulting polyethylene imine adduct was allowed to react with the activated polymer surfaces 15 for 2 h at 40°C, whereupon the surfaces were thoroughly rinsed with deionised water.

For comparison, a hydrophilised product was produced by adsorbing polyethelene imine in the form of a 5% solution in carbonate buffer (pH 9.5) to the activated polymer 20 surfaces for 10 min., whereupon the above-mentioned branched polyethylene glycol derivative was reacted with the amino-functional surfaces in the form of a 10% solution for 5 h at 40°C. Finally, the pieces were thoroughly rinsed with deionised water. The test was evaluated with ESCA, and the following results were obtained.

8

T	ab	1	е	2

	Product	<u>0/C</u>	N/C	<u>C-0/C-C</u>	Weight ratio PEG/PEI, %
	LD-PE according to the invention	0.43	0.04	3.92	85
5	LD-PE according to the comparison	0.34	0.06	2.43	12
	PVC according to the invention	0.38	0.07	3.82	78
	PVC according to the comparison	0.29	0.11	1.71	10
10	PS according to				
	the invention PS according to	0.41	0.06	3.55	90
	the comparison	0.34	0.15	1.55	16

PEG = polyethylene glycol; PEI = polyethylene imine

It appears from the Table that the products according to the invention have a far better layer of polyethylene glycol chains than the product produced according to prior art technique. Especially interesting are the values in the column C-O/C-C which indicate the ratios between the carbon atoms in the polyethylene glycol chain and the carbon atoms in the respective LD-PE, PVC and PS surfaces. A higher value thus indicates a better surface coverage.

## Example 3

20

25

30

35

Pieces of polyethylene (PE) and polyvinyl chloride (PVC) were washed in 70% ethanol and grafted with crotonic acid under radiation with UV light of wavelength 350 nm in the presence of benzophenone as initiator for the introduction of carboxyl groups. A 10% solution of polyethylene glycol-bis(carbonyl imidazole) of molecular weight 4,000 was allowed to react with 0.24% polyethylene imine at pH 8.0 for 3 h. The carboxyl-functional pieces were treated with the polyethylene imine derivative for 2 h at 40°C, the derivatives being irreversibly adsorbed to the surfaces.

ż

9

For comparison, test surfaces of polyethylene and polyvinyl choride were prepared. The activated surfaces were allowed to react with polyethylene imine in the form of a 10% solution for 2 h at 40°C and pH 9.5. The surfaces were repeatedly rinsed with water and allowed to react with a 9% solution of polyethylene glycol bis(carbonyl imidazole) of molecular weight 4,000 for 8 h at 40°C and pH 8.0. The hydrophilisation effect was evaluated by protein adsorption meausurements according to so-called 0 ELISA technique. The results were as follows.

#### Table 3

	Product	OD 490 nm	Weight ratio PEG/PEI, %
15	PE according to the invention	0.057	81
	PE according to the comparison	0.312	11
	PVC according to the invention	0.3	71
	PVC according to the comparison	1.005	9

20 PEG = polyethylene glycol; PEI = polyethylene imine

The above results show a far better protein repellency when the hydrophilisation had been carried out according to the invention.

### Example 4

25

30

35

A polystyrene plate having the dimensions 6 x 1 cm was activated with  ${\rm KMnO_4/H_2SO_4}$ , as described in Example 1. A 2% aqueous solution of the nonionic polysaccharide ethyl hydroxyethyl cellulose was treated with 0.3 M NaIO $_4$  for 2 h at 20°C, aldehyde groups being generated on the polysaccharide. To 50 ml of the polysaccharide solution, 0.4 g of a 30% solution of polyethylene imine of molecular weight 500,000, and 0.2 g sodium cyanoborohydride were added. After reaction for 2 h at 20°C and pH 7.0, the activated polystyrene surface was placed in the solution,

10

pH was raised to 9.5, and the bonding reaction was allowed to proceed for 2 h at  $40^{\circ}$ C.

The thickness of the nonionic hydrophilic layer as well as the protein adsorption were evaluated as in Example 1. The Table below clearly indicates that the polysaccharide layer on the surface hydrophilised in accordance with the invention reaches far into the solution and provides a highly effective protein repellency.

## 10 Table 4

	Product	Layer thick- ness (nm)	OD 495 nm	Weight ratio PEG/PEI,%
	Untreated polystyrene	-	1.390	_
15	Polystyrene hydro- philised according to the invention	23	0.095	180%

EHEC = ethyl hydroxyethyl cellulose; PEI = polyethyl imine

20

25

30

35

PCT/SE91/00702

11

#### CLAIMS

- 1. A method of producing a solid surface having a biopolymer-repellent hydrophilic outer layer of hydrophilic polymer chains, c h a r a c t e r i s e d in that a solid surface with anionic groups capable of reacting with amino groups is caused to react with a polyethylene imine partly substituted by hydrophilic nonionic polymer to chains having a molecular weight of 400-200,000.
  - 2. Method as claimed in claim 1, c h a r a c t e r i s e d in that the weight of the hydrophilic nonionic polymer chains is at least 50% of the weight of the polyethylene imine.
- 15 3. Method as claimed in claim 1 or 2, c h a r a c t e r i s e d in that the nonionic hydrophilic polymer chains are at least partly hydrophilic polyalkylene glycol chains deriving from ethylene oxide or from propylene oxide, butylene oxide and/or tetrahydrofuran distributed 20 randomly or in blocks.
  - 4. Method as claimed in claim 1 or 2, c h a r a c t e r i s e d in that the nonionic hydrophilic polymer chains are derived from water-soluble nonionic cellulose ethers.
- 5. Method as claimed in claims 1-4, c h a r a c t e r i s e d in that the solid surface is an activated organic polymer surface, and that the unsubstituted polyethylene imine has a molecular weight of 10,000-100,000.
- 6. A solid surface having a biopolymer-repellent
  30 hydrophilic outer layer consisting of nonionic polymer
  chains covalently bonded at one end to a polyethylene
  imine which in turn is bonded to the solid surface via
  anionic groups capable for reacting with amino groups in
  the polyethylene imine, c h a r a c t e r i s e d in
  35 that the weight of the nonionic polymer chains is at least
  50% of the weight of the polyethylene imine.

12

7. Surface as claimed in claim 6, c h a r a c - t e r i s e d in that the nonionic polymer chains are polyalkylene glycol chains deriving from ethylene oxide or ethylene oxide and polypropylene oxide, butylene oxide and/or tetrahydrofuran distributed randomly or in blocks.

8. Surface as claimed in claim 7, c h a r a c - t e r i s e d in that the nonionic polymer chains are derived from nonionic water-soluble cellulose ethers.

9. Surface as claimed in claim 6, charac10 terised in that the solid surface is an active organic polymer surface, and that the polyethylene imine has a molecular weight of 1,000-100,000.

10. Agent for carrying the method as claimed in claim 1 into effect, c h a r a c t e r i s e d in that it is a polyethylene imine substituted by nonionic hydrophilic polymer chains, the amount by weight of the polymer chains being at least 50% of the unsubstituted polyethylene imine.

20

25

30

## INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 91/00702

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) <sup>6</sup>						
	According to International Patent Classification (IPC) or to both National Classification and IPC IPC5: C 08 J 7/12, 7/04 // A 61 L 33/00					
II. FIELDS	II. FIELDS SEARCHED					
		Minimum Docum	entation Searched <sup>7</sup>			
Classificati	on System		Classification Symbols			
IPC5	PC5 C 08 J; A 61 L					
			er than Minimum Documentation ts are Included in Fields Searched <sup>8</sup>			
SE,DK,F	FI,NO o	lasses as above				
III. DOCU	MENTS CO	DISIDERED TO BE RELEVANT9				
Category *	Citati	on of Document, <sup>11</sup> with indication, where ap	propriate, of the relevant passages <sup>12</sup>	Relevant to Claim No.13		
A	et al: optimi	COLLOID & POLYMER SCI, 74 "Surface grafting of polyzed by means of ESCA", 13 - page 119	(1987) E KISS lyethyleneoxide	1-10		
A	CC	., 0341498 (E.I. DU PONT D MPANY) 15 November 1989, he the whole document 	DE NEMOURS AND	1-10		
A	19 al an	al Abstracts, volume 114, 191, (Columbus, Ohio, US), : "Nonionic hydrophilic s id interactions ", see pag 19778m, & Croat. Chem. Act 6	Per Stenius et surfaces: adsorption ge 473, abstract	1-10		
"A" doc con "E" ear filit "L" doc whi cita "O" doc oth "P" doc late	* Special categories of cited documents: 10  "A" document defining the general state of the art which is not considered to be of particular relevance  "E" earlier document but published on or after the international filing date  "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the cited to understand the principle or theory					
IV. CERTI		npletion of the International Search	Date of Mailing of this International S	earch Report		
28th Ja		·	1992 -02- 0 3			
Internation	al Searchin	g Authority	Signature of Authorized Officer Sofia Nikolopo	culicu		
	SWED	ISH PATENT OFFICE	Sofia Nikolopoulou `			

Form PCT/ISA/210 (second sheet) (January 1985)

ategory *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
	Dialog Information Services, File 350, World Patent Index 63-80, Dialog accession no. 2512387, TOYBO K: "Polyolefin film having improved adhesion propertie - having coating of polyethyleneimine and polyepoxy cpd", JP 55037338, A, 800315, 8017 (Basic)	1-10
		:
	(	

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 91/00702

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 30/11/91 The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Paten mer	Publication date	
EP-A1- 0341498	89-11-15	JP-A- US-A-	2043947 4952519	90-02-14 90-08-28