



(22) Date de dépôt/Filing Date: 2007/01/29

(41) Mise à la disp. pub./Open to Public Insp.: 2008/07/10

(30) Priorité/Priority: 2007/01/10 (US11/621,906)

(51) Cl.Int./Int.Cl. *B60J 11/00* (2006.01)

(71) Demandeurs/Applicants:

LIN, XIAO GU, US;
JIN, LAN, US;
ZHAO, YU LIAN, CA


(72) Inventeurs/Inventors:

LIN, XIAO GU, US;
JIN, LAN, US;
ZHAO, YU LIAN, CA

(74) Agent: RICHES, MCKENZIE & HERBERT LLP

(54) Titre : BACHE PROTECTRICE DE VEHICULE

(54) Title: VEHICLE PROTECTING COVER DEVICE



(57) Abrégé/Abstract:

Disclosed is a vehicle covering device having a housing integral with an axle having a folding crank handle to utilize a reeling action useful in the withdrawing and retracting of a folding cover comprised of a sheet like material that when withdrawn can be expanded to cover a vehicles body by manipulation of an end rod attached to said folding covers end portion that is pulled through the jam of a trunk and over a vehicles forward body to effectively protect said vehicle. Additionally the present invention has base elements integral to its housing for providing support and if desired a secondary rear folding cover that may withdrawn in the same manner that may be utilized to cover the rear or trunk portion of a vehicle as well.

ABSTRACT OF THE DISCLOSURE

Disclosed is a vehicle covering device having a housing integral with an axle having a folding crank handle to utilize a reeling action useful in the withdrawing and retracting of a folding cover comprised of a sheet like material that when withdrawn can be expanded to cover a vehicles body by manipulation of an end rod attached to said folding covers end portion that is pulled through the jam of a trunk and over a vehicles forward body to effectively protect said vehicle. Additionally the present invention has base elements integral to its housing for providing support and if desired a secondary rear folding cover that may withdrawn in the same manner that may be utilized to cover the rear or trunk portion of a vehicle as well.

Vehicle Protecting Cover Device

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to vehicle covers and, more specifically, to a vehicle covering device having a housing integral with an axle having a folding crank handle to utilize a reeling action useful in the withdrawing and retracting of a folding cover comprised of a sheet like material that when withdrawn can be expanded to cover a vehicle's body by manipulation of an end rod attached to said folding cover end portion that is pulled through the jamb of a trunk and over a vehicle's forward body to effectively protect said vehicle and a rear folding cover that is used to cover the rear or trunk portion of a vehicle as well.

Description of the Prior Art

There are other vehicle covering devices designed for protecting a vehicle's exterior. Typical of these is U.S. Patent No. 4,848,823 issued to Flohr, et al. on July 18, 1989.

Another patent was issued to Fasiska on January 5, 1993 as U.S. Patent No. 5,176,421. Yet another U.S. Patent No. 5,176,421 was issued to Heider, et al on April 19, 1994 and still yet another was issued on May 14, 1996 to Thompson as U.S. Patent No. 5,516,181.

Another patent was issued to Gibbs on January 28, 1997 as U.S. Patent No. 5,597,196. Yet another U.S. Patent No. 5,597,197 was issued to Mowar, et al. on January 28, 1997. Another was issued to Cheng, et al. on October 17, 2000 as U.S. Patent No. 6,131,643 and still yet another was issued on February 4, 2003 to Li, et al. as U.S. Patent No. 6,513,858.

Another patent was issued to Porter on November 15, 2005 as U.S. Patent No. 6,964,446. Yet another U.S. Patent No. 6,981,509 was issued to Sharapov on January 3, 2006. Another was issued to Koch on April 24, 1997 as German Patent No. DE 19610751 and still yet another was issued on November 28, 2002 to Hoffmann as German Patent No. DE10124574.

U.S. Patent Number 4,848,823

Inventor: Arno K. Flohr, et al.

Issued: July 18, 1989

A remotely controlled power-assisted vehicle cover is attached to a take-up spool winding and unwinding mechanism which is housed in an eccentric-shaped containment tube, mounted under the front or back bumper areas of a vehicle. The vehicle cover is extracted from the cylindrical cover containment tube and placed over a vehicle by a wand fastened to the leading edge of the vehicle cover and houses a wireless control system including a remote motor control and a transmitter to send: on/off, single or variable speed, and reversing controls to the drive motor of the cover extracting/retracting mechanism. In addition to controlling the cover drive motor, the control wand is used to physically guide the protective cover on or off the vehicle. The control wand can easily be operated with one hand and enables precise control of the power-assisted application or removal of the vehicle cover. The cover application operation is done so quickly that a blanket of air is trapped between the cover and the vehicle and helps the cover slide freely over the surface of the vehicle.

U.S. Patent Number 5,176,421

Inventor: Edward J. Fasiska

Issued: January 5, 1993

A cover system for an automobile includes a flexible cover, preferably of nylon, having leading, trailing and side edge portions and of a suitable dimension to fit over the entire car body from the rear bumper to the front bumper and sides thereof. The flexible cover includes an elastic leader segment attached at a first end to the cover and spaced from the trailing edge thereof. A second end of the leader segment is attached to a rotatable spool housed in a containment tube. The spool is rotated for storing in the cover by a motor, by a spring-biased shaft arrangement or by a manually turnable crank, or combinations thereof. The containment tube may be pivotally mounted by straps within the interior of the trunk for storage therein and is adapted to be pivotally swung outwardly from the trunk to an operable position at the rear of the trunk lid. After the cover is applied to the automobile, the containment tube is swung back to the trunk compartment for safe storage.

U.S. Patent Number 5,303,972

Inventor: Merle J. Heider

Issued: April 19, 1994

A top closure for a rectangular box includes a tarpaulin having one edge connected to one top edge of the box, and having the opposite edge wound around an elongated shaft. A reversible motor is connected to the shaft for winding and unwinding the tarpaulin to open and close the top closure. A remote transmitter is adapted to send either a wind or an unwind signal to a receiver which is connected through solenoids to the reversible motor. By pressing one button on the remote transmitter it is possible to rotate the motor in one direction, and by pressing the other button on the remote transmitter it is possible to rotate the motor in the opposite direction.

U.S. Patent Number 5,516,181

Inventor: Craig D. Thompson

Issued: May 14, 1996

A roll-up covering for motor vehicles comprised of a rectangular main section 10 and side flaps 14 with antenna slits 18, 20 in either to accommodate antennas. A cylinder 16 is fixed perpendicular to the length of the main section and located between the main section and the top of the vehicle while in use. The side flaps 14 partially cover the side of the vehicle while in use and fold over the top of the main section for removal. Combined, the covering rolls around the cylinder for compact storage. Rear adjustable straps 26 anchor the covering in the rear compartment of the vehicle for theft prevention and as a means of changing the fit of the covering. Front elastic straps 11 and side elastic straps 12, in conjunction with the rear adjustable straps and the cylinder, tension the main section and side flaps to provide an airspace 34. The airspace between the covering material and the majority of the top vehicle surfaces provides for insulation and ventilation.

U.S. Patent Number 5,597,196

Inventor: Edward R. Gibbs

Issued: January 28, 1997

A system for the deploying and storing of an automobile cover. The system is provided with a roller assembly which can be made to be pivotally disposed about the axis of an axle. Attached to the roller at one end and the axle at another end is a spring means. The roller assembly has attached to it a full body automobile cover. The cover having one end adapted to covering and being secured to the end of the automobile opposite from the trunk, and the other end attached to the roller. The cover wound around the roller assembly and the roller assembly is stored in the trunk compartment of the automobile. The cover can be easily unwound from and wound back onto the roller with the assistance of the spring biased roller. The operator can quickly deploy the cover by pulling it from the back of the trunk over the trunk lid, and over the car, securing it to front bumper. The trunk can be closed after the cover is secured to the front bumper, thus securing the system inside the trunk.

U.S. Patent Number 5,597,197

Inventor: Zeev Mowar, et al.

Issued: January 28, 1997

An automobile sunshade cover shades a passenger compartment of an automobile. The sunshade is attached at one end to a pouch for storing the cover, and is arranged so that the pouch is freely suspended by laces from suitable fittings of the automobile, such as the hinges attaching the lid of the trunk to the automobile body. The pouch serves to anchor the sunshade when deployed. The sunshade has a crossbar attached to its front edge which provides a convenient grip for the user during the deployment and folding back of the cover, while acting as a second anchor of the cover when placed under the windshield wipers. In its operative position, the sunshade covers all the automobile's windows providing protection against the sun regardless of the time of day that the sunshade is deployed or the orientation of the parked vehicle. The sunshade does not cover the automobile's registration plates or rear reflectors. It is conveniently and unobtrusively stored away in the trunk when not in use to overcome the disadvantages of regular sunblinds, which typically obstruct a driver's field of view or clutter up an automobile's interior.

U.S. Patent Number 6,131,643

Inventor: Carson Jun Ping Cheng, et al.

Issued: October 17, 2000

A sun shield device for automobile includes a tubular central axle, a revolving sleeve which has a diameter larger than and a length shorter than that of the central axle being rotatably supported around the central axle, a shading sheet engaged on and wound around the revolving sleeve, an auto-rewinding device which is installed between the central axle and the revolving sleeve for driving the revolving sleeve to rotate so as to automatically rewind the shading sheet around the revolving sleeve, a supporting device including a pair of supporters extendably connected to two ends of the central axle respectively, and an adjusting device for adjusting the length of at least one of the supporters so as to adjust an overall length of the sun shield device until two supporting end members of the two supporters respectively firmly pressed against two interior side walls of a trunk of an automobile so as to horizontally support the sun shield device within the trunk. Whereby, the user may simply open the trunk cover and pull the shading sheet from the revolving sleeve out of the trunk

through the gap formed between the opened trunk cover and trunk edge for at least covering the roof of the automobile.

U.S. Patent Number 6,513,858

Inventor: Xingkang Li, et al.

Issued: February 4, 2003

A spring tensioned roller and spaced tension bar have a vehicle cover folded in half and rolled around the spring tensioned roller. The rear half of the cover has an end rod and a central opening which allows it to be hooked over a trunk lock mechanism and kept secure when the trunk is shut. The front half of the cover has a lead rope or belt with two hooks for securing it under the hood of the vehicle or any other edged surface on the front of the car. The tensioned cover is elevated above the roof of the vehicle by the roller and tension bar for purposes of ventilation.

U.S. Patent Number 6,964,446

Inventor: Matthew B. Porter

Issued: November 15, 2005

A retractable vehicle cover apparatus for covering a vehicle comprises an elongated, hollow housing, and axle disposed therein for rotation about a central axis, and an elongated cover having a proximal end coupled with the axle and also having a distal end. The housing includes wall structure having an elongated aperture defined through the wall structure. The cover is fed through the aperture for selective movement between a retracted position where the cover is wrapped around the axle, and an extended position where a substantial portion of the cover extends from the housing. The cover includes an outer layer of aligned cover strips, a middle, elastic layer and an inner layer of aligned padding strips. The elastic layer biases the cover toward a rest width substantially the same length as the aperture to facilitate extension and retraction of the cover, and permits selective expansion of the cover in order to more fully cover the vehicle.

U.S. Patent Number 6,981,509

Inventor: Sergey Sharapov

Issued: Jan. 3, 2006

A protective cover for a vehicle comprising a sheet or a web of a flexible material that possesses a property of buckling or curving in the upward direction from the vehicle with the formation of a canopy-type shield for protecting the vehicle from direct sun rays, birds' droppings, etc. The sheet has a length exceeding the length of the upper surface periphery of the vehicle so that the upwardly curved canopy is formed either by applying two oppositely directed forces to the opposite ends of the sheet or by prestressing the sheet. The sheet can be made from plastic or a fabric that incorporates springing metal strips that tend to curve upward when they are in a free state. The sheet can be conveniently stored in wound state in a cylindrical cassette. Storage of the flexible material in a wound state enhances the property of bucking or curving when the sheet is withdrawn from the cassette.

German Patent Number DE 19610751

Inventor: Michael Koch

Issued: April 24, 1997

The cover has lateral roof frame parts (2) which extend along a support arc contour over the complete length of the closed cover and consist of several frame components arranged one after the other, the face ends of which work in conjunction with one another. In the rear area of the vehicle a drum is arranged, with which the cover can be wound up in a non-usage position. The frame components on each of the two roof sides are articulately connected to one another by a flexible belt (12) or wire rope (14), the rear ends of which are held by the drum. The belt or rope runs along the upper side of their frame components on the corresponding roof side.

U.S. Patent Number DE 10124574

Inventor: Helmut Hoffmann

Issued: November 28, 2002

A protective cover for a parked vehicle provides protection from either cold conditions or sunshine. A flexible sheet is stretched over the vehicle and is secured at each end to the vehicle. Spacers hold the sheet away from the vehicle for optimum protection. An alternate design has rigid panels positioned over the vehicle on spacers. The panels can be sheet material or frame over which flexible material is stretched.

While these vehicle covering devices may be suitable for the purposes for which they were designed, they would not be as suitable for the purposes of the present invention, as hereinafter described.

SUMMARY OF THE PRESENT INVENTION

A primary object of the present invention is to provide a vehicle covering device having a folding cover that is easily withdrawn and dispersed over a vehicle and easily retracted by a reeling mechanism

Another object of the present invention is to provide vehicle covering device having a folding crank handle for retracting a withdrawn folding cover utilizing a reeling action.

Yet another object of the present invention is to provide vehicle covering device having base elements to provide stability.

Still yet another object of the present invention is to provide vehicle covering device having a second rear folding cover that may be used in addition to the folding cover to cover the rear portion of the present invention.

Another object of the present invention is to provide vehicle covering device having an end bar for easy withdrawing and dispersing of the folding covers from the housing

Yet another object of the present invention is to provide vehicle covering device that may be stored in a vehicles trunk and utilized by withdrawing the folding cover through the trunks jam.

Still yet another object of the present invention is to provide vehicle covering device having a housing that contains a rotating axle for the winding and compact storage of a folding cover therein

Additional objects of the present invention will appear as the description proceeds.

The present invention overcomes the shortcomings of the prior art by providing vehicle covering device having a housing with integral base elements having a reeling means with a folding crank handle and an end bar to help in the manipulation and distribution of a folding cover through a trunk's jam and over a vehicle. Additionally the present invention may include a second folding cover utilized in the same manner for covering the rear portion of a vehicle as well.

In one aspect, the present invention provides a method and apparatus for protecting a motor vehicle with a spooled car cover that is selectively stored within the vehicle trunk wherein said method comprises: a) having the spooled car cover within the trunk of the vehicle until deployment is desired; b) opening the trunk to deploy the car cover; c) grasping the free end of the spooled cover by the rod-cord; d) feeding the rod-cord and attached cover through the opening between the jamb of the trunk lid and vehicle body; e) extending the cover toward the front of the vehicle until deployed into its open state; f) closing the trunk;; g) releasing the rear cover from its fastened state with the front cover; and h) extending the rear cover toward the rear of the vehicle until deployed into its open state. Preferably, the method comprises selectively storing the car cover from its deployed car cover state comprising: a) grasping the free end of the shorter trunk cover; b) draping the shorter truck cover over the longer front cover until the mating cover fasteners are aligned; c) positioning the fasteners into an engaged position; d) opening the trunk; e) rewinding the bilayered cover into the cover housing using the car cover housing crank; and f) closing the trunk. Preferably, the apparatus comprises: a) a housing for storing the car cover while not in use; b) an axle rotatable positioned within said housing; c) an exteriorly positioned foldable crank for rotating said axle; d) a cover rotatably mounted on said axle; e) a rod having the free end of the cover fixed thereto; and f) a pliable cord fixed to the distal

ends of the rod serving as a handhold for manipulating the car cover.

In another aspect, the present invention resides in a method for protecting a motor vehicle having a vehicle trunk with a lid wherein a spooled car cover having a front cover portion releasably fastened to a rear cover portion is selectively stored within the vehicle trunk, said method comprising:

- a) storing the spooled car cover within the trunk of the vehicle until deployment is desired; b) opening the trunk to deploy the car cover; c) grasping a free end of the spooled cover by a rod-cord; d) feeding the rod-cord and attached cover through an opening between a jamb of the trunk lid and vehicle body; e) extending the front cover portion toward a front of the vehicle until deployed into an open state; f) closing the trunk; g) releasing the rear cover portion from its fastened state with the front cover portion; and h) extending the rear cover portion toward a rear of the vehicle until deployed into an open state.

In a yet another aspect, the present invention resides in an apparatus for protecting a motor vehicle comprising:

- a) a housing for storing a car cover while not in use; b) an axle rotatably positioned within said housing; c) an exteriorly positioned foldable crank for rotating said axle; d) a cover rotatably mounted on said axle; e) a rod having a free end of the cover fixed thereto; and

f) a pliable cord fixed to the distal ends of the rod serving as a handhold for manipulating the car cover.

In a further aspect, the present invention resides in a method for protecting a motor vehicle with a spooled car cover in a housing configured to be removably secured to a rear hatch of the vehicle, said method comprising:

a) securing the housing to the rear hatch of the vehicle; b) grasping a free end of the spooled cover by a rod-cord; and c) extending the cover toward a front of the vehicle until deployed into an open state.

The foregoing and other objects and advantages will appear from the description to follow. In the description reference is made to the accompanying drawing, which forms a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. These embodiments will be described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized and that structural changes may be made without departing from the scope of the invention. In the accompanying drawing, like reference characters designate the same or similar parts throughout the several views.

The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is best defined by the appended claims.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

In order that the invention may be more fully understood, it will now be described, by way of example, with reference to the accompanying drawing in which:

FIGURE 1 is a side view of prior art.

FIGURE 2 is a side view of the present invention in use.

FIGURE 3 is a perspective view of the present invention in use.

FIGURE 4 is a perspective view of the present invention attached to a trunk by magnets.

FIGURE 5 is a sectional view of the present invention attached to a trunk by magnets.

FIGURE 6 is a perspective view of the present invention.

FIGURE 7 is a back perspective view of the present invention.

FIGURE 8 is a side view of the present invention.

FIGURE 9 is a side sectional view of the present invention.

FIGURE 10 is a side view of the present invention in use.

FIGURE 11 is a side view of the present invention in use.

FIGURE 12 is a perspective view of the present invention having a rear cover.

FIGURE 13 is a perspective view of the present invention is use.

FIGURE 14 is a side view of the present invention having a rear cover in use.

FIGURE 15 is a side sectional view of the present invention.

FIGURE 16 is a top view of the present invention in use.

FIGURE 17 is a front view of the present invention in use.

FIGURE 18 is a perspective view of an additional element of the present invention.

FIGURE 19 is a perspective view of an additional element of the present invention in use.

FIGURE 20 is a side view of the present invention having a rear cover in use.

FIGURE 21 is a side view of the present invention showing the L-shaped bracket.

FIGURE 22 is a perspective view of the present invention shown in Figure 21.

DESCRIPTION OF THE REFERENCED NUMERALS

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, the Figures illustrate the dashboard display system of the present invention. With regard to the reference numerals used, the following numbering is used throughout the various drawing Figures.

- 10 car cover of the present invention
- 11 user
- 12 vehicle
- 14 vehicle trunk
- 16 trunk jamb
- 18 climate
- 20 housing
- 22 axle
- 24 axle bearing
- 26 crank handle housing
- 28 crank

30	crank hinge
32	crank handle
34	housing slot
36	cover
38	front cover
40	front cover fastener
42	front cover window
44	rear cover
46	rear cover fastener
48	rear cover window
50	cover weights
52	rod
54	rod caps
56	pliable cord
58	stand
60	magnet
62	stand-leg cover
64	remote
66	motor

68 L-shaped bracket

70 first portion

72 second portion

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following discussion describes in detail one embodiment of the invention (and several variations of that embodiment). This discussion should not be construed, however, as limiting the invention to those particular embodiments, practitioners skilled in the art will recognize numerous other embodiments as well. For definition of the complete scope of the invention, the reader is directed to appended claims.

FIGURE 1 is an illustrative view of prior art. Motor vehicles **12** are exposed to climate **18** which accelerates the deterioration of the finish. The present invention provides an apparatus and method for protecting the vehicle from sun, rain and snow.

FIGURE 2 is a front view of the present invention. Shown is the apparatus of the present invention comprising car cover housing **20** having an interiorly positioned axle **22** that may include axle bearing **24**. On one end of housing **20** is crank handle housing **26** engaging axle **22** with crank **28** hingedly attached thereto. When crank **28** is pivoted via crank hinge **30**, crank handle **32**

is used to rotate axle **22**. Within the housing body is slot **24** substantially parallel with axle **22**. Cover **36** is spooled onto axle **22** and is extended and retracted through housing slot **34**. To prevent the free end of cover **36** from being wound into housing **20**, rod **52** has a length greater than slot **34**. In addition, rod **52** adds rigidity to the free end of cover **36** and provides pliable cord **56** to aid in handling cover **36**. Rod **52** may also include rod caps **54**. car cover housing **20** has stand legs **58** that may incorporate magnets **60** so that the apparatus can be attached to the interior trunk lid and provides stand-leg cover **62** to prevent marring of the vehicle finish.

FIGURE 3 is a rear view of the present invention. The car cover apparatus **10** comprises stand **58** and housing **20** having a spooled car **36** attached to rod **52** on its free end that provides pliable cord **56** to aid in the handling of the cover.

FIGURE 4 is a front view of the present invention. attached to a trunk by magnets. Shown is the deployable car cover apparatus of the present invention comprising car cover housing **20** having crank**28** hingedly attached by crank hinge **30**. When cover **36** is deployed by withdrawing cover **36** using pliable

cord **56**, it can easily be rewound using crank **28**.

FIGURE 5 is a sectional view of the present invention. Shown is the car cover **36** spooled on axle **22** within housing **20** supported by stand **58**. Housing **20** has housing slot **34** through which the cover is deployed and retracted. Cover **36** comprises front cover **38** and rear cover **44** with the leading edge of front cover **38** attached to rod **52** which has pliable cord **56** fixed to its distal ends to aid in deployment. Also shown is axle bearing **24**.

FIGURE 6 is an illustrative view of the deployed car cover. Shown is car cover **36** deployed from housing **20** through housing slot **34** comprising front cover **38** and rear cover **44** having mating fasteners **40**, **46** respectively. Front cover **38** is attached to rod **52** having pliable cord **56** to aid in deployment. The front and rear covers are of differing lengths with the larger extending from the trunk to the front of the car and the smaller extending from the trunk over the rear of the car. When the front cover **38** is deployed, the rear cover **44** attached at the appropriate length to the front cover by mating fasteners **40**, **46** is unfastened and draped over the rear of the vehicle..

FIGURE 7 is an illustrative view of the present invention in use. The present invention provides a spooled car cover **36** that is securely stored within the vehicle **12** truck and when deployed can only be removed by opening the vehicle trunk since the cover is securely bound within the trunk jamb. To use the cover **36**, the trunk **14** is opened and the free end is feed through the trunk jamb **16** across the top of the vehicle to its desired destination. The car cover is easily deployed from within the housing by virtue of a freewheeling axle. Once the cover **36** is extended to its open state, the trunk is closed binding the cover within the jamb **16**. The shorter rear cover **44** is releasably attached at its free end to the longer front cover **38** by fasteners **40, 46**, such as Velcro[®], that when detached allows the rear cover **44** to be draped over the rear of the vehicle. The process for storing the cover **36** is essentially reversing the deployment process. The shorter rear cover **44** is laid over the front cover **38** placing the fasteners **40, 46** into engagement whereafter the trunk is opened and the cover **36** is rewound into the cover housing **20** using the provided crank. The present invention provides that the car cover housing can be free standing within the trunk or magnetically attached to the underside of the trunk.

FIGURE 8 is a side view of the present invention in use. Illustrated is vehicle **12** having the car cover housing **20** magnetically fastened to the interior side of trunk **14** with the cover **36** free end fed through trunk jamb **16** where it can then be extended across the top of the vehicle.

FIGURE 9 is a perspective view of the present invention in use. The present invention **10** provides a spooled car cover **36** within housing **20** that can be positioned in a free standing state within trunk **14**. To deploy the cover, user **11** simply opens the trunk grasps the car cover free end using pliable cord **56** and inserts it through trunk jamb **16** before extending it across the top of vehicle **12**. The car cover is easily deployed through slot **34** within the housing by virtue of a freewheeling axle.

FIGURE 10 is a perspective view of the present invention in use. The present invention **10** provides a spooled car cover **36** within housing **20** having magnetic elements **60** so that the housing can be attached to the interior side of the trunk lid **14**. To deploy the cover, user **11** simply opens the trunk grasps the car cover free end using pliable cord **56** and inserts it through trunk jamb **16** before extending it across the top of vehicle **12**.

FIGURE 11 is an illustrative view of the cover housing attached to the trunk. Shown is car cover housing **20** having stand **58** with magnetic elements **60** and protective caps **62** so that the housing can be magnetically attached to the underside of trunk lid **14**.

FIGURE 12 is a side view of the car cover partially deployed. The present invention provides a spooled car cover **36** that is securely stored within the vehicle **12** truck and when deployed can only be removed by opening the vehicle trunk since the cover is securely bound within the trunk jamb. To use the cover **36**, the trunk **14** is opened and the free end is feed through the trunk jamb **16** across the top of the vehicle to its desired destination. The car cover is easily deployed from within the housing by virtue of a freewheeling axle. Once the cover **36** is extended to its open state, the trunk is closed binding the cover within the jamb **16**. The shorter rear cover **44** is releasably attached at its free end to the longer front cover **38** by fasteners **40, 46**, such as Velcro™, that when detached allows the rear cover **44** to be draped over the rear of the vehicle.

The covers are not of equal length therefore the shorter cover is attached on its free end to the longer front cover. In deployment the front cover is extended until correctly positioned then the free end (velcroed to the front cover)

of the shorter cover, which is now accessible can be detached and extended over the rear once the trunk is closed. In retracting, the rear cover is folded back over the front cover until the Velcro™ tabs mate. Then the truck is opened and the cover is wound into the housing. Interestingly, this solves another problem with the process of deploying two covers from the trunk, what do you do with the rear cover while it is being deployed since the trunk is open? You would still have to deploy both covers in one direction, close the trunk and then drape the rear cover over the trunk. The shorter rear cover is releasably attached to the longer cover to prevent fouling during extending and retracting from the housing. This also simplifies its use since your only deploying and retracting the cover into the housing in one direction.

FIGURE 13 is a perspective view of the car cover fully deployed. The shorter rear cover **44** is releasably attached at its free end to the longer front cover **38** by mating fasteners **40, 46**, such as Velcro™, so that when detached rear cover **44** can be draped over the rear of the vehicle **12**. The process for storing the cover **36** is essentially reversing the deployment process. The shorter rear cover **44** is laid over the front cover **38** placing the fasteners **40, 46** into engagement where then the trunk is opened and the cover **36** is rewound into the

cover housing **20** using the provided crank.

FIGURE 14 is a side view of the present invention in use. The present invention **10** provides a spooled car cover **36** that is securely stored within the vehicle **12** truck and when deployed can only be removed by opening the vehicle trunk since the cover is securely bound within the trunk jamb. To use the cover **36**, the trunk **14** is opened and the free end is feed through the trunk jamb **16** across the top of the vehicle to its desired destination. Once the cover **36** is extended to its open state, the trunk is closed binding the cover within the jamb **16**. The shorter rear cover **44** is then draped over the rear of the vehicle.

FIGURE 15 is a sectional view of the present invention bound within the trunk jamb. Shown is the present invention **10** having the car cover comprising front cover **38** and rear cover **44** bound when the trunk lid **14** of vehicle **12** is closed.

FIGURE 16 is a top view of the present invention in use. Shown is the car cover of the present invention **10** encompassing vehicle **12**. The car cover **36** comprises front cover **38** and rear cover **44** which extend from the trunk jamb **16**

in their respective directions.

FIGURE 17 is a front view of the present invention in use. Shown is car cover **36** having front cover **38** encompassing the front of vehicle **12**. Also shown is rod **52** providing rigidity to the free end and pliable cord **56** provided for ease of use in handling the car cover.

FIGURE 18 is a perspective view of an additional element of the present invention. Shown is the present invention **10** providing a remote control **64** and motor **66** whereby the cover of the present invention can be extended and retracted using said motor in conjunction with said remote.

FIGURE 19 is a perspective view of an additional element of the present invention in use. The present invention **10** provides a spooled car cover **36** within housing **20** that can be deployed using motor **66** and remote control **64**. To deploy the cover, user **11** simply opens the trunk grasps the car cover free end using pliable cord **56** and presses the remote to feed out enough of the cover to insert through the trunk jamb **16** before again depressing the remote to completely extended it across the top of vehicle **12**.

FIGURE 20 is another additional element of the present invention. The present invention **10** further provides for additional elements wherein car cover **36** is manufactured from a heat reflective material. Also provided for are transparencies whereby the front cover has a window **42** positioned so that the vehicle's **12** inspection and registration are viewable during use of the cover. The rear cover also has a transparency **48** whereby the license plate is viewable when the cover is in use.

In a preferred form, the car cover **36** is designed and sized to substantially cover an entire surface area of a body of the vehicle **12**. While not shown in the drawings, to assist in securing the car cover **36**, a peripheral edge of the car cover **36** has a tightening cord. When the car cover **36** is positioned on the vehicle **12**, the tightening cord fits tightly around a lower periphery of the vehicle **12**. Preferably, the tightening cord is elastic and a periphery of the cover **36** is pulled inwardly around a lower circumference of the vehicle **12**, to contact at each of the four tires.

FIGURE 21 shows an L-shaped bracket **68** having a first portion **70** and a second portion **72**. The L-shaped bracket **68** is used to secure the present invention **10** to a rear hatch or rear door of an sports utility vehicle, station

wagon, jeep or other vehicle having a rear door opening horizontally or vertically. The first portion **70** has a length substantially the same as a thickness of the rear hatch of the vehicle **12** to which the present invention **10** is to be attached. The second portion **72** is substantially perpendicular to the first portion **70** and is positioned for engagement with an inside of the rear door or hatch. When the rear hatch or door is closed, the present invention **10** is secured at an outside of the rear door or hatch with the first portion **70** positioned between a lower edge of the door or hatch and the vehicle **12**.

The first portion **70** is fixed to the housing **20**. Optionally, the housing also has the stands **58** and magnets **60** to additionally secure the housing to the rear hatch or door of the vehicle **12**.

While one L-shaped bracket **68** is shown, two or more L-shaped brackets could be fixed to the housing **20** for securing the invention **10**.

FIGURE 22 shows the L-shaped bracket in perspective view. While the L-shaped bracket **68** is shown as being one piece, it is also appreciated that the first portion **70** and second portion **72** could be separate pieces which are fixed to each other in a substantially perpendicular arrangement. Also, in a preferred embodiment the first portion is made of a deformable material so as to be

accommodated between the rear door and a body of the vehicle **12** when the rear door or hatch is closed to secure the housing **20** at an outside of the vehicle **12**.

It will be understood that each of the elements described above, or two or more together may also find a useful application in other types of methods differing from the type described above.

While certain novel features of this invention have been shown and described and are pointed out in the annexed claims, it is not intended to be limited to the details above, since it will be understood that various omissions, modifications, substitutions and changes in the forms and details of the device illustrated and in its operation can be made by those skilled in the art without departing in any way from the spirit of the present invention.

Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this invention.

CLAIMS

What is claimed is new and desired to be protected by letters patent is set forth in the appended claims.

1. A method and apparatus for protecting a motor vehicle with a spooled car cover that is selectively stored within the vehicle trunk wherein said method comprises:

- a) having the spooled car cover within the trunk of the vehicle until deployment is desired;
- b) opening the trunk to deploy the car cover;
- c) grasping the free end of the spooled cover by the rod-cord;
- d) feeding the rod-cord and attached cover through the opening between the jamb of the trunk lid and vehicle body;
- e) extending the cover toward the front of the vehicle until deployed into its open state;
- f) closing the trunk;;
- g) releasing the rear cover from its fastened state with the front cover; and
- h) extending the rear cover toward the rear of the vehicle until deployed into its open state.

2. The Method of Claim 1 further comprising selectively storing the car cover from its deployed car cover state comprising:

- a) grasping the free end of the shorter trunk cover;
- b) draping the shorter truck cover over the longer front cover until the mating cover fasteners are aligned;
- c) positioning the fasteners into an engaged position;
- d) opening the trunk;
- e) rewinding the bilayered cover into the cover housing using the car cover housing crank; and
- f) closing the trunk.

3. The apparatus of Claim 1 comprising:

- a) a housing for storing the car cover while not in use;
- b) an axle rotatable positioned within said housing;
- c) an exteriorly positioned foldable crank for rotating said axle;
- d) a cover rotatably mounted on said axle;
- e) a rod having the free end of the cover fixed thereto; and
- f) a pliable cord fixed to the distal ends of the rod serving as a handhold for manipulating the car cover.

4. The apparatus of Claim 3, wherein said housing has a slot within the housing and parallel to said axle whereby said cover can be extended and retracted therethrough.

5. The apparatus of Claim 4, wherein said rod is of a greater length than the housing slot to prevent the free end of the cover from being wound into the housing.

6. The apparatus of Claim 3, wherein said housing further comprises a pair of stand-legs positioned on opposing ends of said housing serving to stabilize the housing during deploying and retracting the car cover.

7. The apparatus of Claim 6, further comprising magnetic elements positioned within the base of the stand legs whereby the housing can be magnetically attached to the interior side of the trunk lid.

8. The apparatus of Claim 7, further comprising protective members capping the stand-legs and magnetic elements to prevent marring of the vehicle surface.

9. The apparatus of Claim 3, wherein said cover is comprised of an extendable front portion and an extendable rear portion.

10. The apparatus of Claim 9 wherein the front portion and rear portion having matingly engagable fasteners whereby the covers being of different lengths can be releasably fastened together during storage and releasably disengaged during use.

11. The apparatus of Claim 3, further comprising transparent member whereby the vehicle's inspection and registration stickers are visible and a second transparent portion is situated so that the vehicle's license plate is viewable.

12. The apparatus of Claim 3 wherein the car cover is manufactured from a heat reflective material.

13. A method for protecting a motor vehicle having a vehicle trunk with a lid wherein a spooled car cover having a front cover portion releasably fastened to a rear cover portion is selectively stored within the vehicle trunk, said method comprising:

- a) storing the spooled car cover within the trunk of the vehicle until deployment is desired;
- b) opening the trunk to deploy the car cover;
- c) grasping a free end of the spooled cover by a rod-cord;
- d) feeding the rod-cord and attached cover through an opening between a jamb of the trunk lid and vehicle body;
- e) extending the front cover portion toward a front of the vehicle until deployed into an open state;
- f) closing the trunk;
- g) releasing the rear cover portion from its fastened state with the front cover portion; and
- h) extending the rear cover portion toward a rear of the vehicle until deployed into an open state.

14. The method of Claim 13 further comprising selectively storing the car cover into a cover housing having a cover housing crank from its deployed car cover state comprising:

- a) grasping the free end of the rear cover portion;
- b) draping the rear cover portion over the front cover portion until mating cover fasteners are aligned;
- c) positioning the fasteners into an engaged position;

- d) opening the trunk;
- e) rewinding the bilayered cover into the cover housing using the car cover housing crank; and
- f) closing the trunk.

15. An apparatus for protecting a motor vehicle comprising:

- a) a housing for storing a car cover while not in use;
- b) an axle rotatably positioned within said housing;
- c) an exteriorly positioned foldable crank for rotating said axle;
- d) a cover rotatably mounted on said axle;
- e) a rod having a free end of the cover fixed thereto; and
- f) a pliable cord fixed to the distal ends of the rod serving as a handhold for manipulating the car cover.

16. The apparatus of Claim 15, wherein said housing has a housing slot within the housing and parallel to said axle whereby said cover can be extended and retracted therethrough.

17. The apparatus of Claim 16, wherein said rod is of a greater length than the housing slot to prevent the free end of the cover from being wound into the housing.

18. The apparatus of any one of Claims 15 to 17, wherein said housing further comprises a pair of stand-legs positioned on opposing ends of said housing serving to stabilize the housing during deploying and retracting the car cover.

19. The apparatus of Claim 18, wherein said stand legs further comprise magnetic elements positioned within the base of the stand-legs whereby the housing can be magnetically attached to an interior side of a trunk lid.

20. The apparatus of Claim 19, wherein said stand-legs further comprise protective members capping the stand-legs and magnetic elements to prevent marring of the vehicle surface.

21. The apparatus of any one of Claims 15 to 20, wherein said cover is comprised of an extendable front portion and an extendable rear portion.

22. The apparatus of Claim 21, wherein the front portion and rear portion have matingly engagable fasteners and are releasably fastened together during storage and releasably disengaged during use.

23. The apparatus of any one of Claims 15 to 22, wherein the cover has at least one transparent portion wherein a portion of the vehicle selected from the group consisting of a license plate and identification plate is viewable through the at least one transparent portion when the cover is positioned over the vehicle.

24. The apparatus of any one of Claims 15 to 23, wherein the car cover is manufactured from a heat reflective material.

25. The apparatus of any one of Claims 15 to 24, wherein the car cover is sized to substantially cover an entire surface area of the vehicle body.

26. The apparatus of Claim 25, wherein a peripheral edge of the car cover has a tightening cord for securing the peripheral edge of the car cover around a lower periphery of the vehicle.

27. The apparatus of Claim 26, wherein the tightening cord is elastic.

28. The apparatus of any one of Claims 15 to 27, wherein at least one bracket is positioned on said housing, the bracket comprising a first portion having a length substantially the same as a thickness of a rear hatch of the

vehicle and a second portion substantially perpendicular to the first portion and engageable with an inside of the rear hatch such that the housing is removably securable at an outside surface of the rear hatch by the bracket.

29. A method for protecting a motor vehicle with a spooled car cover in a housing configured to be removably secured to a rear hatch of the vehicle, said method comprising:

- a) securing the housing to the rear hatch of the vehicle;
- b) grasping a free end of the spooled cover by a rod-cord; and
- c) extending the cover toward a front of the vehicle until deployed into an open state.




FIG. 1
(PRIOR ART)




FIG. 3





FIG. 4

**FIG. 5**





FIG. 6



100%




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13





FIG. 14

**FIG. 15**




FIG. 16




FIG. 17




FIG. 18




FIG. 19






FIG. 20

**FIG. 21**

**FIG. 22**

