

Sept. 5, 1933.

E. E. HARRINGTON

Re. 18,939

CATAMENIAL BANDAGE HOLDER

Original Filed Sept. 15, 1928

Fig. 1.




Fig. 2.




Fig. 3.





Fig. 4.



Inventor

Earl E. Harrington

By

Charles B. Mann Jr.
Attorney

UNITED STATES PATENT OFFICE

18,939

CATAMENIAL BANDAGE HOLDER

Earl E. Harrington, Washington, D. C., assignor
to Max Hain, Los Angeles, Calif.

Original No. 1,730,765, dated October 8, 1929,
Serial No. 306,220, September 15, 1928. Ap-
plication for reissue June 20, 1931. Serial
No. 545,796

6 Claims. (Cl. 128—290)

This invention relates to an improved cata-
menial bandage holder and has for its object to
provide an improved pad holder and protector
whereby the pad may be held in place on the
holder by clamping means of a novel character.

5 The present invention is a direct improvement
on the structure set forth in my Letters Patent
No. 1,730,818 dated October 8, 1929 and is directed
to the features whereby the clamping tapes
which secure the pad to the carrier are operated
10 by lengthwise strain on the opposite ends of the
carrier supports.

The invention is illustrated in the accom-
panying drawing, wherein,—

15 Fig. 1 shows the device in perspective attached
to and suspended from a body band.

Fig. 2 illustrates the pad holder as viewed from
the under side thereof.

20 Fig. 3 shows the holder with a pad in place
thereon as viewed from the upper side thereof,
and

Fig. 4 illustrates an enlarged sectional detail
through one end of the holder and the pad there-
of with the clamping tape engaging the end of
the pad,—the section being taken substantially
25 on the line 4—4 of Fig. 3.

In the drawing, the numeral 5 designates a
fabric strip having a wide intermediate portion
6 and the narrower tab-like opposite ends 7.

30 On one side of the wider intermediate portion
I provide a sheet or strip of moisture-proof ma-
terial such as thin rubber 8 and I provide a
binding 9 which extends preferably all the way
around the fabric strip, which binding engages
the longitudinal edges of the two strips 5 and
35 8 and thus permanently secures those strips to-
gether with the rubber strip on top of the fab-
ric strip.

40 The binding is secured by a continuous row
of stitching 10, and the opposite end edges 11
of the rubber strip are secured in a crosswise
direction to the fabric strip by rows of stitch-
ing 12.

45 Near each end of the rubber strip 8, but spaced
from the end-edges 11 thereof, I provide two
perforations 13 which latter extend through both
the rubber strip 8 and the fabric strip 5. The
perforations are arranged in pairs near each end
of the rubber strip, and each perforation of a
pair is spaced from the longitudinal side edge of
50 the holder and substantially on a straight line
with the tape bound side edges of the tab-like
ends 7. There is an advantage in locating the
perforations in line with and at the rear of the
tape-bound side edges of the end tabs as will
55 presently be pointed out.

The two ends 14 of a tape are passed through
the spaced perforations 13 from the upper rubber
strip side so that the ends 14 will project at the
under side of the fabric strip and thus forms a
cross-stretch 15, of the tape over the rubber strip.
The two ends 14 of the tape are extended for-
wardly onto the tab-ends 7 and one tape end is
60 inserted beneath the binding 9 at one longitudi-
nal side-edge of the tab while the other tape end
is inserted beneath the binding at the opposite
longitudinal side-edge of the tab.

65 In this way the two tape-ends 14 are perman-
ently secured to the opposite edges of the tab
7 by the same stitches 10, which secure the bind-
ing 9 to the edges of the tab.

70 A feature of importance resides in the particu-
lar manner in which the tape 14, 15 is applied,
for it will be noted that not only do the tape ends
14 extend straight back from the longitudinally-
bound side edges of the tabs to the perforations
13, but, the forward ends of this tape are at-
75 tached to the tab at a point which requires a
cross-fold or plait 16 to be made in the fabric
strip 5, between the attached ends of the tape and
the perforations. This fold 16 is shown in an
exaggerated form in Fig. 4 of the drawing and
80 has a special object in view.

It is to be understood that the absorbent pad
17, is placed on the upper rubber strip 8 and that
the forward and rear ends of the pad are to be
passed beneath the cross-stretch 15 of the tape
85 so that said stretch, when the tape ends are
pulled taut, will clamp said pad ends against the
rubber strip.

To effect this clamping by the cross-stretch 15,
I attach the ends 14 of the tape far enough for-
90 ward on the tabs 7 and in front of the cross
fold or plait 17, so that when the holder is at-
tached to a body belt 18 by the forward ends of
its tabs 7, the strain will be transferred through
the tape ends back to the cross stretch and this
95 will draw taut across the ends of the pad before
the fold or plait 17 can stretch out.

Moreover, the strain is on the reinforced bound
side edges of the tabs and then straight back
100 through the tape-ends to the perforations, so that
the tabs are kept stretched in a cross-wise direc-
tion and the strain is directed longitudinally
through the holder at opposite sides of a longitu-
dinal center line.

Having described my invention, I claim,— 105

1. A catamenial bandage holder comprising a
flexible strip on which a pad may be laid said
strip having two spaced openings therethrough, a
tape extending through said openings from the
upper side of the strip and the two ends of the
110

tape extending toward the adjacent end of the holder strip and being attached to said strip-end so as to cause a fullness in the strip between said forward attached ends of the tape and the spaced openings through said strip.

2. A catamenial bandage holder comprising a flexible strip on which a pad may be laid said strip having two crosswise-spaced openings near each end thereof, a tape passed through each pair of openings so as to produce a cross stretch of the tape on the upper side of the strip while the two ends of the tape pass through to the lower side of the strip, said two tape-ends extending toward the adjacent end of the holder strip and being permanently attached thereto,—the strip having a lengthwise fullness between the attached ends of the tape and said openings whereby when the ends of the strip are pulled to take up the fullness the cross-stretch of the tape will be drawn toward the upper side of the strip to clamp a pad thereof.

3. A catamenial bandage holder comprising a flexible strip on which a pad may be laid said strip having its ends somewhat reduced to form tabs, the strip being provided with two spaced perforations adjacent the inner end of each of the tabs, a tape having its two ends passed through said perforations from the upper side of the strip so that the ends of the tape will project on the under side of the strip said tape-ends extending from said perforations toward the adjacent tab-end of the holder and the holder being folded crosswise under the tape-ends whereby to produce a fullness in the holder and to draw the intermediate part of the tape against the upper side of the strip.

4. A carrier comprising a flexible strip for supporting a pad, a tape having a portion movably mounted in respect to said strip and adapted to embrace the pad, a portion of said strip forming a supporting means for the carrier, said tape having a lengthwise fullness and connection with said strip supporting means and binding the pad on the carrier when strain is placed on the strip support to remove the lengthwise fullness when strain is placed upon the same when in position upon a wearer.

5. A device of the character described, comprising a strip on which a pad may be laid, a movable cord for embracing said pad, a portion of said strip providing a strip supporting means, said cord attached to said strip supporting means to form in said means a fullness intermediate the length of the cord, and said fullness being taken up and said cord binding the pad on the strip when strain is placed upon the strip supporting means.

6. A device of the kind described comprising a carrier for supporting a pad, supporting means for the carrier adapted to have a cross fold, a cord having a portion movably mounted in respect to said carrier and having a connection with said supporting means for binding a pad upon said carrier, said cord being adapted to embrace and bind the pad upon the carrier when strain is placed upon the supporting means and the cross fold of the carrier is taken up when in position upon a wearer.

EARL E. HARRINGTON.

40

45

50

55

60

65

70

75

80

85

90

95

100

105

110

115

120

125

130

135

140

145

150