

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 October 2003 (16.10.2003)

PCT

(10) International Publication Number
WO 03/085634 A2

(51) International Patent Classification⁷: **G09G**

(21) International Application Number: PCT/US03/09563

(22) International Filing Date: 26 March 2003 (26.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/114,395 1 April 2002 (01.04.2002) US

(71) Applicant: **SONY ELECTRONICS INC.** [US/US]; 1
Sony Drive, Park Ridge, NJ 07656 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor: **RUSS, Ben**; 10915 Sunny Meadow Court, San Diego, CA 92126 (US).

(74) Agent: **ROGITZ, John, L.**; Rogitz & Associates, 750 B Street, Suite 3120, San Diego, CA 92101 (US).

(54) Title: METHOD FOR MAKING COLOR SEPARATOR FOR EMISSIVE DISPLAY



(57) Abstract: A method for making a color separator configured for a large screen display (12) includes covering red, green, and blue subpixels (44) of a phosphor display (12) with a refraction layer (46), and then ink-jet printing a color selection mask (30) layer onto the refraction layer (46) to shield the blue and green subpixels (44) from a first beam, shield the red and green subpixels (44) from a second beam, and shield the red and blue subpixels (44) from a third beam.



WO 03/085634 A2

METHOD FOR MAKING COLOR SEPARATOR FOR EMISSIVE DISPLAY

I. Field of The Invention

The present invention relates generally to image displays.

II. Background Of The Invention

5 Image displays include emissive displays, such as phosphor displays used in cathode tube-based television and computer monitors, and transmissive displays, such as projection displays used for large screen TVs. An emissive display works by emitting visible light from pixels that are excited by, e.g., electron beams or fluorescent lamps. In the case of conventional electron beam-based
10 displays, the electron beam is scanned across the pixels as appropriate to excite the pixels to produce a demanded image. In the case of fluorescent lamp-based displays such as plasma displays, ultraviolet light from a gas discharge is directed to appropriate pixels that are physically shielded from each other, with the pixel illumination pattern necessary to produce the demanded image not being
15 established by scanning the UV light, which is simply a discharge from the lamp, but by appropriately blocking the UV light to impinge only on the desired pixels. Both of the above-mentioned emissive displays require the presence of a vacuum within the device, which can complicate manufacturing and raise costs.

Because the weight of some emissive displays becomes infeasibly large in
20 the case of large screen displays, e.g., displays having sizes of 40"-60" or more, the above-mentioned transmissive displays have been provided, an example of

which is the projection display. A projection display works by projecting pixellated light from a relatively small source onto a relatively large projector, which "transmits" the light toward the viewers.

As recognized herein, while effective, large screen projection-type displays
5 suffer from the drawback of relatively low image quality, compared to the image quality afforded by a smaller emissive display. On the other hand, current emissive display technology, as noted above, cannot easily be used to establish large screen displays owing to weight and other practical restrictions. Nevertheless, the present invention recognizes that it would be desirable to
10 provide a large screen emissive display to overcome the image quality drawback of many large transmissive displays.

SUMMARY OF THE INVENTION

A method for making a color separator configured for an image display apparatus includes providing a substrate, and establishing phosphor-based red,
15 green, and blue subpixels on the substrate. The subpixels are covered with at least one refraction layer. A color selection mask layer is printed onto the refraction layer to shield the blue and green subpixels from a first beam, shield the red and green subpixels from a second beam, and shield the red and blue subpixels from a third beam.

20 Preferably, the display is a large screen phosphor display, and the color selection mask is ink-jet printed onto the refraction layer. The color selection mask defines plural excitation light apertures defining variable pitches established

based on the locations of the respective excitation light apertures relative to the display.

In another aspect, a method for producing a demanded image includes establishing a mask on a phosphor display. The mask has apertures defining
5 pitches between adjacent apertures. At least one pitch is different from another pitch. The method includes receiving the demanded image, and directing light onto a display through the mask.

The details of the present invention, both as to its structure and operation, can best be understood in reference to the accompanying drawings, in which like
10 reference numerals refer to like parts, and in which:

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic diagram of the present emissive display, using a phosphor screen;

Figure 2 is a schematic diagram of the variable pitch mask; and

15 Figure 3 is a schematic diagram of an alternate phosphor screen assembly.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring initially to Figure 1, a display apparatus is shown, generally designated 10, which includes an emissive display 12 that defines plural pixels, each pixel in turn being defined by three subpixels in accordance with emissive
20 display principles known in the art, namely, red, green, and blue subpixels. In the non-limiting illustrative embodiment shown in Figure 1, the display 12 is a large screen phosphor display, the pixels of which may be composed of, e.g., Zinc Sulfide. By "large screen" is meant that the operational "D" of the display 12 is

at least forty inches (40") (about one hundred centimeters) and can be sixty inches (60") (about one hundred fifty centimeters) or more. The principles advanced herein, however, can be applied to smaller displays, as well as to other emissive displays, such as plasma displays. In any case, owing to the structure disclosed below, the display 12 operates at atmospheric pressure, i.e., the display 12 does not require a vacuum in which to operate.

As can be appreciated in reference to Figure 1, the display 12 is irradiated by plural moving light beams 14. In the preferred embodiment, first through third beams 14 are used. As disclosed further below, a first one of the beams 14 can irradiate only red subpixels, a second one of the beams 14 can irradiate only green subpixels, and a third one of the beams 14 can irradiate only blue subpixels. In the presently preferred embodiment, the beams 14 are ultraviolet (UV) beams and more preferably are UV laser beams that originate at a laser 16.

Explaining Figure 1 from the laser 16, a source beam 18 is emitted by the laser 16 that is split into the three beams 14 by a beamsplitter 20 device. The beamsplitter device 20 can include two beamsplitters, one of which splits the source beam 18 in two and another of which splits one of the resulting two beams into two beams, to establish the preferred three beam arrangement shown.

The three beams 14 then propagate toward respective light valves 22. In the preferred embodiment, the light valves 22 are grating light valves (GLVs). In non-limiting examples, the GLVs may be those disclosed in U.S. Pat. No. 5,311,360, incorporated herein by reference.

Accordingly, the light valves 22 reflect their respective beams 14 in accordance with light valve principles known in the art. Specifically, each light valve 22 can include a one-dimensional row of movable mirrors which can reflect light. In a particularly preferred, non-limiting embodiment, six adjacent mirrors per
5 subpixel are used. A processor 24 is operably engaged with the light valves 22 to cause each valve 22 to modulate its respective beam 14 in accordance with a demanded image received from, e.g., a television tuner, a computer, or other video source. That is, the mirrors of the light valves 22 are moved as appropriate to reflect or not the respective beam 14, to thereby establish the position of the
10 beam 14 in the dimension defined by the light valves 22 for any given frame of the demanded image.

Thus, the beams 14 are essentially scanned in one dimension in accordance with the demanded image. To achieve the requisite two-dimensional scan, each beam 14 propagates from its respective light valve 22 to a respective
15 scanning mirror 26, each of which oscillates about its axis as driven by a respective motor 28 in a dimension that is orthogonal to the dimension of the light valves 22. The scanning mirrors 26 need not be controlled in accordance with the demanded image; rather, only the light valves 22 need be controlled to produce the demanded image, with the processor 24 taking account of the orthogonal
20 scanning of the beams 14 provided by the scanning mirrors 26.

If desired, a mask 30 can be interposed between the scanning mirrors 26 and the display 12 to establish a light barrier between adjacent pixels. The mask 30 defines a two-dimensional grid of differently-sized excitation light apertures 32.

The mask 30 can include an opaque substrate and the apertures 32 can be established by openings in the substrate. Alternatively, the mask 30 can include a transparent substrate and the apertures can be established by ink-jet printing an opaque pattern on the substrate, with non-printed portions of the substrate
5 establishing the apertures.

As best shown in Figure 2, the sizes of the excitation light apertures 32 and/or pitch (that is, the spacing between adjacent excitation light apertures 32) are established based on the locations of the respective excitation light apertures 32 relative to the display 12. Specifically, to allow for uniform radiation intensity
10 of pixels near the center of the display 12 and pixels near the edges of the display 12, the size and/or pitch of the excitation light apertures 32 can change from the center of the display 12 outward. Accordingly, in one non-limiting embodiment the sizes of the excitation light apertures 32 and/or the spacing between excitation light apertures 32 that are near the center of the display 12 can be smaller than
15 the sizes of the excitation light apertures 32 and/or the spacing between excitation light apertures 32 that are nearer the edges of the display 12. The particular excitation light aperture size/pitch variation is established based on the geometry of the system 10.

Figure 3 shows an alternate display, generally designated 40, which
20 includes a transparent, e.g., glass, substrate 42 and plural red, green, and blue subpixels 44 that are established on the substrate 42. It is to be understood that three adjacent subpixels establish a pixel. A transparent light refracting layer 46 covers the pixels and is opposed to the substrate 42 as shown. If desired, the

layer 46 can be made of plural sublayers, i.e., a first sublayer for refracting a beam that is to excite only red subpixels, a second sublayer for refracting a beam that is to excite only green subpixels, and a third sublayer for refracting a beam that is to excite only blue subpixels.

5 In any case, as shown in Figure 3, the UV beams 14 are directed against the refracting layer 46. The location and configuration of the light valves 22 relative to the display 12 and the light valve control afforded by the processor 24 ensures that the light valve 22 that is to reflect the beam for exciting only red subpixels reflects the beam at a set of angles α with respect to the plane of the
10 light refracting layer 46, the light valve 22 that is to reflect the beam for exciting only green subpixels reflects the beam at a set of angles β , and the light valve 22 that is to reflect the beam for exciting only blue subpixels reflects the beam at a set of angles γ , with the angles α , β , and γ for any one pixel being different from each other. Consequently, the three beams are refracted at differing angles by
15 the refracting layer 46 only onto respective red, green, and blue subpixels 44.

To ensure that the three beams impinge on only their intended subpixels, a color selection mask layer 48 can be juxtaposed with the refracting layer 46 for shielding the blue and green subpixels from the first beam, shielding the red and green subpixels from the second beam, and shielding the red and blue subpixels
20 from the third beam. The color selection mask layer 48 can be deposited onto the refracting later 46 as one or more thin films by, e.g., ink jet printing the film onto the refracting layer 46. Like the mask 30 shown in Figure 1, the color selection mask layer 48 can define apertures 50 that have a variable pitch and/or variable

size, based on the positions of the apertures 50 relative to the center of the substrate 42.

While the particular METHOD FOR MAKING COLOR SEPARATOR FOR EMISSIVE DISPLAY as herein shown and described in detail is fully capable of attaining the above-described objects of the invention, it is to be understood that it is the presently preferred embodiment of the present invention and is thus representative of the subject matter which is broadly contemplated by the present invention, that the scope of the present invention fully encompasses other embodiments which may become obvious to those skilled in the art, and that the scope of the present invention is accordingly to be limited by nothing other than the appended claims, in which reference to an element in the singular is not intended to mean "one and only one" unless explicitly so stated, but rather "one or more". All structural and functional equivalents to the elements of the above-described preferred embodiment that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the present claims. Moreover, it is not necessary for a device or method to address each and every problem sought to be solved by the present invention, for it to be encompassed by the present claims. Furthermore, no element, component, or method step in the present disclosure is intended to be dedicated to the public regardless of whether the element, component, or method step is explicitly recited in the claims. No claim element herein is to be construed under the provisions of 35 U.S.C. §112, sixth paragraph, unless the element is expressly recited using the phrase "means for"

or, in the case of a method claim, the element is recited as a "step" instead of an "act".

WE CLAIM:

WHAT IS CLAIMED IS:

1. A method for making a color separator configured for an image display apparatus (10, 42), comprising the acts of:
 - providing a substrate (12, 42);
 - 5 establishing phosphor-based red, green, and blue subpixels on the substrate;
 - covering the subpixels with at least one refraction layer; and
 - printing a color selection mask (30) layer onto the refraction layer to shield the blue and green subpixels from a first beam (14), shield the red
 - 10 and green subpixels from a second beam (14), and shield the red and blue subpixels from a third beam (14).
2. The method of Claim 1, wherein the display (10, 42) is a large screen display.
3. The method of Claim 1, wherein the display (10, 42) is a phosphor
- 15 display.
4. The method of Claim 3, wherein the phosphor display (10, 42) operates at atmospheric pressure.
5. The method of Claim 1, wherein the color selection mask (30) is ink-jet printed onto the refraction layer.
- 20 6. The method of Claim 1, wherein the color selection mask (30) defines plural excitation light apertures (36, 50) defining variable pitches established based on the locations of the respective excitation light apertures (36, 50) relative to the display.

7. The method of Claim 1, wherein the source is a laser (16).
8. A method for producing a demanded image, comprising:
establishing a mask (30) on a phosphor display (12), the mask (30)
having apertures (32) defining pitches between adjacent apertures, at least
5 one pitch being different from another pitch;
receiving the demanded image; and
directing light onto a display (12) through the mask (30).
9. The method of Claim 8, wherein the directing act is undertaken using
plural light valves (22), the light valves (22) being controlled in accordance with
10 the demanded image.
10. The method of Claim 8, wherein the display (12) is a phosphor
display.

1/1




Fig. 1




Fig. 2




Fig. 3