

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 September 2011 (22.09.2011)

(10) International Publication Number
WO 2011/115658 A2

(51) International Patent Classification:

A23G 9/04 (2006.01)

(21) International Application Number:

PCT/US2011/000361

(22) International Filing Date:

28 February 2011 (28.02.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

12/661,399 16 March 2010 (16.03.2010) US

(71) Applicant (for all designated States except US): **VITAMIX CORPORATION** [US/US]; 8615 Usher Road, Cleveland, Ohio 44138 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KOZLOWSKI, Eugene J.** [US/US]; 806 Savannah Trail, Medina, Ohio 44256 (US). **BARNARD, John K.** [US/US]; 9155 Devonshire Drive, Olmstead Falls, Ohio 44138 (US).


(74) Agents: **GREIVE, Edward G.** et al.; Renner, Kenner, Greive, Bobak, Taylor & Weber, First National Tower, Suite 400, 106 S. Main Street, Akron, Ohio 44308-1412 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,

[Continued on next page]

(54) Title: CUP HOLDING ASSEMBLY FOR A FOOD MIXING MACHINE



(57) Abstract: A food mixing machine (20) has an agitator (25) to mix food in a cup (C). A cup holder (31) is provided with a flexible boot (32) which receives the cup (C). The cup holder (31) is moveable through an opening (90) in the machine (20) and carries a gripping assembly (33) and an actuator assembly (34). The actuator assembly (34) is moveable relative to the gripping assembly (33) and is biased by springs (35) to maintain fingers (56) of the gripping assembly (33) in engagement with the cup (C). When it is desired to release the cup (C), a release assembly (80) overcomes the bias of the springs (35). As the cup holder (31) moves through the opening (90), the area between the cup holder (31) and the opening (90) is sealed by a seal assembly (91) so that food materials cannot go through the opening (90).



LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, **Published:**

SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, — *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

CUP HOLDING ASSEMBLY FOR A FOOD MIXING MACHINE

TECHNICAL FIELD

This invention relates to a machine which mixes food products in a cup. More particularly, this invention relates to a cup holding assembly for such a machine. More specifically, this invention relates to a cup holding assembly which automatically engages the cup while the food is being mixed therein, and releases the cup when the mixing process is completed.

10

BACKGROUND ART

Many establishments, such as fast food restaurants or the like, mix food products, such as blending condiments into soft serve ice creams, smoothies or the like, directly in the cup to be used by the customer to consume the product. It is a time saving advantage if such machines are fully automated. In such situations, the cup is filled with the products to be blended and is placed in a cup holder. Upon activation of the machine, the cup holder can rotate and can move upwardly to allow an agitator to be received in the cup and mix the products contained therein. The cup holder then moves downwardly to the home position and the machine is deactivated so that the cup can be removed from the cup holder with the food product therein being mixed and ready for consumption.

A problem with this process is that the cup could, at times, become dislodged from the cup holder. That is, as the cup holder and agitator rotate, the turbulence created in the food product could cause the cup to rotate and/or wobble in the cup holder. Such could not only allow food to spill out of the cup, but also if the turbulence is great enough, the cup itself could come out of the cup holder. Such would particularly be the case if the cup were permitted to wobble so much that it was engaged by the agitator thereby being easily dislodged from the cup holder.

30 An additional problem with some machines of the prior art is that food product spillage can reside on the outside of the cup holder. Such could occur based on normal spillage of food as it is being mixed, which could readily happen if the cup is overfilled, or it could occur based on the wobbling of the cup previously described. If unabated, such spillage may then run down the

sides of the cup holder and into the operating components of the machine causing contamination thereto.

The need exists, therefore, for a system of holding a cup stable in a cup holder and also sealing the outside of the cup holder to prevent 5 contamination in the event of food spillage from the cup.

DISCLOSURE OF THE INVENTION

It is thus an object of one aspect of the present invention to provide a food mixing machine with a cup holding assembly that grips the cup while 10 food is being mixed therein and that releases the cup when the mixing process is completed.

It is an object of another aspect of the present invention to provide a cup holding assembly that it is provided with a seal around the exterior periphery of the cup holder.

15 These and other objects of the present invention, as well as the advantages thereof over existing prior art forms, which will become apparent from the description to follow, are accomplished by the improvements hereinafter described and claimed.

In general, a food mixing machine mode in accordance with one 20 aspect of the present invention has an agitator to mix food in a cup and includes a cup holder adapted to receive the cup therein. A gripping member is positioned within the cup holder. A gripping actuator is moveable relative to the gripping member so that upon movement of the actuator, the gripping member selectively engages or releases the cup.

25 In accordance with another aspect of the invention a food mixing machine includes a housing having an opening. A cup holder is adapted to be moved through the opening. A seal assembly is carried by the housing and includes a seal to engage the cup holder as the cup holder moves through the opening.

30 These aspects combine to provide a food mixing machine having an agitator to mix food in a cup and including a housing having an opening. A cup holder is adapted to receive the cup and move through the opening. A seal assembly is carried by the housing and includes a seal to engage the cup holder as the cup holder moves through the opening. A gripping member is positioned within the cup holder. An actuator is moveable relative to the 35

gripping member so that upon movement of the actuator, the gripping member selectively engages or releases the cup.

The invention also contemplates a method of mixing food in a cup with an agitator which includes the steps of placing the cup in a cup holder, moving the cup toward the agitator while at the same time gripping the cup in the cup holder, using the agitator to mix the food, moving the cup holder away from the agitator, and releasing the cup from the cup holder.

A preferred exemplary cup holder for a food mixing machine according to the concepts of the present invention is shown by way of example in the accompanying drawings without attempting to show all the various forms and modifications in which the invention might be embodied, the invention being measured by the appended claims and not by the details of the specification.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a somewhat schematic fragmented representation of a food mixing machine having the cup holding assembly of the present invention.

Fig. 2 is a top perspective exploded view of the components of the cup holding assembly.

Fig. 3 is a bottom perspective exploded view of the components of the cup holding assembly.

Fig. 4 is a top perspective view of the cup holder component of the cup holding assembly.

Fig. 5 is a bottom perspective view of the cup holder component of the cup holding assembly.

Fig. 6 is a perspective view of the cup gripping component of the cup holding assembly.

Fig. 7 is a perspective view of one half of the actuator component of the cup holding assembly.

Fig. 8 is a perspective view of the assembled cup gripping and actuator components.

Fig. 9 is a perspective view of the cup holding assembly showing the cup broken away.

Fig. 10 is a sectional view taken substantially along line 10-10 of Fig. 1.

Fig. 11 is a sectional view taken substantially along line 11-11 of Fig. 1.

Fig. 12 is a sectional view taken substantially along line 12-12 of Fig. 1 and showing the cup holding assembly gripping the cup.

5 Fig. 13 is a sectional view like Fig. 12 but showing the cup released from the cup holding assembly.

Fig. 14 is an exploded top perspective view showing the components of the seal for the cup holding assembly.

10 Fig. 15 is an exploded bottom perspective view showing the components of the seal for the cup holding assembly.

Fig. 16 is a sectional view taken substantially along line 16-16 of Fig. 1.

PREFERRED EMBODIMENT FOR CARRYING OUT THE INVENTION

15 A food mixing machine is somewhat schematically shown in Fig. 1 and is indicated generally by the numeral 20. Machine 20 includes a housing 21 which covers the components of the machine and which includes a lower platform 22, an intermediate platform 23 and an upper platform 24. An agitator 25, shown to be in the configuration of a spoon, extends downwardly from upper platform 24 and is rotated by a motor (not shown) carried by one of the platforms. Agitator 25 is designed to mix food products in a cup C. A travel plate 26 is moveable upwardly and downwardly by a motor (not shown) carried by one of the platforms. Travel plate 26 also carries a shaft 27, bearings 28 and a pulley 29 which is driven by a motor (not shown) carried by one of the platforms, as will hereinafter be described in more detail. Reference is made 20 to U.S. Patent Application Serial No. 12/460,273 filed July 17, 2010 for whatever details are necessary for the complete understanding of a typical machine 20 and its operation.

25

30 Travel plate 26 carries a cup holding assembly generally indicated by the numeral 30. The basic components of cup holding assembly 30 are shown in Fig. 2 and 3 and include a cup holder generally indicated by the numeral 31 and made of a rigid plastic material, a flexible boot 32 made of a rubber-like material, a cup gripping assembly generally indicated by the numeral 33, and a gripping actuator assembly generally indicated by the numeral 34 and shown to be in two pieces. As will hereinafter be described in 35

more detail, cup holder assembly also includes a plurality of springs 35 and its components are held together by a bolt 36 which receives a nut 37.

The construction of cup holder 31 is probably best shown in Figs. 4 and 5 and includes a generally cylindrical sidewall 40 being open at its top, where a flange 41 is formed, and open at its bottom 42. A shelf 43 is formed near the open bottom 42 and includes a central aperture 44 and opposed sockets 45 radially spaced from central aperture 44. Four slots 46 are formed at the periphery of shelf 43 and are spaced ninety degrees of each other. Slots 46 also extend slightly up sidewall 40. A boss 47 is formed under central aperture 44 of shelf 43, and bosses 48 are also formed under sockets 45. In addition, socket bosses 49 are formed on the bottom of shelf 43 and are positioned radially outward of bosses 48.

As best seen in Fig. 6, cup gripping assembly 33 includes a central hub 50 having an aperture 51 therethrough. A base 52 extends outwardly from hub 50 and carries four arms, generally indicated by the numeral 53, which extend upwardly from base 52 evenly spaced at ninety degrees around hub 50. A living hinge 54 is formed at the junction of each arm 53 and base 52 so that arms 53 are pivotable relative to base 52. Each arm 53 includes an outer conical surface 55 which, as will be hereinafter described, is engaged by actuator assembly 34 to pivot arms 53 inwardly. A finger 56 having an inwardly directed lock tab 57 is formed at the top end of each arm 53.

Actuator assembly 34 is shown as being formed from two identical halves, for ease of molding the plastic materials, but could be formed as one piece. When formed from two halves, a pin 60 and socket 61 formed in each half assure proper alignment of the halves which can then be attached to each other by screws (not shown) received through apertures 62. When so assembled, actuator assembly 34 includes a generally circular base 63 having an abbreviated sidewall 64 extending upwardly therefrom. Circumferentially spaced actuator arms 65 extend upwardly from sidewall 64 and are spaced approximately ninety degrees of each other. Each arm 65 has an inwardly directed lip 66 formed near the top thereof, and each lip 66 has an inner actuating surface 67.

Cup gripping assembly 33 and actuator assembly 34 are assembled together and positioned in the bottom of cup holder 31 as now to be described. As shown in Fig. 8, gripping assembly 33 is positioned within actuator

assembly 34 with its arms 53 aligned with arms 65 of actuator assembly 34. For ease of such alignment, one or more of the arms 65 may be provided with tabs 68 extending inwardly from the edges of surface 67 such that an arm 53 of gripping assembly 33 will be received between tabs 68. When so positioned, actuating surfaces 67 are adjacent to and otherwise bear against conical surfaces 55 of gripping assembly 33.

5 Springs 35 are inserted into socket bosses 49 of cup holder 31, and the assembled gripping assembly 33 and actuator assembly 34 are inserted into the bottom of cup holder 31. As such, springs 35 bear against base 63 of actuator assembly 34. Also, at this time, the fingers 56 of the arms 53 of gripping assembly 33 are exposed through cup holder slots 46 thereby allowing fingers 56 to communicate with the inside of cup holder 31. Bolt 36 is inserted through central aperture 44 of cup holder 31 and through aperture 51 of gripping assembly 33, and thus gripping assembly 33 is attached to cup holder 10 31. However, actuator assembly 34 is free to float within cup holder 31. As shown in Figs. 12 and 13, bolt 36 is also utilized to connect cup holding 15 assembly 30 to travel plate 26.

20 In order to mix food, a cup C or other container is placed in cup holding assembly 30. While it may be placed directly into cup holder 31, preferably it is positioned into boot 32 which is, in turn, carried by cup holder 31. To that end, boot 32 is shaped like the inside of cup holder 31 and includes lugs 69 formed on the bottom thereof. Lugs 69 snap into sockets 45 of cup holder 31 to hold boot 32 in place. Also, boot 32 is provided with an upper peripheral lip 70 that engages the top flange 41 of cup holder 31, as best 25 seen in Figs. 10-13. Fingers 56, or more specifically lock tabs 57, bear against the boot 32 to engage the cup C within the boot. The presence of boot 32 protects the cup from any possible damage which could be caused by fingers 56, and the presence of flexible boot 32 also accommodates cups of slightly varying sizes.

30 When travel plate 26 is in the up position as shown in Fig. 1 and more particularly in Fig. 12, food is being mixed in cup C by agitator 25. At the same time, cup holding assembly 30 is being rotated on shaft 27. But cup C is prevented from rotating with the cup holding assembly because in this position the bias of springs 35 is maintaining arms 65, and in particular actuating 35 surfaces 67 thereof, down or conical surfaces 55 of gripping assembly 33

which, in turn, pushes arms 53 of gripping assembly 33 inwardly, pivoting them on hinges 54. This condition is shown in Fig. 12. However, when travel plate 26 moves downwardly to the Fig. 13 position, indicative of the mixing process being completed, the grip on cup C is released by a release initiating assembly 5 generally indicated by the numeral 80 and now to be described.

As best shown in Fig. 1, release initiating assembly 80 includes a bracket 81 which is attached to lower platform 22. Bracket 81 carries a plurality of upstanding posts 82 which are shown to be in the form of screws threaded onto the upper surface 83 of bracket 81. As travel plate 26 approaches the Fig. 13 position, posts 82 will contact the bottom of base 63 of actuator assembly 34. Such overcomes the bias of springs 35 and allows actuator assembly 34 to move relative to gripping assembly 33. As such, actuating surface 67 of actuator assembly 34 moves up conical surface 55 of gripping assembly 34 which allows arms 53 to pivot away from cup C and release the grip so that cup C can be removed from the cup holding assembly 30.

When the cup holding assembly 30 is moving upwardly and downwardly, it is passing through an opening 90 (Figs. 12 and 13) formed in intermediate platform 23 or an equivalent area of housing 21. Opening 90 thus provides access to the machine components that are located below it which is basically those components that may be on lower platform 22. Since food drippings could often accumulate on and otherwise run down the outside of cup holder 31 and potentially pass through opening 90, a seal assembly, generally indicated by the numeral 91 and best shown in Figs. 14-16, is provided.

Seal assembly 91 includes an elastomeric gasket 92 which is carried between an upper plastic plate generally indicated by the numeral 93, and a lower plastic plate generally indicated by the numeral 94. Upper plate 93 is shown as being in the form of a ring having three bosses 95 extending downwardly therefrom. The internal lower periphery 96 of the ring of plate 93 receives gasket 92 which may be press fit therein. The lower plate 94 is also ring shaped and is provided with three recesses 97 which receive bosses 95 therein. Fasteners 98 are provided to hold seal assembly together with the edges of platform 23 at aperture 90 sandwiched therebetween as shown in Fig. 16. As shown there, gasket 92 extends into the aperture 90 so that it

bears against cup holder 31 as it passes therethrough. The edges of the housing platform are held between the upper plate 93 and the lower plate 94 by virtue of the attachment by fasteners 98.

5 In light of the foregoing, it should thus be evident that a food mixing machine constructed as described herein substantially improves the art and otherwise accomplishes the objects of the present invention.

CLAIMS

What is claimed is:

1. 1. A food mixing machine having an agitator to mix food in a cup comprising a cup holder adapted to receive the cup therein, a gripping member positioned within said cup holder, and a gripping actuator, said actuator being moveable relative to said gripping member so that upon movement of said actuator, said gripping member selectively engages or releases the cup.
1. 2. The food mixing machine of claim 1 wherein said gripping member includes fingers adapted to engage the cup.
1. 3. The food mixing machine of claim 2 further comprising means to bias said agitator so that said fingers engage the cup.
1. 4. The food mixing machine of claim 3 further comprising a release assembly to overcome the bias of said means to bias and release said fingers from the cup.
1. 5. The food mixing machine of claim 4 wherein said release assembly includes posts to engage said actuator.
1. 6. The food mixing machine of claim 2 wherein said cup holder includes slots, said slots receiving said fingers.
1. 7. The food mixing machine of claim 2 wherein said cup holder includes sockets, and further comprising springs received in said sockets, said springs bearing against said agitator to maintain said fingers engaging the cup.
1. 8. The food mixing machine of claim 1 further comprising an opening in the machine, said opening being defined by edges, said cup holder moving

3 through said opening, and a seal assembly positioned in said opening
4 and engaging said cup holder.

1 9. The food mixing machine of claim 7 wherein said seal assembly includes
2 a first plate, a second plate and a gasket positioned between said plates,
3 said gasket engaging said cup holder, and said gasket and said plates
4 being connected in such a way so as to engage said edges at said
5 opening.

1 10. The food mixing machine of claim 2 further comprising a flexible boot
2 positioned inside of said cup holder and receiving the cup, said fingers
3 engaging the cup through said flexible boot.

1 11. The food mixing machine of claim 10 wherein said cup holder includes an
2 internal shelf having sockets therein, said boot having lugs received in
3 said sockets to attach said boot to said cup holder.

1 12. The food mixing machine of claim 2 wherein said gripping member
2 includes arms carrying said fingers, said arms having a conical surface
3 engaged by said actuator.

1 13. The food mixing machine of claim 12 wherein said actuator includes arms
2 having an actuator surface, said actuator surface engaging said conical
3 surface to move said fingers.

1 14. The food mixing machine of claim 13 wherein said arms of said gripping
2 member pivot when said actuator surface is moving on said conical
3 surface.


1 15. A food mixing machine comprising a housing, an opening in said housing,
2 a cup holder adapted to be moved through said opening, and a seal
3 assembly carried by said housing around said opening, said seal
4 assembly including a seal to engage said cup holder as said cup holder
5 moves through said opening.

- 1 16. The food mixing machine of claim 15 wherein edges define said opening,
2 said seal assembly engaging said edges.
- 1 17. The food mixing machine of claim 16 wherein said seal is a gasket and
2 said seal assembly includes a first plate carrying said gasket, a second
3 plate, and means to attach said first plate to said second plate with said
4 gasket and said edges between said first and second plates.
- 1 18. The food mixing machine of claim 15 further comprising a gripping
2 member positioned with said cup holder, and an actuator moveable
3 relative to said gripping member so that said gripping member can
4 selectively engage a cup positioned in said cup holder.
- 1 19. A food mixing machine having an agitator to mix food in a cup comprising
2 a housing, an opening in said housing, a cup holder adapted to receive
3 the cup and to move through said opening, a seal assembly carried by
4 said housing, said seal assembly including a seal to engage said cup
5 holder as said cup holder moves through said opening, a gripping
6 actuator and a gripping member positioned within said cup holder, said
7 actuator being moveable relative to said gripping member so that upon
8 movement of said actuator, said gripping member selectively engages or
9 releases the cup.
- 1 20. A method of mixing food in a cup with an agitator comprising the steps of
2 placing the cup in a cup holder, moving the cup toward the agitator while
3 at the same time gripping the cup in the cup holder, using the agitator to
4 mix the food, moving the cup holder away from the agitator, and releasing
5 the cup from the cup holder.
- 1 21. The method of claim 20 further comprising the step of placing a flexible
2 boot in the cup holder whereby the step of placing the cup in the cup
3 holder includes the placement of the cup in the boot.
- 1 22. The method of claim 20 wherein during the moving steps the cup holder is
2 moving through an opening in a food mixing machine and further

3 comprising the step of providing a flexible seal between the opening and
4 the cup holder.

1 23. The method of claim 20 wherein the step of gripping the cup includes the
2 step of biasing an actuator against a gripping member to move fingers of
3 the gripping member to engage the cup.

1 24. The method of claim 23 wherein the step of releasing includes the step of
2 overcoming the biasing of the actuator to release the fingers from the cup.



2/13





FIG-2

3/13



4/13




FIG-4






FIG-5



6/13




FIG-8

7/13




FIG-9

8/13




FIG-11




FIG-10

9/13




FIG-12

10/13




FIG-13

11/13




FIG-14

12/13




FIG-15

13/13




FIG-16