




US 20210338968A1

(19) **United States**(12) **Patent Application Publication**
KILGARD et al.(10) **Pub. No.: US 2021/0338968 A1**(43) **Pub. Date: Nov. 4, 2021**(54) **SYSTEMS, METHODS AND DEVICES FOR
PAIRED PLASTICITY***G09B 23/28* (2006.01)*A61M 21/02* (2006.01)*H04R 25/00* (2006.01)*A61F 11/00* (2006.01)(71) Applicant: **THE BOARD OF REGENTS, THE
UNIVERSITY OF TEXAS SYSTEM,**
Austin, TX (US)(52) **U.S. Cl.**CPC *A61M 21/00* (2013.01); *A61M 2021/0027*
(2013.01); *G09B 19/003* (2013.01); *A61N*
1/361 (2013.01); *A61N 1/36103* (2013.01);
G09B 23/28 (2013.01); *A61N 5/0622*
(2013.01); *G09B 19/00* (2013.01); *A61N*
1/36034 (2017.08); *A61N 1/36053* (2013.01);
A61N 1/36092 (2013.01); *A61M 21/02*
(2013.01); *H04R 25/75* (2013.01); *A61F 11/00*
(2013.01); *A61N 1/36067* (2013.01); *A61N*
1/36139 (2013.01); *A61N 1/36167* (2013.01);
A61N 1/36082 (2013.01); *A61M 2021/0016*
(2013.01); *A61M 2021/0022* (2013.01); *A61M*
2021/0044 (2013.01); *A61M 2021/0072*
(2013.01); *A61M 2021/0077* (2013.01); *A61M*
2205/3515 (2013.01); *A61M 2230/06*
(2013.01); *A61M 2230/08* (2013.01); *A61M*
2230/10 (2013.01); *A61M 2230/205* (2013.01);
A61M 2230/30 (2013.01); *A61M 2230/432*
(2013.01); *A61M 2230/50* (2013.01); *A61M*
2230/60 (2013.01); *A61M 2230/65* (2013.01);
A61N 5/0618 (2013.01)(72) Inventors: **Michael P. KILGARD**, Richardson,
TX (US); **Larry CAULLER**, Plano,
TX (US); **Navzer ENGINEER**, Plano,
TX (US); **Christa McIntyre**
RODRIGUEZ, Richardson, TX (US);
Will ROSELLINI, Dallas, TX (US)(21) Appl. No.: **17/232,772**(22) Filed: **Apr. 16, 2021****Related U.S. Application Data**(63) Continuation of application No. 15/496,766, filed on
Apr. 25, 2017, now Pat. No. 11,116,933, which is a
continuation of application No. 14/809,781, filed on
Jul. 27, 2015, now abandoned, which is a continu-
ation of application No. 12/485,040, filed on Jun. 15,
2009, now Pat. No. 9,089,707.(60) Provisional application No. 61/077,648, filed on Jul.
2, 2008, provisional application No. 61/078,954, filed
on Jul. 8, 2008, provisional application No. 61/086,
116, filed on Aug. 4, 2008, provisional application
No. 61/149,387, filed on Feb. 3, 2009.**Publication Classification**(51) **Int. Cl.***A61M 21/00* (2006.01)*A61N 5/06* (2006.01)*G09B 19/00* (2006.01)*A61N 1/36* (2006.01)

(57)

ABSTRACT

Systems, methods and devices for paired training include timing controls so that training and neural stimulation can be provided simultaneously. Paired trainings may include therapies, rehabilitation and performance enhancement training. Stimulations of nerves such as the vagus nerve that affect subcortical regions such as the nucleus basalis, locus coeruleus or amygdala induce plasticity in the brain, enhancing the effects of a variety of therapies, such as those used to treat tinnitus, stroke, traumatic brain injury, post-traumatic stress disorder, speech deficit or language deficit.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15








FIG. 17

*FIG. 16**FIG. 18**FIG. 19**FIG. 20*




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27

SYSTEMS, METHODS AND DEVICES FOR PAIRED PLASTICITY

PRIORITY CLAIM

[0001] The present application is a Continuation of U.S. application Ser. No. 15/496,766, filed Apr. 25, 2017, which is a Continuation of U.S. application Ser. No. 14/809,781, filed Jul. 27, 2015, which is a Continuation of U.S. application Ser. No. 12/485,040, filed Jun. 15, 2009, which claims priority benefits under 35 U. S.C. § 119(e) from U.S. Provisional Application No. 61/077,648, filed on Jul. 2, 2008 and entitled “Treatment of Tinnitus with Vagus Nerve Stimulation”; U.S. Provisional Application No. 61/078,954, filed on Jul. 8, 2008 and entitled “Neuroplasticity Enhancement”; U.S. Provisional Application No. 61/086,116, filed on Aug. 4, 2008 and entitled “Tinnitus Treatment Methods and Apparatus”; and U.S. Provisional Application No. 61/149,387, filed on Feb. 3, 2009 and entitled “Healing the Human Brain: The Next Medical Revolution.” The present application incorporates the foregoing disclosures herein by reference.

BACKGROUND

[0002] The present disclosure relates generally to therapy, rehabilitation and training including induced plasticity. More particularly, the disclosure relates to methods and systems of enhancing therapy, rehabilitation and training using nerve stimulation paired with training experiences.

SUMMARY

[0003] For purposes of summarizing the invention, certain aspects, advantages, and novel features of the invention have been described herein. It is to be understood that not necessarily all such advantages may be achieved in accordance with any particular embodiment of the invention. Thus, the invention may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] The disclosed inventions will be described with reference to the accompanying drawings, which show important sample embodiments of the invention and which are incorporated in the specification hereof by reference, wherein:

[0005] FIG. 1 is a block diagram depicting a paired training system, in accordance with an embodiment;

[0006] FIG. 2 is a block diagram depicting a paired training system affecting a sub-cortical region, in accordance with an embodiment;

[0007] FIG. 3 is a block diagram depicting a paired training system affecting the nucleus basalis, in accordance with an embodiment;

[0008] FIG. 4 is a block diagram depicting a paired training system affecting the locus coeruleus, in accordance with an embodiment;

[0009] FIG. 5 is a block diagram depicting a paired training system affecting the amygdala, in accordance with an embodiment;

[0010] FIG. 6 is a block diagram depicting a paired training system affecting the nucleus of the solitary tract (NTS), in accordance with an embodiment;

[0011] FIG. 7 is a block diagram depicting a paired training system affecting the cholinergic system, in accordance with an embodiment;

[0012] FIG. 8 is a block diagram depicting a paired training system affecting the noradrenergic system, in accordance with an embodiment;

[0013] FIG. 9 is a simplified diagram depicting a stimulator, in accordance with an embodiment;

[0014] FIG. 10 is a simplified diagram depicting a wireless stimulator, in accordance with an embodiment;

[0015] FIG. 11 is a simplified diagram depicting a dual stimulator configuration, in accordance with an embodiment;

[0016] FIG. 12 is a simplified diagram depicting a multi-stimulator configuration, in accordance with an embodiment;

[0017] FIG. 13 is a graph depicting a constant current stimulation pulse, in accordance with an embodiment;

[0018] FIG. 14 is a graph depicting an exponential stimulation pulse, in accordance with an embodiment;

[0019] FIG. 15 is a graph depicting a train of constant current stimulation pulses, in accordance with an embodiment;

[0020] FIG. 16 is a block diagram depicting a synchronizing control system, in accordance with an embodiment;

[0021] FIG. 17 is a graph depicting synchronized pairing, in accordance with an embodiment;

[0022] FIG. 18 is a block diagram depicting a response control system, in accordance with an embodiment;

[0023] FIG. 19 is a graph depicting response pairing, in accordance with an embodiment;

[0024] FIG. 20 is a block diagram depicting a manual control system, in accordance with an embodiment;

[0025] FIG. 21 is a graph depicting manual pairing, in accordance with an embodiment;

[0026] FIG. 22 is a block diagram depicting a closed loop control system, in accordance with an embodiment;

[0027] FIG. 23 is a graph depicting closed loop pairing, in accordance with an embodiment;

[0028] FIG. 24 is a block diagram depicting an initiated control system, in accordance with an embodiment;

[0029] FIG. 25 is a graph depicting initiated pairing, in accordance with an embodiment;

[0030] FIG. 26 is a block diagram depicting a delayed response timing control system, in accordance with an embodiment; and

[0031] FIG. 27 is a graph depicting delayed response pairing, in accordance with an embodiment.

DETAILED DESCRIPTION OF THE DRAWINGS

[0032] The numerous innovative teachings of the present application will be described with particular reference to presently preferred embodiments (by way of example, and not of limitation). The present application describes several inventions, and none of the statements below should be taken as limiting the claims generally. Where block diagrams have been used to illustrate the invention, it should be recognized that the physical location where described functions are performed are not necessarily represented by the blocks. Part of a function may be performed in one location while another part of the same function is performed at a distinct location. Multiple functions may be performed at the same location.

[0033] With reference to FIG. 1, a paired training system is shown. A timing control system 106 is communicably connected to a neural stimulator system 108 and a training system 110. Receiving timing instruction from the timing control system 106, the neural stimulator system 108 provides stimulation to a nerve 104. Similarly receiving timing instruction from the timing control system 106, or providing timing instruction to the timing control system, the training system 110 generates desired mental images, ideas, formations or states in the brain 102. The stimulation of the nerve 104 affects the brain 102 by inducing plasticity. The temporally paired combination of training and stimulation generates manifestations of plasticity in the brain 102 that may be measured by a plasticity measure system 112.

[0034] The timing controls system 106 generally provides the simultaneous nature of the pairing. The stimulation and the training are simultaneous in that they occur at the same time, that is, there is at least some overlap in the timing. In some embodiments, the stimulation may lead the start of the training while in other embodiments, the stimulation may follow the start of the training. In many cases, the stimulation is shorter in duration than the training, such that the stimulation occurs near the beginning of the training. Plasticity resulting from stimulation has been shown to last minutes or hours, so a single stimulation pulse may suffice for the whole duration of extended training.

[0035] In the treatment of tinnitus, for example, the training may consist of brief audible sounds including selected therapeutic frequencies, paired with stimulations. Because the duration of the sounds may be short, the timing may be controlled very precisely so that the sound coincides temporally with the stimulation. This kind of precision may typically require some form of computer control. In other forms of rehabilitation or education, the timing of the training and/or the stimulation may be controlled manually. Further therapies and training may include training triggered timing or physical condition feedback to provide a closed-loop system.

[0036] The neural stimulation system 108 may provide stimulation of the nerve 104 using electrical stimulation, chemical stimulation, magnetic stimulation, optical stimulation, mechanical stimulation or any other form of suitable nerve stimulation. In accordance with an embodiment, an electrical stimulation is provided to the left vagus nerve. In an electrical stimulation system, suitable stimulation pulses may include a variety of waveforms, including constant current pulses, constant voltage pulses, exponential pulses or any other appropriate waveform. An electrical stimulation system may use a single stimulation pulse or a train of stimulation pulses to stimulate the nerve 104. Stimulation parameters are selected to affect the brain 102 appropriately, with reference to the affected brain regions or systems, plasticity measures, desynchronization or any other appropriate stimulation parameter measure. A half second train of biphasic stimulation pulses, with a pulse width of 100 microseconds, at 0.8 milliamps and at 30 Hz has been used effectively in the treatment of tinnitus.

[0037] Paired stimulation could be accomplished using deep brain stimulation, cortical stimulation, transcranial magnetic stimulation and any other suitable neural stimulation.

[0038] One indication of appropriate stimulation may be desynchronization of the cortical EEG. A 0.8 milliamp pulse has been shown to cause cortical desynchronization at

frequencies between 30 and 150 Hz. 0.4 milliamp pulses desynchronize the cortex at higher frequencies of 100 to 150 Hz. Desynchronization has been shown to last for at least four seconds in response to stimulation of the vagus nerve.

[0039] The simultaneous training system 110 generates the sensory input, motor sequences, cognitive input, mental images, ideas, formations or states that are to be retained by the brain 102. A training system 110 may provide sensory information, such as visual, auditory, olfactory, tactile or any other suitable sensory information. Training system 110 may include physical therapies, cognitive therapies, emotional therapies, chemical therapies, or any other suitable therapies. Training system 110 may present educational information. Training system 110 may include the subject, physically, mentally, emotionally or in any other suitable fashion. Training system 110 may include teachers, doctors, therapists, counselors, instructors, coaches or any other suitable training provider. Training system 110 may evoke specific patterns of neural activity by direct brain stimulation, for example by electrical, magnetic, optical, or any other suitable pattern evocation systems. Training system 110 may inactivate specific brain regions via chemical agents, cooling, magnetic stimulation, or other suitable methods.

[0040] The paired training system of FIG. 1 affects the brain 102 to generate plasticity that can be measured by a plasticity measure system 112. In the treatment of tinnitus, a cortical map may be used to measure the map distortion and correction that accompanies the successful treatment of tinnitus. Less invasively, the plasticity can be measured by behaviorally reactions to stimuli, such as a startle test for tinnitus. Further, plasticity can be measured by inquiring about the subjective experience of a subject. If a tinnitus patient no longer experiences a persistent noise, plasticity has been measured.

[0041] With reference to FIG. 2, a paired training system affecting a subcortical region 114 of the brain 102, in accordance with an embodiment is shown. The stimulation of nerve 104 affects a subcortical region 114. The subcortical region 114, in turn, affects the brain to induce plasticity. Stimulation of nerves 104 such as the trigeminal nerve and other cranial nerves are known to affect the subcortical region 114.

[0042] With reference to FIG. 3, a paired training system affecting the nucleus basalis 116, in accordance with an embodiment, is shown. The stimulation of nerve 104 affects the nucleus basalis 116. The nucleus basalis, in turn, affects the brain 102 to induce plasticity.

[0043] With reference to FIG. 4, a paired training system affecting the locus coeruleus 118, in accordance with an embodiment, is shown. The stimulation of nerve 104 affects the locus coeruleus 118. The locus coeruleus 118, in turn, affects the brain 102 to induce plasticity.

[0044] With reference to FIG. 5, a paired training system affecting the amygdala 120, in accordance with an embodiment, is shown. The stimulation of nerve 104 affects the amygdala 120. The amygdala 120, in turn, affects the brain 102 to induce plasticity.

[0045] With reference to FIG. 6, a paired training system affecting the NTS 122, in accordance with an embodiment, is shown. The stimulation of nerve 104 affects the NTS 122. The NTS 122, in turn, affects the brain 102 to induce plasticity.

[0046] With reference to FIG. 7, a paired training system affecting the cholinergic system 124, in accordance with an

embodiment, is shown. The stimulation of nerve **104** affects the cholinergic system **124**. The cholinergic system **124** releases acetylcholine (ACh) into the brain **102** inducing plasticity.

[0047] With reference to FIG. **8**, a paired training system affecting the noradrenergic system **126**, in accordance with an embodiment, is shown. The stimulation of nerve **104** affects the noradrenergic system **126**. The noradrenergic system **126** releases noradrenaline (NE) into the brain **102** inducing plasticity.

[0048] With reference to FIG. **9**, a neural stimulator system, in accordance with an embodiment, is shown. A neural stimulator control **109** is communicably connected to a neurostimulator **128**. Neurostimulator **128** provides a stimulation pulse to a nerve **104** via a pair of electrodes **130a** and **130b**. Electrodes **130a** and **130b** could be cuff electrodes, conductive plates or any other suitable neural stimulation electrode. The neurostimulator may be powered by a piezo-electric powering system as well as near field inductive power transfer, far-field inductive power transfer, battery, rechargeable battery or any other suitable neurostimulator power system. When neural stimulator control **109** receives timing instructions from a timing control system (not shown), the neural stimulator control **109** initiates a stimulation pulse from the neurostimulator **128** via electrodes **130a** and **130b**.

[0049] With reference to FIG. **10**, a wireless neural stimulator system, in accordance with an embodiment is shown. Neurostimulator **128** communicates with the neural stimulation system **109** using an inductive transponder coil **132**. The neural stimulator system **109** includes an external coil **134**. Information may be communicated between the neural stimulator system **109** and the neurostimulator **128**. Power may be transferred to the neurostimulator **128** by the neural stimulator system.

[0050] With reference to FIG. **11**, a dual neurostimulator system, in accordance with an embodiment, is shown. Two neurostimulators **128** may stimulate neural **104**. The neurostimulators may be controlled to reinforce each other, as redundancy, or to prevent efferent signals from projecting away from the brain.

[0051] With reference to FIG. **12**, a multi-neurostimulator system, in accordance with an embodiment, is shown. A plurality of neurostimulators **128** may stimulate nerve **104**. The neurostimulators may be controlled to reinforce each other, as redundancy, or to prevent efferent signals from projecting away from the brain.

[0052] With reference to FIG. **13**, a graph shows a constant current stimulation pulse, in accordance with an embodiment.

[0053] With reference to FIG. **14**, a graph shows an exponential stimulation pulse, in accordance with an embodiment.

[0054] With reference to FIG. **15**, a graph shows a train of constant current stimulation pulses, in accordance with an embodiment.

[0055] With reference to FIG. **16**, a synchronized timing control system, in accordance with an embodiment, is shown. The synchronized timing control system includes a synchronizing timing control **186**. The synchronizing timing control **186** is communicably connected to the neural stimulation system **108** and the training system **110**. The synchronizing timing control **136** provides timing instructions to the neural stimulation system **108** and the training system **110** so

that the stimulation and training occur simultaneously. In the treatment of tinnitus, the stimulation of the nerve may slightly precedes each training sound, to give the stimulation time to affect the brain when the training sound is presented. Further embodiments may include other suitable timing variations.

[0056] With reference to FIG. **17**, a graph shows a possible timing relationship between event and stimulation for a synchronized timing control system.

[0057] With reference to FIG. **18**, a response timing control system, in accordance with an embodiment, is shown. The response timing control system includes a response timing control **138**. The response timing control **138** is communicably connected to the neural stimulation system **108** and a simultaneous event monitor **140**. The response timing control **138** receives timing instructions from the event monitor **140** and provides timing instructions to the neural stimulation system **108**, so that the stimulation and training occur simultaneously. Because the stimulation is generated in response to an event, the stimulation will generally lag the event by some finite time delta t . In cases where there is an event precursor that can be monitored, the timing can be made more exact.

[0058] With reference to FIG. **19**, a graph shows a possible timing relationship between a monitored event and a nerve stimulation.

[0059] With reference to FIG. **20**, a manual timing control system, in accordance with an embodiment, is shown. The manual timing control system includes a response timing control **138**. The response timing control **138** is communicably connected to the neural stimulation system **108** and a manual input **142**. The response timing control **138** receives timing instructions from the manual input **142** and provides timing instructions to the neural stimulation system **108**, so that the stimulation and training occur simultaneously.

[0060] With reference to FIG. **21**, a graph shows a possible timing relationship between an event, a manual input and a neural stimulation.

[0061] With reference to FIG. **22**, a closed loop timing control system, in accordance with an embodiment, is shown. The closed loop timing control system includes a closed loop timing control **144**. The closed loop timing control **138** is communicably connected to the neural stimulation system **108** and a sensor **146**. The closed loop timing control **144** receives timing instructions from the sensor **146** and provides timing instructions to the neural stimulation system **108**, so that the stimulation and training occur simultaneously.

[0062] With reference to FIG. **23**, a graph shows a possible timing relationship between a sensed training event and a neural stimulation is shown.

[0063] Sensor **146** may monitor external or internal events, including heart-rate, blood pressure, temperature, chemical levels or any other parameter that may indicate a training event.

[0064] With reference to FIG. **24**, an initiated timing control system, in accordance with an embodiment, is shown. The initiated timing control system includes an initiated timing control **148**. The initiated timing control **148** is communicably connected to a neural stimulation system **106** and an event generator **150**. The initiated timing control **148** receives timing information from the neural stimulation system **106**, indicating that a nerve has been stimulated. The initiated timing control **148** provides timing instructions to

the event generator **150**, such as a therapeutic sound generator connected by Bluetooth, such that the event generator **150** generates an event during the stimulation pulse.

[0065] With reference to FIG. **25**, a graph shows a possible timing relationship between a neural stimulation and an event generation.

[0066] With reference to FIG. **26**, a delayed response timing control system, in accordance with an embodiment, is shown. The delayed response timing control system includes a delayed response timing control **152**. The delayed response timing control **152** is communicably connected to a neural stimulation system **106** and a preliminary event sensor **154**. The preliminary event sensor **154** detects a preliminary event that anticipates a pairing event. The delayed response timing control **148** receives timing information from the preliminary event sensor **154**, indicating that a preliminary event has been detected. The delay response timing control **148** provides timing instructions to the neural stimulation system **106** to initiate nerve stimulation. In the depicted embodiment, the timing control **152** initiates the stimulation before the beginning of the pairing event, giving a negative delta t. A delay response timing system may initiate stimulation at the same time as the beginning of the pairing event, or after the beginning of the pairing event.

[0067] With reference to FIG. **27**, a graph shows a possible timing relationship between a neural stimulation, a preliminary event and a pairing event.

[0068] The plasticity induced by neural stimulation can be paired with a variety of therapies, rehabilitation, training and other forms of personal improvement. Each therapy acts as a training source. The specific timing requirements associated with each therapy are derived from the specifics of the therapy, such that the stimulation occurs during the training, and most effectively near the beginning of the training. Some possible therapies may include behavioral therapies such as sensory discrimination for sensory deficits, motor training for motor deficits, with or without robotic assistance and cognitive training/rehabilitation for cognitive deficits. Exercise and motor therapy could be paired to treat motor deficits arising from traumatic brain injury, stroke or Alzheimer's disease and movement disorders. Constraint induced therapy could be paired to help prevent the use of alternative strategies in order to force use of impaired methods. Speech therapy could be paired for speech and language deficits. Cognitive therapies could be paired for cognitive problems.

[0069] Sensory therapies, such as tones, could be paired to treat sensory ailments such as tinnitus. In treating tinnitus, the paired tones may be at frequencies distinct from the frequencies perceived by the tinnitus patient.

[0070] Exposure or extinction therapy could be paired to treat phobias or post-traumatic stress disorder.

[0071] Computer-based therapies such as FastForward for dyslexia, Brain Fitness Program Classic or Insight, could be paired to enhance their effects. Psychotherapy could be paired, as well as other therapeutic activities in the treatment of obsessive-compulsive disorder, depression or addiction.

[0072] Biofeedback therapy could be paired. For example, temperature readings or galvanic skin responses could be paired to treat anxiety or diabetes. An electromyograph could be paired to improve motor control after brain spinal or nerve damage. A pneumograph could be paired to improve breathing control in a paralyzed patient. A real-time

fMRI could be paired to improve pain control or treat OCD. An electrodermograph, EEG, EMG or electrocardiograph could be paired to treat disorders such as anxiety. An electroencephalograph could be paired to treat epilepsy. An hemoencephalography could be paired to treat migraines. A photoplethysmograph could be paired to treat anxiety. A capnometer could be paired to treat anxiety. Virtual reality therapy could be paired to treat disorders such as addiction, depression, anxiety or posttraumatic stress disorder. Virtual reality therapy could also be paired to enhance cognitive rehabilitation or performance. Drug therapies could be paired to treat a variety of conditions. Amphetamine-like compounds could be paired to enhance neuromodulators and plasticity. SSRI's could be paired to enhance neuromodulators and plasticity. MOA inhibitors could be paired to enhance neuromodulators and plasticity. Anti-coagulants could be paired to act as clot busters during acute stroke. Various drugs could be paired to stop spasm after nerve or brain damage such as Botulinum toxin, Lidocaine, etc. Small doses of drugs of abuse could be paired to extinguish cravings in addicts.

[0073] Hormone therapy could be paired. For example, progesterone, estrogen, stress, growth, or thyroid hormone, etc. could be paired to treat traumatic brain injury or Alzheimer's disease. Glucose therapy could be paired to treat anxiety. Electrical or magnetic stimulation of the central or peripheral nervous system could be paired. For example, transcranial magnetic stimulation could be used to enhance or reduce activity in a specific brain area and thereby focus the directed cortical plasticity. Transcutaneous electrical nerve stimulation could be paired to treat chronic pain, tinnitus and other disorders. Subcutaneous electrical nerve stimulation could be paired to treat chronic pain. Stem cell therapy could be paired to treat disorders such as Parkinson's disease. Gene therapy could be paired to treat conditions such as Down's syndrome, Huntington's disease or fragile X syndrome. Hyperbaric oxygen therapy could be paired to treat carbon monoxide poisoning.

[0074] Multiple therapies could be paired simultaneously or sequentially.

[0075] None of the description in the present application should be read as implying that any particular element, step, or function is an essential element which must be included in the claim scope: THE SCOPE OF PATENTED SUBJECT MATTER IS DEFINED ONLY BY THE ALLOWED CLAIMS. Moreover, none of these claims are intended to invoke paragraph six of 35 USC section 112 unless the exact words "means for" are followed by a participle.

[0076] The claims as filed are intended to be as comprehensive as possible, and NO subject matter is intentionally relinquished, dedicated, or abandoned.

What is claimed is:

1. A method of treating a speech deficit in a patient, the method comprising:

providing a neurostimulator to the patient to stimulate a vagus nerve of the patient electrically;

initiating stimulation of the patient's vagus nerve with the neurostimulator before a beginning of speech therapy; and

controlling the stimulation so that the stimulation overlaps an initial interval in a duration of a performance of the speech therapy thereby reducing the speech deficit.

2. The method of claim 1, wherein:
the neurostimulator provides a series of electrical pulse trains.
3. The method of claim 1, wherein:
the neurostimulator provides a programmed sequence of electrical pulse trains.
4. The method of claim 1, wherein:
the neurostimulator provides an electrical pulse train in response to a received signal.
5. The method of claim 1, wherein:
the patient's vagus nerve is also stimulated after the performance of the speech therapy.
6. A method of treating a speech deficit in a patient, the method comprising:
instructing the patient to perform speech therapy; and
at least one of electrically, chemically, magnetically, optically or mechanically stimulating a vagus nerve of the patient in a coordinated manner so that stimulation of the vagus nerve overlaps an initial interval in a duration of a performance of the speech therapy by the patient thereby reducing the speech deficit.
7. The method of claim 6, wherein:
the patient's vagus nerve is stimulated by a series of electrical pulse trains.
8. The method of claim 6, wherein:
the patient's vagus nerve is stimulated by a programmed sequence of electrical pulse trains.
9. The method of claim 6, wherein:
the patient's vagus nerve is stimulated by an electrical pulse train in response to a received signal.
10. The method of claim 6, wherein the coordinated manner includes:
initiating stimulation of the patient's vagus nerve before a beginning of a performance of the speech therapy by the patient; and
continuing the stimulation of the vagus nerve through and after the beginning of the performance of the speech therapy so that the stimulation overlaps the initial interval in a duration of the speech therapy.
11. The method of claim 6, wherein:
the patient's vagus nerve is also stimulated after the performance of the speech therapy.
12. A method of treating a speech deficit in a patient, the method comprising:
providing speech therapy to the patient which includes a pairing event;
applying at least one of electrical, chemical, magnetic, optical or mechanical vagus nerve stimulation in temporal proximity before a beginning of the pairing event; and
applying the vagus nerve stimulation so that the vagus nerve stimulation not only precedes but overlaps an initial interval of in a duration of the pairing event thereby reducing the speech deficit.
13. The method of claim 12, wherein:
the vagus nerve stimulation is a series of electrical pulse trains.
14. The method of claim 12, wherein:
the vagus nerve stimulation is a programmed sequence of electrical pulse trains.
15. The method of claim 12, wherein:
the vagus nerve stimulation is an electrical pulse train in response to a received signal.
16. The method of claim 12, wherein:
the vagus nerve stimulation begins after a performance of the speech therapy by the patient.
17. A method of treating a speech deficit in a patient, the method comprising:
indirectly inducing release of neuromodulators in nucleus basalis or locus coeruleus of the patient by initiating at least one of electrical, chemical, magnetic, optical or mechanical stimulation of a vagus nerve of the patient before performance of speech therapy by the patient begins; and
continuing the stimulation of the vagus nerve after the performance of speech therapy by the patient begins so that the stimulation of the vagus nerve overlaps an initial interval in a duration of a performance of the speech therapy thereby reducing the speech deficit.
18. The method of claim 17, wherein:
the patient's vagus nerve is stimulated by an electrical pulse train.
19. The method of claim 17, wherein:
the patient's vagus nerve is stimulated after the performance of the speech therapy.
20. A method of treating a speech deficit in a patient comprising:
instructing the patient to perform speech therapy which includes a pairing event; and
indirectly inducing release of neuromodulators in nucleus basalis or locus coeruleus of the patient by at least one of electrically, chemically, magnetically, optically or mechanically stimulating a vagus nerve of the patient in a coordinated manner so that stimulation of the vagus nerve overlaps an initial interval in a duration of the pairing event thereby reducing the patient's speech deficit.
21. The method of claim 20, wherein:
the patient's vagus nerve is stimulated by a series of electrical pulse trains.
22. The method of claim 20, wherein the coordinated manner includes:
initiating stimulation of the patient's vagus nerve before a beginning of a performance of the pairing event by the patient; and
continuing the stimulation of the vagus nerve through and after the beginning of the stimulation so that the stimulation overlaps the initial interval in a duration of the pairing event.
23. The method of claim 20, wherein:
the patient's vagus nerve is stimulated after performance of the speech therapy by the patient.
24. A method of treating a patient afflicted with at least one of a speech deficit or a language deficit, the method comprising:
instructing the patient to engage in speech therapy during a training period of training performed by the patient;
stimulating a vagus nerve (VNS) of the patient during a stimulation period; and
controlling the stimulation period to elapse during the training period resulting in synergism of the VNS and the training performed by the patient which reduces the speech deficit.
25. The method of claim 24, wherein the VNS includes:
electrically stimulating the vagus nerve.
26. The method of claim 24, wherein the VNS includes:
optically stimulating the vagus nerve.

27. The method of claim **24**, wherein:
the VNS induces plasticity in a motor cortex of the
patient, which improves a speaking ability of the
patient.

* * * * *