



US 20030141844A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2003/0141844 A1**

Fiebig et al. (43) **Pub. Date: Jul. 31, 2003**

(54) **EQUIPMENT SYSTEM COMPRISING A BATTERY-OPERATED ELECTRICAL DEVICE, A RECHARGEABLE BATTERY UNIT, AND A BATTERY CHARGER**

(30) **Foreign Application Priority Data**

Jan. 30, 2002 (DE)..... 102 03 512.1

Publication Classification

(76) Inventors: **Arnim Fiebig**, Leinfelden-Echterdingen (DE); **Hans-Joachim Baur**, Leinfelden-Echterdingen (DE); **Guenther Lohr**, Leinfelden-Echterdingen (DE); **Stefan Roepke**, Leinfelden (DE); **Rainer Glauning**, Aichtal-Groetzingen (DE); **Volker Bosch**, Stuttgart (DE)

(51) **Int. Cl.⁷** **H02J 7/00**

(52) **U.S. Cl.** **320/128**

(57) **ABSTRACT**

An equipment system includes a battery unit (10) having a monitoring circuit (14), which detects at least one operating parameter of the battery unit (10) and furnishes a control signal, dependent on the operating parameter, for switching means (25, 31). The switching means control the charging and discharging process of the battery unit (10) and are located in the electrical device (20) and in the charger (30), respectively. From the battery unit (10), the control signal is transmitted to the switching means (25, 31) in the electrical device (20) and in the charger (30), respectively. By this provision of shifting the switching means (25, 31) out of the battery unit (10) into the electrical device (20) and into the charger (30), respectively, the heat development in the battery unit (10) and also its structure size are reduced.

Correspondence Address:

STRICKER, STRICKER & STENBY
103 East Neck Road
Huntington, NY 11743 (US)

(21) Appl. No.: **10/335,842**

(22) Filed: **Jan. 2, 2003**

Fig. 1




Fig. 2





Fig. 3



**EQUIPMENT SYSTEM COMPRISING A
BATTERY-OPERATED ELECTRICAL DEVICE, A
RECHARGEABLE BATTERY UNIT, AND A
BATTERY CHARGER**

BACKGROUND OF THE INVENTION

[0001] The present invention relates to an equipment system, comprising at least one battery-operated electrical device, a rechargeable battery unit, and a battery charger, in which the battery unit has a monitoring circuit, which includes at least one operating parameter of the battery unit and furnishes a control signal, dependent on the operating parameter, for switching means that control the charging and discharging process of the battery unit.

[0002] In EP 665 628 A2, a recharge battery unit is described, which, on one hand, can be connected to a battery-operated electrical device in order to provide electrical energy to this device, and on the other hand, is useable in a charger device, in order to receive energy from it to its recharger. In the battery unit, a monitoring device is located, which includes at least one operating parameter, for example, the charging or discharge current or the terminal voltage of the battery unit and which furnishes a control signal, dependent on the operating parameter(s), for the switching means furnished in the battery unit, which controls the charging or discharging process of the battery unit. This means, for example, that this switching means interrupts the current flux from the battery unit to a connected electrical device, when the monitoring circuit registers a falling-short of a given discharge increase. Likewise, the control means interrupts the current flux from a charging device in the battery unit, when the control means is initiated by means of the control signal of the monitoring circuit.

[0003] In the rechargeable battery unit of EP 665 628 A2, then switching means for controlling the monitoring circuit as well as the charging or discharging process of the battery unit are found. In particular, with battery units, in which very high charging or discharge currents flow, such as, for example, with the use of electrical tool apparatus that are operated with relatively high capacity, the switching means must switch very high capacities, which leads to a correspondingly high heat formation in the battery unit. In addition, the structural size of a battery unit increases when a monitoring circuit as well as the switching means for controlling the charging and discharging process are integrated.

[0004] Likewise, such a battery unit, which includes the monitoring circuit and the switching means for controlling the charging and discharging process, is expensive. In an equipment system, comprising at least one battery-operated electrical device, a rechargeable battery unit, and a battery charger, the battery unit is subject to the greatest wear. Thus, it is particularly undesirable to raise the price of the battery unit by integration as many electronic switches as possible.

[0005] The present invention addresses the underlying problem of providing an equipment system, comprising at least one battery-operated electrical device, a rechargeable battery unit, and a battery recharge of the above-described type, in which the battery unit has the least possible expenditure on electronic switches, in order to avoid the development of heat in the battery unit and, in addition, to maintain the structural size of the battery unit to the smallest possible.

SUMMARY OF THE INVENTION

[0006] The above-described problem is resolved by the equipment system of the present invention having a battery unit, a battery charger, and a battery-operated electrical device, only the monitoring device is provided, which detects at least one operating parameter of the battery unit and furnishes a control signal dependent on the at least one operating parameter. The switching means, to which the control signal is supplied, for controlling the charging and discharging process of the battery unit, is located in the electrical device or charging device. Specifically, when the battery unit is connected to the electrical device, the switching means provided therein controls the capacity of the electrical device as a function of the control signal output from the battery unit. And when the battery unit is connected to the charging device, the switching means provided therein controls the transmitted charging current as a function of the control signals produced from the battery unit.

[0007] The switching means that control the charging and discharging process of the battery unit are located outside of the battery unit in the device connected to the battery unit. In this manner, the unit that is subject to the greatest wear and that is most frequently changed is disposed within the equipment system in a cost-effective manner.

[0008] The operating parameters detected by the monitoring circuit include the charging current flowing into the battery unit, and/or the terminal voltage of the battery unit, and/or the temperature of the battery unit, or a variable that is in relation to the temperature.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] **FIG. 1** shows a block diagram of a rechargeable battery unit;

[0010] **FIG. 2** shows a block diagram of an electrical device; and

[0011] **FIG. 3** shows a block diagram of a battery charger.

**DETAILED DESCRIPTION OF THE
PREFERRED EMBODIMENTS**

[0012] In **FIGS. 1 through 3**, the block diagrams of three units belonging to an equipment system are illustrated. **FIG. 1** shows a rechargeable battery unit, **FIG. 2** shows an electrical device **20**—preferably, a hand-held tool (for example, a drill, a hammer drill, a saw, a grinder, and the like), and **FIG. 3** shows a battery charger **30**. The battery unit illustrated in **FIG. 1** is connectable on the one hand to the energy supply on the electrical device **20** and on the other hand, to the recharger on the battery charger **30**. The connections or terminals **1, 2, 3** leading from the battery unit **10** have corresponding connections or terminals on the electrical device **20** and the battery charger **30**, which are designated with corresponding reference numerals **1, 2, 3**.

[0013] The battery unit **10** contains one or more rechargeable battery cells **11**, from whose plus and minus poles, supply lines **12, 13** lead to external supply connections **1, 2**. In the battery unit **10**, a monitoring circuit **14** is disposed. This monitoring circuit **14** detects one or more operating parameters of the battery unit, or more precisely, of the battery cells. These operating parameters include, for example, the discharge current—that is the current flowing

out of the battery unit upon connection of an electrical device **20**—or the charging current—that is, the current flowing into the battery unit upon connection to the charging device **30**—and/or the terminal voltage of the battery cell(s), and/or the temperature of the battery cell(s), or a variable that is in relation to the temperature. For detection of the temperature of the battery cell(s), a temperature sensor **16** is disposed in the vicinity of the battery cell(s).

[0014] The monitoring circuit **14** conducts a control signal for the charging or discharging process of the battery unit from the respective operating parameter. As already known from the state of the art, for example, EP 665 628 A2 or DE 41 06 725 A1, such a control signal that is dependent on one or more operating parameters of the battery unit, serve to interrupt or reduce the current flow from the battery unit to an electric device connected thereto when the battery unit reaches a given minimum charge threshold. Or the control signal serves to interrupt or reduced the charging process upon reaching an upper charging threshold or upper temperature threshold when the battery unit **10** is connected to a charging device **30**, that is, the current flow between the charging device **30** and the battery unit **10** is interrupted or reduced. The monitoring circuit **14** distributes the control signal via a signal line **15**, which leads to an external signal line connection **3**.

[0015] In FIG. 2, an electrical device **20** that is connectable to the battery unit **2** is illustrated. In the electrical device **20**, an electrical drive **21** is located, which, as is common, is an electric motor. Supply lines **22** and **23**, which are contactable with the supply lines **12** and **13** of the battery unit **10**, lead to the electrical drive **21**. In one of the two supply lines **22**, **23**, an electrically controllable switch **24** is disposed. As the electrically controllable switch, common MOS-FETs are used. For controlling the switch **24**, switching means **25** in the electrical device **20** are provided. These switching means **25** receive the control signal from the battery unit **10** via a signal line **25** that is connected to the external signal line connection **3**.

[0016] In dependence on the information that the control signal is running from the battery unit **20** over the discharge state of the battery unit **20**, the switching means **25** controls the switch **24**. If, for example, a given minimum charging threshold is registered from the monitoring circuit **14** in the battery unit **10**, a corresponding control signal transmitted to the control means **25** enables an opening of the switch **24**, so that the electrical device **20** can received no further current from the battery unit **20**. Instead of abruptly switching off the power of the electrical device **20**, also, under certain conditions, a gradual downward switching of the power by means of the control means **25** in dependence on the control signal from the monitoring circuit **14** can be performed. Overall, the consumption of power through the electrical device **20** via the switching means **25** is controlled such that the maximum threshold value of the consumption of power is adapted constantly to the actual charging state of the battery unit **10**. In this manner, the battery unit **20** operates in view of the longest possible longevity.

[0017] In the battery charger **30** illustrated in FIG. 3, a controllable current or voltage source **31** is disposed. This controllable current or voltage source includes on one hand power supplies **4** and **5**, and on the other hand, guide supply lines **32** and **33** to the external supply line connections **1** and

2. Via a signal line **34**, which leads to the external signal line connection **3**, the controllable current or voltage source **31** receives the control signal generated from the monitoring circuit **14** in the battery unit **10**. Control means in the controllable current or voltage source **31** control the charging current flowing over the supply lines **32**, **33** to the battery unit **10** in dependence on the control signal formed in the battery unit **10** and transmitted to the battery charger **30**. In particular, the control signal signals the switching means in the controllable current and voltage source **31**, when the battery unit **10** has reach an upper charging threshold, as a result of which then the charging current is switched off or gradually driven downward from the controllable current or voltage source **31**.

[0018] As previously illustrated, an information exchange via the signal lines **15**, **26**, **34** between the battery unit **10**, the electrical device **20**, and the battery charger **30** is constant. This information exchange can not only lead unidirectionally from the battery unit **10** to the electrical device **20** or battery charger **30**, but also in the reverse direction. As a result of this reciprocal information exchange about the actual operating state of the respective devices **10**, **20**, **30**, an overloading and, correspondingly, a high wear of the devices is substantially reduced.

[0019] Advantageously, the signal lines **15**, **16**, **34** for the reciprocal information exchange are embodied as bus lines, over which control signal data as serial data currents can be transmitted unidirectionally or bidirectionally.

[0020] It will be understood that each of the elements described above, or two or more together, may also find a useful application in other types of constructions differing from the types described above.

[0021] While the invention has been illustrated and described herein as an equipment system comprising a battery-operated electrical device, a rechargeable battery unit, and a battery charger, it is not intended to be limited to the details shown, since various modifications and structural changes may be made without departing in any way from the spirit of the present invention.

[0022] Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this invention.

What is claimed as new and desired to be protected by Letters Patent is set forth in the appended claims:

1. An equipment system, comprising at least one battery-operated electrical device (**20**), a rechargeable battery unit (**10**), and a battery charger (**30**), in which the battery unit (**10**) has a monitoring circuit (**14**), which includes at least one operating parameter of the battery unit (**10**) and furnishes a control signal, dependent on the operating parameter, for switching means (**25**, **31**) that control a charging and discharging process of the battery unit (**10**), characterized in that

in the electrical device (**10**), switching means (**25**) are present for controlling capacity of the electrical device as a function of a control signal output by the monitoring circuit (**14**) of the battery unit (**10**); and

in the battery charger (30), switching means (31) are present for controlling a charging current transmitted from the battery charger (30) to the battery unit (10).

2. A battery unit, which can be connected electrically with an electrical device (20) to supply energy to the battery unit and with a charger (30) to recharge the battery unit (10), in which the battery unit (10) has a monitoring circuit (14) that detects at least one operating parameter of the battery unit (10) and from said at least one operating parameter, derives a control signal for controlling a charging and discharging process, characterized in that the battery unit (10) has means (15) for transmitting the control signal to outside the battery unit (10), namely switching means (25, 31) located in the electrical device (20) and the charger (30), respectively, and the switching means (25) in the electrical device (20) are intended for controlling capacity of the electrical device as a function of the control signal of the battery unit (10), and the switching means (31) in the charger (30) are intended for controlling a charging current transmitted from the charger (30) to the battery unit (10).

3. A charger for a battery unit (10) which has a monitoring circuit (14) that detects at least one operating parameter of the battery unit and from said at least one operating parameter, derives a control signal for controlling the charging process, characterized in that in the charger (30), switching means (31) are present for controlling a charging current, transmitted from the charger (30) to the battery unit (10), as a function of the control signal of the battery unit (10).

4. An electrical device, which can be connected to a battery unit (10) for an energy supply, which has a monitoring circuit (14) that detects at least one operating parameter of the battery unit (10), and from said at least one

operating parameter, derives a control signal for controlling a discharging process, characterized in that in the electrical device (20), switching means (25) are present for controlling capacity of the electrical device as a function of the control signal of the battery unit (10).

5. The equipment system of claim 1, characterized in that the monitoring circuit (14) in the battery unit (10), as the at least one operating parameter, detects a current flowing into or out of the battery unit (10) and/or a terminal voltage of the battery unit (10) and/or a temperature of the battery unit (10), or a variable that is in relation to the temperature.

6. The battery unit of claim 2, characterized in that the monitoring circuit (14) in the battery unit (10), as the at least one operating parameter, detects the current flowing into or out of the battery unit (10) and/or a terminal voltage of the battery unit, and/or a temperature of the battery unit (10), or a variable that is in relation to the temperature.

7. The charger of claim 3, characterized in that the control signal controlling the switching means (31) depends on a charging current flowing into the battery unit (10) and/or a terminal voltage of the battery unit (10), and/or a temperature of the battery unit (10), or a variable that is in relation to the temperature.

8. The electrical device of claim 4, characterized in that the control signal controlling the switching means (31) depends on a current flowing out of the battery unit (10), and/or a terminal voltage of the battery unit (10), and/or a temperature of the battery unit (10), or a variable that is in relation to the temperature.

* * * * *