



(22) Date de dépôt/Filing Date: 2013/04/02

(41) Mise à la disp. pub./Open to Public Insp.: 2013/12/08

(45) Date de délivrance/Issue Date: 2017/06/13

(30) Priorités/Priorities: 2012/06/08 (US61/657,248);
2012/07/09 (US61/669,299); 2012/10/12 (US61/712,930);
2013/01/23 (US13/747,732)

(51) Cl.Int./Int.Cl. *F16L 25/01* (2006.01),
B64D 37/32 (2006.01), *F16L 25/02* (2006.01)


(72) Inventeurs/Inventors:
GAW, KEVIN O'BRIEN, US;
KELLEY, NATHAN MICHAEL, US;
AXTELL, JOHN THOMAS, US;
IRWIN, JAMES PATRICK, US;
MINTEER, DAVID WILLIAM, US;
VELASCO, DIEGO A., US

(73) Propriétaire/Owner:
THE BOEING COMPANY, US

(74) Agent: SIM & MCBURNEY

(54) Titre : ENSEMBLE DE RACCORDEMENT CONDUCTEUR

(54) Title: CONDUCTIVE COUPLING ASSEMBLY



(57) Abrégé/Abstract:

A method and apparatus for conducting an electrical current between a first transport member and a second transport member. In one illustrative embodiment, a coupling assembly comprises a first fitting associated with a first end of a first transport member, a second fitting associated with a second end of a second transport member, and a seal. The seal is configured for placement around the first fitting and the second fitting when the first end of the first transport member is positioned relative to the second end of the second transport member. The seal is further configured to seal an interface between the first transport member and the second transport member. The seal is comprised of a material configured such that the seal has a level of conductivity within a selected range and such that a conductive pathway is formed between the first transport member and the second transport member.

ABSTRACT

A method and apparatus for conducting an electrical current between a first transport member and a second transport member. In one illustrative embodiment, a coupling assembly comprises a first fitting associated with a first end of a first transport member, a second fitting associated with a second end of a second transport member, and a seal. The seal is configured for placement around the first fitting and the second fitting when the first end of the first transport member is positioned relative to the second end of the second transport member. The seal is further configured to seal an interface between the first transport member and the second transport member. The seal is comprised of a material configured such that the seal has a level of conductivity within a selected range and such that a conductive pathway is formed between the first transport member and the second transport member.

CONDUCTIVE COUPLING ASSEMBLY

5

BACKGROUND INFORMATION**1. Field:**

10 The present disclosure relates generally to a fluid
transport system and, in particular, to a fluid transport
system configured to have a desired electrical
configuration. Still more particularly, the present
disclosure relates to a method and apparatus for limiting
15 the flow of electric current, induced by an event such as
lightning or an electrical fault, along a fluid transport
system and allowing static dissipation along the fluid
transport system.

20 **2. Background:**

A fluid transport system typically includes tubes
connected together for moving fluid through the tubes.
As used herein, a "fluid" may comprise any number of
liquids and/or gases. Fluid transport systems may be

used to transport any number of fluids within vehicles, such as, for example, aircraft. A fluid transport system may include groups of tubes connected in series, in parallel, or a combination of the two. In some cases, 5 these tubes may be coupled together using, for example, without limitation, coupling assemblies.

A fuel system is an example of one type of fluid transport system in an aircraft. Some currently available fuel systems comprise fuel tanks comprised of 10 metal and/or composite materials, such as carbon fiber reinforced plastic (CFRP). When used in fuel tanks, fuel tubes comprised of plastic and/or metal materials may be prone to the buildup of electrostatic charge. The buildup of electrostatic charge on a fuel tube may be 15 caused by a number of different factors including, but not limited to, the flow of fuel through and/or around the fuel tube.

When electrostatic charge builds up on a surface of a fuel tube, the fuel tube may be prone to electrical 20 discharge of this electrostatic charge. This electrical discharge may be referred to as "static discharge." Static discharge may take the form of, for example, an electrical arc from the fuel tube to a nearby structure.

Further, when used in a fuel tank comprised of 25 electrically resistive materials such as, for example, carbon reinforced plastic, fuel tubes comprised of plastic and/or metal materials may also be prone to voltages and currents induced by an electromagnetic event, such as lightning. In some situations, the 30 induced voltages may lead to electrical discharge in the form of electrical sparking and/or arcing from the tubes to one or more nearby structures. Additionally, in some situations, the induced currents may lead to electrical discharge within the connections between tubes.

The voltage and currents induced by lightning may typically be small and within selected tolerances inside the fuel tanks of aircraft having wings comprised of metal materials, such as, for example, aluminum.

5 However, the voltages and currents induced by lightning inside the fuel tanks of aircraft having wings comprised of non-metallic materials, such as, for example, carbon fiber reinforced plastic, may be greater and outside of selected tolerances. In particular, the higher

10 electrical resistance of carbon fiber reinforced plastic as compared to aluminum may cause larger voltages and currents to be induced with respect to the tubes inside the fuel tanks.

Typically, with currently available aircraft, fuel

15 transport systems use metal tubing to transport fuel within fuel tanks. In an aircraft comprised of carbon fiber reinforced plastic, the metal tubing may be prone to induced voltages that may cause undesired electrical discharges. Some currently available methods for

20 reducing the level or intensity of an undesired electrical discharge may include inserting high resistance electrical isolators into the metal tubing. These isolators may be used to constrain the currents and voltages that may be induced by lightning, thereby

25 reducing the level of any undesired electrical discharge that may occur.

However, the weight and expense needed to install metal systems having these isolators may be greater than desired. Part of the cost and expense to install such

30 metal systems with isolators may be the need to protect the metal systems against arcing from the induced voltages remaining in the system after the installation of the isolators.

Additionally, an electrical discharge within a fuel system caused by the buildup of electrostatic charge and/or induced voltages and currents in response to an electromagnetic event such as lightning may present safety concerns. Therefore, it would be desirable to have a method and apparatus that takes into account at least some of the issues discussed above, as well as other possible issues.

SUMMARY

10 In one illustrative embodiment, there is provided a coupling assembly comprising: a first fitting associated with a first end of a first transport member; a second fitting associated with a second end of a second transport member; a seal configured for placement around
15 the first fitting and the second fitting when the first end of the first transport member is positioned relative to the second end of the second transport member, wherein the seal is further configured to seal an interface between the first end of the first transport member and
20 the second end of the second transport member, and wherein the seal is comprised of a material configured such that the seal has a level of conductivity within a selected range and such that a conductive pathway is formed between the first transport member and the second
25 transport member; and a cover configured to cover the seal and hold the seal in place, the cover being disposed on the first fitting and the second fitting.

In another illustrative embodiment, there is provided a fuel system comprising: a first transport
30 member; a second transport member; and a coupling assembly configured to couple a first end of the first transport member to a second end of the second transport member, wherein the coupling assembly comprises: a first

fitting associated with the first end of the first transport member and having a level of conductivity within a selected range; a second fitting associated with the second end of the second transport member and having the level of conductivity within the selected range; a first gasket configured for placement around the first fitting, wherein the first gasket comprises a viscoelastic material having the level of conductivity within the selected range; a second gasket configured for placement around the second fitting, wherein the second gasket comprises the viscoelastic material having the level of conductivity within the selected range; a sleeve configured for placement around the first gasket and the second gasket and having the level of conductivity within the selected range in which the sleeve is configured to compress the first gasket and the second gasket to form a seal that seals an interface between the first end of the first transport member and the second end of the second transport member when the first end of the first transport member is positioned relative to the second end of the second transport member, wherein the seal forms a conductive pathway between the first transport member and the second transport member through the first fitting, the seal, and the second fitting, wherein the first gasket is a first O-ring, the second gasket is a second O-ring, and the viscoelastic material is a conductive elastomer; and a cover configured to cover the first gasket, the second gasket, the sleeve, at least a portion of the first fitting, and at least a portion of the second fitting, the cover being disposed on the first fitting and the second fitting.

In another illustrative embodiment, there is provided a method for conducting an electrical current between a first transport member and a second transport

member in a fuel system in an aerospace vehicle, the method comprising: operating the aerospace vehicle such that an electrical charge builds up around a surface of at least one of the first transport member and the second transport member in the fuel system in the aerospace vehicle, wherein a first end of the first transport member is coupled to a second end of the second transport member using a first fitting associated with the first end of the first transport member, a second fitting associated with the second end of the second transport member, a seal, and a cover, wherein the seal is configured to seal an interface between the first end of the first transport member and the second end of the second transport member when the first end of the first transport member is positioned relative to the second end of the second transport member, wherein the seal is comprised of a material configured such that the seal has a level of conductivity within a selected range and such that a conductive pathway is formed between the first transport member and the second transport member, and wherein the cover is configured to cover the seal and hold the seal in place, the cover being disposed on the first fitting and the second fitting; and dissipating electrostatic charge that builds up on at least one of the first transport member and the second transport member during operation of the aerospace vehicle using the conductive pathway formed by the seal between the first transport member and the second transport member.

In another illustrative embodiment, there is provided a coupling assembly comprising: a first ferrule attached to a first end of a first transport member, the first ferrule and the first transport member both having a level of conductivity within a selected range; a second ferrule attached to a second end of a second transport

member, the second ferrule and the second transport member both having the level of conductivity within the selected range; a first gasket received by the first ferrule, wherein the first gasket comprises a viscoelastic material having the level of conductivity within the selected range; a second gasket received by the second ferrule, wherein the second gasket comprises the viscoelastic material having the level of conductivity within the selected range; a clamshell device disposed over the first ferrule and the second ferrule, wherein the first gasket and the second gasket are disposed within the clamshell device, and wherein the clamshell device is non-conductive relative to the level of conductivity; a sleeve connected to an inside surface of the clamshell device, wherein the sleeve is in contact with the first gasket and the second gasket, wherein the sleeve has the level of conductivity within the selected range, and wherein sidewalls of the clamshell device are not in contact with any of the sleeve, the first gasket, and the second gasket, wherein a conductive pathway is formed between the first transport member and the second transport member via the first ferrule, the first gasket, the sleeve, the second gasket, and the second ferrule; and a hinge connected to the clamshell device and configured to allow opening and closing of the clamshell device onto the first ferrule, the second ferrule, the first gasket, and the second gasket, and wherein when closed the clamshell device forms a seal between the first transport member and the second transport member.

30 In another illustrative embodiment, there is provided a coupling assembly comprising: a first ferrule attached to a first end of a first transport member, the first ferrule and the first transport member both having a level of conductivity within a selected range; a second

ferrule attached to a second end of a second transport member, the second ferrule and the second transport member both having the level of conductivity within the selected range; a first gasket received by the first
5 ferrule, wherein the first gasket comprises a viscoelastic material having the level of conductivity within the selected range; a second gasket received by the first ferrule, wherein the second gasket comprises the viscoelastic material having the level of
10 conductivity within the selected range; a third gasket received by the second ferrule, wherein the third gasket comprises a viscoelastic material having the level of conductivity within the selected range; a fourth gasket received by the second ferrule, wherein the fourth gasket
15 comprises the viscoelastic material having the level of conductivity within the selected range; a clamshell device disposed over the first ferrule and the second ferrule, wherein the first gasket and the third gasket are disposed within the clamshell device, wherein the
20 second gasket and the fourth gasket are disposed under the clamshell device, and wherein the clamshell device comprises a material having the level of conductivity; and a sleeve connected to an inside surface of the clamshell device, wherein the sleeve is in contact with
25 the first gasket and the third gasket, wherein the sleeve has the level of conductivity within the selected range, and wherein sidewalls of the clamshell device are not in contact with any of the sleeve, the first gasket, and the second gasket, wherein the sidewalls are in contact with
30 the second gasket and the fourth gasket, wherein a first conductive pathway is formed between the first transport member and the second transport member via the first ferrule, the first gasket, the sleeve, the second gasket, and the second ferrule, and wherein a second conductive

pathway is formed between the first transport member and the second transport member via the first ferrule, the second gasket, the clamshell device, the fourth gasket, the second ferrule, and the second transport member.

5 In another illustrative embodiment, there is provided a fluid transport system comprising: a plurality of transport members; and a number of connections connecting transport members in the plurality of transport members to each other, wherein the plurality of
10 transport members and the number of connections are comprised of materials selected such that an intensity of an electrical discharge that occurs within the fluid transport system is reduced to within selected tolerances and wherein a connection in the number of connections is
15 configured to connect a first transport member in the plurality of transport members and a second transport member in the plurality of transport members and wherein the connection is configured such that an electrical resistance across the connection is less than the
20 electrical resistance through a specified length of at least one of the first transport member and the second transport member.

 In another illustrative embodiment, there is provided a fluid transport system having an electrical
25 configuration configured to reduce an intensity of an electrical discharge that occurs within the fluid transport system, the fluid transport system comprising: a plurality of tubes, wherein a tube in the plurality of tubes is comprised of a composite material selected such
30 that the tube has a resistance within a selected range configured to reduce voltages and currents, induced in response to an electromagnetic event, along the tube to within selected tolerances; and a number of coupling assemblies configured to couple tubes in the plurality of

tubes to each other, wherein a coupling assembly in the number of coupling assemblies comprises: a first fitting associated with a first end of a first tube in the plurality of tubes; a second fitting associated with a
5 second end of a second tube in the plurality of tubes; and a seal configured for placement around the first fitting and the second fitting when the first end of the first tube is positioned relative to the second end of the second tube, wherein the seal is configured to seal
10 an interface between the first end of the first tube and the second end of the second tube and provide a conductive pathway between the first tube and the second tube to allow electrostatic charge that builds up on at least one of the first tube and the second tube to be
15 dissipated, and wherein the first tube, the second tube, and the coupling assembly form the conductive pathway grounding the first tube and the second tube without directly grounding the coupling assembly to a structure.

In yet another illustrative embodiment, there is
20 provided a method for reducing an intensity of an electrical discharge that occurs within a fluid transport system in an aerospace vehicle, the method comprising: operating the aerospace vehicle, wherein the fluid transport system in the aerospace vehicle is comprised of
25 materials selected such that the fluid transport system has an electrical configuration, wherein the fluid transport system comprises a plurality of transport members and a plurality of connections connecting transport members in the plurality of transport members
30 to each other, wherein the plurality of transport members and the plurality of connections are comprised of materials selected such that an intensity of the electrical discharge that occurs within the fluid transport system is reduced to within selected

tolerances, and wherein a connection in the plurality of connections is configured to connect a first transport member in the plurality of transport members and a second transport member in the plurality of transport members, and wherein the connection is configured such that an electrical resistance across the connection is less than the electrical resistance through a specified length of at least one of the first transport member and the second transport member; and reducing the intensity of the electrical discharge that occurs within the fluid transport system during operation of the aerospace vehicle to within selected tolerances by the electrical configuration of the fluid transport system.

In still another illustrative embodiment, there is provided an apparatus comprising: a first transport member configured for use in a fluid transport system, wherein the first transport member is comprised of a material configured to reduce voltages and currents, induced in response to an electromagnetic event, along the first transport member; a second transport member configured for use in the fluid transport system, wherein the second transport member is comprised of the material configured to reduce voltages and currents, induced in response to the electromagnetic event, along the second transport member, and wherein the second transport member is separated from the first transport member by an interface; a coupling assembly connecting the first transport member and the second transport member, the coupling assembly including a first ferrule that connects to the first transport member and a second ferrule that connects to the second transport member, the first ferrule including a first groove in which is a first O-ring and a second groove in which is a second O-ring, the second ferrule including a third groove in which is a

third O-ring and a fourth groove in which is a fourth O-ring, the coupling assembly further including a clamshell device connected to a sleeve, wherein when the coupling assembly is in a closed position: the first O-ring
5 creates a first seal and a first conductive pathway between the first ferrule and the clamshell device, the second O-ring creates a second seal and a second conductive pathway between the first ferrule and the sleeve, the third O-ring creates a third seal and a third
10 conductive pathway between the second ferrule and the sleeve, and the fourth O-ring creates a fourth seal and a fourth conductive pathway between the second ferrule and the clamshell device.

The features and functions can be achieved
15 independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives, and features thereof will best be understood by reference to
25 the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of a fluid transport system in the form of a block diagram in accordance with
30 an illustrative embodiment;

Figure 2 is an illustration of a transport member in the form of a block diagram in accordance with an illustrative embodiment;

Figure 3 is an illustration of a connection in the form of a block diagram in accordance with an illustrative embodiment;

Figure 4 is an illustration of tubes configured for use in a fluid transport system in accordance with an illustrative embodiment;

Figure 5 is an illustration of components for a coupling assembly in accordance with an illustrative embodiment;

Figure 6 is an illustration of a partially-assembled coupling assembly in accordance with an illustrative embodiment;

Figure 7 is an illustration of a fully-assembled coupling assembly in accordance with an illustrative embodiment;

Figure 8 is an illustration of a cross-sectional view of a coupling assembly in accordance with an illustrative embodiment;

Figure 9 is an illustration of a cross-sectional view of a different configuration for a coupling assembly in accordance with an illustrative embodiment;

Figure 10 is an illustration of a cross-sectional view of another configuration for a coupling assembly in accordance with an illustrative embodiment;

Figure 11 is an illustration of a cross-sectional view of a different configuration for a coupling assembly in accordance with an illustrative embodiment;

Figure 12 is an illustration of a process for reducing an intensity of an electrical discharge within a fluid transport system in the form of a flowchart in accordance with an illustrative embodiment;

Figure 13 is an illustration of a process for reducing the energy that can be supplied to an electrical discharge within a fluid transport system in the form of a flowchart in accordance with an illustrative embodiment;

Figure 14 is an illustration of a process for dissipating electrostatic charge in the form of a flowchart in accordance with an illustrative embodiment;

Figure 15 is an illustration of an aircraft manufacturing and service method in the form of a flowchart in accordance with an illustrative embodiment; and

Figure 16 is an illustration of an aircraft in the form of a block diagram in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

The different illustrative embodiments recognize and take into account different considerations. For example, the different illustrative embodiments recognize and take into account that it may be desirable to have a fluid transport system configured to reduce the intensity of electrical discharge from components, such as, for example, tubes, within the fluid transport system.

The different illustrative embodiments recognize and take into account that tubes comprised of materials with high electrical resistance levels may be used in a fluid transport system to reduce the intensity of electrical discharge caused by voltages and currents induced in response to an electromagnetic event such as, for example, lightning. High levels of electrical resistance may include levels above, for example, about 100 kilohms per meter length of tube.

Materials with high levels of electrical resistance include, but are not limited to, nonmetallic fiber reinforced composite materials, carbon reinforced plastic materials, plastic materials, non-homogenous metallic materials, and/or other types of materials. The illustrative embodiments recognize and take into account that tubes comprised of any of these types of materials may limit the levels of voltages and currents induced in response to the occurrence of an electromagnetic event, thereby reducing the intensity of any electrical discharge caused by these induced voltages and/or currents.

For example, materials having high levels electrical resistance may limit the current induced along a tube in response to an electromagnetic event, such as lightning. With fuel tubes in a fuel system, limiting the flow of current along these fuel tubes may limit the voltages induced across the connections between these fuel tubes when the electrical resistance of these connections is lower than the electrical resistance through a specified length of fuel tube connected to the connection. The specified length, for example, may be 0.3 meters of tube. In this manner, electrical discharge in the form of electrical sparking and/or arcing may be reduced and/or prevented. Consequently, the illustrative embodiments recognize and take into account that an upper limit for resistivity or, equivalently, a lower limit for conductivity, may be selected for the materials used in the connections between fuel tubes to reduce electrical discharge across these connections and along the fuel tubes.

However, the illustrative embodiments recognize and take into account that in some cases, if a conductive material were to become dislodged from a connection

between fuel tubes and form a bridge between a metal fuel tube and a structure within the fuel tank, the conductive material could short circuit this bridge and allow, for example, lightning to induce a flow of current or possibly a spark from the fuel tube to the structure. As a result, the illustrative embodiments recognize and take into account that the resistivity of the conductive material may require a lower limit for resistivity, or equivalently, an upper limit for conductivity.

10 However, the different illustrative embodiments recognize and take into account that in other cases, fuel tubes may be used in metallic fuel tanks in which lightning induced voltages and/or currents may be within selected tolerances. Consequently, the materials used in the connections between fuel tubes may only need to be selected to allow dissipation of electrostatic charge that has built up along these fuel tubes. Consequently, the illustrative embodiments recognize and take into account that only an upper limit for resistivity or, 20 equivalently, a lower limit for conductivity, may need to be selected for the materials used in the connections between fuel tubes to reduce electrical discharge across these connections.

25 Further, the illustrative examples recognize and take into account that the possibility of a static discharge caused by the build-up of electrostatic charge may be reduced and/or prevented by grounding fuel tubes to a structure having a resistance that is sufficiently low to remove electrostatic charge from the fuel tubes at a rate faster than the electrostatic charge can build up on the fuel tubes such that a net charge on the fuel tubes within selected tolerances may be maintained. In particular, a net charge on the fuel tubes may be reduced to within selected tolerances. The different

illustrative embodiments recognize and take into account that when fuel tubes are connected in series, electrostatic charge may be removed from the series of fuel tubes by using conductive pathways through the connections between the fuel tubes and then grounding the series to the structure.

Thus, the different illustrative embodiments provide a system and method for reducing an intensity of electrical discharge within a fluid transport system. In one illustrative embodiment, the fluid transport system is located within a vehicle, such as an aerospace vehicle. Further, the fluid transport system may be comprised of materials selected such that the fluid transport system has a selected electrical configuration. This electrical configuration for the fluid transport system may be selected such that electrical discharge that occurs within the fluid transport system during operation of the aerospace vehicle may be reduced to within selected tolerances.

Referring now to the figures and, in particular, with reference to **Figure 1**, an illustration of a fluid transport system in the form of a block diagram is depicted in accordance with an illustrative embodiment. Fluid transport system **100** is configured to transport materials within platform **104**.

The materials transported may include any number of liquid materials, gaseous materials, and/or solid materials. As one illustrative example, fluid transport system **100** may be used to transport fluid **102** within platform **104**. Fluid **102** may comprise any number of liquids and/or gases.

In one illustrative example, platform **104** takes the form of aerospace vehicle **106**. In this illustrative example, fluid transport system **100** may take the form of

fuel system **105** configured to transport fluid **102** in the form of fuel **108** within aerospace vehicle **106**. Aerospace vehicle **106** may be selected from one of an aircraft, a helicopter, an unmanned aerial vehicle (UAV), a space shuttle, or some other suitable type of vehicle configured to travel in air and/or space. Of course, in other illustrative examples, platform **104** may take the form of a ground vehicle, a water vehicle, or some other suitable type of vehicle.

10 As depicted, fluid transport system **100** comprises plurality of transport members **110** and number of connections **112**. As used herein, a "plurality of" items means two or more items. Further, a "number of" items means one or more items. For example, plurality of
15 transport members **110** means two or more transport members, while number of connections **112** means one or more connections.

As used herein, a "transport member," such as one of plurality of transport members **110**, may be any structural
20 member having a channel through which materials may be moved. Depending on the implementation, a transport member in plurality of transport members **110** may take the form of, for example, a tube, a duct, a cylinder, a pipe, a pipeline, a conduit, or some other type of structure
25 having a channel through which materials may flow. As one illustrative example, plurality of transport members **110** may take the form of plurality of tubes **111**.

Further, as used herein, a "connection," such as one of number of connections **112**, may be any type of
30 permanent or removable physical connection between two or more transport members in plurality of transport members **110**. Depending on the implementation, a connection in number of connections **112** may comprise any number of components such as, for example, without limitation,

fasteners, joint elements, screws, ferrules, rings, seals, adhesive bonds, and/or other types of components.

As one illustrative example, number of connections **112** may take the form of number of coupling assemblies **113**. Each coupling assembly in number of coupling assemblies **113** may be configured to couple a transport member in plurality of transport members **110** with another transport member in plurality of transport members **110**. In this manner, when plurality of transport members **110** takes the form of plurality of tubes **111**, number of coupling assemblies **113** may be used to couple tubes in plurality of tubes **111** to each other.

As used herein, a first component, such as a tube, "coupled" to a second component, such as another tube, means that the first component is connected to or fastened to the second component. This connection may be a direct connection or an indirect connection. For example, an end of one tube may be coupled to the end of another tube using a coupling assembly. With a direct connection, the end of the tube may come into contact with the end of the other tube when these two ends are coupled. With an indirect connection, the end of the tube and the end of the other tube may not contact each other when these two ends are coupled.

Of course, in other illustrative examples, number of connections **112** may take other forms. For example, transport members may be attached to each other using other methods, such as, for example, applying adhesives to permanently connect transport members or performing thermoplastic welding operations.

In these illustrative examples, fluid transport system **100** is configured such that fluid transport system **100** has selected electrical configuration **114**. Selected electrical configuration **114** may be comprised of set of

electrical properties **116**, each having a value within a selected range. As used herein, a "set of" items means one or more items.

Set of electrical properties **116** may include, for example, resistance, resistivity, conductivity, and/or other types of electrical properties. Further, in some cases, any component that makes up fluid transport system **100** may be configured such that the component also has a set of electrical properties with values within selected ranges.

Selected electrical configuration **114** may be selected such that an intensity of electrical discharge that occurs within fluid transport system **100** during operation of aerospace vehicle **106** may be reduced to within selected tolerances. In particular, selected electrical configuration **114** may be selected such that voltages and currents, induced within fluid transport system **100** in response to an electromagnetic event such as lighting, may be constrained to within selected tolerances. Still further, selected electrical configuration **114** may be selected to allow dissipation of electrostatic charge that may build up along plurality of transport members **110** during operation of aerospace vehicle **106**.

Turning now to **Figure 2**, an illustration of a transport member in plurality of transport members **110** from **Figure 1** in the form of a block diagram is depicted in accordance with an illustrative embodiment. Transport member **200** in **Figure 2** is an example of one implementation for a transport member in plurality of transport members **110** in **Figure 1**. In one illustrative example, transport member **200** takes the form of tube **201**. Tube **201** may be an example of one implementation for a tube in plurality of tubes **111** in **Figure 1**.

As depicted, transport member **200** has first end **202** and second end **204**. Further, transport member **200** has outer surface **203** and inner surface **205**. Inner surface **205** may form channel **206** that extends along axis **215** through transport member **200** from first end **202** of transport member **200** to second end **204** of transport member **200**. Axis **215** may be a center axis that extends through transport member **200** from first end **202** of transport member **200** to second end **204** of transport member **200**. Fluid **102** from **Figure 1** may be carried within channel **206**.

In these illustrative examples, connection **218** may be an example of a connection in number of connections **112** that may be used to connect transport member **200** to another transport member in plurality of transport members **110** in **Figure 1**. As depicted, connection **218** may be used at either first end **202** of transport member **200** or second end **204** of transport member **200** to connect transport member **200** to another transport member.

In one illustrative example, connection **218** takes the form of coupling assembly **220**. Coupling assembly **220** may comprise any number of components such as, for example, without limitation, fasteners, joint elements, screws, ferrules, rings, seals, and/or other types of components.

In these illustrative examples, transport member **200** may be comprised of material **207**. Material **207** may be selected such that transport member **200** has electrical configuration **210**. Electrical configuration **210** may comprise set of electrical properties **212**, each having a value within a selected range. In one illustrative example, set of electrical properties **212** includes resistance **214**. Resistance **214** may be electrical resistance in these examples.

As used herein, the "resistance" of an item, such as transport member **200**, is the opposition of the item to the flow of electric current through the item. In this manner, resistance **214** of transport member **200** may be the
5 opposition of transport member **200** to the flow of electric current through transport member **200**.

Material **207** may be selected such that resistance **214** is within selected range **216**. Selected range **216** for resistance **214** may be selected such that resistance **214**
10 is sufficiently high to limit the voltages and currents, induced along transport member **200** in response to an electromagnetic event, to within selected tolerances. The electromagnetic event may be, for example, a lightning strike, a short circuit, an overloaded circuit,
15 an electrical field, or some other type of electromagnetic event.

In particular, material **207** may be selected such that the induced voltages and currents may be limited to levels at or below the level at which an undesired
20 electrical discharge may be formed. The undesired electrical discharge may be, for example, an arc between transport member **200** and a structure and/or a spark in connection **218** having at least one property outside of selected tolerances.

25 In one illustrative example, when transport member **200** is installed within a particular specified electromagnetic environment, selected range **216** for resistance **214** of transport member **200** may be selected such that the per unit length resistance **214** of transport
30 member **200** is at or above about 100 kilohms per meter (kΩ/m). For example, when transport member **200** is installed in a fuel tank of an aircraft comprised of carbon fiber reinforced plastic, the specified

electromagnetic environment may be a specified lightning environment.

Further, when transport member **200** is configured to allow static dissipation and reduce and/or prevent the build-up of electrostatic charge, selected range **216** for resistance **214** of transport member **200** may be selected such that the per unit length resistance **214** of transport member **200** is at or below about 100 megohms per meter (MΩ/m).

10 Material **207** may take a number of different forms. Material **207** may comprise, for example, without limitation, non-metallic fiber reinforced composite materials, plastic materials, and/or other suitable types of non-homogeneous metallic materials. In one
15 illustrative example, material **207** takes the form of composite material **208** comprised of any number of non-metallic materials. When comprised of composite material **208**, transport member **200** may be referred to as a composite transport member. In this manner, tube **201** may
20 be referred to as a composite tube.

In this manner, selected range **216** may include levels of resistance **214** sufficiently low to provide static dissipation. Further, selected range **216** may include levels of resistance **214** sufficiently high to
25 limit the voltages and currents induced along transport member **200** in response to an electromagnetic event.

Further, in these illustrative examples, resistance **214** of transport member **200** may vary along axis **215**. However, composite material **208** may be selected such that
30 resistance **214** does not vary outside of selected tolerances. For example, transport member **200** may be formed using composite material **208** selected such that resistance **214** of transport member **200** may vary only by less than a selected percentage over the length of the

transport member and time with respect to axis **215**. This selected percentage may be between about 20 percent and about 40 percent in one illustrative example.

5 In one illustrative example, each transport member in plurality of transport members **110** in **Figure 1** may be implemented in a manner similar to transport member **200**. Resistance within selected range **216** may be distributed evenly over individual intervals of length of tubing installed in fluid transport system **100** in **Figure 1**.

10 When fluid transport system **100** takes the form of fuel system **105** in **Figure 1** located in a fuel tank, the distributed high electrical resistance may keep the electromagnetic fields inside the fuel tank induced by lightning from being concentrated, thereby reducing the
15 voltages and currents induced along the tubing. The per unit length resistance with respect to particular lengths of tubing in fuel system **105** may be different between different length intervals, but evenly distributed within these length intervals.

20 With reference now to **Figure 3**, an illustration of a connection in number of connections **112** from **Figure 1** in the form of a block diagram is depicted in accordance with an illustrative embodiment. Connection **300** is an example of one implementation for a connection in number
25 of connections **112** in **Figure 1**. Connection **300** may take the form of coupling assembly **301**. Coupling assembly **301** may be an example of one implementation for a coupling assembly in number of coupling assemblies **113** in **Figure 1**.

30 In some cases, connection **300** may be used to implement connection **218** in **Figure 2**. For example, coupling assembly **301** may be used to implement coupling assembly **220** in **Figure 2**.

As depicted, connection **300** is used to couple first transport member **302** with second transport member **304**. In particular, first end **306** of first transport member **302** is coupled to second end **308** of second transport member **304** using connection **300**. First transport member **302** has first surface **310** and first channel **312**. Second transport member **304** has second surface **314** and second channel **316**.

First channel **312** and second channel **316** may be configured to allow different types of materials to flow through first transport member **302** and second transport member **304**, respectively. These materials may include any number of liquid materials, gaseous materials, and/or solid materials. In one illustrative example, first transport member **302** and second transport member **304** may be a first fuel transport member and a second fuel transport member, respectively, through which fuel **108** from **Figure 1** is allowed to flow.

When first end **306** of first transport member **302** is coupled to second end **308** of second transport member **304**, material may flow between first channel **312** within first transport member **302** and second channel **316** within second transport member **304**. In this manner, first channel **312** and second channel **316** may form a channel that extends through both first transport member **302** and second transport member **304** when first transport member **302** and second transport member **304** are coupled to each other.

In these illustrative examples, connection **300** may be configured such that the electrical resistance across connection **300** is less than the electrical resistance through a specified length of first transport member **302** and through a specified length of second transport member **304**. This specified length may be, for example, without limitation, about one foot (ft) or about one third of a

meter (m) when connection **300** is implemented within a fuel tank in an aircraft comprised of carbon fiber reinforced plastic. In particular, this specified length may apply when first transport member **302**, second transport member **304**, and connection **300** are comprised of similarly non-metallic highly electrically resistive materials.

In this manner, each of the individual components that make up connection **300** may be configured such that the electrical resistance across connection **300** is less than the electrical resistance through the specified length of first transport member **302** and through the specified length of second transport member **304**. The components that make up connection **300** may be comprised of any number of materials including, but not limited to, metal, plastic, a composite material, and/or other types of materials.

If components having an electrical resistance outside of the selected range are used in forming connection **300**, the size and/or placement of these pieces relative to first transport member **302** and second transport member **304** may have restrictions. As one illustrative example, if a piece of metal having an electrical resistance outside of the selected range is used, the piece may need to have electrical ground paths to and through first transport member **302**, second transport member **304**, and/or other transport members. This type of grounding may allow static dissipation from tube to tube through the piece of metal and from the piece of metal to ground through one of the tubes.

In one illustrative example, connection **300** may include first fitting **318**, second fitting **320**, seal **322**, and cover **324**. First fitting **318** and second fitting **320** are associated with first end **306** of first transport

member **302** and second end **308** of second transport member **304**, respectively. In particular, first fitting **318** is associated with first surface **310** of first transport member **302** at first end **306** of first transport member **302**. Further, second fitting **320** is associated with second surface **314** of second transport member **304** at second end **308** of second transport member **304**.

When one component is "associated" with another component, as used herein, this association is a physical association. For example, a first component, such as first fitting **318**, may be considered to be associated with a second component, such as first transport member **302**, by being secured to the second component, bonded to the second component, mounted to the second component, welded to the second component, fastened to the second component, and/or connected to the second component in some other suitable manner. The first component also may be connected to the second component using a third component. Additionally, the first component may also be considered to be associated with the second component by being formed as part of and/or an extension of the second component.

In one illustrative example, first fitting **318** takes the form of first ferrule **326**, and second fitting **320** takes the form of second ferrule **328**. As used herein, a "ferrule," such as first ferrule **326** and second ferrule **328**, is a ring-type object used for fastening, joining, and/or reinforcement. A ferrule may take the form of a ring, a bracelet, a sleeve, a circular clamp, a spike, a band, or some other suitable type of object.

First ferrule **326** is placed around first surface **310** of first transport member **302** at first end **306** of first transport member **302**. Second ferrule **328** is placed

around second surface **314** of second transport member **304** at second end **308** of second transport member **304**.

In these illustrative examples, seal **322** is configured for placement around first fitting **318** and second fitting **320** when first end **306** of first transport member **302** is positioned relative to second end **308** of second transport member **304**. For example, seal **322** may be placed around first end **306** and second end **308** when first end **306** is positioned against second end **308**.

Seal **322** is configured to seal interface **330** formed between first end **306** of first transport member **302** and second end **308** of second transport member **304** when first end **306** of first transport member **302** and second end **308** of second transport member **304** are positioned relative to each other. Sealing interface **330** means reducing the possibility of material flowing into and/or out of the channel formed by first channel **312** within first transport member **302** and second channel **316** within second transport member **304** at interface **330** when first transport member **302** is coupled to second transport member **304**.

In some illustrative examples, seal **322** may be configured such that connection **300** has electrical configuration **329**. Electrical configuration **329** comprises set of electrical properties **333**, each having a value within a selected range. Electrical configuration **329** for connection **300** may be selected such that connection **300** forms conductive pathway **331** between first transport member **302** and second transport member **304**.

Conductive pathway **331** may be a pathway that allows an electrical current to flow between first transport member **302** and second transport member **304**. In other words, conductive pathway **331** allows an electrical current to be conducted between first transport member

302 and second transport member **304**. For example, electrical currents flowing through first surface **310** of first transport member **302** may be conducted to second surface **314** of second transport member **304** when
5 conductive pathway **331** is present. In this manner, electrostatic charge may be dissipated using conductive pathway **331** formed by connection **300**.

In an illustrative example, at least a portion of seal **322** comprises viscoelastic material **332**.
10 Viscoelastic material **332** is a material that comprises both viscous and elastic properties. A viscous material is a material that is resistant to being deformed by shear forces. An elastic material is a material that can return to its original shape after the stress that caused
15 deformation of the material is no longer applied.

In these illustrative examples, viscoelastic material **332** is nonmetallic. Further, viscoelastic material **332** may be selected such that viscoelastic material **332** has a level of conductivity **335** within
20 selected range **334** in these examples.

Selected range **334** may be selected such that conductive pathway **331** is formed between first transport member **302** and second transport member **304** when first transport member **302** is coupled to second transport
25 member **304** using connection **300**. In this illustrative example, selected range **334** may include levels of conductivity sufficiently high to allow electrostatic charge that builds up on first transport member **302** and/or second transport member **304** to be dissipated
30 through seal **322**.

However, in some cases, selected range **334** may also include levels of conductivity sufficiently low to reduce voltages and currents, induced in response to an electromagnetic event, such as, for example, lightning,

along first transport member **302** and/or second transport member **304**.

For example, selected range **334** may be between about 1×10^{-4} Siemens/centimeters (S/cm) and about 1×10^{-9} Siemens/centimeters (S/cm). Of course, in other illustrative examples, selected range **334** may be a particular level of conductivity between about 1×10^{-4} Siemens/centimeters and about 1×10^{-9} Siemens/centimeters. Of course, in other illustrative examples, the upper limit and/or lower limit for selected range **334** may be different, depending on the particular implementation for seal **322**.

Selected range **334** of conductivity **335** may also be the range selected for the conductivity of other components within connection **300**, first transport member **302**, and/or second transport member **304**. Further, first transport member **302**, second transport member **304**, first fitting **318**, second fitting **320**, seal **322**, and cover **324** may together have a level of conductivity that is within selected range **334**.

Conductivity is related to resistivity. The resistivity of an item is the ability of that item to prevent an electrical current from being conducted through the item. In particular, conductivity is the reciprocal of resistivity. As the conductivity of an item increases, the resistivity of the item decreases. Similarly, as the conductivity of an item decreases, the resistivity of the item increases. Selected range **334** for conductivity **335** corresponds to a range for resistivity between about 1×10^4 ohms-centimeters (Ω -cm) and about 1×10^9 ohms-centimeters (Ω -cm).

Viscoelastic material **332** may be selected from any number of materials configured to provide a level of conductivity **335** within selected range **334**. For example,

viscoelastic material **332** may comprise at least one of a conductive elastomer, a conductive rubber, a conductive silicone material, and other suitable types of materials. An elastomer is a polymer that is viscoelastic.

5 As used herein, the phrase "at least one of," when used with a list of items, means different combinations of one or more of the listed items may be used and only one of each item in the list may be needed. For example, "at least one of item A, item B, and item C" may include,
10 without limitation, item A or item A and item B. This example also may include item A, item B, and item C, or item B and item C. In other examples, "at least one of" may be, for example, without limitation, two of item A, one of item B, and 30 of item C; four of item B and seven
15 of item C; or some other suitable combination.

 In these illustrative examples, seal **322** comprises first gasket **336**, second gasket **338**, and sleeve **340**. As used herein, a "gasket," such as first gasket **336** and second gasket **338**, is a mechanical seal. In one
20 illustrative example, first gasket **336** takes the form of first O-ring **342**, and second gasket **338** takes the form of second O-ring **344**. As used herein, an "O-ring," such as first O-ring **342** and second O-ring **344**, is a mechanical gasket in the shape of a torus. Further, an O-ring has a
25 loop-type shape.

 Of course, in other illustrative examples, first gasket **336** and second gasket **338** may take some other suitable form. For example, in some cases, first gasket **336** and second gasket **338** may be configured such that a
30 cross-section of these gaskets has a triangular shape, a square shape, a rectangular shape, an oval shape, or some other suitable type of shape.

 First O-ring **342** and second O-ring **344** are configured to be received by first fitting **318** and second

fitting **320**, respectively. As one illustrative example, first O-ring **342** may fit into a groove around first fitting **318**, and second O-ring **344** may fit into a groove around second fitting **320**.

5 Sleeve **340** is then placed around first O-ring **342** and second O-ring **344** to apply pressure to first O-ring **342** and second O-ring **344**. This pressure compresses first O-ring **342** and second O-ring **344** and causes these O-rings to seal interface **330** between first end **306** of
10 first transport member **302** and second end **308** of second transport member **304**.

 Additionally, in some illustrative examples, cover **324** may be placed over seal **322**, at least a portion of first fitting **318**, and at least a portion of second
15 fitting **320**. Cover **324** may be used to cover seal **322** and hold seal **322** in place. In one illustrative example, cover **324** takes the form of clamshell device **346**.

 When interface **330** has been sealed using seal **322**, conductive pathway **331** is formed between first transport
20 member **302** and second transport member **304**. As one illustrative example, first O-ring **342** and second O-ring **344** may be comprised of viscoelastic material **332** having a level of conductivity within selected range **334**. Further, each of first fitting **318**, second fitting **320**,
25 and sleeve **340** may be comprised of a nonmetallic material having a level of conductivity within selected range **334**.

 In this illustrative example, conductive pathway **331** may be formed through first transport member **302**, through first fitting **318**, through first O-ring **342**, through
30 sleeve **340**, through second O-ring **344**, through second fitting **320**, and through second transport member **304**. When conductive pathway **331** is formed, an electrical current may flow in one of a first direction and a second direction.

The first direction may be from first transport member **302**, through first fitting **318**, through first O-ring **342**, through sleeve **340**, through second O-ring **344**, through second fitting **320**, and to second transport member **304**. The second direction may be from second transport member **304**, through second fitting **320**, through second O-ring **344**, through sleeve **340**, through first O-ring **342**, through first fitting **318**, and to first transport member **302**.

10 In this manner, electrical currents induced by electrostatic charge that builds up on first surface **310** of first transport member **302** and/or second surface **314** of second transport member **304** may be dissipated using conductive pathway **331**. In particular, with connection
15 **300** coupling first transport member **302** and second transport member **304**, first transport member **302** and second transport member **304** may be considered grounded to each other.

In other words, an electrical current flowing into
20 first transport member **302** may flow into second transport member **304** through coupling assembly **301** without interruption and without the level of the electrical current changing outside of selected tolerances. Similarly, an electrical current flowing into second
25 transport member **304** may flow into first transport member **302** through coupling assembly **301** without interruption and without the level of the electrical current changing outside of selected tolerances.

In some cases, the electrical current traveling
30 along conductive pathway **331** may be electrical current induced in response to an electromagnetic event such as, for example, a lightning strike. Selected range **334** of conductivity **335** may be selected such that the voltage drop across first O-ring **342** and the voltage drop across

second O-ring **344** when this type of electrical current travels through first O-ring **342** and second O-ring **344**, respectively, is reduced to within selected tolerances.

In these illustrative examples, first transport member **302** and second transport member **304** may be fuel tubes in, for example, fuel system **105** in aerospace vehicle **106** in **Figure 1**. In some cases, fuel system **105** may be configured such that fuel system **105** has an overall level of conductivity within selected range **334**. Different portions of fuel system **105** may have different levels of conductivity and different ranges which apply to different portions of the fuel system. Some portions of the system may not be required to be within the range of conductivity specified. The one or more levels of conductivity within selected range **334** may be lower than the levels of conductivity for other portions of aerospace vehicle **106**. For example, fuel system **105** may have a level of conductivity between about 1×10^{-4} Siemens/centimeters and about 1×10^{-9} Siemens/centimeters. However, one or more other portions of aerospace vehicle **106** may have a level of conductivity above about 1×10^{-4} Siemens/centimeters.

In this manner, fluid transport system **100** in **Figure 1** having plurality of transport members **110**, each implemented in a manner similar to transport member **200** in **Figure 2**, and number of connections **112**, each implemented in a manner similar to connection **300** in **Figure 3**, may be configured to reduce electrical discharge within fluid transport system **100**. Plurality of transport members **110**, interconnected within fluid transport system **100** may have high electrical resistance levels substantially evenly distributed throughout this interconnected system of tubing.

In particular, the voltages and currents induced by lightning may be reduced and/or limited such that the energy imparted to the electrical discharge may be reduced. In this manner, the undesired effects of electrical discharge within fluid transport system **100** may be reduced and/or prevented. In particular, the overall energy supplied to the electrical discharge may be constrained to within selected tolerances.

In some cases, when implementing fluid transport system **100** comprising an interconnected network of high electrical resistance transport members, such as plurality of transport members **110**, the network of transport members may need to be grounded to structure at one or more points for the purposes of removing electrostatic charge build-up and constraining the lightning-induced voltages to the transport members. The transport members also may need to be grounded at the penetrations of an enclosure encompassing an electrically shielded volume in which fluid transport system **100** is installed, such as a fuel tank, in order to reduce the possibility of a portion of an external electromagnetic environment such as lightning or an electrical fault, entering the volume.

Grounds made to structure for the purpose of removing electrical charge to prevent electrostatic charge from building up along the transport members may be located at one or more places in fluid transport system **100** as a means to ensure that an electrical path exists though fluid transport system **100** from any point in fluid transport system **100** to structure or ground with a sufficiently low resistance to dissipate the electrostatic charge at a fast enough rate to prevent static charge build up at the point. In an electrostatic charging environment such as a fuel tank on an aircraft,

an acceptable electrical resistance for providing the capability to dissipate electrostatic charge from a point on a tube though a path to structure or ground may be a value at or below about 100 megohms($M\Omega$).

5 In such case, grounds made for this purpose need only assure that this overall ground path resistance is accomplished. As such, a static ground resistance may be a value up to about 100 megohms ($M\Omega$) in the limiting case, but in the usual case a value up to about 10 $M\Omega$.

10 Grounds made to structure for the purpose of constraining the lightning induced voltages in the network of transport members in fluid transport system **100** may be located at one or more places in fluid transport system **100** as a means to ensure that the
15 induced voltage from transport member to transport member and from transport member to structure at any point in fluid transport system **100** is less than a selected threshold. Grounds made to structure on the perimeter of a fuel tank for the purpose of shielding the fuel tank
20 may be located at one or more places in the perimeter to prevent undesired voltages and currents from penetrating the fuel tank by means of conductive members to which said voltages and currents are induced by an external environment such as lightning outside the tank.

25 The illustrations of fluid transport system **100** in **Figure 1**, transport member **200** in **Figure 2**, and connection **300** in **Figure 3** are not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be
30 implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be optional. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and

divided into different blocks when implemented in an illustrative embodiment.

In some illustrative examples, transport member **200** may have additional features not depicted in **Figure 2**.

5 For example, without limitation, one or more structural features may extend into channel **206** from inner surface **205** of transport member **200**. These structural features may need to be taken into account when measuring resistance **214** for transport member **200**.

10 In other illustrative examples, seal **322** may comprise only gasket **352**. Gasket **352** is configured to be placed around first fitting **318** and second fitting **320**. Gasket **352** may have a shape configured for placement around first fitting **318** and second fitting **320**. For
15 example, gasket **352** may have a first end that fits into a groove around first fitting **318** and a second end that fits into a groove around second fitting **320** when first end **306** of first transport member **302** is positioned relative to second end **308** of second transport member
20 **304**. Further, gasket **352** may comprise viscoelastic material **332** having a level of conductivity within selected range **334**.

With this type of configuration for seal **322** in connection **300**, cover **324** is used to compress gasket **352**
25 to seal interface **330** between first end **306** of first transport member **302** and second end **308** of second transport member **304**, instead of sleeve **340**. Further, with this configuration for seal **322**, conductive pathway **331** is formed through first transport member **302**, through
30 first fitting **318**, through gasket **352**, through second fitting **320**, and through second transport member **304**.

In still other illustrative examples, seal **322** may include one or more gaskets in addition to first gasket **336** and second gasket **338**. For example, seal **322** may

also include a third O-ring configured for placement around first fitting **318** and a fourth O-ring configured for placement around second fitting **320**.

These additional O-rings may be positioned such that
5 cover **324** compresses the third O-ring and the fourth O-ring instead of sleeve **340**. Further, the third O-ring and the fourth O-ring provide an additional conductive pathway. This additional conductive pathway is through first transport member **302**, through first fitting **318**,
10 through the third O-ring, through cover **324**, through the fourth O-ring, through second fitting **320**, and through second transport member **304**.

In some illustrative examples, first fitting **318** and/or second fitting **320** may not be considered part of
15 connection **300**. For example, when first fitting **318** and second fitting **320** are part of first transport member **302** and second transport member **304**, respectively, these fittings may be considered separate from connection **300**. In other illustrative examples, cover **324** may not be
20 considered part of connection **300**. For example, in some cases, connection **300** may include only seal **322**.

With reference now to **Figure 4**, an illustration of tubes configured for use in a fluid transport system is depicted in accordance with an illustrative embodiment.
25 In **Figure 4**, tube **402**, tube **404**, and tube **406** may be configured for use in a fluid transport system, such as, for example, fluid transport system **100** in **Figure 1**. In particular, tube **402**, tube **404**, and tube **406** are examples of implementations of tubes in plurality of tubes **111** in
30 **Figure 1**. Further, each of tube **402**, tube **404**, and tube **406** may be implemented in a manner similar to tube **201** in **Figure 2**.

In this illustrative example, tube **402**, tube **404**, and tube **406** are comprised of non-metallic composite

materials and configured to have a resistance within a selected range. This selected range may be between about 100 kilohms per meter to about 100 megohms per meter along axis **405** through tube **402**, tube **404**, and tube **406**.

5 With each of tube **402**, tube **404**, and tube **406** having a resistance within the selected range with respect to axis **405**, the flow of an electric current, induced in response to an electromagnetic event around these tubes, though these tubes may be limited to within selected tolerances.
10 Axis **405** is a center axis for tube **402**, tube **404**, and tube **406**.

The illustration of tube **402**, tube **404**, and tube **406** in **Figure 4** are not meant to imply physical or architectural limitations to the manner in which an
15 illustrative embodiment may be implemented. For example, in some cases, these tubes may be connected using other types of coupling assemblies other than coupling assembly **408** and coupling assembly **410**.

With reference now to **Figures 5-11**, illustrations of
20 different configurations for a coupling assembly are depicted in accordance with different illustrative embodiments. The components depicted in **Figures 5-11** may be illustrative examples of how components shown in block form in **Figure 3** may be implemented as physical
25 structures. The different components shown in **Figures 5-11** may be combined with components in **Figure 3**, used with components in **Figure 3**, or a combination of the two.

Turning now to **Figure 5**, an illustration of components for a coupling assembly is depicted in
30 accordance with an illustrative embodiment. In this illustrative example, components for a coupling assembly, such as coupling assembly **301** in **Figure 3**, are depicted. These components may be assembled to form a coupling assembly configured to couple first tube **500** with second

tube **502**. First tube **500** and second tube **502** are examples of implementations for first transport member **302** and second transport member **304**, respectively, in **Figure 3**.

5 As depicted, first tube **500** has first end **504**, and second tube **502** has second end **506**. Further, first tube **500** has first surface **508** and first channel **510**. Second tube **502** has second surface **512** and second channel **514**.

10 First ferrule **516**, second ferrule **518**, first O-ring **520**, second O-ring **522**, sleeve **524**, and clamshell device **526** are components that may be assembled to form coupling assembly **528**. First ferrule **516** and second ferrule **518** are examples of implementations for first ferrule **326** and second ferrule **328**, respectively, in **Figure 3**. Further, 15 sleeve **524** and clamshell device **526** are examples of implementations for sleeve **340** and clamshell device **346**, respectively, in **Figure 3**.

First ferrule **516**, second ferrule **518**, sleeve **524**, and clamshell device **526** may be comprised of nonmetallic 20 materials having a level of conductivity within a selected range. This range may be, for example, without limitation, between about 1×10^{-4} Siemens/centimeters and about 1×10^{-9} Siemens/centimeters. For example, first ferrule **516**, second ferrule **518**, sleeve **524**, and 25 clamshell device **526** may be comprised of composite materials. In particular, these components may be comprised of composite materials selected such that these components have a level of conductivity within the selected range.

30 First O-ring **520** and second O-ring **522** are examples of implementations for first O-ring **342** and second O-ring **344**, respectively, in **Figure 3**. In this illustrative example, each of first O-ring **520** and second O-ring **522** is comprised of a viscoelastic material, such as

viscoelastic material **332** in **Figure 3**. This viscoelastic material has a level of conductivity within, for example, without limitation, selected range **334** for conductivity **335** in **Figure 3**.

5 As depicted, coupling assembly **528** has been partially assembled. In particular, first ferrule **516** has been placed around first surface **508** of first tube **500** at first end **504** of first tube **500**. Second ferrule **518** has been placed around second surface **512** of second
10 tube **502** at second end **506** of second tube **502**. Further, first O-ring **520** has been placed around first ferrule **516**, and second O-ring **522** has been placed around second ferrule **518**. In this illustrative example, first O-ring **520** fits into a groove in first ferrule **516**. Second O-
15 ring **522** fits into a groove in second ferrule **518**.

Turning now to **Figure 6**, an illustration of a partially-assembled coupling assembly is depicted in accordance with an illustrative embodiment. In **Figure 6**, sleeve **524** has been placed around first O-ring **520** and
20 second O-ring **522** (not shown in this view) of coupling assembly **528** from **Figure 5**.

When sleeve **524** is placed around these two O-rings, these O-rings are compressed by sleeve **524**. Sleeve **524**, first O-ring **520**, and second O-ring **522** form seal **600**
25 when first O-ring **520** and second O-ring **522** are compressed by sleeve **524**. Seal **600** is an example of one implementation for seal **322** in **Figure 3**.

Seal **600** seals the interface (not shown) between first end **504** (not shown) of first tube **500** and second
30 end **506** (not shown) of second tube **502**. Further, seal **600** forms a conductive pathway between first tube **500** and second tube **502**. As depicted, coupling assembly **528** remains partially assembled without clamshell device **526**.

Turning now to **Figure 7**, an illustration of a fully-assembled coupling assembly is depicted in accordance with an illustrative embodiment. In **Figure 7**, coupling assembly **528** has been fully assembled. In particular,
5 clamshell device **526** has been placed around seal **600** and at least a portion of first ferrule **516** and at least a portion of second ferrule **518** to form the fully-assembled coupling assembly **528**.

With reference now to **Figure 8**, an illustration of a
10 cross-sectional view of a coupling assembly is depicted in accordance with an illustrative embodiment. In this illustrative example, a cross-sectional view of coupling assembly **528** in **Figure 7** taken along lines **8-8** is depicted.

15 As depicted, seal **600** forms conductive pathway **800** between first tube **500** and second tube **502**. In particular, conductive pathway **800** is formed at interface **802** between first tube **500** and second tube **502**. Interface **802** is between first end **504** of first tube **500**
20 and second end **506** of second tube **502**. First O-ring **520** fits within groove **806** of first ferrule **516**. Second O-ring **522** fits within groove **808** of second ferrule **518**.

In this illustrative example, conductive pathway **800** is formed through first surface **508** of first tube **500**,
25 first ferrule **516**, first O-ring **520**, sleeve **524**, second O-ring **522**, second ferrule **518**, and second surface **512** of second tube **502**. Conductive pathway **800** allows first tube **500**, second tube **502**, and coupling assembly **528** to function as a ground between the two tubes. At least one
30 of first tube **500**, second tube **502**, and coupling assembly **528** may be connected to ground such that conductive pathway **800** may be considered as grounding these two tubes.

With reference now to **Figure 9**, an illustration of a cross-sectional view of a different configuration for a coupling assembly is depicted in accordance with an illustrative embodiment. In **Figure 9**, coupling assembly 528 has a different configuration than the configuration for coupling assembly 528 in **Figure 8**.

As depicted in **Figure 9**, coupling assembly 528 includes third O-ring 900 and fourth O-ring 902 in addition to first O-ring 520 and second O-ring 522 in seal 600. Third O-ring 900 fits within groove 906 of first ferrule 516. Fourth O-ring 902 fits within groove 908 of second ferrule 518. Third O-ring 900 and fourth O-ring 902 could also be elastic or viscoelastic features that are not seals, but could be attached to clamshell device 526 to provide a conductive pathway as described below.

In this illustrative example, third O-ring 900 and fourth O-ring 902 allow seal 600 to form additional conductive pathway 904 between first tube 500 and second tube 502. In particular, additional conductive pathway 904 is formed through first surface 508 of first tube 500, first ferrule 516, third O-ring 900, clamshell device 526, fourth O-ring 902, second ferrule 518, and second surface 512 of second tube 502.

Turning now to **Figure 10**, an illustration of a cross-sectional view of another configuration for a coupling assembly is depicted in accordance with an illustrative embodiment. In this illustrative example, seal 600 in coupling assembly 528 comprises only one O-ring instead of two O-rings. As depicted, seal 600 uses O-ring 1000 instead of both first O-ring 520 and second O-ring 522 in **Figure 8**.

With this configuration for seal 600, conductive pathway 1002 is formed between first tube 500 and second

tube **502**. Conductive pathway **1002** is formed through first surface **508** of first tube **500**, first ferrule **516**, O-ring **1000**, second ferrule **518**, and second surface **512** of second tube **502**. As depicted, electrical currents may also flow from first ferrule **516** into sleeve **524**, and into second ferrule **518**.

Turning now to **Figure 11**, an illustration of a cross-sectional view of a different configuration for a coupling assembly is depicted in accordance with an illustrative embodiment. In this illustrative example, seal **600** in coupling assembly **528** comprises gasket **1100**. Further, seal **600** does not include sleeve **524** in this example.

As depicted, gasket **1100** has shape **1102**. Shape **1102** is configured such that first end **1104** of gasket **1100** fits into groove **806** in first ferrule **516**. Further, shape **1102** is configured such that second end **1106** of gasket **1100** fits into groove **808** in second ferrule **518**. Clamshell device **526** may be used to compress gasket **1100** such that gasket **1100** forms seal **600** to seal interface **802** when clamshell device **526** is placed around seal **600**.

In this illustrative example, gasket **1100** forms conductive pathway **1108** between first tube **500** and second tube **502**. Conductive pathway **1108** is formed through first surface **508** of first tube **500**, first ferrule **516**, gasket **1100**, second ferrule **518**, and second surface **512** of second tube **502**.

The illustrations of the different configurations for coupling assembly **528** in **Figures 5-11** are not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be optional.

With reference now to **Figure 12**, an illustration of a process for reducing an intensity of an electrical discharge within a fluid transport system in the form of a flowchart is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 12** may be implemented using fluid transport system **100** in **Figure 1**. In this illustrative example, fluid transport system **100** may be configured for use in aerospace vehicle **106** in **Figure 1**.

10 The process begins by operating the aerospace vehicle in which the fluid transport system has an electrical configuration comprising a set of electrical properties in which each electrical property in the set of electrical properties has a value within a selected
15 range (operation **1200**). The process may then reduce an intensity of an electrical discharge within the fluid transport system during operation of the aerospace vehicle to within selected tolerances by the electrical configuration of the fluid transport system (operation
20 **1202**), with the process terminating thereafter.

With reference now to **Figure 13**, an illustration of a process for reducing the energy that can be supplied to an electrical discharge within a fluid transport system in the form of a flowchart is depicted in accordance with
25 an illustrative embodiment. The process illustrated in **Figure 13** may be implemented using fluid transport system **100** in **Figure 1**. In particular, this process may be implemented using tube **201** in **Figure 2**. Tube **201** may be configured for use in aerospace vehicle **106** in **Figure 1**.

30 The process begins by operating the aerospace vehicle in which a transport member in the fluid transport system in the aerospace vehicle is comprised of a material selected such that the transport member has a resistance within a selected range (operation **1300**).

This selected range may include only electrical resistance levels above about 100 kilohms. Further, in some cases, this selected range may also only include electrical resistance levels below about 100 megohms.

5 The process may then reduce voltages and currents, induced in response to an electromagnetic event that occurs during operation of the aerospace vehicle, along the transport member to within selected tolerances by the resistance of the transport member (operation **1302**), with
10 the process terminating thereafter. Reducing these voltages and currents may reduce the energy that can be supplied to an electrical discharge within the fluid transport system. In this manner, this reduction of the
15 induced voltages and currents may reduce the intensity of an electrical discharge that may occur within the fluid transport system.

With reference now to **Figure 14**, an illustration of a process for dissipating electrostatic charge in the form of a flowchart is depicted in accordance with an
20 illustrative embodiment. The process illustrated in **Figure 14** may be implemented using a coupling assembly, such as, for example, coupling assembly **301** in **Figure 3**.

The process begins by operating the aerospace vehicle such that an electrostatic charge builds up on a
25 surface of at least one of a first transport member and a second transport member in the fluid transport system in the aerospace vehicle (operation **1400**). In one illustrative example, a first end of the first transport member may be coupled to a second end of the second
30 transport member using a connection in the form of a coupling assembly comprising a first fitting, a second fitting, and a seal. The first fitting may be associated with the first end of the first transport member. The

second fitting may be associated with the second end of the second transport member.

The seal is placed around the first fitting and the second fitting with the first end of the first transport member positioned next to the second end of the second transport member. The seal is configured to seal an interface between the first end of the first transport member and the second end of the second transport member when the first end and the second end are positioned next to each other.

In one illustrative example, the seal includes a first gasket, a second gasket, and a sleeve. The first gasket is placed around the first fitting, and the second gasket is placed around the second fitting. The sleeve is then placed around the first gasket and the second gasket. The sleeve compresses the first gasket and the second gasket to seal the interface between the first end of the first transport member and the second end of the second transport member. The coupling assembly between the first transport member and the second transport member may be configured to form a conductive pathway between the first transport member and the second transport member.

The process dissipates the electrostatic charge that builds up on the surface of the at least one of the first transport member and the second transport member during operation of the aerospace vehicle, using the conductive pathway between the first transport member and the second transport member (operation **1402**), with the process terminating thereafter. In this manner, the coupling assembly allows the first transport member and the second transport member to be grounded from one transport member to the other. A number of electrical currents may flow from one transport member to the other transport member

without interruption and without the level of the electrical currents changing outside of selected tolerances.

The flowchart and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative embodiment. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, function, and/or a portion of an operation or step.

In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

Illustrative embodiments of the disclosure may be described in the context of aircraft manufacturing and service method **1500** as shown in **Figure 15** and aircraft **1600** as shown in **Figure 16**. Turning first to **Figure 15**, an illustration of an aircraft manufacturing and service method is depicted in accordance with an illustrative embodiment. During pre-production, aircraft manufacturing and service method **1500** may include specification and design **1502** of aircraft **1600** in **Figure 16** and material procurement **1504**.

During production, component and subassembly manufacturing **1506** and system integration **1508** of aircraft **1600** takes place. Thereafter, aircraft **1600** may go through certification and delivery **1510** in order to be

placed in service **1512**. While in service **1512** by a customer, aircraft **1600** is scheduled for routine maintenance and service **1514**, which may include modification, reconfiguration, refurbishment, and other
5 maintenance or service.

Each of the processes of aircraft manufacturing and service method **1500** may be performed or carried out by a system integrator, a third party, and/or an operator. In these examples, the operator may be a customer. For the
10 purposes of this description, a system integrator may include, without limitation, any number of aircraft manufacturers and major-system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator
15 may be an airline, a leasing company, a military entity, a service organization, and so on.

With reference now to **Figure 16**, an illustration of an aircraft is depicted in which an illustrative embodiment may be implemented. In this example, aircraft
20 **1600** is produced by aircraft manufacturing and service method **1500** in **Figure 15** and may include airframe **1602** with systems **1604** and interior **1606**. Examples of systems **1604** include one or more of propulsion system **1608**, electrical system **1610**, hydraulic system **1612**,
25 environmental system **1614**, and fuel system **1616**. Fuel system **1616** and hydraulic system **1612** may be implemented using, for example, fluid transport system **100** in **Figure 1**.

Any number of other systems may be included in
30 systems **1604**, depending on the implementation. Although an aerospace example is shown, different illustrative embodiments may be applied to other industries, such as the automotive industry.

Apparatuses and methods embodied herein may be employed during at least one of the stages of aircraft manufacturing and service method **1500** in **Figure 15**. For example, tubes, such as plurality of tubes **111** in **Figure 1**, may be manufactured, installed, and/or reworked in aircraft **1600** during at least one of component and subassembly manufacturing **1506**, system integration **1508**, and maintenance and service **1514**.

In one illustrative example, components or subassemblies produced in component and subassembly manufacturing **1506** in **Figure 15** may be fabricated or manufactured in a manner similar to components or subassemblies produced while aircraft **1600** is in service **1512** in **Figure 15**. As yet another example, one or more apparatus embodiments, method embodiments, or a combination thereof may be utilized during production stages, such as component and subassembly manufacturing **1506** and system integration **1508** in **Figure 15**. One or more apparatus embodiments, method embodiments, or a combination thereof may be utilized while aircraft **1600** is in service **1512** and/or during maintenance and service **1514** in **Figure 15**. The use of a number of the different illustrative embodiments may substantially expedite the assembly of and/or reduce the cost of aircraft **1600**.

Thus, the different illustrative embodiments provide a method and apparatus for reducing an intensity of an electrical discharge that may occur within a fluid transport system. In one illustrative embodiment, a fluid transport system comprises a plurality of transport members and a number of connections connecting transport members in the plurality of transport members to each other. The plurality of transport members and the number of connections may be comprised of materials selected such that the intensity of an electrical discharge that

occurs within the fluid transport system may be reduced to within selected tolerances.

The description of the different illustrative embodiments has been presented for purposes of illustration and description and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different features as compared to other desirable embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A coupling assembly comprising:
 - a first fitting associated with a first end of a first transport member;
 - a second fitting associated with a second end of a second transport member;
 - a seal configured for placement around the first fitting and the second fitting when the first end of the first transport member is positioned relative to the second end of the second transport member, wherein the seal is further configured to seal an interface between the first end of the first transport member and the second end of the second transport member, and wherein the seal is comprised of a material configured such that the seal has a level of conductivity within a selected range and such that a conductive pathway is formed between the first transport member and the second transport member; and
 - a cover configured to cover the seal and hold the seal in place, the cover being disposed on the first fitting and the second fitting.
2. The coupling assembly of claim 1, wherein the selected range is between about 1×10^{-4} Siemens/centimeters and about 1×10^{-9} Siemens/centimeters.
3. The coupling assembly of claim 1 or 2, wherein the material is a viscoelastic material and wherein the seal comprises:
 - a first gasket configured to be received by the first fitting, wherein the first gasket comprises the viscoelastic material having the level of conductivity within the selected range; and

a second gasket configured to be received by the first fitting, wherein the second gasket comprises the viscoelastic material having the level of conductivity within the selected range.

4. The coupling assembly of claim 3, wherein the seal further comprises:

a sleeve configured for placement around the first gasket and the second gasket when the first end of the first transport member is positioned relative to the second end of the second transport member, wherein the sleeve compresses the first gasket and the second gasket to seal the interface between the first end of the first transport member and the second end of the second transport member.

5. The coupling assembly of claim 4, wherein the conductive pathway is formed such that an electrical current is allowed to flow in at least one of a first direction from the first transport member, through the first fitting, through the first gasket, through the sleeve, through the second gasket, and through the second fitting to the second transport member and in a second direction from the second transport member, through the second fitting, through the second gasket, through the sleeve, through the first gasket, and through the first fitting to the first transport member.

6. The coupling assembly of claim 4, wherein the first fitting, the second fitting, the first gasket, the second gasket, and the sleeve are comprised of nonmetallic materials having the level of conductivity within the selected range.

7. The coupling assembly of claim 3, wherein the first gasket is a first O-ring and the second gasket is a second O-ring.

8. The coupling assembly of any one of claims 1 to 8, wherein an electrical current induced in at least one of the first transport member and the second transport member by electrostatic charge that builds up on the at least one of the first transport member and the second transport member is conducted along the conductive pathway.

9. The coupling assembly of claim 1 or 2, wherein the seal comprises:

a gasket comprising a viscoelastic material having the level of conductivity within the selected range, wherein the conductive pathway is formed between the first transport member and the second transport member through the gasket, and wherein compression of the gasket seals the interface between the first transport member and the second transport member.

10. The coupling assembly of any one of claims 1 to 9, wherein the cover is a clamshell device.

11. The coupling assembly of any one of claims 1 to 10, wherein the cover comprises a nonmetallic material having the level of conductivity within the selected range and is configured to form a portion of the conductive pathway between the first transport member and the second transport member.

12. The coupling assembly of claim 1 or 2, wherein the material is a viscoelastic material that comprises a

conductive elastomer having the level of conductivity within the selected range.

13. The coupling assembly of any one of claims 1 to 12, wherein the seal is configured to seal the interface between the first end of the first transport member and the second end of the second transport member by reducing a possibility of material flowing at least one of into and out of a channel formed by the first transport member and the second transport member when the first transport member and the second transport member are coupled to each other using the coupling assembly.

14. The coupling assembly of any one of claims 1 to 13, wherein the first transport member and the second transport member are fuel transport members in a fuel system for an aerospace vehicle in which the fuel system has an overall level of conductivity within the selected range.

15. A fuel system comprising:
a first transport member;
a second transport member; and
a coupling assembly configured to couple a first end of the first transport member to a second end of the second transport member, wherein the coupling assembly comprises:

a first fitting associated with the first end of the first transport member and having a level of conductivity within a selected range;

a second fitting associated with the second end of the second transport member and having the level of conductivity within the selected range;

a first gasket configured for placement around the first fitting, wherein the first gasket comprises a viscoelastic material having the level of conductivity within the selected range;

a second gasket configured for placement around the second fitting, wherein the second gasket comprises the viscoelastic material having the level of conductivity within the selected range;

a sleeve configured for placement around the first gasket and the second gasket and having the level of conductivity within the selected range in which the sleeve is configured to compress the first gasket and the second gasket to form a seal that seals an interface between the first end of the first transport member and the second end of the second transport member when the first end of the first transport member is positioned relative to the second end of the second transport member, wherein the seal forms a conductive pathway between the first transport member and the second transport member through the first fitting, the seal, and the second fitting, wherein the first gasket is a first O-ring, the second gasket is a second O-ring, and the viscoelastic material is a conductive elastomer; and

a cover configured to cover the first gasket, the second gasket, the sleeve, at least a portion of the first fitting, and at least a portion of the second fitting, the cover being disposed on the first fitting and the second fitting.

16. A method for conducting an electrical current between a first transport member and a second transport member in a fuel system in an aerospace vehicle, the method comprising:

operating the aerospace vehicle such that an electrical charge builds up around a surface of at least one of the first transport member and the second transport member in the fuel system in the aerospace vehicle, wherein a first end of the first transport member is coupled to a second end of the second transport member using a first fitting associated with the first end of the first transport member, a second fitting associated with the second end of the second transport member, a seal, and a cover, wherein the seal is configured to seal an interface between the first end of the first transport member and the second end of the second transport member when the first end of the first transport member is positioned relative to the second end of the second transport member, wherein the seal is comprised of a material configured such that the seal has a level of conductivity within a selected range and such that a conductive pathway is formed between the first transport member and the second transport member, and wherein the cover is configured to cover the seal and hold the seal in place, the cover being disposed on the first fitting and the second fitting; and

dissipating electrostatic charge that builds up on at least one of the first transport member and the second transport member during operation of the aerospace vehicle using the conductive pathway formed by the seal between the first transport member and the second transport member.

17. The method of claim 16, wherein dissipating the electrostatic charge comprises:

dissipating the electrostatic charge that builds up on at least one of the first transport member and the second transport member using the conductive pathway

formed by the seal, wherein the selected range for the level of conductivity for the seal is between about 1×10^{-4} Siemens/centimeters and about 1×10^{-9} Siemens/centimeters.

18. A coupling assembly comprising:

- a first ferrule attached to a first end of a first transport member, the first ferrule and the first transport member both having a level of conductivity within a selected range;

- a second ferrule attached to a second end of a second transport member, the second ferrule and the second transport member both having the level of conductivity within the selected range;

- a first gasket received by the first ferrule, wherein the first gasket comprises a viscoelastic material having the level of conductivity within the selected range;

- a second gasket received by the second ferrule, wherein the second gasket comprises the viscoelastic material having the level of conductivity within the selected range;

- a clamshell device disposed over the first ferrule and the second ferrule, wherein the first gasket and the second gasket are disposed within the clamshell device, and wherein the clamshell device is non-conductive relative to the level of conductivity;

- a sleeve connected to an inside surface of the clamshell device, wherein the sleeve is in contact with the first gasket and the second gasket, wherein the sleeve has the level of conductivity within the selected range, and wherein sidewalls of the clamshell device are not in contact with any of the sleeve, the first gasket, and the second gasket, wherein a conductive pathway is

formed between the first transport member and the second transport member via the first ferrule, the first gasket, the sleeve, the second gasket, and the second ferrule; and

a hinge connected to the clamshell device and configured to allow opening and closing of the clamshell device onto the first ferrule, the second ferrule, the first gasket, and the second gasket, and wherein when closed the clamshell device forms a seal between the first transport member and the second transport member.

19. The coupling assembly of claim 18, wherein the selected range is between about 1×10^{-4} Siemens/centimeters and about 1×10^{-9} Siemens/centimeters.

20. The coupling assembly of claim 18 or 19, wherein the first fitting, the second fitting, the first gasket, the second gasket, and the sleeve are comprised of nonmetallic materials having the level of conductivity within the selected range.

21. The coupling assembly of any one of claims 18 to 20, wherein the first gasket is a first O-ring and the second gasket is a second O-ring.

22. The coupling assembly of any one of claims 18 to 21, wherein an electrical current induced in at least one of the first transport member and the second transport member by electrostatic charge that builds up on the at least one of the first transport member and the second transport member is conducted along the conductive pathway.

23. The coupling assembly of any one of claims 18 to 22, wherein the viscoelastic material comprises a conductive elastomer.

24. The coupling assembly of any one of claims 18 to 23, wherein the seal seals an interface between the first end of the first transport member and the second end of the second transport member by reducing a possibility of material flowing at least one of into and out of a channel formed by the first transport member and the second transport member.

25. The coupling assembly of any one of claims 18 to 24, wherein the first transport member and the second transport member are fuel transport members in a fuel system for an aerospace vehicle in which the fuel system has an overall level of conductivity within the selected range.

26. A coupling assembly comprising:

- a first ferrule attached to a first end of a first transport member, the first ferrule and the first transport member both having a level of conductivity within a selected range;

- a second ferrule attached to a second end of a second transport member, the second ferrule and the second transport member both having the level of conductivity within the selected range;

- a first gasket received by the first ferrule, wherein the first gasket comprises a viscoelastic material having the level of conductivity within the selected range;

- a second gasket received by the first ferrule, wherein the second gasket comprises the viscoelastic

material having the level of conductivity within the selected range;

a third gasket received by the second ferrule, wherein the third gasket comprises a viscoelastic material having the level of conductivity within the selected range;

a fourth gasket received by the second ferrule, wherein the fourth gasket comprises the viscoelastic material having the level of conductivity within the selected range;

a clamshell device disposed over the first ferrule and the second ferrule, wherein the first gasket and the third gasket are disposed within the clamshell device, wherein the second gasket and the fourth gasket are disposed under the clamshell device, and wherein the clamshell device comprises a material having the level of conductivity; and

a sleeve connected to an inside surface of the clamshell device, wherein the sleeve is in contact with the first gasket and the third gasket, wherein the sleeve has the level of conductivity within the selected range, and wherein sidewalls of the clamshell device are not in contact with any of the sleeve, the first gasket, and the second gasket, wherein the sidewalls are in contact with the second gasket and the fourth gasket, wherein a first conductive pathway is formed between the first transport member and the second transport member via the first ferrule, the first gasket, the sleeve, the second gasket, and the second ferrule, and wherein a second conductive pathway is formed between the first transport member and the second transport member via the first ferrule, the second gasket, the clamshell device, the fourth gasket, the second ferrule, and the second transport member.

27. The coupling assembly of claim 26, wherein the selected range is between about 1×10^{-4} Siemens/centimeters and about 1×10^{-9} Siemens/centimeters.

28. The coupling assembly of claim 26 or 27, wherein the first fitting, the second fitting, the first gasket, the second gasket, the third gasket, the fourth gasket, and the sleeve are comprised of nonmetallic materials having the level of conductivity within the selected range.

29. The coupling assembly of any one of claims 26 to 28, wherein the first gasket is a first O-ring, the second gasket is a second O-ring, third gasket is a third O-ring and the fourth gasket is a fourth O-ring.

30. The coupling assembly of any one of claims 26 to 29, wherein an electrical current induced in at least one of the first transport member and the second transport member by electrostatic charge that builds up on the at least one of the first transport member and the second transport member is conducted along the conductive pathway.

31. The coupling assembly of any one of claims 26 to 30, wherein the viscoelastic material comprises a conductive elastomer.

32. The coupling assembly of any one of claims 26 to 31, wherein when closed the clamshell device forms a seal between the first transport member and the second transport member, the seal seals an interface between the first end of the first transport member and the second end of the second transport member by reducing a possibility of material flowing at least one of into and

out of a channel formed by the first transport member and the second transport member.

33. The coupling assembly of any one of claims 26 to 32, wherein the first transport member and the second transport member are fuel transport members in a fuel system for an aerospace vehicle in which the fuel system has an overall level of conductivity within the selected range.

34. The coupling assembly of any one of claims 26 to 33 further comprising:

a hinge connected to the clamshell device and configured to allow opening and closing of the clamshell device onto the first ferrule, the second ferrule, the first gasket, the second gasket, the third gasket, and the fourth gasket, and wherein when closed the clamshell device forms a seal between the first transport member and the second transport member.

35. A fluid transport system having an electrical configuration configured to reduce an intensity of an electrical discharge that occurs within the fluid transport system, the fluid transport system comprising:

a plurality of tubes, wherein a tube in the plurality of tubes is comprised of a composite material selected such that the tube has a resistance within a selected range configured to reduce voltages and currents, induced in response to an electromagnetic event, along the tube to within selected tolerances; and

a number of coupling assemblies configured to couple tubes in the plurality of tubes to each other, wherein a coupling assembly in the number of coupling assemblies comprises:

a first fitting associated with a first end of a first tube in the plurality of tubes;

a second fitting associated with a second end of a second tube in the plurality of tubes; and

a seal configured for placement around the first fitting and the second fitting when the first end of the first tube is positioned relative to the second end of the second tube, wherein the seal is configured to seal an interface between the first end of the first tube and the second end of the second tube and provide a conductive pathway between the first tube and the second tube to allow electrostatic charge that builds up on at least one of the first tube and the second tube to be dissipated, and wherein the first tube, the second tube, and the coupling assembly form the conductive pathway grounding the first tube and the second tube without directly grounding the coupling assembly to a structure.

36. The fluid transport system of claim 35, wherein reducing the voltages and currents, induced in response to the electromagnetic event, along the tube reduces energy available to the electrical discharge.

37. The fluid transport system of claim 35, wherein dissipating the electrostatic charge that builds up on the at least one of the first tube and the second tube reduces energy available to the electrical discharge.

38. An apparatus comprising:

a first transport member configured for use in a fluid transport system, wherein the first transport member is comprised of a material configured to reduce voltages and currents, induced in response to an electromagnetic event, along the first transport member;

a second transport member configured for use in the fluid transport system, wherein the second transport member is comprised of the material configured to reduce voltages and currents, induced in response to the electromagnetic event, along the second transport member, and wherein the second transport member is separated from the first transport member by an interface;

a coupling assembly connecting the first transport member and the second transport member, the coupling assembly including a first ferrule that connects to the first transport member and a second ferrule that connects to the second transport member, the first ferrule including a first groove in which is a first O-ring and a second groove in which is a second O-ring, the second ferrule including a third groove in which is a third O-ring and a fourth groove in which is a fourth O-ring, the coupling assembly further including a clamshell device connected to a sleeve, wherein when the coupling assembly is in a closed position: the first O-ring creates a first seal and a first conductive pathway between the first ferrule and the clamshell device, the second O-ring creates a second seal and a second conductive pathway between the first ferrule and the sleeve, the third O-ring creates a third seal and a third conductive pathway between the second ferrule and the sleeve, and the fourth O-ring creates a fourth seal and a fourth conductive pathway between the second ferrule and the clamshell device.

39. The apparatus of claim 38, wherein the transport member is one in a plurality of transport members configured for use in the fluid transport system.

40. The apparatus of claim 38 or 39, wherein the material for the transport member is selected such that the transport member has an electrical resistance within a selected range that includes per unit length electrical resistance levels at least one of above about 100 kilohms per meter and below about 100 megohms per meter.

41. The apparatus of claim 40, wherein the transport member is a tube and wherein the electrical resistance of the tube varies with respect to an axis through the tube.

42. The apparatus of claim 41, wherein the electrical resistance of the transport member varies by less than a selected percentage over time.

43. The apparatus of claim 42, wherein the selected percentage is between about 20 percent and about 40 percent.

44. The apparatus of any one of claims 38 to 40, wherein the transport member is a tube.

45. The apparatus of any one of claims 38 to 44, wherein the transport member is a fuel transport member located within a fuel tank in the fluid transport system.

46. The apparatus of any one of claims 38 to 45, wherein the transport member is a first transport member and further comprising:

a second transport member configured for use in the fluid transport system, wherein the second transport member is comprised of the material configured to reduce voltages and currents, induced in response to the electromagnetic event, along the second transport member.

47. The apparatus of claim 46 further comprising:
a coupling assembly configured to couple the first transport member to the second transport member in the fluid transport system.
48. The apparatus of any one of claims 38 to 40, wherein the material is a composite material.
49. The apparatus of claim 48, wherein the composite material is a non-metallic composite material.
50. The apparatus of claim 48 or 49, wherein the composite material is selected such that the transport member is configured to at least one of allow static dissipation and prevent a build-up of electrostatic charge.
51. The apparatus of any one of claims 48 to 50, wherein the fluid transport system is a fuel system and the transport member is a tube having a channel through which fuel is moved.
52. The apparatus of any one of claims 38 to 51, wherein the fluid transport system is configured for use in a platform selected from one of an aerospace vehicle, a ground vehicle, and a water vehicle.

1/13






FIG. 1

2/13








FIG. 4

5/13




FIG. 5





FIG. 7



8/13




FIG. 8

9/13




FIG. 9

10/13




FIG. 10

11/13




FIG. 11

12/13




FIG. 12




FIG. 13

13/13

FIG. 14




FIG. 15




FIG. 16

