



US011564603B2

(12) **United States Patent**
Pusey et al.

(10) **Patent No.:** **US 11,564,603 B2**

(45) **Date of Patent:** **Jan. 31, 2023**

(54) **LATCH MECHANISM FOR PREVENTING LANCET OSCILLATION IN A LANCING DEVICE**

5/150022; A61B 5/150412; A61B 5/15113; A61B 5/15194; A61B 5/15117; A61B 5/1519; A61B 5/150183; A61B 5/1513;

(71) Applicant: **FACET TECHNOLOGIES, LLC**,
Atlanta, GA (US)

(Continued)

(72) Inventors: **Lauren R. Pusey**, Woodstock, GA (US); **Greg Lamps**, Smyrna, GA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **FACET TECHNOLOGIES, LLC**,
Atlanta, GA (US)

4,203,446 A 5/1980 Hofert et al.
4,841,985 A 6/1989 Wanamaker

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/741,517**

EP 0898936 A2 3/1999
EP 1074219 A2 2/2001

(Continued)

(22) Filed: **May 11, 2022**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2022/0265182 A1 Aug. 25, 2022

International Search Report & Written Opinion for PCT/US2012/060847; dated Jan. 23, 2013; 11 pgs.

Related U.S. Application Data

(63) Continuation of application No. 17/034,888, filed on Sep. 28, 2020, now abandoned, which is a (Continued)

Primary Examiner — Katherine M Shi

(74) *Attorney, Agent, or Firm* — Gardner Groff & Greenwald, PC

(51) **Int. Cl.**
A61B 5/151 (2006.01)
A61B 5/15 (2006.01)


(57) **ABSTRACT**

A lancing device including a latch that pivots between a non-blocking position allowing a lancet carrier and a lancet to advance and retract through a first forward and reverse lancing stroke and a blocking position preventing further/excess/secondary oscillation of the lancet carrier and lancet. The pivotal latch can pivot about an axis perpendicular (e.g., for an L-shaped latch) or parallel/coaxial (e.g., for a sleeve latch) to the advancement and retraction motion of the lancet carrier and lancet.

(52) **U.S. Cl.**
CPC **A61B 5/15194** (2013.01); **A61B 5/1513** (2013.01); **A61B 5/1519** (2013.01); **A61B 5/150022** (2013.01); **A61B 5/150106** (2013.01); **A61B 5/15113** (2013.01); **A61B 5/15117** (2013.01); **A61B 5/150183** (2013.01); (Continued)

(58) **Field of Classification Search**
CPC A61M 2005/208; A61M 5/2033; A61B

22 Claims, 20 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 15/824,443, filed on Nov. 28, 2017, now Pat. No. 10,820,849, which is a continuation of application No. 13/655,168, filed on Oct. 18, 2012, now Pat. No. 9,844,331.
- (60) Provisional application No. 61/570,894, filed on Dec. 15, 2011.
- (52) **U.S. Cl.**
CPC .. *A61B 5/150412* (2013.01); *A61B 5/150519* (2013.01); *A61B 5/15144* (2013.01); *A61B 5/15146* (2013.01); *A61B 5/150946* (2013.01)
- (58) **Field of Classification Search**
CPC *A61B 5/150503*; *A61B 5/150519*; *A61B 5/15144*; *A61B 5/15186*; *A61B 5/1411*
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

4,895,147	A	1/1990	Bodicky et al.	7,288,102	B2	10/2007	Griffin et al.
4,924,879	A	5/1990	O'Brien	7,311,718	B2	12/2007	Schrage
4,976,724	A	12/1990	Nieto et al.	D560,805	S	1/2008	Young et al.
5,196,025	A	3/1993	Ranalletta et al.	7,322,998	B2	1/2008	Kuhr et al.
D342,573	S	12/1993	Cerola	D569,975	S	5/2008	Wilkinson
5,282,822	A	2/1994	Macors et al.	7,438,694	B2	10/2008	Boozar et al.
5,318,584	A	6/1994	Lange et al.	D581,533	S	11/2008	Ruf et al.
5,423,847	A	6/1995	Strong et al.	D586,465	S	2/2009	Faulkner et al.
5,464,418	A	11/1995	Schrage	D586,916	S	2/2009	Faulkner et al.
5,518,004	A	5/1996	Schrage	7,494,498	B2	2/2009	Lipoma et al.
5,554,166	A	9/1996	Lange et al.	7,510,564	B2	3/2009	Mace
5,613,978	A	3/1997	Harding	7,621,931	B2	11/2009	Shraga
D379,516	S	5/1997	Rutter	7,651,512	B2	1/2010	Chelak et al.
5,730,753	A	3/1998	Morita	7,655,019	B2	2/2010	LeVaughn et al.
RE35,803	E	5/1998	Lange et al.	D612,051	S	3/2010	Ruf
5,916,230	A	6/1999	Brenneman et al.	7,674,232	B2	3/2010	Boecker et al.
5,951,493	A	9/1999	Douglas et al.	7,678,126	B2	3/2010	Schrage
5,954,738	A	9/1999	LeVaughn et al.	7,678,127	B2	3/2010	Trissel et al.
5,984,940	A	11/1999	Davis et al.	7,682,318	B2	3/2010	Alden et al.
6,022,366	A	2/2000	Schrage	7,780,610	B2	8/2010	Sonoda et al.
6,045,567	A	4/2000	Taylor et al.	7,833,170	B2	11/2010	Matsumoto et al.
D428,150	S	7/2000	Ruf et al.	7,842,060	B2	11/2010	List
6,156,050	A	12/2000	Davis et al.	7,867,244	B2	1/2011	Lathrop et al.
6,156,051	A	12/2000	Schrage	7,905,898	B2	3/2011	Schrage
6,168,606	B1	1/2001	Levin et al.	7,909,842	B2	3/2011	Flynn et al.
6,197,040	B1	3/2001	LeVaughn et al.	7,914,547	B2	3/2011	Curry et al.
D444,557	S	7/2001	LeVaughn et al.	7,947,057	B2	5/2011	Schrage
D447,566	S	9/2001	LeVaughn et al.	7,955,348	B2	6/2011	Trissel et al.
6,283,982	B1	9/2001	LeVaughn et al.	7,998,161	B2	8/2011	Shi
6,322,575	B1	11/2001	Schrage	8,016,847	B2	9/2011	Koike et al.
6,332,871	B1	12/2001	Douglas et al.	8,016,848	B2	9/2011	Lathrop et al.
6,409,740	B1	6/2002	Kuhr et al.	8,043,318	B2	10/2011	Schrage
6,419,661	B1	7/2002	Kuhr et al.	8,048,097	B2	11/2011	Schrage
6,451,040	B1	9/2002	Purcell	8,048,098	B2	11/2011	Creaven
6,514,270	B1	2/2003	Schrage	8,062,268	B2	11/2011	Ratjen
6,530,937	B1	3/2003	Schrage	8,105,347	B2	1/2012	Schrage
6,558,402	B1	5/2003	Chelak et al.	8,142,466	B2	3/2012	Lipoma et al.
6,575,939	B1	6/2003	Brunel	8,152,740	B2	4/2012	Thoes et al.
6,602,268	B2	8/2003	Kuhr et al.	8,211,036	B2	7/2012	Schrage
6,645,219	B2	11/2003	Roe	8,257,380	B2	9/2012	Schrage
6,749,618	B2	6/2004	LeVaughn et al.	8,267,950	B2	9/2012	Robbins et al.
D493,532	S	7/2004	LeVaughn et al.	8,357,107	B2	1/2013	Draudt et al.
6,811,557	B2	11/2004	Schrage	8,366,729	B2	2/2013	LeVaughn et al.
6,858,015	B2	2/2005	List	8,388,639	B2	3/2013	Nicholls et al.
6,887,253	B2	5/2005	Schrage	8,398,664	B2	3/2013	Lamps et al.
6,929,650	B2	8/2005	Fukuzawa et al.	8,469,986	B2	6/2013	Schrage
6,986,777	B2	1/2006	Kim	8,709,032	B2	4/2014	Schrage
7,105,006	B2	9/2006	Shraga	8,932,313	B2	1/2015	Weiss et al.
D530,424	S	10/2006	Manser et al.	8,971,982	B2	3/2015	Schrage
7,150,755	B2	12/2006	LeVaughn et al.	9,055,899	B2	6/2015	Lamps et al.
7,175,641	B1	2/2007	Schrage	9,095,293	B2	8/2015	Lamps et al.
7,223,276	B2	5/2007	List et al.	9,282,918	B2	3/2016	Schrage
7,273,484	B2	9/2007	Thoes et al.	9,289,161	B2	3/2016	Schrage
				2003/0212344	A1	11/2003	Yuzhakov et al.
				2004/0039302	A1	2/2004	Kim
				2004/0162573	A1	8/2004	Kheiri
				2004/0249405	A1	12/2004	Watanabe et al.
				2004/0254599	A1	12/2004	Lipoma et al.
				2005/0085840	A1	4/2005	Yi et al.
				2005/0125017	A1	6/2005	Kudrna et al.
				2005/0125019	A1	6/2005	Kudrna et al.
				2005/0143771	A1	6/2005	Stout et al.
				2005/0159768	A1	7/2005	Boehm et al.
				2005/0234492	A1	10/2005	Tsai et al.
				2005/0234495	A1	10/2005	Schrage
				2006/0100655	A1	5/2006	Leong et al.
				2006/0100656	A1	5/2006	Olson et al.
				2006/0224172	A1	10/2006	LeVaughn et al.
				2006/0247671	A1	11/2006	LeVaughn
				2006/0264996	A1	11/2006	LeVaughn et al.
				2007/0055298	A1	3/2007	Uehata et al.
				2007/0083222	A1	4/2007	Schrage
				2007/0100364	A1	5/2007	Sansom
				2007/0173874	A1	7/2007	Uschold et al.
				2007/0173875	A1	7/2007	Uschold
				2008/0082117	A1	4/2008	Ruf
				2008/0146966	A1	6/2008	LeVaughn et al.
				2008/0147108	A1	6/2008	Kennedy
				2008/0255598	A1	10/2008	LeVaughn et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0030441 A1 1/2009 Kudrna et al.
2010/0160942 A1* 6/2010 Lamps A61B 5/150022
606/182
2010/0160943 A1* 6/2010 Lamps A61B 5/15117
606/182
2010/0234870 A1 9/2010 Ruf
2013/0158586 A1 6/2013 Pusey et al.

FOREIGN PATENT DOCUMENTS

EP 1163879 A2 12/2001
EP 1779781 A2 5/2007
WO 9704707 A1 2/1997
WO 0128423 A2 4/2001
WO 2006031535 A2 3/2006
WO 2007130830 A2 11/2007
WO 2007146913 A2 12/2007
WO 2010080584 A1 7/2010
WO 2010080585 A1 7/2010
WO 2011050142 A1 4/2011

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 2A




FIG. 2B







FIG. 2C








FIG. 3D




FIG. 3E




FIG. 4






FIG. 5






FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A





FIG. 8B






FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11A




FIG. 11B




FIG. 11C

**LATCH MECHANISM FOR PREVENTING
LANCET OSCILLATION IN A LANCING
DEVICE**

**CROSS-REFERENCE TO RELATED
APPLICATION**

This application is a continuation of U.S. Non-Provisional patent application Ser. No. 17/034,888 filed Sep. 28, 2020, which is a continuation of U.S. Non-Provisional patent application Ser. No. 15/824,443 filed Nov. 28, 2017, now U.S. Pat. No. 10,820,849 issued Nov. 3, 2020, which is a continuation of U.S. Non-Provisional patent application Ser. No. 13/655,168 filed Oct. 18, 2012, now U.S. Pat. No. 9,844,331 issued Dec. 19, 2017, which claims the priority benefit of U.S. Provisional Patent Application Ser. No. 61/570,894 filed Dec. 15, 2011, the entireties of which are hereby incorporated herein by reference for all purposes.

TECHNICAL FIELD

The present invention relates generally to the field of medical devices, and more particularly to a lancing device for blood sampling and testing with an incorporated mechanism for preventing excess lancet oscillation.

BACKGROUND

Lancing devices are utilized for penetrating the skin of a human or animal subject at a lancing site to obtain a sample of blood or other body fluid for medical testing, as in blood-typing or blood-glucose testing. Known lancing devices commonly include a housing containing a drive mechanism with a drive spring, a charging mechanism for energizing the spring, and a release mechanism for releasing the drive mechanism to propel a lancet through a lancing stroke. A lancet is propelled by the drive mechanism from a retracted position within the housing to an extended position where a sharp tip portion of the lancet projects from the housing to prick the subject's skin at a desired lancing site. U.S. Patent App. Pub. No. US2011/0196261 and U.S. Patent App. Pub. No. US2010/0160942 show example lancing devices and are incorporated herein by reference.

Many known lancing devices include two springs, a drive spring to drive the lancet along an advancing portion of the lancet stroke toward the lancing site, and a return spring to retract the lancet along a return portion of the lancet stroke back into the housing. Achieving the correct balance of spring forces between the two springs presents design challenges, and incorrect balance can reduce the lancet speed, potentially increasing pain sensation. It has also been discovered that some drive mechanisms can cause or permit the lancet to continue to oscillate after the lancing stroke (one forward and reverse cycle) is completed, possibly pricking the subject's skin unintentionally a second time or more and resulting in a greater sensation of pain for the patient. Friction between device components and/or energy dissipation from the lancing of the skin serves to dampen lancet oscillation in previously known lancing devices to some extent, but not to an entirely effective extent.

Thus it can be seen that needs exist for the reduction or elimination of excess lancet oscillation in a lancing device. It is to the provision of a system and method for preventing excess lancet oscillation in a lancing device meeting these and other needs that the present invention is primarily directed.

SUMMARY

The present invention relates to systems and methods for preventing excess lancet oscillation in lancing devices. In example embodiments, a latch mechanism allows operation of the drive mechanism to carry out the lancing stroke unimpeded, but after a single penetration of the skin at the lancing site the latch is engaged to reduce or prevent further oscillation of the lancet, to thereby prevent the lancet from contacting the skin a second time. In multi-use designs, the latch mechanism optionally also holds the drive mechanism during ejection of the lancet from the drive mechanism.

In one aspect, the present invention relates to a lancing device including a drive mechanism for advancing and retracting a lancet through a lancing stroke, and a latch mechanism for allowing advancement and retraction of the lancet once (through the lancing stroke) but limiting further/excess/secondary oscillation thereof. In one embodiment, the latch mechanism includes a pivotal L-shaped latch member having a leg, a foot extending generally perpendicular to and transversely offset from the leg, and a resilient finger extending generally parallel to and transversely offset from the leg and operably engaged and deflected by a ramp. In another embodiment, the latch mechanism includes a pivotal (rotary) tube/sleeve-shaped latch member with an angled guide surface and with an axially extending tooth having a lancet carrier stop projecting transversely therefrom for operable engagement by a resilient finger.

In another aspect, the invention relates to a method of preventing secondary oscillation of a lancet in a lancing device. The method comprises providing a lancing device with a pivotal latch mechanism configured and positioned to permit a first oscillation of the lancet when the latch mechanism is in a non-blocking position, and moving the latch mechanism to a blocking position where subsequent/excess oscillations are prevented.

These and other aspects, features, and advantages of the invention will be understood with reference to the drawing figures and detailed description herein, and will be realized by means of the various elements and combinations particularly pointed out in the appended claims. It is to be understood that both the foregoing general description and the following brief description of the drawings and detailed description of example embodiments are exemplary and explanatory of preferred embodiments of the invention, and are not restrictive of the invention, as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a side view of a lancing device according to a first example embodiment of the present invention, with a portion of the housing removed to show internal components of the device, showing a latch mechanism for preventing excess lancet oscillation, with the latch in a blocking position.

FIG. 1B shows the lancing device of FIG. 1A with the drive mechanism being charged and the latch being pivoted toward an intermediate non-blocking position.

FIG. 1C shows the lancing device of FIG. 1B with the latch in the intermediate non-blocking position.

FIG. 1D shows the lancing device of FIG. 1C with the lancet traveling along a forward portion of its lancing stroke and the latch pivoted to a press non-blocking position.

FIG. 1E shows the lancing device of FIG. 1D with the lancet traveling along a rearward return portion of its lancing stroke and the latch retained in the press non-blocking position.

3

FIG. 1F shows the lancing device of FIG. 1E with the lancet traveling farther along its rearward return portion of its lancing stroke and the latch pivoted back to the blocking position of FIG. 1A.

FIG. 2A is a front perspective view of the latch member of the latch mechanism of FIGS. 1A-1F.

FIG. 2B is a top view of the latch member of the latch mechanism of FIGS. 1A-1F.

FIG. 2C is a rear perspective view of the latch member of the latch mechanism of FIGS. 1A-1F.

FIG. 3A shows the lancing device of FIG. 1A with the housing entirely removed to show details of internal components of the latch, charge, and drive mechanisms, with the latch mechanism in the blocking position of FIG. 1A.

FIG. 3B is a top view of a portion of the lancing device of FIG. 1A with a top portion of the housing removed to show the internal components, with the latch mechanism in the blocking position of FIG. 1A.

FIG. 3C is a front view of the lancing device of FIG. 1A with a front portion of the housing removed to show the internal components, with the latch mechanism in the blocking position of FIG. 1A.

FIG. 3D is a front perspective view of the latch mechanism in the blocking position of FIG. 1A, showing details of a detent ramp of the latch mechanism.

FIG. 3E is a top view of the latch mechanism of FIG. 3D, showing details of the detent ramp of the latch mechanism.

FIG. 4 is a rear perspective view of the latch member and the detent ramp with the latch mechanism in the position of FIG. 1B.

FIG. 5 is a top perspective view of the latch member and the detent ramp with the latch mechanism in the press non-blocking position of FIGS. 1D and 1E.

FIG. 6A is perspective view of a portion of a latch mechanism according to an alternative embodiment to that shown in FIGS. 1A-5, with the latch mechanism in the blocking position.

FIG. 6B shows the latch mechanism portion of FIG. 6A with the latch mechanism in the intermediate non-blocking position.

FIG. 7A is a front perspective view of a latch member of a latch mechanism of a lancing device according to a second example embodiment of the present invention.

FIG. 7B is a rear perspective view of the latch member of FIG. 7A, showing a torsion spring coupled thereto.

FIG. 7C is a top view of the latch member of FIG. 7A.

FIG. 8A is a rear perspective view of a spring finger of the latch mechanism of FIGS. 7A-7C.

FIG. 8B is a front perspective view of the spring finger of FIG. 8A.

FIG. 9A is a perspective view of the lancing device with the latch mechanism of FIGS. 7A-8B, with portions removed to show internal components thereof, showing the latch in a blocking position.

FIG. 9B shows the lancing device of FIG. 9A with the drive mechanism being charged and the latch pivoted to an intermediate non-blocking position.

FIG. 9C shows the lancing device of FIG. 9B with the lancet traveling along a forward portion of its lancing stroke and the latch pivoted to a press non-blocking position.

FIG. 10A is a side view of the lancing device in the blocking position of FIG. 9A.

FIG. 10B is a side view of the lancing device in the intermediate non-blocking position of FIG. 9B.

FIG. 10C is a side view of the lancing device in the press non-blocking position of FIG. 9C.

4

FIG. 11A is a cross-sectional view of the lancing device taken at line 11A-11A of FIG. 10A.

FIG. 11B is a cross-sectional view of the lancing device taken at line 11B-11B of FIG. 10B.

FIG. 11C is a cross-sectional view of the lancing device taken at line 11C-11C of FIG. 10C.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

The present invention may be understood more readily by reference to the following detailed description of the invention taken in connection with the accompanying drawing figures, which form a part of this disclosure. It is to be understood that this invention is not limited to the specific devices, methods, conditions or parameters described and/or shown herein, and that the terminology used herein is for the purpose of describing particular embodiments by way of example only and is not intended to be limiting of the claimed invention. Any and all patents and other publications identified in this specification are incorporated by reference as though fully set forth herein.

Also, as used in the specification including the appended claims, the singular forms “a,” “an,” and “the” include the plural, and reference to a particular numerical value includes at least that particular value, unless the context clearly dictates otherwise. Ranges may be expressed herein as from “about” or “approximately” one particular value and/or to “about” or “approximately” another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another embodiment.

With reference now to the drawing figures, wherein like reference numbers represent corresponding parts throughout the several views, FIGS. 1A-5 show a lancing device 10 according to a first example embodiment of the invention. The lancing device 10 generally includes a drive mechanism 15, a charging mechanism 30, a release mechanism 40, and a housing 12 at least partially enclosing these components.

The drive mechanism 15 includes a drive spring 14 and a return spring 16 for driving a lancet carrier 18 through a lancing stroke. In multi-use embodiments such as that depicted, the lancet carrier 18 removably engages a lancet 20 comprising a lancet body with a sharp lancet tip 22 projecting therefrom. The charging mechanism 30 operates to retract the lancet carrier 18 from a neutral or normal position to a retracted or charged position to energize the drive spring 14, and the release mechanism 40 holds the lancet carrier 18 in the retracted position and upon actuation releases the lancet carrier 18 to initiate the lancing stroke. The charged drive spring 14 propels the lancet carrier 18 and lancet 20 along an advancing/forward portion of the lancing stroke, from the charged position within the housing to an advanced/extended position where at least the sharp lancet tip 22 projects from the housing 12 to penetrate the subject's skin at a lancing site. The forward portion of the lancing stroke charges the return spring 16, and the now-charged return spring then returns the lancet carrier 18 and lancet 20 to the neutral/normal position.

Optionally, the housing can include an endcap or nosecone portion 50 that provides for adjustment of the penetration depth of the lancet tip 22. Removal of the endcap 50 also allows access for removal and replacement of the disposal lancet 20 after use, for example, by actuation of a lancet ejection mechanism 60, in some multi-use designs.

In other embodiments, the lancing device **10** includes other conventional drive mechanisms, charging mechanisms, release mechanisms, and/or depth-adjustment mechanisms. For example, the drive mechanism can include a single spring element for driving and retracting, the charging mechanism can be provided by a twist-to-charge or push-to-charge mechanism, the release mechanism can be provided by a slide or rotary release, and/or the lancing device can include a multi-lancet carrier holding a plurality of lancets for sequential use.

In the depicted embodiment, the lancet carrier **18** and the lancet **20** are separate parts, with the lancet being replaceable so that the lancing device **10** can be used multiple times. In disposable embodiments, the lancet carrier/holder and the lancet are a single integral component. And in the depicted embodiment, a spring retainer **80** for the drive spring **14** and/or return spring **16** is mounted onto and travels with the lancet carrier **18**, and is such considered to be a component of the lancet carrier, even though it could additionally or alternatively be considered to be a component of the drive mechanism. As such, reference herein (including the appended claims) to the lancet carrier **18** is intended to also refer to the lancet **20** itself as well as to any component of the drive mechanism **15** or another mechanism of the lancing device **10** that travels with the lancet carrier.

The lancing device **10** of the first embodiment further includes a latch mechanism **100** that functions to permit a first oscillation of the lancet carrier **18** and lancet **20** then prevent subsequent (i.e., excess or secondary) oscillations. The term "oscillation" as used herein is defined as the lancet **20** generally moving from a first/retracted position forward to a second/extended position (i.e., where the lancet tip **22** projects out of the housing **12** to contact the lancing site), and rearward back to or at least toward the first/retracted position (i.e., such that the lancet tip is retracted back into the housing).

FIGS. 1A-1F show details and a sequence of operation of the lancing device **10** with the latch mechanism **100**, and FIGS. 2A-5 show components of the latch mechanism in greater detail, with FIGS. 3A-3E corresponding to FIGS. 1A and 1F, with FIG. 4 corresponding to FIG. 1B, and FIG. 5 corresponding to FIGS. 1D and 1E. In typical embodiments such as that depicted, the latch mechanism **100** includes a latch member **102**, a latch-pivoting element **135** of the charging mechanism **30**, a latch-engaging element **181** of the lancet carrier **18**, a spring-biased latch retainer **130** of the latch member or other portion of the lancing device **10**, and a ramp **190** of the housing **12** or other portion of the lancing device.

The latch member **102** is pivotally coupled to an element of the lancing device **10**. For example, the latch member **102** can be pivotally coupled to the housing **12** by a pivot pin **107** with an axis transverse to the angular motion of the latch member **102**, as depicted. As used herein, "pivot" (and other terms with that as the root) includes to rotate or otherwise move angularly.

The latch member **102** of the depicted embodiment includes a leg **110** and a foot **120** integrally formed with or attached to the leg and extending at an angle from the leg. In the depicted embodiment, for example, the foot **120** includes at least a portion that extends from the leg **110** in a direction Y that is generally perpendicular to the pivot axis and at least a portion that extends laterally from the leg in a direction X that is generally parallel to the pivot axis. More particularly, the depicted latch member **102** is generally L-shaped with the leg **110** having a first end **104** and a second end **105**, and with the foot **120** extending generally

perpendicularly and laterally offset from the second end of the leg. The foot **120** includes a charge-pivot face **122** that is engaged by the latch-pivoting element **135** of the charging mechanism **30** during operation, and a drive-stop face **128** that interferes with the latch-engaging element **181** of the drive mechanism **15** during operation to mechanically block excess oscillation. The charge-pivot face **122** and the drive-stop face **128** are formed on the portion of the foot **120** that extends in the X and Y direction from the leg **110** and are oppositely facing away from each other. The foot **120** includes portions that extend in the opposite of the X and Y directions (that is, across the leg faces referenced as **111** and **116**, respectively, in FIG. 2A) for providing strength and durability. In addition, the foot **120** includes an end face **124**, and a pressing surface **125** typically defined by a corner chamfer extending between the faces **122** and **128** for pressing engagement against the pressed surface **282** of the lancet carrier **18**.

In the depicted embodiment, the spring-biased latch retainer **130** is in the form of a resilient finger **130** that is integrally formed with or attached to the leg **110**, the housing **12**, or another element of the lancing device **10**, and that interacts with a rear portion **192** of a ramp **190** (described below). In typical embodiments, the finger **130** extends from, and is generally parallel to and laterally offset from the leg **110** on the opposite side from the foot **120**. In the depicted embodiment, for example, the finger **130** extends from the first end **104** of the leg **110**. The finger **130** includes a contact (e.g., outer) face **132** that engages the ramp **190** when the latch **102** is pivoted through its operating motion. In the depicted embodiment, the finger **130** also includes an opposite (e.g., inner) face **134** that cooperates with a face of the leg **110** to define a slit **136**. The finger **130** is preferably sufficiently thin and resilient to allow a degree of flexure/deflection toward (as permitted by the slit **136**) and away from the leg **110**. As such, the resilient finger **130** functions as a spring to provide a biasing force against the ramp **190** when the two components are moved into engagement with each other. In other embodiments, instead of the cantilevered finger depicted, the spring-biased latch retainer is in the form of a leaf spring, detent, or other spring-biased element or mechanism. And in yet other embodiments, the position of the finger **130** and the ramp **190** are switched, with the ramp extending outwardly from the latch member **102** and the finger extending inwardly from the housing **12**.

The leg **110** includes a drive-pivot face **111** that is engaged by the latch-engaging element **181** of the drive mechanism **15** during operation. The drive-pivot face **111** of the leg **110** is laterally offset from and angled relative to the charge-pivot face **122** of the foot **120**, as discussed above. In addition, the pivotal mounting, and thus the pivot point **107**, of the latch member **102** is at the leg **110**. In the depicted embodiment, the leg **110** includes a mounting hole **114** for receiving the pivot pin **107** to attach the latch member **102** to the lancing device **10** and allow the latch member to rotate about an axis A (see FIG. 3E) generally perpendicular to the advancement and retraction motion of the lancet carrier **18**. In other embodiments, the pivot pin extends from the latch member and is rotationally received in a mounting hole in the housing **12** or other element of the lancing device **10**.

The latch-pivoting element **135** of the charging mechanism **30** faces generally rearward and moves axially rearward when the charging actuator **31** is actuated to charge the drive mechanism **15**. In the depicted embodiment, for example, the charging mechanism **30** includes an internal member (e.g., the generally wedge-shaped member **37** depicted) extending from the charging actuator **31** and

having a surface defining a charging element **33** that engages the drive mechanism **15** to charge the drive spring **14** and also having a surface defining the latch-pivoting element **135**. So when the charging actuator **31** is axially retracted, the latch-pivoting element **135** is also axially retracted into contact with the charge-pivot face **122** of the foot **120** to pivot the latch member **102** in a first/rearward direction from a blocking position to an intermediate non-blocking position. The latch-pivoting element **135** is typically ramped, for example it can have an arcuate shape as depicted. Additionally or alternatively, the charge-pivot face **122** of the foot **120** can be ramped, for example arcuate, to induce the latch-pivoting function.

The latch-engaging element **181** of the lancet carrier **18** faces generally forward and moves axially forward with the lancet **20** when the drive mechanism is released/actuated to drive the lancet through the lancing stroke. For example, the drive spring **14** and/or return spring **16** can be held on the lancet carrier **18** by a spring retainer **80** that is mechanically connected to the lancet carrier, with the spring retainer defining the latch-engaging element **181** (see FIG. 3A). In the depicted embodiment, the spring retainer **80** has a forward-facing surface defining the latch-engaging element **181** (and also defining a surface that is engaged by the charging element **33** to charge the drive spring **14**). And a pressed surface **182** of the lancet carrier **18** can be formed for example by a bottom surface of the spring retainer **80**. In other embodiments, the latch-engaging element is in the form of a tab or other projection that extends from or attaches to the spring retainer or another element of the drive mechanism. In any event, when the release mechanism **40** is actuated (e.g., by depressing the release actuator **41**), the lancet carrier **18** is released so it can be propelled by the drive spring **14** through the forward portion of the lancing stroke and at the same time the latch-engaging element **181** is propelled into contact with the drive-pivot face **111** of the leg **110** to pivot the latch member **102** in a second/forward direction from the intermediate non-blocking position back toward the blocking position.

The ramp **190** extends inwardly from the housing **12** or other portion of the device **10**. The ramp **190** has a front ramped portion **191** that is engaged by the deflected resilient finger (or another type of spring-biased latch retainer) **130** when the drive mechanism **15** propels the lancet carrier **18** through the drive/forward portion of the lancing stroke to cooperatively induce the latch **102** to pivot to the blocking position. Thus, a latch spring biasing the latch **102** from the press non-blocking position to the blocking position is provided by the resilient finger **130** interacting with the front portion **191** of the ramp **190**. That is, the deflected resilient finger **130** is biased to resiliently return to its neutral position, and as it so discharges it biases against the front ramped portion **191**. In turn, this biases the latch member **102** (to which the finger **130** is attached) to pivot to the blocking position. So the discharging force exerted by the bias of the deflected finger **130** that is in contact with the front ramped portion **191** overcomes any frictional forces between these components. Similarly, the ramp **190** also includes a rear ramped portion **192** that is engaged by the deflected resilient finger **130** when the charging actuator **31** is axially retracted to cooperatively induce the latch **102** to pivot to and be retained in the intermediate non-blocking position. Thus, the spring-biased latch retainer **130** is provided by the resilient finger interacting with the rear portion **192** of the ramp **190**. In this way, the ramp **190** urges the latch **102** to remain in either the blocked or intermediate non-blocked position when the latch is not in contact with

the latch-engaging element **181** or the latch-pivoting element **135**. In typical embodiments such as that depicted, the ramp **190** is arcuate and elongated, and it includes a tipping point **193** between the front and rear ramped portions **191** and **192**.

In alternative embodiments, the ramp **190** is outwardly extending/facing from/on an extension (e.g., extending from the housing **12**) such that it contacts the inner face **134** of the resilient finger **130** and deflects outwardly (away from the latch member) from its neutral state to its charged state, as depicted in FIGS. 6A-6B, respectively. In such embodiments, the pivot point **107** can be located on the extension defining the ramp **190**. In still other embodiments, friction between a feature on the housing **12** or other portion of device **10** and the resilient finger **130** may be used to hold the latch member **102** in the blocking or intermediate non-blocking position, or the ramp **190** is eliminated and the latch member is urged to the blocking and intermediate non-blocking positions by gravity or other spring-biased latch retaining mechanisms or elements.

Having described details of the structure of the latch mechanism **100**, details of its operation will now be described with respect to FIGS. 1A-1F. In a normal (e.g., neutral) state (FIG. 1A, see also FIGS. 3A-3E), the latch member **102** is in the blocking (leg-down/foot-up) position with the leg **110** lowered and generally aligned with the axis of translation of the lancet carrier **18**, the blocking foot **120** raised and generally upright relative to the leg, and the finger **130** (and/or the leg) resting on a rib or shelf **194** of the housing **12**. As the charging actuator **31** is retracted (as indicated by the linear-motion arrow in FIG. 1B) or otherwise actuated, the latch-pivoting element **135** of the charging mechanism **30** slides rearwardly against the charge-pivot face **122** of the foot **120** of the latch member **102**, pivoting it (e.g., counter-clockwise as indicated by the angular-motion arrow in FIG. 1B) about the pivot pin **107** (see also FIG. 4). Retraction of the charging actuator **31** also retracts the lancet carrier **18** and the drive mechanism **15** by contact between the charging element or shoulder **33** (of the internal component **37** of the charging mechanism **30**) and lancet carrier (e.g., the spring retainer **80** mounted at the distal end of the lancet carrier). As the latch member **102** pivots further, the foot **120** is lowered into a substantially horizontal orientation and the leg **110** is raised to a substantially upright orientation until the latch member is in the intermediate non-blocking (foot-down/leg-up) position (FIG. 1C). Thus, the lancing device **10** is now in the charged state with the latch mechanism **100** in the intermediate non-blocking position.

As the latch member **102** pivots from the blocking position of FIG. 1A (see also FIGS. 3A-3E), through the pivoting motion of FIG. 1B, to the intermediate non-blocking position of FIG. 1C, the outer face **132** of the finger **130** is pivoted into contact with the front ramped portion **191** of the ramp **190** (e.g., extending inward from the housing **12**) to deflect the finger inward (toward the leg **110**). As the latch member **102** pivots further, the outer face **132** of the finger **130** moves past the tipping point **193** and onto the rear ramped portion **192** of the ramp **190**. In typical embodiments such as that depicted, the biasing force of the deflected finger **130** against the rear ramped portion **192** urges the latch member **102** all the way to the intermediate non-blocking position even if it has not been pivoted all the way there by the engagement of the latch-pivoting element **135** and the foot **120**. By the time the latch member **102** has pivoted to the intermediate non-blocking position of FIG. 1C, the

finger 130 has cleared the ramp 190 and resiliently deflected back out to retain the latch member in place.

As shown in FIG. 1D, when the lancing device 10 is actuated by operation of the release mechanism 40, for example by depressing the release actuator 41 (as indicated by the vertical-motion arrow), the discharging of the drive spring 14 drives the lancet carrier 18 and the attached spring retainer 80 forward to propel the lancet carrier through the drive/forward portion of the lancing stroke (as indicated by the horizontal-motion arrow). As the spring retainer 80 translates forward, it passes over the lowered foot 120 of the latch member 102 until its latch-engaging surface 181 contacts and pushes drive-pivot face 111 of the leg 110, which causes the latch member to reverse rotate (e.g., clockwise as indicated by the angular-motion arrow in FIG. 1D), thereby lowering the leg 110 and raising the blocking foot 120. In this way, the latch member 102 is pivoted from the intermediate non-blocking position back toward the blocking position.

In typical embodiments, the lancet carrier 18 and lancet 20 come to their fully extended/forward lancing position before the spring retainer 80 has pivoted the latch member 102 all the way back to the blocking position to avoid imparting vibrations to the lancet while puncturing the skin, as shown in FIG. 1D. In the depicted embodiment, at this point the finger 130 remains deflected and engaged on the front ramped portion 191 of the ramp 190, biasing the latch member 102 toward the blocking position (see also FIG. 5). But the latch member 102 is restrained from completing its full pivotal movement and held in this press non-blocking position (between the intermediate non-blocking and blocking positions) because the pressed surface 282 of the lancet carrier (e.g., of the spring retainer 80 or another element of the lancet carrier or drive mechanism 15) interferes with pressing surface 125 of the foot 120 (e.g., the latch chamfered face). Thus, the spring retainer 80 has a length such that it does not clear the space above the foot 120 when the lancet carrier 18 and the lancet 20 come to their fully extended/forward lancing position (see FIG. 1D).

The return spring 16 then returns the lancet carrier 18 from the extended/forward position back through the return/reverse portion of the lancing stroke (as indicated by the linear-motion arrow of FIG. 1E) toward the normal (e.g., neutral) position, with the spring retainer 80 retracting over the blocking foot 120 in its press non-blocking position (FIG. 1E). Because the charging mechanism 30 is not again being actuated, its latch-pivoting element 135 is not retracted to push the latch member 102 back to the intermediate non-blocking position. So upon the spring retainer 80 clearing the foot 120, the latch member 102 is now free to pivot to the blocking position, and the charged finger 130 discharges against the front ramp surface 191 to return the latch member to its blocking (leg-down/foot-up) position of FIG. 1F (see also FIGS. 1A and 3A-3E). The upright-positioned foot 120 then blocks the spring retainer 80 from passing forward again under the force of the drive spring 14, thereby arresting any further/excess/secondary oscillation of the drive mechanism 15 and preventing the lancet tip 22 from subsequent advancement and potential re-contact with the lancing site.

In the depicted embodiment, there is also provided a lancet-ejection mechanism 60. When the endcap 50 of the lancing device 10 is installed on the housing 12, abutment of an extension 62 of the ejection mechanism 60 against the cap prevents actuation of the ejection mechanism. To eject the lancet, the cap 50 is removed to allow the ejection mechanism 60 to advance. When the extension 62 of the ejection

mechanism 60 is advanced, an ejection finger 64 of the ejection mechanism contacts the lancet 20 through a slot in the lancet carrier 18 to eject the lancet from the lancet carrier in a forward direction (see FIG. 1F). Contact by the foot 120 of the latch member 102 against the spring retainer 80 prevents forward motion of the lancet carrier 18 during ejection of the lancet, enabling a shorter ejection stroke. In other embodiments, the ejection mechanism is eliminated (i.e., for disposable lancing devices) or provided in another conventional form.

FIGS. 7A-11C show the lancing device 10 as substantially described above, except including a latch mechanism 200 according to a second example embodiment of the present invention. The latch mechanism 200 includes a latch member 202, a spring-biased latch retainer 290, a latch-pivoting element 235 of the charging mechanism 30, and a latch-engaging element 281, a pressed surface 282, and a blocking surface 283 of the lancet carrier 18, that cooperatively function to produce a substantially similar result to that of the first embodiment. That is, a first forward and rearward oscillation of the lancet 20 is permitted when the latch member 202 is in intermediate and press non-blocking positions, and subsequent/excess/secondary oscillations are prevented when the latch mechanism is in a blocking position. The latch member 202 pivots (rotates) between the blocking and non-blocking positions about an axis B (FIG. 7C) that is parallel (e.g., coaxial) with the linear advancement and retraction motion of the lancet carrier 18 during the lancing stroke.

FIGS. 7A-7C show details of the sleeve latch member 202. The latch member 202 is typically in the form of a cylindrical or tubular sleeve that pivots (rotates) about an axis, though it can be in the form of a curved wall section that does not define a complete circle/cylinder. The latch member 202 includes a sleeve body 210 extending from a first end 204 to a second end 205 and defining a retainer-biasing surface 223, an anti-pivot surface 224, a pressing surface 225, a drive-stop surface 228, and a charge-pivot cam surface 222. In addition, the latch member 202 includes a spring 244 that pivotally (i.e., rotationally) biases it in an angular direction.

The anti-pivot surface 224 is formed on an axial/radial side of the sleeve body 210 and engages the spring-biased latch retainer 290. In the depicted embodiment, for example, the sleeve body 210 includes a tooth (e.g., a tab, wedge, post, or other projection) 212 that is integrally formed with or attached to it and that has at least a portion extending generally axially therefrom, with the anti-pivot surface 224 formed on an axial/radial side of the tooth. The anti-pivot surface 224 of the tooth 212 is angled (with respect to a radius line) or otherwise formed to accommodate interaction with the spring-biased latch retainer 290. Thus, the anti-pivot surface 224 can be angled so that when the sleeve body 210 is pivoted into the non-blocking position, it is flush with the catch surface 295 of the spring biased latch retainer 290.

The retainer-biasing surface 223 is formed on the sleeve body 210 and engages the spring-biased latch retainer 290. In the depicted embodiment, for example, the sleeve body 210 includes the tooth 212, and the retainer-biasing surface 223 is formed on the outer surface of the tooth of the sleeve body. The spring-biased latch retainer 290 contacts the retainer-biasing surface 223 when the latch member 202 is in the blocking position and the spring-biased latch retainer is in the charged position, with this contact retaining the latch retainer in the charged position (see FIGS. 9A, 10A, and 11A).

The pressing surface **225** is formed on an axial/radial side of the sleeve body **210** and engages the pressed surface **282** of the lancet carrier **18**. And the drive-stop surface **228** is formed on the rear side (transverse to the axial/radial side) of the sleeve body **210** and engages the latch-engaging surface **281** of the lancet carrier **18**. In the depicted embodiment, for example, the sleeve body **210** includes a foot (e.g., a tooth, tab, post, wedge, or other projection) **220** that is integrally formed with or attached to it and that extends generally transversely and radially inward therefrom (e.g., from the tooth **212** or adjacent the tooth), with the pressing surface **225** formed on an axial/radial side of the foot and the drive-stop surface **228** is formed on the rear side of the foot. The pressing surface **225** provides a sufficient contact surface for interference engagement with the pressed surface **282** of the lancet carrier **18** when the latch member **202** is in the press non-blocking angular position (see FIGS. **7C**, **9C**, **10C**, and **11C**).

The charge-pivot surface **222** is formed on an axial/radial surface (transverse to the front and rear sides) of the sleeve body **210** and engages the latch-pivoting element **235** of the charging mechanism **30**. In the depicted embodiment, for example, the sleeve body **210** includes a void **250** formed near the first end **204** of the latch member **202**, with the charge-pivot surface **222** defining a portion of the void. The charge-pivot surface **222** is angled with respect to the axis of the sleeve body **210** so that when the latch-pivoting element **235** of the charging mechanism **30** is moved longitudinally along it the latch member **212** pivots in an angular direction from the blocking position to the intermediate non-blocking position. In alternative embodiments, the charge-pivot surface **222** is formed on a wedge extending radially outward from the sleeve body **210**, is non-linear to provide for a non-constant pivoting rate, is non-angled (or less angled) with the latch-pivoting element **235** being angled, or is provided in other configurations for providing the functionality described herein.

The latch spring **244** biases the latch member **202** to pivot from the intermediate and press non-blocking positions toward the blocking position. In the depicted embodiment, the latch spring **244** is a torsion spring that is positioned around the sleeve body **210** and mounted to it by a retaining bracket **240** at the second end **205** of the latch member **202**. For example, a first arm **245** of the torsion spring can be retained by the retaining bracket **240** and a second arm **246** can engage the housing **12** or another part of the lancing device **10**. In other embodiments, the latch spring is a compression or tension coil spring, a leaf spring, a resiliently deformable member, or another type of spring element that biases the latch member **202** as described herein.

The latch-pivoting element **235** of the charging mechanism **30** engages the charge-pivot cam surface **222** and thereby pivots the latch member from the blocking position to the intermediate non-blocking position when the charging actuator **31** is operated to charge the drive mechanism **15**. In the depicted embodiment, for example, the latch-pivoting element **235** is a pin that extends radially inward from an internal component of the charging mechanism **30** and slides along the charge-pivot surface **222**. In other embodiments, the latch-pivoting element is a post, bar, rod, shaft, panel, finger, boss, or another element that engages the charge-pivot cam surface to pivot the latch member **202** as described herein.

The latch-engaging element **281** and the blocking surface **283** of the lancet carrier **18** engage the spring-biased latch retainer **290**, and the pressed surface **282** of the lancet carrier **18** is engaged by the pressing surface **225** of the latch **202**.

In the depicted embodiment, for example, the latch-engaging element **281**, the pressed surface **282**, and the blocking surface **283** are contact surfaces formed on forward, lateral, and bottom faces of a spring retainer **80** of the lancet carrier **18**, with the spring retainer retaining the return spring **16** in place on the lancet carrier for charging and discharging. In other embodiments, these surfaces are defined by one, two, or three other elements of the lancet carrier **18**, whether dedicated element for use only in the latch mechanism or for shared use in other functions of the lancing device.

FIGS. **8A-8B** show details of the spring-biased latch retainer **290** of the depicted embodiment, which is in the form of a resilient finger that is biased from a charged non-latch-retaining position to a discharged latch-retaining position. The resilient finger **290** extends from a stationary element of the lancing device **10** and includes contact surfaces that selectively engage the latch member **202** and the lancet carrier (or an element coupled thereto) **18** to provide for permitting a first lancet oscillation and preventing subsequent oscillations. In the depicted embodiment, for example, the resilient finger **290** is a cantilevered arm with a head at its free end, the arm projecting inwardly from the housing **12** and the head defining the contact surfaces for engaging the latch member **202** and the lancet carrier **18**. The contact surfaces of the resilient finger **290** include a first surface **292**, second surface **293**, third surface **294**, and fourth surface **295**.

The first surface **292** contacts the latch member **202**, for example the retainer-biasing surface **223** of the tooth **212** of the sleeve body **210**, when the latch member is in the blocking position and the resilient finger **290** is in the charged non-latch-retaining position, with this contact retaining the resilient finger in position (see FIGS. **9A**, **10A**, and **11A**). The first surface **292** can also contact the lancet carrier **18**, for example the blocking surface **283** of the spring retainer **80**, when the latch member is in the press non-blocking position and the resilient finger **290** is in the partially charged (e.g., deflected) non-latch-retaining position, with this contact retaining the resilient finger in position (see FIGS. **9C**, **10C**, and **11C**).

The fourth surface **295** contacts the latch member **202**, for example the anti-pivot surface **224**, when the latch member is in the intermediate non-blocking position and the resilient finger **290** is in the discharged latch-retaining position, with this contact retaining the latch member in the intermediate non-blocking position (see FIGS. **9B**, **10B**, and **11B**).

The third surface **294** extends between the first and fourth surfaces **292** and **295** and is ramped (e.g., chamfered or beveled) to facilitate smooth movement across the anti-pivot surface **224** (or portions thereof) when the resilient finger **290** is in partially charged positions moving between the charged non-latch-retaining and discharged latch-retaining positions (see FIGS. **9C**, **10C**, and **11C**).

And the second surface **293** contacts the lancet carrier **18**, for example the latch-engaging surface **281**, and is ramped (e.g., chamfered or beveled) so that when the lancet carrier is being propelled forward through the lancing stroke the latch-engaging surface **281** of the lancet carrier rides along the ramped second surface **293** to deflect the resilient finger **290** and thereby withdraw it from the discharged latch-retaining position toward the charged non-latch-retaining position (in positions between the positions of FIGS. **11B** and **11C**).

Typically, but not necessary in all commercial embodiments, the resilient finger **290** is fully discharged in the discharged position (that is, in some embodiments the resilient finger can still have a small charge when in the

“discharged” position). In other embodiments, instead of the cantilevered resilient finger, the spring-biased latch retainer includes a compression or tension coil spring, a torsion spring, a leaf spring, a resiliently deformable member, or another type of spring element, and still includes the contact surfaces that biasingly engage the lancet carrier **18** and the latch member **202** to provide the functionality described herein. In still other embodiments, the latch retainer is not spring-biased and instead is moved between the non-latch-engaging and latch-engaging positions by an additional mechanism or element. And in yet still other embodiments, the latch retainer is eliminated or formed by an element of the charging mechanism **30** so that the charging mechanism temporarily retains the latch **202** in the intermediate position until the lancet carrier **18** moves far-enough forward that the latch member can be released to reverse-pivot to the press non-blocking position.

FIGS. **9A-9C**, **10A-10C**, and **11A-11C** show the operational use of the latch mechanism **200**. In a normal (e.g., neutral) state (FIGS. **9A**, **10A**, and **11A**), the latch member **202** is in the blocking position with the foot **220** inserted into the lancing stroke path of the lancet carrier **18** (and/or the lancet **20**). In use, as the charging actuator **31** is retracted (as indicated by the linear-motion arrow in FIGS. **9B** and **10B**) or otherwise actuated, the latch-pivoting element **235** of the charging mechanism **30** slides rearwardly against the ramped charge-pivot cam face **222** of the latch member **202**, pivoting the latch member (e.g., as indicated by the angular-motion arrow in FIGS. **9B** and **10B**) about its axis (e.g., the lancing path axis) from its blocking position to its non-blocking position of FIGS. **9B**, **10B**, and **11B**. Retraction of the charging actuator **31** also retracts the lancet carrier **18** and the drive mechanism **15** by contact between the charging element or rib **33** (of an internal component **37** of the charging mechanism **30**) and the lancet carrier (e.g., the spring retainer **80** mounted at the distal end of the lancet carrier). As the latch member **202** pivots from its blocking position to its intermediate non-blocking position, the spring **244** begins to transition from a normal (neutral/uncharged or only slightly charged) state to a charged state to bias the latch member **202** back towards the blocking position. In the depicted embodiment, for example, as the latch member **202** rotates, the retaining bracket **240** follows along the spring first arm **245**, and as a result the spring second arm **246** is engaged with an inner portion (e.g., an inner wall surface) of the housing **12** (or another element of the lancing device **10**), thus charging the torsional spring to bias the latch member **202** towards the blocking position. The lancing device **10** is now in the charged state with the latch mechanism **200** retained in the intermediate non-blocking position.

The pivotal movement of the latch mechanism **202** from the blocking position to intermediate non-blocking position frees the spring-biased latch retainer **290** (e.g., the resilient finger) to move from the charged non-latch-retaining position to the discharged latch-retaining position. For example, when the latch member **202** is in the blocking position, the resilient finger **290** can be deflected outward with the first finger surface **292** biased against the retainer-biasing surface **223** of the latch body **210**. In the particular case of the depicted embodiment, when the latch member **202** is in the blocking position, the first finger surface **292** is positioned below the tooth **212** and the finger-blocking surface **223** is defined by the outer wall of the tooth of the latch body **210** (FIGS. **9A**, **10A**, and **11A**). And when the latch member **202** is pivoted to the intermediate non-blocking position, the retainer-biasing surface **223** of the latch **202** is pivoted out of contact with the resilient finger **290** (FIGS. **9B**, **10B**, and

11B). So the charged resilient finger **290**, now free of the interference with the latch member **202**, discharges and thereby deflects inward from the charged position to the discharged position.

In the discharged latch-retaining position, the resilient finger **290** prevents the latch member **200** in the intermediate non-blocking position from reverse pivoting back toward the blocking position. In the depicted embodiment, for example, the fourth finger surface **295** (or adjacent surfaces/edges) aligns with the anti-pivot surface **224** of the tooth **212** of the latch member **202** in an interference position to prevent such reverse pivoting (FIGS. **9B**, **10B**, and **11B**).

To initiate the lancing stroke, the release mechanism **40** is actuated to release the lancet carrier **18** to be propelled through the lancing stroke by the drive mechanism **15**. In the depicted embodiment, for example, the release actuator **41** is depressed (as indicated by the downward linear arrow of FIGS. **9C** and **10C**) to disengage mating elements of the release mechanism **40** and the lancet carrier **18**. The released lancet carrier **18** is then propelled along the forward portion of the lancing stroke by the discharging drive spring **14**.

As the lancet carrier **18** moves forward, a portion of it engages the resilient finger **290** and displaces it out of the way. In the depicted embodiment, the blocking surface **283** of the lancet carrier **18** (e.g., formed on the lancet carrier's spring retainer **80**) comes into contact with the second finger surface **293**. The second finger surface **293** is ramped (and/or the blocking surface **283** can be ramped) so that this engagement deflects the resilient finger **290** from the discharged latch-retaining position to a partially charged non-latch-retaining position (FIGS. **9C**, **10C**, and **11C**). So now the fourth finger surface **295** has been removed from interference/alignment with the anti-pivot surface **224** of the latch member **202**, and the latch member reverse-pivots (in the second/reverse angular direction) slightly under the biasing force of the charged spring **244** to the press non-blocking position. But because the lancet carrier **18** has moved forward, its pressed surface **282** (e.g., of the spring retainer **80**) is now in an interfering position with (and is thus pressed upon by) the pressing surface **225** (e.g., of the foot **220**) of the spring-biased latch member **202** to block the latch member from further reverse-pivoting (FIGS. **9C**, **10C**, and **11C**).

The lancet carrier **18** continues blocking the latch member **202** from further reverse-pivoting as it travels forward to the fully extended position to lance the subject's skin and then begins retracting on the reverse portion of the lancing stroke. Thus, the pressed surface **282** of the lancet carrier **18** has a length sufficient to maintain this interference with the pressing surface **225** of the latch member **202** during these segments of the forward and reverse portions of the lancing stroke. Friction caused by contact between the pressed surface **282** (e.g., of the spring retainer **80**) and the pressing surface **225** (e.g., of the foot **220**) is substantially small so that the lancing movement is smooth and easy.

Once the lancet carrier **18** retracts to where its pressed surface **282** has cleared blocking interference with the pressing surface **225** of the latch member **202**, the latch member then further reverse-pivots (in the second/reverse angular direction), under the biasing force of the charged spring **244**, back to the blocking position of FIGS. **9A**, **10A**, and **11A**. This in turn causes the anti-pivot surface **224** of the latch member **202** to drive against the ramped third surface **294** of the resilient finger **290** to return/deflect the finger to the charged non-latch-retaining position.

After this first lancet oscillation (i.e., the lancing stroke), the drive spring **14** may be sufficiently re-charged to initiate

a subsequent lancet oscillation. But with the latch member **202** in the blocking position of FIGS. **9A**, **10A**, and **11A**, the blocking drive-stop surface **228** of the latch member **202** (e.g., of its tooth **220**) is now in an interference position (inserted into the path of the lancet carrier **18** and/or the lancet **20**) so that it will contact the latch-engaging surface **281** of the lancet carrier (e.g., of its spring retainer **80**) and block it from further forward travel. In this way, excess oscillations of the lancet **20** are prevented, thereby minimizing the pain associated with repeated sticks by the lancet tip **22**.

In alternative embodiments, the latch mechanism does not include the spring finger **290** (or the surfaces of the latch and other mechanisms of the lancing device that it engages) and instead includes other types of spring-biased latch retainers that retain the latch member in the intermediate non-blocking position but only until the portion of the lancet carrier that the latch presses against moves into an interference position during the forward portion of the lancing stroke. In some such embodiments, the spring-biased latch retainer is a spring-biased plunger (e.g., a spring-biased pin or projection) extending from the latch member (or the housing) for operating similarly to the resilient finger **290**. In one embodiment, for example, the plunger extends axially from the second end of the latch where it is biased against a portion of the housing. During charging, the spring-biased plunger rides along the housing as the latch member pivots until it aligns with an anti-pivot pocket (e.g., formed with the housing) in the intermediate non-blocking position, and then the plunger is extended into the pocket under the biasing influence of its spring force, thereby retaining the latch member in the intermediate non-blocking position. As the lancet carrier travels forward after operation of the actuation mechanism, a plunger-retraction member (e.g., of the lancet carrier) is engaged to retract the plunger from the anti-pivot pocket and the latch member reverse-pivots slightly (in the second angular direction) under the biasing force of the charged spring to the press non-blocking position. From there, the operation of the latch mechanism is the same as described above. It will be understood that included within the scope of the invention are other forms of spring or biasing latch-retaining elements that operate to retain the latch member in the intermediate non-blocking position and then release the latch member to reverse-pivot to the press non-blocking position as a part of the overall operation to permit the first forward and rearward oscillation of the lancet and to then prevent subsequent/excess oscillations after the latch member returns to the blocking position.

In the depicted embodiment, the latch member **202** pivots in a first angular direction (counter-clockwise when viewed from behind) and a second opposite angular direction (clockwise when viewed from behind) when functioning to permit the first oscillation of the lancet **20** and prevent subsequent oscillations. In other embodiments, the latch mechanism is configured so that the latch member pivots in opposite directions or pivots in only one angular direction (whether clockwise or counter-clockwise) when functioning to permit the first oscillation of the lancet and prevent subsequent oscillations.

While the invention has been described with reference to preferred and example embodiments, it will be understood by those skilled in the art that a variety of modifications, additions and deletions are within the scope of the invention, as defined by the following claims.

What is claimed is:

1. A lancing device for use with a disposable lancet having a lancet body and a sharp lancet tip for penetrating skin to

obtain a sample of blood or other body fluid for medical testing, the lancing device comprising:

- a housing defining a cavity;
- a lancet carrier positioned within the cavity generally along a driving axis, the lancet carrier defining a holder configured to releasably engage a disposable lancet, the lancet carrier being movable in a direction along the driving axis from a retracted position to an extended position where at least the sharp lancet tip of the disposable lancet is configured to project out from the housing, wherein a slot in the lancet carrier allows access to an end of the disposable lancet opposite of the sharp lancet tip when the disposable lancet is positioned within the lancet holder of the lancet carrier and wherein the lancet carrier is held in a neutral position when not in the retracted position or the extended position;
- a return spring positioned within the cavity along the driving axis and configured to propel the lancet carrier from the extended position to the neutral position;
- a drive spring positioned within the cavity distally of the return spring along the driving axis and configured to propel the lancet carrier from the retracted position to the extended position;
- a removable cap positionable over an end of the housing, wherein removal of the cap from the housing allows access to the cavity in order to remove and replace the disposable lancet into the lancet holder of the lancet carrier;
- a unitary member configured to selectively permit ejection of the disposable lancet from the lancet carrier while the lancet carrier is in the neutral position, the unitary member comprising an ejection finger and an extension, wherein the ejection finger extends into the slot of the lancet carrier and, when the disposable lancet is positioned within the lancet holder of the lancet carrier, at least a portion of the ejection finger is movable distally along the driving axis to push against an end of the disposable lancet opposite of the sharp lancet tip to eject the disposable lancet from the lancet holder of the lancet carrier, and wherein, when the cap is positioned over a distal end of the housing, the extension of the unitary member bears against the cap and prevents the ejection finger of the unitary member from moving distally to eject the disposable lancet from the lancet carrier.

2. The lancing device of claim **1**, wherein the extension of the unitary member extends to a position closer to the distal end of the housing than the ejection finger of the unitary member.

3. The lancing device of claim **2**, wherein the ejection finger of the unitary member comprises a portion that extends generally along the driving axis and a portion that extends generally in a direction perpendicular to the driving axis.

4. The lancing device of claim **3**, wherein the ejection finger of the unitary member has a surface defining a plane perpendicular to the driving axis.

5. The lancing device of claim **1**, wherein the ejection finger of the unitary member comprises a portion that extends generally along the driving axis and a portion that extends generally in a direction perpendicular to the driving axis.

6. The lancing device of claim **5**, wherein the ejection finger of the unitary member has a surface defining a plane perpendicular to the driving axis.

17

7. The lancing device of claim 6, wherein the extension of the unitary member extends distally in a position outside of the lancet carrier.

8. The lancing device of claim 7, wherein the unitary member is moveable separately from the lancet carrier. 5

9. A lancing device defining an axis from a forward end and a rearward end, the lancing device comprising:

- a housing defining a cavity;
- a removable cap configured to be couplable to the housing to substantially enclose the cavity along the forward end;
- a lancet carrier positioned within the cavity and configured to receive and temporarily retain a disposable lancet and to move along the axis towards the forward end; and
- a unitary ejection member including a first arm having an ejection portion and a second arm extending closer to the forward end than the first arm,

wherein the ejection portion of the first arm of the unitary ejection member fits into a slot of the lancet carrier through which the ejection portion of the first arm of the unitary ejection member is able to contact the disposable lancet,

wherein, when the cap is coupled to the housing at the forward end, the second arm of the unitary ejection member contacts the cap and prevents the first arm from contacting the disposable lancet, and

wherein, when the cap is not coupled to the housing at the forward end, the unitary ejection member is moveable towards the forward end and the first arm is configured to contact and eject the disposable lancet from the lancet carrier.

10. The lancing device of claim 9, wherein the unitary ejection member is configured to be movable independently of the lancet carrier. 35

11. The lancing device of claim 9, wherein the unitary ejection member is separately controllable from the lancet carrier.

12. The lancing device of claim 9, wherein the first arm of the unitary ejection member comprises a portion that extends generally along the axis and a portion that extends generally in a direction perpendicular to the axis. 40

13. The lancing device of claim 12, wherein the first arm of the unitary ejection member comprises a surface that defines a plane perpendicular to the axis. 45

14. The lancing device of claim 13, wherein the first arm of the unitary ejection member comprises a surface that defines a plane perpendicular to a surface of the second arm.

15. The lancing device of claim 14, wherein the first arm of the unitary ejection member is movable relative to the lancet carrier towards the forward end in order to contact the disposable lancet and to eject the disposable lancet from the lancet holder of the lancet carrier. 50

16. The lancing device of claim 15, wherein the second arm of the unitary ejection member extends to a position outside of the lancet carrier. 55

17. A lancing device for use with a disposable lancet having a lancet body and a sharp lancet tip for penetrating skin to obtain a sample of blood or other body fluid for medical testing, the lancing device comprising:

- a housing defining a cavity;
- a lancet carrier positioned within the cavity generally along a driving axis, the lancet carrier defining a lancet holder configured to releasably engage a disposable lancet, the lancet carrier being movable in a direction along the driving axis between a retracted position, an extended position where at least the sharp lancet tip of

18

- the disposable lancet is configured to project out from the housing, and a neutral position between the retracted position and the extended position, wherein a slot in the lancet carrier allows access to an end of the disposable lancet opposite of the sharp lancet tip when the disposable lancet is positioned within the lancet holder;
- a return spring positioned within the cavity along the driving axis and configured to propel the lancet carrier from the extended position to the neutral position;
- a drive spring positioned within the cavity distally of the return spring along the driving axis and configured to propel the lancet carrier from the retracted position to the extended position;
- a removable cap positionable over an end of the housing, wherein removal of the cap from the housing allows access to the cavity in order to remove and replace the disposable lancet into the lancet holder of the lancet carrier;
- a unitary member configured to selectively permit ejection of the disposable lancet from the lancet carrier while the lancet carrier is in the neutral position, the unitary member comprising an ejection finger and an extension,

wherein the ejection finger of the unitary member extends into the slot of the lancet carrier and, when the disposable lancet is positioned within the lancet holder of the lancet carrier, at least a portion of the ejection finger of the unitary member is movable distally along the driving axis to push against the end of the disposable lancet opposite of the sharp lancet tip to eject the disposable lancet from the lancet holder of the lancet carrier, and

wherein, when the cap is positioned over a distal end of the housing, the extension of the unitary member bears against the cap and prevents the ejection finger of the unitary member from moving distally to eject the disposable lancet from the lancet carrier;

- a slide operably connected to the lancet carrier and adapted to move the lancet carrier from the neutral position to the retracted position to energize the drive spring; and
- a button operably connected to the lancet carrier and configured to temporarily hold the lancet carrier in the retracted position and, when pressed, to release the lancet carrier and to allow the lancet carrier to move from the retracted position to the extended position, and thereafter the return spring and the drive spring together hold the lancet carrier in the neutral position unless the slide moves the lancet carrier to the retracted position.

18. The lancing device of claim 17, wherein the unitary member is moveable separately from the lancet carrier.

19. The lancing device of claim 18, wherein the ejection finger of the unitary member comprises a portion that extends generally along the driving axis and a portion that extends generally in a direction perpendicular to the driving axis. 60

20. The lancing device of claim 19, wherein the ejection finger of the unitary member has a surface defining a plane perpendicular to the driving axis.

21. The lancing device of claim 20, wherein the extension of the unitary member extends to a position closer to the distal end of the housing than the ejection finger of the unitary member. 65

22. The lancing device of claim 21, wherein the extension of the unitary member extends distally in a position outside of the lancet carrier.

* * * * *