



- (51) International Patent Classification:
A63B 21/078 (2006.01)
- (21) International Application Number:
PCT/US2017/061228
- (22) International Filing Date:
13 November 2017 (13.11.2017)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
62/422,350 15 November 2016 (15.11.2016) US
- (71) Applicant: SPECIALTY FITNESS SYSTEMS, LLC
[US/US]; P.O. Box 790, 455 Allegheny Blvd., Franklin,
Pennsylvania 16323 (US).
- (72) Inventor: LEIPHEIMER, Jerry, K.; 2975 Springwood
Drive, Sharpsville, Pennsylvania 16150 (US).
- (74) Agent: MCILVAINE, John, W. et al.; The Webb Law
Firm, One Gateway Center, 420 Ft. Duquesne Blvd., Suite
1200, Pittsburgh, Pennsylvania 15222 (US).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP,
KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

(54) Title: HIGH-LOW PULLEY RACK SYSTEM FOR WEIGHT MACHINE




FIG. 1

(57) Abstract: A pulley rack for an exercise machine includes a support frame, an upright extending generally vertically within the support frame, a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame, one or more guide pulleys mounted to the support frame, a cable end assembly mounted to the upright, and a pull cable having a fixed attachment end connected to the cable end assembly and a pullable end freely passing through the cable end assembly, the counterweight pulleys, and guide pulleys such that a force exerted on the pullable end raises the counterweight. A section of the pull cable extends from the pullable end through the cable end assembly and downwardly to one of the guide pulleys mounted below the cable end assembly.



Published:

- with international search report (Art. 21(3))
- with amended claims (Art. 19(1))

HIGH-LOW PULLEY RACK SYSTEM FOR WEIGHT MACHINE

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to United States Provisional Patent Application No. 62/422,350 filed November 15, 2016, the disclosure of which is hereby incorporated in its entirety by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] This disclosure relates generally to exercise or weight machines and, more particularly, to an adjustable pulley rack system that allows a user to vary the location of a pull cable for performing exercises on a cable exercise machine.

Description of Related Art

[0003] Exercise machines which employ a cable and pulley system attached to a counterweight are well known. Conventionally, cable exercise machines include a support frame to which a moveable counterweight and one or more pulley are mounted. A cable extends vertically from the top of the counterweight and is routed through the one or more pulleys to a free end of the cable. Various attachments, such as D-handles, barbells, or rope handles, may be attached to the free end of the cable.

[0004] Resistance training exercises are performed by pulling on the attachment in order to lift the counterweight against the force of gravity. Often, the counterweight is adjustable to allow the user to select the amount of resistance provided.

[0005] One of the benefits of cable exercise machines is that they permit a variety of different exercise to be performed, because resistance is provided no matter the direction the user pulls the cable. Thus, cable exercise machines reduce the need for multiple exercise machines which are dedicated to providing resistance in a single direction or useful only for a limited number of exercise motions.

[0006] An additional feature of some cable exercise machines is that the attachment point from which the user pulls the cable is moveable along the support frame, so that the exercise machine has greater versatility. For example, the user may move the attachment point to a low position for exercises which require resistance in a downward direction, such a biceps curls or chest flies. The user may move the attachment point to a high position for exercises which require resistance in an upward direction, such as pulldowns.

[0007] However, existing cable exercise machines are limited in that additional components necessary to perform certain exercises, such as bar catches needed for a barbell chess press, cannot be mounted to the cable exercise machine because the pull cable obstructs much of the support frame.

[0008] There exists a need for a cable exercise machine which provides the functionality of a moveable attachment point, while allowing other components to be attached to the support frame without obstructing or being obstructed by the pull cable.

SUMMARY OF THE INVENTION

[0009] In view of the foregoing, a need exists for an adjustable pulley rack which is compatible with other components of an exercise machine.

[0010] According to an aspect of the disclosure, a pulley rack for an exercise machine includes a support frame, an upright extending generally vertically within the support frame, a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame, one or more guide pulleys mounted to the support frame, a cable end assembly mounted to the upright, and a pull cable having a fixed attachment end connected to the cable end assembly and a pullable end freely passing through the cable end assembly. The pull cable is routed through the cable end assembly, the counterweight pulleys, and guide pulleys such that a force exerted on the pullable end raises the counterweight. A section of the pull cable extends from the pullable end through the cable end assembly and downwardly to one of the guide pulleys mounted below the cable end assembly.

[0011] According to another non-limiting aspect of the disclosure, the cable end assembly is vertically slideable along the upright.

[0012] According to another non-limiting aspect of the disclosure, the cable end assembly is lockable in a plurality of positions along the upright.

[0013] According to another non-limiting aspect of the disclosure, the cable end assembly is lockable in any of a plurality of holes in the upright.

[0014] According to another non-limiting aspect of the disclosure, the cable end assembly includes a pivot pin permitting rotation of at least a portion of the cable end assembly about an axis parallel to the upright.

[0015] According to another non-limiting aspect of the disclosure, the pulley rack further includes a bar catch mounted to the upright and adapted to support a barbell at a predetermined height.

[0016] According to another non-limiting aspect of the disclosure, the pulley rack further includes a safety spotter arm mounted to the upright above the cable end assembly and adapted to prevent the barbell from dropping below a second predetermined height.

[0017] According to another non-limiting aspect of the disclosure, the cable end assembly is mounted to the upright at a bottom location of the upright, the barbell rests on the bar catch mounted above the cable end assembly, and the pullable end of the pull cable is affixed to the barbell such that force exerted vertically on the barbell raises the counterweight.

[0018] According to another non-limiting aspect of the disclosure, the pull cable is routed through one of the guide pulleys between a first of the counterweight pulleys and a second of the counterweight pulleys.

[0019] According to other aspects of the disclosure, a pulley rack for an exercise machine includes a support frame, a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame, one or more guide pulleys mounted to the support frame, a cable end assembly moveably mounted to the upright, a first cable section extending from a fixed connection at the cable end assembly to a first of the counterweight pulleys, and a second cable section extending downwardly from a pullable connection at the cable end assembly around one of the guide pulleys and to the first of the counterweight pulleys. The counterweight is vertically moveable by a force exerted on the pullable connection of the second cable section. Movement of the cable end assembly along the upright does not move the counterweight.

[0020] According to another non-limiting aspect of the disclosure, wherein the first cable section extends upwardly from the fixed connection to one of the guide pulleys.

[0021] According to another non-limiting aspect of the disclosure, the first cable section extends around a second of the counterweight pulleys between the cable end assembly and the first of the counterweight pulleys.

[0022] According to another non-limiting aspect of the disclosure, the first cable section extends around one of the guide pulleys between the first of the counterweight pulleys and the second of the counterweight pulleys.

[0023] According to another non-limiting aspect of the disclosure, the first cable section extends around one of the guide pulleys between the cable end assembly and the first of the counterweight pulleys.

[0024] According to another non-limiting aspect of the disclosure, the pulley rack further includes a bar catch mounted to the upright above the cable end assembly, the bar catch adapted to support a barbell at a predetermined height.

[0025] According to another non-limiting aspect of the disclosure, the pulley rack further includes a safety spotter arm mounted to the upright above the cable end assembly and adapted to prevent the barbell from dropping below a second predetermined height.

[0026] According to another non-limiting aspect of the disclosure, the first cable section and the second cable section define a continuous length of cable.

[0027] According to other aspects of the disclosure, a method of operating an exercise machine includes moving a cable end assembly along an upright of a support frame, wherein the cable end assembly has a fixed attachment to a first end of a pull cable, and wherein a second end of the pull cable is pullable through the cable end assembly, and locking the cable end assembly in one of a plurality of positions along the upright. The pull cable, between the first end and the second end, extends downwardly from the cable end assembly and is routed through one or more guide pulleys mounted to the exercise machine and one or more counterweight pulleys mounted to a moveable counterweight. Moving the cable end assembly along the upright does not alter the position of a counterweight.

[0028] According to another non-limiting aspect of the disclosure, the method further includes exerting a force on the second end of the pull cable to raise the counterweight, wherein the counterweight is raised regardless of the direction of the force exerted on the second end of the pull cable.

[0029] According to another non-limiting aspect of the disclosure, the method further includes attaching a barbell to the second end of the pull cable, the barbell adapted to rest on at least one bar catch mounted to the upright.

[0001] The invention is further defined by the following clauses:

[0030] Clause 1: A pulley rack for an exercise machine, the pulley rack comprising: a support frame; an upright extending generally vertically within the support frame; a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame; one or more guide pulleys mounted to the support frame; a cable end assembly mounted to the upright; and a pull cable having a fixed attachment end assembly and a pullable end freely passing through the cable end assembly; wherein the pull cable is routed through the cable end assembly, the counterweight pulleys, and guide pulleys such that a force exerted on the pullable end raises the counterweight, and wherein a section of the pull cable extends from the pullable end through the cable end assembly and downwardly to one of the guide pulleys mounted below the cable end assembly.

[0031] Clause 2: The pulley rack of clause 1, wherein the cable end assembly is vertically slideable along the upright.

[0032] Clause 3: The pulley rack of clause 1 or 2, wherein the cable end assembly is lockable in a plurality of positions along the upright.

[0033] Clause 4: The pulley rack of any of clauses 1 to 3, wherein the cable end assembly is lockable in any of a plurality of holes in the upright.

[0034] Clause 5: The pulley rack of any of clauses 1 to 4, wherein the cable end assembly comprises a pivot pin permitting rotation of at least a portion of the cable end assembly about an axis parallel to the upright.

[0035] Clause 6: The pulley rack of any of clauses 1 to 5, further comprising a bar catch mounted to the upright above the cable end assembly, the bar catch adapted to support a barbell at a predetermined height.

[0036] Clause 7: The pulley rack of any of clauses 1 to 6, further comprising a safety spotter arm mounted to the upright above the cable end assembly, the safety spotter arm adapted to prevent the barbell from dropping below a second predetermined height.

[0037] Clause 8: The pulley rack of any of clauses 1 to 7, wherein the cable end assembly is mounted to the upright at a bottom location of the upright, wherein the barbell rests on the bar catch mounted above the cable end assembly, and wherein the pullable end of the pull cable is affixed to the barbell such that force exerted vertically on the barbell raises the counterweight.

[0038] Clause 9: The pulley rack of any of clauses 1 to 8, wherein the pull cable is routed through one of the guide pulleys between a first of the counterweight pulleys and a second of the counterweight pulleys.

[0039] Clause 10: A pulley rack for an exercise machine, the pulley rack comprising: a support frame; a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame; one or more guide pulleys mounted to the support frame; a cable end assembly moveably mounted to the upright; a first cable section extending from a fixed connection at the cable end assembly to a first of the counterweight pulleys; and a second cable section extending downwardly from a pullable connection at the cable end assembly around one of the guide pulleys and to the first of the counterweight pulleys; wherein the counterweight is vertically moveable by a force exerted on the pullable connection of the second cable section; and wherein movement of the cable end assembly along the upright does not move the counterweight.

[0040] Clause 11: The pulley rack of clause 10, wherein the first cable section extends upwardly from the fixed connection to one of the guide pulleys.

[0041] Clause 12: The pulley rack of clause 10 or 11, wherein the first cable section extends around a second of the counterweight pulleys between the cable end assembly and the first of the counterweight pulleys.

[0042] Clause 13: The pulley rack of any of clauses 10 to 12, wherein the first cable section extends around one of the guide pulleys between the first of the counterweight pulleys and the second of the counterweight pulleys.

[0043] Clause 14: The pulley rack of any of clauses 10 to 13, wherein the first cable section extends around one of the guide pulleys between the cable end assembly and the first of the counterweight pulleys.

[0044] Clause 15: The pulley rack of any of clauses 10 to 14, further comprising a bar catch mounted to the upright above the cable end assembly, the bar catch adapted to support a barbell at a predetermined height.

[0045] Clause 16: The pulley rack of any of clauses 10 to 15, further comprising a safety spotter arm mounted to the upright above the cable end assembly, the safety spotter arm adapted to prevent the barbell from dropping below a second predetermined height.

[0046] Clause 17: The pulley rack of any of clauses 10 to 16, wherein the first cable section and the second cable section define a continuous length of cable.

[0047] Clause 18: A method of operating an exercise machine, comprising: moving a cable end assembly along an upright of a support frame, wherein the cable end assembly has a fixed attachment to a first end of a pull cable, and wherein a second end of the pull cable is pullable through the cable end assembly; and locking the cable end assembly in one of a plurality of positions along the upright; wherein the pull cable, between the first end and the second end, extends downwardly from the cable end assembly and is routed through one or more guide pulleys mounted to the exercise machine and one or more counterweight pulleys mounted to a moveable counterweight; and wherein moving the cable end assembly along the upright does not alter the position of a counterweight.

[0048] Clause 19: The method of clause 18, further comprising exerting a force on the second end of the pull cable to raise the counterweight, wherein the counterweight is raised regardless of the direction of the force exerted on the second end of the pull cable.

[0049] Clause 20: The method of clause 18 or 19, further comprising attaching a barbell to the second end of the pull cable, the barbell adapted to rest on at least one bar catch mounted to the upright.

[0050] These and other features and characteristics of the high-low pulley rack will become more apparent upon consideration of the following description and the appended claims with

reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures. It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only and are not intended as a definition of the limits of the disclosure. As used in the specification and the claims, the singular form of “a”, “an”, and “the” include plural referents unless the context clearly dictates otherwise.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0051] **FIG. 1** is a perspective view of a cable exercise machine including a high-low pulley rack system;
- [0052] **FIG. 2** is a front view the exercise machine of **FIG. 1**;
- [0053] **FIG. 3** is a side view the exercise machine of **FIG. 1**;
- [0054] **FIG. 4** is a top view the exercise machine of **FIG. 1**;
- [0055] **FIG. 5** is a cable schematic of the high-low pulley rack system;
- [0056] **FIG. 6** is a perspective view of the cable exercise machine of **FIG. 1** with a barbell and barbell hooks;
- [0057] **FIG. 7** is a front view the exercise machine of **FIG. 6**;
- [0058] **FIG. 8** is a side view the exercise machine of **FIG. 6**;
- [0059] **FIG. 9** is a top view the exercise machine of **FIG. 6**;
- [0060] **FIG. 10** is a side view of the exercise machine of **FIG. 6** with a user performing a chest press exercise;
- [0061] **FIG. 11** is a side view of the cable exercise machine of **FIG. 1** with the user performing a pulldown exercise; and
- [0062] **FIG. 12** is a side view of the exercise machine of **FIG. 6** showing an alternative counterweight arrangement.

DESCRIPTION OF THE INVENTION

[0063] For purposes of the description hereinafter, the terms “upper”, “lower”, “right”, “left”, “vertical”, “horizontal”, “top”, “bottom”, “lateral”, “longitudinal”, and derivatives thereof shall relate to the disclosure as it is oriented in the figures. However, it is to be understood that the disclosure may assume alternative variations and step sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification,

are simply exemplary aspects of the disclosure. Hence, specific dimensions and other physical characteristics related to the aspects disclosed herein are not to be considered as limiting.

[0064] The present disclosure relates generally to exercise or weight machines and, more particularly, to an adjustable high-low pulley rack that allows a user to vary the location of a pull cable for performing exercises on a cable exercise or weight machine. Certain aspects of the components of the exercise or weight machine and the high-low pulley rack system are illustrated in **FIGS. 1-12**.

[0065] Referring now to **FIGS. 1-4**, an exercise machine **10** including a high-low pulley rack **100** is shown. The exercise machine **10** includes a support frame **12** to which the counterweights **200** and the components of the high-low pulley rack **100** are attached. In particular, the high-low pulley rack **100** includes uprights **101**, cable end assemblies **110**, and pull cables **121**. The exercise machine **10** as illustrated in **FIG. 1** shows a pair of high-low pulley racks **100** arranged in tandem on the exercise machine **10**. However, it is to be understood that in other aspects, a single high-low pulley rack **100** may be used.

[0066] Referring now to **FIG. 2**, each upright **101** includes a plurality of indexing holes **102** spaced vertically along the upright **101**. The plurality of index holes **102** cooperate with a popper pin **111** of the cable end assembly **110** to lock the cable end assembly **110** to the upright **101**. The popper pin **111** of the cable end assembly **110** can be locked into any one of the plurality of index holes **102**, permitting the user to position the cable end assembly **110** at a desired vertical position on the upright **101**.

[0067] Referring now to **FIG. 3**, each cable end assembly **110** of the high-low pulley rack system **100** includes the popper pin **111**, an upper end pulley **112**, and a lower end pulley **113**. The upper end pulley **112** and the lower end pulley **113** are arranged on opposing sides of the pull cable **121**, such that the pull cable **121** is supported whether it is pulled downwardly or upwardly by a user. If the pull cable **121** is pulled downwardly by the user, the pull cable **121** at least partially engages the lower end pulley **113**. Conversely, if the pull cable **121** is pulled upwardly, the pull cable **121** at least partially engages the upper end pulley **112**. The cable end assembly **110** may include a pivot pin **114** which permits the upper end pulley **112** and the lower end pulley **113** to rotate about an axis parallel to the upright **101**. In this manner, the upper end pulley **112** and the lower end pulley **113** may self-align horizontally in the direction which the pull cable **121** is pulled.

[0068] With continued reference to **FIG. 3**, a fixed end connection **122** of the pull cable **121** is attached to the cable end assembly **110**. A pullable end **123** of the pull cable **121** freely passes through the cable end assembly **110** between the upper end pulley **112** and the lower

end pulley **113**. The pullable end **123** includes a retention device **124** which prevents the pullable end **123** from slipping backward through the upper end pulley **112** and the lower end pulley **113**. The retention device **124** may be, for example, a ball encompassing a portion of the pull cable **121** which is too large to pass between the upper end pulley **112** and the lower end pulley **113**.

[0069] Referring now to **FIG. 5**, the pull cable **121** is routed from the fixed end connection **122**, through the counterweight **200**, and back to the pullable end **123** at the cable end assembly **110**. More specifically, the pull cable **121** is routed through one or more guide pulleys **130** mounted to the support frame **12** of the exercise machine **10** and one or more counterweight pulley **131** mounted to the counterweight **200**. Each of the guide pulleys **130** and counterweight pulleys **131** changes the direction of the pull cable **121**. A first section **121a** of the pull cable **121** extends from the fixed end connection **122** at the cable end assembly **110** to one of the counterweight pulleys **131**, such that the weight of the counterweight **200** imparts tension to the pull cable **121**. The first section **121a** of the pull cable **121** may be routed around one or more of the guide pulleys **130** to provide additional guidance and stabilization to the first section **121a**. A second section **121b** of the pull cable **121** extends from one of the counterweight pulleys **131** to the pullable end **123** of the pull cable **121**, such that the tension imparted on the pull cable **121** by the counterweight **200** induces the pullable end **123** of the pull cable **121** towards the cable end assembly **110**. The second section **121b** extends downwardly from the cable end assembly **110** such that other components of the exercise machine **10** may be mounted to the upright **101** above the cable end assembly **110** without obstructing or being obstructed by the second section **121b**. The second section **121b** of the pull cable **121** may be routed around one or more of the guide pulleys **130** to provide additional guidance and stabilization to the second section **121b**.

[0070] With continued reference to **FIG. 5**, the cable routing arrangement of the pull cable **121** described above allows the cable end assembly **110** to be adjusted vertically along the upright **101** as desired by the user. When the popper pin **111** of the cable end assembly **110** is released and the cable end assembly **110** is moved up or down the upright **101**, the pull cable **121** travels freely over the guide pulleys **130** and the counterweight pulleys **131** without moving the counterweight **200**.

[0071] Referring now to **FIG. 6-9**, the exercise machine **10** is shown with the high-low pulley rack **100** is arranged for the user **50** to perform a chest press exercise. A barbell **30** is positioned on bar catches **31** mounted to the uprights **101**. Additionally, safety spotter arms **32** are mounted to the uprights **101** below the bar catches **31**. The cable end assemblies **110** are

attached to the uprights **101** in a position below the bar catches **31** and safety spotter arms **32**. The pullable ends **123** of the pull cables **121** are routed around the upper end pulley **112** of the cable end assemblies **110**, and the pullable ends **123** are clipped to the barbell **30** such that pushing the barbell **30** upwards imparts tension to the pull cables **121**. Referring now to **FIG. 10**, if sufficient force is exerted against the barbell **30** by the user **50**, the force transmitted through the pull cables **121** raises the counterweight **200**.

[0072] Referring now to **FIG. 11**, the exercise machine **10** is shown with the high-low pulley rack system **100** is arranged for the user **50** to perform a pulldown exercise. The cable end assemblies **110** are attached to the uprights **101** in a position above the user **50**, and a bar or other gripping device **40** is attached to the pullable ends **123** of the pull cables **121**. The pullable ends **123** are routed around the lower end pulley **113** of the cable end assemblies **110**, and the user **50** exerts downward force on the pull cables **121** to raise the counterweight **200**.

[0073] Various embodiments of the counterweights **200** may be used with the high-low pulley rack **100**. **FIGS. 1-11** illustrate a trolley arrangement for the counterweight **200**. Referring back to **FIGS. 1** and **7**, a trolley **201** houses the counterweight pulleys **131**. The trolley slides up and down a guide of the support frame **12** as the pull cable **121** is pulled by the user **50**. The trolley **201** may have one or more pegs **202** projecting generally outwardly such that standard weightlifting plates **203** may be loaded onto the pegs **202**.

[0074] Alternatively, the counterweights **200** may be a weight stack arrangement, as shown in **FIG. 12**. The weight stack arrangement includes a plurality of plates **211** having axially aligned bores which slide along one or more guide shafts **212** connected to the support frame **12**. A carrier **213** houses the counterweight pulleys **131**. A pin **214** or other locking mechanism may be used to fix one or more of the plurality of plates **211** to the carrier **213**. Thus, when the pull cable **121** is pulled, the carrier **213** and any plates **211** fixed to the carrier **213** provide resistance to the user **50**.

[0075] While various aspects of the high-low pulley rack **100** were provided in the foregoing description, those skilled in the art may make modifications and alterations to these aspects without departing from the scope and spirit of the invention. For example, it is to be understood that this disclosure contemplates that, to the extent possible, one or more features of any aspect can be combined with one or more features of any other aspect. Accordingly, the foregoing description is intended to be illustrative rather than restrictive. The invention described hereinabove is defined by the appended claims and all changes to the invention that fall within the meaning and the range of equivalency of the claims are to be embraced within their scope.

THE INVENTION CLAIMED IS

1. A pulley rack for an exercise machine, the pulley rack comprising:
 - a support frame;
 - an upright extending generally vertically within the support frame;
 - a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame;
 - one or more guide pulleys mounted to the support frame;
 - a cable end assembly mounted to the upright; and
 - a pull cable having a fixed attachment end assembly and a pullable end freely passing through the cable end assembly;wherein the pull cable is routed through the cable end assembly, the counterweight pulleys, and guide pulleys such that a force exerted on the pullable end raises the counterweight, and
 - wherein a section of the pull cable extends from the pullable end through the cable end assembly and downwardly to one of the guide pulleys mounted below the cable end assembly.
2. The pulley rack of claim 1, wherein the cable end assembly is vertically slideable along the upright.
3. The pulley rack of claim 1, wherein the cable end assembly is lockable in a plurality of positions along the upright.
4. The pulley rack of claim 1, wherein the cable end assembly is lockable in any of a plurality of holes in the upright.
5. The pulley rack of claim 1, wherein the cable end assembly comprises a pivot pin permitting rotation of at least a portion of the cable end assembly about an axis parallel to the upright.
6. The pulley rack of claim 1, further comprising a bar catch mounted to the upright above the cable end assembly, the bar catch adapted to support a barbell at a predetermined height.

7. The pulley rack of claim 6, further comprising a safety spotter arm mounted to the upright above the cable end assembly, the safety spotter arm adapted to prevent the barbell from dropping below a second predetermined height.
8. The pulley rack of claim 6, wherein the cable end assembly is mounted to the upright at a bottom location of the upright,
wherein the barbell rests on the bar catch mounted above the cable end assembly, and
wherein the pullable end of the pull cable is affixed to the barbell such that force exerted vertically on the barbell raises the counterweight.
9. The pulley rack of claim 1, wherein the pull cable is routed through one of the guide pulleys between a first of the counterweight pulleys and a second of the counterweight pulleys.
10. A pulley rack for an exercise machine, the pulley rack comprising:
a support frame;
a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame;
one or more guide pulleys mounted to the support frame;
a cable end assembly moveably mounted to the upright;
a first cable section extending from a fixed connection at the cable end assembly to a first of the counterweight pulleys; and
a second cable section extending downwardly from a pullable connection at the cable end assembly around one of the guide pulleys and to the first of the counterweight pulleys;
wherein the counterweight is vertically moveable by a force exerted on the pullable connection of the second cable section; and
wherein movement of the cable end assembly along the upright does not move the counterweight.
11. The pulley rack of claim 10, wherein the first cable section extends upwardly from the fixed connection to one of the guide pulleys.
12. The pulley rack of claim 10, wherein the first cable section extends around a second of the counterweight pulleys between the cable end assembly and the first of the counterweight pulleys.

13. The pulley rack of claim 12, wherein the first cable section extends around one of the guide pulleys between the first of the counterweight pulleys and the second of the counterweight pulleys.

14. The pulley rack of claim 10, wherein the first cable section extends around one of the guide pulleys between the cable end assembly and the first of the counterweight pulleys.

15. The pulley rack of claim 10, further comprising a bar catch mounted to the upright above the cable end assembly, the bar catch adapted to support a barbell at a predetermined height.

16. The pulley rack of claim 15, further comprising a safety spotter arm mounted to the upright above the cable end assembly, the safety spotter arm adapted to prevent the barbell from dropping below a second predetermined height.

17. The pulley rack of claim 10, wherein the first cable section and the second cable section define a continuous length of cable.

18. A method of operating an exercise machine, comprising:

moving a cable end assembly along an upright of a support frame, wherein the cable end assembly has a fixed attachment to a first end of a pull cable, and wherein a second end of the pull cable is pullable through the cable end assembly; and

locking the cable end assembly in one of a plurality of positions along the upright;

wherein the pull cable, between the first end and the second end, extends downwardly from the cable end assembly and is routed through one or more guide pulleys mounted to the exercise machine and one or more counterweight pulleys mounted to a moveable counterweight; and

wherein moving the cable end assembly along the upright does not alter the position of a counterweight.

19. The method of claim 18, further comprising exerting a force on the second end of the pull cable to raise the counterweight, wherein the counterweight is raised regardless of the direction of the force exerted on the second end of the pull cable.

20. The method of claim 18, further comprising attaching a barbell to the second end of the pull cable, the barbell adapted to rest on at least one bar catch mounted to the upright.

AMENDED CLAIMS
received by the International Bureau on 19 April 2018 (19.04.2018)

THE INVENTION CLAIMED IS

1. A pulley rack for an exercise machine, the pulley rack comprising:
 - a support frame;
 - an upright extending generally vertically within the support frame;
 - a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame;
 - one or more guide pulleys mounted to the support frame;
 - a cable end assembly mounted to the upright; and
 - a pull cable having a fixed attachment end assembly and a pullable end freely passing through the cable end assembly;wherein the pull cable is routed through the cable end assembly, the counterweight pulleys, and guide pulleys such that a force exerted on the pullable end raises the counterweight,
 - wherein the fixed attachment end assembly of the pull cable is connected to the cable end assembly adjacent to a first vertical side of the upright, and
 - wherein a section of the pull cable extends from the pullable end through the cable end assembly and downwardly to one of the guide pulleys mounted below the cable end assembly along a second vertical side of the upright.
2. The pulley rack of claim 1, wherein the cable end assembly is vertically slideable along the upright.
3. The pulley rack of claim 1, wherein the cable end assembly is lockable in a plurality of positions along the upright.
4. The pulley rack of claim 1, wherein the cable end assembly is lockable in any of a plurality of holes in the upright.
5. The pulley rack of claim 1, wherein the cable end assembly comprises a pivot pin permitting rotation of at least a portion of the cable end assembly about an axis parallel to the upright.

6. The pulley rack of claim 1, further comprising a bar catch mounted to the upright above the cable end assembly, the bar catch adapted to support a barbell at a predetermined height.
7. The pulley rack of claim 6, further comprising a safety spotter arm mounted to the upright above the cable end assembly, the safety spotter arm adapted to prevent the barbell from dropping below a second predetermined height.
8. The pulley rack of claim 6, wherein the cable end assembly is mounted to the upright at a bottom location of the upright,
 - wherein the barbell rests on the bar catch mounted above the cable end assembly, and
 - wherein the pullable end of the pull cable is affixed to the barbell such that force exerted vertically on the barbell raises the counterweight.
9. The pulley rack of claim 1, wherein the pull cable is routed through one of the guide pulleys between a first of the counterweight pulleys and a second of the counterweight pulleys.
10. A pulley rack for an exercise machine, the pulley rack comprising:
 - a support frame;
 - a counterweight having one or more counterweight pulleys, the counterweight moveable in a vertical direction relative to the support frame;
 - one or more guide pulleys mounted to the support frame;
 - a cable end assembly moveably mounted to the upright;
 - a first cable section extending from a fixed connection at the cable end assembly along a first vertical side of the upright to a first of the counterweight pulleys; and
 - a second cable section extending downwardly from a pullable connection at the cable end assembly along a second vertical side of the upright around one of the guide pulleys and to the first of the counterweight pulleys;
 - wherein the counterweight is vertically moveable by a force exerted on the pullable connection of the second cable section; and
 - wherein movement of the cable end assembly along the upright does not move the counterweight.
11. The pulley rack of claim 10, wherein the first cable section extends upwardly from the fixed connection to one of the guide pulleys.

12. The pulley rack of claim 10, wherein the first cable section extends around a second of the counterweight pulleys between the cable end assembly and the first of the counterweight pulleys.

13. The pulley rack of claim 12, wherein the first cable section extends around one of the guide pulleys between the first of the counterweight pulleys and the second of the counterweight pulleys.

14. The pulley rack of claim 10, wherein the first cable section extends around one of the guide pulleys between the cable end assembly and the first of the counterweight pulleys.

15. The pulley rack of claim 10, further comprising a bar catch mounted to the upright above the cable end assembly, the bar catch adapted to support a barbell at a predetermined height.

16. The pulley rack of claim 15, further comprising a safety spotter arm mounted to the upright above the cable end assembly, the safety spotter arm adapted to prevent the barbell from dropping below a second predetermined height.

17. The pulley rack of claim 10, wherein the first cable section and the second cable section define a continuous length of cable.

18. A method of operating an exercise machine, comprising:
- moving a cable end assembly along an upright of a support frame, wherein the cable end assembly has a fixed attachment to a first end of a pull cable adjacent to a first vertical side of the upright, and wherein a second end of the pull cable is pullable through the cable end assembly; and
 - locking the cable end assembly in one of a plurality of positions along the upright;
 - wherein the pull cable, between the first end and the second end, extends downwardly from the cable end assembly along a second vertical side of the upright and is routed through one or more guide pulleys mounted to the exercise machine and one or more counterweight pulleys mounted to a moveable counterweight; and
 - wherein moving the cable end assembly along the upright does not alter the position of a counterweight.
19. The method of claim 18, further comprising exerting a force on the second end of the pull cable to raise the counterweight, wherein the counterweight is raised regardless of the direction of the force exerted on the second end of the pull cable.
20. The method of claim 18, further comprising attaching a barbell to the second end of the pull cable, the barbell adapted to rest on at least one bar catch mounted to the upright.




FIG. 1

2/12




FIG. 2

3/12




FIG. 3




FIG. 4




FIG. 5

6/12




FIG. 6

7/12




FIG. 7

8/12




FIG. 8

9/12




FIG. 9

10/12




FIG. 10




FIG. 11

12/12




FIG. 12

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2017/061228

A. CLASSIFICATION OF SUBJECT MATTER Int.Cl. A63B21/078 (2006.01) i According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) Int.Cl. A63B21/078 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Published examined utility model applications of Japan 1922-1996 Published unexamined utility model applications of Japan 1971-2018 Registered utility model specifications of Japan 1996-2018 Published registered utility model applications of Japan 1994-2018 Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5725459 A (REXACH, Marco L.) 1998.03.10, Column4 Line27-Column9 Line34, Figs.1-3,10 & WO	1-5, 10-11, 14, 17-19
Y	1997/041927 A1 & AU 2750497 A	6-9, 12-13, 15-16, 20
Y	US 2013/0184128 A1 (TOWLEY, Carl K.) 2013.07.18, Fig.9 & WO 2013/009749 A1 & EP 2731683 A1	6-8, 15-16, 20
Y	US 2016/0250514 A1 (GVOICH FITNESS SYSTEMS) 2016.09.01, Figs.1-7 (Family: none)	9, 12-13
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: “A” document defining the general state of the art which is not considered to be of particular relevance “E” earlier application or patent but published on or after the international filing date “L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) “O” document referring to an oral disclosure, use, exhibition or other means “P” document published prior to the international filing date but later than the priority date claimed “T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention “X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone “Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art “&” document member of the same patent family		
Date of the actual completion of the international search 06.02.2018	Date of mailing of the international search report 20.02.2018	
Name and mailing address of the ISA/JP Japan Patent Office 3-4-3, Kasumigaseki, Chiyoda-ku, Tokyo 100-8915, Japan	Authorized officer TANIGAKI, Keiji Telephone No. +81-3-3581-1101 Ext. 3241	2D 3010