



(22) Date de dépôt/Filing Date: 2012/11/27

(41) Mise à la disp. pub./Open to Public Insp.: 2013/06/01

(45) Date de délivrance/Issue Date: 2016/05/31

(30) Priorité/Priority: 2011/12/01 (EP11191580.7)

(51) Cl.Int./Int.Cl. *H04W 8/22* (2009.01),
H04B 5/00 (2006.01)


(72) Inventeurs/Inventors:
ZHU, LIZHONG, CA;
ZHU, LIBO, CA

(73) Propriétaire/Owner:
BLACKBERRY LIMITED, CA

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : APPAREIL MOBILE DE COMMUNICATION SANS FIL AYANT UN CAPTEUR DE COMMUNICATIONS EN CHAMP PROCHE ET UN CAPTEUR MAGNETIQUE ET PROCEDES CONNEXES

(54) Title: MOBILE WIRELESS COMMUNICATIONS DEVICE HAVING NFC SENSOR AND MAGNETIC SENSOR AND ASSOCIATED METHODS



(57) Abrégé/Abstract:

A mobile wireless communications device (30) includes a near field communications (NFC) device (32), and a magnetic sensor (31). A processor (33) is coupled to the NFC device and the magnetic sensor, and is switchable between an active mode and an idle mode based upon the magnetic sensor. The processor is configured to remain in the active mode based upon communication via the NFC device irrespective of the magnetic sensor.

42022-CA-PAT

**MOBILE WIRELESS COMMUNICATIONS DEVICE HAVING NFC SENSOR
AND MAGNETIC SENSOR AND ASSOCIATED METHODS**

Abstract of the Disclosure

A mobile wireless communications device (30) includes a near field communications (NFC) device (32), and a magnetic sensor (31). A processor (33) is coupled to the NFC device and the magnetic sensor, and is switchable between an active mode and an idle mode based upon the magnetic sensor. The processor is configured to remain in the active mode based upon communication via the NFC device irrespective of the magnetic sensor.

42022-CA-PAT

**MOBILE WIRELESS COMMUNICATIONS DEVICE HAVING NFC SENSOR AND
MAGNETIC SENSOR AND ASSOCIATED METHODS**

Technical Field

[0001] The present disclosure relates to the field of mobile wireless communications devices, and, more particularly, to mobile wireless communications having NFC sensors and magnetic sensors.

Background

[0002] Mobile wireless communications systems continue to grow in popularity and have become an integral part of both personal and business communications. For example, cellular telephones allow users to place and receive voice calls almost anywhere they travel. Moreover, as cellular telephone technology has increased, so too has the functionality of cellular devices and the different types of devices available to users. For example, many cellular devices now incorporate personal digital assistant (PDA) features such as calendars, address books, task lists, etc. Moreover, such multi-function devices may also allow users to wirelessly send and receive electronic mail (email) messages and access the Internet via a cellular network and/or a wireless local area network (WLAN), for example.

[0003] Some cellular devices incorporate contactless card technology and/or Near Field Communication chips. Near Field Communication technology is commonly used for contactless short-range communications based on radio frequency identification (RFID) standards, using magnetic field induction to enable communication

42022-CA-PAT

between electronic devices, including mobile wireless communications devices. These short-range applications include payment and ticketing, electronic keys, identification, device set-up service and similar information sharing. This short-range high frequency wireless communication technology exchanges data between devices over a short distance, such as only a few centimeters.

[0004] In devices with multiple means of wireless communications, issues may sometimes arise when a signal intended for one wireless receiver is received and acted upon by another wireless receiver. This may lead to the device functioning in an undesired manner. As such, further advances in mobile wireless communications device technology are still needed.

Brief Description of the Drawings

[0005] FIG. 1 is a block diagram showing a mobile wireless communications device of the present disclosure in proximity to and communicating with another mobile wireless communications device via near field communications (NFC).

[0006] FIG. 2 is a more detailed block diagram showing a mobile wireless communications device of the present disclosure in proximity to and communicating with another mobile wireless communications device via near field communications (NFC).

42022-CA-PAT

[0007] FIG. 3 is a flowchart illustrating a method of operating a mobile wireless communications device according to the present disclosure.

[0008] FIG. 4 is a schematic block diagram illustrating components of a mobile wireless communications device in accordance with an example embodiment of the present disclosure.

Detailed Description

[0009] The present description is made with reference to the accompanying drawings, in which various embodiments are shown. However, many different embodiments may be used, and thus the description should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete. Like numbers refer to like elements throughout, and prime notation is used to indicate similar elements or steps in alternative embodiments.

[0010] Generally speaking, a mobile wireless communications device may include a near field communications (NFC) device, and a magnetic sensor. A processor may be coupled to the NFC device and the magnetic sensor, and may be switchable between an active mode and an idle mode based upon the magnetic sensor. The processor may be configured to remain in the active mode based upon communication via the NFC device irrespective of the magnetic sensor.

[0011] This mobile wireless communications device advantageously allows the processor to switch to the idle mode based upon the magnetic sensor detecting a magnetic source, such as when the mobile wireless communications device is

42022-CA-PAT

placed into a holster having a magnet, while not inadvertently switching to the idle mode when "swiped" near another mobile wireless communications device (and thus, a magnet in the speaker of that device) to perform NFC communications.

[0012] As will be readily understood by those of skill in the art, the NFC device has a greater operating range than an operating range of the magnetic sensor. Therefore, the NFC device can detect NFC signals at a greater distance than the magnetic sensor can detect magnetic signals.

[0013] The magnetic sensor may be configured to generate an idle signal based upon detection of a magnetic source, and the processor may be switchable between the active mode and the idle mode based upon the idle signal. The processor may be configured to remain in the active mode based upon communication via the NFC device irrespective of idle signal.

[0014] In addition, a display may be coupled to the processor, and the processor may be configured to activate the display when in the active mode, and to deactivate the display when in the idle mode. The processor may be configured to operate according to a first device indication profile while in the active mode, and to operate according to a second device indication profile while in the idle mode.

[0015] Further, an input device may be coupled to the processor, and the processor may be configured to cooperate with the input device to perform at least one device function when in the active mode, and to ignore the input device when in the idle mode. The active mode may be a high power consumption mode, and the idle mode may be a low power consumption mode.

42022-CA-PAT

[0016] A portable housing may carry the NFC device, the magnetic sensor, and the processor. Additionally, a cellular transceiver may be coupled to the processor and configured to perform at least one cellular communications function.

[0017] A method aspect may be directed to a method of operating a mobile wireless communications device comprising a near field communications (NFC) device, a magnetic sensor, a processor coupled to the NFC device and the magnetic sensor, and being switchable between an active mode and an idle mode based upon the magnetic sensor. The method comprises causing the processor to remain in the active mode based upon communication via the NFC device irrespective of the magnetic sensor.

[0018] With initial reference to FIG. 1, a communications system **5** including a mobile wireless communications device **30** according to the present disclosure is now described. Here, the mobile wireless communications device **30** includes a portable housing **34** carrying a processor **33** that is coupled to a magnetic sensor **31** and a NFC device **32**. The processor **33** is switchable between an active mode and an idle mode. In some applications, the active mode is a high power consumption mode, and the idle mode is a low power consumption mode. As will be explained below, the active mode may include fully powering other components of the mobile wireless communications device **30**, while the idle mode may include deactivating such components. Additionally, the active mode may include operating the processor **33** at a peak clock speed, while the idle mode may include operating the processor at a slower clock speed.

[0019] The magnetic sensor **31** may be a Hall effect sensor, for example, and is used to detect a magnetic source. A holster may be used to carry the mobile wireless communications device **30**, and may include a permanent magnet therein. When mobile wireless communications device **30** is placed in the holster, and thus adjacent the permanent magnet, the magnetic sensor **31** senses the magnet, and the processor **30** then switches to the idle mode to conserve power.

[0020] With respect to the NFC device **32**, Near Field Communication (NFC) technology is an extension of the ISO 14443 proximity-card standard as a contactless card, RF ID standard that incorporates the interface of a smart card and a reader into one device. A NFC device typically includes an NFC integrated circuit (IC) chip that communicates with both existing ISO 14443 smart cards and readers and other NFC devices and is compatible with any existing contactless infrastructure. The NFC IC chips use magnetic field induction where two loop antennas are located near each other and form an air-core transformer. The technology operates on the unlicensed radio frequency ISM band of about 13.56 MHz and has a bandwidth of about 2 MHz. The working distance is usually about 0 to 20 centimeters and a user of the NFC device touches another NEC device or tag to initiate communication, with data rates ranging from 106 to about 424 kbit/s. Further details are set forth in the Mobile NFC Technical Guidelines, Version 2.0, November 2007 by GSMA.

[0021] The communications system **5** also includes a second mobile wireless communications device **10**. This second mobile wireless communications device **10** includes a speaker having a

magnet **11** therein, as well as a NFC device **12**. The second mobile wireless communications device **10** is configured to communicate with the first mobile wireless communications device **30** via the NFC device **12**.

[0022] Turning back to the first mobile wireless communications device **30**, the processor **33** is configured to remain in the active mode based upon NFC communications irrespective of the magnetic sensor. Therefore, so long as the first mobile wireless communications device **30** is engaged in NFC communications with the second mobile wireless communications device **10**, the processor **33** will not switch to the idle mode, despite the magnetic sensor **31** detecting a magnetic source (e.g. the magnet **11** in the speaker of the second mobile wireless communications device **10**).

[0023] Since NFC communications take place with the participating devices in close proximity to each other, the design of the mobile wireless communications device **30** helps eliminate a situation where the magnetic sensor **31** detects the magnet **11** in the speaker of the second mobile wireless communications device **10**, the processor **33** then mistakenly interprets this as meaning the device has been placed in a holster, and switches into the idle mode at an undesired time. Existing mobile wireless communications devices may be subject to such an issue, which would prove frustrating to a user.

[0024] With reference to FIG. 2, a more detailed embodiment of the communications system **5'** is now described. Here, the first mobile wireless communications device **30'** also includes a cellular transceiver **36'**, display **34'**, and input device **35'** coupled to the processor **33'**. The processor **33'** is configured to cooperate with the cellular transceiver **36'** for performing

cellular communications, such as placing or receiving voice calls.

[0025] The display **34'** may be a typical liquid crystal display (LCD) or organic light emitting diode display (OLED), as will be appreciated by those of skill in the art. The input device **35'** may be formed from one device, such as a keypad, button, touch sensor, thumbwheel, or trackball, or may be formed from a plurality of such devices. In addition, the display **34'** may be a touch sensitive display, and may function as all or part of the input device **35'**.

[0026] Here, the processor **33'** is configured to activate the display **34'** when in the active mode, but to deactivate the display when in the idle mode. In addition, the processor **33'** is configured to operate according to a first indication profile when in the active mode, and to operate according to a second indication profile when in the idle mode. An indication profile specifies how the mobile wireless communications device **30'** indicates a user of incoming messages, e-mails, and voice calls. For example, an indication profile may specify that incoming voice calls are indicated by the playing of an audible ring tone, or that incoming voice calls are indicated by activation of a vibration unit. Further, the processor **33'** may be configured to perform at least one device function based upon the input device **35'** when in the active mode, but to ignore the input device when in the idle mode.

[0027] The switching of the processor **33'** between the active mode and the idle mode proceeds similarly as described above with reference to the mobile wireless communications device **30**. The magnetic sensor **31'** cooperates with the processor **33'** to generate an idle signal based upon detection

42022-CA-PAT

of a magnetic source. The processor **33'** is configured to remain in the active mode based upon NFC communications irrespective of the idle signal.

[0028] With reference to the flowchart **40** of FIG. 3, a method of operating the mobile wireless communications devices **30, 30'** discussed above is now described. After the start (Block **41**), the processor operates in the active mode (Block **42**). At Block **43**, if a magnetic source is detected, operation proceeds to Block **44**. If a magnetic source is not detected, operation of the processor proceeds in the active mode as the method proceeds back to Block **42**. If a magnetic source is detected, at Block **44**, it is determined whether NFC communications are detected. If NFC communications are detected, then the method proceeds back to Block **42**, and the processor continues operating in the active mode. If NFC communications are not detected, then the method proceeds to Block **45**, and the processor switches to the idle mode. Block **46** indicates the end of the method.

[0029] Example components of a hand-held mobile wireless communications device **1000** that may be used in accordance with the present disclosure are further described in the example below with reference to FIG. 4. The device **1000** illustratively includes a housing **1200**, a keypad **1400** and an output device **1600**. The output device shown is a display **1600**, which may comprise a full graphic LCD. In some example embodiments, display **1600** may comprise a touch-sensitive input and output device. Other types of output devices may alternatively be utilized. A processing device **1800** is contained within the housing **1200** and is coupled between the keypad **1400** and the display **1600**. The processing device **1800** controls the

42022-CA-PAT

operation of the display **1600**, as well as the overall operation of the mobile device **1000**, in response to actuation of keys on the keypad **1400** by the user. In some example embodiments, keypad **1400** may comprise a physical keypad or a virtual keypad (e.g., using a touch-sensitive interface) or both.

[0030] The housing **1200** may be elongated vertically, or may take on other sizes and shapes (including clamshell housing structures). The keypad **1400** may include a mode selection key, or other hardware or software for switching between text entry and telephony entry.

[0031] In addition to the processing device **1800**, other parts of the mobile device **1000** are shown schematically in FIG. 4. These include a communications subsystem **1001**; a short-range communications subsystem **1020**; the keypad **1400** and the display **1600**, along with other input/output devices **1060**, **1080**, **1100** and **1120**; as well as memory devices **1160**, **1180** and various other device subsystems **1201**. The mobile device **1000** may comprise a two-way RF communications device having voice and data communications capabilities. In addition, the mobile device **1000** may have the capability to communicate with other computer systems via the Internet.

[0032] Operating system software executed by the processing device **1800** may be stored in a persistent store, such as the flash memory **1160**, but may be stored in other types of memory devices, such as a read only memory (ROM) or similar storage element. In addition, system software, specific device applications, or parts thereof, may be temporarily loaded into a volatile store, such as the random access memory (RAM) **1180**.

42022-CA-PAT

Communications signals received by the mobile device may also be stored in the RAM **1180**.

[0033] The processing device **1800**, in addition to its operating system functions, enables execution of software applications **1300A-1300N** on the device **1000**. A predetermined set of applications that control basic device operations, such as data and voice communications **1300A** and **1300B**, may be installed on the device **1000** during manufacture. In addition, a personal information manager (PIM) application may be installed during manufacture. The PIM may be capable of organizing and managing data items, such as e-mail, calendar events, voice mails, appointments, and task items. The PIM application may also be capable of sending and receiving data items via a wireless network **1401**. The PIM data items may be seamlessly integrated, synchronized and updated via the wireless network **1401** with the device user's corresponding data items stored or associated with a host computer system.

[0034] Communication functions, including data and voice communications, are performed through the communications subsystem **1001**, and possibly through the short-range communications subsystem. The communications subsystem **1001** includes a receiver **1500**, a transmitter **1520**, and one or more antennas **1540** and **1560**. In addition, the communications subsystem **1001** also includes a processing module, such as a digital signal processor (DSP) **1580**, and local oscillators (LOs) **1601**. The specific design and implementation of the communications subsystem **1001** is dependent upon the communications network in which the mobile device **1000** is intended to operate. For example, a mobile device **1000** may

include a communications subsystem **1001** designed to operate with the Mobitex™, Data TAC™ or General Packet Radio Service (GPRS) mobile data communications networks, and also designed to operate with any of a variety of voice communications networks, such as AMPS, TDMA, CDMA, WCDMA, PCS, GSM, EDGE, etc. Other types of data and voice networks, both separate and integrated, may also be utilized with the mobile device **1000**. The mobile device **1000** may also be compliant with other communications standards such as 3GSM, 3G, UMTS, 4G, etc.

[0035] Network access requirements vary depending upon the type of communication system. For example, in the Mobitex and DataTAC networks, mobile devices are registered on the network using a unique personal identification number or PIN associated with each device. In GPRS networks, however, network access is associated with a subscriber or user of a device. A GPRS device therefore utilizes a subscriber identity module, commonly referred to as a SIM card, in order to operate on a GPRS network.

[0036] When required network registration or activation procedures have been completed, the mobile device **1000** may send and receive communications signals over the communication network **1401**. Signals received from the communications network **1401** by the antenna **1540** are routed to the receiver **1500**, which provides for signal amplification, frequency down conversion, filtering, channel selection, etc., and may also provide analog to digital conversion. Analog-to-digital conversion of the received signal allows the DSP **1580** to perform more complex communications functions, such as demodulation and decoding. In a similar manner, signals to be transmitted to the network **1401** are processed (e.g. modulated

42022-CA-PAT

and encoded) by the DSP **1580** and are then provided to the transmitter **1520** for digital to analog conversion, frequency up conversion, filtering, amplification and transmission to the communication network **1401** (or networks) via the antenna **1560**.

[0037] In addition to processing communications signals, the DSP **1580** provides for control of the receiver **1500** and the transmitter **1520**. For example, gains applied to communications signals in the receiver **1500** and transmitter **1520** may be adaptively controlled through automatic gain control algorithms implemented in the DSP **1580**.

[0038] In a data communications mode, a received signal, such as a text message or web page download, is processed by the communications subsystem **1001** and is input to the processing device **1800**. The received signal is then further processed by the processing device **1800** for an output to the display **1600**, or alternatively to some other auxiliary I/O device **1060**. A device user may also compose data items, such as e-mail messages, using the keypad **1400** and/or some other auxiliary I/O device **1060**, such as a touchpad, a rocker switch, a thumb-wheel, track ball, or some other type of input device. The composed data items may then be transmitted over the communications network **1401** via the communications subsystem **1001**.

[0039] In a voice communications mode, overall operation of the device is substantially similar to the data communications mode, except that received signals are output to a speaker **1100**, and signals for transmission are generated by a microphone **1120**. Alternative voice or audio I/O subsystems, such as a voice message recording subsystem, may also be

42022-CA-PAT

implemented on the device **1000**. In addition, the display **1600** may also be utilized in voice communications mode, for example to display the identity of a calling party, the duration of a voice call, or other voice call related information.

[0040] The short-range communications subsystem enables communication between the mobile device **1000** and other proximate systems or devices, which need not necessarily be similar devices. For example, the short-range communications subsystem may include an infrared device and associated circuits and components, or a Bluetooth™ communications module to provide for communication with similarly-enabled systems and devices.

[0041] Many modifications and other embodiments of the present disclosure will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the present disclosure is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.

THAT WHICH IS CLAIMED IS:

1. A mobile wireless communications device comprising:

a near field communications (NFC) device;

a magnetic sensor configured to generate an idle signal based upon detection of a magnetic source; and

a processor coupled to the NFC device and the magnetic sensor, and being switchable between an active mode and an idle mode based upon the idle signal;

the processor configured to remain in the active mode based upon communication via the NFC device irrespective of the idle signal.

2. The mobile wireless communications device of Claim 1, wherein the NFC device has a greater operating range than an operating range of the magnetic sensor.

3. The mobile wireless communications device of Claim 1 or Claim 2, further comprising a display coupled to the processor; and wherein the processor is configured to activate the display when in the active mode, and to deactivate the display when in the idle mode.

4. The mobile wireless communications device of any one of Claims 1 to 3, wherein the processor is configured to operate according to a first device indication profile while in the active mode, and to

operate according to a second device indication profile while in the idle mode.

5. The mobile wireless communications device of any one of Claims 1 to 4, further comprising an input device coupled to the processor; and wherein the processor is configured to cooperate with the input device to perform at least one device function when in the active mode, and to ignore the input device when in the idle mode.

6. The mobile wireless communications device of any one of Claims 1 to 5, wherein the active mode is a high power consumption mode, and wherein the idle mode is a low power consumption mode.

7. The mobile wireless communications device of any one of Claims 1 to 6, further comprising a portable housing carrying the NFC device, the magnetic sensor, and the processor.

8. The mobile wireless communications device of any one of Claims 1 to 7, further comprising a cellular transceiver coupled to the processor and configured to perform at least one cellular communications function.

9. A method of operating a mobile wireless communications device comprising a near field communications (NFC) device, a magnetic sensor configured to generate an idle signal based upon detection of a magnetic source, a processor coupled to the NFC device and the magnetic sensor, and being switchable between an

active mode and an idle mode based upon the idle signal, the method comprising:

causing the processor to remain in the active mode based upon communication via the NFC device irrespective of the idle signal.

10. The method of Claim 9, wherein the NFC device has a greater operating range than an operating range of the magnetic sensor.

11. The method of Claim 9 or Claim 10, further comprising operating the processor to activate a display when in the active mode, and to deactivate the display when in the idle mode.

12. The method of any one of Claims 9 to 11, further comprising operating the processor according to a first device indication profile while in the active mode, and operating the processor according to a second device indication profile while in the idle mode.

13. The method of any one of Claims 9 to 12, further comprising operating the processor to cooperate with an input device to perform at least one device function when in the active mode, and to ignore the input device when in the idle mode.

14. The method of any one of Claims 9 to 13, wherein the active mode is a high power consumption mode, and wherein the idle mode is a low power consumption mode.

15. A non-transitory machine readable medium having tangibly stored thereon executable instructions that, when executed by a processor, cause the processor to perform the method of any one of Claims 9 to 14.

1/4




FIG. 1

2/4




FIG. 2

3/4




FIG. 3

4/4




FIG. 4

