



US 20170036799A1

(19) **United States**(12) **Patent Application Publication**
Schmal et al.(10) **Pub. No.: US 2017/0036799 A1**(43) **Pub. Date: Feb. 9, 2017**(54) **METHOD OF FORMING A CARTON WITH
ARTICLE PROTECTION FEATURE****Publication Classification**(51) **Int. Cl.**

B65B 61/00 (2006.01)
B65D 5/02 (2006.01)
B65D 5/468 (2006.01)
B65B 21/14 (2006.01)
B65B 5/02 (2006.01)
B65B 5/06 (2006.01)
B65B 7/20 (2006.01)
B65D 71/36 (2006.01)
B65D 25/10 (2006.01)

(52) **U.S. Cl.**


CPC **B65B 61/00** (2013.01); **B65D 71/36**
(2013.01); **B65D 5/0227** (2013.01); **B65D**
5/4608 (2013.01); **B65D 25/103** (2013.01);
B65B 5/024 (2013.01); **B65B 5/06** (2013.01);
B65B 7/20 (2013.01); **B65B 21/14** (2013.01)

(71) Applicant: **Graphic Packaging International,
Inc.**, Atlanta, GA (US)(72) Inventors: **Michael R. Schmal**, Atlanta, GA (US);
O'Neal Alexander, Covington, GA
(US); **Mark Baldino**, Marietta, GA
(US); **Michael Cerio**, Kennesaw, GA
(US); **John Murdick Holley, JR.**,
Lawrenceville, GA (US); **Frank N.**
Moncrief, Acworth, GA (US);
Raymond S. Kastanek, Mead, CO
(US); **Colin Ford**, Woodstock, GA (US)(21) Appl. No.: **15/295,238**(22) Filed: **Oct. 17, 2016****Related U.S. Application Data**(60) Continuation of application No. 14/620,595, filed on
Feb. 12, 2015, now Pat. No. 9,499,319, which is a
division of application No. 13/419,740, filed on Mar.
14, 2012, now Pat. No. 9,284,084.(60) Provisional application No. 61/518,504, filed on May
6, 2011, provisional application No. 61/572,638, filed
on Jul. 19, 2011, provisional application No. 61/627,
249, filed on Oct. 7, 2011, provisional application No.
61/548,779, filed on Oct. 19, 2011, provisional appli-
cation No. 61/570,044, filed on Dec. 13, 2011.

(57)

ABSTRACT

A method of forming a carton. The method includes obtain-
ing a blank having at least one panel and at least one article
protection flap foldably connected to the at least one panel.
The method includes positioning the at least one panel to at
least partially form an interior space of the carton, loading
at least one article in the interior space, and folding the at
least one article protection flap relative to the at least one
panel after the loading the at least one article. The folding
includes moving the article protection flap from a first
position that is substantially parallel to the at least one panel
to a second position wherein the article protection flap is
folded relative to the at least one panel.








FIG. 2




FIG. 3




FIG. 4




FIG. 4A




FIG. 5




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7










FIG. 8A






FIG. 10A









FIG. 10B














FIG. 15




FIG. 16




FIG. 17




FIG. 17A




FIG. 18




FIG. 19




FIG. 20




FIG. 20A

FIG. 21




FIG. 22




FIG. 23




FIG. 24

FIG. 25




FIG. 26




FIG. 27




FIG. 27A




FIG. 27B




FIG. 28




FIG. 29




FIG. 30

METHOD OF FORMING A CARTON WITH ARTICLE PROTECTION FEATURE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 14/620,595, filed Feb. 12, 2015, which is a divisional of U.S. patent application Ser. No. 13/419,740, filed Mar. 14, 2012, which claims the benefit of U.S. Provisional Application No. 61/518,504, filed May 6, 2011, U.S. Provisional Application No. 61/572,638, filed Jul. 19, 2011, U.S. Provisional Application No. 61/627,249, filed Oct. 7, 2011, U.S. Provisional Application No. 61/548,779, filed Oct. 19, 2011, and U.S. Provisional Application No. 61/570,044, filed Dec. 13, 2011.

INCORPORATION BY REFERENCE

[0002] The entire contents of U.S. patent application Ser. No. 14/620,595, filed Feb. 12, 2015, U.S. patent application Ser. No. 13/419,740, filed Mar. 14, 2012, U.S. Provisional Application No. 61/518,504, filed May 6, 2011, U.S. Provisional Application No. 61/572,638, filed Jul. 19, 2011, U.S. Provisional Application No. 61/627,249, filed Oct. 7, 2011, U.S. Provisional Application No. 61/548,779, filed Oct. 19, 2011, and U.S. Provisional Application No. 61/570,044, filed Dec. 13, 2011, are hereby incorporated by reference as if presented herein in their entirety.

BACKGROUND OF THE DISCLOSURE

[0003] The present disclosure generally relates to cartons for holding beverage containers or other types of articles. More specifically, the present disclosure relates to cartons having an article protection feature and/or article protection flap that protects the containers or articles from breakage.

SUMMARY OF THE DISCLOSURE

[0004] In general, one aspect of the disclosure is directed to a carton for containing at least one article. The carton comprises at least one panel at least partially forming an interior of the carton. At least one article protection flap is for protecting the at least one article. The at least one article protection flap is foldably connected to the at least one panel and moveable between a first position that is substantially parallel to the at least one panel and a second position wherein the article protection flap is folded relative to the at least one panel. The article protection flap has features for preventing folding of the article protection flap from the second position to the first position.

[0005] In another aspect, the disclosure is generally directed to a blank for forming a carton for containing at least one article. The blank comprises at least one panel for at least partially forming an interior of the carton formed from the blank. At least one article protection flap is for protecting the at least one article. The at least one article protection flap is foldably connected to the at least one panel and moveable between a first position that is substantially parallel to the at least one panel and a second position wherein the article protection flap is folded relative to the at least one panel. The article protection flap has features for preventing folding of the article protection flap from the second position to the first position in the carton formed from the blank.

[0006] In another aspect, the disclosure is generally directed to a method of forming a carton. The method comprises obtaining a blank comprising at least one panel and at least one article protection flap foldably connected to the at least one panel. The method comprises positioning the at least one panel to at least partially form an interior space of the carton, loading at least one article in the interior space, and folding the at least one article protection flap relative to the at least one panel after the loading the at least one article. The folding comprises moving the article protection flap from a first position that is substantially parallel to the at least one panel to a second position wherein the article protection flap is folded relative to the at least one panel.

[0007] In another aspect, the disclosure is generally directed to a carton for containing at least one article. The carton comprises a plurality of panels that extends at least partially around an interior of the carton. At least two end flaps are respectively foldably connected to respective panels of the plurality of panels. The end flaps are for being at least partially overlapped to close an end of the carton. At least one article protection feature is for protecting the at least one article. The at least one article protection feature is positioned between the at least two end flaps.

[0008] In another aspect, the disclosure is generally directed to a blank for forming a carton for containing at least one article. The blank comprises a plurality of panels for extending at least partially around an interior of the carton formed from the blank. At least two end flaps respectively foldably connected to respective panels of the plurality of panels. The end flaps are for being at least partially overlapped to close an end of the carton formed from the blank. At least one article protection feature is for protecting the at least one article. The at least one article protection feature is for being positioned between the at least two end flaps.

[0009] In another aspect, the disclosure is generally directed to a method of forming a carton for containing at least one article. The method comprises obtaining a blank comprising a plurality of panels and at least two end flaps respectively foldably connected to a respective panel of the plurality of panels. The method comprises positioning the plurality of panels to form an interior space of the carton, loading at least one article in the interior space, at least partially overlapping the at least two end flaps to close an end of the carton, and forming an article protection feature that is positioned between the at least two end flaps.

[0010] In another aspect, the disclosure is generally directed to a method of forming a carton. The method comprises obtaining a blank comprising a panel and at least one article protection flap foldably connected to the panel. The method comprises positioning at least two articles to be in contact with the panel and folding the at least one article protection flap relative to the panel after the positioning the at least two articles. The folding comprises moving the article protection flap from a first position that is substantially parallel to the panel to a second position wherein the article protection flap is folded relative to the panel.

[0011] In another aspect, the disclosure is generally directed to a carton for containing at least one article. The carton comprises at least one panel at least partially forming an interior of the carton. At least two end flaps are at least partially overlapped to at least partially close the interior of the carton. At least one article protection feature is for protecting the at least one article. The at least one article

protection feature is positioned between the at least two end flaps. At least one article protection flap is for protecting the at least one article. The at least one article protection flap is foldably connected to the at least one panel and is moveable between a first position that is substantially parallel to the at least one panel and a second position wherein the article protection flap is folded relative to the at least one panel.

[0012] In another aspect, the disclosure is generally directed to a method of forming a carton. The method comprises obtaining a blank comprising at least one panel, at least one article protection flap foldably connected to the at least one panel, and at least two end flaps. The method comprises positioning the at least one panel to at least partially form an interior space of the carton, loading at least one article in the interior space, at least partially overlapping the at least two end flaps to close and end of the carton, forming an article protection feature that is positioned between the at least two end flaps, and folding the at least one article protection flap relative to the at least one panel after the loading the at least one article. The folding comprises moving the article protection flap from a first position that is substantially parallel to the at least one panel to a second position wherein the article protection flap is folded relative to the at least one panel.

[0013] In another aspect, the present disclosure is generally directed to a carton having at least one protection feature.

[0014] In another aspect, the present disclosure is generally directed to a blank for forming a carton having at least one protection feature.

[0015] In another aspect, the present disclosure is generally directed to a method of forming a carton having at least one protection feature for protecting articles held in the carton from breakage.

[0016] Other aspects, features, and details of the present disclosure can be more completely understood by reference to the following detailed description of exemplary embodiments taken in conjunction with the drawings and from the appended claims.

[0017] Those skilled in the art will appreciate the above stated advantages and other advantages and benefits of various additional embodiments reading the following detailed description of the embodiments with reference to the below-listed drawing figures. Further, the various features of the drawings discussed below are not necessarily drawn to scale. Dimensions of various features and elements in the drawings may be expanded or reduced to more clearly illustrate the embodiments of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1 is a plan view of an exterior surface of a blank for forming a carton according to a first embodiment of the disclosure.

[0019] FIG. 2 is an end perspective of the partially assembled carton of the first embodiment.

[0020] FIG. 3 is an end view similar to FIG. 2 with articles added to the partially assembled carton.

[0021] FIG. 4 is a view similar to FIG. 3 but showing the carton further assembled.

[0022] FIG. 4A is a view similar to FIG. 4 but showing alternative features of the carton.

[0023] FIG. 5 is an enlarged portion view of FIG. 4.

[0024] FIG. 5A is a view similar to FIG. 5 but showing alternative features of the carton.

[0025] FIG. 5B is a cross-section taken along the plane 5B-5B of FIG. 5A.

[0026] FIG. 5C is a view similar to FIG. 5 but showing alternative features of the carton.

[0027] FIG. 6 is a side perspective showing the carton of FIG. 5 further assembled.

[0028] FIG. 7 is an end view showing the carton of FIG. 6 further assembled.

[0029] FIG. 8 is an end view showing the carton further assembled.

[0030] FIG. 8A is an end view of a partially assembled carton of the first embodiment with the article protection flaps in the second position.

[0031] FIG. 9 is a cross-section taken along the plane 9-9 of FIG. 8.

[0032] FIG. 9A is a cross-section taken along the plane 9A-9A of FIG. 8.

[0033] FIG. 9B is a view similar to FIG. 9 but showing alternative features of the carton.

[0034] FIG. 9C is a view similar to FIG. 9A but showing alternative features of the carton.

[0035] FIG. 10A is a top plan view of an enlarged portion of a bottom panel of FIG. 1 showing an article protection flap in a first position.

[0036] FIG. 10B is a top plan view of the article protection flap of FIG. 10A in a second position.

[0037] FIG. 10C is a cross-section taken along the plane 10C-10C of FIG. 10B.

[0038] FIG. 10D is a view similar to FIG. 10A but showing alternative features of the article protection flap.

[0039] FIG. 10E is a view similar to FIG. 10B but showing the article protection flap of FIG. 10D.

[0040] FIG. 10F is a cross-section taken along the plane 10F-10F of FIG. 10E.

[0041] FIG. 11 is a plan view of a system for activating the article protection flaps of one embodiment of the disclosure.

[0042] FIG. 12 is an enlarged portion of FIG. 11.

[0043] FIG. 13 is a partial schematic view of a system for activating the article protection flaps of an alternative embodiment of the disclosure.

[0044] FIG. 14 is a partial schematic view of a system for activating the article protection flaps of an alternative embodiment of the disclosure.

[0045] FIG. 15 is a plan view of a blank for forming a carton according to an alternative embodiment of the disclosure.

[0046] FIG. 16 is a plan view of a blank for forming a carton according to an alternative embodiment of the disclosure.

[0047] FIG. 17 is a plan view of a blank for forming a carton according to an alternative embodiment of the disclosure.

[0048] FIG. 17A is an enlarged portion of the bottom panel of FIG. 17 showing an article protection flap.

[0049] FIG. 18 is a plan view of a bottom panel of the carton of the embodiment of FIG. 17 with the article protection flaps in a second position.

[0050] FIG. 19 is an end view of a partially assembled carton of the embodiment of FIG. 17 with the article protection flaps in the second position.

[0051] FIG. 20 is a plan view of a blank for forming a carton according to an alternative embodiment of the disclosure.

[0052] FIG. 20A is an enlarged portion of the bottom panel of FIG. 20 showing an article protection flap.

[0053] FIG. 21 is a plan view of an exterior surface of a bottom panel of a carton according to an alternative embodiment of the disclosure with articles contained in the carton shown in hidden lines.

[0054] FIG. 22 is a perspective view of an interior surface of the bottom panel of the carton of the embodiment of FIG. 21 showing article protection flaps.

[0055] FIG. 23 is a perspective view of the interior surface of the bottom panel of the carton of the embodiment of FIG. 21 showing the article protection flaps in a second position.

[0056] FIG. 24 is a plan view of an exterior surface of a blank for forming a carton according to an alternative embodiment of the disclosure.

[0057] FIGS. 25-27 are various views of forming the carton according to the embodiment of FIG. 24.

[0058] FIG. 27A is a cross-section taken along the plane 27A-27A of FIG. 27.

[0059] FIG. 27B is a cross-section taken along the plane 27B-27B of FIG. 27.

[0060] FIG. 28 is a plan view of an exterior surface of a blank for forming a carton according to an alternative embodiment of the disclosure.

[0061] FIG. 29 is a plan view of an exterior surface of a blank for forming a carton according to an alternative embodiment of the disclosure.

[0062] FIG. 30 is a perspective view of a carton according to the embodiment of FIG. 29.

[0063] FIGS. 31A-31C are various views of a blank and carton according to an alternative embodiment.

[0064] FIGS. 32A-32C are various views of a blank and carton according to an alternative embodiment.

[0065] FIGS. 33A-33C are various views of a blank and carton according to an alternative embodiment of the disclosure.

[0066] Corresponding parts are designated by corresponding reference numbers throughout the drawings.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

[0067] The present disclosure generally relates to cartons that contain a single article or a plurality of articles such as containers, bottles, cans, etc., and protection features of such cartons that protect the article or articles or containers from breakage, damage, or deformation. The article(s) can be used for packaging food and beverage products, for example, or any other item. The article(s) can be made from materials suitable in composition for packaging the particular food or beverage item, or other item, and the materials can include, but are not limited to, glass or other breakable material; aluminum and/or other metals; plastics such as PET, LDPE, LLDPE, HDPE, PP, PS, PVC, EVOH, and Nylon; paperboard; and the like, or any combination thereof, or any other suitable material.

[0068] Cartons according to the present disclosure can accommodate articles of any shape. For the purpose of illustration and not for the purpose of limiting the scope of the disclosure, the following detailed description describes beverage containers (e.g., glass beverage bottles) as disposed within the carton embodiments. In this specification, the terms “lower,” “bottom,” “upper” and “top” indicate orientations determined in relation to fully erected and upright cartons.

[0069] FIG. 1 is a plan view of the exterior side 1 of a blank, generally indicated at 3, used to form a carton 5 (FIG. 8) according to a first exemplary embodiment of the disclosure. The carton 5 can be used to house a plurality of articles such as containers C (FIG. 3). In the illustrated embodiment, the containers C are bottles having a wide bottom B and a narrow top T including a cap CP. In the illustrated embodiment, the carton 5 is sized to house eighteen containers C in a single layer in a 3×6 arrangement, but it is understood that the carton 5 may be sized and shaped to hold containers of a different or same quantity in more than one layer and/or in different row/column arrangements (e.g., 1×6, 2×6, 4×6, 3×8, 2×6×2, 3×4×2, 2×9, 3×4, etc.), or just a single article.

[0070] In one embodiment, the carton 5 has a first end 7 and a second end 9 each having article protection features 11, 11A, 11B (FIG. 8) for protecting at least one article C of the plurality of articles. Alternative, only a single article C could be provided in the carton 5. As will be further discussed below, the carton 5 of the first embodiment may have article protection flaps 13 for protecting the at least one article. The article protection features 11 cushion the ends 7, 9 of the carton and prevent or reduce the likelihood of breakage of the containers C. In one embodiment, the article protection flaps 13 are moveable between a first position (FIG. 10A) and a second position (FIGS. 8A and 10B) placed between adjacent containers C in the carton to reduce movement of the containers in the carton and prevent breakage of the containers. The carton 5 can have other features (e.g., handle, dispenser, etc.) without departing from the disclosure.

[0071] The blank 3 has a longitudinal axis L1 and a lateral axis L2. In the embodiment of FIG. 1, the blank includes a bottom panel 15 foldably connected to a first side panel 17 at a lateral fold line 19. A second side panel 21 is foldably connected to the bottom panel 15 at a lateral fold line 23. A top panel 25 is foldably connected to the first side panel 17 at a lateral fold line 27, and foldably connected to an adhesive panel 29 at a lateral fold line 31.

[0072] The bottom panel 15 is foldably connected to a first bottom end flap 33 and a second bottom end flap 35. The first side panel 17 is foldably connected to a first side end flap 37 and a second side end flap 39. The second side panel 21 is foldably connected to a first side end flap 43 and a second side end flap 45. The top panel 25 is foldably connected to a first top end flap 47 and a second top end flap 49. In one embodiment, when the carton 5 is erected, the end flaps 33, 37, 43, 47, close the first end 7 of the carton, and the end flaps 35, 39, 45, 49 close the second end 9 of the carton. In accordance with an alternative embodiment of the present disclosure, different flap arrangements can be used for closing the ends 7, 9 of the carton 5.

[0073] The end flaps 33, 37, 43, 47 extend along a first marginal area of the blank 3, and are foldably connected at a first longitudinal fold line 61 that extends along the length of the blank. The end flaps 35, 39, 45, 49 extend along a second marginal area of the blank 3, and are foldably connected at a second longitudinal fold line 63 that also extends along the length of the blank. The longitudinal fold lines 61, 63 may be, for example, substantially straight, or offset at one or more locations to account for blank thickness or for other factors. In one embodiment, the side panels 17, 21 have respective diamond panels 65 that are formed by a fold line 67 that is spaced inwardly from the respective longitudinal fold line 61, 63. Also, the side end flaps 37, 39,

43, 45 have a respective lateral fold line 69 extending from a diamond panel 65 to allow a respective end 7, 9 to angle inwardly so that the top of the carton 5 at each end (the portion of the fold line 61, 63 connecting the top end flap 47, 49) is closer to the center of the carton than the bottom of the carton at each end (the portion of the fold line 61, 63 connecting the bottom end flap 33, 35). In this way, the ends 7, 9 are tapered ends, but it is understood that the ends of the carton 5 could be otherwise shaped, arranged, and/or configured (e.g., straight or non-tapered) without departing from the disclosure.

[0074] In the embodiment of FIG. 1, the blank 3 has handle features for forming a handle 71. In the illustrated embodiment, the handle features comprise handle flaps 73 foldably connected to a respective top end flap 47, 49 at a longitudinal fold line 75, and notches or openings 77 in the side end flaps 37, 39, 43, and 45. The openings 77 cooperate to provide an opening at a respective closed end 7, 9 to allow a respective handle flap 73 to be inwardly folded so that the carton 5 can be grasped at a respective end. The blank 3 can have other features for forming the handle 71, or the blank and/or carton 5 can have a handle that is alternatively shaped, arranged, and/or configured without departing from the disclosure. Further, the handle 71 can be omitted without departing from the disclosure.

[0075] In one embodiment, the blank 3 has features for forming the article protection features 11 of the carton 5. As shown in FIG. 1, the side end flaps 37, 39, 43, 45 have deformations in the form of indentations 81 on the exterior surface of the blank 3 such that the indentations form a protrusion on the interior surface of the blank. The bottom end flap 33, 35 each have two rows of deformations in the form of indentations 83 on the interior surface of the blank 3 such that the indentations on the interior surface form a protrusion on the exterior surface 1 of the blank 3. As shown in FIG. 1, the top end flaps 47, 49 each have a respective distal edge 87, 89 having corner notches 91 and a center notch 93. The indentations 81, 83 can be any deformation on a surface of a respective side end flaps 37, 39, 43, 45 or bottom end flap 33, 35 such that the deformation can be any suitable shape (e.g., a concave depression or protrusion, convex depression or protrusion, flat depression or protrusion, embossed area, debossed area, etc., or any other suitable shape). Furthermore, the indentations 81, 83 could be formed on the interior or exterior surface of one or more of the first side panel 17, second side panel 21, top panel 25, bottom panel 15, or top end flaps 47, 49 without departing from the disclosure.

[0076] In the first embodiment, the blank 3 includes nine article protection flaps 13 arranged in a 3×3 arrangement, but the blank could have more or less than nine article protection flaps, and the flaps could be otherwise arranged in other suitable row/column arrangements or in a random configuration on the bottom panel 15, including a single row or single column configuration, or any other suitable configuration. The description herein will describe the detailed arrangement and configuration of a single article protection flap 13; however, the arrangement and configuration of the other article protection flaps will be similar or identical. In other embodiments, the blank 3 can include article protection flaps that are different, similar, or identical to other article protection flaps without departing from the disclosure. In the embodiment of FIG. 1, the middle row of article protection flaps 13 are oriented 180 degrees relative to a row

of article protection flaps that are closer to a respective fold line 61, 63. In other embodiments, the article protection flaps 13 could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

[0077] As shown in FIGS. 1 and 10A, the article protection flaps 13 are each foldably connected to the bottom panel 15 at a respective lateral fold line 101 and are each at least partially defined by a line of weakening 103 in the bottom panel. In one embodiment, the line of weakening 103 is a cut, but the line of weakening could comprise other forms of weakening (e.g., a tear line that comprises cut lines separated by breakable nicks, a tear line that is formed by a series of spaced apart cuts, etc.) that allows the article protection flap 13 to separate from the bottom panel 15 without departing from the disclosure. The cut 103 has a first portion 105 that is generally curved and extending from a first end 106 of the fold line 101 and a second portion 107 that is generally curved and extending from a second end 108 of the fold line 101. Both the first portion 105 and the second portion 107 of the cut 103 extend away from the fold line 101 and form a respective rounded corner 109, 111 of the cut that transitions to a third portion 113 of the cut. The third portion 113 is generally straight and extends in the lateral direction L2 between the two rounded corners 109, 111. In one embodiment, a slit or cut 112 is located adjacent the third portion 113 of the cut 103. As shown in FIGS. 1 and 10A, the article protection flap 13 comprises a second fold line 117 extending from the first end 106 of the first fold line 101 and a third fold line 119 extending from the second end 108 of the first fold line. In the first embodiment, the second and third fold lines 117, 119 are longitudinal fold lines that are generally parallel and extend in the longitudinal direction L1 of the blank 3. The fold lines 101, 117, 119 and cuts 103, 105 could be otherwise shaped, arranged, configured, and/or omitted such that the article protection flap 13 has any other suitable shape or configuration without departing from the disclosure.

[0078] In one embodiment, the first portion 105 of the cut 103, the rounded corner 109 of the cut, a portion of the third portion 113 of the cut, and the second fold line 117 at least partially define a first portion 121 of the article protection flap 13. The second portion 107 of the cut 103, the rounded corner 111 of the cut, a portion of the third portion 113 of the cut, and the third fold line 119 at least partially define a second portion 123 of the article protection flap. A central portion 125 of the article protection flap is at least partially defined by the first fold line 101, second fold line 117, third fold line 119, and a portion of the third portion 113 of the cut 103. The first portion 121 of the article protection flap 13 is foldably connected to the central portion 125 at the second fold line 117. The second portion 123 of the article protection flap 13 is foldably connected to the central portion 125 at the third fold line 119. The first portion 121 and the second portion 123 are foldable relative to each other and the central portion 125 by way of the fold lines 117, 119. Alternatively, the first portion 121 and second portion 123 could be foldably connected at a single fold line without departing from the disclosure.

[0079] FIGS. 2-8 show one exemplary method of forming the carton 5 and the article protection features 11. As shown in FIG. 2, the blank 3 can be formed into a sleeve 131 having open ends 7, 9 by folding the bottom panel 15, side panels 17, 21, and top panel 25 along respective fold lines 19, 23, 27, 31. The adhesive panel 29 can be adhesively secured to

the second side panel **21** by glue or other suitable adhesive. As shown in FIG. **3**, containers **C** can be placed into an interior space **133** of the sleeve **131**. One of the ends **7, 9** can be closed prior to loading the containers **C** or both of the ends **7, 9** can be closed after loading the containers into the interior space **133**. The closing of the first end **7** is described below, but it is understood that the second end **9** can be closed in a similar manner, with the article protection features **11** in the second end being formed in a similar manner as the article protection features in the first end. Alternatively, the second end **9** could have different flap closing sequence or arrangement and the article protection features **11** could be otherwise shaped, arranged, configured, and/or omitted without departing from the disclosure.

[0080] As shown in FIGS. **3** and **4**, the first end **7** is closed by first inwardly folding the side end flaps **37, 43**. As shown in FIGS. **5-7**, the bottom end flap **33** is upwardly folded and the top end flap **47** is downwardly folded to close the end **7** of the carton **5**. The article protection features **11** in the first end of the carton **5** are formed during the closing of the end flaps **33, 37, 43, 47**. As shown in FIG. **6**, the indentations **81** on the exterior surface of the side end flaps **37, 43** are aligned with the indentations **83** on the interior surface of the bottom end flap **33** to form a respective article protection feature **11**. As shown in FIGS. **8** and **9**, the outermost article protection features (when viewing the end **7** as shown in FIG. **9**) are identified by reference number **11A** and are formed by the indentation **81** on the side end flap **43** and the indentation **83** on the bottom end flap **33** that cooperate to form a pocket **135** in the overlapped end flaps. In one embodiment, the width of the pocket **135** as viewed in FIG. **9** is approximately equal to the combined amount of depression of each of the indentations **81, 83**. The indentations **81** are on the exterior surface of the side end flaps **37, 43** and the indentations **83** are on the interior surface of the bottom end flap **33** so that the indentations **81, 83** cooperate to form the pocket **135**. Alternatively, the article protection features **11** could comprise only a single indentation **81, 83**, or one of the indentations **81, 83** could be larger or smaller than the other, or the indentations **81, 83** could be offset from one another, without departing from the disclosure. Moreover, the indentations **81, 83** could be arranged such that the protrusions are in direct contact with each other.

[0081] In one embodiment, the middle article protection features **11B** (FIGS. **8** and **9A**) are formed by an indentation **81** on each of the side end flaps **37, 43** and an indentation on the bottom end flap **33**. As shown in FIG. **9A**, the indentation **81** near the edge of the inner side end flap **43** receives the indentation **81** near the edge of the outer side end flap **37**, and the indentation **83** on the bottom end flap **33** cooperates with the indentation on the outer side end flap **37** to form the pocket **137**. The article protection features **11A, 11B**, and pockets **135, 137** could be otherwise shaped, arranged, positioned, and/or configured without departing from the disclosure.

[0082] FIGS. **9B** and **9C** show alternative configurations of the article protection features **11A, 11B** having pockets **135, 137** similar to the embodiments of FIGS. **9** and **9A** but filled with shock absorbing material **139**. In one embodiment, the shock absorbing material **139** is a thermoplastic adhesive. The shock absorbing material **139** can comprise thermoplastic adhesive that can be hot-melt adhesive including a low temperature hot melt thermoplastic adhesive or a high temperature hot melt thermoplastic adhesive such as

are commercially available. Such hot melt adhesive can include ethylene vinyl acetate (EVA) or any other suitable material. For example, the shock absorbing material **139** can comprise any suitable foam, gel, liquid, or solid, that can be located in the pocket **135, 137** and provide cushioning of the impact forces exerted on the carton **5**. For example, the shock absorbing material could comprise any suitable heat activation material, UV activation material, laser activation material, Styrofoam, thermoplastic, hot melt adhesive, or any material that takes up space in the pocket **135, 137** to provide cushioning to the containers **C**. The article protection features **11** can comprise the same or different thermoplastic adhesive that is used to form and close the carton **5** without departing from the disclosure. In one embodiment, the adhesive used to form the shock absorbing material **139** can be further applied to one or more of the end flaps **33, 37, 43, 47** to secure the end flaps in the closed configuration of the end **7**.

[0083] As shown in FIG. **9**, the lower article protection feature **11, 11A, 11B** is spaced apart from the bottom panel **15** by a first distance **D1** and the upper article protection feature **11, 11A, 11B** is spaced apart from the bottom panel by a second distance **D2**. In one embodiment, the second distance **D2** is greater than the first distance **D1**. The distances **D1** can be selected so that the lower article protection feature **11** contacts the container **C** near a bottom portion **B** of the container. The distance **D2** can be selected so that the upper article protection feature **11** contacts the container **C** near the shoulder **S** of the container. The positioning of the upper and lower article protection features **11** provides a respective container **C** with two contact points with the shock absorbing features at the end **7** of the carton **5** so that each respective container **C** is stabilized and cushioned against impacts occurring at the end of the carton. The article protection features could be otherwise arranged and positioned without departing from the disclosure.

[0084] FIG. **4A** shows an alternative configuration of the end **7** wherein the side end flap **37** has two notches **141** instead of the indentations **81**. The notches **141** allow the indentations **81** near the edge of the exterior surface of the side end flap **43** to cooperate with the middle indentations **83** on the bottom end flap **33** to form a pocket similar to the pocket **135** shown in FIG. **9**, but with the pocket **135** being wider as a result of the intervening layer of material from the side end flap **37**.

[0085] FIGS. **5A** and **5B** show an alternative configuration of the end **7** wherein the bottom end flap **33** is modified from the bottom end flap shown in FIG. **4**. In the embodiment of FIGS. **5A** and **5B**, the indentations **83** on the interior surface near the peripheral edge of the bottom end flap **33** of FIG. **4** are replaced by a deformation **149** at the peripheral edge of the bottom end flap **33**. The deformation **149** includes a series of indentations **151** on the interior surface of the bottom end flap **33** that are adjacent to a respective indentation on the exterior surface **153** of the bottom end flap. The indentations **151** on the interior surface of the bottom end flap **33** communicate with the upper indentations **81** on the side end flaps **37, 43** to form a respective pocket or series of pockets. Alternatively, the upper indentations **81** on the side end flaps **37, 43** could be replaced with a deformation similar to the deformation **149** of the bottom end flap, or any other configuration that is suitable for creating a pocket or series of pockets that form the article protection features.

[0086] FIG. 5C shows an alternative configuration of the end 7 wherein the side end flaps 37, 43 and bottom end flap 33 are modified from the flaps shown in FIG. 4. In the embodiment of FIG. 5C, the bottom end flap 33 has indentations 155 on the interior surface near the peripheral edge of the bottom end flap that are modified from the embodiment of FIG. 4. Further, the side end flaps 37, 43 each have upper indentations 157 that are modified from the embodiment of FIGS. 4 and 5. Both groups of indentations 155, 157 are elongated from the embodiment of FIGS. 4 and 5, and the indentations 155 on the bottom end flap are each sized to extend between two adjacent indentations 157 on the side end flaps 37, 43. The indentations 155 are in communication with multiple indentations 157 so that the pocket formed by the cooperating indentations forms an article protection feature 11 that is elongated and contacts two adjacent articles C. The elongated article protection feature can be filled with shock absorbing material in a similar manner as described above for the first embodiment. Alternatively, the lower indentations on the interior surface of the bottom end flap 33 and the lower indentations 81 on the side end flaps 37, 43 could be similar to the indentations 155, 157 without departing from the disclosure.

[0087] In the first embodiment, the loaded and closed carton 5 of FIG. 8 is further processed so that the article protection flaps 13 are activated. The article protection flaps 13 are foldably connected to the bottom panel 15 and moveable between a first position (FIG. 2) that is substantially parallel to the bottom panel and a second position (FIG. 8A) wherein the article protection flaps are folded relative to the bottom panel. In one embodiment, the article protection flaps 13 are raised or activated to the position of FIG. 8A, and the article protection flaps have features for preventing the folding of the article protection flaps from the second position back to the first position. FIG. 8A illustrates an outermost row of containers C removed and the end flaps 33, 37, 43, 47 at the end 7 open so that the article protection flaps 13 are visible. It is understood that the article protection flaps 13 will be activated to the second position (FIG. 8A) after the ends 7, 9 of the carton 5 have been closed. Alternatively, the article protection flaps 13 could be activated prior to closing one or both of the ends 7, 9 of the carton 5 without departing from the disclosure.

[0088] The article protection flaps 13 can be activated by various forming apparatus, some of which will be described below in further detail, or any other suitable method. The activation of a single article protection flap 13 will be described in detail herein, but it is understood that the other article protection flaps can be activated in a similar or different manner without departing from the disclosure. FIGS. 10A and 10B are enlarged portions of the interior surface of the bottom panel 15, with FIG. 10A showing the interior surface of the bottom panel prior to activation of the article protection flap 13, and FIG. 10B showing the interior of the bottom panel after activation of the article protection flap. In one embodiment, a finger or other portion of an apparatus for forming the carton 5 presses against the central portion 125 (FIG. 10A) of the article protection flap 13 to initiate separation of the article protection flap from the bottom panel 13 along the cut 103. As shown in FIGS. 8A, 10A, and 10C, the article protection flap 13 is pivoted upward relative to the bottom panel 15 at the fold line 101 in the direction of arrow A1 to create an opening 161 in the bottom panel. As the article protection flap 13 is activated,

the first portion 121 and the second portion 123 are folded relative to each other. In one embodiment, the first portion 121 and the second portion 123 of the article protection flap are folded inwardly relative to each other and relative to the central portion 125. As such, the article protection flap 13 provides two layers of material (e.g., the inwardly folded first portion 121 and second portion 123) between adjacent containers C in the carton 5.

[0089] In one embodiment, the article protection flaps 13 are upwardly folded to the second (raised) position shown in FIG. 8A, or the article protection flaps can be upwardly folded to a second (raised) position shown in FIG. 10C. In one embodiment, the upwardly folding of the article protection flaps 13 causes the containers C in the carton 5 to move to accommodate the space required for the article protection flaps in the second position with the first portion 121 and second portion 123 folded relative to each other. The movement of the containers C when the article protection flaps 13 are upwardly folded and located between adjacent containers, tightens the packing of the containers in the carton 5 so that the movement of the containers is limited by the positioning of the article protection flaps 13 and the respective end flaps 33, 37, 43, 47 and 35, 39, 45, 49 at the closed ends 7, 9 of the carton. The article protection flaps 13 are pressed against two adjacent containers C to initiate movement of the containers and provide the tightening feature of the article protection flaps.

[0090] In one embodiment, the configuration of the first portion 121 and the second portion 123 prevents the article protection flap 13 from being downwardly folded from the second or raised position of FIG. 8 to the first or lowered position of FIG. 2. As shown in FIG. 10B, when the first portion 121 and the second portion 123 of the article protection flap 13 are inwardly folded relative to each other, the first and second portions extend beyond the edge 163 of the opening 161 created at the third portion 113 of the cut 103. In one embodiment, an edge 165 (FIG. 10C) of the first portion 121 of the article protection flap 13, formed by the rounded corner 109 of the cut 103 extends beyond the edge 163 of the opening 161. Also, an edge 167 (FIG. 10C) of the second portion 123 of the article protection flap 13 formed by the rounded corner 111 of the cut 103 extends beyond the edge 163 of the opening 161. The positioning of the distal portions 166, 168 of the first portion 121 and second portion 123, including the edges 165, 167 of the article protection flap 13, relative to the edge 163 of the opening 161 prevents the article protection flaps 13 from being downwardly folded to the first position wherein the article protection flaps are substantially parallel to the bottom panel 15. As such, once the article protection flaps 13 are raised to the second position and positioned between adjacent containers C, the article protection flaps stay in the upwardly folded position providing cushioning and protection between adjacent containers. The article protection flaps 13 could be otherwise shaped, arranged, and/or configured to have other features for preventing the article protection flaps from returning to the first or lowered position without departing from the disclosure.

[0091] FIGS. 10D-10F show an article protection flap 13 having alternative features. In the embodiment of FIGS. 10D-10F, the first portion 121 and the second portion 123 of the article protection flap 13 each have a respective deformation 171, 173 in the form of an indentation on the exterior surface of the article protection flap 13. The article protec-

tion flap 13 of the embodiment of FIGS. 10D-10F is activated in a similar manner as described above for the previous embodiment, wherein the first portion 121 is folded relative to the second portion 123 of the article protection flap. As shown in FIG. 10F, the indentations 171, 173 of the respective first and second portions 121, 123 cooperate to form a space 175 between the first portion and the second portion of the article protection flaps 13. The space 175 can comprise shock absorbing material, such as the shock absorbing material 139 discussed above for the article protection features 11, or any other suitable material. The space 175 between the first and second portions 121, 123 of the article protection flap 13 of FIG. 10F provides enhanced article protection and reduction of breakage of the containers C. The deformations 171, 173 could be otherwise shaped, arranged, configured, positioned, and/or omitted without departing from the scope of the disclosure.

[0092] One embodiment of a system 181 for activating the article protection flaps 13 is illustrated in FIGS. 11 and 12. In one embodiment, the cartons 5, having containers C loaded and the ends 7, 9 closed, are conveyed via an inlet conveyor 183 to a first or inlet end 185 of the system 181. However, the system 181 could also be used to activate the article protection flaps 13 of the cartons 5 prior to closing one or both of the ends 7, 9. The system 181 comprises a sled 187 that receives a carton 5 from the inlet conveyor 183 such that the bottom panel 15 of the carton is in contact with the top surface 189 of the sled. The sled 187 is operatively attached to a cam track array or section 191 that includes a series of spaced rails 193 (FIG. 12) with a series of cam tracks 195 mounted therebetween. The sled 187 comprises a series of actuating fingers 197 pivotally mounted to the sled and moveable through a respective slot 199 in the top surface 189 of the sled. The actuating fingers 197 have a lower portion that engages a respective cam track 195 such that the actuating finger 197 is raised or lowered in the slot 199 by the slope of the cam track. As the sled 187 with carton 5 mounted on the top surface 189 moves in the direction of arrow A2 (FIG. 11), the fingers 197 are raised and lowered in the slots 199 to activate the article protection flaps 13 in the bottom panel 15. After the article protection flaps 13 are activated by the system 181, the carton 5 exits an exiting end 201 of the system for further handling and packaging. The system 180 could be alternatively shaped, arranged, and/or configured without departing from the disclosure.

[0093] FIG. 13 illustrates an alternative embodiment of a system 207 for activating the article protection flaps 13 of the carton 5. The system 207 comprises a cassette 209 that can be mounted along the path of travel of the carton 5 in a packaging machine. In one embodiment, the cassette 209 comprises a series of actuating fingers 211 mounted to a chain 213. The fingers 211 move along a cam track 215 that receives a portion of the fingers 211 as the fingers are conveyed around the cassette. As the fingers 211 move along the cam track 215, the fingers can be positioned between non-engaging and engaging positions for selectively activating the article protection flaps 13 of the carton 5. The system 207 could be alternatively shaped, arranged, and/or configured without departing from the disclosure.

[0094] FIG. 14 shows features of an alternative embodiment of a system 221 for activating the article protection flaps 13 of the carton 5. As with the previous embodiments, the system 221 can be mounted along a path of travel of the

cartons 5 in a packaging machine. In the embodiment of FIG. 14, the system 221 includes a series of star wheels or finned discs 223 that will engage and activate the article protection flaps 13 as the cartons move through or along system 221. The star wheels 223 each generally includes a series of actuating fingers 225 arranged in groups or sets spaced about the circumference or periphery 227 of each of the star wheels. In one embodiment, each of the star wheels 223 is positioned to activate a respective row of article protection flaps 13 in the bottom panel 15 of the carton. The actuating fingers 225 engage a respective article protection flap 13 and move the article protection flap from the first (lowered) position that is substantially parallel to the bottom panel 15 to the second (raised) position wherein the article protection flap 13 is folded relative to the bottom panel. The system 221 could be alternatively shaped, arranged, and/or configured without departing from the disclosure.

[0095] FIG. 15 is an alternative embodiment of a blank 303 that is similar to the blank 3 of the first embodiment. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank 303 is for forming a carton 5 having article protection features 11 in respective ends 7, 9 of the carton as discussed above for the first embodiment. As with the embodiment of FIG. 1, the blank 303 has end flaps 33, 37, 43, 47 and 35, 39, 45, 49 that have respective indentations or features 81, 83 that cooperate to form the article protection features 11. In contrast to the first embodiment, the blank 303 has a bottom panel 15 that does not have article protection flaps 13. The blank 303 could have other features and could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

[0096] FIG. 16 is an alternative embodiment of a blank 403 that is similar to the blank 3 of the first embodiment. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank 403 is for forming a carton 5 having article protection flaps 13 foldably connected to the bottom panel 15 as discussed above for the first embodiment. In contrast to the first embodiment, the blank 403 has end flaps 33, 37, 43, 47 and 35, 39, 45, 49 that are free of respective indentations or features 81, 83 that cooperate to form the article protection features 11 of the carton 5 of the first embodiment. The blank 403 could have other features and could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

[0097] FIGS. 17-19 show an alternative embodiment of a blank 503 for forming a carton 505 that is similar to the blank 3 and carton 5 of the first embodiment. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank 503 has article protection flaps 513 that are similar to the article protection flaps 13 of the first embodiment. The blank 503 has fifteen article protection flaps 513 arranged in a 5×3 arrangement, but the blank could have more or less than fifteen article protection flaps and the article protection flaps could be otherwise arranged. In the embodiment of FIGS. 17-19, the article protection flaps 513 are foldably connected to the bottom panel 15 at a lateral fold line 520 and are at least partially defined by a cut 522 or other line of weakening in the bottom panel. Two oblique fold lines 524, 526 extend from respective ends of the lateral fold line 520 to define a central portion 528 of the article protection flap 513. A first portion 530 of the article protection flap 513 is foldably connected to the central portion 528 at the oblique fold line 524 and a

second portion 532 is foldably connected to the central portion 528 at the oblique fold line 526. In addition to the distal portions of the first portion 530 and second portion 532, the features that prevent the article protection flap 513 from being downwardly folded include a heel 534 formed at a distal portion of the article protection flap. In the illustrated embodiment, the heel 534 is a rounded protrusion that extends beyond the edge of the first and second portions 530, 532.

[0098] FIG. 18 illustrates a view of the bottom panel 15 of the carton 505 after the article protection flaps 15 have been activated and positioned in the second (raised) position between adjacent containers C. As shown in FIGS. 18 and 19, the openings 561 is formed in the bottom panel 15 when the article protection flaps 513 are moved to the second position between adjacent containers. As shown in FIG. 19, the first and second portions 530, 532 are folded with respect to one another when a respective article protection flap 513 is positioned in the second position. In the raised position, the first portion 530, second portion 532, and heel 534 of each respective article protection flap 513 interfere with the edges of the bottom panel 15 at the opening 561 to prevent with the article protection flap from being moved to the first position that is substantially parallel to the bottom panel 15. The article protection flaps 513 could be otherwise shaped, arranged, configured, and/or positioned without departing from the disclosure.

[0099] FIGS. 20 and 20A illustrate various features of a blank 603 according to an alternative embodiment of the disclosure and having similar features of the first embodiment. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank 603 has article protection flaps 613 that are similar in shape as the article protection flaps 513 of the previous embodiment. In the embodiment of FIGS. 20 and 20A, the article protection flaps 613 are foldably connected to the bottom panel 15 at a lateral fold line 620 and are at least partially defined by a cut 622 or other line of weakening in the bottom panel. Two curved fold lines 624, 626 extend from respective ends of the lateral fold line 620 to define a central portion 628 of the article protection flap 613. A first portion 630 of the article protection flap 613 is foldably connected to the central portion 628 at the curved fold line 624 and a second portion 632 is foldably connected to the central portion 628 at the curved fold line 626. The article protection flap 613 comprises a heel 634 formed at a distal portion of the article protection flap. In the illustrated embodiment, the heel 634 is a rounded protrusion that extends beyond the edge of the first and second portions 630, 632 (e.g., is the farthest portion of the article protection flap 613 from the fold line 620). In the embodiment of FIGS. 20 and 20A, the article protection flap 613 includes a lateral fold line 636 extending across the first portion 630 and the second portion 632 at the widest portion of the article protection flap and a longitudinal fold line 638 extending from the lateral fold line across the heel portion 634 to the cut 622. The fold lines 636, 638 facilitate the activation of the article protection flap 613 and the folding of the first portion 630 relative to the second portion 632. The article protection flaps 613 could be otherwise shaped, arranged, configured, and/or positioned without departing from the disclosure.

[0100] FIGS. 21-23 illustrate various features of a blank 703 and carton 705 of an alternative embodiment having similar features as the first embodiment of the disclosure.

Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank 703 has a bottom panel 15 with article protection flaps 713 that are foldably connected to the bottom panel at a lateral fold line 720. In the embodiment of FIGS. 21-23 two curved fold lines 724, 726 extend from respective ends of the lateral fold line 720 and define a central portion 728 of the article protection flap 713. The first portion 730 is foldably connected to the central portion 728 of the article protection flap 713 at the fold line 724 and the second portion 732 is foldably connected to the central portion at the fold line 726. The location of the containers C is shown in hidden lines in FIG. 21, with the article protection flaps 713 in the first (lowered) position wherein the article protection flaps are substantially parallel to the bottom panel.

[0101] FIG. 22 shows the article protection flaps 713 being moved to the second position, and FIG. 23 shows the article protection flaps substantially in the second position. In both FIGS. 22 and 23 one row of containers C has been removed to show the positioning of the article protection flaps 713. As with the previous embodiments, an opening 761 is formed in the bottom panel 15 that corresponds with the shape of the article protection flap 713 in the first position. As shown in FIG. 23, the first and second portions 730, 732 are curved or contoured to match the shape of the container C so that the container is held in secure engagement with the article protection flap 713. As with the previous embodiments, the article protection flaps 713 are prevented from being moved from the second (raised) position to the first (lowered) position by the interference of the folded first and second portions 730, 732 with the edge 763 of the bottom panel 15 at the opening 761. The folding of the first and second portions 730, 732 relative to each other and the central portion 730 causes the distal portions of the first and second portions to extend beyond the edge 763 forming the opening. The article protection flaps 713 could be otherwise shaped, arranged, configured, and/or positioned without departing from the disclosure.

[0102] FIGS. 24-27 show an alternative embodiment of a blank 803 for forming a carton 805 that is similar to the blank 3 and carton 5 of the first embodiment. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank 803 has article protection flaps 13 that are the same as the article protection flaps of the first embodiment. The blank 803 has end flaps 33, 37, 43, 47 and 35, 39, 45, 49 that have respective indentations or features 81, 83 that cooperate to form the article protection features 811 that are similar to the article protection features 11, 11A, 11B of the first embodiment. The blank 803 could have other features without departing from the disclosure.

[0103] In the embodiment of FIGS. 24-27, each of the top end flaps 47, 49 has a reinforcement flap 814 foldably connected to a base portion 816 of the top end flap at a longitudinal fold line 818. In one embodiment, the base portion 816 of each top end flap 47, 49 has a group of indentations 83a on the interior surface of the base portion 816 of the end flap, and the reinforcement flap 814 has a group of indentations 83b on the interior surface of the end flap. As with the first embodiment, the side end flaps 37, 39, 43, 45 have indentations 81 on the exterior surface of the side end flaps and the bottom end flaps 33, 35 have indentations 83 on the interior surface of the bottom end flaps. In the embodiment of FIGS. 24-27, each of the side end flaps 43, 45 have only a single indentation 81 on the lower row of

indentations and an edge having notches **810** instead of a second indentation on the lower row. The blank **803** could have other arrangements of indentations **81**, **83** or other features for forming the article protection features **811** without departing from the disclosure.

[0104] As shown in FIGS. 25-27B, when the ends **7**, **9** of the carton **805** are closed, the reinforcement flap **814** of each top end flap **47**, **49** is folded at the fold line **818** to be in face-to-face contact with the interior surface of the base portion **816** of each end flap. As with the previous embodiments, only the closing of the first end **7** of the carton **805** is shown, but it is understood that the second end **9** could be closed in a similar manner as described for the first end. When the reinforcement flap **814** is folded, the indentations **83b** on the reinforcement flap **814** are aligned and in contact with the indentations **83a** on the base portion **816**. The indentations **83a**, **83b** cooperate to form a pocket **836** (FIG. 27A) in the top end flap **47**, **49** that is similar to pockets **135** discussed above for the first embodiment and shown in FIG. 9.

[0105] In the embodiment of FIGS. 24-27B, the indentations **81** on the side end flaps **37**, **39**, **43**, **45** and the indentations **83** on the bottom end flaps **33**, **35** cooperate to form an upper pocket **135** that is similar to the upper pocket **135** described above for the first embodiment and shown in FIG. 9. The upper article protection feature **811A** of the outermost article protection features (e.g., closest to the side panels **17**, **21** when viewed from FIG. 27) comprises the pocket **836** formed by the reinforcement flap **814** and the base portion **816** of the top end flaps **47**, **49** and the upper pocket **135** that is formed by the bottom end flap **33**, **35** and the side end flaps **37**, **39**, **43**, **45**. The lower article protection features **811B** of the outermost article protection features comprises the lower pocket **135** that is formed by the indentation **83** on the bottom end flaps **33**, **35** and the indentation **81** on the side end flaps **37**, **39**, **43**, **45**. Either or both of the pockets **836**, **135** that form the article protection features **811A**, **811B** could comprise shock absorbing material as described above for the first embodiment. The article protection features **811A**, **811B** could be formed by other features of the blank **803** without departing from the disclosure.

[0106] As shown in FIGS. 27 and 27B, the upper article protection feature **811C** of the middle article protection features (e.g., between the two outer article protection features **811A**) comprises the pocket **836** in the top end flaps **47**, **49** and the upper pocket **137** that is formed by the indentations **81** of bottom end flaps **33**, **35** and the overlapped portions of the side end flaps **37**, **39**, **43**, **45**. The lower article protection features **811D** of the middle article protection features comprises the lower pocket **137** that is formed by the indentations **81** of the overlapped portions of the side end flaps **43**. As with the previous embodiments, any or all of the pockets **135**, **137**, **836** could be filled with shock-absorbing material **139** without departing from the disclosure. The pockets **135**, **137** can be similar to the corresponding pockets shown in FIG. 9 for the first embodiment, or the pockets could be otherwise shaped, arranged, configured, and/or omitted. Any of the article protection features **811**, **811A**, **811B**, **811C**, **811D** could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

[0107] In one embodiment, the reinforcement flaps **814** are folded under the base portion **816** to provide an extra

layer of material to reinforce and enhance the cushioning and protection of the container **C** by the article protection features **811A** in the closed ends **7**, **9** of the carton **805**. Alternatively, the reinforcement flap **814** could be folded over and be in contact with the exterior surface of the base portion **816** so that the reinforcement flap is in face-to-face contact with the exterior surface of the base portion. Alternatively, the reinforcement flaps **814** and base portions **816** could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

[0108] FIG. 28 illustrates various features of a blank **903** for forming a carton of an alternative embodiment having similar features as the first embodiment of the disclosure. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank **903** has a bottom panel **15** with primary article protection flaps **913** that are arranged in a single row of three article protection flaps. Secondary article protection flaps **914** are foldably connected to the bottom panel **15** and are spaced apart from a respective primary article protection flap **913**. In the illustrated embodiment, four secondary article protection flaps **914** are included, but more or less than four secondary article protection flaps could be used, or the secondary article protection flaps could be otherwise shaped, arranged, and/or configured without departing from the disclosure. The secondary article protection flaps **914** provide additional cushioning of the containers **C** and tightening of the carton **5** formed from the blank **903**.

[0109] In one embodiment, the secondary article protection flaps **914** are smaller than the primary article protection flaps **913**, but it is understood that the article protection flaps could be otherwise shaped, arranged, and/or configured. The primary and secondary article protection flaps **913**, **914** can be moved to a second (raised) position in a similar manner as described above for the previous embodiments. In the illustrated embodiment, the blank **903** comprises a second top panel **926** that is placed in face-to-face contact with the first top panel **25** to reinforce the top panel of the carton formed from the blank **903**. However, it is understood that the primary article protection flaps **913** and secondary article protection flaps **914** could be included on any other style of blanks (e.g., blanks similar to the blank **3** of FIG. 1 having only a single top panel **25**) for use in forming any other style of carton without departing from the disclosure.

[0110] FIGS. 29-30 illustrate various features of a blank **1003** for forming a carton **1005** of an alternative embodiment having similar features as the first embodiment of the disclosure. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank **1003** is for forming the carton **1005** that is a carrier having an interior space **1008** that has a generally open top with a divider **1010** that at least partially divides the interior space into a front portion **1012** and a back portion **1014**. In one embodiment, the divider **1010** comprises a handle **1016** and the divider does not extend down to the bottom panel **1015**. The divider **1010** could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

[0111] In the illustrated embodiment, the blank **1003** has a front panel **1020**, back panel **1022**, and respective side panels **1024**, **1026**, **1028**, **1030** for forming the sides of the carton **1005**. The blank **1003** has divider panels **1032**, **1034**, **1036**, **1038** that combine to form the divider **1010** of the carton **1005**. In one embodiment the bottom panel **1015** is foldably connected to the back panel **1022** but the bottom

panel **1015** could be otherwise arranged without departing from the disclosure. The bottom panel **1015** includes article protection flaps **1013** that are similar to the article protection flaps **13** of the first embodiment. The article protection flaps **1013** are foldably connected to the bottom panel **1015** and arranged in a single row of three flaps. In the illustrated embodiment, the article protection flaps **1013** are positioned in the second (raised) position in a similar manner as the previous embodiments. The article protection flaps **1013** are positioned on the bottom panel **1015** so that the flaps are placed between adjacent containers **C**, with one of the adjacent containers being located in the front portion **1012** of the interior space **1008** and the other of the adjacent containers being located in the back portion **1014** of the interior space. The article protection flaps **1013** could be otherwise shaped, arranged, and/or configured without departing from the disclosure.

[0112] FIGS. **31A-31C** illustrate various features of a blank **1103** for forming a carton **1105** of an alternative embodiment having similar features as the previous embodiments of the disclosure. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank **1103** is a single panel for supporting the plurality of containers **C**. The blank **1103** comprises article protection flaps **1113** similar to the article protection flaps **13** of the earlier embodiments. The carton **1105** is formed by placing the plurality of containers **C** on the blank **1103** and then activating the article protection flaps **1113** by moving the article protection flaps from the first position that is substantially parallel to the blank **1103** to the second position wherein the article protection flaps are folded relative to the panel of the blank. In one embodiment, the carton **1105** can be further assembly by applying an overwrap of shrink-wrap (e.g., shrinkable polymer film) or other packaging material **M** so that the containers are securely attached to the blank **1103**. In the embodiment of FIGS. **31A-31C** the blank **1103** is a bottom panel, but the blank could be otherwise shaped, arranged, or configured without departing from the disclosure.

[0113] In an alternative embodiment, blank **1103** and articles **C** with activated article protection flaps **113** can be positioned relative to a construct to at least partially enclose the blank and the at least two articles. In one embodiment the construct can be a sleeve similar to the sleeve **131** of FIG. **2**. Further the construct can have at least one open end, such as the ends **7, 9** that can be closed by respective end flaps. The blank **1103** and articles **C** can be positioned in an interior of the sleeve prior to closing both the ends **7, 9**, or one of the ends can be closed prior to positioning the blank and articles. Alternatively, the construct could be a lid that fits over the tops of the articles **C**, and the lid could have one or more side panels extending down from a top panel.

[0114] FIGS. **32A-32C** illustrate various features of a blank **1203** for forming a carton **1205** of an alternative embodiment having similar features as the previous embodiments of the disclosure. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank **1203** comprises a bottom panel **1214** and four side panels **1218, 1220, 1222, 1224** for forming a tray **1226** (FIG. **32B**) having an interior space for holding the container **C**. The blank **1203** comprises article protection flaps **1213** similar to the article protection flaps **13** of the earlier embodiments. The carton **1205** is formed by placing the plurality of containers **C** on the bottom panel **1214** of the

blank **1203** and upwardly folding the side panels **1218, 1220, 1222, 1224** to form the tray **1226**. The article protection flaps **1213** are activated by moving the article protection flaps from the first position that is substantially parallel to the bottom panel **1214** to the second position wherein the article protection flaps are folded relative to the bottom panel of the blank **1203**. In one embodiment, the carton **1205** can be further assembled by applying an overwrap of shrink-wrap (e.g., shrinkable polymer film) or other packaging material **M** so that the containers are securely attached to the tray **1226**. In the embodiment of FIGS. **32A-32C** the blank **1203** is configured for forming the tray **1226**, but the blank could be otherwise shaped, arranged, or configured without departing from the disclosure.

[0115] FIGS. **33A-33C** illustrate various features of a blank **1303** for forming a carton **1305** of an alternative embodiment having similar features as the previous embodiments of the disclosure. Accordingly, like or similar features will be indicated with like or similar reference numbers. The blank **1303** is generally similar to the blank **3** of the first embodiment in that the blank of FIGS. **33A-33C** comprises a bottom panel **1315** and a first side panel **1317**, a second side panel **1321**, and a top panel **1325**. The blank **1303** comprises article protection flaps **1313** similar to the article protection flaps **13** of the earlier embodiments. The carton **1305** is formed by placing the plurality of containers **C** on the bottom panel **1214** of the blank **1203** and upwardly folding the side panels **1317, 1321** around the containers on the bottom panel to partially form the carton as shown in FIG. **33B**. Next, the top panel **1325** is downwardly folded to close the interior of the carton **1305** and the ends **1307, 1309** are closed by closing respective end flaps **1333, 1337, 1343, 1347** and **1335, 1339, 1345, and 1349**. The article protection flaps **1313** are activated by moving the article protection flaps from the first position that is substantially parallel to the bottom panel **1315** to the second position wherein the article protection flaps are folded relative to the bottom panel **1315** of the blank **1303**. The blank **1303** could be otherwise shaped, arranged, or configured without departing from the disclosure.

[0116] The cartons of any of the illustrated or non-illustrated embodiments of the disclosure could have other features (e.g., dispenser features, handle features, reinforcement features, etc.) without departing from the disclosure. Also, the cartons could be otherwise shaped, arranged, or configured and the cartons could be configured to hold articles other than beverage containers **C** without departing from the disclosure.

[0117] In general, the blanks of any of the illustrated or non-illustrated embodiments may be constructed from paperboard having a caliper so that it is heavier and more rigid than ordinary paper. The blank can also be constructed of other materials, such as cardboard, or any other material having properties suitable for enabling the carton to function at least generally as described above. The blank can be coated with, for example, a clay coating. The clay coating may then be printed over with product, advertising, and other information or images. The blanks may then be coated with a varnish to protect information printed on the blanks. The blanks may also be coated with, for example, a moisture barrier layer, on either or both sides of the blanks. The blanks can also be laminated to or coated with one or more sheet-like materials at selected panels or panel sections.

[0118] As an example, a tear line can include: a slit that extends partially into the material along the desired line of weakness, and/or a series of spaced apart slits that extend partially into and/or completely through the material along the desired line of weakness, or various combinations of these features. As a more specific example, one type of tear line is in the form of a series of spaced apart slits that extend completely through the material, with adjacent slits being spaced apart slightly so that a nick (e.g., a small somewhat bridging-like piece of the material) is defined between the adjacent slits for typically temporarily connecting the material across the tear line. The nicks are broken during tearing along the tear line. The nicks typically are a relatively small percentage of the tear line, and alternatively the nicks can be omitted from or torn in a tear line such that the tear line is a continuous cut line. That is, it is within the scope of the present disclosure for each of the tear lines to be replaced with a continuous slit, or the like. For example, a cut line can be a continuous slit or could be wider than a slit without departing from the present disclosure.

[0119] In accordance with the exemplary embodiments, a fold line can be any substantially linear, although not necessarily straight, form of weakening that facilitates folding there along. More specifically, but not for the purpose of narrowing the scope of the present disclosure, fold lines include: a score line, such as lines formed with a blunt scoring knife, or the like, which creates a crushed or depressed portion in the material along the desired line of weakness; a cut that extends partially into a material along the desired line of weakness, and/or a series of cuts that extend partially into and/or completely through the material along the desired line of weakness; and various combinations of these features. In situations where cutting is used to create a fold line, typically the cutting will not be overly extensive in a manner that might cause a reasonable user to incorrectly consider the fold line to be a tear line.

[0120] The above embodiments may be described as having one or more panels adhered together by glue during erection of the carton embodiments. The term “glue” is intended to encompass all manner of adhesives commonly used to secure carton panels in place.

[0121] The foregoing description of the disclosure illustrates and describes various embodiments. As various changes could be made in the above construction without departing from the scope of the disclosure, it is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense. Furthermore, the scope of the present disclosure covers various modifications, combinations, alterations, etc., of the above-described embodiments. Additionally, the disclosure shows and describes only selected embodiments, but various other combinations, modifications, and environments are within the scope of the disclosure as expressed herein, commensurate with the above teachings, and/or within the skill or knowledge of the relevant art. Furthermore, certain features and characteristics of each embodiment may be selectively interchanged and applied to other illustrated and non-illustrated embodiments of the disclosure.

What is claimed is:

1. A method of forming a carton, the method comprising: obtaining a blank comprising at least one panel, at least one article protection flap foldably connected to the at

least one panel, and at least one end flap foldably connected to the at least one panel;

positioning the at least one panel to at least partially form an interior space of the carton;

loading at least one article in the interior space;

closing an end of the carton by folding the at least one end flap; and

folding the at least one article protection flap relative to the at least one panel after the loading the at least one article, the folding comprises moving the at least one article protection flap from a first position that is substantially parallel to the at least one panel to a second position wherein the at least one article protection flap is folded relative to the at least one panel, the folding of the at least one article protection flap is after the closing the end of the carton.

2. The method of claim 1, wherein the loading at least one article comprises loading a plurality of articles.

3. The method of claim 2, wherein the at least one article protection flap comprises a plurality of article protection flaps, and the folding comprises positioning each of the article protection flaps between two respective adjacent articles of the plurality of articles.

4. The method of claim 2, wherein the at least one article protection flap comprises features to facilitate the folding of the flap between adjacent articles.

5. The method of claim 1, wherein the positioning the panels comprises forming a sleeve having a first end and a second end, the blank has a first plurality of end flaps at one end of the blank and a second plurality of end flaps at a second end of the blank, the closing the end comprises closing the first end by at least partially overlapping the first plurality of end flaps and closing the second end by at least partially overlapping the second plurality of end flaps.

6. The method of claim 5, wherein the loading the at least one article comprises arranging a plurality of the articles in at least one row that extends from the first end to the second end, the at least one article protection flap being positioned between two respective adjacent articles in the at least one row.

7. The method of claim 6, wherein the at least one row comprises at least three rows and the at least one article protection flap comprises at least three article protection flaps, the folding the at least one article protection flap comprises positioning each article protection flap between adjacent articles in a respective one of the at least three rows.

8. The method of claim 7, wherein the at least three article protection flaps are primary article protection flaps, the carton further comprising secondary article protection flaps foldably connected to the at least one panel, the method further comprises folding the secondary article protection flaps after the loading of the plurality of articles.

9. The method of carton of claim 1, wherein the at least one article protection flap has features for preventing folding of the at least one article protection flap from the second position to the first position.

10. The method of claim 9, wherein the at least one article protection flap comprises a first portion and a second portion, and the folding of the at least one article protection flap comprises folding the first portion and the second portion relative to each other.

11. The method of claim 10, wherein the first portion and the second portion are folded about a fold line during the

folding so that the first portion and the second portion are inwardly folded relative to each other.

12. The method of claim 11, wherein the at least one panel comprises an opening formed by the folding of the at least one article protection flap from the first position to the second position, the opening having an edge at least partially formed by a line of weakening defining at least a portion of the at least one article protection flap, the features for preventing folding of the at least one article protection flap comprise a free edge of at least one of the first portion and the second portion that are positioned to extend beyond the edge of the opening during the folding the first portion and the second portion relative to each other.

13. The method of claim 12, wherein the features for preventing folding of the at least one article protection flap comprises a distal portion of the first portion and a distal portion of the second portion.

14. The method claim 13, wherein the features for preventing folding of the at least one article protection flap comprises a heel of the at least one article protection flap at the distal end of the at least one article protection flap.

15. The method of claim 10, wherein the at least one article protection flap is foldably connected to the at least one panel at a first fold line, the at least one article protection flap comprises a second fold line extending from the first fold line and a third fold line extending from the first fold line, the at least one article protection flap comprises a central portion at least partially defined by the first fold line, the second fold line, and the third fold line, the first fold line is a longitudinal fold line, the second fold line extends from the first fold line and the third fold line extends from the first fold line, the folding the first portion and second portion relative to each other comprises folding the first portion at the second fold line and folding the second portion at the third fold line.

16. The method of claim 1, wherein at least one panel comprises a plurality of panels comprising a bottom panel, a first side panel foldably connected to the bottom panel, and a second side panel foldably connected to the bottom panel, the positioning the plurality of panels comprises positioning the first side panel and the second side panel relative to the bottom panel.

17. The method of claim 16, wherein the plurality of panels further comprises a top panel foldably connected to the first side panel and the second side panel, the positioning at least one panel comprises positioning the first side panel relative to the bottom panel, positioning the second side panel relative to the bottom panel, and positioning the top panel relative to the first side panel and the second side panel.

18. The method of claim 1, wherein the folding the at least one article protection flap comprises engaging the at least one article protection flap with a finger of a mechanism for forming the carton.

19. The method of claim 1, wherein the folding the at least one article protection flap comprises contacting the at least one article and moving the article.

20. The method of claim 1, wherein the loading at least one article comprises loading a plurality of beverage bottles, each of the plurality of beverage bottles comprises a bottom portion and a top portion.

21. The method of claim 20, wherein the plurality of panels comprises a bottom panel, a first side panel foldably connected to the bottom panel, a second side panel foldably

connected to the bottom panel, and a top panel foldably connected to at least one of the first side panel and the second side panel, the blank comprises at least two first end flaps each being respectively foldably connected to a respective panel of the plurality of panels and at least two second end flaps each being respectively foldably connected to a respective panel of the plurality of panels, the at least one article protection flap is foldably connected to the bottom panel, and the method further comprises folding the at least two first end flaps to close a first end of the carton and folding the at least two second end flaps to close a second end of the carton.

22. The method of claim 21, wherein the folding of the at least one article protection flap tightens the packing of the beverage bottles by contact of the article protection flap with two adjacent beverage bottles.

23. The method of claim 21, wherein the at least one article protection flap is folded into contact with a respective bottom portion of each of two adjacent beverage bottles when the at least one article protection flap is moved to the second position.

24. The method of claim 23, wherein the folding the at least one article protection flap comprises pressing the at least one article protection flap against the bottom portion of each of the two adjacent beverage bottles and moving the two adjacent beverage bottles.

25. The method of claim 24, wherein in the second position of the at least one article protection flap, the movement of the beverage bottles is limited by the positioning of the at least one article protection flap, the at least two first end flaps at the first end, and the at least two second end flaps at the second end.

26. The method of claim 24, wherein the moving the two adjacent beverage bottles comprises moving the two adjacent beverage bottles in respective opposite directions so that one of the two adjacent beverage bottles is moved toward the first end and the other of the two adjacent beverage bottles is moved toward the second end.

27. The method of claim 26, wherein the two adjacent beverage bottles comprise a first beverage bottle and a second beverage bottle,

the first beverage bottle and the second beverage bottle being in a respective first bottle position after the loading of the plurality of beverage bottles and the closing the first end and the closing the second end,

the moving the two adjacent beverage bottles comprises moving the first beverage bottle and the second beverage bottle from the respective first bottle position to a respective second bottle position, wherein in the respective second bottle position the first beverage bottle is moved closer to the first end of the carton and the second beverage bottle is moved closer to the second end of the carton.

28. The method of claim 27, wherein the first beverage bottle and the second beverage bottle are in the first beverage bottle position when the at least one article protection flap is in the first position, and the first beverage bottle and the second beverage bottle are moved to the second beverage bottle position when the at least one article protection flap is moved from the first position to the second position.

29. The method of claim 21, wherein the at least one article protection flap comprises a plurality of article protection flaps, and the folding of the at least one article protection flap comprises positioning each of the plurality of

article protection flaps between respective adjacent beverage bottles of the plurality of beverage bottles.

30. The method of claim **21**, wherein the loading the plurality of beverage bottles comprises arranging the plurality of beverage bottles in at least one row that extends from the first end to the second end.

31. The method of claim **30**, wherein the at least one article protection flap comprises a first article protection flap and a second article protection flap, the first article protection flap is adjacent to the second article protection flap, the first article protection flap and the second article protection flap contact respective adjacent beverage bottles in the at least one row of beverage bottles.

32. The method of claim **31**, wherein the second article protection flap is oriented 180 degrees relative to the first article protection flap.

33. The method of claim **30**, wherein the at least one row of beverage bottles comprises at least three rows and the at least one article protection flap comprises at least three article protection flaps, the folding the at least one article protection flap comprises positioning each article protection flap between adjacent articles in a respective one of the at least three rows of beverage bottles.

34. The method of claim **21**, wherein the folding the at least one article protection flap comprises engaging the at least one article protection flap with a finger of a mechanism for forming the carton.

35. The method of claim **34**, wherein the mechanism for forming the carton is part of a system for activating the at least one article protection flap, the system for activating the at least one article protection flap is downstream of a carton forming machine that forms the interior space of the carton, loads the plurality of beverage bottles, closes the first end of the carton, and closes the second end of the carton.

36. The method of claim **35**, further comprising conveying a carton from the carton forming machine to the system for activating the at least one article protection flap.

37. The method of claim **21**, wherein the folding the article protection flap is after the folding the at least two first end flaps and the folding the at least two second end flaps.

38. The method of claim **21**, wherein the positioning the at least one panel comprises forming a sleeve and the loading the beverage bottles comprising placing the beverage bottles in the sleeve and the closing the first end and the closing the second end encloses the interior space of the carton defined by the plurality of panels, the closed first end, and the closed second end, the plurality of beverage bottles being in a first packing configuration in the interior space after the closing of the first end and the closing of the second end.

39. The method of claim **38**, wherein the moving the at least one article protection flap moves the plurality of beverage bottles to a second packing configuration in the interior space, whereby movement of the beverage bottles in the second packing configuration is limited by the positioning of the at least one article protection flap and the closed first end and the closed second end.

40. The method of claim **39**, wherein the loading the plurality of beverage bottles comprises arranging the plurality of beverage bottles in at least one row that extends from the first end to the second end, the moving the plurality of beverage bottles to the second packing configuration comprises pressing the at least one article protection flap against two adjacent beverage bottles in the at least one row.

41. The method of claim **40**, wherein the moving the plurality of beverage bottles to the second packing configuration comprises moving the two adjacent beverage bottles in respective opposite directions so that one of the two adjacent beverage bottles is moved toward the first end and the other of the two adjacent beverage bottles is moved toward the second end.

42. The method of claim **20**, wherein the moving the at least one article protection flap causes the beverage bottles to move to accommodate the space required for the at least one article protection flap in the second position.

43. The method of claim **42**, wherein the movement of the beverage bottles tightens packing of the bottles in the carton.

* * * * *