

(19) AUSTRALIAN PATENT OFFICE

(54) Title
Biliqid foam entrapment.

(51)⁶ International Patent Classification(s)

A61F 13/49 (2006.01) 9/20
A61F 13/15 (2006.01) 20060101ALI2006031
A61F 13/472 0BMJP **A61K**
(2006.01) 9/48
A61K 8/00 (2006.01) 20060101ALI2006031
A61K 8/04 (2006.01) 0BMJP **A61K**
9/50
A61K 8/11 (2006.01) 20060101ALI2006031
A61K 8/18 (2006.01) 0BMJP **A61K**
A61K 8/73 (2006.01) 47/06
A61K 9/20 (2006.01) 20060101ALI2006031
A61K 9/48 (2006.01) 0BMJP **A61K**
A61K 9/50 (2006.01) 47/10
A61K 47/06 (2006.01) 20060101ALI2006031
A61K 47/10 (2006.01) 0BMJP **A61K**
A61K 47/12 (2006.01) 47/12
A61K 47/14 (2006.01) 20060101ALI2006031
A61K 47/32 (2006.01) 0BMJP **A61K**
A61K 47/34 (2006.01) 47/14
A61K 47/36 (2006.01) 20060101ALI2006031
A61K 47/38 (2006.01) 0BMJP **A61K**
A61K 47/42 (2006.01) 47/32
A61K 47/44 (2006.01) 20060101ALI2006031
A61Q 13/00 (2006.01) 0BMJP **A61K**
A61Q 15/00 (2006.01) 47/34
A61Q 17/04 (2006.01) 20060101ALI2006031
B01J 13/04 (2006.01) 0BMJP **A61K**
47/36
C11D 3/50 (2006.01) 20060101ALI2006031
C11D 11/00 (2006.01) 0BMJP **A61K**
C11D 17/00 (2006.01) 47/38
C11D 17/04 (2006.01) 20060101ALI2006031
C11D 17/06 (2006.01) 0BMJP **A61K**
G09F 3/03 (2006.01) 47/42
A61F 13/49 20060101ALI2006031
20060101AFI2006031 0BMJP **A61K**
0BMJP **A61F** 47/44
13/15 20060101ALI2006031
20060101ALI2006031 0BMJP **A61Q**
0BMJP **A61F** 13/00
13/472 20060101ALI2005100
20060101ALI2006031 8BMEP **A61Q**
0BMJP **A61K** 15/00
8/00 20060101ALI2006031
20060101ALI2006031 0BMJP **A61Q**
0BMJP **A61K** 17/04
8/04 20060101ALI2006031
20060101ALI2005100 0BMJP **B01J**
8BMEP **A61K** 13/04
8/11 20060101ALI2006031
20060101ALI2005100 0BMJP **C11D**
8BMEP **A61K** 3/50
8/18 20060101ALI2005100
20060101ALI2006031 8BMEP **C11D**
0BMJP **A61K** 11/00
8/73 20060101ALI2008053
20060101ALI2005100 1BMEP **C11D**
8BMEP **A61K** 17/00

20060101ALI2008053	20060101ALI2008053		
1BMEP	C11D	1BMEP	G09F
17/04		3/03	
20060101ALI2005100	20060101ALI2005100		
8BMEP	C11D	8BMEP	
17/06		PCT/GB2003/002713	

(21) Application No: 2003236910

(22) Application Date: 2003.06.24

(87) WIPO No: WO04/002436

(30) Priority Data

(31) Number	(32) Date	(33) Country
0214793.2	2002.06.26	GB

(43) Publication Date: 2004.01.19

(43) Publication Journal Date: 2004.03.04

(71) Applicant(s)

Drug Delivery Solutions Limited

(72) Inventor(s)

Gladman, David Charles Fletcher, Lenon, Stephen John, Crutchley, Nigel Stuart

(74) Agent/Attorney

Davies Collison Cave, 1 Nicholson Street, Melbourne, VIC, 3000

(56) Related Art

CH 664372A

US 6165 479A

US 3016308

US 3549555

WO 0162214 A

US 4986429 A

DE 10107217 A

US 6358 493 B1

US 6312760 B1

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/002436 A1

(51) International Patent Classification²: A61K 7/00, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PI, PT, RO, RU, SC, SD, SE, SG, SK, SL, TI, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/GB2003/002713

(22) International Filing Date: 24 June 2003 (24.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 0214793.2 26 June 2002 (26.06.2002) GB

(71) Applicant (for all designated States except US): DISPERSE LIMITED [GB/GB]; Surrey Research Park, 40 Alan Turning Road, Guildford, Surrey GU2 7YF (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CRUTCHLEY, Nigel, Stuart [GB/GB]; 27 Roding Gardens, Loughton, Surrey IG10 3NH (GB). GLADMAN, David, Charles, Fletcher [GB/GB]; 35 Oast House Crescent, Farnham, Surrey GU9 0NP (GB). LENON, Stephen, John [GB/GB]; 19 Foxglove Gardens, Merrow Park, Guildford, Surrey GU4 7ES (GB).

(74) Agents: ALLARD, Susan, Joyce et al.; BOULT WADE TENNANT, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).

(81) Designated States (national): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TI, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW. ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TI, TM). European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PE, RO, SE, SI, SK, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TI, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW. ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TI, TM). European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PE, RO, SE, SI, SK, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BILIQUE FOAM ENTRAPMENT

(57) Abstract: A discrete powder which comprises particles in which a biliquid foam has been entrapped within a matrix of a polymeric material. A process for the preparation of these discrete powders comprises the steps of: i) preparing a biliquid foam, ii) forming a dispersion of the biliquid foam in an aqueous solution, suspension or dispersion of a polymeric material, and iii) subjecting the dispersion to drying under conditions such that a discrete powder is formed.

WO 2004/002436 A1

BILIQUEID FOAM ENTRAPMENT

The present invention relates to biliqid foam entrapment and, in particular, to a biliqid foam 5 entrapped within a matrix of a polymeric material which is in the form of a discrete powder.

The entrapment of oils or oil soluble substances (especially perfumes and coloured dye precursors) in microcapsules and their subsequent coating onto paper 10 and other surfaces is well known in the art.

Microcapsules of this type comprise individual droplets of oil or oil soluble substances (of size ranging from sub-micrometre to tens of millimetres in diameter) around which polymer walls have been formed 15 by one of a number of chemical processes. Usually such microcapsules are prepared as an aqueous suspension which is then capable, with the addition of suitable modifying reagents, of being sprayed or printed onto paper and other surfaces. The object in so doing is 20 usually to prevent the evaporation of volatile substances (for example, perfumes) or the degradation or chemical reaction of oil soluble species (for example, colourless dye precursors) until the microcapsules are broken by the application of shear 25 forces by scratching or scraping the coated surface with the consequent release of their contents. Such coatings find major uses, for example, in the forms of "scratch and sniff" perfume coatings or NCR (No Carbon Required) paper.

30 However, these microcapsules suffer from a number of disadvantages.

Firstly, the process by which microcapsules are formed is a lengthy and uncertain one in which control 35 over temperature, pH and the absence of any form of contamination is essential. The formation of microcapsules, for example, by complex coacervation from gelatin and an anionic complexing species such as

- 2 -

gum acacia takes many hours and demands very close control of pH, temperature and cooling rate. Similarly, the formation of microcapsule walls from aminoplast resins, such as melamine-formaldehyde or 5 urea-formaldehyde takes at least eight hours during which precise control over all controllable parameters needs to be effected. Moreover, the effectiveness and completeness of any individual encapsulation process (and therefore the quality of the microcapsules so 10 formed) depends largely on the chemical nature of the oil and/or oil soluble substances being encapsulated.

A further disadvantage of microcapsulation is 15 that the thickness and therefore the strength of the microcapsule wall is variable and is not easily controllable and varies with the nature of the oil or oil-soluble substances being encapsulated. Thus microcapsules made by the same process but from 20 different oils may have widely differing strengths and resistance to breakage during the printing process and during subsequent storage and use.

A yet further disadvantage of microencapsulation 25 is the limited number of chemical processes and the limited number and type of polymeric wall materials which are available to form them. The choice as to the properties of the wall materials is consequently limited with regard to their flexibility, tensile strength, permeability, chemical inertness, mammalian toxicity and other properties including solubility and melting point (if any). In addition, some of the 30 chemicals commonly used in the wall forming process are themselves highly irritating and may themselves be toxic such, for example, as the use or release of formaldehyde (a potential carcinogen) during the manufacture of aminoplast resin walls. Moreover, the 35 remaining traces of formalin in the resulting microcapsule suspension are virtually impossible to eliminate to below acceptable levels for uses of

- 3 -

microcapsules and requires special precautions to be taken during the manufacturing process.

Whilst many of the processes to produce microcapsules produce dispersions of the microcapsules 5 in a fluid medium, they can also be produced in the form of a powder.

Other methods of encapsulating oil within a powder are generally based upon the drying of an oil-in-water dispersion. Examples of this prior art 10 include EP-B-0938932 which discloses a process for manufacturing a cosmetic and/or dermatological powder in which an oil-in-water dispersion comprising at least one modified starch is dehydrated to form a powder and US-A-6129906 in which a granular powder is 15 formed by spray drying an aqueous dispersion of a silicone oil and a water-soluble carrier, the silicone oil being present in the dispersion as discrete droplets having a droplet size in the range of from 0.5 μ m to 20 μ m.

WO 99/05299 discloses a surface coating in which 20 droplets of a non-polar substance are trapped within a polymer film, the surface coating being prepared by drying a dispersion of a film forming polymer containing droplets of a suspended biliquid foam or 25 emulsion. Surface coatings only are disclosed and this reference does not teach the drying of the dispersions to form a powder.

We have now developed a discrete powder which is based upon the encapsulation of a biliquid foam.

Accordingly, in one aspect of the present 30 invention provides a discrete powder which comprises particles in which a biliquid foam has been entrapped within a matrix of a polymeric material.

In another aspect the present invention provides 35 a process for the preparation of a discrete powder which comprises a biliquid foam entrapped within a matrix of a polymeric material, which process

- 4 -

comprises the steps of:

- i) preparing a biliquid foam,
- ii) forming a dispersion of the biliquid foam in an aqueous solution, suspension or dispersion of a polymeric material, and
- iii) subjecting the dispersion to drying under conditions such that a discrete powder is formed.

5 The discrete powder of the present invention is 10 preferably produced by spray drying of the dispersion.

Biliquid foams are known in the art and are described in the following literature references by Sebba: "Biliquid foams", *J. Colloid and Interface Science*, 40 (1972) 468-474; and "The Behaviour of 15 Minute Oil Droplets Encapsulated in a Water Film", *Colloid Polymer Sciences*, 257 (1979) 392-396. Neither of these articles suggest that biliquid foams might be used in the preparation of spray dried powders.

20 US Patent No. 4486333 to Sebba describes a particular method for the preparation of biliquid foams by agitating a hydrogen bonded liquid containing a soluble surfactant to produce a gas foam and intermittently adding to the gas foam a non-polar liquid which is immiscible with the hydrogen bonded 25 liquid, the surfactant-containing hydrogen bonded liquid being selected to provide a spreading coefficient equal to or greater than zero.

20 The oil-based biliquid foam used in the spray dried powders of the present invention will preferably comprise from 70 to 95% by weight of the oil phase and from 5 to 30% by weight of the continuous phase. A surfactant to stabilise the biliquid foam may also be included in an amount of from 0.01 to 3%, preferably from 0.1 to 1% based on the total weight of the 35 biliquid foam. The surfactant may dissolve in either the oil phase, the continuous phase or both phases of the biliquid foam. Generally, the level of surfactant

- 5 -

used in the formation of the biliquid foams is lower than the level used in the preparation of conventional dry emulsion systems.

Oils which may be used in the biliquid foam will 5 in general be substantially water immiscible and liquid at room temperature and may be, for example, a cyclomethicone, dimethicone, phenyl trimethicone, dimethiconol, dimethicone copolyol, trimethylsiloxy-silicate, an emollient ester such as isopropyl 10 isostearate, lanolate, myristate or palmitate, or octyl palmitate, a glyceride such as avocado oil, coconut oil, soybean oil or sunflower oil, or a caprylic/capric triglyceride, a lanolin oil, orange oil, mineral oil or natural oil, or oleyl alcohol, or 15 any other oil generally known for this purpose, or mixtures of the foregoing. It will be understood that the present invention enables oils to be incorporated into the powder which would normally be difficult to incorporate into conventional dry emulsion systems.

20 It will be understood that the oil phase of the biliquid foam may contain or consist of one or more active ingredients such as fragrances, flavours, deodorisers, perfumes, pharmaceuticals, sunscreens, dyes, pesticides, insect repellants, herbicides, etc.

25 The biliquid foam may contain, as described above, a low level of a surfactant which may be, for example:-

30 a cationic surfactant such as an amidoamine, a quaternary ammonium compound or a sulphonium salt; an amphoteric surfactant such as an acylamino-acid, an N-substituted alkylamine, an N-alkyl- β -amino-propionate, an N-alkylbetaine, an alkylimidazoline or a sulphobetaine;

35 an anionic surfactant such as an acyl-lactate, N-acylsarcosinate, alkyl-carboxylate (either mono- or polyvalent), alkyl ether carboxylate, N-alkyl-glutamate, fatty acid-peptide condensate, phosphated

- 6 -

ethoxylated alcohol, alkyl sulphate, ethoxylated alkyl sulphate, alpha-olefin sulphonate or ester-linked sulphonate;

5 a nonionic surfactant such as an alkanolamide, amine oxide, ester of a polyhydric (for example an ester of an ethylene, diethylene or propylene glycol, or glycerol or a polyglycerol, or sorbitan, glucose or sucrose), a polyoxyethylene or polyoxypropylene derivative of an alcohol, amide or ester, or a 10 polyoxyethylene/polyoxypropylene block copolymer; or a suitable compatible mixture of these surfactants.

15 The continuous phase of the biliquid foam is generally an aqueous phase which may include therein a substantial level of a C₁-C₄ (water miscible) alcohol, or ethylene glycol or mixtures thereof.

20 The continuous phase of the biliquid foam may include therein preservatives, stabilizers or other materials known in the art.

25 Methods of producing biliquid foams are described in US-A-4486333 involving the preliminary formation of a gas foam in order to provide a sufficiently large surface area on which the biliquid foam can subsequently be formed. It has been found that the prior formation of a gas foam is not required to manufacture a stable biliquid foam, provided that a suitable stirring mechanism is provided in the manufacturing vessel. An aspect of the present invention is the ability to manufacture biliquid foams 30 without the preliminary formation of gas foam, by the use of a tank incorporating a suitable stirring mechanism.

35 Such an apparatus comprises a tank provided with a stirrer in which the stirrer blade breaks the interface between the liquid and air. A delivery device is provided through which the oil phase (water immiscible liquid), which will comprise the internal

- 7 -

phase of the dispersion, is delivered to the tank. The design of the delivery device is such that the rate of addition of the internal phase fluid can be controlled and varied during the production process.

5 A feature of the production process is that the internal (oil) phase is added to the stirred aqueous phase slowly at first until sufficient droplets have been formed to constitute a large, additional surface area for the more rapid formation of new droplets. At 10 this point, the rate of addition of the oil phase may be increased.

The production process consists of the following steps:

- 15 1. The addition of one or more chosen surfactants to one or other or both phases (as previously determined by experiment).
2. The charging of the aqueous phase into the bottom of a process vessel.
3. The incorporation of the stirrer into the 20 vessel so that it stirs the surface of the aqueous phase.
4. Adjustment of the stirrer speed to a previously determined level.
5. The slow addition of the internal phase 25 whilst continuing to stir at the prescribed speed.
6. The speeding up of the rate of addition of the oil phase once a prescribed amount (usually between 5% and 10% of the total 30 amount to be added) has been added.

The stirring rate and the rate of addition of the oil phase are variables, the values of which depend upon the detailed design of the manufacturing plant (in particular, the ratio of tank diameter to impeller 35 diameter), the physico-chemical properties of the oil phase and the nature and concentrations of the chosen surfactants. These can all be pre-determined by

- 8 -

laboratory or pilot plant experiment.

It will be understood by those skilled in the art that other manufacturing methods may be used to produce the biliquid foams, as appropriate.

5 In the present invention the biliquid foam is entrapped within a polymeric material and thereby forms a discrete powder. Water-dispersible or water-soluble film forming polymers of many types are well known and include cellulose derivatives (for example, 10 carboxymethylcellulose, hydroxyethylcellulose, cetylhydroxycellulose, hydroxypropylcellulose, hydroxypropylmethylcellulose, hydroxyethylmethylcellulose and methylcellulose), gelatin, gum arabic, gum acacia, gellan gum, shellac, carragenan, natural 15 starches, modified starches, xanthan gums, alginates, dextrans, polyvinyl alcohol, polyvinyl acetate, polyvinyl pyrrolidone or polyamides and other water dispersible or water soluble film forming agents known in the art. The present invention may include the use 20 of all the above singly or in combination. Certain of the polymers may only be water-dispersible or water-soluble at elevated temperatures and therefore in the preparation of the dispersions of the biliquid foams and during spray drying, the dispersion mixture would 25 be used at these elevated temperatures. Industrial, food or pharmaceutical grade polymers may be used, depending upon the end use of the dried powder.

In carrying out the process of the present invention for forming a discrete powder the suspension 30 of the biliquid foam in an aqueous solution, suspension or dispersion of the polymeric film former is dried under conditions such that a discrete powder is formed. Preferably the said dispersion is spray dried. The choice of suitable spray drying conditions 35 will be within the knowledge of a person skilled in the art and will depend upon various factors, including the melt temperature of the polymeric

- 9 -

material, the amount of water contained in the dispersion, the ratio of polymeric material to the biliquid foam etc. Generally the inlet temperature for the spray dryer will be in the range of from 170° 5 to 210°C and the outlet temperature will be in the range of from 85 to 110°C.

The dispersion which is subjected to drying may also incorporate a structuring or gelling agent therein. Any such agent must, however, shear thin 10 when the dispersion is subjected to atomisation forces, for example during spray drying. Such a structuring or gelling agent may assist in maintaining the integrity of the dispersion prior to the drying process.

15 Typically, in carrying out the present invention the biliquid foam will have a mean droplet size in the range of from 1 to 45 micrometres. A biliquid foam having such a droplet size can generally be produced under low shear conditions. For the purpose of the 20 present invention the droplet size of the majority of the droplets of the biliquid foam should preferably be further reduced to below 12 micrometres, for example by using higher shear conditions.

The biliquid foam is then mixed with an aqueous 25 solution, suspension or dispersion of the polymeric material under conditions which generate a homogeneous dispersion. For example, using gentle stirring or using a high shear device, such as a Roto Stator mixer.

30 It will be understood that although spray drying is the preferred method of producing the discrete powders of the present invention, other drying techniques, such as freeze drying and fluidized bed granulation can also be used.

35 The discrete powders of the present invention generally incorporate high levels of oil entrapped within the polymeric material, typically from 5 to 50%

- 10 -

by weight, preferably from 20 to 40% by weight based on the weight of the powder.

The discrete powders of the present invention will generally have a mean particle size in the range 5 of from 5 to 150 μ m. It will be understood, however, that larger particle sizes may be obtained by the use of techniques known in the art, such as granulation. The size range may then be of the order of 5 μ m to 1mm.

The invention provides a means of controlling the 10 rate of release of the oil entrapped within the polymeric material by exercising control over the concentration and ratio to the biliquid foam of the film forming polymer in solution or suspension and thereby controlling the thickness and strength of the 15 film forming the outside of the particles.

The invention also allows for release of the oil 20 by dissolution of the film by contact with water or other polar solvent. For example, the powder may contain a fragrance or aromatherapy oil and be 25 sprinkled onto water in a bath. In addition, the water-soluble or water dispersible film forming polymer may be partially or wholly crosslinked to render it partially or totally water insoluble by which means the rate of release of the entrapped 30 biliquid foam may be controlled by the speed or absence of dissolution when the powder makes contact with water or other polar liquid in which it might otherwise be soluble. Different powders could then be mixed together in order to give a range of release rates, if required.

Alternatively, the choice of film-forming polymer 35 may be such that it is sensitive to acidity or alkalinity so that the release of the entrapped oil may be determined by a change of pH or by the presence of another chemical species with which the film-forming polymers may react, so rendering it permeable or unstable. Alternatively, the choice of film-

- 11 -

5 forming polymer may be such that it is sensitive to temperature or biological conditions. The powder may alternatively comprise a polymer which melts at a known and predetermined temperature to release the entrapped oil.

10 In one embodiment, the entrapped biliquid foam may comprise a perfume which, when dried into a discrete powder will behave and perform precisely as a conventional, microencapsulated "scratch and sniff" perfume as previously described. Furthermore, an encapsulating polymer may be chosen that allows the release of the perfume by diffusion over time, such as in a room fragrancing device.

15 In another embodiment, a perfume or deodorising composition is entrapped according to this invention in a discrete powder which is incorporated into a diaper, incontinence pad or feminine hygiene product during manufacture so that the perfume or deodorising composition is released on contact with aqueous bodily fluids when the diaper, incontinence pad or feminine hygiene product is used, thereby masking or neutralising any disagreeable odour.

20 25 In another embodiment, the powder may be provided as a dry skin wash composition containing a cleansing, moisturising or emollient oil. In this instance, the dry powder would be applied to the skin and rubbed either with or without the addition of water in order to release the entrapped from the polymer matrix.

30 35 In another embodiment, the biliquid foam comprising a household cleaning oil, such as orange oil may be entrapped in water soluble polymer powder particles on a suitable applicator together with other reagents (for example, an abrasive material, such as a pumice or water soluble antimicrobial agents) to form a dry surface which, when wetted, becomes an effective hard surface cleaning product.

In another embodiment the powder may be provided

- 12 -

as a carpet or fabric cleaning or deodorizing composition and the oil will then comprise a suitable cleaning or deodorizing oil.

In yet another embodiment, the matrix forming 5 polymer may comprise a brittle film which ruptures easily when deformed so releasing the entrapped non-polar substance. In one application of this embodiment, the powder may be coated onto a flexible film which may, for example, be shrunk onto the cap of 10 a consumer product such that if the flexible film is removed, the particles rupture so releasing the non-polar substance which, in this instance, may be the colourless precursor of a coloured dye which, on release, undergoes a chemical change to become highly 15 coloured. This embodiment thereby gives a clear indication as to whether or not a closure has been tampered with. Alternatively, the powder may be incorporated into the film forming polymer precursor during the preparation of the flexible films. The 20 film forming polymer precursor will be chosen from suitable materials which do not dissolve the powder.

In a still further embodiment of the present 25 invention the discrete powder particles may be granulated or formed into tablets according to techniques known in the art. In these processes the powder may be combined with one or more binders, excipients, fillers, disintegrants or other suitable materials.

The powders of the present invention may also be 30 incorporated during extrusion of a polymer melt. In this instance the polymer system will be selected such that the polymer melt does not dissolve the polymer used in the preparation of the powders of the invention. The melt temperature of the polymer used 35 in forming the powders will also need to be greater than that of the extruding polymer.

The oil which is incorporated into the powder may

- 13 -

be chosen such that it boils at a given temperature, thereby rupturing the powder, or film or extruded polymer containing the powder, thereby causing a trigger release of the oil. This embodiment may be 5 used, for example, for the release of a latent catalyst which may enable controlled chemical modification of the extruding polymer to take place.

A still further release mechanism may be the use 10 of polymeric systems in the formation of the powders of the invention which are biodegradable, thermally degradable or photodegradable. The oil contained in the powders would then be released on degradation of the polymers.

The present invention will be further described 15 with reference to the following Examples.

PREPARATION OF BILIQUID FOAMS

Preparation 1

20 A biliiquid foam was prepared from the following ingredients.

	Ingredients	Weight (g)	%
Aqueous Phase			
25	Water	396	9.9
	Sodium lauryl ether sulphate	4	0.1
Oil Phase			
30	Volpo L3	36.4	0.9
	Medium viscosity white mineral oil	3563.6	89.1
	Total	4000	100

35 The biliiquid foam was prepared by adding the oil phase to the aqueous phase and stirring with a flat bladed stirrer at 300 rpm until the mean droplet size

- 14 -

was 15-20 micrometres.

A 1kg sample was removed and this was stirred with a flat bladed stirrer at 500 rpm until the mean droplet size was 11 micrometres.

5

Preparation 2

	Ingredients	Weight (g)	%
Aqueous Phase			
10	Water	148.5	9.9
	Tween 20	1.5	0.1
Oil Phase			
	PEG25 castor oil	13.5	0.9
	KMC	1269.7	84.65
15	Pergascript Red I-6B	66.8	4.45
	Total	1500.0	100

The biliquid foam was prepared by adding the oil phase to the aqueous phase and stirring with a flat bladed stirrer at 116 rpm. The mean droplet diameter was 35 micrometres. The stirrer speed was then increased to 250 rpm and stirred until the mean droplet size was less than 12 micrometres.

25

Preparation 3

	Ingredients	Weight (g)	%
Aqueous Phase			
	Water	47.67	9
30	Sodium lauryl ether sulphate	0.53	0.1
Oil Phase			
	Laureth 3	4.77	0.9
	Dow Corning 200 50cst	476.74	90.0
35	Total	529.71	100

- 15 -

The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 200 rpm for 45 minutes.

5

Preparation 4

	Ingredients	Weight (g)	%
Aqueous Phase			
	Water	44.97	9
10	Sodium lauryl ether sulphate	0.5	0.1
	Kathon 1CG II	0.03	0.006
Oil Phase			
	Oleth 10	4.5	0.9
15	Orange oil	450.0	90.0
	Total	500	100

The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 200 rpm for 45 minutes.

Preparation 5

	Ingredients	Weight (g)	%
Aqueous Phase			
	Water	52.60	9.8
25	Sodium lauryl ether sulphate	0.532	0.1
	Kathon 1CG II	0.026	0.0048
Oil Phase			
	Etocas 25 (PEG25 Castor oil)	4.78	0.9
30	Rose oil fragrance L301844	478.44	89.2
	Total	536.378	100

- 16 -

The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 200 rpm for 45 minutes.

5

Preparation 6

	Ingredients	Weight (g)	%
Aqueous Phase			
	Water	14.85	9.9
10	Tween 20	0.15	0.1
Oil Phase			
	Oleth 10	1.35	0.9
	Octyl methoxy cinnamate	133.65	89.1
	Total	150	100

15

The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 200 rpm for 45 minutes.

20

Preparation 7

	Ingredients	Weight (g)	%
Aqueous Phase			
	Water	11.29	8.79
25	Tween 20	0.26	0.20
Oil Phase			
	PEG25 castor oil	0.64	0.5
	Oleth 10	0.64	0.5
	Household Fragrance oil	115.55	90
30	Total	128.38	100

The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 200 rpm for 45 minutes.

35

- 17 -

Preparation 8

	Ingredients	Weight (g)	%
Aqueous Phase			
5	Water	9	9
	Laureth 23	1	1
Oil Phase			
	Gransil GCM-5	49.24	49.24
	Cetearyl isonanoate	7.78	7.78
10	Isopar K	7.78	7.78
	Dow Corning 200 50cst	0.97	0.97
	Gransil DMCM-5	24.25	24.25
	Total	100	100

15 The biliquid foam was prepared by adding the oil phase to the aqueous phase and stirring with a flat bladed stirrer at 174 rpm. The stirrer speed was increased to 300 rpm to help with the inclusion of the oil before continuing to stir at 174 rpm until the 20 mean droplet size was 11 μm .

Preparation 9

	Ingredients	Weight (g)	%
Aqueous Phase			
25	Water	9.9	9.9
	Tween 20	0.1	0.1
Oil Phase			
	Ibuprofen	4.5	4.5
30	Isopropyl myristate	84.5	84.5
	Laureth 3	1	1
	Total	100	100

35 The biliquid foam was prepared by adding the oil phase (ibuprofen fully dissolved in the isopropyl myristate) to the aqueous phase and stirring with a

- 18 -

flat bladed stirrer at 174 rpm. The preparation was stirred after the inclusion of the oil until the mean droplet size was 18 micrometres.

5

Preparation 10

	Ingredients	Weight (g)	%
Aqueous Phase			
	Water	49.5	9.9
10	Tween 20	0.5	0.1
Oil Phase			
	PEG25 castor oil	2.5	0.5
	Oleth 10	2.5	0.5
	Household Fragrance oil	445	89
15	Total	500	100

20 The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 220 rpm for 60 minutes. The procedure was repeated twice more to generate three 500g batches which were blended together for use in spray drying examples.

25

Preparation 11

	Ingredients	Weight (g)	%
Aqueous Phase			
	Water	99	9.9
	Sodium lauryl ether	1	0.1
30	sulphate		
Oil Phase			
	Laureth 4	9	0.9
	Mineral oil with red dye	891	89.1
35	Total	1000	100

- 19 -

5 The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 110 rpm for 30 minutes. The preparation was then sheared at 230 rpm until the droplet size was less than 10 microns.

Preparation 12

	Ingredients	Weight (g)	%
Aqueous Phase			
10	Water	39.6	9.9
	Tween 20	0.4	0.1
Oil Phase			
	Emulsifier A	4	1
	Deodorising oil	356	89
15	Total	500	100

20 The biliquid foam was prepared by adding the oil phase to the aqueous phase whilst stirring with a flat bladed stirrer at 180 rpm for 60 minutes. The preparation was stirred at 230 rpm until the droplet size was less than 10 microns.

Emulsifier A consists of:

25	Ethoxylated isotridecanol (9EO)	52.52%
	Dipropylene glycol	25.25%
	PEG 40 Hydrogenated castor oil	22.23%

- 20 -

Preparation of Dispersions and Spray Drying

EXAMPLE 1

5 The dispersion was prepared by stirring the biliquid foam into the aqueous polymer immediately before spray drying.

	Ingredients	Weight (g)	%
10	Preparation 1	76.9	7.7
	Gum acacia (30% by weight in demineralized water)	923.1	92.3
	Total	1000	100

	Spray drying conditions
15	Pilot plant Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles 34.6%
	Oil: polymer (dry basis) 20:80
	Inlet/outlet temperature 200°C/95°C
	Yield 85.2%
20	Comment
Product Characterisation	
	Nature of dry particle Fine powder
	Oil encapsulation Good
	Oil release Moderate amount of loose oil visible on release.
25	Mean droplet size before spraying 1.99 μ m

- 21 -

EXAMPLE 2

The dispersion was prepared by stirring the
 5 biliquid foam into the aqueous polymer immediately
 before spray drying.

Ingredients	Weight (g)	%
Preparation 1	73.85	8.7
PVP K30 (30% by weight 10 in demineralized water)	465.9	54.8
Mowiol (5% by weight in demineralized water)	310.6	36.5
Total	850.4	100

15	Spray drying conditions	
Pilot plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.	
Total non volatiles	26%	
Oil: polymer (dry basis)	30:70	
Inlet/outlet temperature	210°C/110°C	
20 Yield	about 100%	
Comment		
Product Characterisation		
Nature of dry particle	Good	
Oil encapsulation	Good	
25 Oil release	Little visible oil.	
Mean droplet size before spraying	6.1µm, peak at 11µm.	

- 22 -

EXAMPLE 3

The dispersion was prepared by stirring the biliquid foam and water into the aqueous polymer immediately before spray drying.

	Ingredients	Weight (g)	%
5	Preparation 1	100	11.7
	Water	74.64	8.7
	Maltodextrin (40% by weight in demineralized water)	52.5	6.1
10	PVP k30 (30% by weight in demineralized water)	630	73.5
	Total	847.14	100

	Spray drying conditions
15	Pilot plant Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles
	Oil: polymer (dry basis)
	Inlet/outlet temperature
	Yield
20	Comment Product slightly damp initially but spray dried well with higher outlet temperature.
	Product Characterisation
	Nature of dry particle
	Oil encapsulation
	Oil release
25	Mean droplet size before spraying

- 23 -

EXAMPLE 4

The dispersion was prepared by stirring the
 5 biliquid foam and make up water into the aqueous polymer
 immediately before spray drying.

Ingredients	Weight (g)	%
Preparation 2	116.67	11.67
Water	66.67	6.67
10 PVP K30 (30% by weight in demineralized water)	816.67	81.67
Total	1000	100

Spray drying conditions	
15 Pilot plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
Total non volatiles	35%
Oil: polymer (dry basis)	30:70
Inlet/outlet temperature	203°C/95°C
Yield	64.21%
Comment	
Product Characterisation	
Nature of dry particle	Good
Oil encapsulation	Good
Oil release	Little visible free oil.
25 Mean droplet size before spraying	0.58µm, peaks at 0.15, 0.7 and 12µm.

- 24 -

EXAMPLE 5

The dispersion was prepared by stirring the
 5 biliquid foam and water into the aqueous polymers
 immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 3	89.9	11.7
	Water	67.1	8.7
10	Maltodextrin (40% by weight in demineralized water)	47.2	6.1
	PVP k30 (30% by weight in demineralized water)	566.6	73.5
15	Total	770.9	100

Spray drying conditions	
	Pilot plant
	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles
20	35%
	Oil: polymer (dry basis)
	30:70
	Inlet/outlet temperature
	195°C/95°C
	Yield
	56.6%
	Comment
	Spray dried well
Product Characterisation	
	Nature of dry particle
25	Good
	Oil encapsulation
	Good
	Oil release
	No visible oil on surface
	Mean droplet size before spraying
30	9.9µm

- 25 -

EXAMPLE 6

The dispersion was prepared by stirring the
 5 biliquid foam and water into the aqueous polymers
 immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 4	105.4	13.7
	Water	48.8	6.3
10	Maltodextrin (40% by weight in demineralized water)	614.7	79.9
	Total	768.9	100

	Spray drying conditions	
15	Pilot plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles	45%
	Oil: polymer (dry basis)	27.8 : 72.2
	Inlet/outlet temperature	195°C/95°C
20	Yield	about 100%
	Comment	Spray dried well
	Product Characterisation	
	Nature of dry particle	Good
	Oil encapsulation	Good
25	Oil release	Little visible oil.
	Mean droplet size before spraying	1.4µm

- 26 -

EXAMPLE 7

The dispersion was prepared by stirring the
5 biliquid foam and water into the aqueous polymers
immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 4	101.7	11.7
	Water	147.1	16.9
10	Maltodextrin (40% by weight in demineralized water)	266.9	30.6
	Gum acacia	355.9	40.8
	Total	871.6	100

15

Spray drying conditions	
	Pilot plant
	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles
	35%
	Oil: polymer (dry basis)
	30:70
20	Inlet/outlet temperature
	195°C/95°C
	Yield
	78.3%
	Comment
	Spray dried well
	Product Characterisation
	Nature of dry particle
	Good
25	Oil encapsulation
	Good
	Oil release
	Little visible oil at surface.
	Mean droplet size before spraying
	1.3µm

- 27 -

EXAMPLE 8

The dispersion was prepared by stirring the
biliquid foam and water into the aqueous polymers
5 immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 5	81.4	11.7
	Water	89.3	12.8
10	Maltodextrin (40% by weight in demineralized water)	128.3	18.4
	PVP k30 (30% by weight in demineralized water)	399.1	57.2
15	Total	698.1	100

	Spray drying conditions	
	Pilot plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles	35%
20	Oil: polymer (dry basis)	30:70
	Inlet/outlet temperature	195°C/95°C
	Yield	66.1%
	Comment	Spray dried well
	Product Characterisation	
25	Nature of dry particle	Good
	Oil encapsulation	Good
	Oil release	No visible oil at surface
30	Mean droplet size before spraying	0.95µm, peaks at 1µm and 6.5µm

- 28 -

EXAMPLE 9

The dispersion was prepared by stirring the
 5 biliquid foam and water into the aqueous polymer
 immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 6	100	11.7
	Water	74.64	8.7
10	Maltodextrin (40% by weight in demineralized water)	52.5	6.1
	PVP k30 (30% by weight in demineralized water)	630	73.5
15	Total	857.14	100

Spray drying conditions	
	Pilot plant
	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
20	Total non volatiles
	35%
	Oil: polymer (dry basis)
	30:70
	Inlet/outlet temperature
	175°C/95°C
	Yield
	92%
	Comment
	Spray dried well
Product Characterisation	
25	Nature of dry particle
	Good
	Oil encapsulation
	Good
	Oil release
	Minimal free oil visible on surface.
	Mean droplet size before spraying
	0.7µm, peak at 10µm

- 29 -

EXAMPLE 10

5 The dispersion was prepared by stirring the
biliquid foam and water into the aqueous polymers
immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 7	89.9	11.7
	Water	67.1	8.7
10	Maltodextrin (40% by weight in demineralized water)	47.2	6.1
	PVP k30 (30% by weight in demineralized water)	566.6	73.5
15	Total	770.9	100

Spray drying conditions	
	Pilot plant
	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
20	Total non volatiles
	35%
	Oil: polymer (dry basis)
	30:70
	Inlet/outlet temperature
	195°C/90°C
	Yield
	93.8%
	Comment
	Spray dried well
Product Characterisation	
25	Nature of dry particle
	Good
	Oil encapsulation
	Good
	Oil release
	Little visible oil on surface.
30	Mean droplet size before spraying
	2.39µm, peaks at 1.5µm and 7.5µm

- 30 -

EXAMPLE 11

The dispersion was prepared by stirring the
 5 biliquid foam and water into the aqueous polymers
 immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 8	67.2	11.3
	Water	50.2	8.5
10	Maltodextrin (40% by weight in demineralized water)	53.3	9.0
	PVP k30 (30% by weight in demineralized water)	423.3	71.3
15	Total	594	100

Spray drying conditions	
Pilot plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
Total non volatiles	35%
20 Oil: polymer (dry basis)	29:71
Inlet/outlet temperature	195°C/95°C
Yield	82.3%
Comment	Spray dried well
Product Characterisation	
Nature of dry particle	Good
Oil encapsulation	Good
Oil release	No visible free oil
30 Mean droplet size before spraying	7.26µm, peak at 11µm

- 31 -

EXAMPLE 12

The dispersion was prepared by stirring the
 5 biliquid foam and water into the aqueous polymers
 immediately before spray drying.

	Ingredients	Weight (g)	%
	Preparation 9	79.1	11.7
	Water	59.1	8.7
10	Maltodextrin (40% by weight in demineralized water)	41.5	6.1
	PVP k30 (30% by weight in demineralized water)	498.5	73.5
15	Total	678.1	100

Spray drying conditions	
Pilot plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
Total non volatiles	35%
20 Oil: polymer (dry basis)	30:70
Inlet/outlet temperature	195°C/98°C
Yield	76.5%
Comment	Spray dried well
Product Characterisation	
25 Nature of dry particle	Good
Oil encapsulation	Good
Oil release	Minimal free oil visible on surface.
Mean droplet size before spraying	18.71µm

- 32 -

Compression of the powder was performed using a tabletting machine. Successful tablets were produced. The powder was found to withstand high compression forces without affecting the redispersion of the oil droplets upon dissolution in deionised water and the droplet size distribution appeared unaffected.

- 33 -

EXAMPLE 13

The dispersion was prepared by stirring the
 5 biliquid foam and water into the aqueous polymers
 immediately before spray drying.

	Ingredients	Weight (g)	%
10	Preparation 10	136.11	13.61
	PVP k30 (40% by weight in demineralized water)	511.87	51.19
15	Water	295.15	29.52
	Maltodextrin (40% by weight in demineralized water)	56.87	5.69
	Total	1000	100

Spray Drying conditions	
20	Pilot Plant
	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	-Total non volatiles 35%
25	Oil : polymer (dry basis) 35 :65
	Inlet / outlet temperature 210°C/96°C
	Yield 80.40%
	Comment Spray dried well
Product Characterisation	
	Nature of dry particle Good
	Oil encapsulation Good
	Oil release Good some coalescence
	Mean droplet size before spraying 4.0µm, peak at 8µm

- 34 -

EXAMPLE 14

5 The dispersion was prepared by stirring the
 biliquid foam and water into the aqueous polymers
 immediately before spray drying.

	Ingredients	Weight(g)	%
10	Preparation 10	155.56	15.55
	PVP k30 (40% by weight in demineralized water)	472.60	47.2
15	Water	319.44	31.9
	Maltodextrin (40% by weight in demineralized water)	52.5	5.25
	Total	1000.1	100

	Spray Drying conditions
20	Pilot Plant Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles
	35%
	Oil : polymer (dry basis)
	40:60
	Inlet / outlet temperature
	210°C/95°C
25	Yield
	74.71%
	Comment
	Spray dried well
	Product Characterisation
	Nature of dry particle
	Good
	Oil encapsulation
	Good
	Oil release
	Good little coalescence
30	Mean droplet size before spraying
	3.0µm, peak at 8µm

- 35 -

EXAMPLE 15

The dispersion was prepared by stirring the biliquid foam and water into the aqueous polymers immediately before spray drying.

5

	Ingredients	Weight (g)	%
	Preparation 10	175.00	17.5
	PVP k30 (40% by weight in demineralized water)	433.12	43.31
10	Water	343.75	38.38
	Maltodextrin (40% by weight in demineralized water)	48.12	4.81
15			

	Total	1000	100
--	-------	------	-----

	<u>Spray Drying conditions</u>	
	Pilot Plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
20	Total non volatiles	35%
	Oil : polymer (dry basis)	45:55
	Inlet / outlet temperature	210°C/95°C
	Yield	68.69%
	Comment	Spray dried well, good powder produced.
25	<u>Product Characterisation</u>	
	Nature of dry particle	Good
	Oil encapsulation	Appears good from appearance but probably encapsulation lower than expected.
	Oil release	Good some coalescence
30	Mean droplet size before spraying	4.0µm, peak at 8µm

- 36 -

EXAMPLE 16

5 The dispersion was prepared by stirring the
biliquid foam and water into the aqueous polymers
immediately before spray drying.

	Ingredients	Weight (g)	%
10	Preparation 10	136.11	13.61
	Gum acacia (40% by weight in demineralized water)	568.74	56.87
	Water	295.15	29.52
	Total	1000	100

15

Spray Drying conditions	
Pilot Plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
Total non volatiles	35%
Oil : polymer (dry basis)	35 :65
Inlet / outlet temperature	210°C/95°C
Yield	82.31%
Comment	Spray dried well
Product Characterisation	
Nature of dry particle	Good
Oil encapsulation	Good
Oil release	Good but moderate amount of coalescence
Mean droplet size before spraying	4.2µm, peak at 7.5µm

- 37 -

EXAMPLE 17

5 The dispersion was prepared by stirring the
biliquid foam and water into the aqueous polymers
immediately before spray drying.

	Ingredients	Weight(g)	%
10	Preparation 10	136.11	13.61
	Water	295.15	29.52
	Maltodextrin (40% by weight in demineralized water)	568.74	56.87
15	Total	1000	100

Spray Drying conditions	
Pilot Plant	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
20	Total non volatiles
	35%
	Oil : polymer (dry basis)
	35 : 65
	Inlet / outlet temperature
	210°C/96°C
	Yield
	69.25%
	Comment
	Spray dried well but lower yield than Example 16
Product Characterisation	
25	Nature of dry particle
	Moderate
	Oil encapsulation
	Some free oil visible
	Oil release
	Large amount of coalescence
	Mean droplet size before spraying
	7.4µm, peak at 9µm

- 38 -

Example 18

5 The dispersion was prepared by stirring the biliquid foam and water into the aqueous polymers immediately before spray drying. The dispersion was sheared for 2 minutes on a Silverson disperser before spraying to ensure good mixing.

	Ingredients	Weight (g)	%
10	Preparation 11	116.67	11.66
	Modified starch (40% by weight in demineralized water)	612.5	61.25
15	Water	270.38	27.09
	Total	1000	100

	Spray Drying conditions
20	Pilot Plant Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles 35%
	Oil : polymer (dry basis) 30 :70
	Inlet / outlet temperature 210°C/96°C
	Yield 98.70%
25	Comment Spray dried well
	Product Characterisation
	Nature of dry particle Good
	Oil encapsulation Good
	Oil release Good some coalescence
30	Mean droplet size before spraying 7.6µm, peak at 8µm

"Modified starch" is a chemically modified food starch with a dextrose equivalent value of 32-37%.

- 39 -

Example 19

The dispersion was prepared by stirring the biliquid foam and water into the aqueous polymers immediately before spray drying. The dispersion was sheared for 2 minutes on a Silverson disperser before spraying to ensure good mixing.

	Ingredients	Weight (g)	%
10	Preparation 12	116.67	11.66
	Modified starch (40% by weight in demineralized water)	612.5	61.25
15	Water	270.88	27.09
	Total	1000.5	100

Spray Drying conditions	
20	Pilot Plant
	Tests were carried out in a 1m diameter pilot spray drying tower with downward co current air flow. Atomisation was carried out with a two fluid nozzle.
	Total non volatiles
	35%
	Oil : polymer (dry basis)
	30 : 70
	Inlet / outlet temperature
	210°C/95°C
	Yield
	94.06%
25	Comment
	Spray dried well
	Product Characterisation
	Nature of dry particle
	Good
	Oil encapsulation
	Good
	Oil release
	Good, little coalescence
30	Mean droplet size before spraying
	9.26µm, peak at 9µm

- 40 -

"Modified starch" is a chemically modified food starch with a dextrose equivalent value of 32-37%.

Footnote to the Examples

	Trade Name	Supplier	INCI Name
5	Dow Corning 200 50cst	Dow Corning	Silicone
	Etocas 25	Croda Chemicals	PEG-25 Castor Oil
10	Gransil DMCM-5	Grant Chemicals	Cyclopentasiloxane (D5) (and) Polysilicone-11 (and) Dimethicone. (An Organopolysiloxane mixture)
	Gransil GCM-5	Grant Chemicals	Cyclopentasiloxane (D5) (and) Polysilicone-11 (An Organopolysiloxane mixture)
	Isopar K	Exxon Chemical Ltd	Isoparaffin
	Kathon ICG 11	Chesham Chemicals Limited	Mixture of: 5-chloro 2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one
	KMC	Rutgers Kureha Solvents GmbH	Diisopropylnaphthalene isomers (mixture)
15	Mowiol 4-88	Kuraray Specialties Europe	Polyvinyl alcohol, partly saponified
	Pergascript red I-6B	Ciba Specialties	Bisindolylphthalide compound
	Tween 20	Fisher Chemicals	Polysorbate 20

- 40A -

Throughout this specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or 5 step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

The reference in this specification to any prior publication (or information derived from it), or to any matter which is 10 known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates.

2003236910 08 Mar 2007

- 41 -

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A discrete powder which comprises particles in which a biliquid foam has been entrapped within a matrix of a 5 polymeric material.
2. A powder as claimed in claim 1 which is a spray dried powder, a freeze dried powder or a powder produced by fluidized bed granulation.
- 10 3. A powder as claimed in claim 1 or claim 2 which has a mean particle size in the range of from 5 to 150 μ m.
4. A powder as claimed in any one of the preceding claims 15 wherein the polymeric material encapsulating the biliquid foam is selected from carboxymethylcellulose, hydroxyethylcellulose, cetyl-hydroxycellulose, hydroxypropylcellulose, hydroxyl-propylmethylcellulose, hydroxyethylmethylcellulose methylcellulose, gelatine, gum 20 arabic, gum acacia, gellan gum, shellac, carragenan, natural starch, modified starch, xanthan gum, an alginate, a dextrin, polyvinyl alcohol, polyvinyl acetate, polyvinylpyrrolidone or a polyamide, or mixtures thereof.
- 25 5. A powder as claimed in any one of the preceding claims wherein the biliquid foam comprises a substantially water immiscible internal oil phase which comprises a cyclomethicone, dimethicone, phenyl trimethicone, dimethiconol, dimethicone copolyol, trimethylsiloxy silicate, 30 isopropyl isostearate, lanolate, myristate or palmitate, or octyl palmitate, avocado oil, coconut oil, soybean oil or sunflower oil, a caprylic/capric triglyceride, a lanolin

2003236910 08 Mar 2007

- 42 -

oil, orange oil, mineral oil or natural oil, or oleyl alcohol or mixtures thereof.

6. A powder as claimed in claim 5 which comprises from 5% to 50% by weight of an oil, based upon the weight of the powder.

7. A powder as claimed in claim 1 wherein the biliquid foam comprises a substantially water immiscible internal oil phase which contains or consists of one or more fragrances, flavours, deodorisers, perfumes, pharmaceuticals, sunscreens, dyes, pesticides, insect repellents and herbicides.

15 8. A powder as claimed in claim 7 wherein the substantially water immiscible internal oil phase contains or consists of pharmaceuticals.

9. A process for the preparation of a discrete powder 20 which comprises a biliquid foam entrapped within a matrix of a polymeric material, which process comprises the steps of:

25 i) preparing a biliquid foam,
ii) forming a dispersion of the biliquid foam in an aqueous solution, suspension or dispersion of a polymeric material, and
iii) subjecting the dispersion to drying under conditions such that a discrete powder is formed.

10. A process as claimed in claim 9 wherein the drying is 30 carried out by spray drying or freeze drying of the dispersion, or subjecting the dispersion to a fluidized bed granulation process.

2003236910 08 Mar 2007

- 43 -

11. A process as claimed in claim 9 or claim 10 wherein the biliquid foam prepared in step (i) has a mean droplet size in the range of from 1 to 45 micrometres.

5

12. A process as claimed in claim 9 wherein the biliquid foam has a droplet size of below 12 micrometres.

13. A process as claimed in any one of claims 9 to 11
10 wherein the polymeric material is selected from carboxymethylcellulose, hydroxyethylcellulose, cetylhydroxycellulose, hydroxypropylcellulose, hydroxypropylmethylcellulose, hydroxyethylmethyl-cellulose, methylcellulose, gelatine, gum arabic, gum acacia, gellan
15 gum, shellac, carragenan, natural starch, modified starch, xanthan gum, an alginate, a dextrin, polyvinyl alcohol, polyvinyl acetate, polyvinyl-pyrollidone or a polyamide, or mixtures thereof.

20 14. A process as claimed in any one of claims 9 to 13
wherein the biliquid foam comprises an essentially water immiscible internal oil phase which comprises a cyclomethicone, dimethicone, phenyl trimethicone, dimethiconol, dimethicone copolyol, trimethylsiloxy silicate, 25 isopropyl isostearate, lanolate, myristate or palmitate, octyl palmitate, avocado oil, coconut oil, soybean oil or sunflower oil, a caprylic/capric triglyceride, a lanolin oil, orange oil, mineral oil or natural oil, or oleyl alcohol, or mixtures thereof.

30

27 May 2009
2003236910

- 44 -

15. A process as claimed in any one of claims 9 to 13 wherein the continuous phase of the biliquid foam is an aqueous phase.
- 5 16. A process as claimed in claim 15 wherein the aqueous phase includes therein a C1-C4 alcohol or ethylene glycol.
- 10 17. A process as claimed in any one of claims 9 to 15 wherein the spray drying conditions comprise an inlet temperature in the range of from 170 to 210OC and an outlet temperature in the range of from 85 to 110OC.
- 15 18. A process as claimed in any one of claims 9 to 17 wherein the discrete powder has a mean particle size in the range of from 5 to 150 μ m.
19. A process as claimed in any one of claims 9 to 18 wherein the discrete powder is subjected to granulation or formed into tablets.
- 20 20. A fragrance composition or a deodorizing composition which comprises a powder as claimed in any one of claims 1 to 6 in which a fragrance or deodorizing material is entrapped within an encapsulating polymer that allows the release of the fragrance or deodorizing material over time, or by rupture of the encapsulating polymer on the application of pressure, or by dissolution of the encapsulating polymer on contact with a solvent therefor.
- 30 21. A powder according to claim 1 or a process according to claim 9 or a composition of claim 20, substantially as hereinbefore described with reference to the Examples.