



(51) International Patent Classification:

H04L 29/08 (2006.01) H04L 12/58 (2006.01)
G08G 5/00 (2006.01) H04L 29/06 (2006.01)

(21) International Application Number:

PCT/US2013/024157

(22) International Filing Date:

31 January 2013 (31.01.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/432,190 28 March 2012 (28.03.2012) US

(71) Applicant: THE BOEING COMPANY [US/US]; 100 North Riverside Plaza, Chicago, Illinois 60606-2016 (US).

(72) Inventors: MYERS, Robert James; 100 North Riverside Plaza, Chicago, Illinois 60606-2016 (US). ANSTEY, Timothy William; 100 North Riverside Plaza, Chicago, Illinois 60606-2016 (US). BATSAKES, Peter James; 100 North Riverside Plaza, Chicago, Illinois 60606-2016 (US).


(74) Agents: SATERMO, Eric K et al.; The Boeing Company, PO Box 2515, MC 110-SD54, Seal Beach, California 90740-1515 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: INFORMATION HANDLING FOR AIRCRAFT FLIGHT DECKS



(57) Abstract: A system and method for handling information for use on a flight deck network on an aircraft. Information is received from a number of information sources. The number of information sources is not part of the flight deck network. The flight deck network is a certified network. It is determined whether the information is approved to be used on the flight deck network. A manner in which the information is allowed to be used on the flight deck network is also determined. Responsive to a determination that the information is approved to be used on the flight deck network, the information is sent to the flight deck network during operation of the aircraft.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, —
ML, MR, NE, SN, TD, TG).

*before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

INFORMATION HANDLING FOR AIRCRAFT FLIGHT DECKS

BACKGROUND

The present disclosure relates generally to aircraft flight decks and to handling the information that is used on aircraft flight decks and displayed on aircraft flight deck display systems. More particularly, the present disclosure relates to handling non-essential information from sources outside of the aircraft flight deck network for use on the aircraft flight deck during operation of the aircraft and controlling the manner in which the non-essential information is displayed on the flight deck.

A flight deck is the area on an aircraft from which a pilot and other flight crew members control the aircraft. The flight deck is usually located near the front of an aircraft. The flight deck also may be referred to as the cockpit. In addition to a pilot, the flight crew on the flight deck during operation of the aircraft may include, for example, a copilot, a navigator, or other personnel or combinations of personnel.

The flight deck of an aircraft includes the instruments and controls that enable the flight crew to fly the aircraft. For example, the flight deck may include a number of displays. Various types of information may be displayed for use by the flight crew to operate the aircraft. For example, it is desirable that the information displayed on the aircraft flight deck includes information that may be required for use by the flight crew to operate the aircraft safely.

It is desirable that the information used by the flight crew on the aircraft flight deck is handled to ensure safe operation of the aircraft. For example, the information displayed on the aircraft flight deck may be controlled to ensure that the information displayed to the aircraft flight crew is both appropriate and accurate.

Control of the information used on the aircraft flight deck may be provided by separating the aircraft flight deck network from other data processing systems on the aircraft. This separation may be implemented by physical separation of the hardware used to implement the aircraft flight deck network from other data processing system hardware on the aircraft. For example, the aircraft flight deck network may be implemented as a local area network or other grouping of data processing resources that is physically separated from other data processing systems and networks on the aircraft. As another example, software may be used to separate the aircraft flight deck network from other aircraft network data processing systems.

The separation of the flight deck data processing network from the other aircraft network data processing systems allows the information used on the aircraft flight deck to be separated from the information used by other aircraft network data processing systems. For example, the information to be used on the aircraft flight deck
5 may be stored in a database that is only accessible by the aircraft flight deck network during operation of the aircraft. For example, such a database may be part of the flight deck local area network that includes the flight deck display system.

The information used on the aircraft flight deck network may be further controlled by subjecting the flight deck network to a certification process. For example,
10 information to be used on the aircraft flight deck network may be stored on a database that is accessible by the aircraft flight deck network. The flight deck network, including the database and flight deck display system, may be subject to the certification process. The certification process may be performed to verify that the information to be used
15 on the flight deck network satisfies a number of requirements related to the appropriateness and accuracy of the information. Typically, the certification process may be conducted and granted by a regulatory authority. In some cases the certification process may be conducted by another entity.

Changes to the flight deck network, including changes for using information from new information sources or in new formats, typically may require
20 recertification. Processes for certifying the components of the flight deck network may be time-consuming and costly. As a result, changes to the aircraft flight deck network may be delayed due to the time required for the certification process. In other cases, changes to the aircraft flight deck network may be delayed or not undertaken at all, in order to delay or avoid entirely the costs associated with the certification process.

25 Current methods for handling information used on aircraft flight decks that rely on certification processes and separating the flight deck network from other aircraft network data processing systems form a closed system. The inflexibility of such a system discourages system changes and, thus, may limit the information that is available to be used by the flight crew on the aircraft flight deck.

30 Accordingly, it would be beneficial to have a method and apparatus that takes into account one or more of the issues discussed above as well as possibly other issues.

SUMMARY

An illustrative embodiment of the present disclosure provides a method for handling information for use on a flight deck network on an aircraft. Information is received from a number of information sources. The number of information sources is not part of the flight deck network. The flight deck network is a certified network. It is determined whether the information is approved to be used on the flight deck network. A manner in which the information is allowed to be used on the flight deck network is also determined. Responsive to a determination that the information is approved to be used on the flight deck network, the information is sent to the flight deck network during operation of the aircraft.

Another illustrative embodiment of the present disclosure provides a method for handling information on a flight deck network on an aircraft. During operation of the aircraft, a request is sent from the flight deck network for information to be used on the flight deck network. The flight deck network is a certified network. In response to the request, the information to be used on the flight deck network is received from a source of information that is not part of the flight deck network. The information is used on the flight deck network during operation of the aircraft while other information that is part of the flight deck network is simultaneously used on the flight deck network.

Another illustrative embodiment of the present disclosure provides an apparatus comprising an information controller on an aircraft. An information receiver is configured to receive information from a number of information sources. The number of information sources is not part of a flight deck network on the aircraft. The flight deck network is a certified network. An approved information checker is configured to determine whether information received by the information receiver is approved to be used on the flight deck network. An allowed uses tagger is configured to associate data with the information received by the information receiver. The data indicates a manner in which the information is allowed to be used on the flight deck network. An information request handler is configured to receive a request from the flight deck network during operation of the aircraft to send information to the flight deck network, and, in response to receiving the request, to send information that is determined to be approved to be used on the flight deck network with the data to the flight deck network.

The features, functions, and benefits may be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives, and features thereof will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of a block diagram of a system for handling information for use on an aircraft flight deck in accordance with an illustrative embodiment;

Figure 2 is an illustration of a block diagram of an information controller in accordance with an illustrative embodiment;

Figure 3 is an illustration of an arrangement of displays on an aircraft flight deck showing allowed locations for displaying information in accordance with an illustrative embodiment;

Figure 4 is an illustration of an arrangement of displays on an aircraft flight deck showing allowed replications of displayed information in accordance with an illustrative embodiment;

Figure 5 is an illustration of information transfers for information to be used on an aircraft flight deck in accordance with an illustrative embodiment;

Figure 6 is an illustration of a flowchart of a process for handling information received by an information controller in accordance with an illustrative embodiment;

Figure 7 is an illustration of a flowchart of a process for responding to a request for information by an information controller in accordance with an illustrative embodiment;

Figure 8 is an illustration of a flowchart of a process for handling information by an information display system on an aircraft flight deck in accordance with an illustrative embodiment; and

Figure 9 is an illustration of a data processing system in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

5 The different illustrative embodiments recognize and take into account a number of different considerations. “A number”, as used herein with reference to items, means one or more items. For example, “a number of different considerations” means one or more different considerations.

10 The different illustrative embodiments recognize and take into account that current systems and methods for handling the information that is used on an aircraft flight deck includes separating the aircraft flight deck network from other aircraft network data processing systems. The separated aircraft flight deck network is subject to a certification process or requirement. This separation of a certified flight deck network from other aircraft network data processing systems allows only information that is
15 certified for use on the flight deck to be accessed by the aircraft flight deck network. Changes to the flight deck network may require recertification.

 The different illustrative embodiments recognize and take into account that there may be different levels of certification for aircraft systems and for the information that is used on aircraft. A higher level of certification may require a certification process
20 that is more time consuming and expensive than the certification process required for a lower level of certification. Components of a flight deck network, including information that is a part of the flight deck network, may require a higher level of certification than other systems and information that may be used on an aircraft. Therefore, changes to the flight deck network that require recertification may be more time consuming and
25 expensive than changes to other aircraft systems.

 Current systems and methods for handling the information on aircraft flight deck networks that rely on flight deck network separation and certification result in a closed system. Such a system may be inflexible and may limit the information that is available to be used by a flight crew on the aircraft flight deck network. Essential
30 information that is required for safe operation of the aircraft is made available for use by flight crews on the flight deck network. However, non-essential information from new information sources or new display formats may not be made available on the flight deck in a timely manner or at all.

The different illustrative embodiments recognize and take into account that certain information may be useful for operation of an aircraft, even if such information is not required for safe operation of the aircraft. However, certifying changes to the flight deck network for such non-essential information, as required by current systems and methods, may incur a higher level of engineering effort. In some cases, such information may be used on the flight deck on dedicated auxiliary systems that are separated from the flight deck network. The different illustrative embodiments recognize and take into account that it would be desirable to use such non-essential but useful information on the flight deck network itself.

The different illustrative embodiments recognize and take into account that information from various sources may be available on an aircraft or accessible by the aircraft during operation of the aircraft. Such information may include information that is non-essential for safe operation of the aircraft but which would be useful for operation of the aircraft if such information were available to the flight crew on the flight deck. For example, such information, if made available to the flight crew during operation of the aircraft, might be used by the flight crew to improve aircraft operating efficiency, to enhance the experience of aircraft passengers during a flight, or for some other useful purpose.

Potentially useful information may include operationally approved information or information that has been subjected to a lower level certification process than may be used to certify information that is allowed to be part of the aircraft flight deck network. In some cases, such potentially useful information may include new information products, information products from new information sources, or new information formats. New or changed information products, sources, or formats may become available so frequently that certification of the latest versions of potentially useful information for use as part of a certified flight deck network is not possible or practical. In other words, information that may be potentially useful if made available to a flight crew during an aircraft operation may be information that is not certified at the higher level required for information that is part of the flight deck network.

The different illustrative embodiments also recognize and take into account that it is desirable that any information used on an aircraft flight deck is handled so that the use of such information on the flight deck does not interfere with safe operation of the aircraft. In particular, the different illustrative embodiments recognize

and take into account that it is desirable that any useful but non-essential information on the flight deck network should not affect the use by the flight crew of essential information that is required for safe operation of the aircraft in any undesired manner.

Thus, one or more of the illustrative embodiments provides a system and method for handling information that is used by a flight crew on an aircraft flight deck. In accordance with an illustrative embodiment, information to be used on an aircraft flight deck is handled so that both essential information, that may be required for safe operation of the aircraft, and potentially useful but non-essential information may be used together by the flight crew during operation of the aircraft on a certified flight deck network. The useful but non-essential information to be used on the flight deck may be obtained from various information sources, including information sources on the aircraft or off the aircraft and information sources that may be accessible by the aircraft when in operation. Non-essential information may be handled such that useful information may be made available on the flight deck network along with essential information required for safe operation of the aircraft in a manner that does not affect safe operation of the aircraft in any undesired way.

In accordance with an illustrative embodiment, potentially useful but non-essential information is approved for use on the flight deck before the non-essential information is sent to the flight deck. The approval process may be a flexible process that is less time consuming and less costly than the process for certifying a change to the flight deck network if the information were to be certified as part of the flight deck network. Therefore, in accordance with an illustrative embodiment, information products, sources of information, and information formats that are approved may be changed more easily over the course of time after an aircraft enters into service. The manner in which such non-essential information is allowed to be used on the flight deck may be determined and controlled so that the use of non-essential information on the flight deck does not interfere with the use by the flight crew of essential information on the flight deck. Therefore, the flight crew is able to operate the aircraft safely and in an improved manner.

One or more of the illustrative embodiments provides an information controller for handling the information that is provided to a flight deck network. Potentially useful information from various sources on-board the aircraft, or that are

accessible by the aircraft when in operation, may be provided to the information controller.

The information controller may determine whether any such potentially useful information is approved for use by the flight crew on the flight deck network and may check the integrity of any such approved information. The information controller only passes information that is approved and that has passed an integrity check to the flight deck network. The information controller also may determine the manner in which such information is allowed to be used on the flight deck network. The information controller may tag the information that is provided to the flight deck with tags indicating how that information is allowed to be used on the flight deck . The flight deck network may then control the manner in which the information is used on the flight deck based on the allowed uses indicated by the tags.

Turning now to **Figure 1**, an illustration of a block diagram of a system for handling information for use on an aircraft flight deck is depicted in accordance with an illustrative embodiment. In this illustrative example, flight deck **100** may be a flight deck on aircraft **102**. Flight deck **100** also may be referred to as the cockpit of aircraft **102**. Flight deck **100** may include various controls which enable flight crew **104** to control the operation of aircraft **102**. For example, without limitation, flight deck **100** may include an area located near the front of aircraft **102**. In another example, without limitation, flight crew **104** may include a pilot, a copilot, a navigator, other personnel, or various combinations of personnel for controlling the operation of aircraft **102**.

Flight deck **100** may include displays **106**. Displays **106** may be a number of displays in this illustrative example. Displays **106** may include any number of devices or systems for displaying various types of information for use by flight crew **104**. In accordance with an illustrative embodiment, the information that is displayed to flight crew **104** on displays **106** may include both information that is required for safe operation of aircraft **102** by flight crew **104** and other information. The information displayed to flight crew **104** is controlled so that the display of such information may enhance the operation of aircraft **102** without affecting the safe operation of aircraft **102** in any undesired manner.

The location of flight deck **100** on aircraft **102**, the composition of flight crew **104**, the number and types of devices and systems used to implement displays **106**, and the types of information displayed to flight crew **104** may depend on various

factors including, for example, without limitation, the type of aircraft **102**, the operations to be performed by aircraft **102**, specific flight or mission requirements, or other factors or various combinations of factors. Aircraft **102** may be any type of aircraft. For example, without limitation, aircraft **102** may include a fixed wing, rotary wing, or lighter than air aircraft. Aircraft **102** may be configured for carrying passengers, cargo, both passengers and cargo, or may be used for performing any other operation or mission. Aircraft **102** may be operated by an airline, a military unit, or any other private or governmental entity.

Aircraft **102** is an example of vehicle **108** in which illustrative embodiments may be implemented. Information handling, in accordance with an illustrative embodiment, may be implemented in types of vehicles other than aircraft **102**. For example, without limitation, vehicle **108** may be any vehicle that is configured for travelling through the air, in space, on land, on the surface of water, underwater, or in any other operating environment or combination of environments.

Vehicle **108** is an example of platform **110** in which illustrative embodiments may be implemented. Information handling, in accordance with an illustrative embodiment, may be implemented in types of platforms other than vehicle **108**. For example, platform **110** may include any fixed or movable structure that may be controlled by an operator using information that is displayed to the operator on one or more display devices.

In cases where illustrative embodiments are implemented on vehicles or platforms other than aircraft **102**, displays **106** may be provided in one or more areas or locations on vehicle **108** or platform **110** where functions corresponding to the functions performed on flight deck **100** for aircraft **102** are performed for vehicle **108** or platform **110**. For example, without limitation, displays **106** may be provided in a control room or one or more other locations or combinations of locations on vehicle **108** or platform **110** from which a human operator may control operation of vehicle **108** or platform **110** using the information displayed. In other words, illustrative embodiments may be used for handling information that is used in an area of vehicle **108** or platform **110** to perform operations similar to those performed on flight deck **100**, even though such an area may not be referred to as a flight deck or a cockpit.

Continuing with the example of aircraft **102**, displays **106** may be provided as part of information display system **112** on flight deck **100**. Information display system

112 also may include crew interfaces **114**. Crew interfaces **114** are configured to receive input for information display system **112** from flight crew **104**. For example, without limitation, crew interfaces **114** may be configured to receive input from flight crew **104** for selecting or changing the information displayed, for selecting or changing the manner in which information is displayed, or for otherwise controlling the operation of information display system **112** in any other manner.

Crew interfaces **114** may be implemented using a number of devices or systems that are separate from displays **106**, that are included as part of displays **106**, or both. For example, without limitation, one or more of displays **106** may be implemented as touch screen display devices. In this example, the touch screen display devices operate as both displays **106** for displaying information to flight crew **104** and crew interfaces **114** for receiving instructions for controlling the operation of information display system **112** from flight crew **104**.

The functions performed by information display system **112** may be implemented in hardware or software operating in combination with hardware. For example, without limitation, a number of functions performed by information display system **112** may be implemented in software running on one or more data processing systems.

Information display system **112**, along with other data processing systems or other systems or devices, may be part of flight deck network **116**. Flight deck network **116** may be implemented in any appropriate manner to provide for the communication of information between the various parts of flight deck network **116**. For example, without limitation, flight deck network **116** may be implemented as a local area network or another type of network using any appropriate network configuration. Flight deck network **116** is associated with flight deck **100**. In accordance with an illustrative embodiment, the parts of flight deck network **116** may include data processing systems, other systems and devices, and software and other information used for implementing information display system **112** and other functions to be performed on flight deck **100**.

All of the parts of flight deck network **116** may be physically located on or adjacent to flight deck **100** on aircraft **102**. Alternatively, some of the parts of flight deck network **116** may be remotely located from flight deck **100**. In any case, the various parts of flight deck network **116** may be connected to flight deck network **116** via appropriate wired, optical, wireless, or other connections or combinations of

connections. The various parts of flight deck network **116** and the various connections between those parts may be secured using known techniques to prevent unauthorized physical or other access to flight deck network **116**. For purposes of the present application, including in the claims, flight deck network **116**, including displays **106** on flight deck **100**, may be referred to as being “on” flight deck **100**, “for” flight deck **100**, or other similar terms even though some parts of flight deck network **116** may be located remotely from flight deck **100**.

Flight deck network **116** is an example of higher level certified network **117**. Higher level certified network **117** is a network wherein all of the parts of the network, including hardware, software, and information to be displayed on higher level certified network **117**, is required to pass a relatively high level certification process. In accordance with an illustrative embodiment, as will be described in more detail below, systems that are certified at a lower level of certification may connect to flight deck network **116**, and non-essential information may be displayed on flight deck network **116** at certain times and under certain controlled conditions. In the present application, including in the claims, such non-essential systems and information are not considered to be parts of flight deck network **116** or of higher level certified network **117**.

Information display system **112** is configured to display essential information **118**. Essential information **118** may include information that is required by flight crew **104** to operate aircraft **102** safely. Essential information **118** may be higher level certified information **120**. Higher level certified information **120** is any information that has passed an appropriate relatively high level certification process. In some cases, higher level certified information **120** may include information other than essential information **118**. In other words, information that is not necessarily required for operation of aircraft **102** by flight crew **104** may be passed through a relatively high level certification process to become part of higher level certified information **120**.

In the present application, including in the claims, essential information **118** is considered to be a part of flight deck network **116** and, thus, a part of higher level certified network **117**. Essential information **118** may include any information that is certified to be part of flight deck network **116**. Essential information **118** may be displayed to flight crew **104** by information display system **112**.

For example, without limitation, essential information **118** may be stored in a database that is part of flight deck network **116**. Information display system **112** may

access essential information **118** from such a database for displaying such information on flight deck network **116**.

Appropriate procedures may be specified and followed for establishing and making any changes to higher level certified network **117** including loading essential information **118** onto flight deck network **116**. The process for certifying higher level certified network **117** including essential information **118**, the process for establishing and changing higher level certified network **117**, including the process for loading essential information **118** onto flight deck network **116**, and the security provided for the various parts of flight deck network **116** in combination provide appropriate controls for higher level certified network **117** and for essential information **118** that is displayed to flight crew **104**. Such controls may ensure that essential information **118** that is required by flight crew **104** for safe operation of aircraft **102** is accurately displayed to flight crew **104** in a manner so that aircraft **102** is operated safely.

Aircraft **102** may include aircraft network data processing system **122**. Aircraft network data processing system **122** may include a number of data processing systems and other devices for performing various functions on aircraft **102**. Aircraft network data processing system **122** is separate from flight deck network **116**. Information is not allowed to pass freely between flight deck network **116** and aircraft network data processing system **122**. However, in accordance with an illustrative embodiment, information may be passed between flight deck network **116** and aircraft network data processing system **122** in a controlled manner.

In accordance with an illustrative embodiment, the flow of information between aircraft network data processing system **122** and flight deck network **116** may be controlled by information controller **124**. In accordance with an illustrative embodiment, information controller **124** provides a single control point for the flow of information between aircraft network data processing system **122** and flight deck network **116** when aircraft **102** is in operation. Information controller **124** is configured to implement information handling functions **126**. Information handling functions **126** control the flow of information between aircraft network data processing system **122** and flight deck network **116** in accordance with information handling rules **128**. In accordance with an illustrative embodiment, information handling rules **128** may be defined in order to ensure that any information that is passed to flight deck network **116**

from aircraft network data processing system **122** during aircraft operation may be used in a manner that does not affect the safe operation of aircraft **102** in any undesired manner. As will be discussed in more detail below, information handling rules **128** may define information from aircraft network data processing system **122** that is approved for use on flight deck **100** as well as rules defining the manner in which such information is allowed to be used on flight deck network **116**.

Information controller **124** may be configured to allow various types of non-essential information **130** to be provided to flight deck network **116** for use in a controlled manner. Non-essential information **130** may be any information that has not gone through a certification process to be approved to be a part of higher level certified network **117**. Non-essential information **130** may include information that has gone through a process to determine that the information is approved for operational use on flight deck **100**. For example, without limitation, non-essential information **130** may include lower level certified information **131** or operationally approved information **132**. Non-essential information **130** may include any information that has gone through an approval process that is less time consuming, less expensive, or both less time consuming and less expensive than the certification process for essential information **118**.

Non-essential information **130** may include useful information **134**. Useful information **134** may include any information that may be useful to flight crew **104** for operating aircraft **102**, but is not required for safe operation of aircraft **102**. For example, without limitation, useful information **134** may include information that may improve the efficiency with which flight crew **104** operates aircraft **102**, information that may improve the experience of passengers on aircraft **102** during a flight, or any other useful information, potentially useful information, or combinations of such information.

In some cases, useful information **134** may include information that is certified to be part of flight deck network **116**. For example, useful information **134** may include information that has passed through a process for certifying the information for flight deck network **116** but that has not been loaded onto or otherwise made a part of flight deck network **116**. In this case, such useful information **134** may be provided to flight deck network **116** via information controller **124** in the manner described herein.

Non-essential information **130** may include information that is provided to or obtained by information controller **124** before or during aircraft operation. For

example, non-essential information **130** may include information that is provided to information controller **124** or that may be obtained by information controller **124** while aircraft **102** is in flight, before takeoff, or during any other state of operation of aircraft **102**.

5 In the present application, including in the claims, “operation” of aircraft **102** refers generally to any state of operation of aircraft **102** in which flight crew **104** or similar operational personnel control operation of aircraft **102**. Operation of aircraft **102** may be distinguished from other states of aircraft **102** when aircraft **102** is not in operation. For example, without limitation, aircraft **102** is not in operation when aircraft
10 **102** is under construction or undergoing maintenance. Procedures may generally specify that parts of higher level certified network **117** on aircraft **102** may not be changed during operation of aircraft **102** as defined herein. For example, essential information **118** generally may not be loaded onto flight deck network **116** or otherwise made a part of flight deck network **116** during operation of aircraft **102** as defined
15 herein.

Non-essential information **130** may be provided to or obtained by information controller **124** from on-board information sources **136**, off-board information sources **138**, or both. On-board information sources **136** may include any source for non-essential information **130** that is located onboard aircraft **102**. For example, without
20 limitation, on-board information sources **136** may include computers or other data processing devices that are located onboard aircraft **102** during operation of aircraft **102**. Such computers or other data processing devices may be part of aircraft network data processing system **122** or separate from, but in communication with, aircraft network data processing system **122**. Computers or other data processing devices
25 located in the passenger cabin or cockpit of aircraft **102** are examples, without limitation, of on-board information sources **136**. Off-board information sources **138** may include any sources for non-essential information **130** that are not located on aircraft **102** but that may be in communication with aircraft network data processing system **122** during operation of aircraft **102**.

30 Non-essential information **130** may be transferred from on-board information sources **136**, off-board information sources **138**, or both, to information controller **124** via information transfer systems **140**. Similarly, information controller **124** may request non-essential information **130** from on-board information sources **136**, off-

board information sources **138**, or both, via information transfer systems **140**. Information transfer systems **140** may include hardware or software running on hardware that is configured to provide for information transfer and other communications between on-board information sources **136**, off-board information sources **138**, and information controller **124**.

Specific implementations of information transfer systems **140** for any specific application may depend upon the specific implementations of on-board information sources **136** and off-board information sources **138** for that application, the types of information provided by such information sources, protocols that may be required for transferring information from such information sources, or other factors or combinations of factors that may be relevant for any particular application.

For example, without limitation, information transfer systems **140** may include appropriate hardware, or hardware and software, for wired transfer **142** or for wireless transfer **144** of non-essential information **130** to information controller **124**. For example, wired transfer **142** may include the transfer of non-essential information **130** via electrical or optical conductors or other similar conduction media or combinations of media. Wireless transfer **144** may be provided via appropriate transmission frequencies and using appropriate wireless information transfer protocols.

As another example, information transfer systems **140** may include hardware, or hardware and software, configured to provide hardware transfer **146** of non-essential information **130** to information controller **124**. Hardware transfer **146** may include connecting a hardware device or other tangible computer readable media containing non-essential information **130** to aircraft network data processing system **122** and transferring non-essential information **130** from the hardware device or other media to information controller **124**. For example, without limitation, hardware transfer **146** may include physically connecting a portable hardware memory device or other portable computer readable media to aircraft network data processing system **122**.

As another example, information transfer systems **140** may include hardware, or hardware and software, configured for manual entry **148** of non-essential information **130** to information controller **124**. For example, without limitation, manual entry **148** may include manual entry of non-essential information **130** using a keyboard, keypad, touch screen, or other such device or combinations of devices for manually entering information into a data processing system.

In accordance with an illustrative embodiment, non-essential information **130** from on-board information sources **136**, off-board information sources **138**, or both, may be provided to information controller **124** automatically on a periodic or irregular basis, or both. Alternatively or additionally, non-essential information **130** may be retrieved by information controller **124** from on-board information sources **136**, off-board information sources **138**, or both, on a periodic or irregular basis, or both.

Non-essential information **130** that may be used on flight deck **100** may be obtained by information controller **124** before a request for such information is received by information controller **124** from flight deck network **116**. In this case, information controller **124** may process such information as it is received using information handling functions **126** and information handling rules **128**.

Non-essential information **130** processed in this manner may then be stored by information controller **124** on aircraft network data processing system **122**. For example, information controller **124** may store such processed information in one or more databases implemented in one or more storage devices provided as part of aircraft network data processing system **122** or accessible by aircraft network data processing system **122**. Storing non-essential information **130** that is processed by information controller **124** in this manner allows information controller **124** to respond more rapidly when a request for such information is received from flight deck **100**.

In accordance with an illustrative embodiment, non-essential information **130** may be provided to flight deck network **116** in response to a request for such information from flight deck network **116**. Preferably, non-essential information **130** is not pushed or otherwise transferred to higher level certified network **117** unless a request for such information is received from higher level certified network **117**. For example, without limitation, flight crew **104** may employ crew interfaces **114** to initiate a request for non-essential information **130** that is not part of higher level certified network **117**. The request may be sent from information display system **112** to information controller **124**. Information controller **124** may respond to such a request by providing non-essential information **130** that has already been processed and stored by information controller **124** to flight deck network **116** if non-essential information **130** that is requested has already been processed and stored and is available on aircraft network data processing system **122**.

Alternatively, information controller **124** may respond to a request for non-essential information **130** from flight deck network **116** by attempting to locate and retrieve non-essential information **130** that has been requested from on-board information sources **136**, off-board information sources **138**, or both. In this case, if the requested information is obtained by information controller **124**, information controller **124** processes the information using information handling functions **126** and information handling rules **128** before providing non-essential information **130** that has been requested to flight deck network **116**.

In any case, non-essential information **130** that is provided by information controller **124** to flight deck network **116** in response to a request may be displayed to flight crew **104** by information display system **112**. Thus, in accordance with an illustrative embodiment, essential information **118** and non-essential information **130** may be displayed together on higher level certified network **117** during operation of aircraft **102**.

As will be discussed in more detail below, information display system **112** may be configured to control the display of non-essential information **130** in an allowed manner. The manner in which non-essential information **130** may be used on flight deck network **116** may be defined by information handling rules **128** as applied to non-essential information **130** by information handling functions **126** before non-essential information **130** is provided to flight deck network **116**.

Turning now to **Figure 2**, an illustration of a block diagram of an information controller is depicted in accordance with an illustrative embodiment. In this example, information controller **200** is an example of one implementation of information controller **124** in **Figure 1**.

Information controller **200** may obtain information from information sources **202**. Information sources **202** include sources of information that are not part of flight deck network **219** of an aircraft. Information sources **202** may include sources of information that are not certified for being part of flight deck network **219**. However, information that may be obtained from information sources **202** may include information that may be useful for operating an aircraft if such information is available for use on flight deck network **219**. Information sources **202** may include, for example, without limitation, on-board information sources **136** and off-board information sources **138** in **Figure 1**.

Information controller **200** includes information receiver **204**. Information receiver **204** is configured to receive information from information sources **202**. Information received by information receiver **204** is processed by information controller **200** using information handling functions **206** and information handling rules **208**. In accordance with an illustrative embodiment, information handling functions **206** are implemented by approved information checker **210**, information integrity checker **212**, and allowed uses tagger **214**. Information handling rules **208** may include approved information list **216** and allowed uses rules **218**.

Approved information checker **210** determines whether information obtained by information controller **200** from information sources **202** is a type of information that is allowed to be sent to and displayed on flight deck network **219**. Approved information may be defined by approved information list **216**. Thus, approved information checker **210** may determine whether information received by information controller **200** is approved information using approved information list **216**. Approved information list **216** may be stored in whole or in part in a database or other data structure that is part of information controller **200**. Alternatively, approved information list **216** may be stored in any other form or location where approved information list **216** may be accessed by approved information checker **210**.

Approved information list **216** may identify a number of criteria for determining whether information received by information controller **200** is allowed to be sent to and displayed on flight deck network **219**. For example, without limitation, such criteria may identify approved types of information, approved sources of information, approved information formats, approved standards classifications, or other criteria or combinations of criteria for identifying approved information. The process for identifying approved information may be less time consuming and expensive than the process for certifying information to be part of flight deck network **219**. Information that is approved by approved information checker **210** may include lower level certified information and operationally approved information.

Information that is identified as approved information by approved information checker **210** may then be processed by information integrity checker **212**. Information integrity checker **212** is configured to determine whether or not any information received from information sources **202** may be corrupted. Even approved types of information from approved sources may become corrupted before such

information is received by information controller **200**. For example, without limitation, such information may become corrupted during transmission from information sources **202** to information controller **200**. It may not be safe to send such corrupted information to flight deck network **219**.

5 Information integrity checker **212** may employ a number of processes for determining whether or not information from information sources **202** may be corrupted. For example, without limitation, information integrity checker **212** may perform digital signature check **220**. Digital signature check **220** may include checking a digital signature provided with the information to verify that that information is from a known
10 source. As another example, information integrity checker **212** may perform virus scan **222** to verify that the information is clean of any undesired computer viruses or other undesired computer executable code.

Information that is identified as approved information by approved information checker **210** and passed by information integrity checker **212** may be
15 processed by allowed uses tagger **214**. Allowed uses tagger **214** identifies how approved information is allowed to be used on flight deck network **219**. Stated in another way, allowed uses tagger **214** may identify limitations on the manner in which approved information may be used on flight deck network **219**. The manner in which approved information is allowed to be used on flight deck network **219** may be defined
20 by allowed uses rules **218**. Thus, allowed uses tagger **214** may use allowed uses rules **218** to identify the manner in which approved information is allowed to be used on flight deck network **219**. Allowed uses rules **218** may be stored in whole or in part in a database or other data structure that is part of information controller **200**. Alternatively, allowed uses rules **218** may be stored in any other form or location where allowed uses
25 rules **218** may be accessed by allowed uses tagger **214**.

Allowed uses rules **218** may be established to define the manner in which approved information is allowed to be used on flight deck network **219** based on a number of factors. For example, without limitation, such factors may include the desired degree of interaction with the information by the flight crew, desired ease of viewing the
30 information by the flight crew, flight crew resource management, or other factors or combinations of factors. Another factor may include displaying non-essential information on flight deck network **219** in a manner that does not interfere with the displaying of information that is required for safe operation of the aircraft and does not

distract the flight crew from using such required information. In accordance with an illustrative embodiment, different allowed uses rules **218** may be provided for different types of approved information. Different allowed uses rules **218** for different types of information may be established based on different factors of interest or concern.

5 Allowed uses tagger **214** may associate tag **224** with information processed by allowed uses tagger **214**. Tag **224** may be data in any form that is attached to or otherwise associated with information to indicate allowed uses **226** for the information. Allowed uses **226** for information are identified by allowed uses tagger **214** using allowed uses rules **218**.

10 Allowed uses **226** define the manner in which information is allowed to be used on flight deck network **219**. For example, without limitation, allowed uses **226** may include allowed display locations **228**, allowed display replications **230**, allowed operating conditions **234**, allowed information integration **236**, or other definitions or combinations of a number of definitions of the manner in which information is allowed to
15 be used on flight deck network **219**.

 Allowed display locations **228** may identify locations on the flight deck at which the information is allowed to be displayed. For example, without limitation, allowed display locations **228** may identify display devices on the flight deck on which the information is allowed to be displayed, portions of individual display devices on
20 which the information is allowed to be displayed, the size of an area on a display device that may be used for displaying the information, or any other indication or combination of indications for identifying locations on the flight deck at which the information is allowed to be displayed. Allowed display replications **230** may indicate a number of locations on the flight deck at which information may be displayed simultaneously.

25 Allowed operating conditions **234** may indicate operating conditions of an aircraft during which the information is allowed to be displayed on the flight deck or is not allowed to be displayed on the flight deck. For example, without limitation, allowed operating conditions **234** may indicate that the information is allowed to be displayed on the flight deck only at certain times during operation of the aircraft, such as during
30 certain phases of flight, or under other defined operating conditions or combinations of conditions.

 Allowed information integration **236** identifies the degree to which the information provided by information controller **200** to flight deck network **219** may be

integrated with essential information on flight deck network **219**. For example, without limitation, allowed information integration **236** at the level of stand-alone display **238** indicates that the information provided by information controller **200** may be displayed on the flight deck as separate video or other displays that are not integrated in any way with the display of essential information that is part of flight deck network **219**. Allowed information integration **236** at the level of graphical integration **240** indicates that the display of information from information controller **200** may be overlaid, under-laid, or otherwise combined at the graphical level with the display of essential information that is part of flight deck network **219**. Allowed information integration **236** at the level of data integration **242** indicates that the information provided by information controller **200** may be combined with essential information that is part of flight deck network **219** before using the combined information on flight deck network **219**. In this case, the information provided by information controller **200** may be used to modify the essential information, or vice versa, before the information is used on flight deck network **219**. For example, without limitation, using the combined information on flight deck network **219** may include generating a display from the combined information.

Information controller **200** also may include information request handler **244**. Information request handler **244** may be configured to receive a request for information from flight deck network **219**. Information request handler **244** may be configured to determine whether the requested information is available to or otherwise may be obtained by information controller **200**. Information request handler **244** may be configured to provide requested information from information controller **200** to flight deck network **219** in response to a request. For example, requested information that is approved by approved information checker **210** and that passes the checks performed by information integrity checker **212** may be provided along with an associated tag **224** to flight deck network **219** by information request handler **244**.

Information request handler **244** also may be configured to send a request denial message to flight deck network **219** if a received request for information cannot be satisfied by information controller **200**. For example, without limitation, a received request for information may not be satisfied by information controller **200** if the requested information is not available to or cannot be obtained by information controller **200**, if the requested information is not approved by approved information checker **210**, if the requested information does not pass a check performed by information integrity

checker **212**, or for some other reason or combination of reasons. The request denial message may or may not indicate why the request for information is denied by information controller **200**.

Information sent to flight deck network **219** by information request handler **244** may be used on flight deck network **219** in the manner in which the information is allowed to be used as indicated by the associated tag **224**. For example, the information may be displayed on the flight deck along with the display of essential information that is part of flight deck network **219**.

The illustrations of **Figure 1** and **Figure 2** are not meant to imply physical or architectural limitations to the manner in which different illustrative embodiments may be implemented. Other components in addition to, in place of, or both in addition to and in place of the ones illustrated may be used. Some components may be unnecessary in some illustrative embodiments. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined or divided into different blocks when implemented in different illustrative embodiments.

For example, in accordance with an illustrative embodiment, information controller **124** may be used to control both the flow of information from aircraft network data processing system **122** to flight deck network **116** and the flow of information from flight deck network **116** to aircraft network data processing system **122**. Functions and criteria similar to or different from those described above may be employed by information controller **124** to control the flow of information from flight deck network **116** to aircraft network data processing system **122**.

A number of the functions of information controller **124** or information controller **200**, as described above, may be performed in whole or in part by a data processing system that is part of aircraft network data processing system **122**, that is not part of flight deck network **116**, or by a data processing system that is part of flight deck network **116**. For example, without limitation, a number of the functions of approved information checker **210** may be performed on flight deck network **116**. For example, it may be determined by an appropriate function on flight deck network **116** that certain information requested by flight crew **104** via crew interfaces **114** is not approved information. In this case, the request for such information may not be sent from flight deck network **116** to information controller **124** that is not part of flight deck network **116**.

The handling of information in accordance with an illustrative embodiment may include the presentation of information on flight deck network **116** in audible form. In this case, the information may be presented on speakers that are part of flight deck network **116**.

5 Turning now to **Figure 3**, an illustration of an arrangement of displays on an aircraft flight deck showing allowed locations for displaying information is depicted in accordance with an illustrative embodiment. In this example, displays **300**, **302**, **304**, **306**, **308**, **310**, and **312** are examples of displays **106** in **Figure 1**. Circles **314** and **316** indicate example positions of flight crew members with respect to displays **300**, **302**,
10 **304**, **306**, **308**, **310**, and **312**.

In this example, hash marks in display **300** and display **302** indicate that particular information is allowed to be displayed anywhere in display **300** or in the left half of display **302**. These allowed locations for displaying the information may be indicated by a tag or other data that is attached to or otherwise associated with the
15 information.

Turning now to **Figure 4**, an illustration of an arrangement of displays on an aircraft flight deck showing allowed replications of displayed information is depicted in accordance with an illustrative embodiment. In this example, displays **400**, **402**, **404**, **406**, **408**, **410**, and **412** are examples of displays **106** in **Figure 1**.

20 In this example, cross symbols **414** and **416** indicate that one type of information may be displayed in up to two replications on displays **400** and **410**. Diamond symbols **418** and **420** indicate that another type of information may be allowed to be displayed in up to two replications on displays **402** and **408**. Triangle symbol **422** indicates a third type of information that may be allowed to be displayed in only one
25 replication on display **404**. Pentagon symbols **424** and **426** indicate that a fourth type of information may be allowed to be displayed in up to two replications on displays **408** and **410**. These allowed replications for the display of various types of information may be indicated by a tag or other data that is attached to or otherwise associated with the information.

30 Turning now to **Figure 5**, an illustration of information transfers for information to be used on an aircraft flight deck is depicted in accordance with an illustrative embodiment. In this example, an example of the flow of information between information sources **500**, information controller **502**, and flight deck network **504** is

depicted. In this example, information sources **500** is an example of information sources **202** in **Figure 2**, information controller **502** is an example of information controller **200** in **Figure 2**, and flight deck network **504** is an example of flight deck network **219** in **Figure 2**.

5 Non-essential information **506**, **507**, and **514** may be transferred from information sources **500** to information controller **502** at various times. Information request **508** may be received by information controller **502** from flight deck network **504**. In response to receiving information request **508**, information controller **502** may send request denial message **510** to flight deck network **504** if the requested information
10 cannot be provided by information controller **502**. Request denial message **510** may or may not indicate why the request for information is being denied.

If the requested information can be provided, information controller **502** may send tagged information **512** to flight deck network **504** in response to information request **508**. Tagged information **512** may include non-essential information **506** that is
15 received by information controller **502** before information request **508** or non-essential information **507** that is received by information controller **502** after information request **508**. For example, tagged information **512** may include non-essential information **507** that is obtained by information controller **502** from information sources **500** in response to information request **508**. Thus, non-essential information **506**, **507**, and **514** may be
20 provided from information sources **500** to information controller **502** independently of the receipt of information request **508** by information controller **502** from flight deck network **504**. In any case, tagged information **512** may be tagged by information controller **502** with data indicating the manner in which the information may be used on flight deck network **504**.

25 Essential information **516** includes information that is certified to be part of flight deck network **504**. Essential information **516** may be provided from information sources **500** to flight deck network **504** without passing through information controller **502**. For example, essential information **516** may be loaded on flight deck network **504** using appropriate procedures for making changes to flight deck network **504**. Tagged
30 information **512** and essential information **516** may be used together on flight deck network **504**.

Turning now to **Figure 6**, an illustration of a flowchart of a process for handling information received by an information controller is depicted in accordance

with an illustrative embodiment. The process illustrated may be implemented, for example, in information controller **124** in **Figure 1** or information controller **200** in **Figure 2**.

The process begins by receiving information from a variety of information sources (operation **602**). The variety of information sources includes information sources that are not part of a higher level certified network. The process determines whether the received information is approved information (operation **604**). Approved information includes information that is approved to be displayed on the higher level certified network. If it is determined that the received information is approved information, the process then checks the integrity of the information (operation **606**). Operation **606** may include, for example, without limitation, checking a digital signature associated with the information, scanning the information for viruses, or performing other integrity checks or combinations of integrity checks. It then may be determined whether the integrity check is passed (operation **608**). If the integrity check is passed, allowed uses may be associated with the information (operation **610**). For example, operation **610** may include attaching or otherwise associating tags to the information that include data for indicating the manner in which the information is allowed to be used on the higher level certified network. After operation **610** the process may be repeated starting at operation **602** with the receiving of further information from the information sources.

If it is determined at operation **604** that the information is not approved, or if it is determined at operation **608** that the information integrity check is not passed, the received information is rejected (operation **612**). If the information is rejected, the information may not be sent to the higher level certified network. After operation **612**, the process may be repeated starting at operation **602** with the receiving of further information from the information sources. The process illustrated in **Figure 6** may be performed each time information is received by an information controller.

Turning now to **Figure 7**, an illustration of a flowchart of a process for responding to a request for information by an information controller is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 7** may be performed by information controller **124** in **Figure 1** or information controller **200** in **Figure 2**.

The process begins by receiving an information request from a higher level certified network (operation **702**). For example, the higher level certified network may be a flight deck network on an aircraft. The information controller may then determine whether the information request can be satisfied (operation **704**). If the information request can be satisfied, the requested information with allowed uses may be sent to the higher level certified network (operation **706**), with the process terminating thereafter. The allowed uses may include data associated with the information sent to the higher level certified network that indicates the manner in which the information may be used on the higher level certified network.

If it is determined that the information request cannot be satisfied, a request denial message may be sent back to the higher level certified network (operation **708**), with the process terminating thereafter. The request denial message may or may not indicate why the request for information is denied.

Turning now to **Figure 8**, an illustration of a flowchart of a process for handling information by an information display system on an aircraft flight deck is depicted in accordance with an illustrative embodiment. In this example, the process illustrated in **Figure 8** may be performed by information display system **112** in **Figure 1**.

The process begins by an information display system receiving flight crew input requesting the display of certain information on the flight deck (operation **802**). It may be determined whether the information requested is essential information that is part of the flight deck network (operation **804**). If it is determined that the requested information is essential information that is part of the flight deck network, the requested information may be displayed on the flight deck (operation **806**), with the process terminating thereafter.

If it is determined that the requested information is not essential information that is part of the flight deck network, it may be determined whether the information request can be satisfied (operation **808**). If it is determined that the information request cannot be satisfied, a request denial indication may be displayed to the flight crew (operation **810**), with the process terminating thereafter. For example, it may be determined that the information request cannot be satisfied if the information requested is not information that is approved to be displayed on the flight deck network.

If it is determined that the information request can be satisfied, the information request may be sent to an information controller (operation **812**). It may

then be determined whether the information request is denied by the information controller (operation **814**). If the information request is denied, a request denial indication may be displayed to the flight crew on the flight deck (operation **816**), with the process terminating thereafter.

5 If it is determined that the information request is not denied, the requested information may be received from the information controller (operation **818**). The information received from the information controller may then be displayed on the flight deck in a manner as indicated by allowed uses for the information (operation **820**), with the process terminating thereafter. The allowed uses for the information may be
10 indicated by data that is attached to or otherwise associated with the information from the information controller.

Turning now to **Figure 9**, an illustration of a data processing system is depicted in accordance with an illustrative embodiment. In this example, data processing system **900** is an example of one implementation of a data processing
15 system for implementing information display system **112** or information controller **124** in **Figure 1**.

In this illustrative example, data processing system **900** includes communications fabric **902**. Communications fabric **902** provides communications between processor unit **904**, memory **906**, persistent storage **908**, communications unit
20 **910**, input/output (I/O) unit **912**, and display **914**. Memory **906**, persistent storage **908**, communications unit **910**, input/output (I/O) unit **912**, and display **914** are examples of resources accessible by processor unit **904** via communications fabric **902**.

Processor unit **904** serves to run instructions for software that may be loaded into memory **906**. Processor unit **904** may be a number of processors, a multi-
25 processor core, or some other type of processor, depending on the particular implementation. Further, processor unit **904** may be implemented using a number of heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **904** may be a symmetric multi-processor system containing multiple processors of the same type.

30 Memory **906** and persistent storage **908** are examples of storage devices **916**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and other suitable information either on a temporary basis or a permanent basis. Storage

devices **916** also may be referred to as computer readable storage devices in these examples. Memory **906**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **908** may take various forms, depending on the particular implementation.

5 For example, persistent storage **908** may contain one or more components or devices. For example, persistent storage **908** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **908** also may be removable. For example, a removable hard drive may be used for persistent storage
10 **908**.

Communications unit **910**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **910** is a network interface card. Communications unit **910** may provide communications through the use of either or both physical and wireless
15 communications links.

Input/output unit **912** allows for input and output of data with other devices that may be connected to data processing system **900**. For example, input/output unit **912** may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device. Further, input/output unit **912** may send output to a printer.
20 Display **914** provides a mechanism to display information to a user.

Instructions for the operating system, applications, and/or programs may be located in storage devices **916**, which are in communication with processor unit **904** through communications fabric **902**. In these illustrative examples, the instructions are in a functional form on persistent storage **908**. These instructions may be loaded into
25 memory **906** for execution by processor unit **904**. The processes of the different embodiments may be performed by processor unit **904** using computer-implemented instructions, which may be located in a memory, such as memory **906**.

These instructions are referred to as program instructions, program code, computer usable program code, or computer readable program code that may be read
30 and executed by a processor in processor unit **904**. The program code in the different embodiments may be embodied on different physical or computer readable storage media, such as memory **906** or persistent storage **908**.

Program code **918** is located in a functional form on computer readable media **920** that is selectively removable and may be loaded onto or transferred to data processing system **900** for execution by processor unit **904**. Program code **918** and computer readable media **920** form computer program product **922** in these examples.

5 In one example, computer readable media **920** may be computer readable storage media **924** or computer readable signal media **926**.

Computer readable storage media **924** may include, for example, an optical or magnetic disk that is inserted or placed into a drive or other device that is part of persistent storage **908** for transfer onto a storage device, such as a hard drive, that is part of persistent storage **908**. Computer readable storage media **924** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory, that is connected to data processing system **900**. In some instances, computer readable storage media **924** may not be removable from data processing system **900**.

10 In these examples, computer readable storage media **924** is a physical or tangible storage device used to store program code **918** rather than a medium that propagates or transmits program code **918**. Computer readable storage media **924** is also referred to as a computer readable tangible storage device or a computer readable physical storage device. In other words, computer readable storage media **924** is a media that can be touched by a person.

20 Alternatively, program code **918** may be transferred to data processing system **900** using computer readable signal media **926**. Computer readable signal media **926** may be, for example, a propagated data signal containing program code **918**. For example, computer readable signal media **926** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link. In other words, the communications link and/or the connection may be physical or wireless in the illustrative examples.

25 In some illustrative embodiments, program code **918** may be downloaded over a network to persistent storage **908** from another device or data processing system through computer readable signal media **926** for use within data processing system **900**. For instance, program code stored in a computer readable storage medium in a server data processing system may be downloaded over a network from the server to

data processing system **900**. The data processing system providing program code **918** may be a server computer, a client computer, or some other device capable of storing and transmitting program code **918**.

The different components illustrated for data processing system **900** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to and/or in place of those illustrated for data processing system **900**. Other components shown in **Figure 9** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code. As one example, data processing system **900** may include organic components integrated with inorganic components and/or may be comprised entirely of organic components excluding a human being. For example, a storage device may be comprised of an organic semiconductor.

In another illustrative example, processor unit **904** may take the form of a hardware unit that has circuits that are manufactured or configured for a particular use. This type of hardware may perform operations without needing program code to be loaded into a memory from a storage device to be configured to perform the operations.

For example, when processor unit **904** takes the form of a hardware unit, processor unit **904** may be a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device is configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. With this type of implementation, program code **918** may be omitted, because the processes for the different embodiments are implemented in a hardware unit.

In still another illustrative example, processor unit **904** may be implemented using a combination of processors found in computers and hardware units. Processor unit **904** may have a number of hardware units and a number of processors that are configured to run program code **918**. With this depicted example,

some of the processes may be implemented in the number of hardware units, while other processes may be implemented in the number of processors.

In another example, a bus system may be used to implement communications fabric **902** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system.

Additionally, communications unit **910** may include a number of devices that transmit data, receive data, or both transmit and receive data. Communications unit **910** may be, for example, a modem or a network adapter, two network adapters, or some combination thereof. Further, a memory may be, for example, memory **906**, or a cache, such as found in an interface and memory controller hub that may be present in communications fabric **902**.

The flowcharts and block diagrams described herein illustrate the architecture, functionality, and operation of possible implementations of systems, methods, and computer program products according to various illustrative embodiments. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function or functions. It should also be noted that, in some alternative implementations, the functions noted in a block may occur out of the order noted in the figures. For example, the functions of two blocks shown in succession may be executed substantially concurrently, or the functions of the blocks may sometimes be executed in the reverse order, depending upon the functionality involved.

The description of the different illustrative embodiments has been presented for purposes of illustration and description and is not intended to be exhaustive or to limit the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different benefits as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various

embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

5

1. A method for presenting information on a flight deck network (116) on an aircraft (102) comprising:

10

receiving the information from a number of information sources (202), wherein the number of information sources (202) is not a part of the flight deck network (116), wherein the flight deck network (116) is a certified network (117);

determining whether the information is approved to be presented on the flight deck network (116);

determining a manner in which the information is allowed to be presented on the flight deck network (116); and

15

responsive to a determination that the information is approved to be presented on the flight deck network (116), sending the information to the flight deck network (116) during operation of the aircraft (102) to be presented on the flight deck network (116) during the operation of the aircraft (102) in the manner in which the information is allowed to be presented on the flight deck network (116).

20

2. The method of claim 1, wherein the number of information sources (202) includes information sources selected from information sources on the aircraft (102) and information sources not on the aircraft (102).

25

3. The method of claim 1, wherein the information includes information selected from information that is not certified to be part of the flight deck network (116) and information that is useful for the operation of the aircraft (102) when presented on the flight deck network (116) but is not required to be presented on the flight deck network (116) for safe operation of the aircraft (102).

30

4. The method of claim 1, wherein determining whether the information is approved to be presented on the flight deck network (116) comprises determining whether the information matches criteria provided in an approved information list (216), wherein the

criteria are selected from a group of criteria consisting of approved types of information, approved sources of information, approved information formats, and approved standards classifications.

5 5. The method of claim 1, wherein the manner in which the information is allowed to be presented on the flight deck network (116) comprises at least one of locations on a number of displays (106) that are the part of the flight deck network (116) at which the information is allowed to be presented, a number of replications of the information that is allowed to be presented simultaneously on the number of displays (106), a condition
10 of operation of the aircraft (102) during which the information is allowed to be presented on the flight deck network (116), and allowed integration of the information with certified information (120) that is a part of the flight deck network (116).

6. The method of claim 1, wherein the manner in which the information is allowed to be presented on the flight deck network (116) is selected from stand-alone presentation
15 (238) of the information separate from a presentation of certified information (120) that is a part of the flight deck network (116), graphical integration (240) of the presentation of the information with the presentation of the certified information (120) that is a part of the flight deck network (116), and data integration (242) of the information with the
20 certified information (120) that is a part of the flight deck network (116) before generating a presentation of the information.

7. The method of claim 1 further comprising:
during the operation of the aircraft (102), receiving a request for the information
25 from the flight deck network (116) and sending the information to the flight deck network (116) in response to receiving the request.

8. The method of claim 7, wherein receiving the information from the number of information sources (202) comprises
30 receiving the information from the number of information sources (202) before receiving the request for the information from the flight deck network (116).

9. The method of claim 7, wherein receiving the information from the number of information sources (202) comprises obtaining the information from the number of information sources (202) in response to receiving the request for the information from the flight deck network (116).

5

10. The method of claim 1, wherein sending the information to the flight deck network (116) comprises sending the information to the flight deck network (116) to be presented on the flight deck network (116) during the operation of the aircraft (102) simultaneously with presenting other information that is a part of the flight deck network (116) on the flight deck network (116) on a number of displays (106) that are a part of the flight deck network (116).

10

11. The method of claim 10, wherein the other information that is a part of the flight deck network (116) comprises information selected from information certified to be a part of the flight deck network (116) and information that is required to be presented on the flight deck network (116) for safe operation of the aircraft (102).

15

12. A method for presenting information on a flight deck network (116) on an aircraft (102) comprising:

during operation of the aircraft (102), sending a request from the flight deck network (116) for the information to be presented on the flight deck network (116), wherein the flight deck network (116) is a certified network (117);

20

in response to the request, receiving the information to be presented on the flight deck network (116) from a source of information that is not a part of the flight deck network (116); and

presenting the information on the flight deck network (116) during the operation of the aircraft (102) while simultaneously presenting other information that is a part of the flight deck network (116) on the flight deck network (116) on a number of displays (106) that are a part of the flight deck network (116).

25

13. The method of claim 12, wherein presenting the information on the flight deck network (116) comprises presenting the information on the flight deck network (116) in a manner in which the information is allowed to be presented on the flight deck network (116).

30

14. The method of claim 13, wherein the manner in which the information is allowed to be presented on the flight deck comprises at least one of locations on the number of displays (106) at which the information is allowed to be presented, a number of
5 replications of the information that is allowed to be presented simultaneously on the number of displays (106), a condition of operation of the aircraft (102) during which the information is allowed to be presented on the flight deck network (116), and allowed integration of the information with certified information (120) that is part of the flight deck network (116).

10 15. The method of claim 13, wherein the manner in which the information is allowed to be presented on the flight deck network (116) is selected from stand-alone presentation (238) of the information separate from a presentation of certified information (120) that is a part of the flight deck network (116), graphical integration
15 (240) of a presentation of the information with the presentation of the certified information (120) that is a part of the flight deck network (116), and data integration (242) of the information with the certified information (120) that is a part of the flight deck network (116) before generating the presentation of the information.

20 16. The method of claim 12, wherein:

the information includes information selected from information that is not certified to be a part of the flight deck network (116) and information that is useful for the operation of the aircraft (102) when presented on the flight deck network (116) but is not required to be presented on the flight deck network (116) for safe operation of the
25 aircraft (102); and

the other information that is a part of the flight deck network (116) comprises information selected from information certified to be a part of the flight deck network (116) and information that is required to be presented on the flight deck network (116) for the safe operation of the aircraft (102).

30 17. An apparatus comprising an information controller (124) on an aircraft (102) comprising:

an information receiver (204) configured to receive information from a number of information sources (202), wherein the number of information sources (202) is not a part of a flight deck network (116) on the aircraft (102), wherein the flight deck network (116) is a certified network (117);

5 an approved information checker (210) configured to determine whether information received by the information receiver (204) is approved to be presented on the flight deck network (116);

a presentation allowances tagger (214) configured to associate data with the information received by the information receiver (204), wherein the data indicates a
10 manner in which the information is allowed to be presented on the flight deck network (116); and

an information request handler (244) configured to receive a request from the flight deck network (116) during operation of the aircraft (102) to send the information to the flight deck network (116), and, in response to receiving the request, to send the
15 information that is determined to be approved to be presented on the flight deck network (116) with the data to the flight deck network (116) to be presented on the flight deck network (116) in the manner in which the information is allowed to be presented on the flight deck network (116) as indicated by the data.

20 18. The apparatus of claim 17, wherein the data indicates at least one of locations on a number of displays (106) that are a part of the flight deck network (116) at which the information is allowed to be presented, a number of replications of the information that is allowed to be presented simultaneously on the number of displays (106), a condition of operation of the aircraft (102) during which the information is allowed to be presented
25 on the flight deck network (116), and allowed integration of the information with certified information (120) that is a part of the flight deck network (116).

19. The apparatus of claim 17, wherein the data indicates at least one of the information is allowed to be presented on the flight deck network (116) as a stand-alone
30 presentation (238) of the information separate from a presentation of certified information (120) that is a part of the flight deck network (116), a graphical presentation of the information is allowed to be graphically integrated with the graphical presentation of certified information (120) that is a part of the flight deck network (116), or the

information is allowed to be integrated with certified information (120) that is a part of the flight deck network (116) before generating the presentation of the information.

20. The apparatus of claim 17, wherein the information request handler (244) is
5 configured to send the information that is determined to be approved to be presented on the flight deck network (116) to the flight deck network (116) during the operation of the aircraft (102) to be presented on the flight deck network (116) during the operation of the aircraft (102) while other information that is a part of the flight deck network (116) is presented on a number of displays (106) that are a part of the flight deck network (116).

10

FIG. 1

1/7







FIG. 2


200





3/7



4/7





6/7





FIG. 8

7/7

FIG. 9



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2013/024157

A. CLASSIFICATION OF SUBJECT MATTER

INV. H04L29/08 G08G5/00 H04L12/58 H04L29/06
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

H04L G08G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, COMPENDEX, INSPEC, PAJ, IBM-TDB, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2008/086554 A1 (ROYALTY CHARLES D [US]) 10 April 2008 (2008-04-10) abstract paragraph [0003] - paragraph [0005] paragraph [0018] - paragraph [0023] paragraph [0030] - paragraph [0032] figures 1-3 -----	1-20
X	US 2006/227012 A1 (HE GANG [US]) 12 October 2006 (2006-10-12) abstract paragraph [0021] - paragraph [0023] figure 4 ----- -/-	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 July 2013

Date of mailing of the international search report

19/07/2013

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Horn, Marc-Philipp

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2013/024157

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,P	EP 2 434 727 A1 (HONEYWELL INT INC [US]) 28 March 2012 (2012-03-28) abstract paragraph [0015] - paragraph [0022] paragraph [0028] - paragraph [0041] figures 1-3 -----	1-20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2013/024157

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2008086554	A1	10-04-2008	AU 2007307266 A1 17-04-2008
		CA 2659120 A1 17-04-2008	
		CN 101523854 A 02-09-2009	
		EP 2074788 A1 01-07-2009	
		US 2008086554 A1 10-04-2008	
		WO 2008045154 A1 17-04-2008	

US 2006227012	A1	12-10-2006	EP 1869408 A1 26-12-2007
			US 2006227012 A1 12-10-2006
			WO 2006113105 A1 26-10-2006

EP 2434727	A1	28-03-2012	EP 2434727 A1 28-03-2012
			US 2012075124 A1 29-03-2012
