

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/008762 A1

(51) International Patent Classification⁷: **H04N 7/12**, 11/02

(21) International Application Number:

PCT/US2003/021735

(22) International Filing Date: 14 July 2003 (14.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/395,843 15 July 2002 (15.07.2002) US
60/395,874 15 July 2002 (15.07.2002) US
10/410,481 9 April 2003 (09.04.2003) US

(71) Applicant (for all designated States except US): **THOMSON LICENSING S.A.** [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne (FR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BOYCE, Jill, MacDonald** [US/US]; 3 Brandywine Court, Manalapan, NJ 07726 (US).

(74) Agents: **TRIPOLI, Joseph, S. et al.**; c/o Thomson Licensing Inc., Two Independence Way, Suite #200, Princeton, NJ 08540 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: ADAPTIVE WEIGHTING OF REFERENCE PICTURES IN VIDEO DECODING



(57) Abstract: A video decoder (300), encoder (500), and corresponding methods for processing video signal data for an image block and a particular reference picture index to predict the image block are disclosed that utilize adaptive weighting of reference pictures to enhance video compression, where a decoder (300) includes a reference picture weighting factor unit (380) for determining a weighting factor corresponding to the particular reference picture index; an encoder (500) includes a reference picture weighting factor assignor (572) for assigning a weighting factor corresponding to the particular reference picture index; and a method for decoding includes receiving a reference picture index with the data that corresponds to the image block, determining a weighting factor for each received reference picture index, retrieving a reference picture for each index, motion compensating the retrieved reference picture, and multiplying the motion compensated reference picture by the corresponding weighting factor to form a weighted motion compensated reference picture.

WO 2004/008762 A1



- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

ADAPTIVE WEIGHTING OF REFERENCE PICTURES IN VIDEO DECODING

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application Serial

5 No. 60/395,843 (Atty. Docket No. PU020340), entitled "Adaptive Weighting Of
Reference Pictures In Video CODEC" and filed July 15, 2002, which is incorporated
by reference herein in its entirety. In addition, this application claims the benefit of
U.S. Provisional Patent Application Serial No. 60/395,874 (Atty. Docket No.
PU020339), entitled "Motion Estimation With Weighting Prediction" also filed July 15,
10 2002, which is incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

The present invention is directed towards video decoders, and in particular,
towards utilization of adaptive weighting of reference pictures in video decoders.

15

BACKGROUND OF THE INVENTION

Video data is generally processed and transferred in the form of bit streams.
Typical video compression coders and decoders ("CODECs") gain much of their
compression efficiency by forming a reference picture prediction of a picture to be
20 encoded, and encoding the difference between the current picture and the prediction.
The more closely that the prediction is correlated with the current picture, the fewer
bits that are needed to compress that picture, thereby increasing the efficiency of the
process. Thus, it is desirable for the best possible reference picture prediction to be
formed.

25 In many video compression standards, including Moving Picture Experts
Group ("MPEG")-1, MPEG-2 and MPEG-4, a motion compensated version of a
previous reference picture is used as a prediction for the current picture, and only the
difference between the current picture and the prediction is coded. When a single
picture prediction ("P" picture) is used, the reference picture is not scaled when the
30 motion compensated prediction is formed. When bi-directional picture predictions
("B" pictures) are used, intermediate predictions are formed from two different
pictures, and then the two intermediate predictions are averaged together, using
equal weighting factors of (1/2, 1/2) for each, to form a single averaged prediction. In

these MPEG standards, the two reference pictures are always one each from the forward direction and the backward direction for B pictures.

SUMMARY OF THE INVENTION

5 These and other drawbacks and disadvantages of the prior art are addressed by a system and method for adaptive weighting of reference pictures in video decoders.

10 A video decoder and corresponding methods for processing video signal data for an image block and a particular reference picture index to predict the image block are disclosed that utilize adaptive weighting of reference pictures to enhance video compression. A decoder includes a reference picture weighting factor unit for determining a weighting factor corresponding to the particular reference picture index.

15 A corresponding method for decoding video includes receiving a reference picture index with the data that corresponds to the image block, determining a weighting factor for each received reference picture index, retrieving a reference picture for each index, motion compensating the retrieved reference picture, and multiplying the motion compensated reference picture by the corresponding weighting factor to form a weighted motion compensated reference picture.

20 These and other aspects, features and advantages of the present invention will become apparent from the following description of exemplary embodiments, which is to be read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

25 Adaptive weighting of reference pictures in video coders and decoders in accordance with the principles of the present invention are shown in the following exemplary figures, in which:

Figure 1 shows a block diagram for a standard video decoder;

Figure 2 shows a block diagram for a video decoder with adaptive bi-prediction;

30 Figure 3 shows a block diagram for a video decoder with reference picture weighting in accordance with the principles of the present invention;

Figure 4 shows a block diagram for a standard video encoder;

Figure 5 shows a block diagram for a video encoder with reference picture weighting in accordance with the principles of the present invention;

Figure 6 shows a flowchart for a decoding process in accordance with the principles of the present invention; and

5 Figure 7 shows a flowchart for an encoding process in accordance with the principles of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention presents an apparatus and method for motion vector estimation and adaptive reference picture weighting factor assignment. In some video sequences, in particular those with fading, the current picture or image block to be coded is more strongly correlated to a reference picture scaled by a weighting factor than to the reference picture itself. Video CODECs without weighting factors applied to reference pictures encode fading sequences very inefficiently. When 10 weighting factors are used in encoding, a video encoder needs to determine both weighting factors and motion vectors, but the best choice for each of these depends on the other, with motion estimation typically being the most computationally 15 intensive part of a digital video compression encoder.

In the proposed Joint Video Team (“JVT”) video compression standard, each P 20 picture can use multiple reference pictures to form a picture’s prediction, but each individual motion block or 8x8 region of a macroblock uses only a single reference picture for prediction. In addition to coding and transmitting the motion vectors, a reference picture index is transmitted for each motion block or 8x8 region, indicating which reference picture is used. A limited set of possible reference pictures is stored 25 at both the encoder and decoder, and the number of allowable reference pictures is transmitted.

In the JVT standard, for bi-predictive pictures (also called “B” pictures), two predictors are formed for each motion block or 8x8 region, each of which can be from a separate reference picture, and the two predictors are averaged together to form a 30 single averaged predictor. For bi-predictively coded motion blocks, the reference pictures can both be from the forward direction, both be from the backward direction, or one each from the forward and backward directions. Two lists are maintained of the available reference pictures that may be used for prediction. The two reference

pictures are referred to as the list 0 and list 1 predictors. An index for each reference picture is coded and transmitted, `ref_idx_I0` and `ref_idx_I1`, for the list 0 and list 1 reference pictures, respectively. Joint Video Team (“JVT”) bi-predictive or “B” pictures allows adaptive weighting between the two predictions, i.e.,

5
$$\text{Pred} = [(P0)(\text{Pred0})] + [(P1)(\text{Pred1})] + D,$$

where $P0$ and $P1$ are weighting factors, Pred0 and Pred1 are the reference picture predictions for list 0 and list 1 respectively, and D is an offset.

Two methods have been proposed for indication of weighting factors. In the first, the weighting factors are determined by the directions that are used for the 10 reference pictures. In this method, if the `ref_idx_I0` index is less than or equal to `ref_idx_I1`, weighting factors of $(\frac{1}{2}, \frac{1}{2})$ are used, otherwise $(2, -1)$ factors are used.

15 In the second method offered, any number of weighting factors is transmitted for each slice. Then a weighting factor index is transmitted for each motion block or 8x8 region of a macroblock that uses bi-directional prediction. The decoder uses the received weighting factor index to choose the appropriate weighting factor, from the transmitted set, to use when decoding the motion block or 8x8 region. For example, if three weighting factors were sent at the slice layer, they would correspond to weight factor indices 0, 1 and 2, respectively.

The following description merely illustrates the principles of the invention. It 20 will thus be appreciated that those skilled in the art will be able to devise various arrangements that, although not explicitly described or shown herein, embody the principles of the invention and are included within its spirit and scope. Furthermore, all examples and conditional language recited herein are principally intended expressly to be only for pedagogical purposes to aid the reader in understanding the 25 principles of the invention and the concepts contributed by the inventor to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects, and embodiments of the invention, as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof.

30 Additionally, it is intended that such equivalents include both currently known equivalents as well as equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure.

Thus, for example, it will be appreciated by those skilled in the art that the block diagrams herein represent conceptual views of illustrative circuitry embodying the principles of the invention. Similarly, it will be appreciated that any flow charts, flow diagrams, state transition diagrams, pseudocode, and the like represent various processes which may be substantially represented in computer readable media and so executed by a computer or processor, whether or not such computer or processor is explicitly shown.

The functions of the various elements shown in the figures may be provided through the use of dedicated hardware as well as hardware capable of executing software in association with appropriate software. When provided by a processor, the functions may be provided by a single dedicated processor, by a single shared processor, or by a plurality of individual processors, some of which may be shared. Moreover, explicit use of the term "processor" or "controller" should not be construed to refer exclusively to hardware capable of executing software, and may implicitly include, without limitation, digital signal processor ("DSP") hardware, read-only memory ("ROM") for storing software, random access memory ("RAM"), and non-volatile storage. Other hardware, conventional and/or custom, may also be included. Similarly, any switches shown in the figures are conceptual only. Their function may be carried out through the operation of program logic, through dedicated logic, through the interaction of program control and dedicated logic, or even manually, the particular technique being selectable by the implementer as more specifically understood from the context.

In the claims hereof any element expressed as a means for performing a specified function is intended to encompass any way of performing that function including, for example, a) a combination of circuit elements that performs that function or b) software in any form, including, therefore, firmware, microcode or the like, combined with appropriate circuitry for executing that software to perform the function. The invention as defined by such claims resides in the fact that the functionalities provided by the various recited means are combined and brought together in the manner which the claims call for. Applicant thus regards any means that can provide those functionalities as equivalent to those shown herein.

As shown in Figure 1, a standard video decoder is indicated generally by the reference numeral 100. The video decoder 100 includes a variable length decoder

(“VLD”) 110 connected in signal communication with an inverse quantizer 120. The inverse quantizer 120 is connected in signal communication with an inverse transformer 130. The inverse transformer 130 is connected in signal communication with a first input terminal of an adder or summing junction 140, where the output of 5 the summing junction 140 provides the output of the video decoder 100. The output of the summing junction 140 is connected in signal communication with a reference picture store 150. The reference picture store 150 is connected in signal communication with a motion compensator 160, which is connected in signal communication with a second input terminal of the summing junction 140.

10 Turning to Figure 2, a video decoder with adaptive bi-prediction is indicated generally by the reference numeral 200. The video decoder 200 includes a VLD 210 connected in signal communication with an inverse quantizer 220. The inverse quantizer 220 is connected in signal communication with an inverse transformer 230. The inverse transformer 230 is connected in signal communication with a first input 15 terminal of a summing junction 240, where the output of the summing junction 240 provides the output of the video decoder 200. The output of the summing junction 240 is connected in signal communication with a reference picture store 250. The reference picture store 250 is connected in signal communication with a motion compensator 260, which is connected in signal communication with a first input of a 20 multiplier 270.

25 The VLD 210 is further connected in signal communication with a reference picture weighting factor lookup 280 for providing an adaptive bi-prediction (“ABP”) coefficient index to the lookup 280. A first output of the lookup 280 is for providing a weighting factor, and is connected in signal communication to a second input of the multiplier 270. The output of the multiplier 270 is connected in signal communication to a first input of a summing junction 290. A second output of the lookup 280 is for providing an offset, and is connected in signal communication to a second input of the summing junction 290. The output of the summing junction 290 is connected in signal communication with a second input terminal of the summing junction 240.

30 Turning now to Figure 3, a video decoder with reference picture weighting is indicated generally by the reference numeral 300. The video decoder 300 includes a VLD 310 connected in signal communication with an inverse quantizer 320. The inverse quantizer 320 is connected in signal communication with an inverse

transformer 330. The inverse transformer 330 is connected in signal communication with a first input terminal of a summing junction 340, where the output of the summing junction 340 provides the output of the video decoder 300. The output of the summing junction 340 is connected in signal communication with a reference picture store 350. The reference picture store 350 is connected in signal communication with a motion compensator 360, which is connected in signal communication with a first input of a multiplier 370.

The VLD 310 is further connected in signal communication with a reference picture weighting factor lookup 380 for providing a reference picture index to the lookup 380. A first output of the lookup 380 is for providing a weighting factor, and is connected in signal communication to a second input of the multiplier 370. The output of the multiplier 370 is connected in signal communication to a first input of a summing junction 390. A second output of the lookup 380 is for providing an offset, and is connected in signal communication to a second input of the summing junction 390. The output of the summing junction 390 is connected in signal communication with a second input terminal of the summing junction 340.

As shown in Figure 4, a standard video encoder is indicated generally by the reference numeral 400. An input to the encoder 400 is connected in signal communication with a non-inverting input of a summing junction 410. The output of the summing junction 410 is connected in signal communication with a block transformer 420. The transformer 420 is connected in signal communication with a quantizer 430. The output of the quantizer 430 is connected in signal communication with a variable length coder (“VLC”) 440, where the output of the VLC 440 is an externally available output of the encoder 400.

The output of the quantizer 430 is further connected in signal communication with an inverse quantizer 450. The inverse quantizer 450 is connected in signal communication with an inverse block transformer 460, which, in turn, is connected in signal communication with a reference picture store 470. A first output of the reference picture store 470 is connected in signal communication with a first input of a motion estimator 480. The input to the encoder 400 is further connected in signal communication with a second input of the motion estimator 480. The output of the motion estimator 480 is connected in signal communication with a first input of a motion compensator 490. A second output of the reference picture store 470 is

connected in signal communication with a second input of the motion compensator 490. The output of the motion compensator 490 is connected in signal communication with an inverting input of the summing junction 410.

Turning to Figure 5, a video encoder with reference picture weighting is

5 indicated generally by the reference numeral 500. An input to the encoder 500 is connected in signal communication with a non-inverting input of a summing junction 510. The output of the summing junction 510 is connected in signal communication with a block transformer 520. The transformer 520 is connected in signal communication with a quantizer 530. The output of the quantizer 530 is connected in 10 signal communication with a VLC 540, where the output of the VLC 440 is an externally available output of the encoder 500.

The output of the quantizer 530 is further connected in signal communication with an inverse quantizer 550. The inverse quantizer 550 is connected in signal communication with an inverse block transformer 560, which, in turn, is connected in 15 signal communication with a reference picture store 570. A first output of the

reference picture store 570 is connected in signal communication with a first input of a reference picture weighting factor assignor 572. The input to the encoder 500 is further connected in signal communication with a second input of the reference picture weighting factor assignor 572. The output of the reference picture weighting 20 factor assignor 572, which is indicative of a weighting factor, is connected in signal communication with a first input of a motion estimator 580. A second output of the reference picture store 570 is connected in signal communication with a second input of the motion estimator 580.

The input to the encoder 500 is further connected in signal communication with 25 a third input of the motion estimator 580. The output of the motion estimator 580,

which is indicative of motion vectors, is connected in signal communication with a first input of a motion compensator 590. A third output of the reference picture store 570 is connected in signal communication with a second input of the motion compensator 590.

The output of the motion compensator 590, which is indicative of a motion 30 compensated reference picture, is connected in signal communication with a first

input of a multiplier 592. The output of the reference picture weighting factor assignor 572, which is indicative of a weighting factor, is connected in signal communication with a second input of the multiplier 592. The output of the multiplier 592 is

connected in signal communication with an inverting input of the summing junction 510.

Turning now to Figure 6, an exemplary process for decoding video signal data for an image block is indicated generally by the reference numeral 600. The process 5 includes a start block 610 that passes control to an input block 612. The input block 612 receives the image block compressed data, and passes control to an input block 614. The input block 614 receives at least one reference picture index with the data for the image block, each reference picture index corresponding to a particular reference picture. The input block 614 passes control to a function block 616, which 10 determines a weighting factor corresponding to each of the received reference picture indices, and passes control to an optional function block 617. The optional function block 617 determines an offset corresponding to each of the received reference picture indices, and passes control to a function block 618. The function block 618 retrieves a reference picture corresponding to each of the received reference picture 15 indices, and passes control to a function block 620. The function block 620, in turn, motion compensates the retrieved reference picture, and passes control to a function block 622. The function block 622 multiplies the motion compensated reference picture by the corresponding weighting factor, and passes control to an optional function block 623. The optional function block 623 adds the motion compensated 20 reference picture to the corresponding offset, and passes control to a function block 624. The function block 624, in turn, forms a weighted motion compensated reference picture, and passes control to an end block 626.

Turning now to Figure 7, an exemplary process for encoding video signal data for an image block is indicated generally by the reference numeral 700. The process 25 includes a start block 710 that passes control to an input block 712. The input block 712 receives substantially uncompressed image block data, and passes control to a function block 714. The function block 714 assigns a weighting factor for the image block corresponding to a particular reference picture having a corresponding index. The function block 714 passes control to an optional function block 715. The optional 30 function block 715 assigns an offset for the image block corresponding to a particular reference picture having a corresponding index. The optional function block 715 passes control to a function block 716, which computes motion vectors corresponding to the difference between the image block and the particular reference picture, and

passes control to a function block 718. The function block 718 motion compensates the particular reference picture in correspondence with the motion vectors, and passes control to a function block 720. The function block 720, in turn, multiplies the motion compensated reference picture by the assigned weighting factor to form a 5 weighted motion compensated reference picture, and passes control to an optional function block 721. The optional function block 721, in turn, adds the motion compensated reference picture to the assigned offset to form a weighted motion compensated reference picture, and passes control to a function block 722. The function block 722 subtracts the weighted motion compensated reference picture 10 from the substantially uncompressed image block, and passes control to a function block 724. The function block 724, in turn, encodes a signal with the difference between the substantially uncompressed image block and the weighted motion compensated reference picture along with the corresponding index of the particular reference picture, and passes control to an end block 726.

15 In the present exemplary embodiment, for each coded picture or slice, a weighting factor is associated with each allowable reference picture that blocks of the current picture can be encoded with respect to. When each individual block in the current picture is encoded or decoded, the weighting factor(s) and offset(s) that correspond to its reference picture indices are applied to the reference prediction to 20 form a weight predictor. All blocks in the slice that are coded with respect to the same reference picture apply the same weighting factor to the reference picture prediction.

25 Whether or not to use adaptive weighting when coding a picture can be indicated in the picture parameter set or sequence parameter set, or in the slice or picture header. For each slice or picture that uses adaptive weighting, a weighting factor may be transmitted for each of the allowable reference pictures that may be used for encoding this slice or picture. The number of allowable reference pictures is transmitted in the slice header. For example, if three reference pictures can be used to encode the current slice, up to three weighting factors are transmitted, and they 30 are associated with the reference picture with the same index.

If no weighting factors are transmitted, default weights are used. In one embodiment of the current invention, default weights of (½, ½) are used when no

weighting factors are transmitted. The weighting factors may be transmitted using either fixed or variable length codes.

Unlike typical systems, each weighting factor that is transmitted with each slice, block or picture corresponds to a particular reference picture index. Previously, 5 any set of weighting factors transmitted with each slice or picture were not associated with any particular reference pictures. Instead, an adaptive bi-prediction weighting index was transmitted for each motion block or 8x8 region to select which of the weighting factors from the transmitted set was to be applied for that particular motion block or 8x8 region.

10 In the present embodiment, the weighting factor index for each motion block or 8x8 region is not explicitly transmitted. Instead, the weighting factor that is associated with the transmitted reference picture index is used. This dramatically reduces the amount of overhead in the transmitted bitstream to allow adaptive weighting of reference pictures.

15 This system and technique may be applied to either Predictive "P" pictures, which are encoded with a single predictor, or to Bi-predictive "B" pictures, which are encoded with two predictors. The decoding processes, which are present in both encoder and decoders, are described below for the P and B picture cases. Alternatively, this technique may also be applied to coding systems using the 20 concepts similar to I, B, and P pictures.

The same weighting factors can be used for single directional prediction in B pictures and for bi-directional prediction in B pictures. When a single predictor is used for a macroblock, in P pictures or for single directional prediction in B pictures, a single reference picture index is transmitted for the block. After the decoding process 25 step of motion compensation produces a predictor, the weighting factor is applied to predictor. The weighted predictor is then added to the coded residual, and clipping is performed on the sum, to form the decoded picture. For use for blocks in P pictures or for blocks in B pictures that use only list 0 prediction, the weighted predictor is formed as:

30

$$\text{Pred} = W0 * \text{Pred0} + D0 \quad (1)$$

where W_0 is the weighting factor associated with the list 0 reference picture, D_0 is the offset associated with the list 0 reference picture, and $Pred_0$ is the motion-compensated prediction block from the list 0 reference picture.

For use for blocks in B pictures which use only list 0 prediction, the weighted 5 predictor is formed as:

$$Pred = W_1 * Pred_1 + D_1 \quad (2)$$

where W_1 is the weighting factor associated with the list 1 reference picture, 10 D_0 is the offset associated with the list 1 reference picture, and $Pred_1$ is the motion-compensated prediction block from the list 1 reference picture.

The weighted predictors may be clipped to guarantee that the resulting values will be within the allowable range of pixel values, typically 0 to 255. The precision of the multiplication in the weighting formulas may be limited to any pre-determined 15 number of bits of resolution.

In the bi-predictive case, reference picture indexes are transmitted for each of the two predictors. Motion compensation is performed to form the two predictors. Each predictor uses the weighting factor associated with its reference picture index to 20 form two weighted predictors. The two weighted predictors are then averaged together to form an averaged predictor, which is then added to the coded residual..

For use for blocks in B pictures that use list 0 and list 1 predictions, the weighted predictor is formed as:

$$Pred = (P_0 * Pred_0 + D_0 + P_1 * Pred_1 + D_1) / 2 \quad (3)$$

25

Clipping may be applied to the weighted predictor or any of the intermediate values in the calculation of the weighted predictor to guarantee that the resulting values will be within the allowable range of pixel values, typically 0 to 255.

Thus, a weighting factor is applied to the reference picture prediction of a 30 video compression encoder and decoder that uses multiple reference pictures. The weighting factor adapts for individual motion blocks within a picture, based on the reference picture index that is used for that motion block. Because the reference picture index is already transmitted in the compressed video bitstream, the additional

overhead to adapt the weighting factor on a motion block basis is dramatically reduced. All motion blocks that are coded with respect to the same reference picture apply the same weighting factor to the reference picture prediction.

These and other features and advantages of the present invention may be 5 readily ascertained by one of ordinary skill in the pertinent art based on the teachings herein. It is to be understood that the teachings of the present invention may be implemented in various forms of hardware, software, firmware, special purpose processors, or combinations thereof.

Most preferably, the teachings of the present invention are implemented as a 10 combination of hardware and software. Moreover, the software is preferably implemented as an application program tangibly embodied on a program storage unit. The application program may be uploaded to, and executed by, a machine comprising any suitable architecture. Preferably, the machine is implemented on a computer platform having hardware such as one or more central processing units 15 ("CPU"), a random access memory ("RAM"), and input/output ("I/O") interfaces. The computer platform may also include an operating system and microinstruction code. The various processes and functions described herein may be either part of the microinstruction code or part of the application program, or any combination thereof, which may be executed by a CPU. In addition, various other peripheral units may be 20 connected to the computer platform such as an additional data storage unit and a printing unit.

It is to be further understood that, because some of the constituent system components and methods depicted in the accompanying drawings are preferably implemented in software, the actual connections between the system components or 25 the process function blocks may differ depending upon the manner in which the present invention is programmed. Given the teachings herein, one of ordinary skill in the pertinent art will be able to contemplate these and similar implementations or configurations of the present invention.

Although the illustrative embodiments have been described herein with 30 reference to the accompanying drawings, it is to be understood that the present invention is not limited to those precise embodiments, and that various changes and modifications may be effected therein by one of ordinary skill in the pertinent art without departing from the scope or spirit of the present invention. All such changes

and modifications are intended to be included within the scope of the present invention as set forth in the appended claims.

CLAIMS

1. A video decoder (300) for decoding video signal data for an image block and a particular reference picture index to predict the image block, the decoder comprising a reference picture weighting factor unit (380) having an output for determining a weighting factor corresponding to the particular reference picture index.
5
2. A video decoder (300) as defined in Claim 1 wherein the reference picture weighting factor unit (380) has a second output for determining an offset corresponding to the particular reference picture index.
10
3. A video decoder (300) as defined in Claim 1, further comprising a variable length decoder (310) in signal communication with the reference picture weighting factor unit (380) for providing the particular reference picture index to the reference picture weighting factor unit.
15
4. A video decoder (300) as defined in Claim 1, further comprising a motion compensator (360) in signal communication with the reference picture weighting factor unit (380) for providing motion compensated reference pictures responsive to the reference picture weighting factor unit.
20
5. A video decoder (300) as defined in Claim 4, further comprising a multiplier (370) in signal communication with the motion compensator (360) and the reference picture weighting factor unit (380) for applying a weighting factor to a motion compensated reference picture.
25
6. A video decoder (300) as defined in Claim 4, further comprising an adder (390) in signal communication with the motion compensator (360) and the reference picture weighting factor unit (380) for applying an offset to a motion compensated reference picture.
30
7. A video decoder (300) as defined in Claim 1 wherein the video signal data is streaming video signal data comprising block transform coefficients.

8. A video decoder (300) as defined in Claim 1 usable with bi-predictive picture predictors, the decoder further comprising:

prediction means for forming first and second predictors from two different reference pictures;

5 averaging means for averaging the first and second predictors together using their corresponding weighting factors to form a single averaged predictor.

9. A video decoder (300) as defined in Claim 8 wherein the two different reference pictures are both from the same direction relative to the image block.

10

10. A method (600) for decoding video signal data for an image block, the method comprising:

receiving (614) at least one reference picture index with the data for the image block, each corresponding to a particular reference picture;

15 determining (616) a weighting factor corresponding to each of the received at least one reference picture index;

retrieving (618) a reference picture corresponding to each of the received at least one reference picture index;

motion compensating (620) the retrieved reference picture; and

20 varying (622) the motion compensated reference picture by the corresponding weighting factor to form a weighted motion compensated reference picture.

11. A method as defined in Claim 10, further comprising:

determining (617) an offset corresponding to each of the received at least one reference picture index; and

adjusting (623) the motion compensated reference picture with the corresponding offset.

12. A method as defined in Claim 10, further comprising adding the 30 weighted motion compensated reference picture to the data for the image block to predict the image block.

13. A method as defined in Claim 12, further comprising storing the predicted image block as a reference picture for future retrieval.

14. A method as defined in Claim 10 wherein the video signal data is
5 streaming video signal data comprising block transform coefficients.



15. A method as defined in Claim 10 wherein bi-predictive picture predictors are used, the method further comprising:

10 forming first and second predictors from two different reference pictures;
motion compensating each of the first and second predictors;
averaging the first and second predictors together using their corresponding weighting factors to form a single averaged predictor.



16. A method as defined in Claim 15, further comprising:

15 determining first and second offsets corresponding to each of the first and second predictors; and
adding the the first and second predictors with the corresponding first and second offsets, respectively.


20 17. A method as defined in Claim 15 wherein the two different reference pictures are both from the same direction relative to the image block.

**FIG. 1****FIG. 2**

2/5

**FIG. 3****FIG. 4**

3/5






FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US03/21735

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : H04N 7/12, 11/02
US CL : 375/240.16, 240.18, 240.23, 240.24, 240.25

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 375/240.15, 240.16, 240.18, 240.23, 240.24, 240.25

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 6,292,514 B1 (YAMAGUCHI et al.) 18 September 2001, col. 11, lines 8-41, col. 26, lines 41-64, col. 60, lines 1-15, Figure 23B, col. 34, lines 45-59, Figure 67 B, col 63, lines 31-53.	1-7, and 10-14
Y	US 6,151,075 A (SHIN et al.) 21 November 2000, col. 7, lines 19-67.	8, 9, and 15-17
A	US 5,592,228 A (DACHIKU et al.) 07 January 1997.	
A	US 5,781,788 A (WOO et al.) 14 July 1998.	
A	US 6,175,592 B1 (KIM et al.) 16 January 2001.	

Further documents are listed in the continuation of Box C.

See patent family annex.

*	Special categories of cited documents:	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A"	document defining the general state of the art which is not considered to be of particular relevance	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E"	earlier document published on or after the international filing date	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&"	document member of the same patent family
"O"	document referring to an oral disclosure, use, exhibition or other means		
"P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

16 SEPTEMBER 2003

Date of mailing of the international search report

09 DEC 2003

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

GEORGE A. BUGG

Telephone No. (703) 305-2829