



US010267848B2

(12) **United States Patent**  
**Smith**

(10) **Patent No.:** **US 10,267,848 B2**  
(45) **Date of Patent:** **Apr. 23, 2019**

(54) **METHOD OF ELECTRICALLY CONTACTING A BOND PAD OF A DEVICE UNDER TEST WITH A PROBE**

*G01R 1/0735* (2013.01); *Y10T 29/49126* (2015.01); *Y10T 29/49208* (2015.01)

(71) Applicant: **Cascade Microtech, Inc.**, Beaverton, OR (US)

(58) **Field of Classification Search**  
CPC .. *G01R 3/00*; *G01R 1/06711*; *G01R 1/06744*; *G01R 1/067*; *G01R 31/2851*; *Y10T 29/49147*; *Y10T 29/49117*; *Y10T 29/49126*; *Y10T 29/49208*; *Y10S 428/929*  
USPC .. 29/876, 402.01, 402.08, 402.11, 874, 877; 156/64, 98  
See application file for complete search history.

(72) Inventor: **Kenneth R. Smith**, Beaverton, OR (US)

(73) Assignee: **FormFactor Beaverton, Inc.**, Beaverton, OR (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,337,866 A	4/1920	Whitaker
2,142,625 A	1/1939	Zoethout
2,376,101 A	5/1945	Tyzzler
2,389,668 A	11/1945	Johnson
3,176,091 A	3/1965	Hanson et al.
		(Continued)

(21) Appl. No.: **15/222,113**

(22) Filed: **Jul. 28, 2016**

(65) **Prior Publication Data**

US 2016/0334465 A1 Nov. 17, 2016

**Related U.S. Application Data**

(63) Continuation of application No. 13/854,725, filed on Apr. 1, 2013, now Pat. No. 9,429,638, which is a continuation of application No. 12/592,186, filed on Nov. 20, 2009, now Pat. No. 8,410,806.

(60) Provisional application No. 61/199,910, filed on Nov. 21, 2008.

FOREIGN PATENT DOCUMENTS

DE	4012839	10/1990
DE	4223658	1/1993
		(Continued)

OTHER PUBLICATIONS

English-language abstract of Chinese Patent No. CN 1083975, Mar. 16, 1994.

(Continued)

(51) **Int. Cl.**

<b>H01R 43/20</b>	(2006.01)
<b>G01R 31/28</b>	(2006.01)
<b>G01R 1/067</b>	(2006.01)
<b>B32B 38/10</b>	(2006.01)
<b>G01R 35/00</b>	(2006.01)
<b>G01R 1/073</b>	(2006.01)

*Primary Examiner* — Thiem D Phan

(74) *Attorney, Agent, or Firm* — Dascenzo Intellectual Property Law, P.C.


(52) **U.S. Cl.**

CPC ..... **G01R 31/2891** (2013.01); **B32B 38/10** (2013.01); **G01R 1/06711** (2013.01); **G01R 35/00** (2013.01); **G01R 1/06772** (2013.01);

(57) **ABSTRACT**

The contacts of a probing apparatus are elastically supported on a replaceable coupon and electrically interconnected with conductors on a membrane or a space transformer.

**11 Claims, 11 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

3,193,712 A	7/1965	Harris	4,636,772 A	1/1987	Yasunaga
3,230,299 A	1/1966	Radziejowski	4,641,659 A	2/1987	Sepponen
3,401,126 A	9/1968	Miller et al.	4,642,417 A	2/1987	Ruthrof et al.
3,429,040 A	2/1969	Miller	4,646,005 A	2/1987	Ryan
3,441,315 A	4/1969	Paes et al.	4,649,339 A	3/1987	Grangroth et al.
3,442,831 A	5/1969	Dickstein et al.	4,651,115 A	3/1987	Wu
3,445,770 A	5/1969	Harmon	4,663,840 A	5/1987	Ubbens et al.
3,484,679 A	12/1969	Hodgson et al.	4,673,839 A	6/1987	Veenendaal
3,541,222 A	11/1970	Parks et al.	4,684,883 A	8/1987	Ackerman et al.
3,595,228 A	7/1971	Simon et al.	4,691,163 A	9/1987	Blass et al.
3,596,228 A	7/1971	Reed, Jr. et al.	4,697,143 A	9/1987	Lockwood et al.
3,609,539 A	9/1971	Gunthert	4,705,447 A	11/1987	Smith
3,634,807 A	1/1972	Grobe et al.	4,707,657 A	11/1987	Bøegh-Petersen
3,654,585 A	4/1972	Wickersham	4,711,563 A	12/1987	Lass
3,680,037 A	7/1972	Nellis et al.	4,713,347 A	12/1987	Mitchell et al.
3,700,998 A	10/1972	Lee et al.	4,719,417 A	1/1988	Evans
3,710,251 A	1/1973	Hagge et al.	4,725,793 A	2/1988	Igarashi
3,714,572 A	1/1973	Ham et al.	4,727,391 A	2/1988	Tajima et al.
3,740,900 A	6/1973	Youmans et al.	4,727,637 A	3/1988	Buckwitz et al.
3,806,801 A	4/1974	Bove	4,742,571 A	5/1988	Letron
3,829,076 A	8/1974	Sofy	4,744,041 A	5/1988	Strunk et al.
3,839,672 A	10/1974	Anderson	4,746,857 A	5/1988	Sakai et al.
3,849,728 A	11/1974	Evans	4,749,942 A	6/1988	Sang et al.
3,858,212 A	12/1974	Tompkins et al.	4,754,239 A	6/1988	Sedivec
3,862,790 A	1/1975	Davies et al.	4,755,746 A	7/1988	Mallory et al.
3,866,093 A	2/1975	Kusters et al.	4,755,747 A	7/1988	Sato
3,936,743 A	2/1976	Roch	4,755,874 A	7/1988	Esrig et al.
3,952,156 A	4/1976	Lahr	4,757,255 A	7/1988	Margozzi
3,970,934 A	7/1976	Aksu	4,766,384 A	8/1988	Kleinberg et al.
3,971,610 A	7/1976	Buchhoff et al.	4,772,846 A	9/1988	Reeds
3,976,959 A	8/1976	Gaspari	4,780,670 A	10/1988	Cherry
3,992,073 A	11/1976	Buchhoff et al.	4,791,363 A	12/1988	Logan
4,008,900 A	2/1977	Khoshaba	4,793,814 A	12/1988	Zifcak et al.
4,027,935 A	6/1977	Byrnes et al.	4,795,962 A	1/1989	Yanagawa et al.
4,038,599 A	7/1977	Bove et al.	4,805,627 A	2/1989	Klingenbeck et al.
4,038,894 A	8/1977	Knibbe et al.	4,812,754 A	3/1989	Tracey et al.
4,049,252 A	9/1977	Bell	4,827,211 A	5/1989	Strid et al.
4,066,943 A	1/1978	Roch	4,831,494 A	5/1989	Arnold et al.
4,072,576 A	2/1978	Arwin et al.	4,835,495 A	5/1989	Simonutti
4,093,988 A	6/1978	Scott	4,837,507 A	6/1989	Hechtman
4,099,120 A	7/1978	Aksu	4,839,587 A	6/1989	Flatley et al.
4,115,735 A	9/1978	Stanford	4,849,689 A	7/1989	Gleason et al.
4,135,131 A	1/1979	Larsen et al.	4,853,624 A	8/1989	Rabjohn
4,184,729 A	1/1980	Parks et al.	4,853,627 A	8/1989	Gleason et al.
4,275,446 A	6/1981	Blaess	4,859,989 A	8/1989	McPherson
4,277,741 A	7/1981	Faxvog et al.	4,864,227 A	9/1989	Sato
4,284,033 A	8/1981	del Rio	4,871,883 A	10/1989	Guiol
4,284,682 A	8/1981	Frosch et al.	4,871,964 A	10/1989	Boll et al.
4,287,473 A	9/1981	Sawyer	4,891,584 A	1/1990	Kamieniecki et al.
4,306,235 A	12/1981	Christmann	4,893,914 A	1/1990	Hancock et al.
4,312,117 A	1/1982	Robillard et al.	4,894,612 A	1/1990	Drake et al.
4,327,180 A	4/1982	Chen	4,899,998 A	2/1990	Teramachi
4,330,783 A	5/1982	Toia	4,904,933 A	2/1990	Snyder et al.
4,357,575 A	11/1982	Uren et al.	4,904,935 A	2/1990	Calma et al.
4,376,920 A	3/1983	Smith	4,906,920 A	3/1990	Huff et al.
4,383,217 A	5/1983	Shiell	4,912,399 A	3/1990	Greub et al.
4,401,945 A	8/1983	Juengel	4,916,002 A	4/1990	Carver
4,425,395 A	1/1984	Negishi et al.	4,916,398 A	4/1990	Rath
4,453,142 A	6/1984	Murphy	4,918,383 A	4/1990	Huff et al.
4,468,629 A	8/1984	Choma, Jr.	4,922,128 A	5/1990	Dhong et al.
4,487,996 A	12/1984	Rabinowitz et al.	4,922,186 A	5/1990	Tsuchiya et al.
4,515,133 A	5/1985	Roman	4,922,192 A	5/1990	Gross et al.
4,515,439 A	5/1985	Esswein	4,929,893 A	5/1990	Sato et al.
4,528,504 A	7/1985	Thornton, Jr. et al.	4,975,638 A	12/1990	Evans et al.
4,531,474 A	7/1985	Inuta	4,980,637 A	12/1990	Huff et al.
4,552,033 A	11/1985	Marzhauser	4,983,910 A	1/1991	Majidi-Ahy et al.
4,567,321 A	1/1986	Harayama	4,987,100 A	1/1991	McBride et al.
4,568,890 A	2/1986	Bates	4,991,290 A	2/1991	MacKay
4,581,679 A	4/1986	Smolley	4,998,062 A	3/1991	Ikeda
4,588,950 A	5/1986	Henley	5,001,423 A	3/1991	Abrami et al.
4,593,243 A	6/1986	Lao et al.	5,003,253 A	3/1991	Majidi-Ahy et al.
4,600,907 A	7/1986	Grellman et al.	5,020,219 A	6/1991	Leedy
4,621,169 A	11/1986	Petinelli et al.	5,021,186 A	6/1991	Ota et al.
4,626,618 A	12/1986	Takaoka et al.	5,030,907 A	7/1991	Yih et al.
4,636,722 A	1/1987	Ardezzone	5,041,782 A	8/1991	Marzan
			5,045,781 A	9/1991	Gleason et al.
			5,059,898 A	10/1991	Barsotti et al.
			5,061,192 A	10/1991	Chapin et al.
			5,061,823 A	10/1991	Carroll

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,066,357	A	11/1991	Smyth, Jr. et al.	5,412,330	A	5/1995	Ravel et al.
5,069,628	A	12/1991	Crumly	5,412,866	A	5/1995	Woith et al.
5,082,627	A	1/1992	Stanbro	5,414,565	A	5/1995	Sullivan et al.
5,084,671	A	1/1992	Miyata et al.	5,422,574	A	6/1995	Kister
5,089,774	A	2/1992	Nakano	5,441,690	A	8/1995	Ayala-Esquilin et al.
5,091,692	A	2/1992	Ohno et al.	5,451,722	A	9/1995	Gregoire
5,091,732	A	2/1992	Mileski et al.	5,451,884	A	9/1995	Sauerland
5,095,891	A	3/1992	Reitter	5,453,404	A	9/1995	Leedy
5,097,101	A	3/1992	Trobough	5,457,398	A	10/1995	Schwindt et al.
5,097,207	A	3/1992	Blanz	5,467,024	A	11/1995	Swapp
5,107,076	A	4/1992	Bullock et al.	5,469,324	A	11/1995	Henderson et al.
5,126,286	A	6/1992	Chance	5,475,316	A	12/1995	Hurley et al.
5,126,696	A	6/1992	Grote et al.	5,476,211	A	12/1995	Khandros
5,133,119	A	7/1992	Afshari et al.	5,477,011	A	12/1995	Singles et al.
5,134,365	A	7/1992	Okubo et al.	5,478,748	A	12/1995	Akins, Jr. et al.
5,136,237	A	8/1992	Smith et al.	5,479,108	A	12/1995	Cheng
5,138,289	A	8/1992	McGrath	5,479,109	A	12/1995	Lau et al.
5,142,224	A	8/1992	Smith et al.	5,481,196	A	1/1996	Nosov
5,145,552	A	9/1992	Yoshizawa et al.	5,481,936	A	1/1996	Yanagisawa
5,148,103	A	9/1992	Pasiecznik, Jr.	5,487,999	A	1/1996	Farnworth
5,159,264	A	10/1992	Anderson	5,488,954	A	2/1996	Sleva et al.
5,159,267	A	10/1992	Anderson	5,493,070	A	2/1996	Habu
5,159,752	A	11/1992	Mahant-Shetti et al.	5,493,236	A	2/1996	Ishii et al.
5,160,883	A	11/1992	Blanz	5,500,606	A	3/1996	Holmes
5,164,319	A	11/1992	Hafeman et al.	5,505,150	A	4/1996	James et al.
5,166,606	A	11/1992	Blanz	5,506,498	A	4/1996	Anderson et al.
5,172,049	A	12/1992	Kiyokawa et al.	5,506,515	A	4/1996	Godshalk et al.
5,172,050	A	12/1992	Swapp	5,510,792	A	4/1996	Ono et al.
5,172,051	A	12/1992	Zamborelli	5,511,010	A	4/1996	Burns
5,177,438	A	1/1993	Littlebury et al.	5,512,835	A	4/1996	Rivera et al.
5,180,977	A	1/1993	Huff	5,517,126	A	5/1996	Yamaguchi
5,187,443	A	2/1993	Bereskin	5,521,518	A	5/1996	Higgins
5,198,752	A	3/1993	Miyata et al.	5,521,522	A	5/1996	Abe et al.
5,198,753	A	3/1993	Hamburgen	5,523,694	A	6/1996	Cole, Jr.
5,202,558	A	4/1993	Barker	5,528,158	A	6/1996	Sinsheimer et al.
5,202,648	A	4/1993	McCandless	5,530,372	A	6/1996	Lee et al.
5,207,585	A	5/1993	Byrnes et al.	5,531,022	A	7/1996	Beaman et al.
5,214,243	A	5/1993	Johnson	5,532,608	A	7/1996	Behfar-Rad et al.
5,214,374	A	5/1993	St. Onge	5,537,372	A	7/1996	Albrecht et al.
5,225,037	A	7/1993	Elder et al.	5,539,323	A	7/1996	Davis, Jr.
5,227,730	A	7/1993	King et al.	5,539,676	A	7/1996	Yamaguchi
5,232,789	A	8/1993	Platz et al.	5,565,788	A	10/1996	Burr et al.
5,233,197	A	8/1993	Bowman et al.	5,565,881	A	10/1996	Phillips et al.
5,233,306	A	8/1993	Misra	5,569,591	A	10/1996	Kell et al.
5,245,292	A	9/1993	Milesky et al.	5,571,324	A	11/1996	Sago et al.
5,266,889	A	11/1993	Harwood et al.	5,578,932	A	11/1996	Adamian
5,267,088	A	11/1993	Nomura	5,583,445	A	12/1996	Mullen
5,270,664	A	12/1993	McMurtry et al.	5,584,120	A	12/1996	Roberts
5,274,336	A	12/1993	Crook et al.	5,584,608	A	12/1996	Gillespie
5,280,156	A	1/1994	Niori et al.	5,589,781	A	12/1996	Higgins et al.
5,293,175	A	3/1994	Hemmie et al.	5,600,256	A	2/1997	Woith et al.
5,298,972	A	3/1994	Heffner	5,601,740	A	2/1997	Eldridge et al.
5,304,924	A	4/1994	Yamano et al.	5,610,529	A	3/1997	Schwindt
5,313,157	A	5/1994	Pasiecznik, Jr.	5,611,008	A	3/1997	Yap
5,315,237	A	5/1994	Iwakura et al.	5,617,035	A	4/1997	Swapp
5,321,352	A	6/1994	Takebuchi	5,623,213	A	4/1997	Liu et al.
5,321,453	A	6/1994	Mori et al.	5,623,214	A	4/1997	Pasiecznik, Jr.
5,326,412	A	7/1994	Schreiber et al.	5,628,057	A	5/1997	Phillips et al.
5,355,079	A	10/1994	Evans et al.	5,631,571	A	5/1997	Spaziani et al.
5,357,211	A	10/1994	Bryson et al.	5,633,780	A	5/1997	Cronin
5,361,049	A	11/1994	Rubin et al.	5,634,267	A	6/1997	Farnworth et al.
5,363,050	A	11/1994	Guo et al.	5,635,846	A	6/1997	Beaman et al.
5,367,165	A	11/1994	Toda et al.	5,642,298	A	6/1997	Mallory et al.
5,368,634	A	11/1994	Hackett	5,644,248	A	7/1997	Fujimoto
5,369,368	A	11/1994	Kassen et al.	5,653,939	A	8/1997	Hollis et al.
5,371,654	A	12/1994	Beaman et al.	5,656,942	A	8/1997	Watts et al.
5,373,231	A	12/1994	Boll et al.	5,659,421	A	8/1997	Rahmel et al.
5,374,938	A	12/1994	Hatazawa et al.	5,666,063	A	9/1997	Abercrombie et al.
5,376,790	A	12/1994	Linker et al.	5,669,316	A	9/1997	Faz et al.
5,389,885	A	2/1995	Swart	5,670,322	A	9/1997	Eggers et al.
5,395,253	A	3/1995	Crumly	5,670,888	A	9/1997	Cheng
5,397,855	A	3/1995	Ferlier	5,672,816	A	9/1997	Park et al.
5,404,111	A	4/1995	Mori et al.	5,675,499	A	10/1997	Lee et al.
5,408,188	A	4/1995	Katoh	5,675,932	A	10/1997	Mauney
5,408,189	A	4/1995	Swart et al.	5,676,360	A	10/1997	Boucher et al.
				5,685,232	A	11/1997	Inoue
				5,686,317	A	11/1997	Akram et al.
				5,688,618	A	11/1997	Hulderman et al.
				5,700,844	A	12/1997	Hedrik et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,704,355	A	1/1998	Bridges	5,949,579	A	9/1999	Baker
5,715,819	A	2/1998	Svenson et al.	5,959,461	A	9/1999	Brown et al.
5,720,098	A	2/1998	Kister	5,963,364	A	10/1999	Leong et al.
5,723,347	A	3/1998	Hirano et al.	5,970,429	A	10/1999	Martin
5,726,211	A	3/1998	Hedrick et al.	5,973,504	A	10/1999	Chong
5,731,920	A	3/1998	Katsuragawa	5,981,268	A	11/1999	Kovacs et al.
5,742,174	A	4/1998	Kister et al.	5,982,166	A	11/1999	Mautz
5,744,383	A	4/1998	Fritz	5,983,493	A	11/1999	Eldridge et al.
5,744,971	A	4/1998	Chan et al.	5,990,695	A	11/1999	Daugherty, Jr.
5,748,506	A	5/1998	Bockelman	5,993,611	A	11/1999	Moroney, III et al.
5,751,252	A	5/1998	Phillips	5,994,152	A	11/1999	Khandros et al.
5,756,021	A	5/1998	Hedrick et al.	5,995,914	A	11/1999	Cabot
5,767,690	A	6/1998	Fujimoto	5,996,102	A	11/1999	Haulin
5,772,451	A	6/1998	Dozier, II et al.	5,998,228	A	12/1999	Eldridge et al.
5,773,780	A	6/1998	Eldridge et al.	5,998,768	A	12/1999	Hunter et al.
5,777,485	A	7/1998	Tanaka et al.	5,998,864	A	12/1999	Khandros et al.
5,785,538	A	7/1998	Beaman et al.	5,999,268	A	12/1999	Yonezawa et al.
5,792,668	A	8/1998	Fuller et al.	6,001,760	A	12/1999	Katsuda et al.
5,793,213	A	8/1998	Bockelman et al.	6,002,426	A	12/1999	Back et al.
5,794,133	A	8/1998	Kashima	6,013,586	A	1/2000	McGhee et al.
5,804,607	A	9/1998	Hedrick et al.	6,019,612	A	2/2000	Hasegawa et al.
5,804,982	A	9/1998	Lo et al.	6,020,745	A	2/2000	Taraci
5,804,983	A	9/1998	Nakajima et al.	6,023,103	A	2/2000	Chang et al.
5,806,181	A	9/1998	Khandros et al.	6,028,435	A	2/2000	Nikawa
5,807,107	A	9/1998	Bright et al.	6,029,344	A	2/2000	Khandros et al.
5,810,607	A	9/1998	Shih et al.	6,031,383	A	2/2000	Streib et al.
5,810,609	A	9/1998	Faraci et al.	6,032,356	A	3/2000	Eldridge et al.
5,811,751	A	9/1998	Leong et al.	6,032,714	A	3/2000	Fenton
5,811,982	A	9/1998	Beaman et al.	6,033,935	A	3/2000	Dozier, II et al.
5,813,847	A	9/1998	Eroglu et al.	6,034,533	A	3/2000	Tervo et al.
5,814,847	A	9/1998	Shihadeh et al.	6,037,785	A	3/2000	Higgins
5,820,014	A	10/1998	Dozier, II et al.	6,040,739	A	3/2000	Wedeen et al.
5,821,763	A	10/1998	Beaman et al.	6,042,712	A	3/2000	Mathieu
5,824,494	A	10/1998	Feldberg	6,043,563	A	3/2000	Eldridge et al.
5,829,128	A	11/1998	Eldridge et al.	6,049,216	A	4/2000	Yang et al.
5,829,437	A	11/1998	Bridges	6,049,976	A	4/2000	Khandros
5,831,442	A	11/1998	Heigl	6,050,829	A	4/2000	Eldridge et al.
5,832,601	A	11/1998	Eldridge et al.	6,051,422	A	4/2000	Kovacs et al.
5,833,601	A	11/1998	Swartz et al.	6,052,653	A	4/2000	Mazur et al.
5,838,160	A	11/1998	Beaman et al.	6,054,651	A	4/2000	Fogel et al.
5,841,288	A	11/1998	Meaney et al.	6,054,869	A	4/2000	Hutton et al.
5,846,708	A	12/1998	Hollis et al.	6,059,982	A	5/2000	Palagonia et al.
5,847,569	A	12/1998	Ho et al.	6,060,888	A	5/2000	Blackham et al.
5,848,500	A	12/1998	Kirk	6,060,892	A	5/2000	Yamagata
5,852,232	A	12/1998	Samsavar et al.	6,061,589	A	5/2000	Bridges et al.
5,854,608	A	12/1998	Leisten	6,062,879	A	5/2000	Beaman et al.
5,864,946	A	2/1999	Eldridge et al.	6,064,213	A	5/2000	Khandros et al.
5,867,073	A	2/1999	Weinreb et al.	6,064,217	A	5/2000	Smith
5,869,326	A	2/1999	Hofmann	6,064,218	A	5/2000	Godfrey et al.
5,869,974	A	2/1999	Akram et al.	6,066,911	A	5/2000	Lindemann et al.
5,874,361	A	2/1999	Collins et al.	6,075,376	A	6/2000	Schwindt
5,876,082	A	3/1999	Kempf et al.	6,078,183	A	6/2000	Cole, Jr.
5,878,486	A	3/1999	Eldridge et al.	6,078,500	A	6/2000	Beaman et al.
5,883,522	A	3/1999	O'Boyle	6,090,261	A	7/2000	Mathieu
5,883,523	A	3/1999	Ferland et al.	6,091,236	A	7/2000	Piety et al.
5,884,398	A	3/1999	Eldridge et al.	6,091,255	A	7/2000	Godfrey
5,888,075	A	3/1999	Hasegawa et al.	6,096,567	A	8/2000	Kaplan et al.
5,892,539	A	4/1999	Colvin	6,100,815	A	8/2000	Pailthorp
5,896,038	A	4/1999	Budnaitis et al.	6,104,201	A	8/2000	Beaman et al.
5,896,326	A	4/1999	Akashi	6,104,206	A	8/2000	Verkuil
5,900,737	A	5/1999	Graham et al.	6,110,823	A	8/2000	Eldridge et al.
5,900,738	A	5/1999	Khandros et al.	6,114,864	A	9/2000	Soejima et al.
5,903,143	A	5/1999	Mochizuki et al.	6,114,865	A	9/2000	Lagowski et al.
5,905,421	A	5/1999	Oldfield	6,118,287	A	9/2000	Boll et al.
5,910,727	A	6/1999	Fujihara et al.	6,118,894	A	9/2000	Schwartz et al.
5,912,046	A	6/1999	Eldridge et al.	6,124,725	A	9/2000	Sato
5,914,613	A	6/1999	Gleason et al.	6,127,831	A	10/2000	Khoury et al.
5,914,614	A	6/1999	Beaman et al.	6,137,302	A	10/2000	Schwindt
5,916,689	A	6/1999	Collins et al.	6,144,212	A	11/2000	Mizuta
5,917,707	A	6/1999	Khandros et al.	6,147,502	A	11/2000	Fryer et al.
5,926,029	A	7/1999	Ference et al.	6,147,851	A	11/2000	Anderson
5,926,951	A	7/1999	Khandros et al.	6,150,186	A	11/2000	Chen et al.
5,944,093	A	8/1999	Viswanath	6,160,407	A	12/2000	Nikawa
5,945,836	A	8/1999	Sayre et al.	6,160,412	A	12/2000	Martel et al.
5,949,383	A	9/1999	Hayes et al.	6,166,333	A	12/2000	Crumly et al.
				6,166,553	A	12/2000	Sinsheimer
				6,168,974	B1	1/2001	Chang et al.
				6,169,410	B1	1/2001	Grace et al.
				6,172,337	B1	1/2001	Johnsgard et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,174,744	B1	1/2001	Watanabe et al.	6,396,298	B1	5/2002	Young et al.
6,175,228	B1	1/2001	Zamborelli et al.	6,400,168	B2	6/2002	Matsunaga et al.
6,176,091	B1	1/2001	Kishi et al.	6,404,211	B2	6/2002	Hamel et al.
6,181,144	B1	1/2001	Hembree et al.	6,404,213	B2	6/2002	Noda
6,181,149	B1	1/2001	Godfrey et al.	6,407,562	B1	6/2002	Whiteman
6,181,297	B1	1/2001	Leisten	6,409,724	B1	6/2002	Penney et al.
6,181,416	B1	1/2001	Falk	6,414,478	B1	7/2002	Suzuki
6,184,053	B1	2/2001	Eldridge et al.	6,415,858	B1	7/2002	Getchel et al.
6,184,587	B1	2/2001	Khandros et al.	6,418,009	B1	7/2002	Brunette
6,184,845	B1	2/2001	Leisten et al.	6,419,500	B1	7/2002	Kister
6,191,596	B1	2/2001	Abiko	6,420,722	B2	7/2002	Moore et al.
6,194,720	B1	2/2001	Li et al.	6,420,887	B1	7/2002	Kister et al.
6,206,273	B1	3/2001	Beaman et al.	6,424,164	B1	7/2002	Kister
6,208,225	B1	3/2001	Miller	6,424,316	B1	7/2002	Leisten et al.
6,211,663	B1	4/2001	Moulthrop et al.	6,429,029	B1	8/2002	Eldridge et al.
6,211,837	B1	4/2001	Crouch et al.	6,441,315	B1	8/2002	Eldridge et al.
6,215,196	B1	4/2001	Eldridge et al.	6,442,831	B1	9/2002	Khandros et al.
6,215,295	B1	4/2001	Smith, III	6,447,339	B1	9/2002	Reed et al.
6,215,670	B1	4/2001	Khandros	6,448,788	B1	9/2002	Meaney et al.
6,218,910	B1	4/2001	Miller	6,448,865	B1	9/2002	Miller
6,222,031	B1	4/2001	Wakabayashi et al.	6,452,406	B1	9/2002	Beaman et al.
6,229,327	B1	5/2001	Boll et al.	6,452,411	B1	9/2002	Miller et al.
6,232,149	B1	5/2001	Dozier, II et al.	6,456,099	B1	9/2002	Eldridge et al.
6,232,787	B1	5/2001	Lo et al.	6,456,103	B1	9/2002	Eldridge et al.
6,232,788	B1	5/2001	Schwindt et al.	6,459,343	B1	10/2002	Miller
6,233,613	B1	5/2001	Walker et al.	6,459,739	B1	10/2002	Vitenberg
6,236,223	B1	5/2001	Brady et al.	6,468,098	B1	10/2002	Eldridge
6,242,803	B1	6/2001	Khandros et al.	6,475,822	B2	11/2002	Eldridge et al.
6,242,929	B1	6/2001	Mizuta	6,476,333	B1	11/2002	Khandros et al.
6,245,692	B1	6/2001	Pearce et al.	6,476,442	B1	11/2002	Williams et al.
6,246,247	B1	6/2001	Eldridge et al.	6,476,630	B1	11/2002	Whitten et al.
6,250,933	B1	6/2001	Khoury et al.	6,479,308	B1	11/2002	Eldridge
6,251,595	B1	6/2001	Gordon et al.	6,480,013	B1	11/2002	Nayler et al.
6,255,126	B1	7/2001	Mathieu et al.	6,480,978	B1	11/2002	Roy et al.
6,256,882	B1	7/2001	Gleason et al.	6,481,939	B1	11/2002	Gillespie et al.
6,257,564	B1	7/2001	Avneri et al.	6,482,013	B2	11/2002	Eldridge et al.
6,265,950	B1	7/2001	Schmidt et al.	6,483,327	B1	11/2002	Bruce et al.
6,268,015	B1	7/2001	Mathieu et al.	6,488,405	B1	12/2002	Eppes et al.
6,268,016	B1	7/2001	Bhatt et al.	6,490,471	B2	12/2002	Svenson et al.
6,271,673	B1	8/2001	Furuta et al.	6,491,968	B1	12/2002	Mathieu et al.
6,274,823	B1	8/2001	Khandros et al.	6,499,121	B1	12/2002	Roy et al.
6,275,738	B1	8/2001	Kasevich et al.	6,501,343	B2	12/2002	Miller
6,278,051	B1	8/2001	Peabody	6,509,751	B1	1/2003	Mathieu
6,278,411	B1	8/2001	Ohlsson et al.	6,512,482	B1	1/2003	Nelson et al.
6,281,691	B1	8/2001	Matsunaga et al.	6,514,783	B1	2/2003	Welstand
6,286,208	B1	9/2001	Shih et al.	6,520,778	B1	2/2003	Eldridge et al.
6,292,760	B1	9/2001	Burns	6,525,552	B2	2/2003	Kister
6,295,729	B1	10/2001	Beaman et al.	6,525,555	B1	2/2003	Khandros et al.
6,300,775	B1	10/2001	Peach et al.	6,526,655	B2	3/2003	Beaman et al.
6,300,780	B1	10/2001	Beaman et al.	6,528,984	B2	3/2003	Beaman et al.
6,307,161	B1	10/2001	Grube et al.	6,528,993	B1	3/2003	Shin et al.
6,307,387	B1	10/2001	Gleason et al.	6,529,844	B1	3/2003	Kapetanic et al.
6,307,672	B1	10/2001	DeNure	6,530,148	B1	3/2003	Kister
6,310,483	B1	10/2001	Taura et al.	6,534,856	B1	3/2003	Dozier, II et al.
6,320,372	B1	11/2001	Keller	6,538,214	B2	3/2003	Khandros
6,320,396	B1	11/2001	Nikawa	6,538,538	B2	3/2003	Hreish et al.
6,327,034	B1	12/2001	Hoover et al.	6,539,531	B2	3/2003	Miller et al.
6,329,827	B1	12/2001	Beaman et al.	6,548,311	B1	4/2003	Knoll
6,330,164	B1	12/2001	Khandros et al.	6,549,022	B1	4/2003	Cole, Jr. et al.
6,332,270	B2	12/2001	Beaman et al.	6,549,106	B2	4/2003	Martin
6,334,247	B1	1/2002	Beaman et al.	6,551,884	B2	4/2003	Masuoka
6,335,625	B1	1/2002	Bryant et al.	6,559,671	B2	5/2003	Miller et al.
6,339,338	B1	1/2002	Eldridge et al.	6,566,079	B2	5/2003	Hefti
6,340,568	B2	1/2002	Hefti	6,573,702	B2	6/2003	Marcuse et al.
6,340,895	B1	1/2002	Uher et al.	6,578,264	B1	6/2003	Gleason et al.
6,351,885	B2	3/2002	Suzuki et al.	6,580,283	B1	6/2003	Carbone et al.
6,352,454	B1	3/2002	Kim et al.	6,582,979	B2	6/2003	Coccioli et al.
6,359,456	B1	3/2002	Hembree et al.	6,586,956	B2	7/2003	Aldaz et al.
6,362,792	B1	3/2002	Sawamura et al.	6,587,327	B1	7/2003	Devoe et al.
6,366,247	B1	4/2002	Sawamura et al.	6,597,187	B2	7/2003	Eldridge et al.
6,369,776	B1	4/2002	Leisten et al.	6,603,322	B1	8/2003	Boll et al.
6,376,258	B2	4/2002	Hefti	6,603,323	B1	8/2003	Miller et al.
6,384,614	B1	5/2002	Hager et al.	6,603,324	B2	8/2003	Eldridge et al.
6,395,480	B1	5/2002	Hefti	6,605,951	B1	8/2003	Cowan
6,396,296	B1	5/2002	Tartar et al.	6,605,955	B1	8/2003	Costello et al.
				6,606,014	B2	8/2003	Miller
				6,606,575	B2	8/2003	Miller
				6,608,494	B1	8/2003	Bruce et al.
				6,611,417	B2	8/2003	Chen

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,615,485	B2	9/2003	Eldridge et al.	6,791,176	B2	9/2004	Mathieu et al.
6,616,966	B2	9/2003	Mathieu et al.	6,794,888	B2	9/2004	Kawaguchi et al.
6,617,862	B1	9/2003	Bruce	6,794,950	B2	9/2004	Du Toit et al.
6,621,082	B2	9/2003	Morita et al.	6,798,225	B2	9/2004	Miller
6,621,260	B2	9/2003	Eldridge et al.	6,798,226	B2	9/2004	Altman et al.
6,622,103	B1	9/2003	Miller	6,806,724	B2	10/2004	Hayden et al.
6,624,648	B2	9/2003	Eldridge et al.	6,806,836	B2	10/2004	Ogawa et al.
6,627,461	B2	9/2003	Chapman et al.	6,807,734	B2	10/2004	Eldridge et al.
6,627,483	B2	9/2003	Ondricek et al.	6,809,533	B1	10/2004	Anlage et al.
6,627,980	B2	9/2003	Eldridge	6,811,406	B2	11/2004	Grube
6,628,503	B2	9/2003	Sogard	6,812,691	B2	11/2004	Miller
6,628,980	B2	9/2003	Atalar et al.	6,812,718	B1	11/2004	Chong et al.
6,633,174	B1	10/2003	Satya et al.	6,815,963	B2	11/2004	Gleason et al.
6,636,182	B2	10/2003	Mehitretter	6,816,031	B1	11/2004	Miller
6,639,461	B1	10/2003	Tam et al.	6,817,052	B2	11/2004	Grube
6,640,415	B2	11/2003	Eslamy et al.	6,818,840	B2	11/2004	Khandros
6,640,432	B1	11/2003	Mathieu et al.	6,822,463	B1	11/2004	Jacobs
6,642,625	B2	11/2003	Dozier, II et al.	6,822,529	B2	11/2004	Miller
6,643,597	B1	11/2003	Dunsmore	6,825,052	B2	11/2004	Eldridge et al.
6,644,982	B1	11/2003	Ondricek et al.	6,825,422	B2	11/2004	Eldridge et al.
6,646,520	B2	11/2003	Miller	6,827,584	B2	12/2004	Mathieu et al.
6,653,903	B2	11/2003	Leich et al.	6,835,898	B2	12/2004	Eldridge et al.
6,655,023	B1	12/2003	Eldridge et al.	6,836,962	B2	1/2005	Khandros et al.
6,657,455	B2	12/2003	Eldridge et al.	6,838,885	B2	1/2005	Kamitani
6,657,601	B2	12/2003	McLean	6,838,890	B2	1/2005	Tervo et al.
6,661,316	B2	12/2003	Hreish et al.	6,839,964	B2	1/2005	Henson
6,664,628	B2	12/2003	Khandros et al.	6,845,491	B2	1/2005	Miller et al.
6,669,489	B1	12/2003	Dozier, II et al.	6,856,129	B2	2/2005	Thomas et al.
6,672,875	B1	1/2004	Mathieu et al.	6,856,150	B2	2/2005	Sporck et al.
6,677,744	B1	1/2004	Long	6,860,009	B2	3/2005	Gleason et al.
6,678,850	B2	1/2004	Roy et al.	6,862,727	B2	3/2005	Stevens
6,678,876	B2	1/2004	Stevens et al.	6,864,105	B2	3/2005	Grube et al.
6,680,659	B2	1/2004	Miller	6,864,694	B2	3/2005	McTigue
6,685,817	B1	2/2004	Mathieu	6,870,381	B2	3/2005	Grube
6,686,754	B2	2/2004	Miller	6,882,239	B2	4/2005	Miller
6,690,185	B1	2/2004	Khandros et al.	6,882,546	B2	4/2005	Miller
6,701,265	B2	3/2004	Hill et al.	6,887,723	B1	5/2005	Ondricek et al.
6,701,612	B2	3/2004	Khandros et al.	6,888,362	B2	5/2005	Eldridge et al.
6,707,548	B2	3/2004	Kreimer et al.	6,891,385	B2	5/2005	Miller
6,708,386	B2	3/2004	Gleason et al.	6,900,646	B2	5/2005	Kasukabe et al.
6,708,403	B2	3/2004	Beaman et al.	6,900,647	B2	5/2005	Yoshida et al.
6,710,798	B1	3/2004	Hershel et al.	6,900,652	B2	5/2005	Mazur
6,713,374	B2	3/2004	Eldridge et al.	6,900,653	B2	5/2005	Yu et al.
6,714,828	B2	3/2004	Eldridge et al.	6,902,416	B2	6/2005	Feldman
6,717,426	B2	4/2004	Iwasaki	6,902,941	B2	6/2005	Sun
6,720,501	B1	4/2004	Henson	6,903,563	B2	6/2005	Yoshida et al.
6,722,032	B2	4/2004	Beaman et al.	6,906,506	B1	6/2005	Reano et al.
6,724,205	B1	4/2004	Hayden et al.	6,906,539	B2	6/2005	Wilson et al.
6,724,928	B1	4/2004	Davis	6,906,542	B2	6/2005	Sakagawa et al.
6,727,579	B1	4/2004	Eldridge et al.	6,906,543	B2	6/2005	Lou et al.
6,727,580	B1	4/2004	Eldridge et al.	6,907,149	B2	6/2005	Slater
6,727,716	B1	4/2004	Sharif	6,908,364	B2	6/2005	Back et al.
6,729,019	B2	5/2004	Grube et al.	6,909,297	B2	6/2005	Ji et al.
6,731,804	B1	5/2004	Carrieri et al.	6,909,300	B2	6/2005	Lu et al.
6,734,687	B1	5/2004	Ishitani et al.	6,909,983	B2	6/2005	Sutherland
6,737,920	B2	5/2004	Jen et al.	6,910,268	B2	6/2005	Miller
6,741,085	B1	5/2004	Khandros et al.	6,911,814	B2	6/2005	Miller et al.
6,741,092	B2	5/2004	Eldridge et al.	6,911,826	B2	6/2005	Plotnikov et al.
6,744,268	B2	6/2004	Hollman	6,911,834	B2	6/2005	Mitchell et al.
6,753,679	B1	6/2004	Kwong et al.	6,911,835	B2	6/2005	Chraft et al.
6,753,699	B2	6/2004	Stockstad	6,912,468	B2	6/2005	Marin et al.
6,759,311	B2	7/2004	Eldridge et al.	6,913,468	B2	7/2005	Dozier, II et al.
6,764,869	B2	7/2004	Eldridge	6,914,244	B2	7/2005	Alani
6,768,328	B2	7/2004	Self et al.	6,914,427	B2	7/2005	Gifford et al.
6,770,955	B1	8/2004	Coccioli et al.	6,914,430	B2	7/2005	Hasegawa et al.
6,771,806	B1	8/2004	Satya et al.	6,914,580	B2	7/2005	Leisten
6,777,319	B2	8/2004	Grube et al.	6,917,195	B2	7/2005	Hollman
6,778,140	B1	8/2004	Yeh	6,917,210	B2	7/2005	Miller
6,778,406	B2	8/2004	Eldridge et al.	6,917,211	B2	7/2005	Yoshida et al.
6,780,001	B2	8/2004	Eldridge et al.	6,917,525	B2	7/2005	Mok et al.
6,784,674	B2	8/2004	Miller	6,917,732	B2	7/2005	Miyata et al.
6,784,677	B2	8/2004	Miller et al.	6,919,732	B2	7/2005	Yoshida et al.
6,784,679	B2	8/2004	Sweet et al.	6,922,069	B2	7/2005	Jun
6,788,093	B2	9/2004	Aitren et al.	6,924,653	B2	8/2005	Schaeffer et al.
6,788,094	B2	9/2004	Khandros et al.	6,924,655	B2	8/2005	Kirby
				6,927,078	B2	8/2005	Saijyo et al.
				6,927,079	B1	8/2005	Fyfield
				6,927,586	B2	8/2005	Thiessen
				6,927,587	B2	8/2005	Yoshioka

(56)

## References Cited

## U.S. PATENT DOCUMENTS

			7,088,981	B2	8/2006	Chang
			7,096,133	B1	8/2006	Martin et al.
			7,148,711	B2	12/2006	Tervo et al.
			7,187,188	B2	3/2007	Andrews et al.
			7,188,037	B2	3/2007	Hidehira
			7,212,088	B1	5/2007	Norregaard et al.
			7,266,889	B2	9/2007	Gleason et al.
			7,368,927	B2	5/2008	Smith et al.
			7,888,957	B2	2/2011	Smith et al.
			2001/0002794	A1	6/2001	Draving et al.
			2001/0009061	A1	7/2001	Gleason et al.
			2001/0009377	A1	7/2001	Schwindt et al.
			2001/0010468	A1	8/2001	Gleason et al.
			2001/0020283	A1	9/2001	Sakaguchi
			2001/0024116	A1	9/2001	Draving
			2001/0030549	A1	10/2001	Gleason et al.
			2001/0043073	A1	11/2001	Montoya
			2001/0044152	A1	11/2001	Burnett
			2001/0045511	A1	11/2001	Moore et al.
			2001/0054906	A1	12/2001	Fujimura
			2002/0005728	A1	1/2002	Babson et al.
			2002/0008533	A1	1/2002	Ito et al.
			2002/0009377	A1	1/2002	Shafer
			2002/0009378	A1	1/2002	Obara
			2002/0011859	A1	1/2002	Smith et al.
			2002/0011863	A1	1/2002	Takahashi et al.
			2002/0050828	A1	5/2002	Seward, IV et al.
			2002/0070743	A1	6/2002	Felici et al.
			2002/0070745	A1	6/2002	Johnson et al.
			2002/0079911	A1	6/2002	Schwindt
			2002/0109514	A1	8/2002	Brandorff et al.
			2002/0118034	A1	8/2002	Laureanti
			2002/0149377	A1	10/2002	Hefti et al.
			2002/0153909	A1	10/2002	Petersen et al.
			2002/0163769	A1	11/2002	Brown
			2002/0168659	A1	11/2002	Hefti et al.
			2002/0180466	A1	12/2002	Hiramatsu et al.
			2002/0197709	A1	12/2002	van der Weide et al.
			2003/0010877	A1	1/2003	Landreville et al.
			2003/0030822	A1	2/2003	Finarov
			2003/0032000	A1	2/2003	Liu et al.
			2003/0040004	A1	2/2003	Hefti et al.
			2003/0057513	A1	3/2003	Leedy
			2003/0057957	A1	3/2003	McQuade et al.
			2003/0062915	A1	4/2003	Arnold et al.
			2003/0072549	A1	4/2003	Facer et al.
			2003/0088180	A1	5/2003	vanVeen et al.
			2003/0119057	A1	6/2003	Gascoyne et al.
			2003/0128086	A1	7/2003	Martin
			2003/0139662	A1	7/2003	Seidman
			2003/0139790	A1	7/2003	Ingle et al.
			2003/0155939	A1	8/2003	Lutz et al.
			2003/0170898	A1	9/2003	Gundersen et al.
			2003/0184332	A1	10/2003	Tomimatsu et al.
			2004/0015060	A1	1/2004	Samsouondar et al.
			2004/0021475	A1	2/2004	Ito et al.
			2004/0061514	A1	4/2004	Schwindt et al.
			2004/0066181	A1	4/2004	Thies
			2004/0069776	A1	4/2004	Fagrell et al.
			2004/0090223	A1	5/2004	Yonezawa
			2004/0095145	A1	5/2004	Boudiaf et al.
			2004/0095641	A1	5/2004	Russum et al.
			2004/0100276	A1	5/2004	Fanton
			2004/0100297	A1	5/2004	Tanioka et al.
			2004/0108847	A1	6/2004	Stoll et al.
			2004/0113640	A1	6/2004	Cooper et al.
			2004/0124861	A1	7/2004	Zaerpoor
			2004/0130787	A1	7/2004	Thome-Forster et al.
			2004/0132222	A1	7/2004	Hembree et al.
			2004/0134899	A1	7/2004	Hiramatsu et al.
			2004/0147034	A1	7/2004	Gore et al.
			2004/0162689	A1	8/2004	Jamneala et al.
			2004/0175294	A1	9/2004	Ellison et al.
			2004/0186382	A1	9/2004	Modell et al.
			2004/0193382	A1	9/2004	Adamian et al.
			2004/0197771	A1	10/2004	Powers et al.
			2004/0199350	A1	10/2004	Blackham et al.
			2004/0207072	A1	10/2004	Hiramatsu et al.
			2004/0207424	A1	10/2004	Hollman
6,927,598	B2	8/2005	Lee et al.			
6,930,498	B2	8/2005	Tervo et al.			
6,933,713	B2	8/2005	Cannon			
6,933,717	B1	8/2005	Dogaru et al.			
6,933,725	B2	8/2005	Lim et al.			
6,933,736	B2	8/2005	Kobayashi et al.			
6,933,737	B2	8/2005	Sugawara			
6,937,020	B2	8/2005	Munson et al.			
6,937,037	B2	8/2005	Eldridge et al.			
6,937,039	B2	8/2005	Barr et al.			
6,937,040	B2	8/2005	Maeda et al.			
6,937,042	B2	8/2005	Yoshida et al.			
6,937,045	B2	8/2005	Sinclair			
6,937,341	B1	8/2005	Woollam et al.			
6,940,264	B2	9/2005	Ryken, Jr. et al.			
6,940,283	B2	9/2005	McQueeney			
6,943,563	B2	9/2005	Martens			
6,943,571	B2	9/2005	Worledge			
6,943,574	B2	9/2005	Actmann et al.			
6,944,380	B1	9/2005	Hideo et al.			
6,946,375	B2	9/2005	Hattori et al.			
6,946,859	B2	9/2005	Karavakis et al.			
6,946,860	B2	9/2005	Cheng			
6,948,391	B2	9/2005	Brassell et al.			
6,948,981	B2	9/2005	Pade			
6,970,001	B2	11/2005	Chheda et al.			
6,987,483	B2	1/2006	Tran			
7,001,785	B1	2/2006	Chen			
7,002,133	B2	2/2006	Beausoleil et al.			
7,002,363	B2	2/2006	Mathieu			
7,002,364	B2	2/2006	Kang et al.			
7,003,184	B2	2/2006	Ronnekleiv et al.			
7,005,842	B2	2/2006	Fink et al.			
7,005,868	B2	2/2006	McTigue			
7,005,879	B1	2/2006	Robertazzi			
7,006,046	B2	2/2006	Aisenbrey			
7,007,380	B2	3/2006	Das et al.			
7,009,188	B2	3/2006	Wang			
7,009,383	B2	3/2006	Harwood et al.			
7,009,415	B2	3/2006	Kobayashi et al.			
7,011,531	B2	3/2006	Egitto et al.			
7,012,425	B2	3/2006	Shoji			
7,012,441	B2	3/2006	Chou et al.			
7,013,221	B1	3/2006	Friend et al.			
7,014,499	B2	3/2006	Yoon			
7,015,455	B2	3/2006	Mitsuoka et al.			
7,015,689	B2	3/2006	Kasajima et al.			
7,015,690	B2	3/2006	Wang et al.			
7,015,703	B2	3/2006	Hopkins et al.			
7,015,707	B2	3/2006	Cherian			
7,015,708	B2	3/2006	Beckous et al.			
7,015,709	B2	3/2006	Capps et al.			
7,015,710	B2	3/2006	Yoshida et al.			
7,015,711	B2	3/2006	Rothaug et al.			
7,019,541	B2	3/2006	Kittrell			
7,019,544	B1	3/2006	Jacobs et al.			
7,019,701	B2	3/2006	Ohno et al.			
7,020,360	B2	3/2006	Satomura et al.			
7,020,363	B2	3/2006	Johannessen			
7,022,976	B1	4/2006	Santana, Jr. et al.			
7,022,985	B2	4/2006	Knebel et al.			
7,023,225	B2	4/2006	Blackwood			
7,023,226	B2	4/2006	Okumura et al.			
7,023,231	B2	4/2006	Howland, Jr. et al.			
7,025,628	B2	4/2006	LaMeres et al.			
7,026,832	B2	4/2006	Chaya et al.			
7,026,833	B2	4/2006	Rincon et al.			
7,026,834	B2	4/2006	Hwang			
7,026,835	B2	4/2006	Farnworth et al.			
7,030,599	B2	4/2006	Douglas			
7,030,827	B2	4/2006	Mahler et al.			
7,032,307	B2	4/2006	Matsunaga et al.			
7,034,553	B2	4/2006	Gilboe			
7,035,738	B2	4/2006	Matsumoto et al.			
7,057,404	B2	6/2006	Gleason et al.			

(56)

## References Cited

## OTHER PUBLICATIONS

## U.S. PATENT DOCUMENTS

2004/0239338	A1	12/2004	Johnsson et al.
2004/0246004	A1	12/2004	Heuermann
2004/0251922	A1	12/2004	Martens et al.
2005/0024069	A1	2/2005	Hayden et al.
2005/0026276	A1	2/2005	Chou
2005/0030047	A1	2/2005	Adamian
2005/0054029	A1	3/2005	Tomimatsu et al.
2005/0062533	A1	3/2005	Vice
2005/0083130	A1	4/2005	Grilo
2005/0101846	A1	5/2005	Fine et al.
2005/0156675	A1	7/2005	Rohde et al.
2005/0164160	A1	7/2005	Gunter et al.
2005/0165316	A1	7/2005	Lowery et al.
2005/0168722	A1	8/2005	Forstner et al.
2005/0174191	A1	8/2005	Brunker et al.
2005/0178980	A1	8/2005	Skidmore et al.
2005/0195124	A1	9/2005	Puente Baliarda et al.
2005/0236587	A1	10/2005	Kodama et al.
2005/0237102	A1	10/2005	Tanaka
2006/0052075	A1	3/2006	Galivanche et al.
2006/0077649	A1	4/2006	Kumagai
2006/0155270	A1	7/2006	Hancock et al.
2006/0226864	A1	10/2006	Kramer
2007/0024506	A1	2/2007	Hardacker
2007/0030021	A1	2/2007	Cowan et al.

## FOREIGN PATENT DOCUMENTS

EP	0230348	7/1987
EP	0259163	3/1988
EP	0304868	3/1989
EP	0945736	9/1999
JP	56-88333	7/1981
JP	57-163035	10/1982
JP	62-11243	1/1987
JP	62-51235	3/1987
JP	62-107937	5/1987
JP	62-239050	10/1987
JP	63-108736	5/1988
JP	63-129640	6/1988
JP	1-165968	6/1989
JP	1-214038	8/1989
JP	1-219575	9/1989
JP	2-22836	1/1990
JP	2129393	5/1990
JP	2-191352	7/1990
JP	3-175367	7/1991
JP	3-196206	8/1991
JP	3-228348	10/1991
JP	4-130639	5/1992
JP	4-159043	6/1992
JP	4165361	6/1992
JP	4-206930	7/1992
JP	4-340248	11/1992
JP	5-82631	4/1993
JP	6-85044	3/1994
JP	6-102313	4/1994
JP	6-132709	5/1994
JP	7-12871	1/1995
JP	8-35987	2/1996
JP	8-261898	10/1996
JP	8-330401	12/1996
JP	11-4001	1/1999
JP	2000-329664	11/2000
JP	2001-124676	5/2001
JP	2002-203879	7/2002
SU	843040	6/1981
SU	1392603	4/1988
WO	WO 98/07040	2/1998
WO	WO 00/73905	12/2000
WO	WO 01/07207	2/2001
WO	WO 01/69656	9/2001

English-language abstract of German Patent No. DE 3637549, May 11, 1988.

English-language abstract of German Patent No. DE 19522774, Jan. 2, 1997.

English-language abstract of German Patent No. DE 10000324, Jul. 19, 2001.

English-language abstract of Japanese Patent No. JP 53-037077, Apr. 5, 1978.

English-language abstract of Japanese Patent No. JP 53-052354, May 12, 1978.

English-language abstract of Japanese Patent No. JP 55-115383, Sep. 5, 1980.

English-language abstract of Japanese Patent No. JP 56-007439, Jan. 26, 1981.

English-language abstract of Japanese Patent No. JP 57-075480, May 12, 1982.

English-language abstract of Japanese Patent No. JP 62-098634, May 8, 1987.

English-language abstract of Japanese Patent No. JP 63-143814, Jun. 16, 1988.

English-language abstract of Japanese Patent No. JP 63-318745, Dec. 27, 1988.

English-language abstract of Japanese Patent No. JP 1-296167, Nov. 29, 1989.

English-language abstract of Japanese Patent No. JP 2-124469, May 11, 1990.

English-language abstract of Japanese Patent No. JP 51-57790, Jun. 25, 1993.

English-language abstract of Japanese Patent No. JP 51-66893, Jul. 2, 1993.

English-language abstract of Japanese Patent No. JP 60-71425, Mar. 15, 1994.

English-language abstract of Japanese Patent No. JP 7-005078, Jan. 10, 1995.

English-language abstract of Japanese Patent No. JP 10-116866, May 6, 1998.

English-language abstract of Japanese Patent No. JP 11-023975, Jan. 29, 1999.

English-language abstract of Japanese Patent No. JP 2001-189285, Jul. 10, 2001.

English-language abstract of Japanese Patent No. JP 2001-189378, Jul. 10, 2001.

English-language abstract of Japanese Patent No. JP 2002-243502, Aug. 28, 2002.

English-language abstract of PCT Patent Application Publication No. WO 2004/065944, Aug. 5, 2004.

English-language abstract of PCT Patent Application Publication No. WO 2004/079299, Sep. 16, 2004.

English-language abstract of PCT Patent Application Publication No. WO 2005/062025, Jul. 7, 2005.

Aebersold, Ruedi, et al., "insight review articles, Mass spectrometry-based proteomics," *Nature*, vol. 422, Mar. 13, 2003, pp. 198-207.

Afsar, Mohammed Nurul, et al., "The Measurement of the Properties of Materials," *Proceedings of the IEEE*, vol. 74, No. 1, Jan. 1986, pp. 183-199.

Basu, Saswata, et al., "An SOLR Calibration for Accurate Measurement of Orthogonal On-Wafer DUTS," 1997 IEEE MTT-S Digest, pp. 1335-1338.

Boguski, Mark S., et al., "Biomedical informatics for proteomics," insight: review article, *Nature*, vol. 422, pp. 233-237, Mar. 13, 2003; doi:10.1038/nature01515.

Cascade Microtech, Inc., "Probe Heads, Care and cleaning of coaxial input microwave probes," *Microwave Probe Care and Cleaning Instruction Manual*, 1990, 28 pages.

Cascade Microtech, Inc., "Information Sheet for Pyramid Probe," 5 pages, 2001.

Fink, Donald G., et al., "Bridge Circuits, Detectors, and Amplifiers, Principles of Bridge Measurements," *Electronics Engineers' Handbook*, First Edition, McGraw-Hill Book Company, New York, 1975, pp. 17-22-17-27.

(56)

**References Cited**

## OTHER PUBLICATIONS

- Grober, Robert D., et al., "Optical antenna: Towards a unity efficiency near-field optical probe," *Appl. Phys. Lett.* 70 (11), Mar. 17, 1997, American Institute of Physics, 1997, pp. 1354-1356.
- Hanash, Sam, "insight review articles, Disease proteomics," *Nature*, vol. 422, Mar. 13, 2003, pp. 226-232.
- Hayden, Leonard, "A Multi-Line TRL Calibration," Feb. 2, 1994, 5 pages.
- Kim, Yong-Dae, et al., "Fabrication of a Silicon Micro-Probe for Vertical Probe Card Application," *Japanese Journal of Applied Physics*, vol. 37, pp. 7070-7073, 1998.
- Kraszewski, Andrzej W., et al., "Use of a Microwave Cavity for Sensing Dielectric Properties of Arbitrarily Shaped Biological Objects," *IEEE Transactions on Microwave Theory and Techniques*, vol. 38, No. 7, Jul. 1990, pp. 858-863.
- Liang, Qingqing, et al., "Accurate ac Transistor Characterization to 110 GHz Using a New Four-port Self-Calibrated Extraction Technique," *IEEE, 2004 Topical Meeting on Silicon Monolithic Integrated Circuits in RF Systems*, pp. 282-285.
- Marte, Barbara, Senior Editor, "Nature Insight Proteomics," *Nature*, vol. 422, Mar. 13, 2003, pp. 191-194.
- Martens, J., "Multiport SOLR Calibrations: Performance and an Analysis of Some Standards Dependencies," *ARFTG Microwave Measurements Conference*, Dec. 4-5, 2003, pp. 205-213.
- Phizicky, Eric, et al., "insight: review article, Protein analysis on a proteomic scale," *Nature*, vol. 422, pp. 208-215, Mar. 13, 2003; doi: 10.1038/nature01512.
- Purroy, Francesc, et al., "New Theoretical Analysis of the LRRM Calibration Technique for Vector Network Analyzers," *IEEE Transactions on Instrumentation and Measurement*, vol. 50, No. 5, Oct. 2001, pp. 1307-1313.
- Risacher, Christophe, et al., "Waveguide-to-Microstrip Transition With Integrated Bias-T," *IEEE Microwave and Wireless Components Letters*, vol. 13, No. 7, Jul. 2003, pp. 262-264.
- Sali, Andrej, et al., "insight: review article, From words to literature in structural proteomics," *Nature*, vol. 422, pp. 216-225, Mar. 13, 2003; doi: 10.1038/nature01513.
- Seguinot, Christophe, et al., "Multimode TRL—A New Concept in Microwave Measurements: Theory and Experimental Verification," *IEEE Transactions on Microwave Theory and Techniques*, vol. 46, No. 5, May 1998, pp. 536-542.
- Sharma, Arvind Kumar, "Tunable Waveguide-to-Microstrip Transition for Millimeter-Wave Applications," J-27, RCA Laboratories, David Sarnoff Research Center, Princeton, NJ, 1987 *IEEE MTT-S Digest*, pp. 353-356.
- Sohn, L. L., et al., "Capacitance cytometry: Measuring biological cells one by one," *PNAS* Sep. 26, 2000, vol. 97, No. 20, pp. 10687-10690, [www.pnas.org](http://www.pnas.org).
- Tyers, Mike, et al., "insight overview, From genomics to proteomics," *Nature*, vol. 422, Mar. 13, 2003, pp. 193-197.
- Venkatesh, M. S., et al., "An overview of dielectric properties measuring techniques," *Canadian Biosystems Engineering*, vol. 47, 2005, pp. 7.15-7.30.
- Xu, Deming, et al., "Measurement of the Dielectric Properties of Biological Substances Using an Improved Open-Ended Coaxial Line Resonator Method," *IEEE Transactions on Microwave Theory and Techniques*, vol. MTT-35, No. 12, Dec. 1987, pp. 1424-1428.






FIG. 1






FIG. 4





FIG. 5



80 ↗

FIG. 6






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14






FIG. 17




FIG. 18




FIG. 19

**METHOD OF ELECTRICALLY  
CONTACTING A BOND PAD OF A DEVICE  
UNDER TEST WITH A PROBE**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a continuation patent application that claims priority to U.S. patent application Ser. No. 13/854,725, which was filed on Apr. 1, 2013, and which claims priority to U.S. Pat. No. 8,410,806, which issued on Apr. 2, 2013, and which claims priority to U.S. Provisional Patent Application Ser. No. 61/199,910, which was filed on Nov. 21, 2008. The entire disclosures of the above-identified patent and patent applications are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

The present invention relates to probe assemblies of the type commonly used for testing integrated circuits (ICs) that are fabricated on a wafer or substrate.

The trend in electronic production, particularly in integrated circuit technology, has been toward fabricating larger numbers of discrete circuit elements with higher operating frequencies and smaller geometries on a single substrate or “wafer.” After fabrication, the wafer is divided into a number of rectangular-shaped chips or “dies” where each die presents a rectangular or other regular arrangement of metallic bond or contact pads through which connections are made for the inputs and outputs of the electrical circuit on the die. Although each die is eventually packaged separately, for efficiency sake, testing of the circuits formed on the wafer is preferably performed while the dies are still joined together on the wafer. One typical procedure is to support the wafer on a flat stage or “chuck” and to move the wafer in X, Y and Z directions relative to the head of a probing assembly so that contacts on the probing assembly move relative to the surface of the wafer for consecutive engagement with the contact pads of one or more of a plurality of dies or test structures on the wafer. Respective signal, power and ground conductors that interconnect the test instrumentation with the contacts on the probing assembly enable each circuit on the wafer to be sequentially connected to the instrumentation and tested.

Gleason et al., U.S. Pat. No. 5,914,613, discloses a membrane probing system for use in a probe station. The membrane probing system comprises a probe head and a membrane probing assembly. The probe head includes an interface board, a multi-layer printed circuit board that facilitates interconnection of the membrane probing assembly and the test instrumentation supplying power and signals to and receiving signals from the electrical circuit being tested, the device-under test (DUT). The power and signals are transmitted over one or more conductors that are conductively interconnected with respective data/signal traces on the interface board. The data/signal traces on the interface board are conductively connected to respective conductive traces on the surface of the membrane assembly. A metallic layer below the surface of the interface board provides a ground plane for the interface board and a ground reference for the power and lower frequency signals.

Typically, higher frequency signals; commonly in the radio or microwave frequency ranges, collectively referred herein to as RF signals; are communicated between the test instrumentation and the membrane probing system with coaxial cable. The coaxial cable is connected to an adapter

that is secured to the interface board. A second portion of coaxial cable, conductively interconnected with the first portion in the adapter, is connected to one or more conductive traces on the surface of the interface board. Typically, the end of the second portion of coaxial cable is cut at an angle and the conductors of the cable are connected to respective traces on the interface board to transition the signal path from the coaxial cable to a co-planar waveguide. For example, the center conductor of the coaxial cable may be soldered to a trace on the interface board while the outer conductor of the cable, connected to a ground potential, is soldered to a pair of traces that are respectively spaced apart to either side of the trace to which the center conductor is connected transitioning the signal path from coaxial cable to a ground-signal-ground (GSG) co-planar waveguide on the interface board. The traces on the interface board are conductively engaged with respective, corresponding traces on the lower surface of the membrane assembly extending the co-planar waveguide to the contacts on the membrane. The impedance of the transition signal path from the coaxial cable to the coplanar waveguide on the membrane is, ideally, optimized, with a typical value of 50 ohms ( $\Omega$ ). However, inconsistencies in connections with the ground plane of the interface board may cause the impedance of a particular signal path to vary from the desired matched impedance producing a reflection of the RF signals that are absorbed by other structures resulting in erratic performance of the probing system.

The membrane of the probing system is supported by a support element that is made of an incompressible material, such as a hard polymer, and detachably affixed to the upper surface of the interface board. The support element includes a forward support or plunger portion that protrudes through a central aperture in the interface board to project below the interface board. The forward support has the shape of a truncated pyramid with a flat forward support surface. The membrane assembly which is also detachably secured to the interface board by the support element includes a center portion that extends over and is separated from the forward support surface of the support element by an intervening elastomeric layer. The flexible membrane assembly comprises one or more plies of insulating sheeting, such as polyimide film. Flexible conductive layers or strips are provided between or on these layers to form power/data/signal traces that interconnect with the traces on the interface board at one end. The second end of the traces on the membrane terminate in conductive connections to respective contacts which are arranged on the lower surface of the portion of the membrane extending over the forward support. The contacts are arranged in a pattern suitable for contacting the bond pads of the DUT when the chuck is moved to bring the contacts of the probe assembly into pressing engagement with the bond pads.

The contacts of the probing system comprise a beam which is affixed to the lower surface of the membrane assembly and which is conductively interconnected with the appropriate trace on the surface of the membrane. A contact bump or tip for engaging a bond pad of the DUT is affixed to one end of the beam. When the contact bump is pressed against the bond pad of the DUT, the membrane assembly is deflected, compressing a portion of the elastomeric layer proximate the end of the beam to which the contact bump is affixed. The compliance of the elastomeric layer enables relative displacement of the respective contact bumps and facilitates simultaneous engagement with a plurality of bond pads that may have respective contact surfaces that lie in different planes. The resilience of the elastomeric layer

controls the force exerted by the contacts and returns the contacts to the at-rest position when the probe is withdrawn from pressing engagement with the DUT.

The bond pads on DUTs are subject to the rapid development of a layer of oxidation which can electrically insulate the bond pad from the contact. To improve the conductivity of the bond pad/contact interface, the contacts of membrane probes are commonly pressed into the bond pad with sufficient force to penetrate the oxide layer. While penetration of the oxide layer improves conductivity, excessive force can damage the bond pad. With the membrane probe disclosed by Gleason et al, the force of contact with the bond pad is exerted at one end of the beam and the off-center loading on the beam causes the beam to rotate as the portion elastomeric layer adjacent the deflected end of the beam is compressed. The rotation of the beam causes the surface of the contact bump to translate across the bond pad surface and abrade or scrub the oxide coating on the surface improving conductivity between the bond pad and the contact.

However, the conductors within the membrane assembly and attached to the contacts can be broken by excessive displacement of the contacts or may fail from fatigue due to repeated bending when the contacts are displaced during probing. In addition, bond pad material may build up in the area of the contacts of wafer probing assemblies requiring frequent cleaning and, eventual replacement due to wear. While the membrane assembly is detachable from the interface card for cleaning or replacement, the membrane assembly is complex and fairly expensive to replace.

What is desired, therefore, is a probing apparatus having improved impedance characteristics, longer service life and less expensive contacts that can be quickly replaced.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing an exemplary membrane probing assembly bolted to a probe head and a wafer supported on a chuck in suitable position for probing by this assembly.

FIG. 2 is a bottom plan view showing various parts of the probing assembly of FIG. 1, including a support element and flexible membrane assembly, and a fragmentary view of a probe card having power, and data/signal lines connected with corresponding lines on the membrane assembly.

FIG. 3 is a side elevation view of the membrane probing assembly of FIG. 1 where a portion of the membrane assembly has been cut away to expose hidden portions of the support element.

FIG. 4 is a schematic sectional elevation view of an exemplary probing assembly.

FIG. 5 is a top plan view of an exemplary support element.

FIG. 6 is a bottom plan view of an exemplary coupon.

FIG. 7 is a sectional view of a membrane and coupon taken along line 7-7 of FIG. 6.

FIG. 8 is a sectional view of a membrane and coupon taken along line 8-8 of FIG. 6.

FIG. 9 is a sectional view of a membrane and coupon illustrating connection to a conductor extending through the forward support.

FIG. 10 is a sectional view of a membrane and coupon illustrating an alternative method of connecting a contact and a membrane supported trace.

FIG. 11 is a sectional view of a membrane and coupon illustrating an alternative method of connecting a contact and a membrane supported trace.

FIG. 12 is a sectional view of a coupon useful with a space transformer of a needle card-type probing apparatus.

FIG. 13 is a sectional view of additional embodiments of contacts for a coupon useful with a membrane probing device.

FIG. 14 is a bottom plan view of a multi-layered tile portion of a coupon.

FIG. 15 is a sectional view of the multi-layered tile of FIG. 14 taken along line 15-15.

FIG. 16 is a sectional view of the multi-layered tile of FIG. 14 taken along line 16-16.

FIG. 17 is a top view of a portion of an exemplary interface board and an impedance optimized co-axial cable to co-planar waveguide interface.

FIG. 18 is a sectional view of the exemplary co-axial cable to co-planar waveguide interface taken along line 18-18 of FIG. 17.

FIG. 19 is a top view of an alternative impedance optimized co-axial cable to co-planar waveguide interface.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring in detail to the drawings where similar parts are identified by like reference numerals, and, more particularly to FIGS. 1 and 4, a probe head 40 for mounting a membrane probing assembly 42 is illustrated. In order to measure the electrical performance of the electrical circuit or device-under-test (DUT) of a particular die area 44 included on the silicon wafer 46, input and output ports of the test instrumentation 49 are communicatively connected to contacts 81 included on the lower portion of the membrane probing assembly and the chuck 51 which supports the wafer is moved in mutually perpendicular X, Y, and Z directions in order to bring bond pads of the DUT into pressing engagement with the probe's contacts.

The probe head 40 includes an interface board 52 on which traces 48 and shielded transmission lines are arranged for communicating data, signals and power between the test instrumentation and the DUT. Typically, high frequency signals are communicated between the test instrumentation and the probe with co-axial cables 53 which connect the instrumentation to co-axial cable adapters 55 on the interface board. The shielded transmission lines, typically comprising second lengths of co-axial cable 50 connect the adapters to metallic traces 87 on the interface board to transition the communication path from the coaxial cable to a co-planar waveguide. Referring also to FIG. 2, contact portions 86 that terminate conductors on surface of the membrane are arranged to overlap and conductively interconnect with the traces on the interface board extending the co-planar waveguide from the interface board to the lower surface of the membrane assembly in the vicinity of the contacts and, eventually, to appropriate contacts 81 of the probing apparatus.

Referring also to FIG. 3, the membrane probing assembly 42 includes a support element 54 formed of incompressible material such as a transparent, hard polymer. This element is detachably connected to the upper side of the interface board by means of four Allen screws 56 and corresponding nuts 58 (each screw passes through a respective attachment arm 60 of the support element, and a separate backing element 62 that evenly distributes the clamping pressure of the screws over the entire back side of the supporting element). This detachable connection enables different membrane assemblies having different arrangements of conductors to be quickly substituted for each other as needed for probing

different devices. A transparent window **63** enables an operator of the probing apparatus to view the portion of the wafer in the vicinity of the probe contacts **81**.

Referring to also FIG. **5**, the support element **54** includes a rearward base portion **64** to which the attachment arms **60** are integrally joined. Also included on the support element **54** is a forward support or plunger **66** that projects outwardly from the flat base portion. This forward support has angled sides **68** that converge toward a flat support surface **70** so as to give the forward support the shape of a truncated pyramid. Referring also to FIG. **2**, a flexible membrane assembly **72** is attached to the support after being aligned by means of alignment pins **74** included on the base portion. This flexible membrane assembly is formed by one or more plies of insulating sheeting such as KAPTON™ polyimide film sold by E. I. Du Pont de Nemours or other polyimide film, and flexible conductive layers or strips are provided on the surfaces of the plies or between the plies to form various conductors connecting the probe's contacts with the traces and shielded transmission lines on the interface board.

When the support element **54** is mounted on the upper side of the interface board **52** as shown in FIG. **3**, the forward support **66** protrudes through a central opening **78** in the interface board so as to present the contacts **81** which are arranged on a coupon **80** that is attached to the surface of the membrane assembly **72** in a position suitable for pressing engagement with the pads of the DUT. Referring to FIG. **2**, the membrane assembly includes radially extending arm segments **82** that are separated by inwardly curving edges **84** that give the assembly the shape of a formee cross, and these segments extend in an inclined manner along the angled sides **68** thereby clearing any upright components surrounding the pads. A series of contact pads **86** terminate the conductors of the membrane so that when the support element is mounted, these pads electrically engage corresponding termination pads provided on the upper side of the interface board so that the traces **48** and shielded transmission lines **50** on the interface board are conductively connected to the contacts **81** on the coupon **80**.

The exemplary membrane probing assembly **42** is capable of probing a dense arrangement of contact pads over a large number of contact cycles in a manner that ensures reliable electrical connection between the contacts and pads during each cycle despite oxide buildup on the pads. This capability is a function of the construction and interconnection of the support element **54**, the flexible membrane assembly **72** and the coupon **80**. In particular, the membrane probing assembly is so constructed and connected to the support element to enable the contacts to engage a plurality of bond pads on the DUT even if the contact surfaces of the pads are not co-planar. Moreover, the contacts on the membrane assembly preferably wipe or scrub, in a locally controlled manner, laterally across the pads when brought into pressing engagement with the pads. Alternatively, the contacts may be constructed to enable the tips of the contacts to penetrate an oxide coating on the surfaces of the pads with substantially vertical motion. In the event that the contacts require replacement due to, for examples, a built up of pad material, wear, or a change in the arrangement of the pads to be probed, the contacts can be easily replaced by removing and replacing the coupon without the added expense of replacing the membrane assembly.

Referring also to FIGS. **7** and **8**, for ease of illustration, an exemplary flexible membrane assembly **72** (indicated by a bracket) comprises one or more traces **76** affixed to an outer surface of a ply **92** comprising a dielectric material which is separated by a backplane conductive layer **94** from a second

dielectric ply **96**. However, additional dielectric plies and conductive layers can be used in accordance with conventional layering techniques. Preferably, the conductors of the backplane layer and the other traces are fabricated using a photolithographic process to enable precise control of the dimensions of the conductors. The membrane assembly is secured along its edges and extends over the flat support surface **70** of the plunger **66**. Typically, the plurality of traces **76** affixed to the outer surface of, the membrane assembly provide communication paths for conducting data/signals and/or power from the conductors at the interface board to the surface of the membrane proximate the forward surface of the plunger. In conjunction with the backplane conductive layer, the conductive traces on the outer surface of the membrane assembly comprise controlled impedance communication structures connecting the interface board to the surface of the membrane in the vicinity of the forward surface of the plunger. The backplane conductive layer **94** may include portions defining one or more apertures which, in turn, define conductive strips of the backplane layer that are located proximate the various traces **76** on the outer surface of the membrane assembly. Filter capacitors **83** may be affixed to the membrane to provide frequency dependent interconnection between the conductive backplane layer and the power and signal conductors.

FIG. **8** shows an enlarged plan view of the lower surface of an exemplary coupon **80** that is attachable to the lower surface of the membrane **72** in area of the forward support surface **70** of the plunger. Typically, the coupon is attached to the surface of the membrane by an adhesive **95** that enables removal of the coupon by breaking the adhesive bond. The adhesive may be applied proximate the periphery of the coupon, at particular locations on the surface or as layer that substantially covers the surface of the coupon but which is displaced from the points of electrical contact by pressure applied to the lower surface of the coupon. The coupon includes a plurality of contacts **81** which in the illustrated exemplary embodiment are arranged in a square pattern suitable for engaging a square-like arrangement of bond pads. Referring also to FIGS. **7** and **8**, which represent sectional views taken along lines **7-7** and **8-8**, respectively, in FIG. **6**, the coupon comprises an elastomeric layer **98** that is substantially co-extensive with the exposed surface of the portion of the membrane that covers the forward support surface **70** of the plunger. The elastomeric layer can be formed by a silicon rubber compound such as ELMER'S STICK-ALL™ silicon rubber made by the Borden Company or Sylgard 182 silicon rubber from Dow Corning Corporation. Each contact comprises a relatively thick rigid elongate beam **100**, preferably 150 to 250 microns long, having an upper surface that is affixed to the elastomeric layer. At one end of the beam a contact tip **102** having the general shape of a truncated pyramid is formed. For wear resistance, the contact tip may include a tip end portion **104** comprising an alloy of rhodium and nickel. Proximate the end of the beam opposite of the contact tip and on the opposite side of the beam, a post portion **106** projects in the direction opposite of the contact tip. The post **106** projects through the elastomeric layer and, preferably, projects proud of the upper surface of the coupon. As illustrated in FIG. **7**, the posts of selected contacts are arranged for conductive contact with one of the traces **76** on the outer surface of the membrane. As illustrated in FIG. **8**, the posts of other contacts are arranged for conductive contact with contact buttons **108** projecting from the backplane conductive layer **94** through the lower ply **92** of the membrane assembly.

Additional dielectric layers, for example layer **112**, may be affixed to the lower surface of the elastic layer.

As indicated in FIG. 7, when an exemplary contact **102** is brought into pressing engagement with a respective bond pad **110**, the contact force is exerted upward at the end of the beam to which the contact tip is affixed. However, the opposite end of the beam is constrained by the contact between the post **106** and the trace which is supported by the substantially incompressible membrane. The resulting off-center force on the rigid beam **100** causes the beam to pivot or tilt against the elastic recovery force exerted on the beam by the elastically supported lower surface of elastomeric layer **98**. This tilting motion is localized in the sense that the portion of the beam proximate the tip moves a greater distance toward the forward support surface **70** than a rearward portion of the same beam. The effect is such as to cause the tip of the contact to translate across the pad in a lateral scrubbing movement with a solid-line and a dashed-line representing the beginning **102** and ending positions **102'**, respectively, of the contact tip on the pad **110** which, after displacement relative to the coupon, will be in position **110'**. In this fashion, the insulating oxide buildup on the pad is abraded so as to provide reliable probe contact-to-bond pad electrical connections. On the other hand, the movement of the contact does not cause flexing of the trace or other conductor of the membrane which substantially reducing fatigue of the conductors and extending the service life of the membrane.

Referring to FIG. 9, the power transmissible on the traces deposited on the plies of the flexible membrane is limited by the cross-section of the traces. As a result, extremely wide traces or large numbers of traces may be required to provide sufficient power to operate the electrical circuits of a OUT or a plurality of DUTs. To increase the power available for testing single or multiple DUTs and reduce the number and size of traces on the membrane, the probing assembly **42** includes a power conductor **114** that is routed through the support **66** to a contact button **116** that extends through the lower wall of the forward support surface **70**. The contact button conductively engages a buss **118**, which may comprise a grid, on the upper surface of the membrane **72**. At selected locations, the buss is extended downward to the lower surface of the membrane through apertures **119** in the other layers of the membrane. Selected contacts **81** include post portions that engage the buss extensions to provide power to the appropriate bond pad(s) of the DUT(s). The buss can have a substantially greater cross-section than the other conductors on the membrane because it is not located in an area of the membrane where flexibility is required.

The resilient elastomeric layer **98** of the coupon, backed by the incompressible support surface **70** and the substantially incompressible membrane **72**, exerts a recovery force on each tilting beam contact and thus each contact tip to maintain an adequate level of contact tip-to-bond pad pressure during scrubbing. At the same time, the elastomeric layer accommodates minor height variations between the respective contacts and pads. Thus, when a relatively shorter contact is situated between an immediately adjacent pair of relatively taller contacts and these taller contacts are brought into engagement with their respective pads, deformation of the elastomeric layer enables the shorter contact to be brought into engagement with its pad after only a small amount of further over travel by the longer contact tips. Similarly, the compressibility of the elastomeric layer enables the contact tips to be brought into proper pressing engagement with a plurality of bond pads having surfaces that are not co-planar.

Referring to FIGS. **10** and **11**, alternatively, the contacts **120** may comprise an elongate beam portion **122** affixed to the elastically supported lower surface of the elastomer layer **98**. The contact tip portion **102** is affixed proximate one end of the beam portion. When the tip is brought into pressing engagement with the bond pad of the DUT, the lower surface of the elastomer layer is displaced proximate the end of the beam to which the tip is affixed, but the elastic force exerted at other end of the beam causes the beam to tilt facilitating the scrubbing action when the tip is pressed toward the bond pad of the DUT. The contact **120** is conductively connected to one of the traces **76** or the backplane layer **94** by a flexible conductive pigtail **124**. The conductive pigtail may terminate on the surface of the elastomeric layer at a location suitable for contact with a trace **76** or a contact button **108** or may be conductively connected with a contact pad **126** suitably located on the surface of the coupon for contact with the appropriate trace or contact button.

FIG. **12** illustrates a coupon **150** (indicated by a bracket) having a plurality of elastomer suspended contacts that is suitable for use with components of a needle card-type probe head enabling the needle card-type probing assembly to be converted to a lower inductance probing assembly with elastically suspended contacts by removing the needle card-type probe head and replacing it with the coupon **150** that interfaces with a space transformer **152** (indicated with a bracket) of the needle card-type probing apparatus. In the schematic cross-sectional view of FIG. **12**, the size of certain elements and components are exaggerated, for illustrative clarity. The interface board **154** of the needle card-type probing assembly is generally a conventional circuit board substrate having a plurality of terminals **156** (two of many shown) disposed on a surface thereof. The terminals provide an interface for wires **158** that connect instrumentation (not shown) to the probing assembly. As illustrated, the wires may be connected to terminals on one side of the interface board which are, in turn, connected by conductive vias **160** to terminals **162** or traces on the opposing side of the interface board. Additional components (not shown), such as active and passive electronic components, connectors, and the like, may be mounted on the interface board and connected to additional terminals. The interface board is typically round and commonly has a diameter on the order of 12 inches. The terminals **156**, **162** on the interface board are often arranged at a 100 mil pitch or separation distance.

While some probing assemblies do not utilize an interposer, the exemplary probing assembly of FIG. **12** includes an interposer **164** (indicated by a bracket) disposed between the interface board and the space transformer. An interposer comprises interconnected electrical contacts disposed on opposing sides of a substrate so that components on opposing sides of the substrate can be conductively interconnected. An interposer is often used in a probing assembly to facilitate reliable conductive connection between the terminals of an interface board and the terminals of a space transformer. The interposer also aids in accommodating differences in thermal expansion of the interface board and the space transformer. The interposer **164** comprises a substrate **166** and a plurality of fuzz buttons **168** (two are shown) that protrude through holes in the substrate. The fuzz buttons each comprise a fine wire that is compressed into a small cylindrical shape to produce an electrically conductive, elastic wire mass. As a general proposition, the fuzz buttons are arranged at a pitch which matches that of the terminals **162** of the interface board. One end of each of the conductive fuzz buttons is in contact with a terminal on the interface board while the second end of the fuzz button is in

contact with a terminal **170** on the space transformer. The elastic fuzz buttons are compressed providing compliance to accommodate variations in the separation distances between of the various terminals of the interface board and the space transformer and exerting pressure on the contacts to promote good conductivity.

The fuzz buttons protruding through the substrate of the interposer **164** contact conductive terminals **170** on one side of the space transformer **152**. The space transformer **154** (indicated by a bracket) comprises a suitably circuited substrate **172**, such as a multi-layer ceramic substrate having a plurality of terminals (contact areas, pads) **170** (two of many shown) disposed on the surface adjacent to the interposer and a plurality of terminals **174** (contact areas, pads) (two of many shown) disposed on the opposing surface. In the exemplary probing assembly, the contact pads adjacent the interposer are disposed at the pitch of the terminals of the interface board, and the contact pads **174** arranged on the opposing surface of the space transformer are disposed at a finer pitch corresponding to the pitch and arrangement of the needle-type probes included in the needle card with which the space transformer was intended to interface. While the pitch of the terminals of the interface board is commonly approximately 100 mil, the pitch of needle-type probes can be as fine as approximately 125  $\mu\text{m}$ . Conductive traces **176** in the multilayer substrate of the space transformer re-route the electrical connections from the finely pitched pattern required to interface with the probe head to the more coarsely pitched pattern that is obtainable with a printed circuit board, such as the interface board.

The various elements of the probing assembly are stacked and any suitable mechanism for stacking these components and ensuring reliable electrical contacts may be employed. As illustrated, the probing assembly includes a rigid front mounting plate **180** arranged on one side of the interface board. A stand-off **182** with a central aperture to receive the space transformer is attached to the front mounting plate. A mounting ring **184** which is preferably made of a springy material such as phosphor bronze and which may have a pattern of springy tabs extending therefrom, is attachable by screws **186** to the stand-off with the space transformer captured between the mounting ring and the stand-off.

A coupon **150** (indicated by a bracket) comprising an elastomeric layer **190** and a plurality of electrically conductive contacts is affixed to the face of the space transformer, preferably with an adhesive **191**. The contacts, for example exemplary contact **192**, may comprise, generally, a relatively thick, elongate, rigid beam portion **194** with a post portion **196** proximate one end of the beam and a contact tip **102** projecting in the opposite direction from the opposite side of the beam proximate the second end of the beam. Although other shapes and materials may be utilized, the contact tip preferably has the general shape of a truncated pyramid and the distal end of the contact tip may be coated with a layer of nickel and/or rhodium to provide good electrical conductivity and wear resistant when the contact tip is repeatedly pressed into engagement with the bond pads of DUTs. The post **196** has a rounded end distal of the beam that abuts a terminal **174** of the space transformer **152**. The rounded end facilitates movable contact between the post and the terminal when the contact tip is displaced upward by interaction with a bond pad. Additional dielectric layer(s) **198** may be affixed to the lower surface of the elastomeric layer.

The contact **200** exemplifies a second type of contact that may included in the coupon. The contact **200** comprises a contact tip portion **202** which, preferably, has the shape of a

truncated pyramid or cone and a body **204** with, preferably, a square or circular cross-section. A shoulder **206** may project from the body adjacent to the bottom surface of the elastomeric layer. The contact is conductively connected to the upper surface of the coupon **150** by a pig-tail **204** that is conductively attached to the body of the contact at one end and has a second end exposed at the upper surface of the coupon. The exposed portion of the pig-tail is arranged to contact a terminal **174** of the space transformer when the coupon is affixed to the surface of the transformer. Alternatively, a conductive connection between the contact and the terminal of the space transformer may incorporate a fuzz button, similar to fuzz button **168**, that is embedded in the elastomeric layer with one end exposed at the surface of the coupon and the second end abutting the contact.

For better conductivity between a bond pad and the contact, the tip **202** of the contact **200** is intended to be pushed through the oxide layer that may develop on the surface of a bond pad and the elasticity of the elastomeric layer may be varied to aid penetration of the oxide layer. For example, the body **204** of the contact may be extended so as to directly contact the terminal of the space transformer, eliminating the need for the pigtail and enabling vertical movement of the contact in response to pressure from the pad to be limited to the deflection of the relatively rigid space transformer while the resiliency of the elastomeric layer may enable the contact to tilt if the surface of the pad is not parallel to the end surface of the tip of the contact. On the other hand, the elastomeric layer **190** may comprise a single layer with graduated resiliency or a plurality of sub-layers with differing resiliency to enable controlled vertical movement of the contact in response to the application of force at the tip of the contact. The coupon provides an economical way of converting a needle-type probing apparatus to a probing apparatus with much lower inductance. The relatively long, closely spaced, needle-like probes typically exhibit a single path inductance of 1-2 nano-Henrys (nH) which is sufficient to substantially distort high frequency signals and limit the usefulness of needle-type probes for testing devices with high frequency signals. On the other hand, single path inductance of 0.2 nH has been demonstrated with elastically suspended probes of membrane-type probing apparatuses.

Referring to FIG. 13, surface penetrating contacts **252**, **254** can also be utilized in a coupon **250** (indicated by a bracket) suitable for use with a membrane probing apparatus. The contact **254** may be rigidly supported by the support **66** and the substantially incompressible membrane assembly **72**. As illustrated, the body of the contact is extended through the elastomeric layer **98** so that it abuts the contact button **108** of the backplane layer **94**. The abutting end of the contact is rounded enabling tilting of the contact, by compressing the elastomer surrounding the contact's body, to aid in aligning the end of the contact with a non-co-planar pad surface.

On the other hand, the body of the contact **252** terminates in the elastomeric layer and the contact can exhibit elastic behavior as determined by the properties of the elastomer layer. The elastomeric layer **98** may comprise sub-layers **98A** and **98B**, each having different elastic properties. The elasticity of the contact during vertical displacement may be determined by the properties of the sub-layer **98A** which acts on a portion of the surface area of the upper end of the contact and the properties of sub-layer **98B** which acts on the upper surface of a contact flange **253**. A fuzz button **256** conductively connects the contact **252** with the trace **76**.

Referring to FIGS. 14 and 15, a coupon 300 for use with a membrane probe or a space transformer may comprise a plurality of coupons or tiles 300a, 300b, 300c, 300d, each independently detachably affixed to a membrane or a space transformer enabling damaged or worn portions of the coupon to be independently replaced or portions of the coupon to include differing arrangements of contacts 81. Flexibility in arranging contacts and conductive connections to membranes and space transformers can be facilitated by layering the conductive and non-conductive elements of the coupon. For example, the tile 300c includes layered circuitry enabling conductive connection of thirteen finely pitched contact tips to a space transformer or membrane having six coarsely pitched contact pads enabling a typically less costly, more coarsely pitched space transformer or membrane to interface with the finely pitched contacts useful for probing small DUTs. The tile includes six grounded contact tips 302 including ground contact tips spaced to each side of a pair of high frequency signal contact tips 304 comprising the terminations of the conductors of a pair of ground-signal-ground (GSG) co-planar waveguides 310 (collectively indicated by a bracket). In addition, the exemplary tile includes a pair of contact tips 308 that are arranged to conduct DC power to a DUT and a pair of contact tips 306 that are arranged to conduct a lower frequency signal to the DUT. The contacts tips of the coupon are affixed to an elastically supported lower surface 314 of an elastomer layer 312. The coupon is affixed the lower surface to a space transformer 320 by adhesive 322.

The ground contact tips 302 are conductively connected to a conductive backplane layer 318 deposited between a pair of dielectric layers 320 and 321. The elastomeric layer is affixed to lower surface of the dielectric layer 321. The backplane layer extends over the area of the coupon that is occupied by the contact tips 302-308. The backplane layer is conductively connected to a suitable conductor in the space transformer by a contact button 324 on the upper surface of the coupon which is connected to the backplane layer by a via 326. The contact button 324 is arranged to engage a corresponding contact button on the lower surface of the space transformer. The contact tips 302 include post portions 327 in contact with backplane or a pigtail 328 that conductively connects the side of the beam portion of the contact tip and the back plane layer.

High frequency signals are transmitted between the test instrument and the DUT through the high frequency contact tips 304. Each of the high frequency contact tips is connected to one of a pair of contact buttons 330 on the upper surface of the coupon by a via 332 and a high frequency signal trace 324 that is deposited between the upper surface of the elastomeric layer 312 and the dielectric layer 321 which separates the high frequency trace from the backplane layer.

The contact tips 308 facilitating the transmission of DC power to the DUT are connected to an appropriate conductor 334 in the space transformer through a contact button 336 on the upper surface of the coupon. A trace 338, including portions that are conductively affixed to the lower surfaces of the beam portions of the power contact tips 308, is affixed to the lower surface of a dielectric layer 340 that is, in turn, affixed to the lower surface of the elastomer layer. A via 342 connects the power trace on the lower surface of the coupon to a contact button 344 on the upper surface of the coupon.

The coupon 300c also enables communication of a lower frequency AC signal to the DUT through contact tips 306 which include posts conductively engaging a lower frequency signal layer 346. The lower frequency signal is

conducted from the lower frequency signal layer to the space transformer through a via 348 connecting the lower frequency signal layer with a low frequency signal contact button 350 on the upper surface of the coupon. A multilayered coupon such as the coupon 300 including the tile 300c provides flexibility for connecting an arrangement of finely pitched contact tips with the more coarsely pitched contacts of more moderately priced space transformers.

Referring to FIG. 16, the coupon 300 also includes one or more forming posts 370 that extend from the upper surface of the elastomer layer 312 to the lower surface of the elastomer layer. The forming posts aid in controlling the thickness and in maintaining the planarity of the surfaces of the elastomeric layer during the curing of the elastomer but are not conductively connected to a circuit of the probing apparatus. Posts 372, extending proud of the surfaces of the coupon are not arranged to conduct electricity but may be provided as an aid for the user in gauging the deflection of the elastically suspended contacts. For example, a post 372 having a first end in contact with the space transformer and a second end projecting from the bottom of the coupon a distance slightly less than the height of a contact tip may serve as a contact gage to prevent damage to the coupon from excess deflection of the elastically supported contact tips. Similarly, an elastically supported post 374 that projects below the lower surface of the coupon may be arranged to provide a signal of the limits of contact tip deflection. When the elastically suspended contact tip is pushed upward by engagement with the wafer, the end of the post contacts and conductively connects traces 376, 378 in the coupon to close an electrical circuit and provide a signal at a contact button 380 which may be connected to an indicator circuit.

At RF frequencies, signal frequencies in the radio frequency and microwave frequency ranges, it is important to match the impedance, typically 50Ω, of the coaxial cable that typically interconnects the test instrumentation and the probing apparatus with the impedance of the coplanar waveguide that extends from the interface board 52 of the probing apparatus to the lower surface of the membrane in the area of the forward support surface 70. A mismatch of impedance will produce reflections of the signals which can couple to adjacent structures causing frequency dependent inaccuracies in the measurements of the DUT's performance. Referring to FIGS. 4 and 17, to transition the signal path from a coaxial cable 50 to the co-planar waveguide comprising traces on the membrane, the conductors of the coaxial cable are first conductively connected to respective traces 87 on the surface of the interface board which collectively comprise an interface board co-planar waveguide. Typically, the center conductor of the coaxial cable is connected to a center trace and the outer conductor of the cable, which is connected to a ground potential, is connected a pair of side traces, one spaced to either side of the center trace to form a ground-signal-ground (GSG) co-planar waveguide. The traces of the interface board co-planar waveguide terminate proximate the edge of the central opening 78 in the interface board and portions of the conductive traces on the membrane's lower surface are arranged to overlap portions of the surfaces of respective traces of the interface board co-planar waveguide when the membrane is clamped to the interface board. The overlapping surface portions conductively interconnect the traces of interface board waveguide to respective traces of a membrane waveguide extending the signal path to the lower surface of the membrane in the region proximate the forward support surface 70.

Typically, the interface board includes a sub-surface conductive layer that is connected to a ground potential to

13

provide a ground plane for the interface board co-planar waveguide. However, inconsistency in the interconnection of the interface board co-planar waveguide and the ground plane may produce an impedance mismatch as the signal path transitions from coaxial cable to co-planar waveguide. The inventors realized that eliminating the interconnections with the interface board ground plane would eliminate this source of error but would also increase the impedance of the interface board co-planar waveguide to unacceptable levels. The inventors came to the unexpected conclusion that the interface board ground plane could be eliminated by decreasing the gaps between the signal trace and the ground traces of the coplanar waveguide, interconnecting the ground traces of adjacent waveguides and providing a low impedance structure for interconnecting the traces of the membrane and interface board waveguides.

The exemplary interface board **500** includes a plurality of conductive traces deposited on the upper surface. Three traces **502**, **504**, **506** comprise an interface board co-planar waveguide **508** (indicated by a bracket). The center conductor **510** of a coaxial cable **502** is conductively interconnected with the center trace **502** of the waveguide and the outer conductor **514** of the cable is connected to a first side trace **504** spaced apart from one edge of the center trace and a second side trace **506** spaced apart from the second edge of the center trace. Typically, a signal is communicated between the test instrumentation and the probing apparatus over the center conductor of the coaxial cable and the outer conductor is connected to a ground level electrical potential. The interface board ground plane **516**, if any, terminates a substantial distance from the area of the interface board that is overlaid by the traces of the waveguide and is not electrically interconnected with the traces of the waveguide. To reduce the impedance of the “ungrounded” waveguide, the width of the center trace **502** differs from the widths of the side traces and the widths of the respective side traces may also differ from each other. For example, the center trace or signal conductor of an exemplary GSG waveguide having an impedance of  $50\Omega$  is 0.0179 inches wide and is separated from each of the spaced apart side traces of the waveguide by a gap of 0.004 inches. If a side trace, for example the side trace **506** of the exemplary waveguide is adjacent to the center traces of two waveguides, for example center trace **502** and the center trace **522** of a second waveguide **520** (indicated by a bracket), the side trace is shared by the adjacent waveguides **508**, **512**. The side trace preferably has a width of 0.029 inches and the outer conductors **514** of two adjacent coaxial cables **512**, **526** are conductively connected to the trace. If a side trace, for example the side trace **504** of the exemplary interface board co-planar waveguide **508**, is adjacent to only one center trace, the side trace has a width of 0.0107 inches.

Referring to also FIG. **19**, while the impedance of a co-planar waveguide is substantially affected by the width of the gap between the traces of the waveguide, to improve the tolerance of the waveguide to misalignment between overlapping portions of the traces of the membrane waveguide and the traces of the interface board waveguide, the width of the center trace of the interface board waveguide may be narrowed for the portion of the length that is overlapped by the membrane trace. For example, the exemplary waveguide **600** includes a central trace **602** comprising a first length portion **604** that is preferably 0.0179 inches wide and a second length portion **606** which is overlapped by the membrane trace **614** and which is preferably 0.0159 inches wide. The gap **608** between the center trace and the side traces for the first length portion is 0.004 inches while the

14

gap **610** for the second length portion is 0.005 inches increasing the tolerance to misalignment between the traces of interface and membrane waveguides. However, the impedance of the exemplary waveguide **600** is substantially the same as the impedance of a waveguide with uniform 0.004 inch gaps between traces.

The interconnection of the respective traces of the interface board waveguide and the corresponding traces of the membrane waveguide substantially effects the impedance of the waveguide. The electro-magnetic field is carried in the gap between the traces of a waveguide and the interconnection between the traces can produce a “pinch point” that substantially increases the waveguide’s impedance. The inventors concluded that the more closely the geometry of the interconnecting structure resembles the geometry of the waveguide’s traces the lower the impedance of the connection. Referring also to FIG. **18**, when the membrane probe is assembled, contact portions **86** of the traces on the membrane overlap portions of the surfaces of the traces on the interface board. The inventors concluded that a signal path comprising a plurality of raised pads **540** on one of the overlapping surfaces of a pair of traces would facilitate a low impedance interconnection between the interface board waveguide and the membrane waveguide. The interconnecting structure for the center traces **502** and **530** of the interface board and membrane waveguides, respectively, comprises four pads **540** that project from the surface of one of the traces into contact with the surface of the other trace. A pair of the raised pads, indicated generally as **542** and **544**, is arranged substantially parallel to each of the edges of the center trace on which the pads are affixed and the pads are located as close to the edge of the trace as tolerance for misalignment of the trace will allow. Preferably, a raised pad is located at each of the corners of a substantially rectangular area on the surface of the trace.

Similarly, a portion of the side trace **534** on the membrane overlaps a portion of the side trace **504** on the surface of the interface board **500** and a portion of the membrane side trace **532** overlaps a portion of the interface board waveguide side trace **506**. On the side (ground) traces, the pair **546** of raised pads **540** nearest the center trace **502** are located as close to the inner edge of the trace as is permitted by the tolerance to misalignment and the second pair **548** of raised pads are preferably located nearer the center line of the membrane trace than the second edge of the trace. The electro-magnetic field is carried in the region between the traces of the waveguide and locating the pads of interconnecting structure closer to the region in which the electro-magnetic field is confined reduces the inductance of the connection.

The accuracy of measurements performed with the membrane probing apparatus, particularly at frequencies in the radio and microwave frequency ranges, is improved by optimizing the impedance of the interface between co-axial cables, interconnecting the test instrumentation and the probing apparatus, and the co-planar waveguide that extends the signal path to the contact tips. A longer service life and lower operating cost for a membrane probing apparatus is achievable by including the contact tips on an elastic coupon that is attachable to a membrane that includes a plurality of traces over which signals, data and power can be transmitted. Replacing the probe needles of a needle type probing apparatus with a coupon attachable to a space transformer and including elastically supported contact tips can also improve the performance of a needle-type probing apparatus by substantially lower the inductance of the apparatus.

The detailed description, above, sets forth numerous specific details to provide a thorough understanding of the

present invention. However, those skilled in the art will appreciate that the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid obscuring the present invention.

All the references cited herein are incorporated by reference.

The terms and expressions that have been employed in the foregoing specification are used as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding equivalents of the features shown and described or portions thereof, it being recognized that the scope of the invention is defined and limited only by the claims that follow.

The invention claimed is:

1. A method of electrically contacting a bond pad of a device under test with a probe of a membrane probing assembly, wherein the membrane probing assembly includes an elastomeric layer having an upper surface and a lower surface, and further wherein the probe includes a rigid beam, which is adhered to the elastomeric layer and extends at least substantially parallel to the lower surface of the elastomeric layer, a post portion, which projects from the rigid beam in a direction that is at least substantially perpendicular to the lower surface of the elastomeric layer such that the post portion is exposed on the upper surface of the elastomeric layer, and a contact tip, which projects from a side of the rigid beam that is opposed to the post portion and in a direction that is at least substantially perpendicular to the lower surface of the elastomeric layer such that the contact tip extends from the lower surface of the elastomeric layer, the method comprising:

bringing the contact tip into pressing engagement with the bond pad of the device under test such that the bond pad applies a contact force to the contact tip;

constraining displacement of the post portion in a direction that is parallel to the contact force with a trace of the membrane probing assembly, wherein the elastomeric layer and the probe together define a coupon, wherein the coupon is detachably affixed to a flexible membrane assembly that includes the trace, and further wherein the constraining displacement of the post portion includes constraining displacement of the post portion with the flexible membrane assembly;

responsive to receipt of the contact force, pivoting the rigid beam; and

responsive to the pivoting, translating the contact tip across the bond pad to produce a lateral scrubbing motion on the bond pad.

2. The method of claim 1, wherein the flexible membrane assembly is at least substantially incompressible.

3. The method of claim 1, wherein the elastomeric layer is a compressible elastomeric layer, and further wherein the pivoting includes compressing the elastomeric layer between the rigid beam and the flexible membrane assembly.

4. The method of claim 1, wherein the membrane probing assembly further includes an incompressible support surface that supports the flexible membrane assembly, and further wherein the constraining displacement of the post portion includes constraining displacement of the post portion with the incompressible support surface.

5. The method of claim 4, wherein the incompressible support surface is in direct physical contact with the flexible membrane assembly such that both the incompressible support surface and the flexible membrane assembly exert a recovery force on the rigid beam during the pivoting.

6. The method of claim 1, wherein the contact tip and the post portion project from opposed ends of the rigid beam.

7. The method of claim 1, wherein, during the pivoting, the method further includes applying an elastic recovery force to the probe with the elastomeric layer.

8. The method of claim 1, wherein the translating the contact tip across the bond pad includes abrading an oxide that is present on the bond pad.

9. The method of claim 1, wherein the membrane probing assembly includes a plurality of probes supported by the elastomeric layer, wherein the plurality of probes is positioned to contact a corresponding plurality of bond pads of the device under test, and further wherein, subsequent to initial pressing engagement between a given one of the plurality of probes and a corresponding one of the plurality of bond pads, the method includes providing an over travel sufficient to provide pressing engagement between each of the plurality of probes and the corresponding bond pad of the plurality of bond pads.

10. The method of claim 9, wherein the method includes compressing the elastomeric layer to provide the over travel.

11. The method of claim 1, wherein an adhesive operatively attaches the elastomeric layer to the flexible membrane assembly.

\* \* \* \* \*