(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
16 November 2023 (16.11.2023)

WIPO | PCT

(10) International Publication Number
WO 2023/220517 A1

(51) International Patent Classification:
B01L 3/02 (2006.01) *G01F 11/28* (2006.01)
G01N 35/10 (2006.01) *G01F 11/02* (2006.01)

(21) International Application Number:
PCT/US2023/065982

(22) International Filing Date:
20 April 2023 (20.04.2023)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
17/741,647 11 May 2022 (11.05.2022) US

(71) Applicant: **PERKINELMER HEALTH SCIENCES, INC.** [US/US]; 940 Winter Street, Waltham, Massachusetts 02451 (US).

(72) Inventors: **PERROUD, Thomas**; 940 Winter Street, Waltham, Massachusetts 02451 (US). **RAWLINS, Thomas**; 940 Winter Street, Waltham, Massachusetts 02451 (US). **TIEDTKE, Hans-Juergen**; Garstligweg 6, 8634 Hombrechtikon (CH). **HASSLER, Kai**; Garstligweg 6, 8634 Hombrechtikon (CH).

(74) Agent: **BEATTY, David D.**; Myers Bigel, P.A., PO Box 37428, Raleigh, North Carolina 27627 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, MG, MK, MN, MU, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, CV, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ,

(54) Title: PIPETTING APPARATUS AND METHODS




FIG. 1

(57) Abstract: An automated pipetting system includes a pipettor. The pipettor includes a pipetting channel, a first plunger mechanism operable to change a pressure in the pipetting channel to aspirate or dispense a liquid, and a second plunger mechanism operable to change the pressure in the pipetting channel to aspirate or dispense the liquid.

WO 2023/220517 A1

[Continued on next page]

DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

PIPETTING APPARATUS AND METHODS

Field

[0001] The present technology relates to automated liquid handling systems and, more particularly, to apparatus and methods for aspirating and/or dispensing liquids using a pipettor.

Background

[0002] Laboratory liquid handling systems are used to transport and operate on volumes of liquid. The liquid handling system may include one or more pipettors that are used to aspirate portions of liquid samples and/or to dispense liquid samples. In some cases, the liquid samples are aspirated and dispensed robotically and, in some cases, automatically and programmatically.

Summary

[0003] According to some embodiments, an automated pipetting system includes a pipettor. The pipettor includes a pipetting channel, a first plunger mechanism operable to change a pressure in the pipetting channel to aspirate or dispense a liquid, and a second plunger mechanism operable to change the pressure in the pipetting channel to aspirate or dispense the liquid.

[0004] According to some embodiments, the first and second plunger mechanisms are operable to displace an air volume in the pipetting channel.

[0005] According to some embodiments, the first and second plunger mechanisms are operable independently of one another to change the pressure in the pipetting channel.

[0006] In some embodiments, the pipetting system includes a pipetting orifice and a liquid collection volume, and the first and second plunger mechanisms are operable to change the pressure in the pipetting channel to aspirate the liquid into the liquid collection volume through the pipetting orifice or to dispense the liquid from the liquid collection volume through the pipetting orifice.

[0007] The automated pipetting system may include a pipette tip removably coupled to the pipettor, wherein the pipette tip includes the liquid collection volume and the pipetting orifice.

[0008] In some embodiments, the pipettor includes an ejection mechanism operable to force the pipette tip off of the pipettor.

[0009] According to some embodiments, the first plunger mechanism includes a first chamber and a first plunger, wherein the first plunger mechanism is operable to move the first plunger through the first chamber to change the pressure in the pipetting channel, and the second plunger mechanism includes a second chamber and a second plunger, wherein the second plunger mechanism is operable to move the second plunger through the second chamber to change the pressure in the pipetting channel.

[0010] In some embodiments, the first plunger mechanism includes a first plunger actuator operable to move the first plunger through the first chamber, the second plunger mechanism includes a second plunger actuator operable to move the second plunger through the second chamber, and the automated pipetting system includes a controller configured to automatically and programmatically control the first plunger actuator and the second plunger actuator.

[0011] The first plunger actuator and the second plunger actuator may be linear actuators.

[0012] In some embodiments, the first plunger mechanism is configured to translate the first plunger along a first plunger axis, the second plunger mechanism is configured to translate the second plunger along a second plunger axis, the first plunger has a first cross-sectional area in a plane orthogonal to the first plunger axis, the second plunger has a second cross-sectional area in a plane orthogonal to the second plunger axis, and the second cross-sectional area is greater than the first cross-sectional area.

[0013] In some embodiments, the second cross-sectional area is at least three times the first cross-sectional area.

[0014] According to some embodiments, the first plunger mechanism is configured to translate the first plunger through the first chamber, the second plunger mechanism is configured to translate the second plunger through the second chamber, the first plunger displaces an air volume in the first chamber at a first rate of air volume displacement per unit translation, the second plunger displaces an air volume in the second chamber at a second rate of air volume displacement per unit translation, and the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation.

[0015] In some embodiments, the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

[0016] In some embodiments, the first plunger mechanism is configured to provide a first maximum air volume displacement, the second plunger mechanism is configured to

provide a second maximum air volume displacement, and the second maximum air volume displacement is greater than the first maximum air volume displacement.

[0017] In some embodiments, the second maximum air volume displacement is at least ten times the first maximum air volume displacement.

[0018] In some embodiments, the first chamber has a first chamber volume, and the second chamber has a second chamber volume that is greater than the first chamber volume.

[0019] In some embodiments, the second chamber volume is at least ten times the first chamber volume.

[0020] According to some embodiments, the pipettor includes a valve to selectively control fluid communication between the second chamber and a port to atmosphere.

[0021] According to some embodiments, the pipettor includes at least one valve to selectively control fluid communication between the second chamber and the pipetting channel. In some embodiments, the first plunger is disposed in the pipetting channel.

[0022] According to some embodiments, the first plunger is disposed in the pipetting channel.

[0023] The automated pipetting system may include a controller configured to automatically and programmatically control the first and second plunger mechanisms.

[0024] The automated pipetting system may include a pressure sensor coupled to the pipetting channel, wherein the controller is configured to receive a pipetting channel pressure signal from the pressure sensor indicating the pressure in the pipetting channel.

[0025] According to some embodiments, the pipettor includes a valve to selectively control fluid communication between the second plunger mechanism and the pipetting channel, and the controller is configured to automatically and programmatically control the valve.

[0026] According to some embodiments, a method for operating an automated pipetting system includes performing, by at least one control circuit, operations comprising: operating a first plunger mechanism of a pipettor of the automated pipetting system to change a pressure in a pipetting channel of the pipettor to aspirate or dispense a liquid; and operating a second plunger mechanism of the pipettor to change the pressure in the pipetting channel to aspirate or dispense the liquid.

[0027] According to some embodiments, the method includes operating the first and second plunger mechanisms to displace an air volume in the pipetting channel.

[0028] According to some embodiments, the method includes operating the first and second plunger mechanisms independently of one another to change the pressure in the pipetting channel.

[0029] According to some embodiments, the method includes operating the first and second plunger mechanisms to aspirate the liquid into a liquid collection volume through a pipetting orifice or to dispense the liquid from the liquid collection volume through the pipetting orifice.

[0030] In some embodiments, the method includes removably coupling a pipette tip to the pipettor, wherein the pipette tip includes the liquid collection volume and the pipetting orifice.

[0031] In some embodiments, the method includes operating an ejection mechanism to force the pipette tip off of the pipettor.

[0032] According to some embodiments, the first plunger mechanism includes a first chamber and a first plunger, the second plunger mechanism includes a second chamber and a second plunger, the method includes operating the first plunger mechanism to move the first plunger through the first chamber to change the pressure in the pipetting channel, and the method includes operating the second plunger mechanism includes moving the second plunger through the second chamber to change the pressure in the pipetting channel.

[0033] In some embodiments, the first plunger mechanism includes a first plunger actuator operable to move the first plunger through the first chamber, the second plunger mechanism includes a second plunger actuator operable to move the second plunger through the second chamber, and the method includes automatically and programmatically controlling the first plunger actuator and the second plunger actuator using a controller.

[0034] The first plunger actuator and the second plunger actuator may be linear actuators.

[0035] According to some embodiments, the first plunger mechanism is configured to translate the first plunger along a first plunger axis, the second plunger mechanism is configured to translate the second plunger along a second plunger axis, the first plunger has a first cross-sectional area in a plane orthogonal to the first plunger axis, the second plunger has a second cross-sectional area in a plane orthogonal to the second plunger axis, and the second cross-sectional area is greater than the first cross-sectional area.

[0036] In some embodiments, the second cross-sectional area is at least three times the first cross-sectional area.

[0037] In some embodiments, the first plunger mechanism is configured to translate the first plunger through the first chamber, the second plunger mechanism is configured to translate the second plunger through the second chamber, the first plunger displaces an air volume in the first chamber at a first rate of air volume displacement per unit translation, the second plunger displaces an air volume in the second chamber at a second rate of air volume displacement per unit translation, and the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation.

[0038] In some embodiments, the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

[0039] According to some embodiments, the first plunger mechanism is configured to provide a first maximum air volume displacement, the second plunger mechanism is configured to provide a second maximum air volume displacement, and the second maximum air volume displacement is greater than the first maximum air volume displacement.

[0040] In some embodiments, the second maximum air volume displacement is at least ten times the first maximum air volume displacement.

[0041] According to some embodiments, the first chamber has a first chamber volume, and the second chamber has a second chamber volume that is greater than the first chamber volume.

[0042] In some embodiments, the second chamber volume is at least ten times the first chamber volume.

[0043] The method may include selectively controlling fluid communication between the second chamber and the pipetting channel using a valve forming a part of the pipettor. In some embodiments, the first plunger is disposed in the pipetting channel.

[0044] According to some embodiments, the first plunger is disposed in the pipetting channel.

[0045] The method may include automatically and programmatically controlling the first and second plunger mechanisms using a controller.

[0046] According to some embodiments, the pipettor includes a pressure sensor coupled to the pipetting channel, and the controller receives a pipetting channel pressure signal from the pressure sensor indicating the pressure in the pipetting channel.

[0047] In some embodiments, the pipettor includes a valve to selectively control fluid communication between the second plunger mechanism and the pipetting channel, and the method includes automatically and programmatically controlling the valve using the controller.

[0048] According to some embodiments, a pipetting system includes a pipettor including: a barrel; a pipetting channel; a passage defined in the barrel and in fluid communication with the pipetting channel, the passage including a rear chamber, and a front chamber between the rear chamber and the pipetting channel; a front plunger mounted in the front chamber to translate relative to the passage through a front plunger stroke; a rear plunger mounted in the rear chamber to translate relative to the passage through a rear plunger stroke; and a front seal about the front plunger. During a first part of the front plunger stroke, the front chamber is fluidly sealed from the rear chamber by the front seal, and translation of the front plunger in the front chamber generates a change in a pressure in the pipetting channel to aspirate or dispense a liquid. During a second part of the front plunger stroke, the front chamber is fluidly coupled to the rear chamber, and translation of the rear plunger in the rear chamber along the rear plunger stroke generates a change in the pressure in the pipetting channel to aspirate or dispense the liquid.

[0049] According to some embodiments, the pipettor includes a plunger member including both the front plunger and the rear plunger, and the plunger member is mounted in the passage to translate through a plunger member stroke including the front plunger stroke and the rear plunger stroke.

[0050] In some embodiments, the translation of the of the front plunger in the front chamber and the translation of the rear plunger in the rear chamber displace an air cushion in the pipetting channel.

[0051] In some embodiments, during the first part of the front plunger stroke, a connecting opening between the front and rear chambers is plugged by the front plunger, and during the second part of the front plunger stroke, the connecting opening is not plugged by the front plunger and the front chamber is fluidly coupled to the rear chamber through the connecting opening.

[0052] In some embodiments, the front seal includes an annular seal member slidably engaging the front plunger or the barrel.

[0053] According to some embodiments, the pipetting system includes a rear seal about the rear plunger.

[0054] The rear seal may include an annular seal member slidably engaging the rear plunger or the barrel.

[0055] According to some embodiments, the rear chamber is defined between the front seal and the rear seal.

[0056] The pipetting may include a pressure relief valve arranged and configured to relieve pressure in the rear chamber during the first part of the front plunger stroke.

[0057] According to some embodiments, the pipetting system includes a pressure sensor arranged and configured to detect the pressure in the pipetting channel.

[0058] In some embodiments, the pipetting system includes an opening mechanism selectively operable to place the rear chamber in fluid communication with the front chamber when the front plunger is not in the second part of the front plunger stroke.

[0059] In some embodiments, the opening mechanism includes a valve selectively operable to place the rear chamber in fluid communication with the front chamber when the front plunger is not in the second part of the front plunger stroke.

[0060] According to some embodiments, the valve is selectively operable to place the rear chamber in fluid communication with a port to atmosphere.

[0061] In some embodiments, the pipetting system is configured such that the front seal forms a seal about the front plunger throughout the first part of the front plunger stroke and the second part of the front plunger stroke.

[0062] The pipetting system may include a pipette tip removably coupled to the barrel. The pipette tip includes a liquid collection volume fluidly coupled to the pipetting channel, and a tip orifice in fluid communication with the liquid collection volume.

[0063] According to some embodiments, the pipetting system includes: at least one actuator to drive the front and rear plungers through the front and rear plunger strokes; and a controller configured to automatically and programmatically operate the at least one actuator.

[0064] In some embodiments, the front and rear plunger strokes extend along a plunger axis, the front plunger has a first cross-sectional area in a plane orthogonal to the plunger axis, the rear plunger has a second cross-sectional area in a plane orthogonal to the plunger axis, and the second cross-sectional area is greater than the first cross-sectional area.

[0065] In some embodiments, the second cross-sectional area is at least three times the first cross-sectional area.

[0066] According to some embodiments, the front plunger displaces an air volume in the front chamber at a first rate of air volume displacement per unit translation, the rear plunger displaces an air volume in the rear chamber at a second rate of air volume displacement per unit translation, and the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation.

[0067] In some embodiments, the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

[0068] According to some embodiments, the front plunger is configured to provide a first maximum air volume displacement in the front chamber, the rear plunger is configured to provide a second maximum air volume displacement in the rear chamber, and the second maximum air volume displacement is greater than the first maximum air volume displacement.

[0069] In some embodiments, the second maximum air volume displacement is at least ten times the first maximum air volume displacement.

[0070] According to some embodiments, the front chamber has a front chamber volume, and the rear chamber has a rear chamber volume that is greater than the front chamber volume.

[0071] In some embodiments, the rear chamber volume is at least ten times the front chamber volume.

[0072] According to some embodiments, a method for pipetting a liquid includes providing a pipettor including: a barrel; a pipetting channel; a passage defined in the barrel and in fluid communication with the pipetting channel, the passage including a rear chamber, and a front chamber between the rear chamber and the pipetting channel; a front plunger mounted in the front chamber to travel a front plunger stroke; a rear plunger mounted in the rear chamber to travel a rear plunger stroke; and a front seal about the front plunger. The method further includes translating the front plunger through the front plunger stroke and translating the rear plunger through the rear plunger stroke to aspirate or dispense a liquid. During a first part of the front plunger stroke, the front chamber is fluidly sealed from the rear chamber by the front seal, and translation of the front plunger in the front chamber generates a change in a pressure in the pipetting channel to aspirate or dispense a liquid. During a second part of the front plunger stroke, the front chamber is fluidly coupled to the rear chamber, and translation of the rear plunger in the rear chamber along the rear plunger stroke generates a second change in the pressure in the pipetting channel to aspirate or dispense the liquid.

[0073] According to some embodiments, the pipettor includes a plunger member including both the front plunger and the rear plunger, the plunger member is mounted in the passage to translate a plunger member stroke including the front plunger stroke and the rear plunger stroke, and translating the front plunger through the front plunger stroke and translating the rear plunger through the rear plunger stroke are executed by translating the plunger member through the plunger member stroke.

[0074] In some embodiments, the translation of the of the front plunger in the front chamber and the translation of the rear plunger in the rear chamber displace an air volume in the pipetting channel.

[0075] In some embodiments, during the first part of the front plunger stroke, a connecting opening between the front and rear chambers is plugged by the front plunger, and during the second part of the front plunger stroke, the connecting opening is not plugged by the front plunger and the front chamber is fluidly coupled to the rear chamber through the connecting opening.

[0076] According to some embodiments, the method includes: translating the front plunger in a first direction through the first part of the front plunger stroke to aspirate the liquid; and thereafter, translating the front plunger in a second direction opposite the first direction through the first part of the front plunger stroke to dispense the liquid. The front plunger is not translated through the second part of the front plunger stroke between translating the front plunger in the first direction and translating the front plunger in the second direction.

[0077] In some embodiments, the method includes: translating the front plunger in a first direction through the first and second parts of the front plunger stroke to aspirate the liquid using the front plunger and the rear plunger; and thereafter, translating the front plunger in a second direction opposite the first direction through the first and second parts of the plunger stroke to dispense the liquid using the front plunger and the rear plunger.

[0078] According to some embodiments, the method includes: with the front plunger in the first part of the front plunger stroke, operating an opening mechanism to place the rear chamber in fluid communication with the front chamber; and thereafter, with the rear chamber in fluid communication with the front chamber, translating the rear plunger along the rear plunger stroke to aspirate the liquid.

[0079] In some embodiments, the front seal forms a seal about the front plunger throughout the front plunger stroke and the rear plunger stroke.

[0080] According to some embodiments, a pipetting system includes a pipettor including: a barrel; a pipetting channel; a passage defined in the barrel and in fluid communication with the pipetting channel, the passage including a rear chamber, and a front chamber between the rear chamber and the pipetting channel; a front plunger mounted in the front chamber to translate relative to the passage along a plunger axis; and a rear plunger mounted in the rear chamber to translate relative to the passage along the plunger axis. Translation of the front plunger in the front chamber along the plunger axis generates a

change in a pressure in the pipetting channel to aspirate or dispense a liquid. Translation of the rear plunger in the rear chamber along the plunger axis generates a change in the pressure in the pipetting channel to aspirate or dispense the liquid. The front plunger has a first cross-sectional area in a plane orthogonal to the plunger axis. The rear plunger has a second cross-sectional area in a plane orthogonal to the plunger axis. The second cross-sectional area is greater than the first cross-sectional area.

[0081] In some embodiments, the pipettor includes a plunger member including both the front plunger and the rear plunger, and the plunger member is mounted in the passage to translate along the plunger axis.

[0082] According to some embodiments, a pipetting system includes a pipettor, an air displacement pipette tip, and a positive displacement pipette tip. The air displacement pipette tip and the positive displacement pipette tip are alternatively and removably mountable on the pipettor. The pipettor is operable to aspirate a liquid into the air displacement pipette tip when the air displacement pipette tip is mounted on the pipettor. The pipettor is operable to aspirate a liquid into the positive displacement pipette tip when the positive displacement pipette tip is mounted on the pipettor.

[0083] According to some embodiments, the pipettor includes a tip mount interface configured to engage and releasably secure the air displacement pipette tip and the positive displacement pipette tip to the pipettor.

[0084] In some embodiments, the tip mount interface is configured to form a gas-tight fit with the air displacement pipette tip when the air displacement pipette tip is mounted on the pipettor.

[0085] According to some embodiments, the air displacement pipette tip includes an air displacement tip orifice and a liquid collection volume in fluid communication with the air displacement tip orifice, and the positive displacement pipette tip includes a positive displacement tip orifice, a tip passage in fluid communication with the positive displacement tip orifice, and a piston slidably mounted in the tip passage. The positive displacement pipette tip is operative to generate a negative pressure at the positive displacement tip orifice to aspirate the liquid when the piston is translated away from the positive displacement tip orifice.

[0086] In some embodiments, the pipettor is operable to displace an air volume in the air displacement pipette tip to generate a negative pressure at the air displacement tip orifice.

[0087] In some embodiments, the pipettor includes a plunger that is translatable to generate a negative pressure at the air displacement tip orifice to aspirate the liquid when the air displacement pipette tip is mounted on the pipettor.

[0088] In some embodiments, the pipettor includes a plunger configured to engage and translate the piston through the tip passage when the positive displacement pipette tip is mounted on the pipettor.

[0089] According to some embodiments, the pipettor includes a plunger, the plunger is translatable to generate a negative pressure at the air displacement tip orifice to aspirate the liquid when the air displacement pipette tip is mounted on the pipettor, and the plunger is configured to engage and translate the piston through the tip passage when the positive displacement pipette tip is mounted on the pipettor.

[0090] In some embodiments, the pipettor includes a chamber and a pipetting channel, the pipetting channel is fluidly coupled to the liquid collection volume when the air displacement pipette tip is mounted on the pipettor, and the plunger is mounted to translate in the chamber to generate a negative pressure in the pipetting channel.

[0091] In some embodiments, the pipettor is operable in each of an air displacement mode with the air displacement pipette tip mounted on the pipettor and, alternatively, a positive displacement mode with the positive displacement pipette tip mounted on the pipettor, and the chamber is sealed in the air displacement mode, and is not sealed in positive displacement mode.

[0092] In some embodiments, the pipettor includes a barrel defining the chamber, and an annular seal about the plunger between the plunger and the barrel. The annular seal seals the chamber in the air displacement mode, and does not seal the chamber in positive displacement mode.

[0093] The pipettor may include a pressure sensor arranged and configured to output a detection signal indicating a pressure in the chamber.

[0094] According to some embodiments, the pipettor includes at least one plunger actuator to drive the plunger, and a controller configured to automatically and programmatically operate the at least one actuator.

[0095] In some embodiments, the at least one plunger actuator includes a linear actuator.

[0096] According to some embodiments, the positive displacement pipette tip includes a tip body defining the tip passage; and a venting port in the tip body to relieve a pressure in the tip passage between the piston and the pipettor.

[0097] According to some embodiments, a pipettor includes an air displacement mechanism, and a positive displacement mechanism. The pipettor is configured to mount an air displacement pipette tip thereon and, alternatively, a positive displacement pipette tip thereon. When the air displacement pipette tip is mounted on the pipettor, the air displacement mechanism is operable to generate a negative pressure in the air displacement pipette tip to aspirate a liquid into the air displacement pipette tip. When the positive displacement pipette tip is mounted on the pipettor, the positive displacement mechanism is operable to displace a piston of the positive displacement pipette tip to aspirate a liquid into the positive displacement pipette tip.

[0098] According to some embodiments, the pipettor includes a plunger, the plunger is translatable to generate the negative pressure in the air displacement pipette tip to aspirate the liquid when the air displacement pipette tip is mounted on the pipettor, and the plunger is configured to engage and translate the piston through a tip passage of the positive displacement pipette tip when the positive displacement pipette tip is mounted on the pipettor.

[0099] According to some embodiments, a method for pipetting a liquid includes: with an air displacement pipette tip mounted on a pipettor, operating the pipettor to aspirate a liquid into the air displacement pipette tip; and thereafter, with a positive displacement pipette tip mounted on the pipettor, operating the pipettor to aspirate a liquid into the positive displacement pipette tip.

[00100] According to some embodiments, the method includes performing, by at least one control circuit controlling at least one actuator, operations comprising: mounting the air displacement pipette tip mounted on the pipettor; removing the air displacement pipette tip from the pipettor; mounting the positive displacement pipette tip mounted on the pipettor; and removing the positive displacement pipette tip from the pipettor.

[00101] According to some embodiments, a pipette tip includes a tip member comprising a first end having an opening therein for aspirating and/or dispensing a liquid, and a second end opposite the first end for connection to a pipettor. A conductive electrode is provided on the tip member and is configured to output a signal responsive to contact with the liquid. The first end of the tip member comprises a non-conductive tip bottom adjacent the opening.

[00102] In some embodiments, the conductive electrode is on an outer surface of the tip member between the first end and the second end.

[00103] In some embodiments, the conductive electrode is at least partially embedded within a surface of the tip member.

[00104] In some embodiments, the non-conductive tip bottom is free of the conductive electrode.

[00105] In some embodiments, the non-conductive tip bottom comprises a portion of the conductive electrode having a non-conductive coating thereon.

[00106] In some embodiments, a conductive element is provided at the second end of the tip member, and a conductive connection extends along the tip member and electrically connects the conductive electrode to the conductive element.

[00107] In some embodiments, the conductive connection extends along the outer surface of the tip member.

[00108] In some embodiments, the conductive connection is at least partially embedded within the tip member.

[00109] In some embodiments, an inner surface of the tip member is free of the conductive electrode.

[00110] In some embodiments, the inner surface of the tip member is non-conductive and the conductive electrode is a single electrode.

[00111] In some embodiments, the non-conductive tip bottom comprises a length of about 2 millimeters (mm) or more.

[00112] In some embodiments, a shape of the conductive electrode defines a surface area that varies with distance from the opening.

[00113] In some embodiments, the conductive electrode is configured to be coupled to a controller circuit that is configured to dynamically detect a level of the liquid and/or predict a loss of contact between the pipette tip and the liquid based on changes in capacitance indicated by the signal output from the conductive electrode.

[00114] According to some embodiments, an automated pipetting system includes a robotic arm assembly comprising an arm member that is adapted to hold a pipettor and an actuator mechanism configured to move the arm member along at least one axis responsive to a control signal, and a controller circuit coupled to the robotic arm assembly. The controller circuit is configured to perform operations including receiving a signal from a conductive electrode on a pipette tip, where the conductive electrode is between a first end of the pipette tip having an opening therein for aspirating and/or dispensing a liquid and a second end of the pipette tip that is connected to the pipettor opposite the first end; and transmitting the control

signal to the actuator mechanism to move the arm member towards or away from a surface of the liquid along the at least one axis responsive to the signal from the conductive electrode.

[00115] In some embodiments, the operations further include dynamically detecting a level of the liquid based on changes in capacitance indicated by the signal from the conductive electrode, optionally independent of a shape or size of a container of the liquid.

[00116] In some embodiments, dynamically detecting the level of the liquid includes predicting a loss of contact between the pipette tip and the liquid based on the changes in the capacitance indicated by the signal from the conductive electrode, and transmitting the control signal to the actuator mechanism is responsive to predicting the loss of contact.

[00117] In some embodiments, the control signal is varied based on the changes in capacitance to move the arm member towards or away from the surface of the liquid along the at least one axis while maintaining the contact between the pipette tip and the liquid.

[00118] In some embodiments, the first end of the pipette tip includes a non-conductive tip bottom adjacent the opening.

[00119] In some embodiments, the conductive electrode is on an outer surface of the pipette tip between the first end and the second end.

[00120] In some embodiments, the conductive electrode is at least partially embedded within a surface of the pipette tip.

[00121] In some embodiments, the non-conductive tip bottom is free of the conductive electrode.

[00122] In some embodiments, the non-conductive tip bottom includes a portion of the conductive electrode having a non-conductive coating thereon.

[00123] In some embodiments, an inner surface of the pipette tip is free of the conductive electrode.

[00124] In some embodiments, the inner surface of the tip member is non-conductive and the conductive electrode is a single electrode.

[00125] In some embodiments, the actuator mechanism includes a first operating mode where the arm member is restricted to motion towards the surface of the liquid along the at least one axis during the aspirating, and a second operating mode where the arm member is restricted to motion away from the surface of the liquid along the at least one axis during the dispensing.

[00126] In some embodiments, the operations further include calculating an aspirated or dispensed volume of the liquid based on a distance of movement of the arm member along

the at least one axis; and controlling subsequent motion of the arm member along the at least one axis based on the aspirated or dispensed volume that was calculated.

[00127] According to some embodiments, a method of operating an automated pipetting system, includes executing computer readable instructions stored in a non-transitory storage medium by a controller circuit to perform operations including receiving a signal from a conductive electrode on a pipette tip, where the conductive electrode is between a first end of the pipette tip having an opening therein for aspirating and/or dispensing a liquid and a second end of the pipette tip that is connected to the pipettor opposite the first end; and transmitting, to an actuator mechanism of a robotic arm assembly, a control signal to move an arm member that is adapted to hold the pipettor towards or away from a surface of the liquid along at least one axis responsive to the signal from the conductive electrode.

[00128] In some embodiments, the operations further include dynamically detecting a level of the liquid based on changes in capacitance indicated by the signal from the conductive electrode, optionally independent of a shape or size of a container of the liquid.

[00129] In some embodiments, dynamically detecting the level of the liquid includes predicting a loss of contact between the pipette tip and the liquid based on the changes in the capacitance indicated by the signal from the conductive electrode, and transmitting the control signal to the actuator mechanism is responsive to predicting the loss of contact.

[00130] In some embodiments, the control signal is varied based on the changes in capacitance to move the arm member towards or away from the surface of the liquid along the at least one axis while maintaining contact between the pipette tip and the liquid.

[00131] In some embodiments, the first end of the pipette tip includes a non-conductive tip bottom extending beyond the conductive electrode.

[00132] In some embodiments, the conductive electrode is on an outer surface of the pipette tip between the first end and the second end.

[00133] In some embodiments, the conductive electrode is at least partially embedded within a surface of the pipette tip

[00134] In some embodiments, the non-conductive tip bottom is free of the conductive electrode.

[00135] In some embodiments, an inner surface of the pipette tip is free of the conductive electrode.

[00136] In some embodiments, the inner surface of the tip member is non-conductive and the conductive electrode is a single electrode.

[00137] In some embodiments, the operations further include restricting the arm member to motion towards the surface of the liquid along the at least one axis during the aspirating; and restricting the arm member to motion away from the surface of the liquid along the at least one axis during the dispensing.

[00138] In some embodiments, the operations further include calculating an aspirated or dispensed volume of the liquid based on a distance of motion of the arm member along the at least one axis; and controlling subsequent motion of the arm member along the at least one axis based on the aspirated or dispensed volume that was calculated.

[00139] According to some embodiments, an automated pipetting system includes a pipettor comprising a channel therein, a pressure sensor coupled to the channel, and at least one controller circuit. The at least one controller circuit is configured to perform operations including receiving, from the pressure sensor, a signal indicating pressure in the channel of the pipettor, and, based on the pressure indicated by the signal, performing at least one of: detecting evaporation of a liquid in the channel; or automatically performing one or more compensation operations.

[00140] In some embodiments, the pipettor includes a pipette tip having an opening therein for aspirating the liquid, and detecting the evaporation is performed after removal of the pipette tip from the liquid.

[00141] In some embodiments, detecting the evaporation further includes calculating an evaporation rate based on a change in the pressure indicated by the signal after the removal of the pipette tip from the liquid.

[00142] In some embodiments, calculating the evaporation rate is independent of a surface tension or type of the liquid.

[00143] In some embodiments, the evaporation rate is calculated in proportion to the change in the pressure indicated by the signal over time.

[00144] In some embodiments, detecting the evaporation further includes controlling movement of a plunger in the channel after removal of the pipette tip from the liquid. Calculating the evaporation rate is based on the change in the pressure indicated by the signal responsive to the movement of the plunger.

[00145] In some embodiments, detecting the evaporation further includes continuously controlling a position of a plunger in the channel of the pipettor such that the pressure indicated by the signal remains substantially constant over time; and calculating an evaporation rate based on displacement of the plunger over time.

[00146] In some embodiments, automatically performing the one or more compensation operations includes performing one or more evaporation compensation operations responsive to detecting the evaporation of the liquid in the channel, based on comparison to a threshold.

[00147] In some embodiments, performing the one or more evaporation compensation operations includes performing a prewetting operation prior to the aspirating of the liquid; and/or adapting one or more aspiration parameters for the aspirating of the liquid; and/or controlling movement of a plunger in the channel.

[00148] In some embodiments, the operations further include estimating an evaporation volume based on the evaporation rate and a duration of the aspirating of the liquid, where the threshold is volume-based.

[00149] In some embodiments, the evaporation volume indicates an amount of under-aspiration. Performing the one or more evaporation compensation operations includes adapting the one or more aspiration parameters to aspirate a further amount of the liquid based on the amount of under-aspiration; and aspirating the further amount of the liquid based on the one or more aspiration parameters that were adapted.

[00150] In some embodiments, performing the one or more evaporation compensation operations includes, after the removal of the pipette tip from the liquid, controlling the movement of the plunger to aspirate air to reduce or avoid dripping of the liquid from the pipette tip.

[00151] In some embodiments, performing the one or more evaporation compensation operations includes, after the removal of the pipette tip from the liquid, controlling the movement of the plunger to maintain a substantially constant pressure in the pipette tip.

[00152] In some embodiments, the substantially constant pressure is based on the pressure indicated by the signal after removal of the pipette tip from the liquid.

[00153] In some embodiments, the substantially constant pressure is a predetermined pressure.

[00154] In some embodiments, the operations further include calculating an aspirated volume of the liquid based on a change in the pressure indicated by the signal.

[00155] In some embodiments, automatically performing the one or more compensation operations includes adapting one or more aspiration parameters based on a comparison of the aspirated volume to a target volume; and aspirating the liquid based on the one or more aspiration parameters that were adapted.

[00156] In some embodiments, automatically performing the one or more compensation operations includes adapting an aspiration speed based on a change in the pressure indicated by the signal relative to a pressure change threshold; and/or performing a prewetting operation based on a temperature of the liquid relative to a temperature threshold.

[00157] According to some embodiments, a method of operating an automated pipetting system includes executing computer readable instructions stored in a non-transitory storage medium by at least one controller circuit to perform operations including receiving, from a pressure sensor, a signal indicating pressure in a channel of a pipettor, and, based on the pressure indicated by the signal, performing at least one of: detecting evaporation of the liquid in the channel; or automatically performing one or more compensation operations.

[00158] In some embodiments, the pipettor includes a pipette tip having an opening therein for aspirating the liquid, and detecting the evaporation is performed after removal of the pipette tip from the liquid.

[00159] In some embodiments, detecting the evaporation further includes calculating an evaporation rate based on a change in the air pressure indicated by the signal after the removal of the pipette tip from the liquid.

[00160] In some embodiments, calculating the evaporation rate is independent of a surface tension or type of the liquid.

[00161] In some embodiments, the evaporation rate is calculated in proportion to the change in the pressure indicated by the signal over time.

[00162] In some embodiments, detecting the evaporation further includes controlling movement of a plunger in the channel after removal of the pipette tip from the liquid, and calculating the evaporation rate is based on the change in the pressure indicated by the signal responsive to the movement of the plunger.

[00163] In some embodiments, detecting the evaporation further includes continuously controlling a position of a plunger in the channel of the pipettor such that the pressure indicated by the signal remains substantially constant over time, and calculating an evaporation rate based on displacement of the plunger over time.

[00164] In some embodiments, automatically performing the one or more compensation operations includes performing one or more evaporation compensation operations responsive to detecting the evaporation of the liquid in the channel, based on comparison to a threshold.

[00165] In some embodiments, performing the one or more evaporation compensation operations includes performing a prewetting operation prior to the aspirating of the liquid;

and/or adapting one or more aspiration parameters for the aspirating of the liquid; and/or controlling movement of a plunger in the channel.

[00166] In some embodiments, the operations further include estimating an evaporation volume based on the evaporation rate and a duration of the aspirating of the liquid, where the threshold is volume-based.

[00167] In some embodiments, the evaporation volume indicates an amount of under-aspiration. Performing the one or more evaporation compensation operations includes adapting the one or more aspiration parameters to aspirate a further amount of the liquid based on the amount of under-aspiration, and aspirating the further amount of the liquid based on the one or more aspiration parameters that were adapted.

[00168] In some embodiments, performing the one or more evaporation compensation operations includes, after the removal of the pipette tip from the liquid, controlling the movement of the plunger to aspirate air to reduce or avoid dripping of the liquid from the pipette tip.

[00169] In some embodiments, performing the one or more evaporation compensation operations includes, after the removal of the pipette tip from the liquid, controlling the movement of the plunger to maintain a substantially constant pressure in the pipette tip.

[00170] In some embodiments, the substantially constant pressure is based on the pressure indicated by the signal after removal of the pipette tip from the liquid.

[00171] In some embodiments, the substantially constant pressure is a predetermined pressure.

[00172] In some embodiments, the operations further include calculating an aspirated volume of the liquid based on a change in the pressure indicated by the signal.

[00173] In some embodiments, performing the one or more compensation operations includes adapting one or more aspiration parameters based on a comparison of the aspirated volume to a target volume, and aspirating the liquid based on the one or more aspiration parameters that were adapted.

[00174] In some embodiments, automatically performing the one or more compensation operations includes adapting an aspiration speed based on a change in the pressure indicated by the signal relative to a pressure change threshold; and/or performing a prewetting operation based on a temperature of the liquid relative to a temperature threshold.

[00175] According to some embodiments, an automated pipetting system includes a pipettor comprising a channel therein, a sensor coupled to the channel, and at least one controller circuit. The controller circuit is configured to perform operations comprising

receiving, from the sensor, a sensor signal indicating a pressure change in the channel; determining a displaced air volume in the channel based on the sensor signal; and transmitting at least one control signal to control a pressure in the channel based on the displaced air volume.

[00176] In some embodiments, the operations further include identifying a rate of air flow in the channel based on the pressure change, and determining the displaced air volume is based on the rate of air flow.

[00177] In some embodiments, the at least one control signal includes a flow restriction control signal. A flow restriction mechanism is coupled to the channel and configured to be switched between respective states that provide different flow rates responsive to the flow restriction control signal.

[00178] In some embodiments, the sensor is a dual sensor, and the sensor signal comprises first and second pressure data indicating first and second flow rates, respectively.

[00179] In some embodiments, the dual sensor includes first and second pressure sensors in a parallel arrangement that provide the first and second pressure data, respectively. A range of measurement of the second pressure sensor is greater than that of the first pressure sensor.

[00180] In some embodiments, the range of measurement of the second pressure sensor is more than an order of magnitude greater than that of the first pressure sensor.

[00181] In some embodiments, the at least one control signal includes a plunger actuator control signal that is varied based on changes in the displaced air volume indicated by the rate of air flow in the channel. A plunger actuator is configured to dynamically control a position and/or a speed of motion of a plunger in the channel responsive to the plunger actuator control signal.

[00182] In some embodiments, the plunger actuator control signal is generated independent of determining a previous position or distance of motion of the plunger in the channel.

[00183] In some embodiments, the at least one control signal includes a valve control signal. An air valve is operable to couple the channel to a pressure source responsive to the valve control signal.

[00184] In some embodiments, the pressure source includes a negative pressure source and a positive pressure source. One of the negative pressure source or the positive pressure source is configured to be selected to control a direction of the air flow in the channel.

[00185] In some embodiments, the operations further include receiving a pressure signal from a pressure sensor in a pipette tip coupled to the pipettor; and determining a volume of a liquid in the pipette tip based on the pressure signal. The at least one control signal is transmitted to control a position of a plunger based on the volume of the liquid in the pipette tip.

[00186] In some embodiments, a microfluidic manifold including a plurality of passages is configured to couple the channel to a pipette tip. One or more of the passages has a diameter of about 0.2 to 0.8 mm.

[00187] According to some embodiments, a method of operating an automated pipetting system includes executing computer readable instructions stored in a non-transitory storage medium by at least one controller circuit to perform operations including receiving, from a sensor coupled to a channel of a pipettor, a sensor signal indicating pressure change in the channel; determining a displaced air volume in the channel based on the sensor signal; and transmitting at least one control signal to control a pressure in the channel based on the displaced air volume.

[00188] In some embodiments, the operations further include identifying a rate of air flow in the channel based on the pressure change indicated by the sensor signal, where determining the displaced air volume is based on the rate of air flow.

[00189] In some embodiments, the at least one control signal includes a flow restriction control signal, and the operations further include switching a flow restriction mechanism, which is coupled to the channel, between respective states that provide different air flow rates responsive to the flow restriction control signal.

[00190] In some embodiments, the sensor is a dual sensor, and the sensor signal comprises first and second pressure data indicating first and second flow rates, respectively.

[00191] In some embodiments, the dual sensor includes first and second pressure sensors in a parallel arrangement that provide the first and second pressure data, respectively. A range of measurement of the second pressure sensor is greater than that of the first pressure sensor.

[00192] In some embodiments, the range of measurement of the second pressure sensor is more than an order of magnitude greater than that of the first pressure sensor.

[00193] In some embodiments, the at least one control signal includes a plunger actuator control signal that is varied based on changes in the displaced air volume indicated by the rate of air flow in the channel, and the operations further include dynamically

controlling a position and/or speed of motion of a plunger in the channel responsive to the plunger actuator control signal.

[00194] In some embodiments, the plunger actuator control signal is generated independent of determining a previous position or distance of motion of the plunger in the channel.

[00195] In some embodiments, the at least one control signal includes a valve control signal, and the operations further include operating an air valve to couple the channel to a pressure source responsive to the valve control signal.

[00196] In some embodiments, the pressure source includes a negative pressure source and a positive pressure source, and the operations further include selecting one of the negative pressure source or the positive pressure source to control a direction of the air flow in the channel.

[00197] In some embodiments, the operations further include receiving a pressure signal from a pressure sensor in a pipette tip coupled to the pipettor; and determining a volume of a liquid in the pipette tip based on the pressure signal. The at least one control signal is transmitted to control a position of a plunger based on the volume of the liquid in the pipette tip.

[00198] In some embodiments, the sensor is coupled to at least one passage of a microfluidic manifold that is configured to couple the channel to a pipette tip. The at least one passage comprises a diameter of about 0.2 to 0.8 mm.

[00199] According to some embodiments, a positive displacement pipette tip includes a tip orifice, a rear chamber, a tip passage between the tip orifice and the rear chamber and in fluid communication with the tip orifice, and a piston slidably mounted in the tip passage. The piston is responsive to a negative pressure in the rear chamber to translate rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

[00200] According to some embodiments, the positive displacement pipette tip includes a body defining the rear chamber, and a sliding seal between the piston and the body. The seal separates the rear chamber from the tip passage. The seal translates through the body with the piston.

[00201] In some embodiments, the body includes a body cavity, and the seal partitions the body cavity into the rear chamber and an intermediate chamber between the rear chamber and the tip passage.

[00202] The positive displacement pipette tip may include a pressure relief port in fluid communication with the intermediate chamber.

[00203] According to some embodiments, the positive displacement pipette tip includes a body and an indexing mechanism. The indexing mechanism includes at least one first indexing feature on the body, and at least one second indexing feature on the piston. The first and second indexing features cooperate to stop displacement of the piston at prescribed positions.

[00204] The positive displacement pipette tip may include a seal on the piston that translates through the body with the piston.

[00205] According to some embodiments, a pipette includes a pipettor and a positive displacement pipette tip mounted on the pipettor. The positive displacement pipette tip includes a tip orifice, a rear chamber, a tip passage between the tip orifice and the rear chamber and in fluid communication with the tip orifice, and a piston slidably mounted in the tip passage. The pipettor is operable to generate a negative pressure in the rear chamber, which translates the piston rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

[00206] According to some embodiments, the pipettor is coupled to the piston by an air cushion, and the air cushion is displaced within the pipettor and/or the positive displacement pipette tip as the piston translates.

[00207] According to some embodiments, a method for pipetting a liquid includes mounting a positive displacement pipette tip on a pipettor. The positive displacement pipette tip includes a tip orifice, a rear chamber, a tip passage between the tip orifice and the rear chamber and in fluid communication with the tip orifice, and a piston slidably mounted in the tip passage. The method further includes using the pipettor, generating a negative pressure in the rear chamber, which translates the piston rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

[00208] According to some embodiments, a positive displacement pipette tip includes a tip orifice, a tip passage in fluid communication with the tip orifice, a piston slidably mounted in the tip passage, a body, and an indexing mechanism. The indexing mechanism includes at least one first indexing feature on the body, and at least one second indexing feature on the piston. The first and second indexing features cooperate to stop displacement of the piston at prescribed positions.

[00209] According to some embodiments, the at least one first indexing feature includes a series of first indexing features axially distributed along a lengthwise axis of the positive displacement pipette tip.

[00210] According to some embodiments, a pipette includes a pipettor and a positive displacement pipette tip mounted on the pipettor. The positive displacement pipette tip includes a tip orifice, a tip passage in fluid communication with the tip orifice, a piston slidably mounted in the tip passage, a body, and an indexing mechanism. The indexing mechanism includes at least one first indexing feature on the body, and at least one second indexing feature on the piston. The first and second indexing features cooperate to stop displacement of the piston at prescribed positions.

[00211] According to some embodiments, a method for pipetting a liquid includes mounting a positive displacement pipette tip on a pipettor. The positive displacement pipette tip includes a tip orifice, a tip passage in fluid communication with the tip orifice, a piston slidably mounted in the tip passage, a body, and an indexing mechanism. The indexing mechanism includes at least one first indexing feature on the body, and at least one second indexing feature on the piston. The first and second indexing features cooperate to stop displacement of the piston at prescribed positions. The pipettor, translating the piston rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

[00212] According to some embodiments, a positive displacement pipette tip for use with a pipettor includes a tip body, a piston, and an integral piston restraint mechanism. The tip body includes a distal tip portion. The distal tip portion defines a tip passage. The piston is slidably mounted in the tip passage. The piston is displaceable to aspirate a liquid into the positive displacement pipette tip. The integral piston restraint mechanism is operable to limit movement between the piston and the tip body.

[00213] According to some embodiments, the piston restraint mechanism is positionable in each of a restraining configuration, wherein the piston restraint mechanism prevents the piston from being retracted beyond a prescribed position relative to the tip body, and a release configuration, wherein the piston restraint mechanism does not prevent the piston from being retracted beyond the prescribed position.

[00214] In some embodiments, the piston restraint mechanism does not limit movement between the piston and the tip body when in the release configuration.

[00215] According to some embodiments, the piston restraint mechanism includes a latch that is movable between a latching position, wherein the latch engages the piston, and a non-latching position, wherein the latch does not engage the piston.

[00216] In some embodiments, the latch includes a displaceable sleeve or tab.

[00217] In some embodiments, the pipette tip includes an interlock insert mounted on the tip body, wherein the latch forms a part of the interlock insert.

[00218] In some embodiments, the piston restraint mechanism includes an integral interlock feature on the piston, and the interlock feature is configured to interlock with the latch when the piston restraint mechanism is in the restraining configuration to limit movement between the piston and the tip body.

[00219] According to some embodiments, the piston includes an integral coupling feature configured to secure the piston to a driver forming a part of the pipettor.

[00220] According to some embodiments, the tip body includes a mounting section configured to engage the pipettor to removably secure the positive displacement pipette tip to the pipettor.

[00221] According to some embodiments, a pipetting system includes a pipettor and a positive displacement pipette tip mounted on the pipettor. The positive displacement pipette tip includes a tip body, a piston, and an integral piston restraint mechanism. The tip body includes a distal tip portion. The distal tip portion defines a tip passage. The piston is slidably mounted in the tip passage. The piston is displaceable to aspirate a liquid into the positive displacement pipette tip. The integral piston restraint mechanism is operable to limit movement between the piston and the tip body.

[00222] According to some embodiments, a method for pipetting a liquid includes mounting a positive displacement pipette tip on a pipettor. The positive displacement pipette tip includes: a tip body including a distal tip portion, the distal tip portion defining a tip passage; a piston slidably mounted in the tip passage; and an integral piston restraint mechanism operable to limit movement between the piston and the tip body. The method further includes: using the pipettor, translating the piston through the tip passage to aspirate a liquid into the positive displacement pipette tip; and ejecting the positive displacement pipette tip from the pipettor while the piston restraint mechanism limits movement between the piston and the tip body.

[00223] According to some embodiments, mounting the positive displacement pipette tip on the pipettor includes coupling a driver of the pipettor to the piston, and translating the piston through the tip passage includes translating the piston using the driver.

[00224] In some embodiments, the piston restraint mechanism is positionable in each of a restraining configuration, wherein the piston restraint mechanism prevents the piston from being retracted beyond a prescribed position relative to the tip body, and a release configuration, wherein the piston restraint mechanism does not prevent the piston from being retracted beyond the prescribed position, translating the piston through the tip passage includes translating the piston using the driver while the piston restraint mechanism is in the release configuration, and ejecting the positive displacement pipette tip from the pipettor includes relatively displacing the driver and the piston while the piston restraint mechanism is in the restraining configuration.

[00225] In some embodiments, ejecting the positive displacement pipette tip from the pipettor includes pushing the tip body away from the pipettor using an ejector forming a part of the pipettor while the piston restraint mechanism is in the restraining configuration.

[00226] According to some embodiments, the piston restraint mechanism includes an integral interlock feature on the piston; the piston restraint mechanism includes a latch forming a part of the tip body; the latch is positionable in each of a latching position, wherein the latch interlocks with the interlock feature, and a non-latching position, wherein the latch does not interlock with the interlock feature; mounting the positive displacement pipette tip on the pipettor includes inserting a shaft of the pipettor into the tip body and thereby deflecting the latch into the non-latching position; and ejecting the positive displacement pipette tip from the pipettor includes pushing the tip body away from the shaft, responsive to which the latch resiliently returns to the latching position.

Brief Description of the Drawings

[00227] The accompanying drawings, which form a part of the specification, illustrate embodiments of the technology.

[00228] FIG. 1 is a front view of an illustrative laboratory liquid handling system including a pipetting system according to embodiments of the technology.

[00229] FIG. 2 is a perspective view of a pipettor of the pipetting system of **FIG. 1**.

[00230] FIG. 3 is a cross-sectional view of the pipettor of **FIG. 2** taken along the line **3-3** of **FIG. 2**.

[00231] FIG. 4 is an enlarged, fragmentary, cross-sectional view of the pipettor of **FIG. 2**.

[00232] FIG. 5 is an enlarged, fragmentary, cross-sectional view of the pipettor of **FIG. 2**.

[00233] FIG. 6 is a cross-sectional view of the pipettor of **FIG. 2** taken along the line **6-6** of **FIG. 4**.

[00234] FIG. 7 is a cross-sectional view of the pipettor of **FIG. 2** taken along the line **7-7** of **FIG. 3**.

[00235] FIG. 8 is a cross-sectional view of a pipette tip for use with the pipettor of **FIG. 2**.

[00236] FIGS. 9-13 are fragmentary, cross-sectional views of the pipettor of **FIG. 2** illustrating operations of the pipettor.

[00237] FIG. 14 is a fragmentary, cross-sectional view of a pipetting system according to further embodiments.

[00238] FIG. 15 is an exploded, fragmentary, cross-sectional view of the pipetting system of **FIG. 14**.

[00239] FIGS. 16 and **17** are fragmentary, cross-sectional views of the pipetting system of **FIG. 14** wherein a plunger member thereof is disposed in different positions.

[00240] FIG. 18 is a cross-sectional view of the pipetting system of **FIG. 14** taken along the line **18-18** of **FIG. 14**.

[00241] FIG. 19 is a cross-sectional view of the pipetting system of **FIG. 14** taken along the line **19-19** of **FIG. 14**.

[00242] FIG. 20 is a fragmentary, cross-sectional view of a pipetting system according to further embodiments.

[00243] FIG. 21 is an enlarged, fragmentary, cross-sectional view of the pipetting system of **FIG. 20** wherein an interchamber valve thereof is in an open position.

[00244] FIG. 22 is an enlarged, fragmentary, cross-sectional view of the pipetting system of **FIG. 20** wherein the interchamber valve is in a closed position.

[00245] FIGS. 23 and **24** are fragmentary, cross-sectional views of the pipetting system of **FIG. 20** wherein a plunger member thereof is disposed in different positions.

[00246] FIG. 25 is a fragmentary, cross-sectional view of a pipetting system according to further embodiments.

[00247] FIGS. 26 and **27** are enlarged, fragmentary, cross-sectional views of the pipetting system of **FIG. 25** illustrating operations of the pipetting system.

[00248] FIG. 28 is a cross-sectional view of a pipetting system according to further embodiments of the technology.

[00249] FIGS. 29-32 are cross-sectional views of a pipettor of the pipetting system of **FIG. 28** illustrating operations of the pipetting system.

[00250] FIG. 33 is an exploded, cross-sectional view of the pipettor of **FIG. 28**.

[00251] FIG. 34 is a cross-sectional view of an air displacement tip for use with the pipetting system of **FIG. 28**.

[00252] FIG. 35 is an exploded, cross-sectional view of positive displacement tip for use with the pipetting system of **FIG. 28**.

[00253] FIG. 36 is a cross-sectional view of a pipetting system according to further embodiments of the technology.

[00254] FIG. 37 is a schematic perspective view illustrating a further example of an automated liquid handling system according to some embodiments.

[00255] FIG. 38 is an enlarged side view illustrating a conductive pipette tip according to some embodiments.

[00256] FIGS. 39A, 39B, and **39C** are cross-sectional views illustrating embodiments of the tip member of **FIG. 38**.

[00257] FIGS. 40A, **40B**, and **40C** are cross-sectional views illustrating embodiments of the conductive electrode in various "crown" shapes.

[00258] FIG. 41 is a diagram illustrating changes in capacitance with vertical position of a pipette tip including a conductive electrode and non-conductive tip bottom in accordance with some embodiments.

[00259] FIG. 42 is a schematic diagram illustrating an automated pipetting system configured for evaporation detection and compensation according to some embodiments.

[00260] FIG. 43A is a schematic diagram illustrating evaporation detection according to some embodiments.

[00261] FIG. 43B is an enlarged view of the orifice of the pipette tip of **FIG. 43A**, illustrating liquid bead formation due to evaporation.

[00262] FIG. 44A is a graph illustrating changes in pressure and displaced volume in operations for evaporation detection operations according to some embodiments.

[00263] FIG. 44B is a graph illustrating changes in pressure and displaced volume in operations for evaporation detection operations according to further embodiments.

[00264] FIG. 45 is a flowchart diagram illustrating operations for evaporation detection in a pipette tip according to some embodiments.

[00265] FIGS. 46A and **46B** re flowchart diagrams illustrating operations for evaporation compensation in a pipette tip according to some embodiments.

[00266] FIG. 47 is a side view illustrating a dual metering pipettor that may be used in an automated pipetting system according to some embodiments.

[00267] FIG. 48 is an enlarged schematic diagram illustrating a dual metering pipettor according to some embodiments.

[00268] FIG. 49 is a simplified schematic diagram illustrating the plunger and manifold assembly of a dual metering pipettor according to some embodiments.

[00269] FIG. 50 is an enlarged schematic diagram illustrating the manifold and flow rate sensor of the dual metering pipettor of **FIG. 49** according to some embodiments.

[00270] FIG. 51 is an enlarged perspective view further illustrating a manifold assembly according to some embodiments.

[00271] FIG. 52 is a schematic diagram illustrating connections of pressure sensors in dual metering pipettor according to some embodiments.

[00272] FIG. 53 is a schematic diagram illustrating operation of a dual metering pipettor according to some embodiments.

[00273] FIG. 54 is a cross-sectional view of a pipetting system and PD pipette tip according to further embodiments of the technology, wherein the PD pipette tip is in an extended position.

[00274] FIG. 55 is a cross-sectional view of the pipetting system of **FIG. 54** wherein the PD pipette tip is in a retracted position.

[00275] FIG. 56 is an exploded, cross-sectional view of the PD pipette tip of **FIG. 54**.

[00276] FIG. 57 is an enlarged, cross-sectional view of the PD pipette tip of **FIG. 54** showing an indexing mechanism of the PD pipette tip.

[00277] FIG. 58 is cross-sectional view of the PD pipette tip taken along the line **58-58** of **FIG. 54**.

[00278] FIG. 59 is cross-sectional view of the PD pipette tip taken along the line **59-59** of **FIG. 57**.

[00279] FIG. 60 is an exploded view of a pipetting system including a positive displacement pipette tip according to some embodiments.

[00280] FIG. 61 is an exploded, bottom perspective view of the positive displacement pipette tip of **FIG. 60**.

[00281] FIG. 62 is a cross-sectional, perspective view of the positive displacement pipette tip of **FIG. 60** taken along the line **62-62** of **FIG. 60**.

[00282] FIG. 63 is a cross-sectional view of a tip body forming a part of the positive displacement pipette tip of **FIG. 60** taken along the line **62-62** of **FIG. 60**.

[00283] FIG. 64 is a side view of a piston forming a part of the positive displacement pipette tip of **FIG. 60**.

[00284] FIG. 65 is a cross-sectional view of an interlock insert forming a part of the positive displacement pipette tip of **FIG. 60** taken along the line **62-62** of **FIG. 60**.

[00285] FIGS. 66-75 are schematic, cross-sectional views of the pipetting system of **FIG. 60** illustrating operations using the pipetting system.

Detailed Description

[00286] With reference to **FIGS. 1-13**, an example pipetting system **101** according to certain embodiments of the present technology is shown. The pipetting system **101** forms a part of an automated liquid handling system **10** (**FIG. 1**) according to the illustrated embodiments of the present technology. However, it shall be understood that the disclosed methods, systems, and apparatus are not limited to the liquid handling system **10** or use therein, and the present disclosure is applicable to other systems and applications where it is desired to aspirate and/or dispense liquid volumes. The pipetting system **101** aspirates and dispenses liquid volumes within the liquid handling system **10**.

[00287] With reference to **FIG. 1**, the illustrative liquid handling system **10** includes a platform or deck **12**, a frame **14**, a controller **20**, an analytical instrument **16**, a pipetting module **30**, a pipetting module positioner **34A**, and the pipetting system **101**. The pipetting system **101** includes one or more pipettors **100**. One or more receptacles, reservoirs, or containers **36** may be provided in the liquid handling system **10** to hold liquid samples.

[00288] For the purpose of discussion and as indicated in **FIGS. 1** and **3**, the liquid handling system **10** includes a workspace that defines a Z-axis corresponding to vertical, and orthogonal X- and Y-axes that together define a horizontal plane.

[00289] The pipetting module **30** may include a housing, support or base **32**. In the illustrated embodiment, a plurality of pipettors **100** are mounted on the base **32**. However, in other embodiments, the pipetting module **30** may carry only a single pipettor **100**. The pipettors **100** may be arranged in a single row or in a prescribed X-Y array, for example. The pipetting module positioner **34A** is operable to move the pipetting module **30** about the deck **12**. The pipetting module **30** may include one or more pipettor actuators **34B** to selectively lower and raise (extend and retract) the pipettors **100** with respect to the base **32** and/or to raise and lower the base **32** with respect to the deck **12**. The pipetting module positioning system **34A** and the actuator(s) **34B** may be controlled by the controller **20**.

[00290] With reference to **FIG. 3**, and as discussed in more detail herein, each pipettor **100** may be understood to have a lengthwise axis **A-A** and a distal end portion **112A**. Each pipettor **100** includes a shaft **112** that terminates at a distal end portion **112A**. In use in accordance with a system according to **FIG. 1**, each pipettor **100** can be raised and lowered along its lengthwise axis **A-A** by the pipettor actuator(s) **34B**. In some embodiments, the axis **A-A** is substantially parallel to the vertical axis **Z-Z**.

[00291] Operations described herein can be executed by or through the controller **20**. The actuators **34A**, **34B**, as well as the actuators **128A**, **148A** discussed below, and other devices of the liquid handling system **10** can be electronically controlled. According to some embodiments, the controller **20** programmatically executes some, and in some embodiments all, of the steps described. According to some embodiments, the movements of the actuators **34A**, **34B** are fully automatically and programmatically executed by the controller **20**. The controller **20** may be provided with an HMI **22** to receive user commands. The controller **20** may comprise one or more controllers.

[00292] The pipetting system **101** includes the pipettor(s) **100** and one or more pipette tips **160**. In the illustrative embodiment, each pipette tip **160** is mounted on a respective one of the pipettors **100** in the manner discussed below. In some embodiments, the pipette tips **160** are removable and replaceable on the pipettors **100**, and may be effectively disposable or consumable components of the pipetting system **101**. However, in other embodiments, the pipette tips **160** may be omitted and the structures and functionalities of the pipette tips **160** may be provided as integral parts of the pipettors **100**.

[00293] The pipetting system **101** may include one or more pipettors **100** on the pipettor module **30**. The pipettors **100** may be constructed and operate in the same manner, and it will be appreciated that the description of a representative one of the pipettors **100** that follows may apply equally to each of the pipettors **100**. If multiple pipettors **100** are provided, the pipettors **100** may be operated independently of one another or in tandem.

[00294] With reference to **FIGS. 2-4**, the pipettor **100** includes a frame **108**, an interface **109**, a pipetting channel **102**, a pipettor orifice **104**, a pressure control system **106,** a shaft **112**, an ejector mechanism **151**, a tip mount feature or adaptor **156**, and a manifold **175**. The pressure control system **106** includes a first plunger mechanism **110**, a second plunger mechanism **130**, and an air flow control system **171**. In the illustrative embodiment, the pipette tip **160** includes a pipetting orifice **162** and a liquid collection volume **165** that are in fluid communication with the pipetting channel **102**. The shaft **112** has a lengthwise or main axis **A-A**. As discussed herein, the pipettor **100** is operative to selectively operate the first

plunger mechanism **110** or the second plunger mechanism **130**, or the first plunger mechanism **110** and the second plunger mechanism **130**, to change a pressure in the pipetting channel **102** to aspirate or dispense a liquid volume. The first plunger mechanism **110** and the second plunger mechanism **130**, may be understood to be operable independently of and in parallel with one another to change a pressure in the pipetting channel **102** to aspirate or dispense a liquid volume.

[00295] The components of the pipettor **100** may be mounted on the frame **108**, which is in turn mounted on the pipettor module base **32**. The electrical interface **109** may be operably mated to an electrical interface of the pipettor module base **30** or another component of the liquid handling system **10** to provide electrical power to the pipettor **100** and control or data communications interconnection between the pipettor **100** and other components of the liquid handling system **10** (*e.g.*, the analytical instrument **16** and/or remote controller(s)). The electrical interface **109** may include a printed circuit board (PCB).

[00296] As noted above, the controller **20** may include one or more controllers, which may be distributed within the liquid handling system **10**. In some embodiments, the controller **20** includes one or more controllers integral with or embodied in the pipettor **100** and operative to execute some or all of the pipettor control functions described herein. In some embodiments, these controller or controllers is/are embodied in and/or on the PCB **109**.

[00297] With reference to **FIGS. 2-5**, the first plunger mechanism **110** includes the shaft **112**, a guide sleeve **118**, a plunger assembly **122** (including a first plunger **120**), a first annular seal (*e.g.*, an O-ring) **126**, a second annular seal (*e.g.*, an O-ring) **127**, and a first linear drive mechanism **128**.

[00298] The shaft **112** serves as a barrel for the first plunger **120**. The shaft **112** defines a barrel bore **114** aligned with the axis **A-A** and extending from a first end **114A** to an opposing second end **114B** (**FIG. 4**). A top opening or port **114D** is defined at the second end **114B** and fluidly communicates with the bore **114**. The pipettor orifice **104** is defined at the first end **114A** and fluidly communicates with the bore **114**.

[00299] The plunger assembly **122** (**FIG. 5**) includes an upper sleeve **124** and the first plunger **120** affixed to the upper sleeve **124** at a leading end of the upper sleeve **124**. A bore **124A** is defined in the upper sleeve **124**. The first plunger **120** has a leading end **120A** (**FIG. 4**). The first plunger **120** is mounted in the guide sleeve **118** and the barrel bore **114** such that the first plunger **120** can slidably translate relative to the shaft **112** along a first plunger axis **P1-P1** in an extension direction **E1** and an opposing retraction direction **E2**. In

some embodiments, the first plunger axis **P1-P1** is substantially coincident with the shaft axis **A-A**.

[00300] The first O-ring **126** (**FIG. 4**) forms an airtight seal between the outer diameter of the first plunger **120** and the manifold **175**. The first plunger **120** is able to slide through the O-ring **126**. The second O-ring **127** forms an airtight seal between the outer diameter of the shaft **112** and the manifold **175**.

[00301] The outer diameter **D1** (**FIG. 6**) of the first plunger **120** is less than the inner diameter **D2** (**FIG. 6**) of the bore **114** so that the first plunger **120** and the bore **114A** are radially spaced apart along their lengths. This spacing defines a tubular or annular air passage or channel **103** (**FIGS. 4** and **6**) between the outer diameter of the first plunger **120** and the inner diameter of the bore **114**. The channel **103** extends from the O-ring **126** to the pipettor orifice **104**.

[00302] The linear drive mechanism **128** includes an actuator **128A**, a spindle **128B**, a spindle nut **128C**, and a first plunger position sensor **129** (**FIG. 3**). The actuator **128A** may be an electric motor. The spindle **128B** is coupled to the output of the motor **128A** to be rotationally driven thereby. In at least some embodiments, the spindle **128B** is operatively coupled to the output of the motor **128A** via a planetary gear box (not shown). The spindle nut **128C** is affixed to the upper end of the upper sleeve **124**.

[00303] The motor **128A** is operable to drive the spindle **128B** in each of a first direction (*e.g.*, clockwise) and an opposite second direction (*e.g.*, counterclockwise). When the motor **128A** drives the spindle **128B** in the first direction, the spindle nut **128C**, the upper sleeve **124**, and the first plunger **120** are thereby pulled in the retraction direction **E2** relative to the bore **114**. When the motor **128A** drives the spindle **128B** in the second direction, the spindle nut **128C**, the upper sleeve **124**, and the first plunger **120** are thereby pushed in the extension direction **E1** relative to the bore **114**. The spindle **128B** translates into and out from the upper sleeve bore **124A** as the plunger **120** travels.

[00304] The first plunger position sensor **129** is connected to the controller **20** to detect and monitor the position of the first plunger **120** in the bore **114**. The first plunger position sensor **129** may be an encoder, for example. The first plunger sensor **129** may be electrically connected to the PCB **109**. The PCB **109** may contain a controller (which forms one or more of the controller(s) **20**) that steers the motor **128A**.

[00305] In use, a first chamber **115** (**FIG. 4**) is defined in the barrel bore **114** substantially between the leading end **120A** of the first plunger **120** and the first end **114A** of the barrel bore **114**. As the first plunger **120** is driven in the direction **E1**, air volume is

displaced from the first chamber **115**, and the effective volume of the first chamber **115** is reduced. As the first plunger **120** is driven in the direction **E2**, air volume is replaced in the first chamber **115**, and the effective volume of the first chamber **115** is increased.

[00306] The first plunger **120** may be formed of any suitable material. In some embodiments, the first plunger **120** is formed of stainless steel.

[00307] The shaft **112** may be formed of any suitable material. In some embodiments, the shaft **112** is formed of stainless steel.

[00308] The spindle **128B** and the spindle nut **128C** may be formed of any suitable material(s). In some embodiments, the spindle **128B** is formed of ceramic and the spindle nut **128C** is formed of brass.

[00309] The second plunger mechanism **130** (**FIGS. 3** and **5**) includes a barrel **132**, an end plug **136**, a second plunger **140**, a first annular seal (*e.g.*, an O-ring) **146**, a second annular seal (*e.g.*, an O-ring) **147**, and a second linear drive mechanism **148**. In some embodiments (as illustrated, for example) and as discussed in more detail below, the second plunger **140** is larger than the first plunger **120**.

[00310] The barrel **132** defines a barrel bore **134**. The barrel bore **134** may be laterally offset from the axis **A-A**. The barrel bore **134** extends from a first end **134A** to an opposing second end **134B**. The end plug **136** is located at the first end **134A**. A fluid channel **136A** is defined in the end plug **136**.

[00311] The second plunger **140** has a leading end **140A**. An axially extending plunger bore **142** is defined in the plunger **140** and is closed at the end **140A**. The O-ring **146** (**FIGS. 5** and **7**) is mounted on the plunger **140** at the leading end **140A**. The O-ring **146** forms a sliding seal between the outer diameter of the second plunger **140** and the barrel **132**, and translates with the second plunger **140**.

[00312] The second plunger **140** is mounted in the barrel bore **134** such that the second plunger **140** can slidably translate relative to the barrel bore **134** along a second plunger axis **P2-P2** in an extension direction **E3** and an opposing retraction direction **E4**. In some embodiments, the second plunger axis **P2-P2** is laterally offset from the shaft axis **A-A**.

[00313] The second linear drive mechanism **148** (**FIG. 3**) includes an actuator **148A**, a spindle **148B**, a spindle nut **148C**, and a first plunger position sensor **149**. The actuator **148A** may be an electric motor. The spindle **148B** is coupled to the output of the motor **148A** to be rotationally driven thereby. The spindle nut **148C** is affixed to the upper end of the second plunger **140**.

[00314] The motor **148A** is operable to drive the spindle **148B** in each of a first direction (*e.g.*, clockwise) and an opposite second direction (*e.g.*, counterclockwise). When the motor **148A** drives the spindle **148B** in the first direction, the spindle nut **148C** and the first plunger **140** are thereby pulled in the retraction direction **E4** relative to the bore **134**. When the motor **148A** drives the spindle **148B** in the second direction, the spindle nut **148C** and the second plunger **140** are thereby pushed in the extension direction **E3** relative to the bore **134**. The spindle **148B** translates into and out from the plunger bore **142** as the plunger **140** travels.

[00315] The second plunger position sensor **149** is connected to the controller **140** to detect and monitor the position of the first plunger **140** in the bore **134**. The second plunger position sensor **149** may be an encoder, for example. The second plunger position sensor **149** may be electrically connected to the PCB **109**. The PCB **109** may contain a controller (which forms one or more of the controller(s) **20**) that steers the motor **148A**.

[00316] While the illustrated first and second linear drive mechanisms **128**, **148** each include a rotary motor, spindle and spindle nut arrangement, linear drive mechanisms of other types may be used instead in some embodiments. For example, but not limited to, a direct linear motor.

[00317] In use, a second chamber **135** (**FIG. 5**) is defined in the barrel bore **134** substantially between the leading end **140A** of the second plunger **140** and the first end **134A** of the barrel bore **134**. As the first plunger **140** is driven in the direction **E3**, air volume is displaced from the second chamber **135**, and the effective volume of the second chamber **135** is reduced. As the second plunger **140** is driven in the direction **E4**, air volume is replaced in the second chamber **135**, and the effective volume of the second chamber **135** is increased.

[00318] The second plunger **140** may be formed of any suitable material. In some embodiments, the second plunger **140** is formed of aluminum.

[00319] The barrel **132** may be formed of any suitable material. In some embodiments, the barrel **132** is formed of aluminum.

[00320] The spindle **148B** and the spindle nut **148C** may be formed of any suitable material(s). In some embodiments, the spindle **148B** may be formed of ceramic or stainless steel and the spindle nut **148C** may be formed of plastic or a high-temperature resistant thermoplastic, *e.g.*, Polyether ether ketone (PEEK).

[00321] The tip adaptor **156** is configured to removably secure the pipette tip **160** (and suitably constructed replacement pipette tips) to the end **112A** of the shaft **112**. In some embodiments, the tip adaptor **156** forms an air-tight, pressure-tight seal between the mount

section **166** and the shaft **112**. In the illustrated embodiment, the tip adaptor **156** includes annular ribs **156A** configured to form a secure friction fit with a mount section **166** of the pipette tip, as well as an air-tight, pressure-tight seal between the mount section **166** and the shaft **112**. However, other suitable pipette tip mounting structures may be provided. For example, the tip adaptor and the pipette tip may include interlocking features. The tip adaptor **156** may be integrally formed with the shaft or may be formed as a separate component.

[00322] The ejector mechanism **151** (**FIGS. 5** and **13**) includes an ejector member or sleeve **150** slidably mounted on a guide rod **152**. A spring **154** biases the ejector sleeve **150** in a downward direction **E6** toward the shaft end **112A**. When the pipetting tip **160** is picked up, the ejector sleeve **150** is pushed upwards (direction **E5**). This upward movement and the sleeve positioning may be used with a magnet on the sleeve **150** and a Hall effect sensor to detect the presence of the pipette tip **160**. An upper end **150B** of the ejector sleeve **150** is configured to engage the lower end of the upper sleeve **124**. A lower end **150A** of the ejector sleeve **150** is configured to engage the pipette tip **160**, as discussed below. In use, when the plunger assembly **122** is driven downward (direction **E1**) sufficiently by the first linear drive mechanism **128**, it will abut the upper end **114B** and drive the ejector sleeve **150** in an ejecting direction **E6** to thereby force the pipette tip **160** off of the shaft **112**.

[00323] The pipette tip **160** (**FIG. 8**) is an example of a pipette tip that may be used with the pipettor **100**. However, it will be appreciated that pipette tips of other designs may be used instead.

[00324] The pipette tip **160** is a tubular body having a distal end **160A** and a proximal end **160B**. The pipette tip **160** defines a tip volume or passage **164** extending from the pipetting orifice **162** (at the distal end **160A**) to an interface opening **163** (at the proximal end **160B**). The mount section **166** is provided at the proximal end **160B**. As discussed herein, a portion (some or all) of the tip passage **164** may serve as a liquid collection volume **165** in use.

[00325] With reference to **FIG. 5**, the air flow control system **171** includes a valve **178**, a first channel **172**, a second channel **174**, and a third channel **176**.

[00326] The first channel **172** fluidly connects or couples the second chamber **135** (via the channel **136A** in the end plug **136**) to the valve **178**.

[00327] The second channel **174** fluidly connects or couples the valve **178** to a port **174A** to the ambient atmosphere.

[00328] With reference to **FIG. 4**, the third channel **176** fluidly connects or couples the valve **178** to the first barrel bore **114**. More particularly, in the illustrative embodiment, the third channel **176** terminates at a port **176A** between the O-rings **126**, **127**. The port **176A** is in fluid communication with the barrel port **114D**, which in turn fluidly communicates with the annular channel **103** between the first plunger **120** and the shaft **112**. The channel **103** permits airflow through the pipetting channel **102** (*i.e.*, through the bore **114**) from the barrel port **114D** to the pipettor orifice **104**.

[00329] Some or all of the channels **172**, **174**, **176** may be formed in whole or in part in the manifold **175**. In some embodiments, each channel **172**, **174**, **176** has a diameter in the range of from about 0.2 to 1 mm.

[00330] The pressure control system **106** may also include a pipetting channel pressure sensor **179** (**FIG. 5**) fluidly coupled to the pipetting channel **102** via the channel **176**.

[00331] The controller **20** is operative to control the valve **178** to assume first, second, and third valve states. The channel **176** is not fluidly connected to the atmosphere port **174A** in any of the three valve states. When the second chamber **135** is fluidly connected to the first bore **114**, the second chamber **135** is fluidly connected to the pipetting channel **102** and the pipettor orifice **104** via the first bore **114**.

[00332] In the first valve state, the valve **178** closes the channel **172** from the channels **174**, **176**. As a result, the second chamber **135** is not fluidly connected to the first bore **114** (and thereby the pipetting channel **102**) or the atmosphere port **174A**.

[00333] In the second valve state, the valve **178** closes the channel **172** from the channel **176** and opens the channel **172** to the channel **174**. As a result, the second chamber **135** is not fluidly connected to the first bore **114** (and thereby the pipetting channel **102**), and the second chamber **135** is fluidly connected to the atmosphere port **174A**.

[00334] In the third valve state, the valve **178** closes the channel **172** from the channel **174** and opens the channel **172** to the channel **176**. As a result, the second chamber **135** is fluidly connected to the first bore **114** (and thereby the pipetting channel **102**), and the second chamber **135** is not fluidly connected to the atmosphere port **174A**.

[00335] The liquid handling system **10** and the pipetting system **100** may be used as follows in accordance with some methods to aspirate and/or dispense one or more liquid samples. Generally, the first and second plunger mechanisms **110**, **130** are used to displace air volumes in their respective chambers **115**, **135** and thereby correspondingly change a

pressure in the pipetting channel **102** to aspirate or dispense a liquid sample into or from the liquid collection volume **165**.

[00336] The pipettor **100** may be operated in each of several different modes of operation. The operator or controller **20** may select and implement the mode of operation depending on the conditions or parameters of the aspirating or dispensing task.

[00337] Typically, the pipettor **100** will initially be set (*e.g.*, by the controller **20**) in a start position as shown in **FIG. 9**. In the start position, the first plunger **120** is positioned in its lowermost position. In some embodiments and as shown, in this lowermost, start position of the first plunger **120**, the leading end **120A** of the first plunger **120** is substantially flush or axially coincident with the pipettor orifice **104**. In the start position, the second plunger **140** is positioned in its lowermost position. In some embodiments and as shown, in this lowermost, start position of the second plunger **140**, the leading end **140A** of the second plunger **140** is substantially flush or axially coincident with the pipettor orifice end plug **136**.

[00338] A pipette tip **160** is mounted on the tip adaptor **156**, as shown in **FIG. 9**.

[00339] The controller **20** may then operate the actuator(s) **34A, 34B**, for example, to position the pipette tip **160** over a liquid sample **LS**. The sample **LS** may be disposed in a container **36**, for example. The controller **20** may then operate the actuator **34B**, for example, to lower the distal end **160A**, and thereby the pipetting orifice **162**, into the sample **LS**. In some embodiments, the distal end **160A**, and thereby the pipetting orifice **162**, are immersed in the sample **LS** to at least a prescribed depth to ensure that the pipetting orifice **162** remains immersed in the sample during aspiration.

[00340] With the pipettor **100** in the start position and the pipetting orifice **162** immersed, the pipetting system **101** may be operated in a first aspirating mode to aspirate a portion of the sample **LS**. In the first aspirating mode, the valve **178** is set in the first valve state so that the pipetting channel **102** is fluidly sealed from the second chamber **135**. The first drive mechanism **128** is then actuated to draw the first plunger **120** away from the pipettor orifice **104** in the retraction direction **E2** as shown in **FIG. 10**, for example. The retraction of the first plunger **120** expands the effective air volume of the first chamber **115**, thereby generating a negative pressure at the pipettor orifice **104**. The negative pressure draws a liquid sample volume **LV** of the liquid sample **LS** into the liquid collection volume **165** (in the tip passage **164**) of the pipette tip **160**. An air volume or air cushion **AC** may remain in the tip passage **164** and the first chamber **115** between the proximal end of the liquid sample volume **LV** and the leading end **120A** of the first plunger **120**.

[00341] The pipettor **100** may then be used to dispense the liquid sample volume **LV** in a first dispensing mode. In order to dispense the liquid sample volume **LV**, the valve **178** is set or retained in the first valve state. The first drive mechanism **128** is actuated to push the first plunger **120** toward the pipettor orifice **104** in the extension direction **E1**. The extension of the first plunger **120** displaces air volume from the first chamber **115**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV**. The positive pressure expels the liquid sample volume **LV** from the liquid collection volume **165** through the pipetting orifice **162**. The air cushion **AC** may remain between the proximal end of the liquid sample volume **LV** and the leading end **120A** of the first plunger **120** until the liquid sample volume **LV** is fully dispensed.

[00342] Alternatively, the pipetting system **101** may be operated in a second aspirating mode to aspirate a portion of the liquid sample **LS**. In the second aspirating mode, the valve **178** is set in the third valve state so that the second chamber **135** is fluidly connected to the pipetting channel **102** and is fluidly sealed from the atmosphere port **174A**. With the pipettor **100** in the start position and the pipetting orifice **162** immersed, the second drive mechanism **148** is actuated to draw the second plunger **140** away from the end plug **136** in the retraction direction **E4** as shown in **FIG. 11**, for example. The retraction of the second plunger **140** expands the effective air volume of the second chamber **135**, thereby generating a negative pressure at the pipettor orifice **104** (via the channel **172**, the valve **178**, the channel **176** and the bore **114**). The negative pressure draws a liquid sample volume **LV** of the liquid sample **LS** into the liquid collection volume **165** (in the tip passage **164**) of the pipette tip **160**. An air volume or air cushion **AC** may remain in the tip passage **164** between the proximal end of the liquid sample volume **LV** and the leading end **120A** of the first plunger **120**.

[00343] The pipettor **100** may then be used to dispense the liquid sample volume **LV** in a second dispensing mode. In order to dispense the liquid sample volume **LV**, the valve **178** is set or retained in the third valve state. The second drive mechanism **148** is actuated to push the second plunger **140** toward the end plug **136** in the extension direction **E3**. The extension of the second plunger **140** displaces air volume from the second chamber **135**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV** (via the channel **172**, the valve **178**, the channel **176** and the bore **114**). The positive pressure expels the liquid sample volume **LV** from the liquid collection volume **165** through the pipetting orifice **162**. An air cushion **AC** may remain between the proximal end of the liquid

sample volume **LV** and the leading end **120A** of the first plunger **120** until the liquid sample volume **LV** is fully dispensed.

[00344] Alternatively, the pipetting system **101** may be operated in a third aspirating mode to aspirate a portion of the liquid sample **LS**. In the third aspirating mode, the valve **178** is set in the third valve state so that the second chamber **135** is fluidly connected to the pipetting channel **102** and is fluidly sealed from the atmosphere port **174A**. The first drive mechanism **128** is then actuated to draw the first plunger **120** away from the pipettor orifice **104** in the retraction direction **E2**, as shown in **FIG. 12**, for example. The retraction of the first plunger **120** expands the effective air volume of the first chamber **115**, thereby generating a negative pressure at the pipettor orifice **104**. Additionally, and simultaneously with the retraction of the first plunger **120**, the second drive mechanism **148** is actuated to draw the second plunger **140** away from the end plug **136** in the retraction direction **E4**, as also shown in **FIG. 12**. The retraction of the second plunger **140** expands the effective air volume of the second chamber **135**, thereby also generating a negative pressure at the pipettor orifice **104**. As a result, the displacements of the two plungers **120**, **140** both create a negative pressure that draws a liquid sample volume **LV** of the liquid sample **LS** into the liquid collection volume **165** (in the tip passage **164**) of the pipette tip **160**. An air volume or air cushion **AC** may remain in the tip passage **164** between the proximal end of the liquid sample volume **LV** and the leading end **120A** of the first plunger **120**.

[00345] The pipettor **100** may then be used to dispense the liquid sample volume **LV** in a third dispensing mode. In order to dispense the liquid sample volume **LV**, the valve **178** is set or retained in the third valve state. The first drive mechanism **128** is actuated to push the first plunger **120** toward the pipettor orifice **104** in the extension direction **E1**. The extension of the first plunger **120** displaces air volume from the first chamber **115**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV**. Additionally, and simultaneously with the extension of the first plunger **120**, the second drive mechanism **148** is actuated to push the second plunger **140** toward the end plug **136** in the extension direction **E3**, which displaced air volume from the second chamber **135**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV** (via the channel **172**, the valve **178**, the channel **176** and the bore **114**). As a result, the displacements of the two plungers **120**, **140** both create a positive pressure that expels the liquid sample volume **LV** from the liquid collection volume **165** through the pipetting orifice **162**. An air cushion **AC** may remain between the proximal end of the liquid sample volume

LV and the leading end **120A** of the first plunger **120** until the liquid sample volume **LV** is fully dispensed.

[00346] Alternatively, the pipetting system **101** may be operated in a fourth aspirating mode to aspirate a portion of the liquid sample **LS**. In the fourth aspirating mode, the valve **178** is also set in the third valve state, and the first and second drive mechanisms **128**, **148** are operated to retract the plungers **120**, **140** in the manner described above for the third aspiration mode. However, in the fourth aspirating mode, the first plunger **120** and the second plunger **140** are retracted at different times from one another (*e.g.*, sequentially or alternately) rather than simultaneously.

[00347] Similarly, the pipetting system **101** may be operated in a fourth dispensing mode to dispense a portion of the liquid sample **LS**. In the fourth dispensing mode, the valve **178** is also set in the third valve state, and the first and second drive mechanisms **128**, **148** are operated to extend the plungers **120**, **140** in the manner described above for the third dispensing mode. However, in the fourth dispensing mode, the first plunger **120** and the second plunger **140** are extended at different times from one another (*e.g.*, sequentially or alternately) rather than simultaneously.

[00348] In some operations, the valve **178** is set in the second valve state to connect the second chamber **135** to the atmosphere port **174A**. The second drive mechanism **148** is then operated to position in the second plunger **140** in its start position. The air displaced from the chamber **135** by the second plunger **140** is expelled through the atmosphere port **174A** so that the air volume in the chamber **135** is not pressurized. The valve **178** may then be set in the first valve state or the second valve state to re-seal the second chamber **135** to the atmosphere port **174A** for an aspirating or dispensing operation.

[00349] In operations according to some embodiments, the second plunger **140** and the valve **178** are cooperatively operated repetitive or cycling pump in order to aspirate and dispense larger volumes, for example. In this case, the valve **178** is switched between its second and third valve states between movements of the second plunger **140**. More particularly, the valve **178** and the second plunger **140** may be operated as follows. With the valve **178** in the third valve state (fluidly connecting the second chamber **135** to the pipetting channel **102**, and closing the second chamber **135** from the atmosphere port **174A**), the second plunger **140** is retracted (direction **E4**) to draw liquid sample volume **LV** into the pipette tip **160**. The valve **178** is then placed in the second valve state (fluidly connecting the second chamber **135** to the atmosphere port **174A**, and closing the second chamber **135** from the pipetting channel **102**). With the valve **178** in the second valve state, the second plunger

140 is extended (direction **E3**) to expel air from the second chamber **135** and return the second plunger **140** to or toward its starting position. Because the valve **178** is in the second valve state, the aspirated liquid sample volume **LV** remains in the pipette tip **160** (*i.e.*, is not dispensed by the extension of the second plunger **140**. The valve **178** is then again placed in the third valve state and, with the valve **178** in the third valve state, the second plunger **140** is again retracted (direction **E4**) to draw additional liquid sample volume **LV** into the pipette tip **160**. This sequence may be repeated multiple times to incrementally aspirate liquid sample volumes **LV** into the pipette tip **160**. For example, the sequence may be repeated five times, each aspirating 1 ml, to aspirate a total of 5 ml into the pipette tip **160**. The operation may also be reversed to dispense increments of a larger volume from the pipette tip **160** (*e.g.*, to dispense a series of five 1 ml liquid volumes from a pipette tip **160** containing 5 ml of the liquid sample).

[00350] As discussed above, the pipetting system **101** aspirates liquid sample by decreasing the pressure in the pipetting channel and dispenses liquid sample by increasing the pressure in the pipetting channel **102**. However, the pressure in the pipetting channel **102** may fluctuate in response to other actions or conditions in the procedure. For example, in some embodiments for aspirating, the pressure in the pipetting channel **102** increases as the plunger **120** or **140** is retracted. After the plunger **120**, **140** stops, the inflow into the pipette tip **160** stops and the pressure drops associated with the plunger movement goes to zero. However, the pressure in the pipetting channel **102** may remain negative, caused by the weight of the liquid sample in the pipette tip **160**. After the pipette tip **160** is removed from the liquid sample supply, the pressure in the pipetting channel **102** may drop further slightly because of diminished buoyancy. The pressure in the pipetting channel **102** may then increase slowly after that, caused by evaporation of the liquid sample in the pipette tip **160**. Therefore, it will be appreciated that the pressure changes in the pipetting channel **102** may be caused or determined by phenomena other than and in addition to the movement of the plungers **120**, **140**.

[00351] The aspirating modes and dispensing modes described above can be implemented as desired in different combinations. For example, the third aspirating mode (simultaneous plunger retraction) may be used to aspirate a liquid sample volume, and the fourth dispensing mode (sequential plunger extension) may be used to dispense the liquid sample volume.

[00352] The pipettor **100** may be relocated as desired between steps of aspirating and dispensing. An aspirating procedure may include aspirating a liquid volume from a single

liquid sample source or multiple liquid sample sources. A dispensing procedure may include dispensing a liquid volume to a single location or to multiple locations. For example, a quantity of the liquid sample may be aspirated from a single source, and then smaller quantities of the aspirated liquid sample may be dispensed into respective different locations (*e.g.*, wells of a well plate). In some embodiments, the liquid sample volume **LV** (or a portion thereof) is dispensed by the pipettor **100** into the analytical apparatus **16**.

[00353] In some embodiments, the controller **20** automatically and programmatically operates the valve **178** and the actuators **128A**, **148A** to set the valve states and to extend and retract the plungers **120**, **140** as described herein.

[00354] In some embodiments, the controller **20** receives pressure signals from the pipetting channel pressure sensor **179** indicating the air pressure in the pipetting channel **102**. The controller **20** may continuously monitor the pressure in the pipetting channel **102**.

[00355] With reference to **FIG. 13**, the pipetting system **101** may be operated to automatically remove the pipette tip **160** from the pipettor **100** using the ejector mechanism **151**. In order to eject the pipette tip **160**, the controller **20** operates the first drive mechanism **128** to push the plunger assembly **122** in the extension direction **E6**. The leading end **124B** of the plunger sleeve **122** will engage the upper end **150B** of the ejector sleeve **150** and push the ejector sleeve **150** in the direction **E6** as the first drive mechanism **128** continues to drive the plunger assembly **122**. The lower end **150A** of the ejector sleeve **150** engages the mount section **166** of the pipette tip **160** and pushes the pipette tip **160** off of the tip adaptor **156**. In some embodiments, the controller **20** automatically and programmatically operates the actuator **128A** to eject the pipette tip **160**.

[00356] As described herein, the first and second plunger mechanisms **110**, **120** can be operated independently of one another or together to aspirate and dispense liquid sample volumes. The choice of which plunger mechanism(s) **120**, **140** to operate for a given aspirating or dispensing procedure can be a function of or tailored to the conditions or parameters of the aspirating or dispensing procedure. By employing dual plunger mechanisms, the volume range of the pipettor **100** can be enlarged, and process specific volume accuracy and precision can be supported without the need for multiple pipetting channels.

[00357] For example, when only a relatively small quantity of the liquid sample is to be aspirated or dispensed, the pipettor **100** may be operated in the first aspirating mode or first dispensing mode. The use of the smaller plunger **120** can provide higher resolution, and thereby better accuracy and precision.

[00358] When a relatively large quantity of the liquid sample is to be aspirated or dispensed, the pipettor **100** may be operated in the second aspirating mode or second dispensing mode. The use of the larger plunger **140** can enable the pipettor **100** to draw and hold a greater quantity of the liquid sample at once. The use of the larger plunger **140** can enable the pipettor **100** to aspirate or dispense the liquid sample at a higher rate.

[00359] When a relatively large quantity of the liquid sample is to be aspirated or dispensed, the pipettor **100** may also be operated in the third aspirating mode or third dispensing mode, as well as in the fourth aspirating mode or fourth dispensing mode. The use of the smaller plunger **120** and the larger plunger **140** together can enable the pipettor **100** to draw and hold an even greater quantity of the liquid sample at once. Displacing the smaller plunger **120** and the larger plunger **140** simultaneously can enable the pipettor **100** to aspirate or dispense the liquid sample at an even higher rate.

[00360] For example, in an illustrative embodiment, the first plunger **120** has a stroke distance **L1** (**FIG. 12**) of 25 mm and a diameter **D1** (**FIG. 6**) of 2 mm, so that the first plunger mechanism **110** can displace up to 55 microliters of air. In the illustrative embodiment, the second plunger **140** has a stroke distance **L5** (**FIG. 12**) of 45 mm and a diameter **D5** (**FIG. 7**) of 6 mm, so that the second plunger mechanism **130** can displace up to 1100 microliters of air. When operated in the first aspirating mode, the pipettor **100** can aspirate up to 55 microliters of liquid sample. When operated in the second aspirating mode, the pipettor **100** can aspirate up to 1100 microliters of liquid sample. When operated in the third or fourth aspirating mode, the pipettor **100** can aspirate up to 1155 microliters of liquid sample.

[00361] In some embodiments, the controller **20** automatically and programmatically executes the steps of operating the actuators **128A**, **148A** to extend and retract the plungers **120**, **140** and eject the pipette tip **160**.

[00362] In some embodiments, the controller **20** automatically and programmatically executes the steps of operating the actuators **34A**, **34B** to position the pipettor **100**.

[00363] As mentioned above, in some embodiments the second plunger **140** is larger than the first plunger **120**. The first plunger **120** has a cross-sectional area **A1** (**FIG. 6**) in a cross-sectional plane orthogonal to the first plunger axis **P1-P1** (*i.e.*, the axis along which the first plunger is translated to aspirate and dispense). The second plunger **140** has a cross-sectional area **A2** (**FIG. 7**) in a cross-sectional plane orthogonal to the second plunger axis **P2-P2** (*i.e.*, the axis along which the second plunger is translated to aspirate and dispense). In some embodiments (as illustrated, for example), the cross-sectional area **A2** of the second

plunger **140** is greater than the cross-sectional area **A1** of the first plunger **120**. In some embodiments, the cross-sectional area **A2** is at least three times the cross-sectional area **A1**.

[00364] In some embodiments, the cross-sectional area **A1** is in the range of from about 0.1 to 4 mm^2, and the cross-sectional area **A2** is in the range of from about 1.25 to 50 mm^2.

[00365] The smaller first plunger **120** displaces an air volume in the first chamber **115** at a first rate of air volume displacement per unit translation. The larger second plunger displaces an air volume in the second chamber **135** at a second rate of air volume displacement per unit translation. Because the larger plunger **120** has a greater cross-sectional area, the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation. In some embodiments, the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

[00366] In some embodiments, the first rate of air volume displacement per unit translation is in the range of from about 0.01 microliters/s to 100 microliters/s, and the second rate of air volume displacement per unit translation is in the range of from about 0.1 microliters/s to 2500 microliters/s.

[00367] In some embodiments, pipettor is configured such that the maximum air volume displaceable by the second plunger **140** (when the second plunger **140** is translated through its full stroke) is greater than the maximum air volume displaceable by the first plunger **120** (when the first plunger **120** is translated through its full stroke). In some embodiments, the maximum air volume displaceable by the second plunger **140** is at least ten times the maximum air volume displaceable by the first plunger **120**.

[00368] In some embodiments, the maximum air volume displaceable by the second plunger **140** is in the range of from about 10 microliters to 5000 microliters, and the maximum air volume displaceable by the first plunger **120** is in the range of from about 1 microliter to 100 microliters.

[00369] In some embodiments, the maximum air volume of the second chamber **135** (when the second plunger **140** is in its fully retracted position) is at least ten times the maximum air volume of the first chamber **115** (when the first plunger **120** is in its fully retracted position). In some embodiments, the maximum air volume of the second chamber **135** is in the range of from about 11 microliters to 5500 microliters, and the maximum air volume of the first chamber **115** is in the range of from about 1.5 microliters to 110 microliters.

[00370] In some embodiments and as shown in the illustrative embodiment of **FIGS. 2-7**, the first chamber **115** (**FIG. 4**; *i.e.*, the chamber containing the air volume displaced by the first plunger **120** as it translates) occupies a portion of the pipetting channel **102**. Accordingly, the first plunger **120** may be disposed in and travel through the pipetting channel **102**. In some embodiments, the distal end **120A** of the first plunger **120** is coincident with or extends past the pipetting orifice **104** when the first plunger **120** is fully extended. The provision of the first plunger **120** in the shaft **112** and the positioning of the distal end **120A** at the start position can help to minimize the death volume in the pipetting channel **102** and permit a more compact pipettor. The arrangement of the first plunger mechanism **110**, the shaft **112** and the ejection mechanism **151** also enables the use of a single drive mechanism to execute the aspirating/dispensing functions and the tip ejection function.

[00371] With reference to **FIGS. 14-19**, an example pipetting system **201** according to further embodiments of the present technology is shown. The pipetting system **201** can aspirate and dispense liquid volumes within a liquid handling system. The pipetting system **201** may be used in place of the pipetting system **101** in the automated liquid handling system **10** (**FIG. 1**), for example. However, it shall be understood that the disclosed methods, systems, and apparatus are not limited to the liquid handling system **10** or use therein, and the present disclosure is applicable to other systems and applications where it is desired to aspirate and/or dispense liquid volumes. The pipetting system **201** includes a pipettor **200**.

[00372] The pipetting system **201** includes one or more pipettors **200**. The pipettor(s) may be mounted on the pipettor module **30**. The pipettors **200** may be constructed and operate in the same manner, and it will be appreciated that the description of a representative one of the pipettors **200** that follows may apply equally to each of the pipettors **200**. If multiple pipettors **200** are provided, the pipettors **200** may be operated independently of one another or in tandem.

[00373] The pipetting system **201** includes the pipettor(s) **200**, the controller **20**, and one or more pipette tips **160** (as described herein with reference to **FIG. 8**). In some embodiments, the pipette tips **160** are removable and replaceable on the pipettors **200**, and may be effectively disposable or consumable components of the pipetting system **201**. However, in other embodiments, the pipette tips **160** may be omitted and the structures and functionalities of the pipette tips **160** may be provided as integral parts of the pipettors **200**. A filter media **169** may be provided in the pipette tip **160** (**FIG. 15**).

[00374] With reference to **FIGS. 14** and **15**, and as discussed in more detail herein, the pipettor **200** may be understood to have a lengthwise axis **A-A** and a distal end portion **212A**. The pipettor **200** includes a tubular barrel **210**, a pressure control system **206**, a pipetting channel **202**, a pipettor orifice **204**, a tip adaptor **214**. The barrel **210** extends from a distal end **210A** to as proximal end **210B**. The barrel **210** includes a shaft **212** that terminates at the distal end **210A**. The pipettor orifice **204** is located at the distal end **210A** and fluidly communicates with the pipetting channel **202**.

[00375] The pressure control system **206** system includes a barrel bore or passage **220**, a pressure relief port **228** to atmosphere, a plunger member **240** (including a front plunger **242** and a rear plunger **244**), a front seal **252**, a rear seal **254**, a plunger drive mechanism **258**, a pressure relief valve **255**, and a pressure sensor **256**.

[00376] The passage **220** is aligned lengthwise with the axis **A-A** and extends from a front end **220A** to an opposing rear end **220B**. With reference to **FIG. 15**, the passage **220** includes a front section **222D** and a rear section **224D**. The front seal **252** is located axially between the front section **222D** and the rear section **224D**. The rear seal **254** is located axially between the rear section **224D** and a rear opening **220E** at the rear end **210B**. A front chamber **222** is defined by the front section **222D** and the front seal **252** between the front seal **252** and the pipetting channel **202**. A rear chamber **224** is defined by the rear section **224D**, the front seal **252** and the rear seal **254** between the front seal **252** and the rear seal **254**.

[00377] The front and rear seals **252**, **254** may each be an annular seal (*e.g.*, an O-ring). The front O-ring **252** (or other type seal) defines a seal opening **252A** therein.

[00378] The plunger member **240** has a front or leading end **240A**, an opposing rear end **240B**, and an intermediate transition **246**. The front plunger **242** extends from a leading end **242A** (at the front end **240A**) to a rear end **242B** (at the transition **246**). The rear plunger **244** extends from a leading end **244A** (at the transition **246**) to a rear end **244B** (at the rear end **240B**).

[00379] The front plunger **242** and the rear plunger **244** are joined, merged, or connected at the transition **246**. In some embodiments, the front plunger **242** and the rear plunger **244** together form a unitary member. In some embodiments, the plungers **242**, **244** form a rigid, unitary member. In some embodiments, the front plunger **242** and the rear plunger **244** together form a monolithic member.

[00380] The plunger member **240** is mounted in the passage **220** such that the plunger member **240** can slidably translate relative to the barrel **210** along a plunger axis **P4-P4** in an

extension direction **E8** and an opposing retraction direction **E9**. In some embodiments, the plunger axis **P4-P4** is substantially coincident with the shaft axis **A-A**.

[00381] The plunger member **240** is slidable to translate (relative to the passage **220**, through a plunger member stroke) between a starting or fully extended position, as shown in **FIG. 14**, and a fully retracted position, as shown in **FIG. 17**. In the fully extended position, the front plunger **242** resides in the front chamber **222** with its leading end **242A** proximate the pipetting channel **202**, the rear plunger **244** resides in the rear chamber **224** with its leading end **244A** proximate the front O-ring **252**, and the front plunger **242** extends through the opening **252A** in the front O-ring **252**. The front O-ring **252** forms a stationary, airtight, pressure tight seal between the front O-ring **252** and the barrel **210**, and an airtight, pressure tight seal between the outer diameter of the front plunger **242** and the inner diameter of the front O-ring **252**. The front plunger **242** is able to slide through the front O-ring **252** while maintaining the airtight, pressure tight seal therewith. The rear O-ring **254** forms an airtight, pressure tight seal between the outer diameter of the rear plunger **244** and the barrel **210**. The rear plunger **244** is able to slide through the rear O-ring **254** while maintaining the airtight, pressure tight seal therewith.

[00382] In the illustrative pipettor **200**, the stroke of the plunger member **240** corresponds to the strokes of the front plunger **242** and the rear plunger **244**. Referring to **FIG. 17**, the front plunger **242** is translatable relative to the passage **220** through a front plunger stroke **SF**. The rear plunger **244** is translatable relative to the passage **220** through a rear plunger stroke **SR**. During a first part **SF1** of the front plunger stroke **SF**, the front chamber **222** is fluidly sealed from the rear chamber **224** by the front seal **252**. During a second part **SF2** of the front plunger stroke **SF**, the front chamber **222** is fluidly coupled or connected to the rear chamber **224** through the opening **252A** of the front seal **252**.

[00383] The plunger drive mechanism **258** is selectively operable to drive the plunger member **240** in each of an extension direction **E8** and retraction direction **E9**. The plunger drive mechanism **258** may be a linear drive mechanism. The plunger drive mechanism **258** may include an actuator and may be any suitable type of linear drive mechanism. In some embodiments, the actuator includes an electric motor. In some embodiments, the linear drive mechanism **258** includes a spindle and spindle nut linkage driven by an electric motor. In some embodiments, the plunger drive mechanism **258** is manually operable and does not include a powered actuator. For example, the plunger member **240** may be pushed and pulled using an extension, lever, knob or other feature that is hand-driven.

[00384] In use, as the front plunger **242** is driven in the extension direction **E8**, air volume is displaced from the front chamber **222**, and the effective volume of the front chamber **222** is reduced. As the front plunger **242** is driven in the retraction direction **E9**, air volume is replaced in the front chamber **222**, and the effective volume of the front chamber **222** is increased.

[00385] Similarly, in use, as the rear plunger **244** is driven in the extension direction **E8**, air volume is displaced from the rear chamber **224**, and the effective volume of the rear chamber **224** is reduced. As the rear plunger **244** is driven in the retraction direction **E9**, air volume is replaced in the rear chamber **224**, and the effective volume of the rear chamber **224** is increased.

[00386] The plunger member **240** may be formed of any suitable material(s). In some embodiments, the plunger member **240** is formed of stainless steel.

[00387] The barrel **210** may be formed of any suitable material. In some embodiments, the barrel **210** is formed of aluminum.

[00388] The tip adaptor **214** is configured to removably secure the pipette tip **160** (and suitably constructed replacement pipette tips) to the end **212A** of the shaft **212** in the same manner as described above for the tip adaptor **156**.

[00389] The pipette tip **160** (**FIG. 8**) is an example of a pipette tip that may be used with the pipettor **100**. However, it will be appreciated that pipette tips of other designs may be used instead.

[00390] The pressure sensor **256** is fluidly coupled to the pipetting channel **202**. In some embodiments, the pressure sensor **256** is an in-line pressure sensor positioned in or along the pipetting channel **202**.

[00391] The controller **20** is operative to control the pressure relief valve **255** to assume an open valve state and a closed valve state. In the open valve state, the rear chamber **224** is fluidly connected to the ambient atmosphere through the relief port **228**. In the closed valve state, the rear chamber **224** is not fluidly connected to the ambient atmosphere through the relief port **228**.

[00392] The liquid handling system **10** and the pipetting system **201** may be used as follows in accordance with some methods to aspirate and/or dispense one or more liquid samples. Generally, the front and rear plungers **242**, **244** are used to displace air volumes in their respective chambers **222, 224** and thereby correspondingly change a pressure in the pipetting channel **202** to aspirate or dispense a liquid sample into or from the liquid collection volume **165**.

[00393] The pipettor **200** may be operated in each of several different modes of operation. The operator or controller **20** may select and implement the mode of operation depending on the conditions or parameters of the aspirating or dispensing task.

[00394] Typically, the pipettor **200** will initially be set (*e.g.*, by the controller **20**) in a first start position. The start position may be a lowermost position as **FIG. 14**, for example. In other embodiments, the start position is somewhat raised or retracted from the lowermost, fully extended position of **FIG. 14** (*i.e.*, the plunger member **240** is partially retracted relative to its position shown in **FIG. 14**). Starting aspiration with this offset can help to assure that the pipette tip is fully emptied by the dispensing operation. For example, the offset of the plunger member distal end **242A** from the distal end of the front chamber **222D** may be in the range of from about 10 to 20% of the pipetting volume.

[00395] A pipette tip **160** is mounted on the tip adaptor **214**, as shown in **FIG. 14**.

[00396] The controller **20** may then operate the actuator(s) **34A, 34B**, for example, to position the pipette tip **160** over a liquid sample **LS**. The sample **LS** may be disposed in a container **36**, for example. The controller **20** may then operate the actuator **34B**, for example, to lower the distal end **160A**, and thereby the pipetting orifice **162**, into the sample **LS**. In some embodiments, the distal end **160A**, and thereby the pipetting orifice **162**, are immersed in the sample **LS** to at least a prescribed depth to ensure that the pipetting orifice **162** remains immersed in the sample during aspiration.

[00397] With the pipettor **200** in the first start position and the pipetting orifice **162** immersed, the pipetting system **201** may be operated in a first aspirating mode to aspirate a portion of the sample **LS**. In the first aspirating mode, the pressure relief valve **255** is set in the open valve state so that the rear chamber **224** is fluidly connected to the relief port **228**. In the first aspirating mode, the pipetting channel **202** is fluidly sealed from the rear chamber **224** by the front seal **252**. More particularly, the front plunger **242** plugs (airtight) the connecting opening **252A** in the front seal **252**.

[00398] The drive mechanism **258** is then actuated to displace the plunger member **240** in the retraction direction **E9** and thereby draw the front plunger **242** away from the pipettor orifice **204**. The front plunger **242** is thereby translated through a portion of its first stroke **SF1**, but not into the second portion **SF2** of its stroke, as illustrated in **FIG. 16**. The front chamber **222** remains sealed from the rear chamber **224** by the front seal **252**. The retraction of the front plunger **242** expands the effective air volume of the front chamber **222**, thereby generating a negative pressure at the pipettor orifice **204**. The negative pressure draws a liquid sample volume **LV** of the liquid sample **LS** into the liquid collection volume

165 (in the tip passage **164**) of the pipette tip **160**. An air volume or air cushion **AC** may remain in the tip passage **164** and the front chamber **222** between the proximal end of the liquid sample volume **LV** and the leading end **220A** of the front chamber **222**.

[00399] The pipettor **200** may then be used to dispense the liquid sample volume **LV** in a first dispensing mode. The front plunger **242** is in the first part **SF1** of its stroke so that the front chamber **222** remains sealed from the rear chamber **224** by the front seal **252**. The pressure relief valve **255** is set or retained in the open valve state. The drive mechanism **258** is then actuated to displace the plunger member **240** in the extension direction **E8** and to thereby to push the front plunger **242** toward the pipettor orifice **204** in the extension direction **E8**. The extension of the front plunger **242** displaces air volume from the front chamber **222**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV**. The positive pressure expels the liquid sample volume **LV** from the liquid collection volume **165** through the pipetting orifice **162**. The air cushion **AC** may remain between the proximal end of the liquid sample volume **LV** and the leading end **242A** of the front plunger **242** until the liquid sample volume **LV** is fully dispensed.

[00400] Alternatively, the pipetting system **101** may be operated in a second aspirating mode to aspirate a portion of the liquid sample **LS**. The pressure relief valve **255** is initially set in the open valve state so that the rear chamber **224** is fluidly connected to the relief port **228**. The plunger member **240** is placed in a second start position. In the second start position, the distal end **242A** of the plunger member **240** is located rearward of the front seal **252** (*e.g.*, slightly aft of the front seal **252**) so that the plunger member **242** and the front seal **252** do not seal the front chamber **222** off from the rear chamber **224**. The controller **20** then sets the pressure relief valve **255** in the closed valve state so that the rear chamber **224** is fluidly sealed from the relief port **228**. With the pipettor **200** in the second start position and the pipetting orifice **162** immersed, the drive mechanism **258** is actuated to draw the plunger member **240** in the retraction direction **E9**. The front plunger **242** is thereby translated through some or all of the second portion **SF2** of its stroke as shown in **FIG. 17**. The retraction of the rear plunger **244** expands the effective air volume of the rear chamber **224**, thereby generating a negative pressure at the pipettor orifice **204**. The negative pressure draws additional liquid sample volume **LV** of the liquid sample **LS** into the liquid collection volume **165** of the pipette tip **160**. An air volume or air cushion **AC** may remain in the tip passage **164** between the proximal end of the liquid sample volume **LV** and the leading end **242A** of the first plunger **242**.

[00401] Similarly, the pipettor **200** may then be used to dispense the liquid sample volume **LV** in a second dispensing mode. The pressure relief valve **255** is set or retained in the closed valve state. The drive mechanism **258** is actuated to push the plunger member **240** in the extension direction **E8**. The extension translation of the plunger member **240** displaces air volume from the rear chamber **224**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV**. The positive pressure expels the liquid sample volume **LV** from the liquid collection volume **165** through the pipetting orifice **162**.

[00402] The plunger member **240** may be extended beyond the front seal **252**. In this case, once the leading end **242A** of the front plunger **242** reaches and closes the opening **252A** of the front seal **252**, the controller **20** may open the pressure relief valve **255**. The drive mechanism **258** then continues to push the plunger member **240** in the extension direction **E8**. The continued extension of the plunger member **240** displaces air volume from the front chamber **222**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV**. The positive pressure expels the additional liquid sample volume **LV** from the liquid collection volume **165** through the pipetting orifice **162**.

[00403] During the foregoing operations, the valve **255** is opened at certain times to permit air to be expelled from the rear chamber **224** through the relief port **228** so that the air volume in the chamber **224** is not unduly pressurized (negatively or positively) by the displacement of the rear plunger **244**. When the pressure relief valve **255** is closed, the rear chamber **224** is sealed from the atmosphere so that the displacement of the rear plunger **244** can generate a pressure change in the rear chamber **224** for the aspirating or dispensing operation.

[00404] As discussed above, the pipetting system **201** aspirates liquid sample by decreasing the pressure in the pipetting channel and dispenses liquid sample by increasing the pressure in the pipetting channel **202**. However, the pressure in the pipetting channel **202** may fluctuate in response to other actions or conditions in the procedure, for example, as discussed above with regard to the pipetting system **101**.

[00405] In some embodiments, the controller **20** automatically and programmatically operates the pressure relief valve **255** and the actuator of the linear drive mechanism **258** to open and close the valve **255** and to extend and retract the plunger member **240** as described herein.

[00406] In some embodiments, the controller **20** receives pressure signals from the pipetting channel pressure sensor **256** indicating the air pressure in the pipetting channel **202**. The controller **20** may continuously monitor the pressure in the pipetting channel **202**.

[00407] The choice of which aspirating or dispensing mode to use for a given aspirating or dispensing procedure can be a function of or tailored to the conditions or parameters of the aspirating or dispensing procedure. By employing serial plungers of different sizes, the volume range of the pipettor **200** can be enlarged, and process specific volume accuracy and precision can be supported without the need for multiple pipetting channels.

[00408] For example, when only a relatively small quantity of the liquid sample is to be aspirated or dispensed, the pipettor **200** may be operated in the first aspirating mode or first dispensing mode. The use of the smaller front plunger **242** can provide higher resolution, and thereby better accuracy and precision.

[00409] When a relatively large quantity of the liquid sample is to be aspirated or dispensed, the pipettor **200** may be operated in the second aspirating mode or second dispensing mode. The use of the larger rear plunger **244** can enable the pipettor **200** to draw and hold a greater quantity of the liquid sample at once. The use of the larger rear plunger **244** can enable the pipettor **200** to aspirate or dispense the liquid sample at a higher rate.

[00410] For example, in an illustrative embodiment, the first part **SF1** of the stroke of the front plunger **242** has a stroke distance **L6** (**FIG. 17**) of 25 mm and the front plunger **242** has a diameter **D6** (**FIG. 18**) of 2 mm, so that the front plunger **242** can displace up to 78.5 microliters of air. In the illustrative embodiment, the rear plunger **244** has a stroke distance **L7** (**FIG. 17**) of 50 mm and a diameter **D7** (**FIG. 19**) of 6 mm, so that the rear plunger **244** can displace up to 1413 microliters of air. When operated in the first aspirating mode, the pipettor **200** can aspirate up to 60 microliters of liquid sample. When operated in the second aspirating mode, the pipettor **200** can aspirate up to 1300 microliters of liquid sample.

[00411] As mentioned above, in some embodiments the rear plunger **244** is larger than the front plunger **242**. The front plunger **242** has a cross-sectional area **A6** (**FIG. 18**) in a cross-sectional plane orthogonal to the plunger axis **P4-P4** (*i.e.*, the axis along which the first plunger is translated to aspirate and dispense). The rear plunger **244** has a cross-sectional area **A7** (**FIG. 19**) in a cross-sectional plane orthogonal to the plunger axis **P4-P4** (*i.e.*, the axis along which the rear plunger **244** is translated to aspirate and dispense). In some embodiments (as illustrated, for example), the cross-sectional area **A7** of the rear plunger **244** is greater than the cross-sectional area **A6** of the front plunger **242**. In some embodiments, the cross-sectional area **A7** is at least three times the cross-sectional area **A6**. In some embodiments, the cross-sectional area **A6** is in the range of from about 3 to 64 times the cross-sectional area **A6**.

[00412] In some embodiments, the cross-sectional area **A6** is in the range of from about 0.5 to 5 mm^2, and the cross-sectional area **A7** is in the range of from about 5 to 85 mm^2.

[00413] The smaller front plunger **242** displaces an air volume in the front chamber **222** at a first rate of air volume displacement per unit translation. The larger rear plunger **244** displaces an air volume in the rear chamber **224** at a second rate of air volume displacement per unit translation. Because the rear plunger **244** has a greater cross-sectional area, the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation. In some embodiments, the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

[00414] In some embodiments, the first rate of air volume displacement per unit translation is in the range of from about 0.1 microliters/second to 100 microliters/second, and the second rate of air volume displacement per unit translation is in the range of from about 1 microliters/second to 2500 microliters/second.

[00415] In some embodiments, pipettor **200** is configured such that the maximum air volume displaceable by the rear plunger **244** (when the rear plunger **244** is translated through its full stroke) is greater than the maximum air volume displaceable by the front plunger **242** (when the front plunger **242** is translated through its full stroke). In some embodiments, the maximum air volume displaceable by the rear plunger **244** is at least ten times the maximum air volume displaceable by the front plunger **242**.

[00416] In some embodiments, the maximum air volume displaceable by the rear plunger **244** is in the range of from about 100 microliters to 5000 microliters, and the maximum air volume displaceable by the front plunger **242** is in the range of from about 10 microliters to 200 microliters.

[00417] In some embodiments, the volume of the rear chamber **224** is greater that the volume of the front chamber **222**. In some embodiments, the volume of the rear chamber **224** is at least ten times volume of the front chamber **222**.

[00418] With reference to **FIGS. 20-24**, a pipetting system **301** according to further embodiments is shown therein. The pipetting system **301** is constructed and may be used in the same manner as the pipetting system **201**, except as discussed below.

[00419] The pipetting system **301** includes a pipettor **300** in place of the pipettor **200**. The pipettor **300** is constructed and may be used in the same manner as the pipettor **200**, except as follows. The pipettor **300** further includes an opening mechanism in the form of an

interchamber valve **360**. The interchamber valve **360** includes a connecting passage **362** and a valve control mechanism **364**. The connecting passage **362** may be formed in the barrel **310** and fluidly couples the rear chamber **324** to the front chamber **322**. The valve control mechanism **364** includes an actuator **364A** (*e.g.*, a solenoid) and a valve member **366**.

[00420] The actuator **364A** is selectively operable to place the valve member **366** in each of a closed position (**FIGS. 20**, **22** and **23**) and an open position (**FIGS. 21** and **24**). In the closed position, the valve member **366** blocks the connecting passage **362** so that the rear chamber **324** is not fluidly connected to the front chamber **322** through the connecting passage **362**. In the open position, the valve member **366** does not block the connecting passage **362** so that the rear chamber **324** is fluidly connected to the front chamber **322** through the connecting passage **362**.

[00421] In use, the valve member **366** is closed when aspirating or dispensing in the first aspirating mode or the first dispensing mode as described above with regard to the pipettor **200** (*i.e.*, aspirating and dispensing using the front plunger **342** and not using the rear plunger **344**; as illustrated in **FIG. 23**). Thus, in these procedures, the connecting passage **362** is sealed by the valve member **366** and the opening of the front seal **352** is sealed by the front plunger **342**, so that the front chamber **322** is fluidly sealed from the rear chamber **324**. The pressure relief valve **355** is opened during these procedures, as discussed above.

[00422] The pipettor **300** can also be used to aspirate or dispense in a second aspirating mode or a second dispensing mode similar to the second aspirating mode or the second dispensing mode as described above with regard to the pipettor **200**.

[00423] When aspirating in the second aspirating mode (*i.e.*, aspirating using both the front plunger **342** and the rear plunger **344**; as illustrated in **FIG. 24**), the valve member **366** is opened and the pressure relief valve **355** is closed. In this embodiment, the plunger member **340** is positioned in the first start position at the beginning of the aspiration step. That is, the plunger member **340** is positioned such that the front plunger **342** extends through the front seal **352** and occupies the front chamber **322**. In the first start position, the distal end of the plunger member **340** may be at a lowermost position or offset from the lowermost position as discussed above for the pipettor **200**. With the plunger member **340** in this first start position, the valve member **366** open and the pressure relief valve **355** closed, the plunger member **340** is then translated in the retraction direction **E9** to aspirate. The plunger member **340** is translated such that the front plunger **342** travels through the first part **SF1** of its stroke and into the second part **SF2** of its stroke. In this case, the rear chamber **324** will be fluidly connected to the front chamber **322** (via the connecting passage **362**)

during both stroke parts **SF1**, **SF2** and both plungers **342**, **344** will contribute in parallel to the aspiration throughout the stroke of the plunger member **340**.

[00424] To dispense in the second dispensing mode (*i.e.*, dispensing using both the front plunger **342** and the rear plunger **344**), the plunger member **340** is translated in the extension direction **E8** with the valve member **366** open and the pressure relief valve **355** closed. The plunger member **340** is translated such that the front plunger **342** travels through the second part **SF2** of its stroke and the first part **SF1** of its stroke. In this case, the rear chamber **324** will be fluidly connected to the front chamber **322** (via the connecting passage **362**) during both stroke parts **SF1**, **SF2** and both plungers **342**, **344** will contribute in parallel to the dispensing throughout the stroke **SF**.

[00425] By fluidly connecting the front chamber **322** and the rear chamber **324** during the second aspirating and dispensing modes, the pipettor **300** can initiate the aspiration retraction of the plunger member **340** while the front section **342** is disposed in the front chamber **322** and the front seal **252** is sealed about the plunger member **340**. As a result, the pipettor **300** can reduce the dead volume in the rear chamber **324**.

[00426] With reference to **FIGS. 25-27**, a pipetting system **401** according to further embodiments is shown therein. The pipetting system **401** is constructed and may be used in the same manner as the pipetting system **301**, except as discussed below.

[00427] The pipetting system **401** includes a pipettor **400** in place of the pipettor **300**. The pipettor **400** is constructed and may be used in the same manner as the pipettor **300**, except as follows.

[00428] The pipettor **400** includes a connecting valve **460** in place of the interchamber valve **360** and the pressure relief valve **355**. The connecting valve **460** is selectively operable to fluidly connect the rear chamber **424** to the front chamber **422** (via channels **468A**, **468B** on either side of the front seal **452**) and to the atmosphere (via a channel **468C** to a relief port **468D**). In a first valve state, the connecting valve **460** closes the rear chamber **424** from the front chamber **422** and opens the rear chamber **424** to the pressure relief port **468D** to atmosphere. In a second valve state, the connecting valve **460** opens the rear chamber **424** to the front chamber **422** and closes the rear chamber **424** from the pressure relief port **468D**. The connecting valve **460** may be an electronically controlled valve.

[00429] In use, the connecting valve **460** is set in the first valve state when aspirating or dispensing in the first aspirating mode or the first dispensing mode as described above

with regard to the pipettor **200** (*i.e.*, aspirating and dispensing using the front plunger **442** and not using the rear plunger **444**; as illustrated in **FIG. 27**).

[00430] When aspirating in the second aspirating mode (*i.e.*, aspirating using both the front plunger **442** and the rear plunger **444**; as illustrated in **FIG. 26**), the connecting valve **460** is set in the second valve state. With the connecting valve **460** is set in the second valve state, the plunger member **440** is then translated in the retraction direction **E9** to aspirate. The plunger member **440** is translated such that the front plunger **442** travels through the first part **SF1** of its stroke and into the second part **SF2** of its stroke. In this case, the rear chamber **324** will be fluidly connected to the front chamber **422** (via the connecting valve **460**) during both stroke parts **SF1**, **SF2** and both plungers **442**, **444** will contribute in parallel to the aspiration throughout the stroke of the plunger member **340**.

[00431] To dispense in the second dispensing mode (*i.e.*, dispensing using both the front plunger **442** and the rear plunger **444**), the plunger member **440** is translated in the extension direction **E8** with the connecting valve **460** set in the second valve state. The plunger member **440** is translated such that the front plunger **442** travels through the second part **SF2** of its stroke and the first part **SF1** of its stroke. In this case, the rear chamber **424** will be fluidly connected to the front chamber **422** (via the connecting valve **460**) during both stroke parts **SF1**, **SF2** and both plungers **442**, **444** will contribute in parallel to the dispensing throughout the stroke **SF**.

[00432] The pipettor **400** further includes an annular seal (*e.g.*, an O-ring) **453** mounted on the rear plunger **444** to travel with the rear plunger **444** through the rear chamber **424**. The seal **453** forms a sliding air-tight, pressure-tight seal between the front end of the rear plunger **444** and the volume of the rear chamber **424** rearward of the front end of the rear plunger **444**. In this way, the seal **453** can reduce the death volume in the rear chamber **424** around the rear plunger **444**. Pipettors according to other embodiments (*e.g.*, the pipettors **200** and **300**) may include seals corresponding to the seal **453**.

[00433] According to a further embodiment, the pipettor **400** may be configured and/or operated such that the front plunger **442** extends through the front seal **452** throughout both the first part **SF1** of the plunger stroke and the second part **SF2** of the plunger stroke (with the front seal **452** maintaining a seal about the front plunger **442** throughout the stroke). That is, also in the second aspirating mode (when the connecting valve **460** is set in the second valve state and fluidly connects the rear chamber **424** to the front chamber **422**), the front seal **452** remains plugged by the plunger member **440** throughout the full aspiration stroke **SF1**, **SF2**. In this way, the front plunger **442** will always be engaged within the front

seal **452**. Any pressure jumps due to deformation of the front seal **452** are thereby avoided. The front seal will experience fewer mechanical forces, thus improving the stability and reliability of the seal.

[00434] In order to accomplish this effect or function of not unsealing or disengaging the front plunger **442** from the front seal **452**, the front plunger **442** may be extended or lengthened as compared to that shown in **FIG. 25**. In some embodiments, the length of the front plunger **442** is at least as long as the second part **SF2** of the plunger stroke.

[00435] In other embodiments, the pressure sensor (*e.g.*, pressure sensor **256**) can be positioned and configured to detect the air pressure in the rear chamber (*e.g.*, the rear chamber **224**), and the controller **20** may use the pressure detection data from the rear pressure sensor in the same manner as described for the front pressure sensor to control operation of the pipettor.

[00436] With reference to **FIGS. 28-35**, an example pipetting system **601** according to further embodiments of the present technology is shown. The pipetting system **601** can aspirate and dispense liquid volumes within a liquid handling system. The pipetting system **601** may be used in place of the pipetting system **101** in the automated liquid handling system **10** (**FIG. 1**), for example. However, it shall be understood that the disclosed methods, systems, and apparatus are not limited to the liquid handling system **10** or use therein, and the present disclosure is applicable to other systems and applications where it is desired to aspirate and/or dispense liquid volumes.

[00437] The pipetting system **601** is configured to be used in each of an air displacement (AD) mode and an alternative displacement (PD) mode. In the AD mode, the pipetting system **601** is operated to aspirate and/or dispense a liquid using an air displacement pipette tip. In the PD mode, the pipetting system **601** is operated to aspirate and/or dispense a liquid using a positive displacement pipette tip.

[00438] The pipetting system **601** includes one or more pipettors **600**. The pipettor(s) may be mounted on the pipettor module **30**. The pipettors **600** may be constructed and operate in the same manner, and it will be appreciated that the description of a representative one of the pipettors **600** that follows may apply equally to each of the pipettors **600**. If multiple pipettors **600** are provided, the pipettors **600** may be operated independently of one another or in tandem. For the purpose of discussion, only a single pipettor is described below.

[00439] The pipetting system **601** includes the pipettor **600**, the controller **20**, one or more air displacement (AD) pipette tips **660** (**FIG. 34**), and one or more positive

displacement (PD) pipette tips **670** (**FIG. 35**). The pipette tips **660, 670** are removable and replaceable on the pipettor **600**, and may be effectively disposable or consumable components of the pipetting system **601**.

[00440] With reference to **FIGS. 28** and **33**, and as discussed in more detail herein, the pipettor **600** may be understood to have a lengthwise axis **A-A** and a distal end **600A**. The pipettor **600** includes a tubular barrel **610**, a pressure control system **606**, a pipetting channel **602**, a pipettor orifice **604**, and a tip adaptor **614**. The barrel **610** extends from a distal end **610A** to a proximal end **610B**. The barrel **610** includes a shaft **612** that terminates at the distal end **610A**. The tip adaptor **614** is mounted or formed in the distal end **610A**. The pipettor orifice **604** is located at the distal end **600A** and fluidly communicates with the pipetting channel **602**.

[00441] The pressure control system **606** includes the barrel **610**, a plunger **640**, a rear seal **654**, a plunger drive mechanism **658**, and a pressure sensor **656**.

[00442] With reference to **FIG. 33**, the barrel **610** includes a barrel passage **620**. The passage **620** is aligned lengthwise with the axis **A-A** and extends from a front end **620A** to an opposing rear end **620B**. The passage **620** terminates at and communicates with a rear opening **620E** at a proximal end **610B** of the barrel **610**. The barrel passage **620** includes a barrel chamber **621**. The rear seal **654** is located axially between the barrel chamber **621** and a rear opening **620E** at the proximal end **610B**. The barrel chamber **621** fluidly communicates with the pressure sensor **656** via a sensor port **656A**.

[00443] The rear seal **654** may be an annular seal (*e.g.*, an O-ring).

[00444] The plunger **640** has a front or leading end **640A** and an opposing rear end **640B**, and a rear plunger section **644**.

[00445] The plunger **640** further includes an integral piston engagement feature **646** on the leading end **640A**. In some embodiments and as illustrated in **FIG. 33**, the piston engagement feature **646** includes a slot **646A**. The slot **646A** may be configured as a blind hole, for example, as shown. The piston engagement feature may have any suitable construction and is not limited to a slot or opening.

[00446] The plunger **640** is mounted in the passage **620** such that the plunger **640** can slidably translate relative to the barrel **610** along a plunger axis **P5-P5** in an extension direction **E10** and an opposing retraction direction **E11**. In some embodiments, the plunger axis **P5-P5** is substantially coincident with the shaft axis **A-A**.

[00447] The plunger **640** is slidable to translate (relative to the passage **620**, through a plunger stroke) between a fully extended position, as shown in **FIG. 31**, and a fully retracted

position, as shown in **FIG. 30**. As discussed below, the plunger **640** can also be slid into an AD mode starting position as shown in **FIG. 28** and, alternatively, a PD mode starting position as shown in **FIG. 31**.

[00448] In the fully extended position (**FIG. 31**), a portion of the front plunger section **642** extends distally beyond the distal end **600A** of the pipettor **600**. Through a first part **SF1** of the retraction stroke (**FIG. 31**; starting from the fully extended position), the rear end **640B** of the plunger **640** is forward of the rear seal **654** so that the passage **620** is open to the rear opening **620E**.

[00449] Through a second part **SF2** of the retraction stroke (**FIG. 30**; following the first part **SF1**), the rear end **640B** of the plunger **640** is rearward of the rear seal **654** so that the plunger rear section **644** is disposed in the rear seal **654**. In this portion of the stroke, the rear O-ring **654** forms an airtight, pressure tight seal between the outer diameter of the rear plunger section **644** and the barrel **610**, which seals the passage **620** from the rear opening **620E**. The rear plunger section **644** is able to slide through the rear O-ring **654** while maintaining the airtight, pressure tight seal therewith.

[00450] The plunger drive mechanism **658** is selectively operable to drive the plunger **640** in each of an extension direction **E10** and retraction direction **E11**. The plunger drive mechanism **658** may be a linear drive mechanism. The plunger drive mechanism **658** may include an actuator and may be any suitable type of linear drive mechanism. In some embodiments, the actuator includes an electric motor. In some embodiments, the linear drive mechanism **658** includes a spindle and spindle nut linkage driven by an electric motor. In some embodiments, the plunger drive mechanism **658** is manually operable and does not include an actuator. For example, the plunger member **640** may be pushed and pulled using an extension, lever, knob or other feature that is hand-driven.

[00451] In use, as the plunger **640** is driven in the extension direction **E10** through the stroke portion **SF2**, air volume is displaced from the barrel chamber **621**, and the effective volume of the barrel chamber **621** is reduced. As the plunger **240** is driven in the retraction direction **E11**, air volume is replaced in the barrel chamber **621**, and the effective volume of the barrel chamber **621** is increased.

[00452] The plunger **640** may be formed of any suitable material(s). In some embodiments, the plunger **640** is formed of stainless steel.

[00453] The barrel **610** may be formed of any suitable material. In some embodiments, the barrel **610** is formed of aluminum.

[00454] The tip adaptor **614** is configured to removably secure the pipette tips **660** and **670** to the end **600A** of the pipettor **600** in the same manner as described above for the tip adaptor **156**.

[00455] The AD pipette tip **660** (**FIGS. 28-30** and **34**) is an example of a pipette tip that may be used with the pipettor **600** for aspirating and dispensing in the AD mode. However, it will be appreciated that pipette tips of other designs may be used instead. The AD pipette tip **660** may be a tubular body constructed in same manner as described for the AD pipette tip **160**, and includes a distal end **660A**, a proximal end **660B**, a tip volume or passage **664**, a pipetting orifice **662**, an interface opening **663**, a mount section **666**, and a liquid collection volume **665** corresponding to the components **160A**, **160B**, **164**, **162**, **163**, **166**, and **165**, respectively.

[00456] The PD pipette tip **670** (**FIGS. 31, 32** and **35**) includes a tubular tip body **678** and a piston **680** slidably mounted in the tip body **678**. The piston **680** is slidable between an extended or ready position (**FIG. 31**) and a retracted position (*e.g.*, **FIG. 32**).

[00457] With reference to **FIG. 35**, the tip body **678** extends from a distal end **670A** to a proximal end **670B**. The tip body **678** includes a front section **678A** and a rear section **678B** which together define a tip volume or passage **674**. The front section **678A** defines a front chamber **679A** and the rear section **678B** defines a rear chamber **679B**, each forming a part of the passage **674**. The rear section **678B** includes a mount section **676** and defines an interface opening **673**. A pipetting orifice **672** is defined in the distal end **670A**. The passage **674** terminates at the interface opening **673** and the pipetting orifice **672**.

[00458] The piston **680** includes a shaft **682**, a base **684**, and a plunger engagement feature **686**. In some embodiments, the shaft **682**, the base **684**, and the plunger engagement feature **686** form a rigid, unitary member. In some embodiments, the shaft **682**, the base **684**, and the plunger engagement feature **686** together form a monolithic member.

[00459] The shaft **682** extends from a proximal end **682B** secured to the base **684** to an opposing distal end **682A**. In some embodiments, the distal end **682A** is positioned at or proximate the pipetting orifice **672** when the piston **680** is in the ready position. The front side of the base **684** may have a convex or otherwise contoured shape to fit the facing profile of the tip body **678**.

[00460] The illustrated plunger engagement feature **686** includes two or more opposed legs **686A**. The plunger engagement feature **686** is configured to be received in the slot **646A** to releasably secure the piston engagement feature **646A** to the plunger

engagement feature **686**. In some embodiments, the legs **686A** have a relaxed width that is greater than the width of the slot **646A** and are elastically deflectable.

[00461] The liquid handling system **10** and the pipetting system **601** may be used as follows in accordance with some methods to aspirate and/or dispense one or more liquid samples. As discussed above, the pipetting system **601** is configured to be used in each of an air displacement (AD) mode and an alternative displacement (PD) mode.

[00462] Generally, in the AD mode, the AD pipette tip **660** is mounted on the pipettor **600**. The plunger **640** is driven to displace an air volume in the passage **620** and thereby correspondingly change a pressure in the pipetting channel **602** to aspirate or dispense a liquid sample into or from the liquid collection volume **665**. In the AD mode, the displacement of the plunger **640** displaces or expands air volume in the barrel **614**, which generates the pressure change, and an air cushion may be (and typically is) present and maintained between the liquid sample in the liquid collection volume **665** and the distal end **640A** of the plunger **640**.

[00463] Generally, in the PD mode, PD pipette tip **660** is mounted on the pipettor **600**. The piston **680** is driven via the plunger **640** to displace an air volume in the front chamber **679A** and thereby correspondingly change a pressure in the front chamber **679A** to aspirate or dispense a liquid sample into or from the liquid collection volume **675**. In the PD mode, the displacement of the piston **680** displaces or expands air volume in the front chamber **679A**, which generates the pressure change. In some embodiments, the distal end **682A** of the piston **680** contacts the liquid sample in the front chamber **679A**.

[00464] The operator or controller **20** may select and implement the mode of operation (AD mode or PD mode). For example, the operator may instruct the controller **20** using the HMI **22**, for example, that the pipette tip installed on the pipettor **600**, or to be installed on the pipettor **600**, is an AD-type tip **660** or is a PD-type tip **670**. The controller **20** may then automatically and programmatically operate the pipetting system **601** in a manner corresponding to the type of pipette tip (*e.g.*, as described below).

[00465] Operation of the pipetting system in the AD mode will now be described in more detail. The AD pipette tip **660** is mounted on the tip adaptor **614** as shown in **FIG. 28**. For example, the AD pipette tip may be held in a tray and the controller **20** may operate the operate the actuator(s) **34A, 34B**, for example, to position the pipettor **600** over the AD pipette tip **660**, then drive the pipettor **600** down to insert the tip adaptor **614**, and then raise the pipettor **600** to remove the AD pipette tip **660** from the tray. During this pickup operation, the plunger **640** may be in the AD mode starting position.

[00466] The controller **20** may then operate the actuator(s) **34A, 34B**, for example, to position the pipette tip **660** over a liquid sample **LS**. The sample **LS** may be disposed in a container **36**, for example. If the plunger **640** is not in the AD mode starting position, it is placed in the AD mode starting position, as shown in **FIG. 28**. The controller **20** may then operate the actuator **34B**, for example, to lower the distal end **660A**, and thereby the pipetting orifice **662**, into the sample **LS**. In some embodiments, the distal end **660A**, and thereby the pipetting orifice **662**, are immersed in the sample **LS** to at least a prescribed depth to ensure that the pipetting orifice **662** remains immersed in the sample during aspiration.

[00467] With the plunger **640** in the AD mode starting position and the pipetting orifice **662** immersed, the drive mechanism **658** is operated to displace the plunger **640** in the retraction direction **E11** through some or all of the stroke portion **SF2**, and thereby draw the plunger **640** away from the pipettor orifice **604**. Throughout the stroke portion **SF2** of the retraction stroke, the pipetting channel **602** is sealed (except at the pipettor orifice **604**) by the engagement between the rear seal **654** and the rear section **644** of the plunger **640**.

[00468] The retraction of the plunger **640** expands the effective air volume of the barrel chamber **621**, thereby generating a negative pressure at the pipettor orifice **604**. The negative pressure draws a liquid sample volume **LV** of the liquid sample **LS** into the liquid collection volume **665** (in the tip passage **664**) of the pipette tip **660**. The plunger **640** may be further retracted until the desired amount of liquid sample volume **LV** has been aspirated into the collection volume **665**. An air volume or air cushion **AC** may remain in the tip passage **664** and the barrel chamber **621** between the proximal end of the liquid sample volume **LV** and the pipettor **600**.

[00469] The pipettor **600** may then be used to dispense the liquid sample volume **LV** from the AD pipette tip **660**. The drive mechanism **658** is operated to displace the plunger **640** in the extension direction **E10** and thereby push the plunger **640** toward the pipettor orifice **604**. Throughout the extension stroke, the pipetting channel **602** is sealed (except at the pipettor orifice **604**) by the engagement between the rear seal **654** and the rear section **644** of the plunger **640**. The extension of the plunger **640** displaces air volume from the barrel chamber **621**, thereby generating a positive pressure at the proximal end of the liquid sample volume **LV**. The positive pressure expels the liquid sample volume **LV** from the liquid collection volume **665** through the pipetting orifice **662**. The air cushion **AC** may remain between the proximal end of the liquid sample volume **LV** and the leading end **640A** of the plunger **640** until the liquid sample volume **LV** is fully dispensed.

[00470] In the illustrated embodiment, the pipettor **600** is not provided with a front seal corresponding to the front seal **252** (**FIG. 17**). Therefore, the front portion of the barrel chamber **621** is not sealed from the rear portion of the barrel chamber **624**. In some embodiments or applications, the PD tip **670** is used for smaller volumes and the AD tip **660** is used for relatively larger volumes. However, in other embodiments, the pipettor **600** may be configured to operate in AD mode as discussed for the pipettor **200** (**FIG. 14**), for example.

[00471] In some embodiments, when executing the aspirating or dispensing operations in the AD mode, the controller **20** receives pressure signals from the pressure sensor **656** indicating the air pressure in the pipetting channel **602**. The controller **20** may continuously monitor the pressure in the pipetting channel **602**.

[00472] As discussed above, the pipetting system **601** aspirates liquid sample by decreasing the pressure in the pipetting channel **602** and dispenses liquid sample by increasing the pressure in the pipetting channel **602**. However, the pressure in the pipetting channel **602** may fluctuate in response to other actions or conditions in the procedure, for example, as discussed above with regard to the pipetting system **101**.

[00473] Operation of the pipetting system in the PD mode will now be described in more detail. The PD pipette tip **670** is mounted on the tip adaptor **614** as shown in **FIG. 31**. For example, the PD pipette tip **670** may be held in a tray and the controller **20** may operate the operate the actuator(s) **34A, 34B**, for example, to position the pipettor **600** over the PD pipette tip **670**, then drive the pipettor **600** down to insert the tip adaptor **614**, and then raise the pipettor **600** to remove the PD pipette tip **670** from the tray.

[00474] During this pickup operation, the plunger **640** is disposed in the PD mode starting position (**FIG. 31**). The pipettor **600** is configured such that, when the PD pipette tip **670** is sufficiently mounted on the tip adaptor **614** and the piston **680** is in its forwardmost position relative to the tip body **678**, the plunger engagement feature **686** is received in the slot **646A** of the plunger **640**. In this way, the piston **680** is releasably captured by or affixed to the distal end of the plunger **640**.

[00475] The controller **20** may then operate the actuator(s) **34A, 34B**, for example, to position the PD pipette tip **670** over a liquid sample **LS**. The sample **LS** may be disposed in a container **36**, for example. The controller **20** may then operate the actuator **34B**, for example, to lower the distal end **670A**, and thereby the pipetting orifice **672**, into the sample **LS**. In some embodiments, the distal end **670A**, and thereby the pipetting orifice **672**, are

immersed in the sample **LS** to at least a prescribed depth to ensure that the pipetting orifice **672** remains immersed in the sample during aspiration.

[00476] With the plunger **640** in the PD mode starting position and the pipetting orifice **672** immersed, the drive mechanism **658** is operated to displace the plunger **640** in the retraction direction **E11** through some or all of the stroke potion **SF1**, and thereby draw the plunger **640** away from the pipettor orifice **604**. Throughout the retraction stroke, the pipetting channel **602** is not sealed because the rear seal **654** does not seal the rear section **644** from the rear opening **620E**.

[00477] The retraction of the plunger **640** retracts the piston **680** in the retraction direction **E11** as shown in **FIG. 32**, for example. The retraction of the piston **680** expands the effective fluid volume of the front chamber **679A**, thereby generating a negative pressure at the pipetting orifice **672**. The negative pressure draws a liquid sample volume **LV** of the liquid sample **LS** into the liquid collection volume **675** (in the front chamber **679A**) of the PD pipette tip **670**. The plunger **640** may be further retracted until the desired amount of liquid sample volume **LV** has been aspirated into the collection volume **675**. In some embodiments, no air cushion or air volume is present between the distal end **682A** of the piston **680** and the liquid sample volume **LV.**

[00478] The pipettor **600** may then be used to dispense the liquid sample volume **LV** from the PD pipette tip **670**. The drive mechanism **658** is operated to displace the plunger **640** in the extension direction **E10** and thereby push the plunger **640** toward the pipettor orifice **604**. Throughout the extension stroke, the pipetting channel **602** is not sealed because the rear seal **654** does not seal the rear section **644** from the rear opening **620E**.

[00479] The extension of the plunger **640** extends the piston **680** in the extension direction **E10**. The extension of the piston **680** displaces fluid volume from the front chamber **679A**, thereby expelling the liquid sample volume **LV** from the liquid collection volume **675** through the pipetting orifice **672**.

[00480] The pipetting system **601** and the pipettor **600** can be used to execute aspirating and dispensing procedures as described above using AD pipette tips **660** and PD pipette tips **670** selectively and interchangeably.

[00481] For example, an AD pipette tip **660** may be mounted on the pipettor **600** and used to aspirate and dispense in the AD mode. The AD pipette tip **660** is then removed (*e.g.*, ejected) from the pipettor **600**, and a PD pipette tip **670** is then mounted on the pipettor **600** and used to aspirate and dispense in the PD mode. Likewise, a PD pipette tip **670** can be

mounted on the pipettor **600**, used to aspirate and dispense in the PD mode then removed, and replaced with an AD pipette tip **660** that is used to aspirate and dispense in the AD mode.

[00482] Any number of each type of pipette tip may be used in a sequence of procedures (*e.g.*, the pipetting system **601** may aspirate and dispense in the AD mode (or, alternatively, the PD mode) using a series of AD pipette tips **660** before switching to aspirate and dispense in the PD mode (or the AD mode) using one or more PD pipette tips **670**.

[00483] It is not necessary for a user to use the pipetting system **601** and the pipettor **600** in with both AD pipette tips **660** and PD pipette tips **670**.

[00484] The pipette tips **660**, **670** may be removed from the pipettor **600** using any suitable technique and hardware. In some embodiments, the pipettor **600** includes an ejector (not shown in **FIGS. 28-33**; *e.g.*, an ejector sleeve) that pushes the pipette tips **660**, **670** off of the tip adaptor **614**. The pipettor **600** may include an ejector mechanism corresponding to the ejector mechanism **151** of the pipettor **100**, for example.

[00485] In some embodiments, the PD pipette tip **670** is removed from the pipettor **600** as follows. The plunger **640** is retracted in direction **E11** until the base **684** of the piston **680** abuts the tip adaptor **614**. The plunger **640** is retracted in direction **E11** until the piston engagement feature **646** is decoupled or disengaged from the plunger engagement feature **686**, thereby releasing the piston **680**. The PD pipette tip **670** is then removed using any suitable technique or mechanism for removing the tip body **678** from the tip adaptor **614**.

[00486] It will be appreciated that the pipetting systems and the pipettors as described (*e.g.*, the pipetting system **601** and the pipettor **600**) support both positive displacement pipetting and air displacement pipetting in a single pipetting channel. If both types of tips are required to be used on one instrument, no tool change is required.

[00487] With reference to **FIG. 36**, a pipetting system **701'** according to further embodiments is shown therein. The pipetting system **701'** corresponds to, is constructed, and operates in the same manner as the pipetting system **601**, except as discussed below. The pipetting system **701'** includes one or more AD pipette tips **660** (not shown in **FIG. 36**), and also a pipettor **700'** and one or more PD pipette tips **770'** that correspond to, are constructed and operate in the same manner as the pipettor **600** and the PD pipette tips **770'**, except as discussed below.

[00488] In the pipettor **600**, the plunger **740'** is lengthened or extended (as compared to the plunger **640**) so that the rear portion of the plunger **740'** maintains an air-tight seal with the rear seal **754'** throughout operation of the pipettor **700'** in its AD and PD aspirating and dispensing procedures, even when the plunger **740'** is fully extended (as shown in **FIG.**

36). Additionally, the tip body **778'** of the PD pipette tip **770'** includes a venting port **779C'** that fluidly connects the rear chamber **779B'** of the tip passage **774'** to the ambient atmosphere. The venting port **779C'** serves as a pressure relief port or passage from the tip passage **774'** between the piston **780'** and the pipettor **700'**. In this way, the venting port **779C'** can prevent the translation of the piston **780'** (in the tip body **778'**) and the plunger **740'** (in the barrel **710'**) from generating negative or positive pressures in rear chamber **779B'** that may interfere with control of the piston **780'**.

[00489] As discussed above, automated liquid handling systems may be used to transfer specific quantities of liquids, such as reagents or samples, between designated containers. Such systems may use pipettors both for aspirating and dispensing liquids. Advantages of automating liquid handling processes include increasing throughput and efficiency of operations and eliminating human errors, but may be contingent on the accuracy and repeatability of pipetting operations.

[00490] FIG. 37 is a schematic perspective view illustrating a further example of an automated liquid handling system **901** according to some embodiments. The system **901** includes elements similar to the pipetting system **101** and automated liquid handling system **10** described above, and description of similar elements may be omitted for brevity.

[00491] With reference to **FIG. 37**, the automated liquid handling system **901** includes a robotic arm assembly **914** comprising an arm member **912** that is adapted to hold one or more pipettors **900** (which may include one or more of the pipettors **100** or any other suitable pipettor(s)), and an actuator mechanism **934** (which may include the pipetting module positioning system **34A** and the actuator(s) **34B** of **FIG. 1**). The actuator mechanism **934** is configured to move the arm member **912** along at least one axis responsive to a control signal from a control circuit **920** (which may include the controller **20** of **FIG. 1**). In the example of **FIG. 36**, the robotic arm **914** has a first horizontal movement axis (X-direction, *e.g.*, forward and backward), a second horizontal movement axis (Y-direction, *e.g.*, left and right) and a vertical movement axis (Z-direction, *e.g.*, up and down). The controller circuit **920** may include at least one processor **925**, memory **910**, and input/output (I/O) circuit **915** that are operable to generate and transmit control signals to the actuator mechanism **934** to move the arm member **912** towards or away from a surface of a liquid sample **LS** along the at least one axis. More generally, the memory **910** may be a non-transitory storage medium configured to store computer readable instructions therein, and the controller circuit **920** may be configured to execute the computer readable instructions stored in the memory **910** to perform operations as described herein.

[00492] **FIG. 37** illustrates each of the pipettors **900** with an attached pipette tip **960**. The pipette tip **960** may be similar to the pipette tip **160** described herein in some aspects. For example, the pipette tip **960** may include a pipette orifice or opening **962** that provides a passage through the tip **960** to the pipettor **900**, where the passage can serve as a liquid sample collection volume. The pipette tip **960** may be an air displacement type tip or a positive displacement type tip as described herein. The pipette tip **960** may be retrieved from a pipette tip holder and moved vertically upwards by the robotic arm assembly **914** under control of the controller circuit **920** in an automated manner.

[00493] Further embodiments described herein may arise from realization that, as a liquid is aspirated by a pipettor **900** (in a liquid handler system **901** or in a standalone pipettor **900**), the volume of the liquid in the container is decreasing. If the container is of an unknown size, etc., the placement of the pipette tip **160** may impact whether the correct amount of liquid is effectively being aspirated into the pipettor **900** (*i.e.*, if the pipette tip **160** is positioned too high relative to the level of the liquid, the desired amount of liquid may not be aspirated). Thus, effective pipetting may require knowledge of variables such as the container from which the liquid is aspirated, the type of liquid, the container into which the liquid will be transferred, etc.

[00494] Capacitive liquid level detection (LLD) can be used to determine the level difference between immersion in and emersion from a sample liquid. Liquid level detection may be used to detect the fill level at a start of an aspiration or dispensation when the level is unknown to the instrument. The aspirated or dispensed volume can be calculated from the level difference and the cross-sectional area of the vessel. However, these methods may be too inaccurate for small volumes and large cross-sectional areas. Parasitic capacitances can also cause an inaccurate determination of the processed sample quantities or liquid volumes.

[00495] Embodiments described herein provide a conductive pipette tip **960** that is configured to provide a control window for axial movement of the pipettor(s) **100**. In contrast to some existing technologies, which may use conductive tips that can detect the surface of the liquid when in contact with the liquid, embodiments described herein allow for dynamic liquid level detection, based on changes in capacitance indicated by the signal from a conductive electrode **1002** on the pipette tip **960**, in some embodiments independent of a shape and/or size of a container of the liquid.

[00496] The conductive pipette tip **960** includes an arrangement of conductive **1002** and non-conductive **1001** areas. **FIG. 38** is an enlarged side view illustrating a conductive pipette tip **960** according to some embodiments described herein. The pipette tip **960**

includes a tip member **1000** having a distal end **960A** with an opening or orifice **962** that is sized and configured for aspirating and/or dispensing a liquid, and an opposite, proximal end **960B** that is configured for connection to an end portion the pipettor **900**. A conductive electrode **1002** extends along a surface of the pipette tip **960** (*e.g.*, on an outer surface of the tip member **1000**, and/or including portions integrated in a sidewall of the tip member **1000**). The tip member **1000** includes a non-conductive or electrically isolated tip "bottom" or "pod" **1001** at the end **960A** of the pipette tip **960**, between the pipetting orifice or opening **962** and the conductive electrode **1002**. A learning circuit may be implemented by (or may otherwise be in communication with) the controller circuit **920** that controls the axial movement of the pipettor **900** (*e.g.*, along the Z-axis or depth direction of the liquid to be aspirated). The learning circuit may be configured to detect and continuously monitor changes in capacitance due to contact between the conductive electrode **1002** and a liquid, as described herein. The inner surface of the tip member **1000** defines a passage through the pipette tip **960**, and can serve as a liquid sample collection volume. The inner surface of the tip member **1000** may be non-conductive, and the conductive electrode **1002** may be configured as a single electrode in some embodiments.

[00497] With reference to **FIG. 38**, the isolated tip bottom **1001** protrudes from the conductive electrode **1002** or is otherwise between the conductive or functional portion of the conductive electrode **1002** and the opening **962** at the end **960A** of the pipette tip **1000**. An external surface of the isolated tip bottom **1001** may be free of the conductive material or layer that forms the conductive electrode **1002**. For example, in some embodiments a lower portion of the conductive electrode **1002** adjacent the opening **962** may include a non-conductive material coating thereon to provide the isolated tip bottom **1001**. In some embodiments, the isolated tip bottom **1001** may be provided by a non-conductive portion of the tip member **1000** that extends beyond the conductive electrode **1002**. The isolated tip bottom **1001** may extend by a length or distance D of about 2 millimeters (mm) or more. The opposing end **960B** of the tip member **1000** includes an electrical interface (shown as conductive element **1004**) connected to a conductive interconnection **1003**, and a mechanical interface for connection to the pipettor **900** (*e.g.*, the end portion **112A** of the pipettor **100** described herein).

[00498] The conductive connection **1003** extends along the tip member **1000** and electrically connecting the conductive electrode **1002** to the conductive element **1004** for signal transmission (*e.g.*, to transmit signals from the conductive electrode **1002** to the

controller circuit **920**). The conductive portions **1002**, **1003**, **1004** of the tip member **1000** may be copper (Cu) or any suitable conductive material.

[00499] FIGS. 39A, 39B, and **39C** are cross-sectional views illustrating embodiments **1000a**, **1000b**, **1000c** of the tip member **1000** of **FIG. 38**. As shown in the embodiment of **FIG. 39A**, the conductive electrode **1002** and conductive interconnection **1003** may extend along an outer surface of the tip member **1000a** between the opposing ends **960A** and **960B** thereof, defining a conductive "wall" of the tip member **1000a**, in some embodiments extending on opposing sidewalls or even completely around the sidewalls of the tip member **1000a**. In some embodiments, as shown in **FIG. 39B**, the conductive interconnection **1003** may be injection molded or otherwise at least partially integrated or embedded in the sidewall(s) of the tip member **1000b**, rather than extending along the outside surface of the tip member **1000b**. In some embodiments, as shown in **FIGS. 38** and **39C**, the conductive electrode **1002** and/or the conductive interconnection **1003** may not completely extend around a perimeter or circumference of the tip member **1000c**. More generally, the tip member **1000** includes one conductive area **1002** at the bottom or distal end **960A**, one conductive area **1004** at top or proximal end **960B** (*e.g.*, inside the tip member **1000**) and a conductive interconnection **1003**, which may be embedded within a surface of or may be on an outside or external surface of the tip member **1000**.

[00500] The conductive electrode **1002** adjacent the end **960A** of the tip member **1000** may be provided in various different shapes. **FIGS. 40A**, **40B**, and **40C** are cross-sectional views illustrating embodiments **1002a**, **1002b**, **1002c** of the conductive electrode **1002** in various "crown" shapes. The crown shapes of the conductive electrode **1002a**, **1002b**, **1002c** include a plurality of end portions that protrude toward the non-conductive tip bottom **1001** such that, when submerged in a liquid to be dispensed, the conductive surface area may increase with submersion depth. More generally, the shape of the conductive electrode **1002** may define a surface area that varies with distance from the opening **962**. This feature can support dynamic LLD-proportional regulation in conductive liquids, as further described in the examples below.

[00501] Contact between the liquid to be aspirated and the conductive electrode **1002** may be detected as a capacitance by controller circuit **920** based on a signal received from the conductive electrode **1002**. **FIG. 41** is a diagram illustrating changes in capacitance **900c** with vertical position **912z** of a pipette tip **960** including a conductive electrode **1002** and non-conductive tip bottom **1001** in accordance with some embodiments, relative to a surface of a liquid **LS**.

[00502] With reference to **FIG. 41**, the capacitance **900c** indicated by the signal from the conductive electrode **1002** is substantially constant as the end **960A** of the tip member **1000** is moved towards a surface of a liquid **LS**, shown by the vertical position **912z**. When the non-conductive tip bottom **1001** contacts the liquid surface at time t=1 (as shown by (1)), the capacitance **900c** remains substantially unchanged. The capacitance **900c** remains substantially constant until the conductive electrode **1002** of the tip member **1000** contacts the surface of the liquid **LS** at time t=2 (as shown by (2)), at which point a near-instantaneous increase in the capacitance **900c** is indicated by the signal from the electrode **1002**. The increase in the capacitance **900c** remains substantially constant even as the submersion depth of the conductive electrode **1002** below the surface of the liquid **LS** is increased at time t=3 (as shown by (3)).

[00503] Still referring to **FIG. 41**, when contact is lost between the conductive electrode **1002** and the surface of the liquid **LS** at time t=6 (*e.g.*, when the liquid level falls below the conductive electrode **1002** due to the motion of the robotic arm **912** being insufficient to maintain contact between the conductive electrode **1002** and the liquid as the level of the liquid falls or rises due to aspiration or dispensing, as shown by (4)), a near-instantaneous decrease in the capacitance **900c** is indicated by the signal from the electrode **1002**. That is, contact (or absence of contact) between the conductive electrode **1002** and the surface of the liquid **LS** may be indicated as an abrupt change or jump in the detected capacitance. The detected capacitance may change or vary over a range of several picofarads (pF). For example, the change or difference in detected capacitance between contact and loss of contact between the conductive electrode **1002** and the surface of the liquid **LS** may vary over a range of about 0.1 to 15 pF, *e.g.*, about 0.5 to 10 pF or about 1 to 3 pF. In the example of **FIG. 40**, the detected capacitance variation is about 1.4 pF for contact versus loss of contact between the conductive electrode **1002** the liquid **LS**.

[00504] In some embodiments, the capacitance indicated by the signal from the electrode **1002** may not vary based on the depth by which the conductive electrode **1002** is submerged below the surface of the liquid **LS** (as shown by the substantially constant capacitance **900c** between time t=3 and t=6). That is, the detected capacitance may be substantially independent of an area of contact between the conductive electrode **1002** and the liquid **LS**, such that submersion depth variation may not alter the measured or indicated capacitance.

[00505] In other embodiments, the capacitance indicated by the signal from the conductive electrode **1002** may more gradually change or vary based on the depth by which

the conductive electrode **1002** is submerged below the surface of the liquid, for example, with conductive electrode shapes **1002a**, **1002b**, **1002c** that increase in surface area with submersion depth as shown in the examples of **FIGS. 12A** to **12C**.

[00506] The configurations of a conductive electrode **1002** and non-conductive tip bottom **1001** in the example tip members **1000** described herein may thus implement a capacitive sensor as an integrated circuit connected to the pipette tip **960**. For example, the capacitive sensor may be integrated on a printed circuit board (*e.g.*, which may also include the controller circuit **920** and associated motor driver circuits, readout circuits, etc.), and may be routed to the tip adapter of the pipettor **900** for connection to the conductive contact **1004** of the pipette tip **960** via a single conductive wire or cable. In some embodiments the capacitive sensor may be configured to indicate capacitance with a resolution of up to about 1 femtofarad (fF) at a desired data acquisition rate (*e.g.*, about 1000 sample per second). The amplitude and time resolution may allow precise detection of the liquid level.

[00507] The controller circuit **920** may thus dynamically detect and continuously monitor changes in the level of the liquid based on the changes in the detected capacitance due to contact (or loss of contact) between the conductive electrode **1002** and the liquid. The detected capacitance from the conductive electrode **1002** on the tip member **1000** may be used as a feedback signal or control loop to provide dynamic liquid level detection and liquid level following, without loss of contact between the pipetting orifice **962** of the pipette tip **960** and the liquid. In particular, based on the capacitance indicated by the signal from the conductive electrode **1002**, the controller circuit **920** may be configured to generate and transmit a control signal to the actuator mechanism **934** of the robotic arm assembly **914.** The control signal may be varied based on changes in the detected capacitance indicated by the signal from the conductive electrode **1002** to move the arm member **912** holding the pipettor(s) **100** towards or away from a surface of the liquid along the at least one axis (*e.g.*, the Z-axis), thereby maintaining contact between the pipette tip **960** and the liquid such that the non-conductive tip bottom **1001** of the tip member **1000** can be constantly submerged, regardless of changes in the liquid level.

[00508] To provide dynamic liquid level detection (LLD) and following, the non-conductive tip bottom **1001** of the tip member **1000** is sized to be larger than the desired control window, *e.g.*, extending by a length or dimension D of about 2 mm or more. The isolated tip bottom **1001** thus functions as a buffer between the conductive electrode **1002** and the surface of the liquid to be aspirated, and is thus submerged before the conductive electrode **1002** contacts the surface of the liquid. As such, the isolated tip bottom **1001** shifts

the jump in capacitance **900c** beyond the initial submersion of the tip bottom **1001** (as shown in (1) in **FIG. 40**) to the submersion of or contact with the conductive electrode **1002** (as shown in (2) in **FIG. 40**).

[00509] The delay in the change in capacitance **900c** due to the distance D of protrusion of the non-conductive tip bottom **1001** can be used to maintain submersion of the pipette tip **960** within the liquid. As the liquid level in a container is reduced, a loss of contact between the liquid and the conductive electrode **1002** is identified based on the change in detected capacitance **900c**, before contact between the opening **962** and the liquid surface is lost. In response, the arm member **912** is controlled to move the pipettor(s) **100** along the Z-axis, such that the pipette tip **960** follows the liquid level during aspiration or dispensing while maintaining the opening **962** submerged or immersed in the liquid.

[00510] The control signal provided to the actuator mechanism **934** may thus be varied based on changes in the detected capacitance indicated by the signal from the conductive electrode **1002**. The movement of the arm member **912** can be stepwise or continuous in some embodiments. For example, based on previous movement along the Z-axis, the controller circuit **920** can control the motion along the Z-axis to be more continuous or smooth.

[00511] In some embodiments, the direction of movement of the arm member **912** along the Z-axis may be mode-dependent, which may further reduce oscillation and smooth movement. For example, in aspirating mode the arm member **912** may be constrained so as to allow movement of the pipette tip **960** only in the downward direction towards the liquid, while in dispensing mode the arm member **912** may be constrained so as to allow movement of the pipette tip **960** only in the upward direction away from the liquid. That is, the actuator mechanism **934** may have a first operating mode in which the arm member **912** is restricted to motion towards the surface of the liquid along the at least one axis during the aspirating, and a second operating mode in which the arm member **912** is restricted to motion away from the surface of the liquid along the at least one axis during the dispensing.

[00512] In some embodiments, the controller circuit **920** may calculate or estimate an aspirated or dispensed volume of the liquid based on a distance of motion of the arm member **912** along the Z-axis, and may control subsequent motion of the arm member **912** along the Z-axis based on the aspirated or dispensed volume that was calculated or estimated. That is, the controller circuit **920** may utilize the variation in capacitance along with the previous movement of the arm member **912** along the z-axis to estimate the amount of liquid that has

been dispensed or aspirated, and may generate the control signals to the actuator mechanism **934** to predictively move the arm member **912** in response.

[00513] The controller circuit **920** thus uses the signal from the conductive electrode **1002** to measure or determine the capacitance, and monitor variations in the capacitance to predict (*e.g.*, from the jump or abrupt change in detected capacitance caused by a loss of contact between the conductive electrode **1002** and the liquid) that the non-conductive tip bottom **1001** of the pipette tip **960** will soon lose contact with the liquid, thereby continuously and dynamically monitoring the liquid level as it changes. In response, the controller circuit **920** transmits a control signal to the actuator mechanism **934** to move the arm member **912** holding the pipettor(s) **100** along the Z-axis (*e.g.*, down/towards the liquid in aspirating mode, or up/away from the liquid in dispensing mode), providing dynamic liquid level following.

[00514] The extension of the non-conductive tip bottom **1001** below or beyond the portion of the conductive electrode **1002** providing the signal for capacitance detection can allow the controller to move the arm member **912** to follow the liquid level while maintaining the opening **962** of the pipette tip **960** submerged or immersed in the liquid (due to the buffer provided by the distance D between the conductive electrode **1002** and the opposite end of the non-conductive tip bottom **1001**).

[00515] Dynamic liquid level detection and following as described herein may be used with various liquid solutions, including conductive and non-conductive liquids, independent of a shape or size of a container of the liquid. For example, embodiments described herein may (but are not limited to) be used with ethanol, MilliQ water, and salted buffer solutions. The control signals provided to the actuator mechanism **934** may be continuously regulated (*e.g.*, with nonconductive liquids), or may be regulated in a stepwise manner (*e.g.*, for high conductive liquids).

[00516] Further embodiments described herein may arise from realization that, during or after the aspiration of liquid in a pipetting or other liquid handling system, some of the liquid will evaporate in the channel, thereby increasing the volume of trapped air, which may cause less liquid to be aspirated than intended. Precision and accuracy in pipetting performance may not be possible without compensation for evaporation.

[00517] Embodiments described herein thus provide methods for detecting whether there is evaporation in the pipetting channel, for example, during or after aspiration of a liquid. If an increase in pressure is detected in the channel, systems described herein are configured to automatically deploy countermeasures to prevent (or reduce the rate of) the

evaporation. Some conventional technology may require analysis and development of liquid classes, where for each developed liquid class, compensation parameters may need to be determined and updated in the software. In contrast, some embodiments described herein do not require differentiation of liquid classes and/or the amount of evaporation to be expected per liquid class in order to quantify and/or compensate for evaporation.

[00518] **FIGS. 42**, **43A**, and **43B** schematically illustrate evaporation detection in a pipette tip of an automated pipetting system **1101** according to some embodiments described herein. The system **1101** includes elements similar to the pipetting systems **101**, **901** and automated liquid handling system **10** described above, and description of similar elements may be omitted for brevity.

[00519] With reference to **FIGS. 42** and **43A**, the system **1101** includes a pipettor **1100**, one or more pressure sensors **1156** coupled to a channel **1102** of the pipettor **1100**, and a controller or control circuit **1120**. The controller circuit **1120** may include the controller(s) **20, 920** and associated processor **925**, memory **910**, and I/O circuits **915** described herein. The pressure sensor(s) **1156** are fluidly coupled to the pipetting channel **1102**. In some embodiments, the pressure sensor **1156** is an in-line pressure sensor positioned in or along the pipetting channel **1102**, similar to or including the pressure sensor **256** of **FIG. 14**, or in the pipette tip **1160** attached to the distal end of the pipettor **1100**. In other embodiments, the channel **1102** fluidly communicates with the pressure sensor **1156** via a sensor port. The pipette tip **1160** can be removable or replaceable (such as the pipette tips **160**, **960** described herein) or may be integrated into the pipettor **1100**. More generally, the pipettor **1100** may be of any suitable type or design, and may include any suitable plunger configuration (which may include any of the pipettor and plunger configurations described herein). A drive mechanism **1128** (including one or more actuators) may be operated to drive the plunger **1140** to aspirate, dispense, and/or perform compensation operations as described herein responsive to control signals from the controller circuit **1120**. The drive mechanism **1128** may be and/or may operate in a manner similar to any of the drive mechanisms (*e.g.*, **128**, **148**) described herein.

[00520] Operations described herein can be executed by or through the controller circuit **1120**. The controller circuit **1120** receives pressure signals from the pressure sensor **1156** indicating the pressure in the pipetting channel **1102**. In particular, based on the pressure signals from the pressure sensor **1156**, the controller circuit **1120** may determine a quantitative measurement of the pressure (or pressure difference) in the channel **1102**. The pressure measurement may indicate air pressure or pressure of one or more other gases in the

channel **1102**. The controller circuit **1120** may operate the drive mechanism **1128** to control movement of the plunger **1140** in response to the signals from the pressure sensor **1156** (*e.g.*, via feedback loop **1150**) to perform aspiration, dispensing, and/or compensation operations described herein.

[00521] With reference to **FIG. 43A**, the controller circuit **1120** can detect evaporation of a liquid in the channel based on the pressure indicated by the signal from the pressure sensor **1156**. For example, after aspiration of a liquid, a liquid sample **LS** may occupy a volume **V1** (with a fill level **h1**) in the pipette tip **1160** attached to the distal end of the pipettor **1100**, with an initial pressure **p1** in the channel **1102**. The controller circuit **1120** removes the pipette tip **1160** from the container including the liquid volume, for example, by controlling movement of the arm member **912** away from the container of a liquid volume via the actuator mechanism **934** as described herein. If evaporation occurs, the number of molecules in the gas phase in channel **1102** (and the volume between the plunger **1140** and the liquid sample **LS**) increases. As a result, a portion of the liquid sample **LS** is pushed through the opening **1162** in the pipette tip **1160** and forms a bead **LB**, resulting in a reduction in the volume **V2** (and fill level **h2**) occupied by the liquid sample **LS** in the pipette tip **1160**. The surface tension at the surface of the bead **LB** increases the internal pressure **p2** in the channel **1102**.

[00522] FIG. 43B illustrates an example of bead **LB** formation due to evaporation of an EtOH solution **LS**, for a 1 ul target volume with a 10 ul tip volume. As shown in **FIG. 43B**, after removal of the pipette tip **1160** from the liquid volume but before evaporation occurs, the liquid sample **LS** is fully contained in the pipette tip **1160**. With the pipette tip **1160** removed from the liquid volume, the opening **1162** is sealed by the effect of surface tension, such that changes in pressure in the channel **1102** can be attributed to evaporation. As evaporation occurs, pressure in the channel **1102** may increase, such that the liquid sample **LS** is forced out of the opening **1162** in the tip **1160**, forming a bead **LB** as long as the radius of the bead decreases. With ongoing evaporation, the bead reaches the shape of a hemisphere (shown with radius **r1**), at that time the bead radius starts increasing (shown with radius r2) and the pressure inside the channel **1102** decreases again.

[00523] The controller circuit **1120** utilizes the signals from the pressure sensor(s) **1156** to measure the pressure inside the channel and the displacement volume. More particularly, the signals from the pressure sensor(s) **1156** can be used to monitor the pressure change inside the channel **1102** after aspiration, due to the change in volume caused by

evaporation and bead formation (*e.g.*, from volume **V1** before evaporation to volume **V2** after evaporation was ongoing for some time).

[00524] Operations which may be performed by the controller circuit **1120** to control the position and aspiration of the pipettor **1100** and detecting changes in pressure in the channel **1102** to detect evaporation are described below with reference to the graphs of **FIGS. 44A** and **44B** and the flowchart of **FIG. 45**. In the graphs of **FIGS. 44A** and **44B**, line **4401** indicates the gauge pressure (in Pascals (Pa)) determined from the signals from the pressure sensor(s) **1156**, and line **4402** indicates the volume displaced by the plunger **1140** (in microliters (μl)).

[00525] With reference to **FIGS. 44A**, **44B** and **FIG. 45**, the pipettor **1100** is moved (*e.g.*, via arm member **912** responsive to control signals provided to actuator **934**) such that the pipette tip **1160** contacts a liquid volume to be aspirated, as shown at step **1111**. Capillary effects may force the liquid into the pipette orifice **1162** in response to the contact (thereby increasing the pressure in the pipetting channel **1102** as shown at step **1112**). The liquid sample **LS** is aspirated into the pipettor **1100**, as shown at step **1112a**, by driving the plunger **1140** responsive to control signals from the controller circuit **1120**. At step **1113**, aspiration is completed, and at step **1114** the pipette tip **1160** is removed from the liquid volume (*e.g.*, via arm member **912** and actuator **934**). When the pipette tip **1160** is in the air, the orifice **1162** may be substantially sealed by the surface tension of the liquid sample **LS**, such that changes in pressure in the channel **1102** may be due to evaporation. With the tip **1160** in the air or otherwise removed from the liquid volume, the pressure change over time dp/dt is monitored as shown at step **1115** based on the signals from the pressure sensor(s) **1156**. The plunger **1140** may also be moved in the channel **1102** (*e.g.*, by the drive mechanism **1128** responsive to a control signals from the controller **1120**) by a relatively small distance or displacement ΔV_{Dis} to probe the elasticity of the system (*e.g.*, a combination of air cushion elasticity and surface tension) at step **1116**. The change in volume ΔV_{Dis} due to displacement of the plunger **1140** may be small enough to avoid dripping of the liquid bead **LB** from the tip **1160**.

[00526] Evaporation of the liquid sample **LS** may be detected if the signals from the pressure sensor(s) **1156** indicate an increase in pressure over time, *e.g.*, between **1114** and **1116**. The pressure may be monitored at step **1115** immediately after removal of the tip **1160** from the liquid volume (*i.e.*, prior to bead formation **LB**), to ensure accuracy.

[00527] In addition to detection of evaporation, the rate of evaporation is calculated at step **1118**, in some embodiments along with estimation of an aspiration error induced by the

evaporation. For example, the evaporation rate may be calculated based on a change in the pressure indicated by the pressure signal over time (*i.e.*, the slope of the line **4401**) as monitored at step **1115**, in some embodiments together with the measurement of a pressure change resulting from the movement of the plunger **1140** at step **1116**. The evaporation rate may be proportional to the change in the pressure over time dp/dt. As shown in **FIG. 44A**, the pressure change rate measurement (and thus the evaporation rate) can be determined by line fit to the pressure curve between removal of the pipette tip **1160** from the liquid volume at step **1114** and piston or plunger displacement at step **1116**.

[00528] As noted above, in some embodiments the evaporation rate may be calculated using in addition the measurement of a pressure change resulting from the movement of the plunger **1140** at step **1116**. In particular, at step **1117**, the change in the pressure Δp_{Dis} (as indicated by the pressure signal from the pressure sensor(s) **1156**) caused by the change in volume ΔV_{Dis} resulting from the plunger displacement at step **1116** is measured and used to calculate the evaporation rate at step **1118**. That is, as shown in **FIG. 44B**, the pressure response Δp_{Dis} due to the small volume change ΔV_{Dis} responsive to the movement of the plunger **1140** in the channel **1102** may be used to calculate the evaporation rate E = dVe/dt from the pressure change rate measurement, using the following equation:

$$\frac{dV_e}{dt} = \frac{\Delta V_{Dis}}{\Delta p_{Dis}} \frac{dp_e}{dt}$$

Note that the described methods do not require prior knowledge of the aspirated liquid class for the determination of the evaporation rate. Liquid class dependencies are eliminated because the dependence on surface tension of the terms $\Delta V_{Dis}/\Delta p_{Dis}$ and dpe/dt cancel each other in the proposed formula.

[00529] The evaporation rate may be determined by continuously controlling the position or displacement of the plunger **1140** in the channel **1102** based on the pressure indicated by the pressure signal, such that the pressure in the channel **1102** is maintained substantially constant. Under the condition of constant pressure, the evaporation rate is directly given by the displacement rate of the plunger **1140** as the following equation illustrates:

$$\frac{dV_e}{dt} = \frac{dV_{Dis}}{dt}$$

[00530] As such, the system **1101** can detect that evaporation has occurred based on the pressure (or change in pressure) in the channel **1102** or tip **1160**, as indicated by the signals from the pressure sensor(s) **1156**. While the graphs of **FIGS. 44A** and **44B** illustrate

example operations from experimental data using EtOH as the liquid sample **LS**, it will be understood that the detected pressure changes (and calculated evaporation rates) may significantly differ based on the material of the liquid sample LS. For example, using H_2O as the liquid sample **LS** may result in a significantly smaller pressure change and calculated evaporation rate in response to the operations of **FIG. 45**. In some embodiments, comparison of the differences in pressure change and/or evaporation rate may be used for identification of the liquid sample **LS** in the pipette tip **1160**. However, in the example operations described herein, the evaporation rate may be calculated independent of a surface tension or type of the liquid of the aspirated liquid sample **LS**. That is, evaporation detection and calculation of evaporation rate as described herein can be performed based on the pressure change rate measurement without determining the surface tension of the liquid sample **LS**, and without prior knowledge or identification of the liquid class of the liquid sample **LS**.

[00531] The evaporation rate E (as calculated at step **1118**) and the aspiration time (*i.e.*, the duration of the aspiration between steps **1112** and **1113**) can be used to estimate the additional gas or vapor volume that is generated by evaporation during aspiration, also referred to herein as the evaporation volume (Vevap). The evaporation volume Vevap may be equal to or otherwise indicate the amount of under-aspiration caused by the evaporation. Embodiments described herein may thus use the estimated evaporation volume Vevap as a relevant parameter to decide whether the evaporation rate is low enough to be tolerated, or whether evaporation is greater than a predetermined threshold (TH) for reducing or compensating for the evaporation. The threshold for such a determination may vary based on the desired accuracy; for example, if 5% accuracy is acceptable for a particular dispensing application, an evaporation volume of less than 5% of the target volume may be tolerable, while an evaporation volume of more than 5% of the target volume may require compensation.

[00532] Referring again to **FIG. 42**, a feedback loop **1150** may be used to perform compensation operations automatically or programmatically, *e.g.*, based on calculation of the evaporation rate from the pressure signals and comparison of the evaporation rate to the threshold. For example, if the evaporation rate E is above the threshold TH, one or more countermeasures may be initiated by the controller circuit **1120** (*e.g.*, by repeating the aspiration and by operating the drive mechanism **1128** to adapt the aspiration by the plunger **1140**) to compensate for the detected evaporation.

[00533] **FIGS. 46A** and **46B** are flowcharts illustrating evaporation compensation operations during aspiration (*e.g.*, between blocks **1112** and **1113** of **FIG. 45**) and after tip

removal (*e.g.*, after block **1114** of **FIG. 45**), respectively, in accordance with some embodiments. The compensation may include multiple operations performed by the controller circuit **1120** based on the pressure signals from the pressure sensor **1156** to compensate for the evaporation. For example, the evaporation compensation operations may include performing a prewetting operation (by which an amount of the liquid is aspirated and dispensed prior to aspirating the liquid for delivery), adapting one or more aspiration parameters (*e.g.*, to over-aspirate a further amount of the liquid volume to compensate for under-aspiration due to evaporation), and/or controlling movement of the plunger **1140** in the pipetting channel **1102** (*e.g.*, to maintain a defined or predetermined constant pressure in the pipetting channel **1102** and/or in the pipette tip **1160** to avoid dripping).

[00534] With reference to **FIG. 46A**, aspiration (*e.g.*, at or during step **1112** of **FIG. 45**) may include calculating an aspirated volume (Va) of the liquid sample **LS** at step **1119a**. The calculation of the aspirated volume Va at step **1119a** may account for expansion of the air cushion (**AC** in **FIG. 16**). For example, the aspirated volume Va may change by an equal amount or in proportion to changes in the air cushion volume. In some embodiments, the aspirated volume Va may be calculated as follows:

$$Va = (pi - pa)V_0/pa + A\Delta x,$$

where pi/pa represents the pressure inside/outside the channel, V_0 represents the initial air cushion volume, A is the plunger cross sectional area, and Δx represents the distance of plunger movement.

[00535] At step **1121** the calculated aspirated volume Va is compared to a desired or target volume (Vtarget). In some embodiments, a control loop may be used to reduce or minimize a difference between the aspirated volume Va and the target volume Vtarget. For example, the controller circuit **1120** may include a proportional–integral–derivative controller (PID controller) that uses a control loop mechanism employing feedback to continuously calculate an error value as the difference between a desired target volume Vtarget and the aspirated volume Va and apply a correction to the plunger movement. In particular, if the comparison of the aspirated volume Va to the target volume Vtarget is beyond a desired error threshold (*i.e.*, if Va -Vtarget > errorTH), compensation operations may be performed at step **1123a**. For example, one or more aspiration parameters may be adapted to reduce the aspiration error, and the aspiration may be altered or repeated based on the adapted parameters. The operations of FIG. **46A** for calculating the aspirated volume Va at step **1119a**, comparing the aspirated volume Va to the target volume Vtarget at block **1121a**, and using the comparison result (Va – Vtarget) as input to a control loop for

controlling or correcting the plunger movement may be continuously performed during aspiration in order to reduce or minimize the difference between the calculated aspirated volume Va and the target volume Vtarget. The operations of **FIG. 46A** are performed with the tip submerged (*e.g.*, before step **1114** of **FIG. 45**). The calculation at step **1119a** is based on a known plunger position and the air volume expansion (or contraction) derived from the measured gauge pressure. The operations of FIG. **46A** may be independent of evaporation, and thus may be performed even if the evaporation rate was not assessed in a previous pipetting step.

[00536] Additionally or alternatively, in **FIG. 46B**, the aspirated volume Va may be calculated (or recalculated if the operations of **FIG. 46A** have been previously performed) at step **1119b** based on the change in the pressure indicated by the signals from the pressure sensors **1156** after the removing the pipette tip **1160** from the liquid volume (*e.g.*, at step **1114** of **FIG. 45**). At this time, effects of unintended liquid inflow during withdrawal of the tip as may be caused by the effect of surface tension is reflected in the aspirated volume Va. If the (re)calculated aspirated volume Va is less than the target volume Vtarget by a sufficient margin at step **1121b**, one or more aspiration parameters are adapted at step **1123b**, and aspiration is repeated. For example, a further amount of liquid may be over-aspirated (based on the calculated or estimated evaporation rate) to compensate for the initial under-aspiration caused by the evaporation, thereby ensuring that the desired amount of liquid is delivered. In some cases, it may be enough to report or log the aspiration error (Va – Vtarget).

[00537] At step **1122**, the calculated evaporation rate E (or evaporation volume Vevap) is compared to a threshold TH. For example the threshold TH may be volume-based for comparison to the calculated evaporation volume Vevap. If the evaporation volume or rate is below the threshold TH, no action may be taken. If the evaporation rate or volume exceeds the threshold TH, one or more compensation operations are performed at step **1123b**, and the aspirated volume Va is recalculated at step **1119b**. As such, the evaporation rate can be accounted for in the calculation of Va. Based on the recalculated aspirated volume Va at step **1119b**, the system can decide on and perform compensation measures at step **1123b** to increase accuracy (*e.g.*, repeating a pipetting step, prewetting, adapting parameters, or simply logging or reporting the deviation from the target volume Vtarget).

[00538] The operations shown in **FIGS. 46A** and **46B** may be performed in combination, or independently of one another. That is, the operations of **FIGS. 46A** and **46B** may be performed sequentially, or the operations of **FIG. 46A** may be performed during aspiration without further performing the operations of **FIG. 46B** after tip removal, or the

operations of **FIG. 46B** may be performed after tip removal without performing the operations of **FIG. 46A** during aspiration.

[00539] As noted above, the evaporation compensation operations at steps **1123a, 1123b** may include, but are not limited to, prewetting, adapting aspiration parameter(s), and/or controlling plunger movement. For example, a prewetting operation may be performed at step **1123a, 1123b** to reduce or prevent evaporation in the tip **1160**. Prewetting can increase humidity within the pipette tip **1160**, thereby reducing or prevent evaporation in the tip air space and increasing accuracy of the aspiration. Prewetting of the pipette tip can thus reduce or eliminate the pressure change indicated by the signals from the pressure sensor(s) **1156**.

[00540] Additionally or alternatively, one or more aspiration parameters may be adapted at steps **1123a, 1123b** (*e.g.*, to over-aspirate to compensate for under-aspiration, or vice versa), as discussed above. For example, when aspirating water, water surface tension may lead to a measurable inflow into the tip **1160** during withdrawal at step **1114**, which can be corrected by reducing the amount of aspiration.

[00541] In addition to or as an alternative to the above, at step **1123b**, the plunger **1140** in the pipetting channel **1102** may be controlled to move by a distance sufficient to maintain a defined or predetermined constant pressure in the pipette tip **1160** and/or channel **1102**. For example, the position or displacement of the plunger **1140** in the channel **1102** may be continuously controlled based on the pressure indicated by the pressure signal, such that the pressure in the channel **1102** and/or tip **1160** is maintained substantially constant, as discussed above. The constant pressure may be a predetermined pressure, or may be based on the measured pressure in the channel immediately after removal of the pipette tip from the liquid volume (*e.g.*, at step **1114**). Keeping the pressure constant or moving the plunger **1140** to aspirate a small amount of air (after liquid aspiration and removal of the tip **1160** from the liquid volume) may thus reduce or avoid dripping from the bead formation **LB** at the orifice **1162** of the pipette tip **1160**. The pressure sensor(s) **1156** may be provided in the channel **1102** or pipette tip **1160** to provide the pressure signals with a high level of precision (sufficient to counteract tip bead formation LB) even with small volumes of trapped air, *e.g.*, as described herein with reference to dual plunger pipettor (*e.g.*, pipettor **100**), serial plunger pipettor (*e.g.*, pipettor **200**), and/or dual metering pipette (*e.g.*, pipettor **1200**) embodiments.

[00542] It will be understood that the adaptation of pipetting parameters and/or other compensation operations at steps **1123a, 1123b** are not limited to evaporation compensation. For example, as noted above, adapting the aspiration based on a difference between the

calculated aspirated volume Va and the target volume Vtarget may also provide hydrostatic and capillary pressure compensation. The compensation operations may also include providing a viscosity-dependent pipetting speed (*e.g.*, by adapting the aspiration speed based on the change in the pressure Δp indicated by the signals from the pressure sensors **1156** relative to a target pressure change Δp_{target}), and/or heat transfer compensation (*e.g.*, by initiating prewetting if the temperature of the liquid is below a minimum temperature). Such operations may be used to effectively compensate for differences in liquid density, surface tension, wettability, and/or viscosity of the liquid sample **LS**.

[00543] Further embodiments described herein may arise from realization that, in conventional pipetting or other liquid handling systems, a precise piston or plunger control system is typically used to control the displacement of air. For example, some pipetting systems aspirate liquid into a disposable tip and dispense the liquid into another container, with an air cushion AC between the liquid sample LS and the pipetting channel, also referred to as an air displacement pipette or pipette tip. This may avoid cross-contamination of the pipettor with different liquid samples. The pipetting performance may primarily be derived from the geometry (*i.e.*, based on the distance of movement or stroke of the piston or plunger within the interior volume or bore of the pipette) and precision and/or accuracy of the plunger control motor that operates the plunger, with the higher the positioning precision and accuracy, the better the pipetting performance (*e.g.*, with respect to over- or under-aspiration). Therefore, conventional pipetting performance may be limited to the resolution of the encoder for the plunger control motor.

[00544] Embodiments described herein provide a dual metering pipetting system that is configured to control plunger position based on an amount of displaced air in the pipetting channel, as determined from a sensor signal (for example, as output from a flow rate sensor coupled to the pipetting channel). The system may also include a negative or positive pressure source coupled to a valve and/or flow restriction mechanism. The air flow over time (flow rate) indicated by the sensor signal can be used to determine the amount of air displaced (*i.e.*, a displaced air volume) in the channel. The flow rate sensor may have sufficient sensitivity to measure a wide range of flow rates (*e.g.*, over a range of measurement of an order of magnitude or more), which may be difficult to implement using conventional encoder and plunger control motors.

[00545] In some embodiments, the flow rate sensor may be implemented by a pressure sensor with sufficient sensitivity to provide a feedback loop for controlling the channel pressure/air displacement volume. For example, the flow rate sensor may be

implemented by two pressure sensors in a parallel arrangement (also referred to herein as a dual metering or dual flow sensor) across a flow restriction mechanism. The flow rate sensor, valve, and pressure source(s) may thus provide a control loop to control the liquid flow inside the pipetting channel, with the inline measurement provided by the flow rate sensor, allowing for precise and accurate control of the liquid flow. As the plunger position can be determined based on the air displacement volume calculated from the flow rate or pressure change measurement, highly precise plunger movement may not be required, and thus precision requirements for the plunger control motor and/or encoder may be relaxed.

[00546] **FIG. 47** is a side view illustrating a dual metering pipettor that may be used in an automated pipetting system according to some embodiments. **FIG. 48** is an enlarged schematic diagram illustrating the dual metering pipettor of **FIG. 47** with the pipette tip removed. The automated pipetting system (*e.g.*, **101**, **901, 1101**) may include one or more of the illustrated pipettors **1200**. If multiple pipettors **1200** are provided, the pipettors **1200** may be operated independently of one another or in tandem. For the purpose of discussion, only a single pipettor is described below.

[00547] With reference to **FIGS. 47** and **48**, the pipettor **1200** includes a mechanical interface **1207**, a frame **1208**, an electrical interface (shown as a printed circuit board) **1209**, a pressure control system **1206**, a tip mount feature or adaptor **1276**, and a manifold **1275**. The pressure control system **1206** includes sensors **1279A**, **1279B**, **1280**, a plunger **1240** in the pipetting channel **1202** and controlled by a drive mechanism **1228**, and an air flow control system **1271** including a valve **1278** and a switchable flow restriction mechanism **1277** (see **FIG. 53**) that is operable to couple the channel **1202** to a pressure source. A pipette tip **1260** can be attached to the tip adaptor **1276** and includes a pipetting orifice **1262** and a liquid collection volume **LV** that are in fluid communication with the pipetting channel **1202** via passages **1274** in the manifold **1275**. As used herein, the pipetting channel **1202** may generally include features in communication between the tip **1260**/adaptor **1276** and the chamber or barrel including the plunger **1240** therein.

[00548] The plunger mechanism is operable in response to control signals provided to the drive mechanism **1228** to translate the plunger **1240** to change a pressure in the pipetting channel **1202** to aspirate or dispense a liquid volume. The drive mechanism **1228** may be a linear drive system including a plunger actuator and an encoder. A linear sensor **1229** (*e.g.*, with about 1 μm resolution) may be configured to measure a deflection caused by a tip **1260** which touches the side wall of a vessel.

[00549] The components of the pipettor **1200** may be mounted on the frame **1208**. The mechanical interface **1207** may couple the pipettor **1200** to automated pipetting systems (*e.g.*, **101**, **1101**) as described herein. For example, the mechanical interface **1207** may provide a mechanical coupling between the frame **1208** (including the components of the pipettor **1200** thereon) and an arm member (*e.g.*, **912**) of a robotic arm assembly (*e.g.*, **914**) to control movement of the pipettor **1200** along one or more axes (*e.g.*, the Z-axis) as described herein.

[00550] The electrical interface **1209** may include one or more controller circuits **1220** (which may include any of the controller circuits **20**, **920**, **1120** described herein), including an input/output (I/O) circuit (*e.g.*, **915**), memory (*e.g.*, **910**), processor/microcontroller (*e.g.*, **925**), and driver circuits for the motors/drive mechanisms **1228**. Readout and preprocessing functions of the sensors **1279**, **1280** may also be performed via the electrical interface **1209**. More generally, the memory may be a non-transitory storage medium configured to store computer readable instructions therein, and the controller circuit **1220** may be configured to execute the computer readable instructions stored in the memory to perform operations as described herein.

[00551] Accordingly, pipetting control operations described herein can be executed by or through the controller circuit **1220**. The controller circuit **1220** receives sensor signals from one or more of the sensors **1279A**, **1279B**, **1280** coupled to the pipetting channel **1202**. The sensors include pipetting channel pressure sensors **1279A, 1279B** (which may include the pressure sensors **179** described herein) and sensor **1280** configured to output a sensor signal from which the air displacement in the channel **1202** can be determined, described herein primarily with reference to a flow rate sensor **1280**. The pipetting channel pressure sensors **1279A, 1279B** may include the pressure sensors **179** described herein. The flow rate sensor **1280** may be configured to output sensor signals indicating a flow rate in the channel **1202**, for example, as detected or otherwise identified based on pressure change data of air (or other gases) in the channel **1202**.

[00552] Based on the sensor signals from the sensor **1280**, the controller circuit **1220** may determine a displaced air volume in the channel **1202**. The controller circuit **1120** may transmit one or more control signals (*e.g.*, to a pressure source) to control a position of the plunger **1240** in the channel **1202** based on the displaced air volume in the channel **1202** or otherwise in response to the signals from the pressure sensor **1279A**, **1279B**, **1280** to perform aspiration and/or dispensing operations described herein. The control signals may include, but are not limited to, the plunger actuator signals that directly operate the drive

mechanism **1228** and/or associated control signals, such as flow restriction control signals that operate or control the operating state of a flow rate or flow restriction mechanism **1277** (see **FIG. 53**), and/or valve control signals that operate or control the operating state of the valve **1278**. The pressure source to provide the pressure difference which drives the flow can thus be the plunger **1240**/actuator **1228**, a pressure reservoir **1290** (see **FIG. 53**), or other pump mechanism.

[00553] The valve **1278** is operable to couple the channel **1202** to a pipette tip **1260** mounted on the tip adaptor **1276** and/or to a pressure source (see **FIG. 53**) responsive to a valve control signal from the controller circuit **1220**. As described in greater detail below, the pressure source may include a negative pressure source and a positive pressure source, which can be selected (responsive to operation of the valve **1278** and the switchable flow restriction **1277**) to control a direction of the air flow in the channel **1202**.

[00554] FIG. 49 is a simplified schematic diagram illustrating the plunger **1240** and manifold assembly **1275** of the dual metering pipettor of **FIG. 48**. **FIG. 50** is an enlarged view of the area **L** in **FIG. 49**, illustrating the microfluidic manifold **1275** and the flow rate sensor **1280** in greater detail. With reference to **FIGS. 49** and **50**, the manifold **1275** interconnects the pipetting channel **1202** and plunger **1240** with the pressure sensors **1279**, **1280** and the valve **1278**. The manifold **1275** includes a plurality of microfluidic passages **1274** therein that are configured to couple the channel **1202** to the tip adaptor **1276** responsive to operation of the valve **1278**. A dead volume or death volume (*i.e.*, a residual volume of the aspirated liquid that may be lost to waste) may be defined within the area **F**, for example, as resulting from connections provided by the microfluidic passages **1274** and/or sensor volumes.

[00555] The manifold **1275** compactly integrates the pipette channels **1274**, sensors **1279A**, **1279B**, **1280**, and valve **1278** operably coupled with the plunger **1240**, thus reducing the distances of all interconnected fluid channels. In some such embodiments, the manifold **1275** may be configured to reduce or minimize the dead volume (for example, to provide death volumes of less than about 120 µl) based on one or more dimensions of the micro-fluidic passages or channels **1274** therein. For example, each passage **1274** in the microfluidic manifold **1275** may have a diameter in the range of from about 0.2 mm to 0.8 mm. In the illustrated embodiment, the flow rate sensor **1280** is coupled to the microfluidic passages **1274** to provide the pressure change measurements described herein. Some embodiments described herein may provide precise pressure change measurements with death volumes of less than about 50 µl, or with a volume range from about 50 µl to 100 µl.

[00556] FIG. 51 is a perspective view of the manifold **1275** mounted on a portion of the PCB **1209** including the pressure sensors **1279A**, **1279B** and the flow rate sensor **1280**, also referred to herein as a manifold assembly. As shown in the manifold assembly of **FIG. 51**, the manifold **1275** and the sensors **1279**, **1280** may be mounted on opposite sides of the PCB **1209** in some embodiments, with the microfluidic passages **1274** routed under and/or through the PCB **1209** for coupling to the sensor(s) **1279** and/or **1280**. The PCB **1209** may include metallized holes to prevent swelling when exposed to moisture. The air connections and/or sensor connections provided by the microfluidic passages **1274** may provide a death volume of less than about 50 µl in some embodiments. The manifold **1275** may also be used in some embodiments without the flow rate sensor **1280** (*e.g.*, in the dual plunger embodiments of **FIGS. 2-13**), with a further reduction in death volume (*e.g.*, less than about 20 µl). That is, it will be understood that dual metering pipettors as described herein may be operable with single- or dual-plunger embodiments, as the air displacement is precisely measured based on integration of two or more pressure sensors **1279A**, **1279B** in the manifold **1275** as described herein.

[00557] FIG. 52 is a schematic circuit diagram illustrating connections of the sensors **1279**, **1280** in the manifold **1275**. With reference to **FIG. 52**, the valve **1278** is operable to couple the channel **1202** (including the plunger **1240** therein) to the pipette tip **1260** mounted on the tip adaptor **1276**. A pressure sensor **1279B** configured to provide a relatively higher range of pressure measurement (*e.g.*, up to about 350 millibar or more) is mounted on the manifold **1275** and is coupled via the microfluidic passages **1274** to the channel **1202**, which may define a relatively large swept volume (*e.g.*, with a relatively large diameter (~ 6mm) plunger **1240** therein). A pressure sensor **1279A** configured to provide a relatively lower range of pressure measurement (*e.g.*, up to about 10 millibar or more) is mounted on the manifold **1275** and coupled via the microfluidic passages **1274** to the pipette tip **1260** on the tip adaptor **1276**. In some embodiments, an additional pressure sensor **1256** (such as the pressure sensors **256**, **1156** described herein) may be included in or coupled to the pipette tip **1260**. A relatively small death volume may be defined by the connections provided by the microfluidic passages **1274** and/or sensor volumes within the area **F**.

[00558] The flow rate sensor **1280** is coupled to the pipetting channel **1202** (*e.g.*, between the pipetting channel **1202** and the pipette tip **1260** or tip adaptor **1276**) and is configured to output a sensor signal indicating a rate of air flow in the channel **1202**, for example, based on detected pressure or pressure change data. For example, the flow rate sensor **1280** may be a dual metering or differential pressure sensor including first and second

pressure sensors **1280A** and **1280B** coupled to the channel **1202** via the microfluidic passages **1274** in a parallel arrangement. The first and second pressure sensors **1280A** and **1280B** may output respective signals including first and second pressure data indicating first and second flow rates, respectively. In some embodiments, a range of measurement of the second pressure sensor **1280B** may be greater than that of the first pressure sensor **1280A**, *e.g.*, by an order of magnitude or more, which may allow for flow measurements with increased dynamic range. For example, changes in flow rate near zero may result in extremely small pressure differences, which may be difficult or impossible to detect using a pressure sensor that is configured to detect larger pressure variations in the channel **1202**.

[00559] As such, in some embodiments, the first pressure sensor **1280A** may be highly-sensitive so as to detect sub-pascal (Pa) variations at low pressures (*e.g.*, less than about 50 Pa), while the second pressure sensor **1280B** may have a broad measurement range, so as to detect variations at high pressures (*e.g.*, up to about 5000 Pa). The first and second pressure data indicated by the respective outputs of the first and second pressure sensors **1280A** and **1280B** may be combined by the controller circuit **1220**. That is, the controller circuit **1220** may include signal processing capability so as to stitch together the respective pressure data provided by the first and second pressure sensors **1280A** and **1280B**, thereby providing an increased dynamic range of flow measurement.

[00560] Referring again to **FIGS. 47** and **48**, the controller circuit **1220** may be configured to determine a displaced air volume in the channel **1202** based on the flow rate in the channel **1202** indicated by the signal output from the sensor **1280** (*e.g.*, as indicated by the change in pressure) and may output a plunger actuator control signal to the drive mechanism **1228** based on the displaced air volume, which may improve accuracy in aspiration and/or dispensing. The plunger actuator control signal may be continually varied based on changes in the displaced air volume in the channel **1202** (as indicated by a varying output from the sensor **1280**) to dynamically control the position and/or speed of motion of the plunger **1240** in the channel **1202**. For example, the controller circuit **1220** may implement a control loop by which (i) the controller circuit **1220** transmits a plunger actuator control signal to the drive mechanism **1228** to move the plunger **1240** in the channel **1202** to aspirate or dispense, (ii) the flow rate sensor **1280** outputs a signal indicating a pressure change in the channel **1202** (*e.g.*, based on the first and/or second pressure data indicated by the sensor signals from the first and second pressure sensors **1280A**, **1280B**) resulting from the movement of the plunger **1240**, and (iii) the controller circuit **1220** determines the air displacement in the channel **1202** from the pressure change (or flow rate indicated thereby)

and transmits another plunger actuator control signal to the drive mechanism **1228** to move the plunger **1240** based on the determined air displacement. The controller circuit **1220** may thus continually monitor the pressure in the channel **1202** and generate the plunger actuator control signals based on the output of the sensor **1280**, independent of determining a previous position or movement of the plunger **1240** in the channel **1202**, in contrast to some conventional motor/encoder assemblies that may determine displaced air volume based on tracking the distance of movement of the plunger in the pipetting channel.

[00561] Referring again to **FIG. 52**, a flow restriction mechanism **1277** is coupled to the channel **1202**, for example, via the microfluidic passages **1274** of the manifold **1275**. The flow restriction mechanism **1277** may be configured to be switched between respective states that can allow for different ranges of flow rates responsive to a flow restriction control signal from the controller circuit **1220**, for example, to increase or decrease flow rate based on outputs of the dual pressure sensors **1280A** and **1280B**. The valve **1278** is coupled to the channel **1202**, for example, between the flow restriction mechanism **1277** and the channel **1202**. In some embodiments, the flow restriction mechanism **1277** and the valve **1278** may be configured to couple the channel **1202** to a pressure source **1290**, as described with reference to the example of **FIG. 53**.

[00562] FIG. 53 is a schematic diagram illustrating operation of various components of the dual metering pipettor **1200** according to some embodiments in greater detail. With reference to **FIG. 53**, the dual metering pipettor **1200** includes a flow rate sensor **1280** that is coupled to a pipetting channel **1202** and a switchable flow restriction **1277** via an inline valve **1278**, as discussed above with reference to **FIG. 52**. The flow rate sensor **1280** is implemented by a dual metering sensor including first and second pressure sensors **1280A** and **1280B** to measure a flow rate inside the pipetting channel **1202**, for example, based on the pressure differences or changes across the variable flow restriction **1277**. The first pressure sensor **1280A** may be configured to measure a first, narrower pressure range (*e.g.*, about 0 to 25 Pa or Δp = about 0.0036 psi) for lower flow rates, while the second pressure sensor **1280B** may be configured to measure a second, wider pressure range (*e.g.*, about 0 to 500 Pa or Δp = about 0.0725 psi) for higher flow rates. In some embodiments, the second, wider pressure range may be more than an order of magnitude higher than the first pressure range. Utilizing two (narrower range and wider range) pressure sensors **1280A**, **1280B** in parallel across a flow restriction **1277** provides the dual metering pipettor **1200** with sufficient sensitivity to measure a wide range of flows. For example, the differential pressure

sensors **1280A**, **1280B** may be operable to provide a flow rate measurement range from about 1 µl/s to 1000 µl/s.

[00563] The flow restriction mechanism **1277** is configured to provide a variable flow rate in the channel **1202**, *e.g.*, over a corresponding range of about 1 µl/s to 1000 µl/s. In the embodiment of **FIG. 53**, the flow restriction mechanism **1277** is coupled between the channel **1202** and a pressure source **1290**. The pressure source **1290** may include a positive pressure reservoir **1290A** and a negative pressure reservoir **1290B**. The positive pressure reservoir **1290A** may be configured to provide a fixed positive pressure, and the negative pressure reservoir **1290B** may be configured to provide a fixed negative pressure. The flow restriction mechanism **1277** and/or the valve **1278** may be coupled to and configured to switch between the positive pressure reservoir **1290A** and the negative pressure reservoir **1290B** to apply a positive or negative pressure (and thus control a direction of air flow) in the channel **1202**, *e.g.*, during dispensing or aspirating, respectively.

[00564] In greater detail with reference to the example of **FIG. 53**, the flow restriction mechanism **1277** is configured to be switched between respective flow restriction states that provide different ranges of flow rates responsive to a flow restriction control signal from the controller circuit **1220**, *e.g.*, to increase or decrease flow rate based on the range of measurement of the sensors **1280A** and/or **1280B**. For example, the switchable flow restriction mechanism **1277** may include three flow restriction states **A**, **B**, **C**, each providing a stepwise decrease in flow restriction. That is, state **B** provides less flow restriction than state **A**, and state **C** provides less flow restriction than state **B**. However, the stepwise flow restriction mechanism is illustrated by way of example only, and it will be understood that the flow restriction mechanism **1277** may include fewer, more, or continuously varying (rather than stepwise) flow restriction states than those illustrated. The switchable flow restriction mechanism **1277** and valve **1278** may thus be operable to provide (i) switchable flow rates (provided by the multiple flow restriction states **A**, **B**, **C**), and (ii) switchable flow directions (provided by the positive and negative pressure reservoirs **1290A** and **1290B**).

[00565] In some embodiments, the control circuit **1220** may be configured to transmit a valve control signal to the valve **1278** to stop the flow if the displaced air volume indicated by the flow rate sensor **1280** exceeds a threshold air displacement volume, effectively functioning to stop the movement of the plunger **1240** in other embodiments described herein. The threshold air displacement volume may be determined from the target volume and may be calculated to compensate for various side effects during pipetting operation.

[00566] The range of flow rates in the channel **1202** may be based on the pressures provided by the pressure source **1290** and the switchable restrictions of the flow restriction mechanism **1277** (*e.g.*, a lower pressure source may allow for switching between flow rates over a range of about 1 µl/s to 100 µl/s, while a higher pressure source may allow for switching between flow rates over a range of about 10 µl/s to 1000 µl/s), which is within the dynamic range of flow rate measurement provide by the dual pressure sensors **1280A** and **1280B**. In some embodiments, the flow rate sensor **1280** response time may be less than about 5 ms, and the inline valve **1278** may be switchable between open and closed states in less than about 1 ms, *e.g.*, about 200 µs or less.

[00567] As discussed above, a control mechanism or loop may be implemented by the controller circuit **1220** based on the pressure data from the pressure sensors **1280A**, **1280B** to improve the accuracy of over and/or under-aspiration. The pressure data indicated by the signals from the pressure sensors **1280A**, **1280B** can also be used to dynamically control the speed or plunger position (*i.e.*, the end position of the plunger **1240** in the channel **1202**). As such, the end position of the plunger **1240** may be controlled based on changes in the pressure data indicated by the sensor **1280**, rather than by tracking the distance of movement of the plunger. That is, the position of the plunger **1240** in the channel **1202** may be dynamically controlled based on changes in the flow rate or otherwise based on the displaced air volume in the channel **1202** as indicated by a signal from the sensor **1280**, independent of a previous position and/or distance of movement of the plunger **1240**. In some embodiments, the pressure sensors **1279A, 1279B** may be distributed along the channel, with the pressure sensor **1279A** included in or coupled to the pipette tip **1260** (*e.g.*, in place of the pressure sensors **256**, **1156** described herein), and the pressure sensor **1279B** positioned further along the channel, as shown in **FIG. 53**. The tip pressure sensor **1279A** may output a pressure signal, which may be used by the controller circuit **1220** to determine a volume of a liquid **LV** in the pipette tip **1260** based on the pressure signal, and to control the position of the plunger **1240** based on the determined volume of the liquid in the pipette tip **1260**.

[00568] With reference to **FIGS. 54-59**, an example positive displacement (PD) pipette tip **1360** according to further embodiments of the present technology is shown. The PD pipette tip **1360** may be used in combination with a pipettor to form a pipetting system. An example pipetting system **1301** according to embodiments of the present technology is shown in **FIGS. 54-59** and includes the PD pipette tip **1360** and a pipettor **1300**.

[00569] The pipetting system **1301** can aspirate and dispense liquid volumes within a liquid handling system. The pipetting system **1301** may be used in place of the pipetting

system **101** in the automated liquid handling system **10** (**FIG. 1**), for example. However, it shall be understood that the disclosed methods, systems, and apparatus are not limited to the liquid handling system **10** or use therein, and the present disclosure is applicable to other systems and applications where it is desired to aspirate and/or dispense liquid volumes.

[00570] The PD pipette tip **1360** is not limited to use with the pipettor **1300**. The PD pipette tip **1360** may be used with any suitable air displacement-type pipettor. The PD pipette tip **1360** may be used in place of the air displacement pipette tips **160**, for example.

[00571] The pipetting system **1301** includes one or more pipettors **1300**. The pipettor(s) may be mounted on the pipettor module **30** (**FIG. 1**). The pipettors **1300** may be constructed and operate in the same manner, and it will be appreciated that the description of a representative one of the pipettors **1300** that follows may apply equally to each of the pipettors **1300**. If multiple pipettors **1300** are provided, the pipettors **1300** may be operated independently of one another or in tandem. For the purpose of discussion, only a single pipettor is described below.

[00572] The pipetting system **1301** includes the pipettor **1300**, the controller **20**, and one or more of the PD pipette tips **1360**. The pipette tips **1360** are removable and replaceable on the pipettor **1300**, and may be effectively disposable or consumable components of the pipetting system **1301**.

[00573] With reference to **FIGS. 54** and **55**, the pipettor **1300** may be understood to have a lengthwise axis **A-A** and a distal end **1300A**. The pipettor **1300** includes a tubular barrel **1310**, a pressure control system **1306**, a pipetting channel **1302**, a pipettor orifice **1304**, and a tip adaptor **1314**. The barrel **1310** includes a shaft **1313** that terminates at the distal end **1300A**. The tip adaptor **1314** is mounted or formed on the distal end **1300A**. The pipettor orifice **1304** is located at the distal end **1300A** and fluidly communicates with the pipetting channel **1302**.

[00574] In some embodiments, the pressure control system **1306** includes a plunger mechanism (*e.g.*, as described below and illustrated). The pipettor **1300** may be constructed and operable in the same manner as described herein for any one of the pipettors **100**, **200**, **300**, **400**, **600**, for example.

[00575] However, the pressure control system **1306** is not limited to plunger mechanisms and the pressure control system **1306** may include and use any suitable type of mechanism for controlling the pressure in the tip **1360** as discussed herein. For example, other suitable types of pressure control mechanisms may include one or more pumps of other

designs that are integrated into the pipettor **1300** or that are remote from and fluidly connected to the pipettor **1300**.

[00576] The example pressure control system **1306** includes the barrel **1310**, a plunger **1340**, a plunger drive mechanism **1358** (shown schematically in **FIGS. 54** and **55**), and a pressure sensor **1356** (shown schematically in **FIGS. 54** and **55**).

[00577] With reference to **FIG. 55**, the barrel **1310** includes a barrel passage **1320**. The passage **1320** is aligned lengthwise with the axis **A-A** and extends rearwardly from a front end **1320A** to an opposing rear end.

[00578] The plunger **1340** is mounted in the passage **1320** such that the plunger **1340** can slidably translate relative to the barrel **1310** along a plunger axis **P6-P6** in an extension direction **E12** and an opposing retraction direction **E13**.

[00579] The plunger drive mechanism **1358** is selectively operable to drive the plunger **1340** in each of the extension direction **E12** and the retraction direction **E13**. The plunger drive mechanism **1358** may be a linear drive mechanism. The plunger drive mechanism **1358** may include an actuator and may be any suitable type of linear drive mechanism. In some embodiments, the actuator includes an electric motor. In some embodiments, the plunger drive mechanism **1358** is manually operable and does not include an actuator. For example, the plunger member **1340** may be pushed and pulled using an extension, lever, knob, or other feature that is hand-driven.

[00580] The tip adaptor **1314** is configured to removably secure the pipette tip **1360** to the end **1300A** of the pipettor **1300** in the same manner as described above for the tip adaptor **156**.

[00581] With reference to **FIGS. 54** and **56**, the PD pipette tip **1360** includes a tubular tip body **1362** and a piston unit **1380** slidably mounted in the tip body **1362**. The piston unit **1380** is slidable between an extended or ready position (**FIG. 54**) and a retracted position (*e.g.*, **FIG. 55**). In some embodiments, the pipette tip **1360** further includes an indexing mechanism **1375**.

[00582] With reference to **FIG. 56**, the tip body **1362** extends from a distal end **1362A** to a proximal end **1362B**. The tip body **1362** includes a front section **1364A**, and a rear section **1364B**, which together define a combined volume or body passage **1370**. The front section **1364A** defines a front chamber or tip passage **1370A**. The rear section **1364B** defines a rear chamber **1370B** (**FIG. 54**) and an intermediate chamber **1370C** (**FIG. 54**) between the tip passage **1370A** and the rear chamber **1370B**. The tip passage **1370A** and the chambers **1370B**, **1370C** each form a part of the passage **1370**. The rear section **1364B**

includes a mount section **1364D** and defines an interface opening **1368**. A tip or pipetting orifice **1366** is defined in the distal end **1362A**. The passage **1370** terminates at the interface opening **1368** and the pipetting orifice **1366**.

[00583] A pressure relief port **1372** is provided in fluid communication with the intermediate chamber **1370C**. The pressure relief port **1372** may vent to and from ambient atmosphere.

[00584] The piston unit **1380** includes a piston **1382** and a seal member **1388**. The piston **1382** and the seal member **1388** may be constructed as a single member that forms the piston unit **1380** as a unitary member, or the piston **1382** and the seal member **1388** may be separate parts that are joined to form the piston unit **1380** as an assembly of parts.

[00585] The piston **1382** extends from a distal end **1382A** to a proximal end **1382B**. The piston **1380** includes a base **1384**, a shaft **1385**, and a rear extension **1386**. In some embodiments, the base **1384**, the shaft **1385**, and the rear extension **1386** form a rigid, unitary member. In some embodiments, the base **1384**, the shaft **1385**, and the rear extension **1386** together form a monolithic member.

[00586] The shaft **1385** extends from a proximal end **1385B** secured to the base **1384** to an opposing distal end **1385A**. In some embodiments, the distal end **1385A** is positioned at or proximate the pipetting orifice **1366** when the piston **1382** is in the ready or extended position. The front side of the base **1384** may have a convex or otherwise contoured shape to fit the facing profile of the tip body **1362**. A pressure relief passage **1384A** is defined in the base **1384**.

[00587] The example seal member **1388** is a generally disc-shaped body or portion. The seal member **1388** is secured to (*i.e.*, affixed to or integral with) the piston **1382** on the proximal end **1382B** of the extension **1386**. The seal member **1388** has an annular peripheral sealing edge section **1388A**.

[00588] The piston **1382** and the seal member **1388** may be formed together (*e.g.*, molded or co-molded), or formed separately and then attached to one another. In some embodiments, the piston **1382** and the seal member **1388** form a unitary member or assembly. In some embodiments, the piston **1382** and the seal member **1388** together form a monolithic member.

[00589] In some embodiments, the piston **1382** and the seal member **1388** are formed of the same material. In some embodiments, the piston **1382** and the seal member **1388** are formed of different materials from one another. In some embodiments, the piston **1382** is formed of a harder material than the material of the seal member **1388**. For example, the seal

member **1388** may be formed of an elastomer or thermoplastic elastomer while the piston **1382** is formed of a thermoplastic. Suitable materials for the piston **1382** may include, but are not limited to, polyethylene (PE). Suitable materials for the seal member **1388** may include, but are not limited to, Silicone. Other types of seals (*e.g.*, an O-ring) may be used in place of or in addition to the seal member **1388**.

[00590] With reference to **FIGS. 54** and **58**, the peripheral sealing edge section **1388A** slidably engages the inner wall surface **1362D** of the rear section **1364B** to form a sliding seal **1389** between the piston unit **1380** and the tip body **1362**. The sliding seal **1389** can slide axially along the axis **P6-P6** relative to the tip body **1362**. The seal member **1388** and the seal **1389** divide, separate and fluidly seal the intermediate chamber **1370C** from the rear chamber **1370B**.

[00591] In use, the seal **1389** translates through the body **1362** with the seal member **1388** and the piston **1382**. It will be appreciated that, as the seal **1389** translates along the axis **P6-P6** relative to the body **1362**, the boundaries and volumes of the intermediate chamber **1370C** and the rear chamber **1370B** will change correspondingly. That is, as the piston unit **1380** translates in the direction **E12**, the volume of the rear chamber **1370B** increases and the volume of the intermediate chamber **1370C** decreases. As the piston unit **1380** translates in the direction **E13**, the volume of the rear chamber **1370B** decreases and the volume of the intermediate chamber **1370C** increases.

[00592] With reference to **FIG. 57**, the indexing mechanism **1375** includes a first indexing feature in the form of a set **1377A** of recesses or annular grooves **1377** on the inner wall **1362C** of the tip body **1362**, and a second indexing feature in the form of a protrusion or annular rib **1387** formed on the base **1384**. The grooves **1377** and rib **1387** are relatively arranged and configured such that the rib **1387** can seat in each groove **1377** to hold the piston **1382** in a corresponding axial position relative to the tip body **1362**, but the rib **1387** can be dislodged from the groove **1377** (upon application of sufficient force) to axially reposition the piston **1382** relative to the tip body **1362**. For example, the tip body **1362** and/or the rib **1387** may be formed of an elastically deformable material.

[00593] The grooves **1377** are serially distributed along the axis **P6-P6**. In some embodiments, the grooves **1377** have a substantially uniform pitch **W14** (**FIG. 57**) between adjacent grooves **1377**. In some embodiments, the grooves **1377** have a pitch **W14** in the range of from 0.05 mm to 0.5 mm.

[00594] In some embodiments, the set **1377A** of grooves includes at least 10 grooves **1377**. In some embodiments, the number of grooves **1377** in the set **1377A** is in the range of from about 10 to 400.

[00595] It will be appreciated that the first and second indexing features may take other forms. For example, an annular groove may be provided on the base **1384** in place of the rib **1387**, and a series of annular ribs may be provided on the tip body **1362** that seat in the annular groove of the base **1384**. The grooves **1377** may be defined between upstanding annular ribs **1377B**, or the grooves **1377** may be flush with the inner diameter of the inner wall **1362C**.

[00596] The liquid handling system **10** and the pipetting system **1301** may be used as follows in accordance with some methods to aspirate and/or dispense one or more liquid samples.

[00597] Generally, the PD pipette tip **1360** is mounted on the pipettor **1300**. The tip body **1362** forms an air-tight, pressure-tight seal with the tip adaptor **1314** so that the rear chamber **1370B** is sealed air-tight and pressure-tight.

[00598] The plunger **1340** is driven to displace an air volume in the pipettor passage **1320** and thereby correspondingly change a pressure in the pipetting channel **1302** and the rear chamber **1370B** (which is in fluid communication with the pipetting channel **1302**). The change in pressure in the rear chamber **1370B** draws the piston unit **1380** in the retraction direction **E13** (responsive to a negative pressure change in the rear chamber **1370B**), or pushes the piston unit **1380** in the extension direction **E12** (responsive to a positive pressure change in the rear chamber **1370B**). The piston assembly **1380** is shown in its ready or fully extended position in **FIG. 54**, and in a retracted position in **FIG. 55**.

[00599] When the piston unit **1380** is drawn in the retraction direction **E13**, the shaft **1385** is displaced in the direction **E13** relative to the front section **1364A**, which expands the fluid volume in the tip passage **1370A**. This expansion generates a negative pressure in the tip passage **1370A**, which aspirates a liquid volume **LV** of a liquid sample **LS** into the tip passage **1370A** through the orifice **1366**.

[00600] When the piston unit **1380** is pushed in the extension direction **E12**, the shaft **1385** is displaced in the direction **E12** relative to the front section **1364A**, which displaces or reduces the fluid volume in the tip passage **1370A**. This reduction generates a positive pressure in the tip passage **1370A**, which expels or dispenses a liquid volume **LV** of the liquid sample **LS** from the tip passage **1370A** through the orifice **1366**.

[00601] Thus, the piston **1382** is responsive to a negative pressure in the rear chamber **1370B** to translate rearwardly (direction **E13**) away from the tip orifice **1366**, whereby the piston **1382** generates a negative pressure at the tip orifice **1366** to aspirate a liquid into the positive displacement pipette tip **1360** through the tip orifice **1366**.

[00602] The piston **1382** is responsive to a positive pressure in the rear chamber **1370B** to translate forwardly (direction **E12**) toward the tip orifice **1366**, whereby the piston **1382** generates a positive pressure in the tip passage **1370A** to expel the liquid from the positive displacement pipette tip **1360** through the tip orifice **1366**.

[00603] It will be appreciated that the piston unit **1380** is operatively coupled to the drive mechanism of the pipettor **1300** via the pipetting channel **1302** and an air cushion **AC** in the rear chamber **1370B**, rather than by a direct mechanical engagement or linkage between a plunger and the piston **1382**. The intervening air cushion **AC** is present and maintained between the distal end **1300A** of the pipettor **1300** and the piston unit **1380**.

[00604] The pressure relief passage **1384A** permits egress and ingress of air from and into intermediate chamber **1370C** forward of the base **1384** as the base **1384** translates. The pressure relief port **1372** permits the egress and ingress of air from and into the intermediate chamber **1370C** as the seal **1389** translates. In this way, the pressure in the intermediate chamber **1370C** can be maintained substantially constant (*e.g.*, at ambient pressure) so that a variation in the pressure in the intermediate chamber **1370C** does not interfere with the displacement of the piston unit **1380**.

[00605] During operation, the indexing system **1375** serves to stop the displacement of the piston **1380** at prescribed, discrete axial positions relative to the tip body **1362**. That is, the indexing system **1375** causes the piston **1380** to move along the axis **P6-P6** in a stepwise manner from one groove **1377** to the next. The step movement can enable or ensure that the pipette tip **1360** dispenses or aspirates a known, discrete volume for each step. The resolution or precision of the volume dispensed can be determined by the number of steps (*e.g.*, grooves) provided. In some embodiments, the grooves **1377** are equidistant apart so that the discrete volumes for each step are substantially equal.

[00606] When the pipette tip **1360** is provided with an indexing system **1375** as disclosed herein, the pressure change provided by the pipettor **1300** to displace the piston **1382** must also be sufficient to overcome the engagement or interlock between the indexing features (*e.g.*, the rib **1387** and the groove **1377** in which the rib **1387** is seated). In some embodiments, the controller **20** operates the pipettor **1300** to deliver pressure pulses to the

rear chamber **1370B** with each pressure pulse being sufficient to move the piston **1382** one step.

[00607] In some embodiments, when executing the aspirating or dispensing operations, the controller **20** receives pressure signals from the pressure sensor **1356** indicating the air pressure in the pipetting channel **1302**. The controller **20** may continuously monitor the pressure in the pipetting channel **1302**. In some embodiments, the controller **20** monitors the pressure in the pipetting channel **1302** using a dual metering flow sensor as described herein (*e.g.*, the dual metering flow sensor **1280**).

[00608] As discussed above, the pipetting system **1301** aspirates liquid sample by decreasing the pressure in the pipetting channel **1302** and dispenses liquid sample by increasing the pressure in the pipetting channel **1302**. However, the pressure in the pipetting channel **1302** may fluctuate in response to other actions or conditions in the procedure, for example, as discussed above with regard to the pipetting system **101**.

[00609] With reference to **FIGS. 60-75**, an example positive displacement (PD) pipette tip **1440** according to further embodiments of the present technology is shown. The PD pipette tip **1440** may be used in combination with a pipettor to form a pipetting system. An example pipetting system **1401** according to embodiments of the present technology is shown in **FIGS. 60-75** and includes the PD pipette tip **1440** and a pipettor **1400**.

[00610] The pipetting system **1401** can aspirate and dispense liquid volumes within a liquid handling system. The pipetting system **1401** may be used in place of the pipetting system **101** in the automated liquid handling system **10** (**FIG. 1**), for example. However, it shall be understood that the disclosed methods, systems, and apparatus are not limited to the liquid handling system **10** or use therein, and the present disclosure is applicable to other systems and applications where it is desired to aspirate and/or dispense liquid volumes.

[00611] The PD pipette tip **1440** is not limited to use with the pipettor **1400**. The PD pipette tip **1440** may be used with any suitable positive displacement-type pipettor. The PD pipette tip **1440** may be used in place of the air displacement pipette tips **160**, for example.

[00612] With reference to **FIG. 60**, the pipetting system **1401** includes one or more pipettors **1400**. The pipettor(s) may be mounted on the pipettor module **30** (**FIG. 1**). The pipettors **1400** may be constructed and operate in the same manner, and it will be appreciated that the description of a representative one of the pipettors **1400** that follows may apply equally to each of the pipettors **1400**. If multiple pipettors **1400** are provided, the pipettors **1400** may be operated independently of one another or in tandem. For the purpose of discussion, only a single pipettor is described below.

[00613] The pipetting system **1401** includes the pipettor **1400**, the controller **20**, and one or more of the PD pipette tips **1440**. The pipette tips **1440** are removable and replaceable on the pipettor **1400**, and may be effectively disposable or consumable components of the pipetting system **1401**.

[00614] The pipettor **1400** may be constructed and operable in the same manner as described herein for the pipettor **600**, for example.

[00615] With reference to **FIGS. 60** and **66**, the pipettor **1400** may be understood to have a lengthwise axis **A-A** and a distal end **1400A**. The pipettor **1400** includes a pipettor orifice **1404**, a tubular barrel **1410**, a tubular tip adaptor **1416**, a driver (in the form of a plunger) **1420**, a plunger drive mechanism **1424**, and an ejection system **1431**. The barrel **1410** includes a pipettor shaft **1414** that terminates at the distal end **1400A**. The tip adaptor **1416** is mounted or formed on the distal end **1400A**. The pipettor orifice **1404** is located at the distal end **1400A**.

[00616] With reference to **FIG. 66**, the barrel **1410** includes a barrel passage **1412**. The passage **1412** is aligned lengthwise with the axis **A-A** and extends rearwardly from the distal end **1400A** to an opposing rear end.

[00617] The plunger **1420** serves as a driver and is mounted in the passage **1412** such that the plunger **1420** can slidably translate relative to the barrel **1410** along a plunger axis **P7-P7** in an extension direction **E14** and an opposing retraction direction **E16** (**FIG. 66**).

[00618] The plunger **1420** includes an integral piston engagement or coupling feature **1422** (**FIG. 66**) on its leading end **1420A**. In some embodiments and as illustrated, the piston coupling feature **1422** includes a slot **1422A**. The piston coupling feature **1422** may be configured and operative in the same manner as described herein for the piston coupling feature **646**, for example.

[00619] The plunger drive mechanism **1424** is selectively operable to drive the plunger **1420** to translate in each of the extension direction **E14** and the retraction direction **E16**. The plunger drive mechanism **1424** may be a linear drive mechanism. The plunger drive mechanism **1424** may include an actuator and may be any suitable type of linear drive mechanism. In some embodiments, the actuator includes an electric motor. In some embodiments, the plunger drive mechanism **1424** is manually operable and does not include an actuator. For example, the plunger member **1424** may be pushed and pulled using an extension, lever, knob, or other feature that is hand-driven.

[00620] The tip adaptor **1416** is configured to removably secure the pipette tip **1440** to the end **1400A** of the pipettor **1400** in the same manner as described above for the tip adaptor **156**.

[00621] With reference to **FIGS. 60** and **66**, the ejection system **1431** includes an ejector member or sleeve **1430** and an ejector drive mechanism **1432**. The ejector sleeve **1430** is mounted around the barrel **1410** such that the ejector sleeve **1430** can slidably translate relative to the barrel **1410** along an ejector axis **P8-P8** in an extension direction **E18** and an opposing retraction direction **E20**. The ejector axis **P8-P8** may be coaxial with the plunger axis **P7-P7**.

[00622] With reference to **FIGS. 61-65**, the PD pipette tip **1440** includes a tubular tip body **1450**, a piston **1460** slidably mounted in the tip body **1450**, and an integral piston restraint mechanism **1471**. The piston restraint mechanism **1471** includes an interlock insert **1470**.

[00623] With reference to **FIG. 63**, the tip body **1450** extends from a distal end **1450A** to a proximal end **1450B**. The tip body **1450** includes a distal tip portion or front section **1452A**, an intermediate section **1452B**, and a rear section **1452C**. The front section **1452A** defines a front chamber or tip passage **1455A**. The rear section **1452C** defines a rear chamber **1455C**. The intermediate section **1452B** defines an intermediate chamber **1455B** between the tip passage **1455A** and the rear chamber **1455C**. The tip passage **1455A** and the chambers **1455B**, **1455C** collectively form a combined volume or tip body passage **1455**.

[00624] The rear section **1452C** includes a mount section **1455D** and defines an interface opening **1458**. A tip or pipetting orifice **1456** is defined in the distal end **1450A**. The passage **1455** terminates at the interface opening **1458** and the pipetting orifice **1456**.

[00625] The tip body **1450** may be formed of any suitable material(s). In some embodiments, the tip body **1450** is formed of a polymer. In some embodiments, the tip body **1450** is formed of a thermoplastic. Suitable materials for the tip body **1450** may include, but is not limited to, polyethylene (PE). In some embodiments, the tip body **1450** is a rigid, unitary member. In some embodiments, the tip body **1450** is a monolithic member.

[00626] The piston **1460** is slidable relative to the tip body **1450** along a piston axis **P9-P9** (**FIG. 62**) in an extension direction **E22** and an opposing retraction direction **E24** between an extended or ready position (**FIGS. 62** and **66**) and a retracted position (*e.g.*, **FIG. 70**).

[00627] The piston **1460** (**FIG. 64**) extends from a distal end **1460A** to a proximal end **1460B**. The piston **1460** includes a piston shaft **1462**, a sealing feature or rib **1462A**, an

intermediate section **1463**, a rear extension **1464**, an interlock feature or flange **1466**, and an integral plunger engagement or coupling feature **1468**.

[00628] The piston shaft **1462** extends rearward from the distal end **1460A**. The annular sealing rib **1462A** is located that the distal end **1460A** and forms a moving seal with the inner diameter of the front passage **1455A**. In some embodiments, the distal end **1460A** is positioned at or proximate the pipetting orifice **1456** when the piston **1460** is in the ready or extended position.

[00629] The intermediate section **1463** extends rearward from the proximal end of the piston shaft **1462**. In some embodiments, the outer diameter of the intermediate section **1463** is greater than the outer diameter of the piston shaft **1462**.

[00630] The rear extension **1464** extends rearward from the proximal end of the intermediate section **1463**. In some embodiments, the outer diameter of the rear extension **1464** is greater than the outer diameter of intermediate section **1463**.

[00631] The plunger coupling feature **1468** is located or formed on the proximal end of the rear extension **1464**. The plunger coupling feature **1468** is configured to be received in the slot **1422A** to releasably secure the piston coupling feature **1422** to the plunger coupling feature **1468**. The illustrated plunger coupling feature **1468** includes two or more opposed, elastically deflectable legs **1468A** configured to be received in the slot **1422A** to releasably secure the piston coupling feature **1422** to the plunger coupling feature **1468**. However, any suitable structure that enables releasable coupling of the plunger coupling feature **1468** to the piston coupling feature **1422** may be used for the plunger coupling feature **1468**.

[00632] For example, the plunger coupling feature **1468** may include two or more opposed, elastically deflectable legs **1468A** configured to be received in the slot **1422A** to releasably secure the piston coupling feature **1422** to the plunger coupling feature **1468**.

[00633] The flange **1466** is annular and positioned axially between the plunger coupling feature **1468** and the intermediate section **1463**. The flange **1466** projects radially outwardly from the rear extension **1464**. In some embodiments, the flange **1466** is substantially concentric with the axis **P9-P9**. In some embodiments, the flange **1466** has a width **W20** (**FIG. 64**) in the range of from about 0.5 mm to 3 mm.

[00634] The piston **1460** may be formed of any suitable material(s). In some embodiments, the piston **1460** is formed of a polymer. In some embodiments, the piston **1460** is formed of a thermoplastic. Suitable materials for the piston **1382** may include a plastic, a thermoplastic, or a high-temperature resistant thermoplastic, *e.g.*, polyether ether ketone (PEEK). In some embodiments, the piston shaft **1462**, the intermediate section **1463**,

the rear extension **1464**, the flange **1466**, and the plunger coupling feature **1468** form a rigid, unitary member. In some embodiments, the piston shaft **1462**, the intermediate section **1463**, the rear extension **1464**, the flange **1466**, and the plunger coupling feature **1468** collectively form a monolithic member.

[00635] The interlock insert **1470** is seated in the rear chamber **1455C** as shown in **FIG. 62**. The interlock insert **1470** is secured in the rear chamber **1455C** to prevent relative axial displacement between the interlock insert **1470** and the tip body **1450**.

[00636] The interlock insert **1470** (**FIG. 65**) has a distal end **1470A** and an opposing proximal end **1470B**. The interlock insert **1470** is tubular and includes a front section **1472A** (at the end **1470A**) defining a front opening **1474A**, and a rear section **1472B** (at the end **1470B**) defining a rear opening **1474B**. A passage **1474** extends from the opening **1474A** to the opening **1474B**. A pair of opposed slots **1475** extend through the front section **1472A** from the rear section **1472B** toward the distal end **1470A**.

[00637] The interlock insert **1470** further includes latches in the form of a pair of opposed latch legs **1476**. Each leg **1476** has a leg axis **P10-P10** and extends axially from a proximal end **1476B** to a distal end **1476A**. Each proximal end **1476B** is connected to the rear section **1472B** and each distal end **1476A** is free so that the legs **1476** are cantilevered from the rear section **1472B**. The legs **1476** are circumferentially spaced apart from one another about the axis **P9-P9** and are circumferentially aligned with the slots **1475**.

[00638] The interlock insert **1470** may be formed of any suitable material(s). In some embodiments, the interlock insert **1470** is formed of a polymer and/or synthetic polymer. In some embodiments, the interlock insert **1470** is formed of a thermoplastic. Suitable materials for the interlock insert **1470** may include, but are not limited to, polyvinyl chloride (PVC). In some embodiments, the interlock insert **1470** is a rigid, unitary member. In some embodiments, the interlock insert **1470** is a monolithic member.

[00639] The interlock insert **1470** may be fastened or bonded (*e.g.*, by adhesive or co-molding) to the tip body **1450**. In other embodiments, the interlock insert **1470** is integrally formed with the tip body **1450**. In some embodiments, the interlock insert **1470** and the tip body **1450** collectively form a unitary or monolithic member. In other embodiments, the interlock insert **1470** is secured to the tip body **1450** by cooperating mechanical features on the interlock insert **1470** and the tip body **1450**.

[00640] The piston restraint mechanism **1471** is operable to selectively limit movement between the piston **1460** and the tip body **1450**. The piston restraint mechanism **1471** includes the flange **1466** and the latch legs **1476** of the interlock insert **1470**. The latch

legs **1476** are positionable in each of a latching position (as shown in **FIGS. 62** and **66**) and a non-latching position (as shown in **FIG. 68**). The piston restraint mechanism **1471** is positionable in each of a restraining configuration (as shown in **FIGS. 62** and **66**) and a release configuration (as shown in **FIG. 68**).

[00641] When the piston restraint mechanism **1471** is in the restraining configuration, the latch legs **1476** are in the latching position and interlock with the flange **1466** to prevent axial displacement of the piston **1460** in the retraction direction **E24** beyond a prescribed position relative to the tip body **1450**.

[00642] When the piston restraint mechanism **1471** is in the release configuration, the latch legs **1476** do not interlock with the flange **1466**, so that they permit axial displacement of the piston **1460** in the retraction direction **E24** beyond the prescribed position relative to the tip body **1450**. In some embodiments and as illustrated, the piston restraint mechanism **1471** does not limit movement between the piston **1460** and the tip body **1450** when in the release configuration.

[00643] In the latching position, the legs **1476** are sloped, tapered or angled radially inward so that the axis **P10-P10** of each leg **1476** forms an angle **AL** (**FIG. 65**) relative to the tip axis **P9-P9**. In the latching position, the distal ends **1470A** of the legs **1476** are axially aligned with portions of the flange **1466**. In some embodiments, the angle **AL** is in the range of from about 2 to 30 degrees.

[00644] In some embodiments, the insert **1470** is constructed such that, in the latching position, the legs **1476** are elastically bent, folded or deflected outwardly (*i.e.*, in directions **E28**; **FIG. 65**) from their relaxed positions. As a result, the legs **1476** are persistently loaded against the rear section **1464** of the piston **1460**, and the distal ends **1470A** of the legs **1476** are thereby maintained in alignment the flange **1466**.

[00645] In some embodiments, the legs **1476** are resilient along their lengths so that the legs **1476** can be elastically bent, folded or deflected from the latching position to the non-latching position. In some embodiments, the proximal ends **1476B** are resiliently connected to the rear section **1472B** so that the legs **1476** can be elastically deflected about the connections from the latching position to the non-latching position.

[00646] The liquid handling system **10** and the pipetting system **1401** may be used as follows in accordance with some methods to aspirate and/or dispense one or more liquid samples.

[00647] Initially, the PD pipette tip **1440** is disposed in the restraining configuration as shown in **FIGS. 62** and **66**. The tip **1440** may be held in a pipette tip supply rack, for example.

[00648] If not already retracted, the plunger **1420** is retracted (as shown in **FIG. 66**). The pipettor shaft **1414** is moved in an insertion direction **I** to insert the pipettor distal end **1400A** into the mount section **1455D** as shown in **FIG. 66**. The pipettor shaft **1414** is further inserted into the tip body **1450** as shown in **FIG. 67** until the tip adaptor **1416** engages the legs **1476**. The pipettor shaft **1414** is further inserted in this manner until the tip adaptor **1416** reaches as prescribed depth within the rear chamber **1455C**, as shown in **FIG. 68**. The plunger **1420** may be retracted relative to the pipettor shaft **1414** to provide clearance between the piston **1460** and the distal end of the plunger **1420**, as shown in **FIG. 68**. As the tip adaptor **1416** is translated to the prescribed depth, the outer diameter of the tip adaptor **1416** displaces or forces the legs **1476** to pivot, fold or deflect in opposed radially outward directions **E28** to their non-latching positions. The tip **1440** is thereby placed in its release configuration as shown in **FIG. 68**.

[00649] During the insertion of the pipettor shaft **1414**, the ejector sleeve **1430** is positioned away from the distal end **1400A** or displaced in the retraction direction **E20** relative to the barrel **1410** to make room for the tip body **1450**. For example, the ejector sleeve **1430** may be driven in the retraction direction **E20** by the tip body **1450** as the pipettor shaft **1414** is inserted.

[00650] The plunger drive mechanism **1424** then drives the plunger **1420** to translate in the extension direction **E14** until the piston coupling feature **1422** interlocks or couples with the plunger coupling feature **1468**, as shown in **FIG. 69**. The plunger **1420** is thereby mechanically coupled to the piston **1460**.

[00651] With the tip **1440** in the release configuration and the plunger **1420** and the piston **1460** coupled, the pipettor **1400** and tip **1440** can be used to aspirate and dispense in the manner described herein with regard to the pipette tip **670** (**FIG. 32**), for example. The plunger **1420** is driven by the plunger drive mechanism **1424** in directions **E14** and **E16** to translate the piston **1460** through the tip passage **1455A** while the tip **1440** is maintained in the release configuration.

[00652] When the piston **1460** is drawn in the retraction direction **E24** by the plunger **1420**, the piston shaft **1462** is translated in the direction **E24** relative to the front section **1452A** (*e.g.*, as illustrated in **FIG. 70**), which expands the fluid volume in the tip passage **1455A**. This expansion generates a negative pressure in the tip passage **1455A**, which

aspirates a liquid volume **LV** of a liquid sample **LS** into the tip passage **1455A** through the orifice **1456**.

[00653] When the piston **1460** is pushed in the extension direction **E22** by the plunger **1420**, the piston shaft **1462** is translated in the direction **E22** relative to the front section **1452A** (*e.g.*, as illustrated in **FIG. 71**), which displaces or reduces the fluid volume in the tip passage **1455A**. This reduction generates a positive pressure in the tip passage **1455A**, which expels or dispenses a liquid volume **LV** of the liquid sample **LS** from the tip passage **1455A** through the orifice **1456**.

[00654] When it is no longer desired to use the pipette tip **1440** on the pipettor **1400**, the tip **1440** may be removed from the pipettor **1400** as follows using the piston restraint mechanism **1471**.

[00655] Starting with the tip **1440** in the release configuration and the plunger **1420** and the piston **1460** coupled as shown in **FIG. 71**, the ejector drive mechanism **1432** translates the ejector sleeve **1430** in the extension direction **E18** relative to the pipettor shaft **1414** while the plunger drive mechanism **1424** drives the plunger **1420** in the direction **E14** relative to the pipettor shaft **1414**. The tip body **1450** and the piston **1460** are thereby pushed in the forward direction **F** relative to the pipettor shaft **1414**, as shown in **FIG. 72**. As a result, the tip adaptor **1416** is slid out from between the legs **1476**, which permits the legs **1476** to elastically return in the radial directions **E30** (by bending, pivoting or folding as illustrated in **FIGS. 72 and 73**).

[00656] The ejector sleeve **1430** and the plunger **1420** are driven in this manner until the tip **1440** and pipettor **1400** reach the configuration shown in **FIG. 73**. The legs **1476** are thereby returned to their latching positions and the tip **1440** has assumed its restraining configuration. In some embodiments, the plunger **1420** is translated in the extension direction **E14** along with the ejector sleeve **1430** to maintain a relative axial positioning between the flange **1466** and the distal ends **1476A** of the legs **1476** so that the distal ends **1476A** close about the piston **1460** rearward of the flange **1466**.

[00657] With the tip **1440** in the restraining configuration and the plunger **1420** and the piston **1460** coupled as shown in **FIG. 73**, the plunger drive mechanism **1424** drives the plunger **1420** to translate in the retraction direction **E16** relative to the pipettor shaft **1414** and the tip body **1450**, as shown in **FIG. 74**. The engagement between the legs **1476** and the flange **1466** prevents the piston **1460** from translating in direction **E24** (**FIG. 70**) relative to the tip body (*i.e.*, the legs **1476** hold the piston **1460** in place). As a result, the piston

coupling feature **1422** is decoupled from the plunger coupling feature **1468** (*i.e.*, the plunger **1420** is disconnected from the piston **1460**), as shown in **FIG. 74**.

[00658] The ejector drive mechanism **1432** then translates the ejector sleeve **1430** in the extension direction **E18** relative to the pipettor shaft **1414** to force the tip body **1450** (and thereby the tip **1440**) off of the pipettor **1400** in the forward direction **F**), as shown in **FIG. 75**.

[00659] In other embodiments, the latch legs **1476** are integrally formed with the tip body **1450**. In some embodiments, integral latches or latch features other than the latch legs **1476** are provided on the pipette tip to selectively restrain the piston **1460**. Each latch may be configured as a tab, protrusion, or sleeve.

[00660] Piston coupling features and plunger coupling features of other designs may be used in place of the piston coupling feature **1422** and the plunger coupling feature **1468** to releasably join the plunger to the piston.

[00661] In some embodiments, the interlocking features **1466**, **1476** may be provided with other designs or configurations.

[00662] In some embodiments, the PD pipette tip **1440** is provided with a vent orifice **1452V** (**FIG. 63**) or other venting passage to prevent overpressurization (positive or negative) in the rear chamber **1455C** that could interfere with the operation of the pipettor or cause damage to the pipettor (*e.g.*, to a pressure sensor).

[00663] The present technology has been described herein with reference to the accompanying drawings, in which illustrative embodiments of the technology are shown. In the drawings, the relative sizes of regions or features may be exaggerated for clarity. This technology may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the technology to those skilled in the art.

[00664] It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer, or section. Thus, a first element, component, region, layer, or section discussed below could be termed a second element, component, region, layer, or section without departing from the teachings of the present technology.

[00665] Spatially relative terms, such as “beneath”, “below”, “lower”, “above”, “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90º or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

[00666] As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless expressly stated otherwise. It will be further understood that the terms “includes,” “comprises,” “including” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. It will be understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[00667] The term "automatically" means that the operation is substantially, and may be entirely, carried out without human or manual input, and can be programmatically directed or carried out.

[00668] The term "programmatically" refers to operations directed and/or primarily carried out electronically by computer program modules, code and/or instructions.

[00669] The term "electronically" includes both wireless and wired connections between components.

[00670] Many alterations and modifications may be made by those having ordinary skill in the art, given the benefit of present disclosure, without departing from the spirit and scope of the invention. Therefore, it must be understood that the illustrated embodiments have been set forth only for the purposes of example, and that it should not be taken as limiting the invention as defined by the following claims. The following claims, therefore, are to be read to include not only the combination of elements which are literally set forth but all equivalent elements for performing substantially the same function in substantially the same

way to obtain substantially the same result. The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, and also what incorporates the essential idea of the invention.

WHAT IS CLAIMED IS:

1. An automated pipetting system comprising:

a pipettor including:

a pipetting channel;

a first plunger mechanism operable to change a pressure in the pipetting channel to aspirate or dispense a liquid; and

a second plunger mechanism operable to change the pressure in the pipetting channel to aspirate or dispense the liquid.

2. The automated pipetting system of Claim 1 wherein the first and second plunger mechanisms are operable to displace an air volume in the pipetting channel.

3. The automated pipetting system of Claim 1 wherein the first and second plunger mechanisms are operable independently of one another to change the pressure in the pipetting channel.

4. The automated pipetting system of Claim 1 wherein:

the pipetting system includes a pipetting orifice and a liquid collection volume; and

the first and second plunger mechanisms are operable to change the pressure in the pipetting channel to aspirate the liquid into the liquid collection volume through the pipetting orifice or to dispense the liquid from the liquid collection volume through the pipetting orifice.

5. The automated pipetting system of Claim 4 including a pipette tip removably coupled to the pipettor, wherein the pipette tip includes the liquid collection volume and the pipetting orifice.

6. The automated pipetting system of Claim 5 wherein the pipettor includes an ejection mechanism operable to force the pipette tip off of the pipettor.

7. The automated pipetting system of Claim 1 wherein:

the first plunger mechanism includes a first chamber and a first plunger, wherein the first plunger mechanism is operable to move the first plunger through the first chamber to change the pressure in the pipetting channel; and

the second plunger mechanism includes a second chamber and a second plunger, wherein the second plunger mechanism is operable to move the second plunger through the second chamber to change the pressure in the pipetting channel.

8. The automated pipetting system of Claim 7 wherein:

the first plunger mechanism includes a first plunger actuator operable to move the first plunger through the first chamber;

the second plunger mechanism includes a second plunger actuator operable to move the second plunger through the second chamber; and

the automated pipetting system includes a controller configured to automatically and programmatically control the first plunger actuator and the second plunger actuator.

9. The automated pipetting system of Claim 8 wherein the first plunger actuator and the second plunger actuator are linear actuators.

10. The automated pipetting system of Claim 7 wherein:

the first plunger mechanism is configured to translate the first plunger along a first plunger axis;

the second plunger mechanism is configured to translate the second plunger along a second plunger axis;

the first plunger has a first cross-sectional area in a plane orthogonal to the first plunger axis;

the second plunger has a second cross-sectional area in a plane orthogonal to the second plunger axis; and

the second cross-sectional area is greater than the first cross-sectional area.

11. The automated pipetting system of Claim 10 wherein the second cross-sectional area is at least three times the first cross-sectional area.

12. The automated pipetting system of Claim 7 wherein:

the first plunger mechanism is configured to translate the first plunger through the first chamber;

the second plunger mechanism is configured to translate the second plunger through the second chamber;

the first plunger displaces an air volume in the first chamber at a first rate of air volume displacement per unit translation;

the second plunger displaces an air volume in the second chamber at a second rate of air volume displacement per unit translation; and

the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation.

13. The automated pipetting system of Claim 12 wherein the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

14. The automated pipetting system of Claim 7 wherein:

the first plunger mechanism is configured to provide a first maximum air volume displacement;

the second plunger mechanism is configured to provide a second maximum air volume displacement; and

the second maximum air volume displacement is greater than the first maximum air volume displacement.

15. The automated pipetting system of Claim 14 wherein the second maximum air volume displacement is at least ten times the first maximum air volume displacement.

16. The automated pipetting system of Claim 7 wherein:

the first chamber has a first chamber volume; and

the second chamber has a second chamber volume that is greater than the first chamber volume.

17. The automated pipetting system of Claim 16 wherein the second chamber volume is at least ten times the first chamber volume.

18. The automated pipetting system of Claim 7 wherein the pipettor includes a valve to selectively control fluid communication between the second chamber and a port to atmosphere.

19. The automated pipetting system of Claim 7 wherein the pipettor includes at least one valve to selectively control fluid communication between the second chamber and the pipetting channel.

20. The automated pipetting system of Claim 19 wherein the first plunger is disposed in the pipetting channel.

21. The automated pipetting system of Claim 7 wherein the first plunger is disposed in the pipetting channel.

22. The automated pipetting system of Claim 1 including a controller configured to automatically and programmatically control the first and second plunger mechanisms.

23. The automated pipetting system of Claim 22 including a pressure sensor coupled to the pipetting channel, wherein the controller is configured to receive a pipetting channel pressure signal from the pressure sensor indicating the pressure in the pipetting channel.

24. The automated pipetting system of Claim 22 wherein:

the pipettor includes a valve to selectively control fluid communication between the second plunger mechanism and the pipetting channel; and

the controller is configured to automatically and programmatically control the valve.

25. A method for operating an automated pipetting system, the method comprising:

performing, by at least one control circuit, operations comprising:

operating a first plunger mechanism of a pipettor of the automated pipetting system to change a pressure in a pipetting channel of the pipettor to aspirate or dispense a liquid; and

operating a second plunger mechanism of the pipettor to change the pressure in the pipetting channel to aspirate or dispense the liquid.

26. The method of Claim 25 including operating the first and second plunger mechanisms to displace an air volume in the pipetting channel.

27. The method of Claim 25 including operating the first and second plunger mechanisms independently of one another to change the pressure in the pipetting channel.

28. The method of Claim 25 including operating the first and second plunger mechanisms to aspirate the liquid into a liquid collection volume through a pipetting orifice or to dispense the liquid from the liquid collection volume through the pipetting orifice.

29. The method of Claim 28 including removably coupling a pipette tip to the pipettor, wherein the pipette tip includes the liquid collection volume and the pipetting orifice.

30. The method of Claim 29 including operating an ejection mechanism to force the pipette tip off of the pipettor.

31. The method of Claim 25 wherein:

the first plunger mechanism includes a first chamber and a first plunger;

the second plunger mechanism includes a second chamber and a second plunger;

the method includes operating the first plunger mechanism to move the first plunger through the first chamber to change the pressure in the pipetting channel; and

the method includes operating the second plunger mechanism includes moving the second plunger through the second chamber to change the pressure in the pipetting channel.

32. The method of Claim 31 wherein:

the first plunger mechanism includes a first plunger actuator operable to move the first plunger through the first chamber;

the second plunger mechanism includes a second plunger actuator operable to move the second plunger through the second chamber; and

the method includes automatically and programmatically controlling the first plunger actuator and the second plunger actuator using a controller.

33. The method of Claim 32 wherein the first plunger actuator and the second plunger actuator are linear actuators.

34. The method of Claim 31 wherein:

the first plunger mechanism is configured to translate the first plunger along a first plunger axis;

the second plunger mechanism is configured to translate the second plunger along a second plunger axis;

the first plunger has a first cross-sectional area in a plane orthogonal to the first plunger axis;

the second plunger has a second cross-sectional area in a plane orthogonal to the second plunger axis; and

the second cross-sectional area is greater than the first cross-sectional area.

35. The method of Claim 34 wherein the second cross-sectional area is at least three times the first cross-sectional area.

36. The method of Claim 31 wherein:

the first plunger mechanism is configured to translate the first plunger through the first chamber;

the second plunger mechanism is configured to translate the second plunger through the second chamber;

the first plunger displaces an air volume in the first chamber at a first rate of air volume displacement per unit translation;

the second plunger displaces an air volume in the second chamber at a second rate of air volume displacement per unit translation; and

the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation.

37. The method of Claim 36 wherein the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

38. The method of Claim 31 wherein:

the first plunger mechanism is configured to provide a first maximum air volume displacement;

the second plunger mechanism is configured to provide a second maximum air volume displacement; and

the second maximum air volume displacement is greater than the first maximum air volume displacement.

39. The method of Claim 38 wherein the second maximum air volume displacement is at least ten times the first maximum air volume displacement.

40. The method of Claim 31 wherein:

the first chamber has a first chamber volume; and

the second chamber has a second chamber volume that is greater than the first chamber volume.

41. The method of Claim 40 wherein the second chamber volume is at least ten times the first chamber volume.

42. The method of Claim 31 including selectively controlling fluid communication between the second chamber and the pipetting channel using a valve forming a part of the pipettor.

43. The method of Claim 42 wherein the first plunger is disposed in the pipetting channel.

44. The method of Claim 31 wherein the first plunger is disposed in the pipetting channel.

45. The method of Claim 25 including automatically and programmatically controlling the first and second plunger mechanisms using a controller.

46. The method of Claim 45 wherein:

the pipettor includes a pressure sensor coupled to the pipetting channel; and

the controller receives a pipetting channel pressure signal from the pressure sensor indicating the pressure in the pipetting channel.

47. The method of Claim 45 wherein:

the pipettor includes a valve to selectively control fluid communication between the second plunger mechanism and the pipetting channel; and

the method includes automatically and programmatically controlling the valve using the controller.

48. A pipetting system comprising:

a pipettor including:

a barrel;

a pipetting channel;

a passage defined in the barrel and in fluid communication with the pipetting channel, the passage including a rear chamber, and a front chamber between the rear chamber and the pipetting channel;

a front plunger mounted in the front chamber to translate relative to the passage through a front plunger stroke;

a rear plunger mounted in the rear chamber to translate relative to the passage through a rear plunger stroke; and

a front seal about the front plunger;

wherein:

during a first part of the front plunger stroke, the front chamber is fluidly sealed from the rear chamber by the front seal, and translation of the front plunger in the front chamber generates a change in a pressure in the pipetting channel to aspirate or dispense a liquid; and

during a second part of the front plunger stroke, the front chamber is fluidly coupled to the rear chamber, and translation of the rear plunger in the rear chamber along the rear plunger stroke generates a change in the pressure in the pipetting channel to aspirate or dispense the liquid.

49. The pipetting system of Claim 48 wherein:

the pipettor includes a plunger member including both the front plunger and the rear plunger; and

the plunger member is mounted in the passage to translate through a plunger member stroke including the front plunger stroke and the rear plunger stroke.

50. The pipetting system of Claim 48 wherein the translation of the front plunger in the front chamber and the translation of the rear plunger in the rear chamber displace an air cushion in the pipetting channel.

51. The pipetting system of Claim 48 wherein:

during the first part of the front plunger stroke, a connecting opening between the front and rear chambers is plugged by the front plunger; and

during the second part of the front plunger stroke, the connecting opening is not plugged by the front plunger and the front chamber is fluidly coupled to the rear chamber through the connecting opening.

52. The pipetting system of Claim 48 wherein the front seal includes an annular seal member slidably engaging the front plunger or the barrel.

53. The pipetting system of Claim 48 including a rear seal about the rear plunger.

54. The pipetting system of Claim 53 wherein the rear seal includes an annular seal member slidably engaging the rear plunger or the barrel.

55. The pipetting system of Claim 53 wherein the rear chamber is defined between the front seal and the rear seal.

56. The pipetting system of Claim 48 including a pressure relief valve arranged and configured to relieve pressure in the rear chamber during the first part of the front plunger stroke.

57. The pipetting system of Claim 48 including a pressure sensor arranged and configured to detect the pressure in the pipetting channel.

58. The pipetting system of Claim 48 including an opening mechanism selectively operable to place the rear chamber in fluid communication with the front chamber when the front plunger is not in the second part of the front plunger stroke.

59. The pipetting system of Claim 58 wherein the opening mechanism includes a valve selectively operable to place the rear chamber in fluid communication with the front chamber when the front plunger is not in the second part of the front plunger stroke.

60. The pipetting system of Claim 59 wherein the valve is selectively operable to place the rear chamber in fluid communication with a port to atmosphere.

61. The pipetting system of Claim 58 wherein the pipetting system is configured such that that front seal forms a seal about the front plunger throughout the first part of the front plunger stroke and the second part of the front plunger stroke.

62. The pipetting system of Claim 48 including a pipette tip removably coupled to the barrel, wherein the pipette tip includes a liquid collection volume fluidly coupled to the pipetting channel, and a tip orifice in fluid communication with the liquid collection volume.

63. The pipetting system of Claim 48 including:

at least one actuator to drive the front and rear plungers through the front and rear plunger strokes; and

a controller configured to automatically and programmatically operate the at least one actuator.

64. The pipetting system of Claim 48 wherein:

the front and rear plunger strokes extend along a plunger axis;

the front plunger has a first cross-sectional area in a plane orthogonal to the plunger axis;

the rear plunger has a second cross-sectional area in a plane orthogonal to the plunger axis; and

the second cross-sectional area is greater than the first cross-sectional area.

65. The pipetting system of Claim 64 wherein the second cross-sectional area is at least three times the first cross-sectional area.

66. The pipetting system of Claim 48 wherein:

the front plunger displaces an air volume in the front chamber at a first rate of air volume displacement per unit translation;

the rear plunger displaces an air volume in the rear chamber at a second rate of air volume displacement per unit translation; and

the second rate of air volume displacement per unit translation is greater than the first rate of air volume displacement per unit translation.

67. The pipetting system of Claim 66 wherein the second rate of air volume displacement per unit translation is at least three times the first rate of air volume displacement per unit translation.

68. The pipetting system of Claim 48 wherein:

the front plunger is configured to provide a first maximum air volume displacement in the front chamber;

the rear plunger is configured to provide a second maximum air volume displacement in the rear chamber; and

the second maximum air volume displacement is greater than the first maximum air volume displacement.

69. The pipetting system of Claim 68 wherein the second maximum air volume displacement is at least ten times the first maximum air volume displacement.

70. The pipetting system of Claim 48 wherein:

the front chamber has a front chamber volume; and

the rear chamber has a rear chamber volume that is greater than the front chamber volume.

71. The pipetting system of Claim 70 wherein the rear chamber volume is at least ten times the front chamber volume.

72. A method for pipetting a liquid, the method comprising:

providing a pipettor including:

a barrel;

a pipetting channel;

a passage defined in the barrel and in fluid communication with the pipetting channel, the passage including a rear chamber, and a front chamber between the rear chamber and the pipetting channel;

a front plunger mounted in the front chamber to travel a front plunger stroke;

a rear plunger mounted in the rear chamber to travel a rear plunger stroke; and

a front seal about the front plunger;

translating the front plunger through the front plunger stroke and translating the rear plunger through the rear plunger stroke to aspirate or dispense a liquid, wherein:

during a first part of the front plunger stroke, the front chamber is fluidly sealed from the rear chamber by the front seal, and translation of the front plunger in the front chamber generates a change in a pressure in the pipetting channel to aspirate or dispense a liquid; and

during a second part of the front plunger stroke, the front chamber is fluidly coupled to the rear chamber, and translation of the rear plunger in the rear chamber along the rear plunger stroke generates a second change in the pressure in the pipetting channel to aspirate or dispense the liquid.

73. The method of Claim 72 wherein:

the pipettor includes a plunger member including both the front plunger and the rear plunger;

the plunger member is mounted in the passage to translate a plunger member stroke including the front plunger stroke and the rear plunger stroke; and

translating the front plunger through the front plunger stroke and translating the rear plunger through the rear plunger stroke are executed by translating the plunger member through the plunger member stroke.

74. The method of Claim 72 wherein the translation of the front plunger in the front chamber and the translation of the rear plunger in the rear chamber displace an air volume in the pipetting channel.

75. The method of Claim 72 wherein:

during the first part of the front plunger stroke, a connecting opening between the front and rear chambers is plugged by the front plunger; and

during the second part of the front plunger stroke, the connecting opening is not plugged by the front plunger and the front chamber is fluidly coupled to the rear chamber through the connecting opening.

76. The method of Claim 72 including:

translating the front plunger in a first direction through the first part of the front plunger stroke to aspirate the liquid; and thereafter

translating the front plunger in a second direction opposite the first direction through the first part of the front plunger stroke to dispense the liquid;

wherein the front plunger is not translated through the second part of the front plunger stroke between translating the front plunger in the first direction and translating the front plunger in the second direction.

77. The method of Claim 72 including:

translating the front plunger in a first direction through the first and second parts of the front plunger stroke to aspirate the liquid using the front plunger and the rear plunger; and thereafter

translating the front plunger in a second direction opposite the first direction through the first and second parts of the plunger stroke to dispense the liquid using the front plunger and the rear plunger.

78. The method of Claim 72 including:

with the front plunger in the first part of the front plunger stroke, operating an opening mechanism to place the rear chamber in fluid communication with the front chamber; and thereafter

with the rear chamber in fluid communication with the front chamber, translating the rear plunger along the rear plunger stroke to aspirate the liquid.

79. The method of Claim 78 wherein the front seal forms a seal about the front plunger throughout the front plunger stroke and the rear plunger stroke.

80. A pipetting system comprising:

a pipettor including:

a barrel;

a pipetting channel;

a passage defined in the barrel and in fluid communication with the pipetting channel, the passage including a rear chamber, and a front chamber between the rear chamber and the pipetting channel;

a front plunger mounted in the front chamber to translate relative to the passage along a plunger axis; and

a rear plunger mounted in the rear chamber to translate relative to the passage along the plunger axis;

wherein:

translation of the front plunger in the front chamber along the plunger axis generates a change in a pressure in the pipetting channel to aspirate or dispense a liquid;

translation of the rear plunger in the rear chamber along the plunger axis generates a change in the pressure in the pipetting channel to aspirate or dispense the liquid;

the front plunger has a first cross-sectional area in a plane orthogonal to the plunger axis;

the rear plunger has a second cross-sectional area in a plane orthogonal to the plunger axis; and

the second cross-sectional area is greater than the first cross-sectional area.

81. The pipetting system of Claim 80 wherein:

the pipettor includes a plunger member including both the front plunger and the rear plunger; and

the plunger member is mounted in the passage to translate along the plunger axis.

82. A pipetting system comprising:

a pipettor;

an air displacement pipette tip; and

a positive displacement pipette tip;

wherein:

the air displacement pipette tip and the positive displacement pipette tip are alternatively and removably mountable on the pipettor;

the pipettor is operable to aspirate a liquid into the air displacement pipette tip when the air displacement pipette tip is mounted on the pipettor; and

the pipettor is operable to aspirate a liquid into the positive displacement pipette tip when the positive displacement pipette tip is mounted on the pipettor.

83. The pipetting system of Claim 82 wherein the pipettor includes a tip mount interface configured to engage and releasably secure the air displacement pipette tip and the positive displacement pipette tip to the pipettor.

84. The pipetting system of Claim 83 wherein the tip mount interface is configured to form a gas-tight fit with the air displacement pipette tip when the air displacement pipette tip is mounted on the pipettor.

85. The pipetting system of Claim 82 wherein:

the air displacement pipette tip includes:

an air displacement tip orifice; and

a liquid collection volume in fluid communication with the air displacement tip orifice; and

the positive displacement pipette tip includes:

a positive displacement tip orifice;

a tip passage in fluid communication with the positive displacement tip orifice; and

a piston slidably mounted in the tip passage;

wherein the positive displacement pipette tip is operative to generate a negative pressure at the positive displacement tip orifice to aspirate the liquid when the piston is translated away from the positive displacement tip orifice.

86. The pipetting system of Claim 85 wherein the pipettor is operable to displace an air volume in the air displacement pipette tip to generate a negative pressure at the air displacement tip orifice.

87. The pipetting system of Claim 85 wherein the pipettor includes a plunger that is translatable to generate a negative pressure at the air displacement tip orifice to aspirate the liquid when the air displacement pipette tip is mounted on the pipettor.

88. The pipetting system of Claim 85 wherein the pipettor includes a plunger configured to engage and translate the piston through the tip passage when the positive displacement pipette tip is mounted on the pipettor.

89. The pipetting system of Claim 85 wherein:

the pipettor includes a plunger;

the plunger is translatable to generate a negative pressure at the air displacement tip orifice to aspirate the liquid when the air displacement pipette tip is mounted on the pipettor; and

the plunger is configured to engage and translate the piston through the tip passage when the positive displacement pipette tip is mounted on the pipettor.

90. The pipetting system of Claim 89 wherein:

the pipettor includes a chamber and a pipetting channel;

the pipetting channel is fluidly coupled to the liquid collection volume when the air displacement pipette tip is mounted on the pipettor; and

the plunger is mounted to translate in the chamber to generate a negative pressure in the pipetting channel.

91. The pipetting system of Claim 90 wherein:

the pipettor is operable in each of an air displacement mode with the air displacement pipette tip mounted on the pipettor and, alternatively, a positive displacement mode with the positive displacement pipette tip mounted on the pipettor; and

the chamber is sealed in the air displacement mode, and is not sealed in positive displacement mode.

92. The pipetting system of Claim 91 wherein:

the pipettor includes:

a barrel defining the chamber; and

an annular seal about the plunger between the plunger and the barrel; and

the annular seal seals the chamber in the air displacement mode, and does not seal the chamber in positive displacement mode.

93. The pipetting system of Claim 91 wherein the pipettor includes a pressure sensor arranged and configured to output a detection signal indicating a pressure in the chamber.

94. The pipetting system of Claim 89 wherein the pipettor includes:

at least one plunger actuator to drive the plunger; and

a controller configured to automatically and programmatically operate the at least one actuator.

95. The pipetting system of Claim 94 wherein the at least one plunger actuator includes a linear actuator.

96. The pipetting system of Claim 85 wherein:

the positive displacement pipette tip includes a tip body defining the tip passage; and

a venting port in the tip body to relieve a pressure in the tip passage between the piston and the pipettor.

97. A pipettor comprising:

an air displacement mechanism; and

a positive displacement mechanism;

wherein:

the pipettor is configured to mount an air displacement pipette tip thereon and, alternatively, a positive displacement pipette tip thereon;

when the air displacement pipette tip is mounted on the pipettor, the air displacement mechanism is operable to generate a negative pressure in the air displacement pipette tip to aspirate a liquid into the air displacement pipette tip; and

when the positive displacement pipette tip is mounted on the pipettor, the positive displacement mechanism is operable to displace a piston of the positive displacement pipette tip to aspirate a liquid into the positive displacement pipette tip.

98. The pipettor of Claim 97 wherein:

the pipettor includes a plunger;

the plunger is translatable to generate the negative pressure in the air displacement pipette tip to aspirate the liquid when the air displacement pipette tip is mounted on the pipettor; and

the plunger is configured to engage and translate the piston through a tip passage of the positive displacement pipette tip when the positive displacement pipette tip is mounted on the pipettor.

99. A method for pipetting a liquid, the method comprising:

with an air displacement pipette tip mounted on a pipettor, operating the pipettor to aspirate a liquid into the air displacement pipette tip; and thereafter

with a positive displacement pipette tip mounted on the pipettor, operating the pipettor to aspirate a liquid into the positive displacement pipette tip.

100. The method of Claim 99 including performing, by at least one control circuit controlling at least one actuator, operations comprising:

mounting the air displacement pipette tip mounted on the pipettor;

removing the air displacement pipette tip from the pipettor;

mounting the positive displacement pipette tip mounted on the pipettor; and

removing the positive displacement pipette tip from the pipettor.

101. A pipette tip, comprising:

a tip member comprising a first end having an opening therein for aspirating and/or dispensing a liquid, and a second end opposite the first end for connection to a pipettor; and

a conductive electrode on the tip member and configured to output a signal responsive to contact with the liquid,

wherein the first end of the tip member comprises a non-conductive tip bottom adjacent the opening.

102. The pipette tip of Claim 101, wherein the conductive electrode is on an outer surface of the tip member between the first end and the second end.

103. The pipette tip of Claim 101, wherein the conductive electrode is at least partially embedded within a surface of the tip member.

104. The pipette tip of Claim 101, wherein the non-conductive tip bottom is free of the conductive electrode.

105. The pipette tip of Claim 101, wherein the non-conductive tip bottom comprises a portion of the conductive electrode having a non-conductive coating thereon.

106. The pipette tip of Claim 101, further comprising:

a conductive element at the second end of the tip member; and

a conductive connection extending along the tip member and electrically connecting the conductive electrode to the conductive element.

107. The pipette tip of Claim 106, wherein the conductive connection extends along the outer surface of the tip member.

108. The pipette tip of Claim 106, wherein the conductive connection is at least partially embedded within the tip member.

109. The pipette tip of Claim 101, wherein an inner surface of the tip member is free of the conductive electrode.

110. The pipette tip of Claim 109, wherein the inner surface of the tip member is non-conductive and the conductive electrode is a single electrode.

111. The pipette tip of Claim 101, wherein the non-conductive tip bottom comprises a length of about 2 millimeters (mm) or more.

112. The pipette tip of Claim 101, wherein a shape of the conductive electrode defines a surface area that varies with distance from the opening.

113. The pipette tip of Claim 101, wherein the conductive electrode is configured to be coupled to a controller circuit that is configured to dynamically detect a level of the liquid and/or predict a loss of contact between the pipette tip and the liquid based on changes in capacitance indicated by the signal output from the conductive electrode.

114. An automated pipetting system, comprising:

a robotic arm assembly comprising an arm member that is adapted to hold a pipettor and an actuator mechanism configured to move the arm member along at least one axis responsive to a control signal; and

a controller circuit coupled to the robotic arm assembly and configured to perform operations comprising:

receiving a signal from a conductive electrode on a pipette tip, wherein the conductive electrode is between a first end of the pipette tip having an opening therein for aspirating and/or dispensing a liquid and a second end of the pipette tip that is connected to the pipettor opposite the first end; and

transmitting the control signal to the actuator mechanism to move the arm member towards or away from a surface of the liquid along the at least one axis responsive to the signal from the conductive electrode.

115. The system of Claim 114, wherein the operations further comprise dynamically detecting a level of the liquid based on changes in capacitance indicated by the signal from the conductive electrode, optionally independent of a shape or size of a container of the liquid.

116. The system of Claim 115, wherein dynamically detecting the level of the liquid comprises predicting a loss of contact between the pipette tip and the liquid based on the changes in the capacitance indicated by the signal from the conductive electrode,

wherein transmitting the control signal to the actuator mechanism is responsive to predicting the loss of contact.

117. The system of Claim 115, wherein the control signal is varied based on the changes in capacitance to move the arm member towards or away from the surface of the liquid along the at least one axis while maintaining contact between the pipette tip and the liquid.

118. The system of Claim 114, wherein the first end of the pipette tip comprises a non-conductive tip bottom adjacent the opening.

119. The system of Claim 118, wherein the conductive electrode is on an outer surface of the pipette tip between the first end and the second end.

120. The system of Claim 118, wherein the conductive electrode is at least partially embedded within a surface of the pipette tip.

121. The system of Claim 118, wherein the non-conductive tip bottom is free of the conductive electrode.

122. The system of Claim 118, wherein the non-conductive tip bottom comprises a portion of the conductive electrode having a non-conductive coating thereon.

123. The system of Claim 118, wherein an inner surface of the pipette tip is free of the conductive electrode.

124. The system of Claim 123, wherein the inner surface of the tip member is non-conductive and the conductive electrode is a single electrode.

125. The system of Claim 114, wherein the actuator mechanism comprises a first operating mode wherein the arm member is restricted to motion towards the surface of the liquid along the at least one axis during the aspirating, and a second operating mode wherein the arm member is restricted to motion away from the surface of the liquid along the at least one axis during the dispensing.

126. The system of Claim 114, wherein the operations further comprise:

calculating an aspirated or dispensed volume of the liquid based on a distance of movement of the arm member along the at least one axis; and

controlling subsequent motion of the arm member along the at least one axis based on the aspirated or dispensed volume that was calculated.

127. A method of operating an automated pipetting system, the method comprising:

executing, by a controller circuit, computer readable instructions stored in a non-transitory storage medium to perform operations comprising:

receiving a signal from a conductive electrode on a pipette tip, wherein the conductive electrode is between a first end of the pipette tip having an opening therein for aspirating and/or dispensing a liquid and a second end of the pipette tip that is connected to a pipettor opposite the first end; and

transmitting, to an actuator mechanism of a robotic arm assembly, a control signal to move an arm member that is adapted to hold the pipettor towards or away from a surface of the liquid along at least one axis responsive to the signal from the conductive electrode.

128. The method of Claim 127, wherein the operations further comprise:

dynamically detecting a level of the liquid based on changes in capacitance indicated by the signal from the conductive electrode, optionally independent of a shape or size of a container of the liquid.

129. The method of Claim 128, wherein dynamically detecting the level of the liquid comprises:

predicting a loss of contact between the pipette tip and the liquid based on the changes in the capacitance indicated by the signal from the conductive electrode,

wherein transmitting the control signal to the actuator mechanism is responsive to predicting the loss of contact.

130. The method of Claim 128, wherein the control signal is varied based on the changes in capacitance to move the arm member towards or away from the surface of the liquid along the at least one axis while maintaining contact between the pipette tip and the liquid.

131. The method of Claim 127, wherein the first end of the pipette tip comprises a non-conductive tip bottom extending beyond the conductive electrode.

132. The method of Claim 131, wherein the conductive electrode is on an outer surface of the pipette tip between the first end and the second end.

133. The method of Claim 131, wherein the conductive electrode is at least partially embedded within a surface of the pipette tip

134. The method of Claim 131, wherein the non-conductive tip bottom is free of the conductive electrode.

135. The method of Claim 131, wherein an inner surface of the pipette tip is free of the conductive electrode.

136. The method of Claim 135, wherein the inner surface of the tip member is non-conductive and the conductive electrode is a single electrode.

137. The method of Claim 127, wherein the operations further comprise:

restricting the arm member to motion towards the surface of the liquid along the at least one axis during the aspirating; and

restricting the arm member to motion away from the surface of the liquid along the at least one axis during the dispensing.

138. The method of Claim 127, wherein the operations further comprise:

calculating an aspirated or dispensed volume of the liquid based on a distance of motion of the arm member along the at least one axis; and

controlling subsequent motion of the arm member along the at least one axis based on the aspirated or dispensed volume that was calculated.

139. An automated pipetting system, comprising:

a pipettor comprising a channel therein;

a pressure sensor coupled to the channel; and

at least one controller circuit configured to perform operations comprising:

receiving, from the pressure sensor, a signal indicating pressure in the channel of the pipettor; and

based on the pressure indicated by the signal, performing at least one of:

detecting evaporation of a liquid in the channel; or

automatically performing one or more compensation operations.

140. The system of Claim 139, wherein the pipettor comprises a pipette tip having an opening therein for aspirating the liquid, and wherein detecting the evaporation is performed after removal of the pipette tip from the liquid.

141. The system of Claim 140, wherein detecting the evaporation further comprises:

calculating an evaporation rate based on a change in the pressure indicated by the signal after the removal of the pipette tip from the liquid.

142. The system of Claim 141, wherein calculating the evaporation rate is independent of a surface tension or type of the liquid.

143. The system of Claim 141, wherein the evaporation rate is calculated in proportion to the change in the pressure indicated by the signal over time.

144. The system of Claim 141, wherein detecting the evaporation further comprises:

controlling movement of a plunger in the channel after removal of the pipette tip from the liquid,

wherein calculating the evaporation rate is based on the change in the pressure indicated by the signal responsive to the movement of the plunger.

145. The system of Claim 139, wherein detecting the evaporation further comprises:

continuously controlling a position of a plunger in the channel of the pipettor such that the pressure indicated by the signal remains substantially constant over time; and

calculating an evaporation rate based on displacement of the plunger over time.

146. The system of Claim 140, wherein automatically performing the one or more compensation operations comprises performing one or more evaporation compensation operations responsive to detecting the evaporation of the liquid in the channel, based on comparison to a threshold.

147. The system of Claim 146, wherein performing the one or more evaporation compensation operations comprises:

performing a prewetting operation prior to the aspirating of the liquid; and/or

adapting one or more aspiration parameters for the aspirating of the liquid; and/or

controlling movement of a plunger in the channel.

148. The system of Claim 147, wherein the operations further comprise:

estimating an evaporation volume based on the evaporation rate and a duration of the aspirating of the liquid, wherein the threshold is volume-based.

149. The system of Claim 148, wherein the evaporation volume indicates an amount of under-aspiration, and wherein performing the one or more evaporation compensation operations comprises:

adapting the one or more aspiration parameters to aspirate a further amount of the liquid based on the amount of under-aspiration; and

aspirating the further amount of the liquid based on the one or more aspiration parameters that were adapted.

150. The system of Claim 147, wherein performing the one or more evaporation compensation operations comprises:

after the removal of the pipette tip from the liquid, controlling the movement of the plunger to aspirate air to reduce or avoid dripping of the liquid from the pipette tip.

151. The system of Claim 147, wherein performing the one or more evaporation compensation operations comprises:

after the removal of the pipette tip from the liquid, controlling the movement of the plunger to maintain a substantially constant pressure in the pipette tip.

152. The system of Claim 151, wherein the substantially constant pressure is based on the pressure indicated by the signal after removal of the pipette tip from the liquid.

153. The system of Claim 151, wherein the substantially constant pressure is a predetermined pressure.

154. The system of Claim 139, wherein the operations further comprise:

calculating an aspirated volume of the liquid based on a change in the pressure indicated by the signal.

155. The system of Claim 154, wherein automatically performing the one or more compensation operations comprises:

adapting one or more aspiration parameters based on a comparison of the aspirated volume to a target volume; and

aspirating the liquid based on the one or more aspiration parameters that were adapted.

156. The system of Claim 139, wherein automatically performing the one or more compensation operations comprises:

adapting an aspiration speed based on a change in the pressure indicated by the signal relative to a pressure change threshold; and/or

performing a prewetting operation based on a temperature of the liquid relative to a temperature threshold.

157. A method of operating an automated pipetting system, the method comprising:

executing, by at least one controller circuit, computer readable instructions stored in a non-transitory storage medium to perform operations comprising:

receiving, from a pressure sensor, a signal indicating pressure in a channel of a pipettor; and

based on the pressure indicated by the signal, performing at least one of:

detecting evaporation of liquid in the channel; or

automatically performing one or more compensation operations.

158. The method of Claim 157, wherein the pipettor comprises a pipette tip having an opening therein for aspirating the liquid, and wherein detecting the evaporation is performed after removal of the pipette tip from the liquid.

159. The method of Claim 158, wherein detecting the evaporation further comprises:

calculating an evaporation rate based on a change in the air pressure indicated by the signal after the removal of the pipette tip from the liquid.

160. The method of Claim 159, wherein calculating the evaporation rate is independent of a surface tension or type of the liquid.

161. The method of Claim 159, wherein the evaporation rate is calculated in proportion to the change in the pressure indicated by the signal over time.

162. The method of Claim 159, wherein detecting the evaporation further comprises:

controlling movement of a plunger in the channel after removal of the pipette tip from the liquid,

wherein calculating the evaporation rate is based on the change in the pressure indicated by the signal responsive to the movement of the plunger.

163. The method of Claim 157, wherein detecting the evaporation further comprises:

continuously controlling a position of a plunger in the channel of the pipettor such that the pressure indicated by the signal remains substantially constant over time; and

calculating an evaporation rate based on displacement of the plunger over time.

164. The method of Claim 158, wherein automatically performing the one or more compensation operations comprises performing one or more evaporation compensation operations responsive to detecting the evaporation of the liquid in the channel, based on comparison to a threshold.

165. The method of Claim 164, wherein performing the one or more evaporation compensation operations comprises:

performing a prewetting operation prior to the aspirating of the liquid; and/or

adapting one or more aspiration parameters for the aspirating of the liquid; and/or

controlling movement of a plunger in the channel.

166. The method of Claim 165, wherein the operations further comprise:

estimating an evaporation volume based on the evaporation rate and a duration of the aspirating of the liquid, wherein the threshold is volume-based.

167. The method of Claim 166, wherein the evaporation volume indicates an amount of under-aspiration, and wherein performing the one or more evaporation compensation operations comprises:

adapting the one or more aspiration parameters to aspirate a further amount of the liquid based on the amount of under-aspiration; and

aspirating the further amount of the liquid based on the one or more aspiration parameters that were adapted.

168. The method of Claim 165, wherein performing the one or more evaporation compensation operations comprises:

after the removal of the pipette tip from the liquid, controlling the movement of the plunger to aspirate air to reduce or avoid dripping of the liquid from the pipette tip.

169. The method of Claim 165, wherein performing the one or more evaporation compensation operations comprises:

after the removal of the pipette tip from the liquid, controlling the movement of the plunger to maintain a substantially constant pressure in the pipette tip.

170. The method of Claim 169, wherein the substantially constant pressure is based on the pressure indicated by the signal after removal of the pipette tip from the liquid.

171. The method of Claim 169, wherein the substantially constant pressure is a predetermined pressure.

172. The method of Claim 157, wherein the operations further comprise:

calculating an aspirated volume of the liquid based on a change in the pressure indicated by the signal.

173. The method of Claim 172, wherein performing the one or more compensation operations comprises:

adapting one or more aspiration parameters based on a comparison of the aspirated volume to a target volume; and

aspirating the liquid based on the one or more aspiration parameters that were adapted.

174. The method of Claim 157, wherein automatically performing the one or more compensation operations comprises:

adapting an aspiration speed based on a change in the pressure indicated by the signal relative to a pressure change threshold; and/or

performing a prewetting operation based on a temperature of the liquid relative to a temperature threshold.

175. An automated pipetting system, comprising:

a pipettor comprising a channel therein;

a sensor coupled to the channel; and

at least one controller circuit configured to perform operations comprising:

receiving, from the sensor, a sensor signal indicating a pressure change in the channel;

determining a displaced air volume in the channel based on the sensor signal; and

transmitting at least one control signal to control a pressure in the channel based on the displaced air volume.

176. The system of Claim 175, wherein the operations further comprise identifying a rate of air flow in the channel based on the pressure change, wherein determining the displaced air volume is based on the rate of air flow.

177. The system of Claim 176, wherein the at least one control signal comprises a flow restriction control signal, and further comprising:

a flow restriction mechanism coupled to the channel and configured to be switched between respective states that provide different flow rates responsive to the flow restriction control signal.

178. The system of Claim 177, wherein the sensor comprises a dual sensor, wherein the sensor signal comprises first and second pressure data indicating first and second flow rates, respectively.

179. The system of Claim 178, wherein the dual sensor comprises first and second pressure sensors in a parallel arrangement that provide the first and second pressure data, respectively, wherein a range of measurement of the second pressure sensor is greater than that of the first pressure sensor.

180. The system of Claim 179, wherein the range of measurement of the second pressure sensor is more than an order of magnitude greater than that of the first pressure sensor.

181. The system of Claim 176, wherein the at least one control signal comprises a plunger actuator control signal that is varied based on changes in the displaced air volume indicated by the rate of air flow in the channel, and further comprising:

a plunger actuator configured to dynamically control a position and/or a speed of motion of a plunger in the channel responsive to the plunger actuator control signal.

182. The system of Claim 181, wherein the plunger actuator control signal is generated independent of determining a previous position or distance of motion of the plunger in the channel.

183. The system of Claim 177, wherein the at least one control signal comprises a valve control signal, and further comprising:

an air valve that is operable to couple the channel to a pressure source responsive to the valve control signal.

184. The system of Claim 183, wherein the pressure source comprises a negative pressure source and a positive pressure source, wherein one of the negative pressure source or the positive pressure source is configured to be selected to control a direction of the air flow in the channel.

185. The system of Claim 175, wherein the operations further comprise:

receiving a pressure signal from a pressure sensor in a pipette tip coupled to the pipettor; and

determining a volume of a liquid in the pipette tip based on the pressure signal,

wherein the at least one control signal is transmitted to control a position of a plunger based on the volume of the liquid in the pipette tip.

186. The system of Claim 175, further comprising:

a microfluidic manifold comprising a plurality of passages configured to couple the channel to a pipette tip, wherein one or more of the passages comprise a diameter of about 0.2 to 0.8 mm.

187. A method of operating an automated pipetting system, the method comprising:

executing, by at least one controller circuit, computer readable instructions stored in a non-transitory storage medium to perform operations comprising:

receiving, from a sensor coupled to a channel of a pipettor, a sensor signal indicating pressure change in the channel;

determining a displaced air volume in the channel based on the sensor signal; and

transmitting at least one control signal to control a pressure in the channel based on the displaced air volume.

188. The method of Claim 187, wherein the operations further comprise:

identifying a rate of air flow in the channel based on the pressure change indicated by the sensor signal,

wherein determining the displaced air volume is based on the rate of air flow.

189. The method of Claim 188, wherein the at least one control signal further comprises a flow restriction control signal, and wherein the operations further comprise:

switching a flow restriction mechanism, which is coupled to the channel, between respective states that provide different air flow rates responsive to the flow restriction control signal.

190. The method of Claim 189, wherein the sensor comprises a dual sensor, wherein the sensor signal comprises first and second pressure data indicating first and second flow rates, respectively.

191. The method of Claim 190, wherein the dual sensor comprises first and second pressure sensors in a parallel arrangement that provide the first and second pressure data, respectively, wherein a range of measurement of the second pressure sensor is greater than that of the first pressure sensor.

192. The method of Claim 191, wherein the range of measurement of the second pressure sensor is more than an order of magnitude greater than that of the first pressure sensor.

193. The method of Claim 188, wherein the at least one control signal comprises a plunger actuator control signal that is varied based on changes in the displaced air volume indicated by the rate of air flow in the channel, and wherein the operations further comprise:

dynamically controlling a position and/or speed of motion of a plunger in the channel responsive to the plunger actuator control signal.

194. The method of Claim 193, wherein the plunger actuator control signal is generated independent of determining a previous position or distance of motion of the plunger in the channel.

195. The method of Claim 189, wherein the at least one control signal comprises a valve control signal, and wherein the operations further comprise:

operating an air valve to couple the channel to a pressure source responsive to the valve control signal.

196. The method of Claim 195, wherein the pressure source comprises a negative pressure source and a positive pressure source, wherein the operations further comprise:

selecting one of the negative pressure source or the positive pressure source to control a direction of the air flow in the channel.

197. The method of Claim 187, wherein the operations further comprise:

receiving a pressure signal from a pressure sensor in a pipette tip coupled to the pipettor; and

determining a volume of a liquid in the pipette tip based on the pressure signal,

wherein the at least one control signal is transmitted to control a position of a plunger based on the volume of the liquid in the pipette tip.

198. The method of Claim 187, wherein the sensor is coupled to at least one passage of a microfluidic manifold that is configured to couple the channel to a pipette tip, and wherein the at least one passage comprises a diameter of about 0.2 to 0.8 mm.

199. A positive displacement pipette tip comprising:

a tip orifice;

a rear chamber;

a tip passage between the tip orifice and the rear chamber and in fluid communication with the tip orifice; and

a piston slidably mounted in the tip passage;

wherein the piston is responsive to a negative pressure in the rear chamber to translate rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

200. The positive displacement pipette tip of Claim 199 including:

a body defining the rear chamber; and

a sliding seal between the piston and the body;

wherein the seal separates the rear chamber from the tip passage; and

wherein the seal translates through the body with the piston.

201. The positive displacement pipette tip of Claim 200 wherein:

the body includes a body cavity; and

the seal partitions the body cavity into the rear chamber and an intermediate chamber between the rear chamber and the tip passage.

202. The positive displacement pipette tip of Claim 201 including a pressure relief port in fluid communication with the intermediate chamber.

203. The positive displacement pipette tip of Claim 199 including:

a body; and

an indexing mechanism including:

at least one first indexing feature on the body; and

at least one second indexing feature on the piston;

wherein the first and second indexing features cooperate to stop displacement of the piston at prescribed positions.

204. The positive displacement pipette tip of Claim 203 including a seal on the piston, wherein the seal translates through the body with the piston.

205. A pipette comprising:

a pipettor; and

a positive displacement pipette tip mounted on the pipettor, the positive displacement pipette tip including:

a tip orifice;

a rear chamber;

a tip passage between the tip orifice and the rear chamber and in fluid communication with the tip orifice; and

a piston slidably mounted in the tip passage;

wherein the pipettor is operable to generate a negative pressure in the rear chamber, which translates the piston rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

206. The pipette of Claim 205 wherein:

the pipettor is coupled to the piston by an air cushion; and

the air cushion is displaced within the pipettor and/or the positive displacement pipette tip as the piston translates.

207. A method for pipetting a liquid, the method comprising:

mounting a positive displacement pipette tip on a pipettor, the positive displacement pipette tip including:

a tip orifice;

a rear chamber;

a tip passage between the tip orifice and the rear chamber and in fluid communication with the tip orifice; and

a piston slidably mounted in the tip passage; and

using the pipettor, generating a negative pressure in the rear chamber, which translates the piston rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

208. A positive displacement pipette tip comprising:

a tip orifice;

a tip passage in fluid communication with the tip orifice;

a piston slidably mounted in the tip passage;

a body; and

an indexing mechanism including:

at least one first indexing feature on the body; and

at least one second indexing feature on the piston;

wherein the first and second indexing features cooperate to stop displacement of the piston at prescribed positions.

209. The positive displacement pipette tip of Claim 208 wherein the at least one first indexing feature includes a series of first indexing features axially distributed along a lengthwise axis of the positive displacement pipette tip.

210. A pipette comprising:

a pipettor; and

a positive displacement pipette tip mounted on the pipettor, the positive displacement pipette tip including:

a tip orifice;

a tip passage in fluid communication with the tip orifice;

a piston slidably mounted in the tip passage;

a body; and

an indexing mechanism including:

at least one first indexing feature on the body; and

at least one second indexing feature on the piston;

wherein the first and second indexing features cooperate to stop displacement of the piston at prescribed positions.

211. A method for pipetting a liquid, the method comprising:

mounting a positive displacement pipette tip on a pipettor, the positive displacement pipette tip including:

a tip orifice;

a tip passage in fluid communication with the tip orifice;

a piston slidably mounted in the tip passage;

a body; and

an indexing mechanism including:

at least one first indexing feature on the body; and

at least one second indexing feature on the piston;

wherein the first and second indexing features cooperate to stop displacement of the piston at prescribed positions;

using the pipettor, translating the piston rearwardly away from the tip orifice, whereby the piston generates a negative pressure at the tip orifice to aspirate a liquid into the positive displacement pipette tip.

212. A positive displacement pipette tip for use with a pipettor, the positive displacement pipette tip comprising:

a tip body including a distal tip portion, the distal tip portion defining a tip passage;

a piston slidably mounted in the tip passage, wherein the piston is displaceable to aspirate a liquid into the positive displacement pipette tip; and

an integral piston restraint mechanism operable to limit movement between the piston and the tip body.

213. The positive displacement pipette tip of Claim 212 wherein the piston restraint mechanism is positionable in each of a restraining configuration, wherein the piston restraint mechanism prevents the piston from being retracted beyond a prescribed position relative to the tip body, and a release configuration, wherein the piston restraint mechanism does not prevent the piston from being retracted beyond the prescribed position.

214. The positive displacement pipette tip of Claim 213 wherein the piston restraint mechanism does not limit movement between the piston and the tip body when in the release configuration.

215. The positive displacement pipette tip of Claim 213 wherein the piston restraint mechanism includes a latch that is movable between a latching position, wherein the latch engages the piston, and a non-latching position, wherein the latch does not engage the piston.

216. The positive displacement pipette tip of Claim 215 wherein the latch includes a displaceable sleeve or tab.

217. The positive displacement pipette tip of Claim 215 including an interlock insert mounted on the tip body, wherein the latch forms a part of the interlock insert.

218. The positive displacement pipette tip of Claim 215 wherein:

the piston restraint mechanism includes an integral interlock feature on the piston; and

the interlock feature is configured to interlock with the latch when the piston restraint mechanism is in the restraining configuration to limit movement between the piston and the tip body.

219. The positive displacement pipette tip of Claim 212 wherein the piston includes an integral coupling feature configured to secure the piston to a driver forming a part of the pipettor.

220. The positive displacement pipette tip of Claim 212 wherein the tip body includes a mounting section configured to engage the pipettor to removably secure the positive displacement pipette tip to the pipettor.

221. A pipetting system comprising:

a pipettor; and

a positive displacement pipette tip mounted on the pipettor, the positive displacement pipette tip including:

a tip body including a distal tip portion, the distal tip portion defining a tip passage;

a piston slidably mounted in the tip passage, wherein the piston is displaceable to aspirate a liquid into the positive displacement pipette tip; and

an integral piston restraint mechanism operable to limit movement between the piston and the tip body.

222. A method for pipetting a liquid, the method comprising:

mounting a positive displacement pipette tip on a pipettor, wherein the positive displacement pipette tip includes:

a tip body including a distal tip portion, the distal tip portion defining a tip passage;

a piston slidably mounted in the tip passage; and

an integral piston restraint mechanism operable to limit movement between the piston and the tip body;

using the pipettor, translating the piston through the tip passage to aspirate a liquid into the positive displacement pipette tip; and

ejecting the positive displacement pipette tip from the pipettor while the piston restraint mechanism limits movement between the piston and the tip body.

223. The method of Claim 222 wherein:

mounting the positive displacement pipette tip on the pipettor includes coupling a driver of the pipettor to the piston; and

translating the piston through the tip passage includes translating the piston using the driver.

224. The method of Claim 223 wherein:

the piston restraint mechanism is positionable in each of a restraining configuration, wherein the piston restraint mechanism prevents the piston from being retracted beyond a prescribed position relative to the tip body, and a release configuration, wherein the piston restraint mechanism does not prevent the piston from being retracted beyond the prescribed position;

translating the piston through the tip passage includes translating the piston using the driver while the piston restraint mechanism is in the release configuration; and

ejecting the positive displacement pipette tip from the pipettor includes relatively displacing the driver and the piston while the piston restraint mechanism is in the restraining configuration.

225. The method of Claim 224 wherein ejecting the positive displacement pipette tip from the pipettor includes pushing the tip body away from the pipettor using an ejector forming a part of the pipettor while the piston restraint mechanism is in the restraining configuration.

226. The method of Claim 224 wherein:

the piston restraint mechanism includes an integral interlock feature on the piston;

the piston restraint mechanism includes a latch forming a part of the tip body;

the latch is positionable in each of a latching position, wherein the latch interlocks with the interlock feature, and a non-latching position, wherein the latch does not interlock with the interlock feature;

mounting the positive displacement pipette tip on the pipettor includes inserting a shaft of the pipettor into the tip body and thereby deflecting the latch into the non-latching position; and

ejecting the positive displacement pipette tip from the pipettor includes pushing the tip body away from the shaft, responsive to which the latch resiliently returns to the latching position.




FIG. 1




FIG. 2



101
149
148A
129
148C
128A
148B
134B
130
128B
140
128C
7-7
124
134
124A
132
120
100
136
112A
160
A
A
Z
X
X
Z

FIG. 3



176
126
100
118
114D
114B
127
110
175
176A
E2
E1
120
150
103
114
112
6
6
156A
156
120A
115
102
156A
114A
104
160
P1
P1

FIG. 4



142
130
140
146
140A
124A
124
E4
E3
122
135
134
120
154
P2
132
150B
152
147
178
134A
P2
136A
E5
E6
136
174
174A
172
118
176
171
150
150A
179
175

FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13



A, P4
A, P4
258
20
E9
E8
255
206
210
200
244
19
19
201
18
18
242
256
202
212A
214
160
165

FIG. 14



220E
220B
240B
210B
254
244B
255
D7
228
240
210
244
224D
212
244A
252
252A
246
242B
222D
D6
202
220A
242
210A
240A
242A
169
214
160
204
164

FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27



A, P5
A, P5
601
654
656
658
644
606
600
20
610
E11
640
E10
600A
666
660
LS
36

FIG. 28




FIG. 29




FIG. 30



654
644
600
610
640
600A
676
614
646
686
670
SF1
684
682
LS
678A
36

FIG. 31




FIG. 32



600
620B
620E
610B
640B
654
656
656A
610
640
621
620
612
602
646
614
640A
604
646A
610A
620A

FIG. 33




FIG. 34



686A
686A
686
684
680
682B
682
682A
673
670B
676
670
678
679B
678B
674
679A
678A
670A
672

FIG. 35




FIG. 36



901
912
Y
934
900
Z
914
960
X
19
Z
X
Y
900
960
1002
1000
1001
962
920
910
925
915

FIG. 37




FIG. 38




FIG. 39A




FIG. 39B




FIG. 39C




FIG. 40A




FIG. 40B




FIG. 40C




FIG. 41




FIG. 42




FIG. 43A




FIG. 43B




FIG. 44A




FIG. 44B




FIG. 45




FIG. 46A




FIG. 46B



1228
1207
1208
1240
1202
1206
1279
1229
1278
1271
1275
1276
1200
LV
1260
1262

FIG. 47



1228
1208
1220
1240
1202
1229
1209
1278
1275
1271
1279A
1280
1279B
1276
1200
1206

FIG. 48



1278
1279A
1240
1202
1228
F
1279B
1280
1275
1276
L

FIG. 49



L
1274
1275
1280

FIG. 50



1209
1275
1280
1274
1279A, B

FIG. 51



1275
1279B
1279A
1280
1280B
1274
1276
1202
1280A
1240
1278
1277
F

FIG. 52



1290B
NEGATIVE PRESSURE RESERVOIR
1290
POSITIVE PRESSURE RESERVOIR
1290A
1277
A
B
C
1279B
1278
1280A
1280B
Δp
Δp
1280
1202
1279A
1276
1200

FIG. 53



1310
1313
1300
1306
1340
1314
1300A
AC
1362
58
1388
1360
1375
1384
1385
LS
1366
36
A
A
1358
1301
1356
20
1370B
1362D
1389
58
1370C
1380

FIG. 54



1340
1310
1300
1320
1302
1304
AC
1389
E13
E12
1360
1384
1377A
1358
P6-P6
1356
20
1301
1300A
1320A
1388
1386
1380
1382
1372
1384A
1362
1385
LV
LS

FIG. 55



1360
1388
1388A
1382B
1368
1362B
1364D
1386
1382
1384A
1380
1387
1384
1370
1362
1385B
1364B
1385
1372
1377A
1385A
1382A
1364A
1370A
1362A
1366

FIG. 56



1370C
1386
1372
1387
59
59
1384
1377
1360
1377
1377A
1377B
1362
1362C
W14
1385

FIG. 57




FIG. 58




FIG. 59



1424
20
1432
1400
1431
1430
1414
1400A
1416
1404
I
62
1450B
1401
1440
1452V
1450A
62
A, P7, P8, P9
A, P7, P8, P9

FIG. 60



1468
1460
1462A
1440
1470
1476B
1475
1476
1475
1476
1476A
1474A
1450
1452C
1452V
1452B
1452A
1456

FIG. 61



P9
1440
1475
P9
1470
1468
1460
1476
1476
1471
1450
1452V
1466
E22
E24
1462

FIG. 62



1450
1458
1450B
1455D
1452C
1455C
1455
1452V
1452B
1455B
1455A
1452A
1450A
1456

FIG. 63




FIG. 64



1470
1474B
1470B
1472B
1474
1476B
1476
1476
E28
E28
E30
E30
1472A
P10
1475
AL
1475
1470A
1476A
1476A
P10
1474A

FIG. 65



1412
1414
1410
1420
E18
E20
E14
E16
1430
1416
1420A
1422
1422A
I
1455D
1476
1476
1466
1450
1440
1460

FIG. 66



1410
1420
1430
1416
1455D
1476
1476
1466
1450
1440

FIG. 67



1410
1420
1430
1455D
1476
1416
E28
1476
E28
1466
1440

FIG. 68



1410
1420
1430
E14
1416
1468
1476
1422
1440
1462

FIG. 69



1410
1420
1430
1468
1422
1416
1466
1476
1440
E16
E24
1462
1455A
LS
LV
1456
36

FIG. 70



1410
1420
1430
1416
1476
1466
E14
E22
1440

FIG. 71



1410
1420
1430
E18
E14
1416
1468
1476
E30
E30
1476
1422
1466
1440
F

FIG. 72



1410
1420
1430
1416
1455D
1422
1468
1476
1476
E30
E30
1466
1440

FIG. 73



1410
1420
1430
E16
1416
1422
1468
1476
1476
1466
1440

FIG. 74




FIG. 75

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2023/065982

A. CLASSIFICATION OF SUBJECT MATTER
INV. B01L3/02 G01N35/10 G01F11/28 G01F11/02
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B01L G01N G01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2021/163437 A1 (DENOVIX INC [US]) 19 August 2021 (2021-08-19)	1-17, 20-22, 25-41, 43-45,80
Y	page 1 - page 18; figures 2, 4A, 8C-D	23,46
X	GB 2 132 346 A (SHIMADZU CORP) 4 July 1984 (1984-07-04)	1,3,4, 7-10,12, 16, 18-22, 24,25, 27,28, 31-34, 36,40, 42-44,47
Y	page 1 - page 3; figures 2, 8, 9	23,46

-/--

[x] Further documents are listed in the continuation of Box C.

[x] See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance;; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance;; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
23 August 2023	25/10/2023

Name and mailing address of the ISA/	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Decaix, François

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2023/065982

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 973 662 B1 (GILSON SAS [FR]) 23 March 2016 (2016-03-23)	1,2,4, 10-22, 24-26, 28, 34-45, 47,80,81
Y	paragraphs [0013] - [0016], [0020]; figures 1-3	23,46
Y	EP 2 359 932 A1 (TECAN TRADING AG [CH]) 24 August 2011 (2011-08-24) paragraph [0009]; figure 1A	23,46
A	US 2016/067705 A1 (GEHRIG STEFAN [DE] ET AL) 10 March 2016 (2016-03-10) paragraphs [0004], [0052], [0054], [0056], [0058], [0090]; figures 1-7	1-47

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2023/065982

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.

2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.

3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims;; it is covered by claims Nos.:

1-47, 80, 81

Remark on Protest

☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.

☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.

☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-47, 80, 81

   how to render a pipetting system more robust

   ---

2. claims: 48-79

   how to render a pipetting system covering multiple aspiration and dispensing ranges

   ---

3. claims: 82-100

   how to render a pipetting system more flexible

   ---

4. claims: 101-113

   how to improve a pipette tip to detect liquid

   ---

5. claims: 114-138

   how to improve a robotic pipetting system for a higher accuracy of liquid volume aspiration

   ---

6. claims: 139-198

   how to improve an automated pipetting system for a higher accuracy of liquid volume aspiration

   ---

7. claims: 199-204, 208, 209, 212-220

   how to improve a pipette tip for more functionalities

   ---

8. claims: 205-207, 210, 211, 221-226

   how to improve a pipette for a higher accuracy of liquid volume aspiration

   ---

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/US2023/065982

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2021163437 A1	19-08-2021	CA 3165085 A1	19-08-2021
		EP 4103327 A1	21-12-2022
		EP 4268960 A2	01-11-2023
		JP 2023515001 A	12-04-2023
		US 2021252496 A1	19-08-2021
		US 2022362759 A1	17-11-2022
		WO 2021163437 A1	19-08-2021
GB 2132346 A	04-07-1984	DE 3335641 A1	30-05-1984
		GB 2132346 A	04-07-1984
		JP S643061 Y2	26-01-1989
		JP S5984453 U	07-06-1984
EP 1973662 B1	23-03-2016	AU 2007203932 A1	12-07-2007
		CA 2633806 A1	12-07-2007
		CN 101365540 A	11-02-2009
		EP 1973662 A1	01-10-2008
		ES 2578279 T3	22-07-2016
		FR 2895920 A1	13-07-2007
		JP 5312044 B2	09-10-2013
		JP 2009531160 A	03-09-2009
		KR 20080092409 A	15-10-2008
		PL 1973662 T3	30-09-2016
		TW 200734056 A	16-09-2007
		US 2007169571 A1	26-07-2007
		WO 2007077527 A1	12-07-2007
EP 2359932 A1	24-08-2011	CN 102135084 A	27-07-2011
		EP 2359932 A1	24-08-2011
		JP 5475695 B2	16-04-2014
		JP 2011149937 A	04-08-2011
		US 2011182781 A1	28-07-2011
		US 2011182782 A1	28-07-2011
US 2016067705 A1	10-03-2016	DE 202013003390 U1	14-07-2014
		EP 2983826 A1	17-02-2016
		US 2016067705 A1	10-03-2016
		WO 2014166635 A1	16-10-2014