




(86) **Date de dépôt PCT/PCT Filing Date:** 2008/12/30
(87) **Date publication PCT/PCT Publication Date:** 2010/07/08
(45) **Date de délivrance/Issue Date:** 2016/04/12
(85) **Entrée phase nationale/National Entry:** 2011/05/04
(86) **N° demande PCT/PCT Application No.:** US 2008/088558
(87) **N° publication PCT/PCT Publication No.:** 2010/077244

(51) **Cl.Int./Int.Cl.** **A61M 31/00** (2006.01),
A61M 37/00 (2006.01), **A61M 5/178** (2006.01)
(72) **Inventeurs/Inventors:**
RANPURA, HIMANSHU, US;
VAN LIERE, CHAD C., US
(73) **Propriétaire/Owner:**
C.R. BARD INC., US
(74) **Agent:** SMART & BIGGAR

(54) **Titre : DISPOSITIF D'ADMINISTRATION DE MARQUEURS DESTINE A PLACER DES MARQUEURS DANS DES TISSUS**
(54) **Title: MARKER DELIVERY DEVICE FOR TISSUE MARKER PLACEMENT**



(57) **Abrégé/Abstract:**

A marker delivery device is configured for deploying a tissue marker. The marker delivery device includes a handle having a chamber, and a cannula. According to one aspect, the cannula has a flexible portion formed by a slot arrangement having of a plurality of spaced-apart substantially parallel peripheral slots extending through the side wall of the cannula to the lumen. A marker introducer rod is movably disposed in the lumen of the cannula for deploying the mark, and has a flexible region that corresponds to the flexible portion of the cannula. According to another aspect, a retraction mechanism is mounted to the handle and is configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
8 July 2010 (08.07.2010)(10) International Publication Number
WO 2010/077244 A1

(51) International Patent Classification:

A61M 31/00 (2006.01) *A61M 5/178* (2006.01)
A61M 37/00 (2006.01)

(21) International Application Number:

PCT/US2008/088558

(22) International Filing Date:

30 December 2008 (30.12.2008)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): **C.R. BARD INC.** [US/US]; 730 Central Avenue, Murray Hill, NJ 07974 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **RANPURA, Himanshu** [IN/US]; 4805 W. Darrell Road, Laveen, AZ 85339 (US). **VAN LIERE, Chad, C.** [US/US]; 6445 S. Maple Ave #2124, Tempe, AZ 85283 (US).(74) Agents: **DASPTT, Jacqueline, M.** et al.; Division Staff Attorney, IP, C.R. Bard, Inc., Bard Peripheral Vascular, Inc., 1415 West 3rd Street, P.O. Box 1740, Temp, AZ 85280-1740 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report (Art. 21(3))

(54) Title: MARKER DELIVERY DEVICE FOR TISSUE MARKER PLACEMENT




Fig. 1

(57) **Abstract:** A marker delivery device is configured for deploying a tissue marker. The marker delivery device includes a handle having a chamber, and a cannula. According to one aspect, the cannula has a flexible portion formed by a slot arrangement having of a plurality of spaced-apart substantially parallel peripheral slots extending through the side wall of the cannula to the lumen. A marker introducer rod is movably disposed in the lumen of the cannula for deploying the mark, and has a flexible region that corresponds to the flexible portion of the cannula. According to another aspect, a retraction mechanism is mounted to the handle and is configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

MARKER DELIVERY DEVICE FOR TISSUE MARKER PLACEMENT**BACKGROUND OF THE INVENTION****1. Field of the Invention**

[0001] The present invention relates to medical devices, and, more particularly, to a marker delivery device for percutaneous tissue marker placement.

2. Description of the Related Art

[0002] Tissue biopsies are commonly performed on many areas and organs of the human body where it is desirable to ascertain whether or not a lesion or other tissue to be biopsied is cancerous. Often, the lesion or other tissue to be biopsied is identified through use of an imaging technique, such as a computerized axial tomography (CAT) scan, ultrasonography, and mammography.

[0003] In breast biopsies, for example, the lesion typically is so small that the biopsy reduces its size to the extent that it is no longer visible by the imaging method employed. In such circumstances, it is desirable to place a tissue marker at the site of the biopsy to enable the medical practitioner subsequently to locate the lesion quickly and accurately in the event complete removal of the affected tissue is indicated. The tissue marker is placed at the biopsy site, for example, by a marker delivery device having a needle cannula that houses the tissue marker.

[0004] In some marker delivery devices, the marker may not be completely ejected from the cannula, or may be drawn back into or toward the cannula by the vacuum created upon the withdrawal of the cannula, which results in the marker being moved from the intended site, leading to inaccurate identification of the location of the biopsy area. Another issue is the safe disposal of the marker delivery device after use,

particularly the safe disposal of the cannula portion of the marker delivery device that is inserted into the tissue of the patient, which typically has a sharp point.

SUMMARY OF THE INVENTION

[0004a] According to various aspects, the present disclosure relates to a marker delivery device configured for deploying a tissue marker, comprising: a handle having a chamber; a cannula configured for holding the tissue marker for deployment; a marker introducer rod movably disposed in the lumen of the cannula; a deployment mechanism mounted to the handle and configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism, and a retraction mechanism mounted to the handle and configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism, wherein the deployment mechanism includes a first shear member that has a first region of reduced cross section dimension configured to shear during retraction of the marker introducer rod to limit the marker delivery device to a single use for marker deployment.

[0004b] According to various aspects, the present disclosure relates to a marker delivery device configured for deploying a tissue marker, comprising: a handle configured to be grasped by a user; a cannula having a proximal end and a distal end, the proximal end being coupled to the handle; and a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, wherein the handle includes a housing having a front end and a back end, with a chamber having a longitudinal extent between the front end and the back end, and having a hole leading to the chamber for receiving the cannula, and further comprising: an introducer rod guide block attached to the actuation end of the marker introducer rod, the introducer rod guide block being slidably disposed in the chamber of the housing; a first shear member that has a first region of reduced cross section dimension configured to shear during retraction of the marker introducer rod; a marker deployment trigger accessible at an exterior of the housing, the marker deployment trigger being linked to the introducer rod guide block by the first shear member, wherein an actuation of the marker deployment trigger causes the first shear member to displace the marker introducer rod to move

the marker introducer rod along the lengthwise extent of the cannula to deploy the tissue marker from the lumen of the cannula; a retraction trigger accessible at the exterior of the housing; a second shear member having a second region of reduced cross section dimension coupled to the retraction trigger, and configured such that the second region of reduced cross section dimension is sheared to separate the retraction trigger from the second shear member when the retraction trigger is actuated; a cannula guide block attached to the proximal end of the cannula, the cannula guide block being slidably disposed in the chamber of the housing, the retraction trigger being linked to the cannula guide block by the second shear member to hold the cannula guide block stationary relative to the housing of the handle; and a spring located between the front end of the housing and the cannula guide block, the spring being in a compressed state prior to actuation of the retraction trigger to provide a preload on the cannula guide block.

[0004c] According to various aspects, the present disclosure relates to a marker delivery device configured for deploying a tissue marker, comprising: a handle configured to be grasped by a user, the handle including a housing having a front end and a back end, with a chamber located between the front end and the back end, and having a hole leading from the chamber to the exterior of the handle; a cannula having a proximal end, a distal end, and a lumen extending along a lengthwise extent of the cannula between the proximal end and the distal end, the cannula being positioned in the handle such that the cannula retractably extends through the hole beyond the front end of the housing; a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, the marker introducer rod having an actuation end and a marker deployment end; a deployment mechanism mounted to the housing, the deployment mechanism being coupled to the actuation end of the marker introducer rod, the deployment mechanism being configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism; a retraction mechanism mounted to the housing, the retraction mechanism being coupled to the proximal end of the cannula, the retraction mechanism being configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism; and a shear mechanism having a shear region of reduced cross section dimension, the shear mechanism configured to be manually displaced by a user and configured such that when manually displaced

the shear region is exposed to a force exerted by the retraction mechanism to shear the shear mechanism at the shear region to enable the retraction.

[0004d] According to various aspects, the present disclosure relates to a marker delivery device configured for deploying a tissue marker, comprising: a handle having a chamber; a cannula configured for holding the tissue marker for deployment, the cannula having a side wall surrounding a lumen that extends along a lengthwise extent of the cannula, the cannula having a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through the side wall of the cannula to the lumen, the plurality of peripheral slots being spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula; a marker introducer rod movably disposed in the lumen of the cannula, the marker introducer rod having a flexible region that corresponds to the flexible portion of the cannula; a deployment mechanism mounted to the handle and configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism, and a retraction mechanism mounted to the handle and configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

[0004e] According to various aspects, the present disclosure relates to a marker delivery device configured for deploying a tissue marker, comprising: a handle configured to be grasped by a user; a cannula having a proximal end and a distal end, the proximal end being coupled to the handle, the cannula being substantially rigid and having a side wall surrounding a lumen that extends along a lengthwise extent of the cannula, the cannula having a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through the side wall of the cannula to the lumen, the plurality of peripheral slots being spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula; and a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, the marker introducer rod having an actuation end and a marker deployment end, and a flexible region that corresponds to the flexible portion of the cannula.

[0004f] According to various aspects, the present disclosure relates to a marker delivery device configured for deploying a tissue marker, comprising: a handle configured to be grasped by a user, the handle including a housing having a front end and a back end, with a chamber located between the front end and the back end, and having a hole leading from the chamber to the exterior of the handle; a cannula having a proximal end, a distal end, and a lumen extending along a lengthwise extent of the cannula between the proximal end and the distal end, the cannula being positioned in the handle such that the cannula retractably extends through the hole beyond the front end of the housing; a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, the marker introducer rod having an actuation end and a marker deployment end; a deployment mechanism mounted to the housing, the deployment mechanism being coupled to the actuation end of the marker introducer rod, the deployment mechanism being configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism, and a retraction mechanism mounted to the housing, the retraction mechanism being coupled to the proximal end of the cannula, the retraction mechanism being configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

[0005] The invention provides, according to one aspect thereof, a marker delivery device configured to fully deliver the tissue marker at a delivery site in the patient where the tissue marker is less likely to migrate, which is achieved by delivering the tissue marker via a rigid cannula having a flexible portion for directing the distal end of the cannula, for example, into tissue adjacent a biopsy site. The invention provides, according to another aspect thereof, a marker delivery device configured to facilitate the safe disposal of the marker delivery device after use. The marker delivery device may be used, for example, in association with various imaging systems, such as X-ray, ultrasound, MRI etc.

[0006] The invention, in one form thereof, is directed to a marker delivery device configured for deploying a tissue marker. The marker delivery device includes a handle having a chamber. A cannula is configured for holding the tissue marker for deployment. The cannula has

a side wall surrounding a lumen that extends along a lengthwise extent of the cannula. The cannula has a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through the side wall of the cannula to the lumen. The plurality of peripheral slots is spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula. A marker introducer rod is movably disposed in the lumen of the cannula. The marker introducer rod has a flexible region that corresponds to the flexible portion of the cannula. A deployment mechanism is mounted to the handle and configured to displace the marker introducer rod for

deploying the tissue marker upon an actuation of the deployment mechanism. A retraction mechanism is mounted to the handle and is configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

[0007] The invention, in another form thereof, is directed to a marker delivery device configured for deploying a tissue marker. The marker delivery device includes a handle configured to be grasped by a user. A cannula has a proximal end and a distal end, the proximal end being coupled to the handle. The cannula is substantially rigid and has a side wall surrounding a lumen that extends along a lengthwise extent of the cannula. The cannula has a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through the side wall of the cannula to the lumen. The slots of the plurality of peripheral slots are spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula. A marker introducer rod is movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula. The marker introducer rod has an actuation end and a marker deployment end, and a flexible region that corresponds to the flexible portion of the cannula.

[0008] The invention, in another form thereof, is directed to a marker delivery device configured for deploying a tissue marker. The marker delivery device includes a handle configured to be to be grasped by a user. The handle includes a housing having a front end and a back end, with a chamber located between the front end and the back end, and having a hole leading from the chamber to the exterior of the handle. A cannula has a proximal end, a distal end, and a lumen extending along a

lengthwise extent of the cannula between the proximal end and the distal end. The cannula is positioned in the handle such that the cannula retractably extends through the hole beyond the front end of the housing. A marker introducer rod is movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula. The marker introducer rod has an actuation end and a marker deployment end. A deployment mechanism is mounted to the housing. The deployment mechanism is coupled to the actuation end of the marker introducer rod. The deployment mechanism is configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism. A retraction mechanism is mounted to the housing, and is coupled to the proximal end of the cannula. The retraction mechanism is configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The above-mentioned and other features and advantages of this invention, and the manner of attaining them, will become more apparent and the invention will be better understood by reference to the following description of embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

[0010] Fig. 1 is a perspective view of a marker delivery device configured for deploying a tissue marker in accordance with an embodiment of the present invention;

[0011] Fig. 2 is a section view of a portion of the marker delivery device of Fig. 1 taken along plane 2-2;

[0012] Fig. 3 is a section view of a portion of the marker delivery device of Fig. 1 taken along plane 3-3;

[0013] Fig. 4A is a top view of a portion of the cannula of the marker delivery device of Fig. 1 depicting a flexible portion of the cannula;

[0014] Fig. 4B is a side view of the flexible portion of the cannula of Fig. 4A, showing in phantom lines the flexure of the flexible portion of the cannula relative to non-flexure;

[0015] Fig. 4C is an end view of the cannula of Fig. 4A from the perspective of looking into the lumen of the cannula from the distal end of the cannula, also showing in phantom lines the flexure of the flexible portion of the cannula relative to non-flexure;

[0016] Fig. 5 is a top view of an alternative configuration of the flexible portion of the marker delivery device of Fig. 1;

[0017] Fig. 6 is a top view of another alternative configuration of the flexible portion of the cannula of the marker delivery device of Fig. 1;

[0018] Fig. 7 is a side view of a portion of the marker introducer rod of the marker delivery device of Fig. 1, showing the actuation end, the marker deployment end, and the flexible region;

[0019] Fig. 8 is a perspective view of the marker delivery device of Fig. 1 used in conjunction with a biopsy device, showing a flexure of flexible portion of the cannula;

[0020] Fig. 9 is a perspective view of the marker delivery device of Fig. 1 following complete retraction of the cannula and marker introducer rod into the longitudinal chamber of the housing of the handle;

[0021] Fig. 10 is a perspective view of a marker delivery device configured for deploying a tissue marker in accordance with another embodiment of the present invention;

[0022] Fig. 11 is a section view of the marker delivery device of Fig. 10 taken along plane 11-11, showing the deployment mechanism in an initial position;

[0023] Fig. 12 is a section view of the marker delivery device of Fig. 10, showing the deployment mechanism in a marker deployed position;

[0024] Fig. 13 is a section view of the marker delivery device of Fig. 10, showing the deployment mechanism in a marker introducer rod initial retraction position;

[0025] Fig. 14 is a section view of the marker delivery device of Fig. 10, showing the deployment mechanism in a marker introducer rod post-initial retraction position; and

[0026] Fig. 15 is a section view of a portion of the marker delivery device of Fig. 10 taken along plane 15-15, depicting the cannula retraction mechanism.

[0027] Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate embodiments of the invention, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION OF THE INVENTION

[0028] Referring now to the drawings, and more particularly to Figs. 1-3, there is shown a marker delivery device 10 configured for deploying a tissue marker 12, in accordance with an embodiment of the present invention.

[0029] Marker delivery device 10 includes a handle 14, a cannula 16, a marker introducer rod 18, a deployment mechanism 20 and a retraction mechanism 22.

[0030] Handle 14 is configured to be grasped by a user, i.e., is of an appropriate size and shape to be grasped by the hand of the user of marker delivery device 10.

Handle 14 includes a housing 24 having a front end 24-1, a back end 24-2 and a side

7/40

wall 24-3, with a longitudinal chamber 26 located between front end 24-1 and back end 24-2 that is surrounded by side wall 24-3. A hole 24-4 leads from chamber 26 through front end 24-1 of housing 24 to the exterior of handle 14. A trigger slot 24-5 extends through side wall 24-3 of housing 24.

[0031] Cannula 16 is configured for holding tissue marker 12 for deployment into a tissue mass of a patient, and may be in the form of a hollow needle. Cannula 16 is positioned in handle 14 such that cannula 16 extends through the hole 24-4 beyond the front end 24-1 of housing 24 prior to marker deployment. Cannula 16 has a proximal end 16-1 and a distal end 16-2, with the proximal end 16-1 being coupled to handle 14. Cannula 16 has a side wall 16-3 that surrounds a lumen 16-4 that extends along a lengthwise extent 28 along a longitudinal axis 16-5 of cannula 16. Cannula 16 is substantially rigid, and may be made, for example, from a metallic material, such as for example, stainless steel, nitinol, a nickel-chromium alloy, titanium, etc.

[0032] Referring also to Figs. 4A-4C, cannula 16 has a flexible portion 30 formed by a slot arrangement 32 having of a plurality of peripheral slots 34 arranged circumferentially around cannula 16. Slot arrangement 32 may be formed in cannula 16, for example, by making cuts in cannula 16, such as through the use of a cutting laser. In the present embodiment, flexible portion 30 of cannula 16 is located closer to the distal end 16-2 of cannula 16 than to proximal end 16-1 of cannula 16. The plurality of peripheral slots 34 extends through the side wall 16-2 of cannula 16 to lumen 16-4. Also, as illustrated in Fig. 4C, in the present embodiment a circumferential extent 34-1 of each of the slots of the plurality of peripheral slots 34 of slot arrangement 32 is approximately two-thirds of the total circumference of cannula 16.

[0033] As illustrated in Figs. 4A and 4B, in the present embodiment the plurality of peripheral slots 34 are spaced apart from one another to be substantially parallel along the lengthwise extent 28 of cannula 16 to facilitate a flexure at flexible portion 30 of cannula 16. Fig. 4B shows in phantom lines the flexure of the flexible portion 30 of cannula 16 relative to a non-flexure of cannula 16. As illustrated in Figs. 4B and 4C, the configuration of the plurality of peripheral slots 34 (e.g., the circumferential placement of the slots along cannula 16) may be selected so that the flexure occurs along a single predetermined plane 36. In the present embodiment, for example, each of the substantially parallel plurality of peripheral slots 34 is arranged to be orthogonal to the longitudinal axis 16-5 of cannula 16.

[0034] The configuration of the plurality of peripheral slots 34 and the material forming cannula 16 may be selected such that the flexure does not result in a permanent deformation of cannula 16. For example, a slot width 34-2 relative to longitudinal axis 16-5 of the slots, the circumferential extent 34-1 of the slots, the axial placement of the slots along cannula 16, and the material used to form cannula 16 may be selected, through empirical studies and/or through materials analysis, so that flexible portion 30 formed by slot arrangement 32 will flex (e.g., bend at an acute angle with respect to longitudinal axis 16-5) when the distal end 16-2 of cannula 16 is acted on by an external force (F), and then return to the pre-deflected state, e.g., straight along longitudinal axis 16-5, when the external force (F) is removed.

[0035] Fig. 5 shows another slot arrangement 38 that may be used as an alternative to slot arrangement 32 shown in Figs. 4A-4C. Slot arrangement 38 may be formed in cannula 16, for example, by making cuts in cannula 16, such as through the use of a cutting laser. Slot arrangement 38 includes of a plurality of peripheral slots

40 arranged circumferentially around cannula 16. The plurality of peripheral slots 40 include a first set of peripheral slots 42-1 having a first circumferential extent 44-1 and a second set of peripheral slots 42-2 having a second circumferential extent 44-2. The first circumferential extent 44-1 of the first set of peripheral slots 42-1 is circumferentially staggered with respect to the second circumferential extent 44-2 of the second set of peripheral slots 42-2.

[0036] Fig. 6 shows another slot arrangement 46 that may be used as a further alternative to slot arrangement 32 shown in Figs. 4A-4C, and includes the plurality of peripheral slots 34 arranged circumferentially around cannula 16, but in addition includes an axial slot 48 that extends along the lengthwise extent 28 of cannula 16 to link at least a portion, or all, of the plurality of peripheral slots 34 in a continuous slot arrangement. Slot arrangement 46 may be formed in cannula 16, for example, by making cuts in cannula 16, such as through the use of a cutting laser.

[0037] Referring again to Figs. 2 and 3, marker introducer rod 18 is movably disposed in lumen 16-4 of cannula 16 to effect a deployment of tissue marker 12 from the distal end 16-2 of cannula 16. Referring also to Fig. 7, marker introducer rod 18 has an actuation end 18-1 and a marker deployment end 18-2, and has a flexible region 50 that corresponds to the flexible portion 30 of cannula 16. Accordingly, as flexible portion 30 of cannula 16 flexes, the flexible region 50 also flexes, while retaining the ability of marker introducer rod 18 to move longitudinally along lumen 16-4 to effect a deployment of tissue marker 12.

[0038] The flexible region 50 of marker introducer rod 18 may be formed as a flexible metallic element or a flexible plastic element, which in the present embodiment may be of reduced diameter with respect to a diameter of the remainder

of marker introducer rod 18. Also, the remainder of marker introducer rod 18 may be formed from metal or plastic.

[0039] Fig. 8 illustrates an exemplary implementation of marker delivery device 10 with respect to the flexible portion 30 of cannula 16, and more particularly shows a portion of an exemplary breast biopsy device 52 having the driver removed (not shown) that drives a cutter and vacuum unit in harvesting a tissue sample via a biopsy needle 54. Thereafter, cannula 16 of marker delivery device 10 is inserted through the lumen of biopsy needle 54 for placing tissue marker 12 in the tissue of the patient.

[0040] Biopsy needle 54 has a side sample notch 56 leading to a sample chamber 58 located at the lumen of biopsy needle 54. As cannula 16 is advanced in the lumen of biopsy needle 54 to the end of sample chamber 58, a ramped surface 58-1 at the end of sample chamber 58 exerts force (F) to deflect the distal end 16-2 of cannula 16 resulting in a flexure of flexible portion 30 of cannula (see also Figs. 4A-4C), thereby exposing the distal end 16-2 of cannula 16 to sample notch 56. With a further advancement of cannula 16 in the lumen of biopsy needle 54, as shown in Fig. 8, the distal end 16-2 of cannula 16 extends through sample notch 56 to penetrate tissue adjacent the biopsy site.

[0041] Thereafter, an advancement of marker introducer rod 18 in lumen 16-4 of cannula 16 (see, e.g., Fig. 3) causes tissue marker 12 to be deployed into the tissue surrounding the biopsy site. Flexible region 50 of marker introducer rod 18 (see, e.g., Fig. 7) conforms to the shape of flexible portion 30 of cannula 16, before, during and after the flexure of flexible portion 30 of cannula 16.

[0042] Alternatively, the distal end 16-2 of cannula 16 may be exposed to sample notch 56 without extending through sample notch 56, and tissue marker 12 may be deployed through sample notch 56 of biopsy needle 54 into the biopsy cavity.

[0043] Referring again to Figs. 1-3, deployment mechanism 20 is mounted to housing 24 of handle 14 and is configured to displace marker introducer rod 18 for deploying tissue marker 12 upon an actuation of deployment mechanism 20 by the user. In general, deployment mechanism 20 is configured to limit marker delivery device 10 to a single use for marker deployment. Figs. 1 and 2 show deployment mechanism 20 in an initial position 60 (marker not deployed) and Fig. 3 shows deployment mechanism 20 in a marker deployed position 62.

[0044] More particularly, deployment mechanism 20 includes an introducer rod guide block 64, a marker deployment trigger 66, and a first shear member 68.

Introducer rod guide block 64 is fixedly attached to the actuation end 18-1 of marker introducer rod 18, such as by molding a portion of marker introducer rod 18 into introducer rod guide block 64, and is slidably disposed in chamber 26 of housing 24. Marker deployment trigger 66 is accessible at an exterior of housing 24 of handle 14. Marker deployment trigger 66 is mounted to housing 24 for sliding movement along trigger slot 24-5 of housing 24 from the initial position 60 shown in Figs. 1 and 2 toward the front end 24-1 of housing 24 to position deployment mechanism 20 at the marker deployed position 62.

[0045] In the present embodiment, marker deployment trigger 66 and introducer rod guide block 64 are linked by first shear member 68. First shear member 68 extends from marker deployment trigger 66 and resides in a recess 70 located in introducer rod guide block 64. Thus, an actuation of marker deployment trigger 66

causes first shear member 68 to displace introducer rod guide block 64, which in turn displaces marker introducer rod 18 along the lengthwise extent 28 of cannula 16 to deploy tissue marker 12 from lumen 16-4 of cannula 16. First shear member 68 has a region of reduced cross section dimension 68-1, e.g., an annular groove, to provide a shear location.

[0046] An outer contour of introducer rod guide block 64 may be selected to be slidably received in a like-inner contour of longitudinal chamber 26 of housing 24 of handle 14. Accordingly, in embodiments where the outer contour of introducer rod guide block 64 and the like-inner contour of longitudinal chamber 26 are non-circular, introducer rod guide block 64 prevents rotation of marker introducer rod 18 with respect to housing 24 of handle 14, thus maintaining a constant orientation of marker introducer rod 18 relative to handle 14.

[0047] Also, in embodiments where the outer contour of introducer rod guide block 64 and the like-inner contour of longitudinal chamber 26 are circular, recess 70 of introducer rod guide block 64 may be in the form of a circumferential groove to facilitate a change in angular position, i.e., rotation, of marker introducer rod 18 with respect to housing 24 of handle 14. In such case, a rotator, e.g., knob, (not shown) positioned external to handle 14 may be coupled to introducer rod guide block 64 to effect a change in orientation of marker introducer rod 18 relative to handle 14.

[0048] As best shown in Fig. 2, deployment mechanism 20 may further include a lock mechanism 72 to lock marker deployment trigger 66 in the marker deployed position 62 after tissue marker 12 has been deployed. In the present embodiment, lock mechanism 72 includes a first lock member 72-1 formed on, or attached to, marker deployment trigger 66 and includes a second lock member 72-2 formed on, or

attached to, housing 24. In operation, first lock member 72-1 permanently engages second lock member 72-2 when marker deployment trigger 66 is positioned in the marker deployed position 62, thereby limiting marker delivery device 10 to a single marker deployment operation.

[0049] One of first lock member 72-1 and second lock member 72-1 may be, for example, a lock channel and the other of first lock member 72-1 and second lock member 72-2 may be a spring-loaded insert member that engages the lock channel when marker deployment trigger 66, and in turn marker introducer rod 18, is positioned in marker deployed position 62. In the present embodiment shown in Fig. 2, for example, first lock member 72-1 is formed as a lock channel in marker deployment trigger 66, and second lock member 72-2 is in the form of a spring-loaded pin that engages the lock channel when marker deployment trigger 66 is slid toward the front end 24-1 of housing 24 to position deployment mechanism 20, and in turn marker introducer rod 18, in marker deployed position 62. As a further example, when second lock member 72-2 is formed as a lock channel in housing 24, the lock channel may be formed by, or integral with, trigger slot 24-5, and first lock member 72-1 as a spring-loaded insert member may be a cantilevered arm having a protrusion that engages the lock channel when marker deployment trigger 66 is positioned in marker deployed position 62.

[0050] Again referring to Figs. 1-3, retraction mechanism 22 is mounted to housing 24 of handle 14 and is configured to facilitate a complete retraction of both cannula 16 and marker introducer rod 18 into chamber 26 of housing 24 of handle 14 upon an actuation of retraction mechanism 22 by the user, which most likely will occur following deployment of tissue marker 12. Retraction mechanism 22 is

configured to prevent cannula 16 and marker introducer rod 18 from extending outside chamber 26 of housing 24 of handle 14 after the complete retraction of cannula 16 and marker introducer rod 18 into chamber 26, thus facilitating the safe disposal of marker delivery device 10, and alleviating concern about the accidental puncturing of medical personnel, or the patient, following the use of marker delivery device 10.

[0051] More particularly, retraction mechanism 22 includes a retraction trigger 74, a cannula guide block 76, a second shear member 78, and a spring 80. Retraction trigger 74 may be in the form of a push button that is accessible at the exterior of the housing 24, e.g., through a hole 24-7 in side wall 24-3. Cannula guide block 76 is fixedly attached to the proximal end 16-1 of cannula 16, such as by molding a portion of cannula 16 into cannula guide block 76. Cannula guide block 76 is slidably disposed in longitudinal chamber 26 of housing 24. In the present embodiment, second shear member 78 is formed as an extension of retraction trigger 74.

[0052] As best shown in Fig. 3, retraction trigger 74 and cannula guide block 76 are linked by second shear member 78 that is resident in a recess 82 located in cannula guide block 76, thus holding cannula guide block 76 stationary, e.g., axially stationary, relative to housing 24 of handle 14. Spring 80 is located between the front end 24-1 of housing 24 and cannula guide block 76, with spring 80 being in a compressed state prior to actuation of retraction trigger 74, thus providing a preload on cannula guide block 76.

[0053] An outer contour of cannula guide block 76 may be selected to be slidably received in an inner like-contour of longitudinal chamber 26 of housing 24 of handle 14. Accordingly, in embodiments where the outer contour of cannula guide block 76

and the inner like-contour of longitudinal chamber 26 are non-circular, cannula guide block 76 prevents rotation of cannula 16 with respect to housing 24 of handle 14, thus maintaining a constant orientation of cannula 16 relative to handle 14.

[0054] However, in embodiments where the outer contour of cannula guide block 76 and the inner like-contour of longitudinal chamber 26 are circular, recess 82 of cannula guide block 76 may be in the form of a circumferential groove to facilitate a change in angular position, i.e., rotation, of cannula 16 with respect to housing 24 of handle 14, thus facilitating a changeable orientation of cannula 16 relative to handle 14. In such case, cannula 16 may be manually rotated by grasping cannula 16 and turning. Alternatively, a rotator, e.g., knob, (not shown) positioned external to handle 14 may be coupled to guide block 76 to effect a change in orientation of cannula 16 relative to handle 14.

[0055] An actuation of retraction trigger 74 causes a complete retraction of both cannula 16 and marker introducer rod 18 into chamber 26 of housing 24 of handle 14. More particularly, as shown in Fig. 3, second shear member 78 has a region of reduced cross section dimension 78-1, e.g., an annular groove, to provide a shear location. Initially, the region of reduced cross section dimension 78-1 of second shear member 78 is contained within the hole 24-7 formed in side wall 24-3, thereby providing additional support at the region of reduced cross section dimension 78-1.

[0056] In the present embodiment, an actuation (depressing) of retraction trigger 74 radially displaces second shear member 78 causing second shear member 78 to shear. More particularly, by depressing retraction trigger 74, the region of reduced cross section dimension 78-1 of second shear member 78 enters longitudinal chamber 26 through side wall 24-3 of housing 24, such that the region of reduced cross section

dimension 78-1 of second shear member 78 is no longer supported by side wall 24-3, and whereby the spring force exerted by spring 80 overcomes the shear resistance of the region of reduced cross section dimension 78-1 of second shear member 78. The shearing of second shear member 78 results in a release of spring 80 from the compressed state shown in Figs. 1-3 to force cannula guide block 76 to move toward the back end 24-2 of housing 24 to begin an initial retraction of cannula 16, and wherein a continued decompression of spring 80 causes cannula guide block 76 to impact introducer rod guide block 64 to shear first shear member 68, whereby beginning a simultaneous retraction of both cannula 16 and marker introducer rod 18 into chamber 26 of housing 24 of handle 14. The simultaneous retraction of both cannula 16 and marker introducer rod 18 into handle 14 terminates after both cannula 16 and marker introducer rod 18 are completely contained in longitudinal chamber 26 of housing 24 of handle 14, as illustrated in Fig. 9.

[0057] Alternatively, a spacing device 84 (see Fig. 1) may be positioned between introducer rod guide block 64 and cannula guide block 76. Spacing device 84 has a length along the lengthwise extent 28 such that cannula guide block 76 is in operable contact with introducer rod guide block 64 when introducer rod guide block 64 is positioned in the marker deployed position 62, such that first shear member 68 and second shear member 78 are sheared substantially simultaneously when retraction trigger 74 displaced, resulting in a complete simultaneous retraction of both cannula 16 and marker introducer rod 18 into chamber 26 of housing 24.

[0058] Figs. 10-15 depict another embodiment of the invention, depicting a marker delivery device 110 that includes a handle 112, cannula 16, marker introducer rod 18, a deployment mechanism 114 and a cannula retraction mechanism 116.

Cannula 16 and marker introducer rod 18 may be configured as previously described, and thus for brevity the full details of their operation will not be repeated here.

Marker delivery device 110 functionally differs from the embodiment of marker delivery device 10, in that deployment mechanism 114 of marker delivery device 110 may be configured to facilitate a full retraction of marker introducer rod 18 prior to beginning the retraction of cannula 16 effected by cannula retraction mechanism 116.

[0059] Handle 112 is configured of an appropriate size and shape to be grasped by the hand of the user of marker delivery device 110. Handle 112 includes a housing 118 having a front end 118-1, a back end 118-2 and a side wall 118-3, with a longitudinal chamber 120 located between front end 118-1 and back end 118-2 that is surrounded by side wall 118-3. A hole 118-4 leads from longitudinal chamber 120 through the front end 118-1 of housing 118 to the exterior of handle 112. Cannula 16 is positioned in handle 112 such that cannula 16 initially extends through hole 118-4 beyond the front end 118-1 of housing 118 prior to marker deployment. A trigger slot 118-5 extends through side wall 118-3 of housing 118.

[0060] Deployment mechanism 114 is mounted to housing 118 of handle 112 and is configured to displace marker introducer rod 18 for deploying tissue marker 12 upon an actuation of deployment mechanism 114 by the user. Figs. 10 and 11 show deployment mechanism 114 in an initial position 121 (unused, marker not deployed), Fig. 12 shows deployment mechanism 114 in a marker deployed position 122, Fig. 13 shows deployment mechanism 114 in a marker introducer rod initial retraction position 124, and Fig. 14 shows deployment mechanism 114 in a marker introducer rod post-initial retraction position 126.

[0061] Deployment mechanism 114 includes an introducer rod guide block 128, a multi-stage marker deployment trigger 130, a first shear member 132, and an introducer rod retraction spring 133. First shear member 132 has a region of reduced cross section dimension 132-1, e.g., an annular groove, to provide a shear location. Introducer rod guide block 128 is attached to the actuation end 18-1 of marker introducer rod 18, and is slidably disposed in longitudinal chamber 120 of housing 118. Marker deployment trigger 130 is accessible at an exterior of housing 118 of handle 112. Marker deployment trigger 130 includes an inner sleeve 130-1 and an outer actuator 130-2. Marker deployment trigger 130 is mounted to housing 118 for sliding movement along trigger slot 118-5.

[0062] Figs. 11-14 show various stages of movement of inner sleeve 130-1 and an outer actuator 130-2 of marker deployment trigger 130. In the present embodiment, marker deployment trigger 130 and introducer rod guide block 128 are linked by first shear member 132. First shear member 132 extends from inner sleeve 130-1 of marker deployment trigger 130 and resides in a recess 134 located in introducer rod guide block 128.

[0063] Initially, as shown in Fig. 11, inner sleeve 130-1 and outer actuator 130-2 of marker deployment trigger 130 are linked by a drive tab 136 mounted to inner sleeve 130-1 that engages a drive slot 138 formed in outer actuator 130-2, so that inner sleeve 130-1 and outer actuator 130-2 initially move concurrently. Drive slot 138 is defined by a downward facing lip 140 that separates drive slot 138 from an elongate introducer rod retraction slot 142. Drive tab 136 may be hinge-mounted, e.g., by a linking membrane, to inner sleeve 130-1. Drive tab 136 includes an upwardly extending protrusion 136-1 that is initially engaged with lip 140 in drive

slot 138. Introducer rod retraction spring 133 is positioned between cannula retraction mechanism 116 and introducer rod guide block 128 under slight compression, and more particularly, between introducer rod guide block 128 and cannula guide block 156.

[0064] Referring to Fig. 12, an actuation of marker deployment trigger 130 by sliding outer actuator 130-2 of marker deployment trigger 130 toward the front end 118-1 of housing 118 of handle 112 causes inner sleeve 130-1 to move first shear member 132 longitudinally along longitudinal chamber 120 to displace introducer rod guide block 128, which in turn displaces marker introducer rod 18 along the lengthwise extent 28 of cannula 16 to deploy tissue marker 12 from lumen 16-4 of cannula 16 when the marker deployed position 122 depicted in Fig. 12 is reached. At this stage, introducer rod retraction spring 133 is being compressed. Housing 118 includes an indicator line 144, such that when a leading edge 146 of inner sleeve 130-1 aligns with indicator line 144 to indicate that the marker deployed position 122 has been reached, the user is assured of a complete deployment of tissue marker 12 out of the distal end 16-2 of cannula 16.

[0065] Also, as depicted in Fig. 12, when marker deployment trigger 130 is positioned at marker deployed position 122, drive tab 136 is positioned over a retraction channel 148 in housing 118. A further sliding of outer actuator 130-2 of marker deployment trigger 130 toward the front end 118-1 of housing 118 of handle 112 causes lip 140 forming a trailing edge of drive slot 138 to force protrusion 136-1 of drive tab 136 to twist forward into a deformation downward into a retraction channel 148 formed in housing 118 of handle 112, thereby allowing lip 140 to begin

to pass over protrusion 136-1 of drive tab 136. At this stage, introducer rod retraction spring 133 has reached maximum compression.

[0066] As depicted in Fig. 13, the further sliding of outer actuator 130-2 of marker deployment trigger 130 toward the front end 118-1 of housing 118 of handle 112 causes lip 140 to pass over the upward protrusion 136-1 of drive tab 136, thereby allowing drive tab 136 to regain its original geometry with respect inner sleeve 130-1, thereby moving upwardly out of retraction channel 148. This action occurs when the leading edge 150 of outer actuator 130-2 aligns with indicator line 152 of inner sleeve 130-1. At this stage, introducer rod retraction spring 133 starts to decompress. Accordingly, a portion of deployment mechanism 114, e.g., inner sleeve 130-1, outer actuator 130-2, drive tab 136, lip 140, and retraction channel 148 of deployment mechanism 114, also functions as an introducer rod retraction mechanism 153 for marker introducer rod 18.

[0067] As depicted in Fig. 14, with upward protrusion 136-1 of drive tab 136 fully released from retraction channel 148 and upward protrusion 136-1 of drive tab 136 being positioned in introducer rod retraction slot 142, the decompression of introducer rod retraction spring 133 forces introducer rod guide block 128 toward the back end 118-2 of housing 118 (see Fig. 10), and in turn marker introducer rod 18 and inner sleeve 130-1 are returned toward their initial positions as depicted in Figs. 10 and 11. The spring force provided by introducer rod retraction spring 133 may be selected, for example, such that the impact of inner sleeve 130-1 with end wall 118-6 of housing 118 causes first shear member 132 to shear at the region of reduced cross section dimension 132-1, thereby facilitating a complete retraction of marker introducer rod 18 into longitudinal chamber 120, prior to initiating retraction of cannula 16.

[0068] Alternatively, the spring force provided by introducer rod retraction spring 133 may be selected, for example, such that the impact of inner sleeve 130-1 with end wall 118-6 of housing 118 stops the retraction of marker introducer rod 18 into longitudinal chamber 120 after a partial retraction of marker introducer rod 18, prior to initiating retraction of cannula 16.

[0069] Also, as depicted in Fig. 14, at this stage outer actuator 130-2 of marker deployment trigger 130 is no longer linked to inner sleeve 130-1. Thus, a subsequent extension of marker introducer rod 18 by actuation of outer actuator 130-2 of marker deployment trigger 130 is prevented, thereby rendering marker delivery device 110 usable for only a single tissue marker deployment.

[0070] Referring again also to Fig. 10 in relation to Fig. 14 and 15, cannula retraction mechanism 116 is mounted to housing 118 of handle 112 and is configured to facilitate a complete retraction of cannula 16 into longitudinal chamber 120 of housing 118 of handle 112 upon an actuation of cannula retraction mechanism 116 by the user, which most likely will occur following deployment of tissue marker 12. Fig. 15 shows cannula retraction mechanism 116, with marker introducer rod 18 in marker deployed position 122. Cannula retraction mechanism 116 is configured to prevent cannula 16 and marker introducer rod 18 from extending outside longitudinal chamber 120 of housing 118 of handle 112 after the complete retraction of cannula 16 and marker introducer rod 18 into longitudinal chamber 120, thus facilitating the safe disposal of marker delivery device 110, and alleviating concern about the accidental puncturing of medical personnel, or the patient, following the use of marker delivery device 110.

[0071] Cannula retraction mechanism 116 includes a retraction trigger 154, a cannula guide block 156, a second shear member 158, and a cannula retraction spring 160. Retraction trigger 154 may be in the form of a push button that is accessible at the exterior of housing 118, e.g., through a hole 118-7 in side wall 118-3. Cannula guide block 156 is attached to the proximal end 16-1 of cannula 16. Cannula guide block 156 is slidably disposed in longitudinal chamber 120 of housing 118. In the present embodiment, second shear member 158 is formed as an extension of retraction trigger 154.

[0072] Retraction trigger 154 and cannula guide block 156 are linked by second shear member 158 that is resident in a recess 162 located in cannula guide block 156, thus holding cannula guide block 156 stationary relative to housing 118 of handle 112. Cannula retraction spring 160 is located between the front end 118-1 of housing 118 and cannula guide block 156, with cannula retraction spring 160 being in a compressed state prior to actuation of retraction trigger 154, thus providing a preload on cannula guide block 156.

[0073] An actuation of retraction trigger 154 causes a complete retraction of cannula 16 into longitudinal chamber 120 of housing 118 of handle 112. More particularly, as shown in Fig. 15, initially, the region of reduced cross section dimension 158-1 of second shear member 158 is supported by side wall 118-3, thereby providing additional support at the region of reduced cross section dimension 158-1. An actuation (depressing) of retraction trigger 154 radially displaces second shear member 158 causing the region of reduced cross section dimension 158-1 of second shear member 158 to enter longitudinal chamber 120 through side wall 118-3 of housing 118, such that the region of reduced cross section dimension 158-1 of

second shear member 158 is no longer supported by the side wall 118-3, and whereby the spring force exerted by cannula retraction spring 160 overcomes the shear resistance of the region of reduced cross section dimension 158-1 of second shear member 158. The shearing of second shear member 158 results in a release of cannula retraction spring 160 from the compressed state shown to force cannula guide block 156 to move toward the back end 118-2 of housing 118 to complete a full retraction of cannula 16 into longitudinal chamber 120 of housing 118 of handle 112.

[0074] In the event of a partial retraction of marker introducer rod 18, or in the event that the user does not perform the previously described retraction of marker reducer rod, into longitudinal chamber 120 of housing 118 of handle 112 prior to actuation of retraction trigger 154 (as depicted in Fig. 15), the continued decompression of cannula retraction spring 160 causes cannula guide block 156 to impact introducer rod guide block 128 to shear first shear member 132, whereby facilitating a full simultaneous retraction of both cannula 16 and marker introducer rod 18 into longitudinal chamber 120 of housing 118 of handle 112.

[0075] The retraction process is completed when both cannula 16 and marker introducer rod 18 are completely contained in longitudinal chamber 120 of housing 118 of handle 112.

[0076] While this invention has been described with respect to at least one embodiment, the present invention can be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known

or customary practice in the art to which this invention pertains and which fall within the limits of the appended claims.

What is claimed is:

1. A marker delivery device configured for deploying a tissue marker, comprising:
 - a handle having a chamber;
 - a cannula configured for holding the tissue marker for deployment;
 - a marker introducer rod movably disposed in the lumen of the cannula;
 - a deployment mechanism mounted to the handle and configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism, and
 - a retraction mechanism mounted to the handle and configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism, wherein the deployment mechanism includes a first shear member that has a first region of reduced cross section dimension configured to shear during retraction of the marker introducer rod to limit the marker delivery device to a single use for marker deployment.
2. The marker delivery device of claim 1, wherein the retraction mechanism includes a retraction trigger and a second shear member having a second region of reduced cross section dimension coupled to the retraction trigger, and configured such that the second region of reduced cross section dimension is sheared to separate the retraction trigger from the second shear member when the retraction trigger is actuated so as to prevent the cannula and the marker introducer rod from extending outside the chamber after the complete retraction of the cannula and the marker introducer rod into the chamber.
3. A marker delivery device configured for deploying a tissue marker, comprising:
 - a handle configured to be grasped by a user;
 - a cannula having a proximal end and a distal end, the proximal end being coupled to the handle; and
 - a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, wherein the handle includes a housing having a front end and a back end, with a chamber having a longitudinal

extent between the front end and the back end, and having a hole leading to the chamber for receiving the cannula, and further comprising:

- an introducer rod guide block attached to the actuation end of the marker introducer rod, the introducer rod guide block being slidably disposed in the chamber of the housing;

- a first shear member that has a first region of reduced cross section dimension configured to shear during retraction of the marker introducer rod;

- a marker deployment trigger accessible at an exterior of the housing, the marker deployment trigger being linked to the introducer rod guide block by the first shear member, wherein an actuation of the marker deployment trigger causes the first shear member to displace the marker introducer rod to move the marker introducer rod along the lengthwise extent of the cannula to deploy the tissue marker from the lumen of the cannula;

- a retraction trigger accessible at the exterior of the housing;

- a second shear member having a second region of reduced cross section dimension coupled to the retraction trigger, and configured such that the second region of reduced cross section dimension is sheared to separate the retraction trigger from the second shear member when the retraction trigger is actuated;

- a cannula guide block attached to the proximal end of the cannula, the cannula guide block being slidably disposed in the chamber of the housing, the retraction trigger being linked to the cannula guide block by the second shear member to hold the cannula guide block stationary relative to the housing of the handle; and

- a spring located between the front end of the housing and the cannula guide block, the spring being in a compressed state prior to actuation of the retraction trigger to provide a preload on the cannula guide block.

4. The marker delivery device of claim 3, configured such that an actuation of the retraction trigger displaces the second shear member in a first direction and the spring decompresses to displace the cannula guide block in a second direction to shear the second shear member at the second region of reduced cross section dimension and to shear the first shear member at the first region of reduced cross section dimension to cause a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

5. The marker delivery device of claim 3, configured such that an actuation of the retraction trigger moves the second region of reduced cross section dimension from a support position within a side wall of the housing to an exposed position in the chamber of the housing, resulting in a release of the spring from the compressed state to force the cannula guide block to move toward the back end of the housing to shear the second shear member at the second region of reduced cross section dimension to begin an initial retraction of the cannula, and wherein a continued decompression of the spring causes the cannula guide block to impact the introducer rod guide block to shear the first shear member at the first region of reduced cross section dimension, whereby beginning a simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

6. The marker delivery device of claim 5, wherein the simultaneous retraction of both the cannula and the marker introducer rod into the handle terminates after both the cannula and the marker introducer rod are completely contained in the chamber of the housing of the handle.

7. The marker delivery device of claim 3, wherein a spacing device is positioned between the introducer rod guide block and the cannula guide block, the spacing device having a length along the lengthwise extent such that the cannula guide block is in operable contact with the introducer rod guide block when the introducer rod guide block is positioned in the marker deployed position, such that the first shear member and the second shear member are sheared simultaneously when the retraction trigger is actuated, resulting in a complete simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing.

8. The marker delivery device of claim 3, further comprising a lock mechanism to lock the marker deployment trigger in a marker deployed position after the tissue marker has been deployed.

9. The marker delivery device of claim 3, wherein: the marker deployment trigger includes a first lock member and the housing includes a second lock member, and wherein the

first lock member permanently engages the second lock member when the marker deployment trigger is positioned in the marker deployed position.

10. The marker delivery device of claim 9, wherein one of the first lock member and the second lock member is a lock channel and the other of the first lock member and the second lock member is a spring-loaded insert member that engages the lock channel lock when the marker deployment trigger is positioned in the marker deployed position.

11. A marker delivery device configured for deploying a tissue marker, comprising:

- a handle configured to be grasped by a user, the handle including a housing having a front end and a back end, with a chamber located between the front end and the back end, and having a hole leading from the chamber to the exterior of the handle;

- a cannula having a proximal end, a distal end, and a lumen extending along a lengthwise extent of the cannula between the proximal end and the distal end, the cannula being positioned in the handle such that the cannula retractably extends through the hole beyond the front end of the housing;

- a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, the marker introducer rod having an actuation end and a marker deployment end;

- a deployment mechanism mounted to the housing, the deployment mechanism being coupled to the actuation end of the marker introducer rod, the deployment mechanism being configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism;

- a retraction mechanism mounted to the housing, the retraction mechanism being coupled to the proximal end of the cannula, the retraction mechanism being configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism; and

- a shear mechanism having a shear region of reduced cross section dimension, the shear mechanism configured to be manually displaced by a user and configured such that when manually displaced the shear region is exposed to a force exerted by the retraction mechanism to shear the shear mechanism at the shear region to enable the retraction.

12. The marker delivery device of claim 11, wherein the deployment mechanism includes:
an introducer rod guide block attached to the actuation end of the marker introducer rod, the introducer rod guide block being slidably disposed in the chamber of the housing;
a first shear member that has a first region of reduced cross section dimension configured to shear during retraction of the marker introducer rod; and
a marker deployment trigger accessible at an exterior of the housing, the marker deployment trigger being linked to the introducer rod guide block by the first shear member, wherein an actuation of the marker deployment trigger causes the first shear member to displace the marker introducer rod to move the marker introducer rod along the lengthwise extent of the cannula to deploy the tissue marker from the lumen of the cannula, and configured such that when the first shear member is sheared the marker deployment trigger is permanently disconnected from the introducer guide block.
13. The marker delivery device of claim 12, wherein: the housing includes a trigger slot that extends through a side wall of the housing,
the marker deployment trigger being mounted to the housing for sliding movement along the trigger slot from an initial position to a marker deployed position,
the marker deployment trigger includes a first lock member and the housing includes a second lock member, and
the first lock member permanently engages the second lock member when the marker deployment trigger is positioned in the marker deployed position.
14. The marker delivery device of claim 13, wherein one of the first lock member and the second lock member is a lock channel and the other of the first lock member and the second lock member is a spring-loaded insert member that engages the lock channel lock when the marker deployment trigger is positioned in the marker deployed position.
15. The marker delivery device of claim 11, wherein the retraction mechanism includes:
a retraction trigger accessible at the exterior of the housing, the retraction trigger;
a second shear member;
a cannula guide block attached to the proximal end of the cannula, the cannula guide block being slidably disposed in the chamber of the housing, the retraction trigger being

linked to the cannula guide block by the second shear member to hold the cannula guide block stationary relative to the housing of the handle;

the second shear member having a second region of reduced cross section dimension configured to shear during a retraction of the cannula guide block, and wherein when the second shear member is sheared the retraction trigger is permanently disconnected from the cannula guide block; and

a spring located between the front end of the housing and the cannula guide block, the spring being in a compressed state prior to actuation of the retraction trigger to provide a preload on the cannula guide block, and configured to decompress to initiate the retraction of the cannula guide block within the housing to shear the second shear member at the second region of reduced cross section dimension when the retraction trigger is actuated.

16. The marker delivery device of claim 15, wherein an actuation of the retraction trigger causes a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

17. The marker delivery device of claim 15, configured such that an actuation of the retraction trigger moves the second region of reduced cross section dimension from a support position within a side wall of the housing to an exposed position in the chamber of the housing, resulting in a release of the spring from the compressed state to force the cannula guide block to move toward the back end of the housing to shear the second shear member at the second region of reduced cross section dimension to begin an initial retraction of the cannula, and wherein a continued decompression of the spring causes the cannula guide block to impact the introducer rod guide block to shear the first shear member at the first region of reduced cross section dimension, whereby beginning a simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

18. The marker delivery device of claim 17, wherein the simultaneous retraction of both the cannula and the marker introducer rod into the handle terminates after both the cannula and the marker introducer rod are completely contained in the chamber of the housing of the handle.

19. The marker delivery device of claim 15, wherein a spacing device is positioned between the introducer rod guide block and the cannula guide block, the spacing device having a length along the lengthwise extent such that the cannula guide block is in operable contact with the introducer rod guide block when the introducer rod guide block is positioned in the marker deployed position, such that the first shear member and the second shear member are sheared simultaneously when the retraction trigger is actuated, resulting in a complete simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing.

20. The marker delivery device of claim 11, wherein: the cannula has a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through a side wall of the cannula to the lumen, the plurality of peripheral slots being spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula; and the marker introducer rod has a flexible region that corresponds to the flexible portion of the cannula.

21. The marker delivery device of claim 20, wherein the flexible portion of the cannula is located closer to the distal end of the cannula than to the proximal end of the cannula.

22. The marker delivery device of claim 20, wherein the plurality of peripheral slots are configured to facilitate the flexure at the flexible portion of the cannula along a single predetermined plane.

23. The marker delivery device of claim 20, wherein the plurality of peripheral slots include a first set of peripheral slots having a first circumferential extent and a second set of peripheral slots having a second circumferential extent.

24. The marker delivery device of claim 23, wherein the first circumferential extent is circumferentially alternately staggered with respect to the second circumferential extent.

25. The marker delivery device of claim 20, wherein the side wall of the cannula includes an axial slot linking at least a portion of the plurality of peripheral slots.

26. The marker delivery device of claim 20, wherein the cannula is formed from a metallic material, and at least the flexible region of the marker introducer rod is formed as a flexible metallic element.

27. The marker delivery device of claim 26, wherein the cannula is formed from a metallic material, and at least the flexible region of the marker introducer rod is formed as a flexible plastic element.

28. The marker delivery device of claim 11, wherein the retraction mechanism includes a first retraction mechanism configured for retracting the marker introducer rod and a second retraction mechanism configured for retracting the cannula, wherein an initial retraction of the introducer rod occurs before a retraction of the cannula.

29. The marker delivery device of claim 11, wherein the retraction mechanism includes a first retraction mechanism configured for retracting the marker introducer rod and a second retraction mechanism configured for retracting the cannula, wherein a complete retraction of the introducer rod occurs before a retraction of the cannula.

30. The marker delivery device of claim 11, wherein the retraction mechanism includes:
an introducer rod guide block attached to the actuation end of the marker introducer rod, the introducer rod guide block being slidably disposed in the chamber of the housing;
a cannula guide block attached to the proximal end of the cannula, the cannula guide block being slidably disposed in the chamber of the housing;
a first spring engagingly located between the introducer guide block and the cannula guide block; and
a marker deployment trigger accessible at an exterior of the housing, the marker deployment trigger being linked to the introducer rod guide block by a first shear member of the shear mechanism, and configured such that an actuation of the marker deployment trigger to a first position causes the first shear member to displace the marker introducer rod to move the marker introducer rod along the lengthwise extent of the cannula to deploy the tissue marker from the lumen of the cannula and to simultaneously compress the first spring, and a further actuation of the marker deployment trigger to a second position different from the first

position releases the first spring for decompression to shear the first shear member to retract the marker introducer rod into the chamber of the housing of the handle.

31. The marker delivery device of claim 30, wherein the decompression of the first spring results in a shearing of the first shear member, and the complete retraction of the marker introducer rod into the chamber of the housing of the handle.

32. The marker delivery device of claim 30, further including:

a retraction trigger mounted to the housing, the retraction trigger being coupled to the cannula guide block; and

a second spring engagingly located between the front end of the housing and the cannula guide block, the second spring being in a compressed state prior to actuation of the retraction trigger to provide a preload on the cannula guide block;

wherein an actuation of the retraction trigger results in a decompression of the second spring causing a complete retraction of the cannula into the chamber of the housing of the handle.

33. A marker delivery device configured for deploying a tissue marker, comprising:

a handle having a chamber;

a cannula configured for holding the tissue marker for deployment, the cannula having a side wall surrounding a lumen that extends along a lengthwise extent of the cannula, the cannula having a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through the side wall of the cannula to the lumen, the plurality of peripheral slots being spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula;

a marker introducer rod movably disposed in the lumen of the cannula, the marker introducer rod having a flexible region that corresponds to the flexible portion of the cannula;

a deployment mechanism mounted to the handle and configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism, and

a retraction mechanism mounted to the handle and configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

34. The marker delivery device of claim 33, wherein the plurality of peripheral slots are configured to facilitate the flexure at the flexible portion of the cannula along a single predetermined plane.

35. The marker delivery device of claim 33, wherein the deployment mechanism is configured to limit the marker delivery device to a single use for marker deployment.

36. The marker delivery device of claim 33, wherein the retraction mechanism is configured to prevent the cannula and the marker introducer rod from extending outside the chamber after the complete retraction of the cannula and the marker introducer rod into the chamber.

37. A marker delivery device configured for deploying a tissue marker, comprising:

a handle configured to be grasped by a user;

a cannula having a proximal end and a distal end, the proximal end being coupled to the handle, the cannula being substantially rigid and having a side wall surrounding a lumen that extends along a lengthwise extent of the cannula, the cannula having a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through the side wall of the cannula to the lumen, the plurality of peripheral slots being spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula; and

a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, the marker introducer rod having an actuation end and a marker deployment end, and a flexible region that corresponds to the flexible portion of the cannula.

38. The marker delivery device of claim 37, wherein the flexible portion of the cannula is located closer to the distal end of the cannula than to the proximal end of the cannula.

39. The marker delivery device of claim 37, wherein the plurality of peripheral slots are configured to facilitate the flexure at the flexible portion of the cannula along a single predetermined plane.

40. The marker delivery device of claim 37, wherein the plurality of peripheral slots include a first set of peripheral slots having a first circumferential extent and a second set of peripheral slots having a second circumferential extent.

41. The marker delivery device of claim 40, wherein the first circumferential extent is circumferentially staggered with respect to the second circumferential extent.

42. The marker delivery device of claim 37, wherein the slot arrangement includes an axial slot linking at least a portion of the plurality of peripheral slots.

43. The marker delivery device of claim 37, wherein the cannula is formed from a metallic material.

44. The marker delivery device of claim 43, wherein the metallic material is one of stainless steel, nitinol, a nickel-chromium alloy and titanium.

45. The marker delivery device of claim 37, wherein the flexible region of the marker introducer rod is formed as a flexible metallic element.

46. The marker delivery device of claim 37, wherein the flexible region of the marker introducer rod is formed as a flexible plastic element and a remainder of the marker introducer rod is formed from at least one of metal and plastic.

47. The marker delivery device of claim 37, wherein the handle includes a housing having a front end and a back end, with a chamber located between the front end and the back end, and having a hole leading to the chamber for receiving the cannula, and comprising:

a deployment mechanism mounted to the housing, the deployment mechanism configured to displace the marker introducer rod for deploying the tissue marker upon actuation of the deployment mechanism by the user, and

a retraction mechanism mounted to the housing, the retraction mechanism being configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon actuation of the retraction mechanism by the user.

48. The marker delivery device of claim 37, wherein the handle includes a housing having a front end and a back end, with a chamber having a longitudinal extent between the front end and the back end, and having a hole leading to the chamber for receiving the cannula, and further comprising:

an introducer rod guide block attached to the actuation end of the marker introducer rod, the introducer rod guide block being slidably disposed in the chamber of the housing;

a first shear member;

a marker deployment trigger accessible at an exterior of the housing, the marker deployment trigger being linked to the introducer rod guide block by the first shear member, wherein an actuation of the marker deployment trigger causes the first shear member to displace the marker introducer rod to move the marker introducer rod along the lengthwise extent of the cannula to deploy the tissue marker from the lumen of the cannula;

a retraction trigger accessible at the exterior of the housing;

a second shear member;

a cannula guide block attached to the proximal end of the cannula, the cannula guide block being slidably disposed in the chamber of the housing, the retraction trigger being linked to the cannula guide block by the second shear member to hold the cannula guide block stationary relative to the housing of the handle; and

a spring located between the front end of the housing and the cannula guide block, the spring being in a compressed state prior to actuation of the retraction trigger to provide a preload on the cannula guide block.

49. The marker delivery device of claim 48, wherein an actuation of the retraction trigger causes a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

50. The marker delivery device of claim 48, wherein an actuation of the retraction trigger causes the second shear member to shear, resulting in a release of the spring from the compressed state to force the cannula guide block to move toward the back end of the housing to begin an initial retraction of the cannula, and wherein a continued decompression of the spring causes the cannula guide block to impact the introducer rod guide block to shear the first shear member, whereby beginning a simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

51. The marker delivery device of claim 50, wherein the simultaneous retraction of both the cannula and the marker introducer rod into the handle terminates after both the cannula and the marker introducer rod are completely contained in the chamber of the housing of the handle.

52. The marker delivery device of claim 48, wherein a spacing device is positioned between the introducer rod guide block and the cannula guide block, the spacing device having a length along the lengthwise extent such that the cannula guide block is in operable contact with the introducer rod guide block when the introducer rod guide block is positioned in the marker deployed position, such that the first shear member and the second shear member are sheared simultaneously when the retraction trigger is actuated, resulting in a complete simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing.

53. The marker delivery device of claim 48, further comprising a lock mechanism to lock the marker deployment trigger in a marker deployed position after the tissue marker has been deployed.

54. The marker delivery device of claim 48, wherein: the marker deployment trigger includes a first lock member and the housing includes a second lock member, and wherein the

first lock member permanently engages the second lock member when the marker deployment trigger is positioned in the marker deployed position.

55. The marker delivery device of claim 54, wherein one of the first lock member the second lock member is a lock channel and the other of the first lock member the second lock member is a spring-loaded insert member that engages the lock channel lock when the marker deployment trigger is positioned in the marker deployed position.

56. A marker delivery device configured for deploying a tissue marker, comprising:

- a handle configured to be to be grasped by a user, the handle including a housing having a front end and a back end, with a chamber located between the front end and the back end, and having a hole leading from the chamber to the exterior of the handle;

- a cannula having a proximal end, a distal end, and a lumen extending along a lengthwise extent of the cannula between the proximal end and the distal end, the cannula being positioned in the handle such that the cannula retractably extends through the hole beyond the front end of the housing;

- a marker introducer rod movably disposed in the lumen of the cannula to effect a deployment of the tissue marker from the distal end of the cannula, the marker introducer rod having an actuation end and a marker deployment end;

- a deployment mechanism mounted to the housing, the deployment mechanism being coupled to the actuation end of the marker introducer rod, the deployment mechanism being configured to displace the marker introducer rod for deploying the tissue marker upon an actuation of the deployment mechanism, and

- a retraction mechanism mounted to the housing, the retraction mechanism being coupled to the proximal end of the cannula, the retraction mechanism being configured to facilitate a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle upon an actuation of the retraction mechanism.

57. The marker delivery device of claim 56, wherein the deployment mechanism includes:

- an introducer rod guide block attached to the actuation end of the marker introducer rod, the introducer rod guide block being slidably disposed in the chamber of the housing;

- a first shear member; and

a marker deployment trigger accessible at an exterior of the housing, the marker deployment trigger being linked to the introducer rod guide block by the first shear member, wherein an actuation of the marker deployment trigger causes the first shear member to displace the marker introducer rod to move the marker introducer rod along the lengthwise extent of the cannula to deploy the tissue marker from the lumen of the cannula.

58. The marker delivery device of claim 57, wherein:

the housing includes a trigger slot that extends through a side wall of the housing,

the marker deployment trigger being mounted to the housing for sliding movement along the trigger slot from an initial position to a marker deployed position,

the marker deployment trigger includes a first lock member and the housing includes a second lock member, and

the first lock member permanently engages the second lock member when the marker deployment trigger is positioned in the marker deployed position.

59. The marker delivery device of claim 58, wherein one of the first lock member the second lock member is a lock channel and the other of the first lock member the second lock member is a spring-loaded insert member that engages the lock channel lock when the marker deployment trigger is positioned in the marker deployed position.

60. The marker delivery device of claim 57, wherein the retraction mechanism includes:

a retraction trigger accessible at the exterior of the housing, the retraction trigger;

a second shear member;

a cannula guide block attached to the proximal end of the cannula, the cannula guide block being slidably disposed in the chamber of the housing, the retraction trigger being linked to the cannula guide block by the second shear member to hold the cannula guide block stationary relative to the housing of the handle; and

a spring located between the front end of the housing and the cannula guide block, the spring being in a compressed state prior to actuation of the retraction trigger to provide a preload on the cannula guide block.

61. The marker delivery device of claim 60, wherein an actuation of the retraction trigger causes a complete retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

62. The marker delivery device of claim 60, wherein an actuation of the retraction trigger causes the second shear member to shear, resulting in a release of the spring from the compressed state to force the cannula guide block to move toward the back end of the housing to begin an initial retraction of the cannula, and wherein a continued decompression of the spring causes the cannula guide block to impact the introducer rod guide block to shear the first shear member, whereby beginning a simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing of the handle.

63. The marker delivery device of claim 62 wherein the simultaneous retraction of both the cannula and the marker introducer rod into the handle terminates after both the cannula and the marker introducer rod are completely contained in the chamber of the housing of the handle.

64. The marker delivery device of claim 60, wherein a spacing device is positioned between the introducer rod guide block and the cannula guide block, the spacing device having a length along the lengthwise extent such that the cannula guide block is in operable contact with the introducer rod guide block when the introducer rod guide block is positioned in the marker deployed position, such that the first shear member and the second shear member are sheared simultaneously when the retraction trigger is actuated, resulting in a complete simultaneous retraction of both the cannula and the marker introducer rod into the chamber of the housing.

65. The marker delivery device of claim 56, wherein:

the cannula has a flexible portion formed by a slot arrangement having of a plurality of peripheral slots extending through a side wall of the cannula to the lumen, the plurality of peripheral slots being spaced apart to be substantially parallel along the lengthwise extent of the cannula to facilitate a flexure at the flexible portion of the cannula; and

the marker introducer rod has a flexible region that corresponds to the flexible portion of the cannula.

66. The marker delivery device of claim 65, wherein the flexible portion of the cannula is located closer to the distal end of the cannula than to the proximal end of the cannula.

67. The marker delivery device of claim 65, wherein the plurality of peripheral slots are configured to facilitate the flexure at the flexible portion of the cannula along a single predetermined plane.

68. The marker delivery device of claim 65, wherein the plurality of peripheral slots include a first set of peripheral slots having a first circumferential extent and a second set of peripheral slots having a second circumferential extent.

69. The marker delivery device of claim 68, wherein the first circumferential extent is circumferentially staggered with respect to the second circumferential extent.

70. The marker delivery device of claim 65, wherein the slot arrangement includes an axial slot linking at least a portion of the plurality of peripheral slots.

71. The marker delivery device of claim 65, wherein the cannula is formed from a metallic material, and at least the flexible region of the marker introducer rod is formed as a flexible metallic element.

72. The marker delivery device of claim 71, wherein the cannula is formed from a metallic material, and at least the flexible region of the marker introducer rod is formed as a flexible plastic element.

73. The marker delivery device of claim 56, wherein the retraction mechanism includes a first retraction mechanism configured for retracting the marker introducer rod and a second retraction mechanism configured for retracting the cannula, wherein an initial retraction of the introducer rod occurs before a retraction of the cannula.

74. The marker delivery device of claim 56, wherein the retraction mechanism includes a first retraction mechanism configured for retracting the marker introducer rod and a second retraction mechanism configured for retracting the cannula, wherein a complete retraction of the introducer rod occurs before a retraction of the cannula.

75. The marker delivery device of claim 56, wherein the retraction mechanism includes:
an introducer rod guide block attached to the actuation end of the marker introducer rod, the introducer rod guide block being slidably disposed in the chamber of the housing;
a cannula guide block attached to the proximal end of the cannula, the cannula guide block being slidably disposed in the chamber of the housing;
a first spring engagingly located between the introducer guide block and the cannula guide block; and
a marker deployment trigger accessible at an exterior of the housing, the marker deployment trigger being linked to the introducer rod guide block by a first shear member, wherein an actuation of the marker deployment trigger to a first position causes the first shear member to displace the marker introducer rod to move the marker introducer rod along the lengthwise extent of the cannula to deploy the tissue marker from the lumen of the cannula and to simultaneously compress the first spring, and a further actuation of the marker deployment trigger to a second position different from the first position releases the first spring for decompression to retract the marker introducer rod into the chamber of the housing of the handle.

76. The marker delivery device of claim 75, wherein the decompression of the first spring results in a shearing of the first shear member, and the complete retraction of the marker introducer rod into the chamber of the housing of the handle.

77. The marker delivery device of claim 75, further including: a retraction trigger mounted to the housing, the retraction trigger being coupled to the cannula guide block; and a second spring engagingly located between the front end of the housing and the cannula guide block, the second spring being in a compressed state prior to actuation of the retraction trigger to provide a preload on the cannula guide block, wherein an actuation of the retraction trigger

results in a decompression of the second spring causing a complete retraction of the cannula into the chamber of the housing of the handle.




Fig. 1

2/13




Fig. 2




Fig. 3

4/13




Fig. 4A




Fig. 4B




Fig. 4C

5/13




Fig. 5




Fig. 6




Fig. 7

6/13




Fig. 8

7/13




Fig. 9

8/13





Fig. 10






Fig. 12




Fig. 13




Fig. 14




Fig. 15

