



US008469975B2

(12) **United States Patent**
Nobles et al.

(10) **Patent No.:** **US 8,469,975 B2**
(45) **Date of Patent:** **Jun. 25, 2013**

(54) **METHOD AND APPARATUS FOR APPLYING
A KNOT TO A SUTURE**

(75) Inventors: **Anthony A. Nobles**, Fountain Valley, CA
(US); **Steven E. Decker**, Anaheim, CA
(US); **Egbert Ratering**, Amsterdam
(NL)

(73) Assignee: **Nobles Medical Technologies, Inc.**,
Fountain Valley, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/489,573**

(22) Filed: **Jun. 6, 2012**

(65) **Prior Publication Data**

US 2012/0316582 A1 Dec. 13, 2012

Related U.S. Application Data

(62) Division of application No. 11/455,894, filed on Jun.
19, 2006, now Pat. No. 8,197,497.

(60) Provisional application No. 60/693,582, filed on Jun.
20, 2005, provisional application No. 60/709,485,
filed on Aug. 19, 2005.

(51) **Int. Cl.**
A61B 17/04 (2006.01)

(52) **U.S. Cl.**
USPC **606/144**; 606/139; 606/148

(58) **Field of Classification Search**
USPC 606/72, 75, 139, 144–148, 151, 153,
606/213, 232

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,664,345	A	5/1972	Dabbs et al.
3,665,926	A	5/1972	Flores
3,877,434	A	4/1975	Ferguson et al.
4,291,698	A	9/1981	Fuchs et al.
4,662,068	A	5/1987	Polonsky
4,750,492	A	6/1988	Jacobs
5,021,059	A	6/1991	Kensey et al.
5,100,418	A	3/1992	Yoon et al.

(Continued)

FOREIGN PATENT DOCUMENTS

WO	WO 95/25470	A1	9/1995
WO	WO 98/12970	A1	4/1998
WO	WO 00/02489	A1	1/2000

OTHER PUBLICATIONS

Invitation to Pay Additional Fees, mailed Dec. 6, 2006 in correspond-
ing International Application No. PCT/US2006/023676, 6 pages.



Primary Examiner — Darwin Erez

Assistant Examiner — Mark Mashack

(57) **ABSTRACT**

A knot placement device allows a physician to apply a knot for securing two or more suture ends extending from an incision in a vessel or organ of a patient relative to each other in order to seal an opening in the vessel or organ. The knot placement device has a handle, an elongate shaft, and a push rod slidably inserted in the shaft. A knot is disposed in the distal end of the shaft. An actuator on the handle may be depressed to distally advance the push rod relative to the shaft, thereby distally advancing the knot. The knot may include a knot body having an inner cavity and a plug sized to fit securely within the inner cavity. In use, the plug may be inserted into the inner cavity of the knot body to fixedly hold two or more suture ends between the knot body and the plug.

2 Claims, 20 Drawing Sheets



US 8,469,975 B2

Page 2

U.S. PATENT DOCUMENTS

5,160,339 A	11/1992	Chen et al.	6,716,243 B1	4/2004	Colvin et al.
5,171,251 A	12/1992	Bregen et al.	6,733,509 B2	5/2004	Nobles et al.
5,176,691 A *	1/1993	Pierce 606/148	6,855,157 B2	2/2005	Foerster et al.
5,222,974 A	6/1993	Kensey et al.	7,083,638 B2	8/2006	Foerster
5,242,459 A	9/1993	Buelna	7,090,690 B2	8/2006	Foerster et al.
5,282,827 A	2/1994	Kensey et al.	7,172,595 B1	2/2007	Goble
5,336,231 A	8/1994	Adair	7,220,266 B2	5/2007	Gambale
5,364,407 A	11/1994	Poll	7,235,086 B2 *	6/2007	Sauer et al. 606/139
5,383,905 A	1/1995	Golds et al.	7,326,221 B2	2/2008	Sakamoto et al.
5,423,837 A	6/1995	Mericle et al.	7,399,304 B2	7/2008	Gambale et al.
5,439,470 A	8/1995	Li	7,435,251 B2 *	10/2008	Green 606/232
5,445,167 A	8/1995	Yoon et al.	7,491,217 B1	2/2009	Hendren et al.
5,474,572 A	12/1995	Hayburst	7,628,797 B2 *	12/2009	Tieu et al. 606/148
5,514,159 A	5/1996	Matula et al.	7,637,926 B2	12/2009	Foerster et al.
5,520,702 A	5/1996	Sauer et al.	7,842,051 B2 *	11/2010	Dana et al. 606/148
5,545,170 A	8/1996	Hart	7,846,181 B2 *	12/2010	Schwartz et al. 606/232
5,584,835 A	12/1996	Greenfield	7,879,072 B2 *	2/2011	Bonutti et al. 606/232
5,584,861 A	12/1996	Swain et al.	7,905,892 B2 *	3/2011	Nobles et al. 606/144
5,593,422 A	1/1997	Muijs Van de Moer et al.	7,918,867 B2 *	4/2011	Dana et al. 606/144
5,626,590 A	5/1997	Wilk	7,993,368 B2	8/2011	Gambale et al.
5,645,553 A	7/1997	Kolesa et al.	8,197,497 B2 *	6/2012	Nobles et al. 606/148
5,669,917 A *	9/1997	Sauer et al. 606/139	8,282,659 B2 *	10/2012	Oren et al. 606/148
5,669,971 A	9/1997	Bok et al.	2002/0087178 A1	7/2002	Nobles et al.
5,681,351 A	10/1997	Jamiolkowski et al.	2002/0111653 A1	8/2002	Foerster
5,700,277 A	12/1997	Nash et al.	2002/0128684 A1	9/2002	Foerster
5,860,990 A	1/1999	Nobles et al.	2003/0078601 A1	4/2003	Shikhman et al.
5,899,921 A	5/1999	Caspari et al.	2003/0144673 A1 *	7/2003	Onuki et al. 606/139
5,902,321 A	5/1999	Caspari et al.	2003/0149448 A1	8/2003	Foerster et al.
5,919,208 A	7/1999	Valenti	2003/0167062 A1 *	9/2003	Gambale et al. 606/138
5,931,844 A *	8/1999	Thompson et al. 606/144	2003/0171760 A1	9/2003	Gambale
5,935,149 A	8/1999	Ek	2003/0181926 A1	9/2003	Dana et al.
5,951,590 A	9/1999	Goldfarb	2003/0208209 A1	11/2003	Gambale et al.
6,015,428 A	1/2000	Pagedas	2004/0093031 A1	5/2004	Burkhart et al.
6,033,430 A	3/2000	Bonutti	2004/0097968 A1	5/2004	Shikhman et al.
6,066,160 A	5/2000	Colvin et al.	2004/0098050 A1	5/2004	Foerster et al.
6,077,277 A	6/2000	Mollenauer et al.	2004/0210238 A1	10/2004	Nobles et al.
6,086,608 A	7/2000	Ek et al.	2004/0260298 A1	12/2004	Kaiseer et al.
6,099,553 A	8/2000	Hart et al.	2005/0033319 A1	2/2005	Gambale et al.
6,110,185 A	8/2000	Barra et al.	2005/0240226 A1	10/2005	Foerster et al.
6,117,144 A	9/2000	Nobles et al.	2005/0261708 A1	11/2005	Pasricha et al.
6,126,677 A	10/2000	Ganaja et al.	2005/0261710 A1	11/2005	Sakamoto et al.
6,174,324 B1	1/2001	Egan et al.	2005/0277986 A1	12/2005	Foerster et al.
6,187,026 B1	2/2001	Devlin et al.	2005/0288688 A1	12/2005	Sakamoto et al.
6,200,329 B1	3/2001	Fung et al.	2006/0047314 A1 *	3/2006	Green 606/232
6,203,565 B1	3/2001	Bonutti et al.	2006/0265010 A1 *	11/2006	Paraschac et al. 606/232
6,217,591 B1	4/2001	Egan et al.	2006/0271074 A1	11/2006	Ewers et al.
6,432,115 B1	8/2002	Mollenauer et al.	2007/0005081 A1 *	1/2007	Findlay et al. 606/148
6,547,725 B1	4/2003	Paolitto et al.	2007/0032798 A1	2/2007	Pantages et al.
6,562,052 B2	5/2003	Nobles et al.	2008/0234729 A1	9/2008	Page et al.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9A








FIG. 9B










FIG. 15




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 19




FIG. 20

FIG. 21




FIG. 22





FIG. 23

*FIG. 24*




FIG. 25

METHOD AND APPARATUS FOR APPLYING A KNOT TO A SUTURE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a division of U.S. application Ser. No. 11/455,894, filed on Jun. 19, 2006, now U.S. Pat. No. 8,197,497, which claims the benefit of U.S. Provisional Application No. 60/693,582, filed on Jun. 20, 2005 and U.S. Provisional Application No. 60/709,485, filed on Aug. 19, 2005, the entirety of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

Certain embodiments of the invention relate to suturing incisions and, more specifically, to the use of sutures for closing incisions in vessels or in organs within a body.

2. Description of the Related Art

Surgeons frequently encounter the need to close incisions, wounds, or otherwise joining tissue portions with a suture. After passing the suture through the tissue portions, the surgeon must tie and cinch the suture to draw the tissue portions together and prevent them from separating. When sutures are tied in a region having restricted access, such as the end of a tissue tract leading to an artery, the surgeon is presented with special challenges. Sutures can often be difficult to handle, thereby increasing the time that it takes for a surgeon to tie a suture. Accordingly, what is needed is a faster and more effective way to tie and cinch a suture.

SUMMARY OF THE INVENTION

Certain embodiments of the present invention describe various methods and apparatus for applying a knot to a suture. When two ends of a suture extend away from an incision in a vessel or an organ of a patient, the preferred embodiments provide a method and apparatus for desirably securing two suture portions relative to each other, with the securement being provided adjacent the incision to hold the incision closed. As used herein, the term "knot" is a broad term encompassing its ordinary meaning and includes, but is not limited to, any arrangement, component or combination of components designed to fixedly hold a suture relative to a desired knot location. More preferably, a knot may encompass any arrangement, component or combination of components designed to fixedly hold two portions of a suture relative to a desired knot location. Thus, a knot encompasses arrangements in which suture portions are tied, and also encompasses arrangements in which suture portions are securely held relative to one another without being tied. The desired knot location may include an incision, a wound, a body cavity, an opening in body tissue, and two adjacent body tissues wherein the space between the two adjacent body tissues is desired to be closed. The two suture portions may be portions of the same suture or different sutures.

In one embodiment, a knot placement device is provided. The knot placement device preferably includes a handle and a shaft. The handle comprises a proximal end and a distal end. The shaft comprises a proximal end and a distal end which extends distally from the handle. A knot is disposed, either partially or entirely, within the distal end of the shaft. The handle further comprises an actuator which places the knot about two suture portions to fix the two suture portions relative to one another.

In one embodiment, the actuator may be a thumb or finger button designed for cooperation with a cam. The cam may be fixedly attached to a push rod. The push rod is concentrically and slidably disposed within an outer tube. The outer tube may be fixedly attached to a distal end portion of the handle. The knot placement device may further comprise an intermediate tube concentrically and slidably disposed between the outer tube and the push rod. The intermediate tube comprises a proximal end and a distal end. The proximal end of the intermediate tube may be located between the cam and the distal end portion of the handle. Partial depression of the actuator distally advances the push rod. At some degree of depression, the actuator contacts the proximal end of the intermediate tube, thus distally advancing the intermediate tube.

In one embodiment, the intermediate tube may comprise a key. The outer tube, the end portion, or both may include a keyway designed for cooperation with the key. The key and associated keyway maintain rotational alignment of the intermediate tube relative to the outer tube. In another embodiment, the intermediate tube may comprise a keyway, and the outer tube or the end portion may comprise a key.

In one embodiment, the shaft comprises an outer tube having a proximal end and a distal end. The outer tube may comprise an aperture located near its distal end. The shaft may further comprise an intermediate tube concentrically and slidably disposed within the outer tube. The intermediate tube may comprise a slot located at or near its distal end. A push rod may be concentrically and slidably disposed within the intermediate tube and outer tube. A knot is disposed, either partially or entirely, within the distal end of the outer tube.

In one embodiment, the knot comprises a plug and a knot body, wherein the plug is adapted to be received within the knot body. The plug comprises a proximal end and a distal end, and may be of a generally constant outer diameter. Alternatively, the plug may be generally tapered from the proximal end to the distal end. Alternatively, the plug may comprise a portion of generally constant outer diameter and a generally tapered portion. The plug may also comprise a rounded or chamfered edge at the distal end. The plug may also comprise a shoulder located near the proximal end having an increased outer diameter.

The knot body may be generally tubular and comprise a proximal end, a distal end, and a longitudinal axis. The knot body may be of a generally constant inner diameter and outer diameter. Alternatively, the inner diameter, the outer diameter, or both may generally taper along the longitudinal axis of the knot body. Alternatively, the inner diameter, the outer diameter, or both may generally taper along a portion of the longitudinal axis and may be of a generally constant inner diameter, outer diameter or both over a portion of the longitudinal axis.

The knot body may comprise an opening at its distal end. The opening at the distal end of the knot body may, in some embodiments, be of a reduced diameter. The knot body may also comprise an opening at the proximal end. The opening at the proximal end may, in some embodiments, be of a reduced diameter. The knot body may further comprise protrusions from the inner surface of the knot body toward the longitudinal axis.

In one embodiment, the knot body may be located distally from the plug within the outer tube. In another embodiment, the plug may be located distally from the knot body within the outer tube.

In one embodiment, a method is provided for placing a knot on a suture to close an opening in the body. A pair of suture ends is passed through a threader. The threader is

3

pulled through a passage in the distal end of a shaft of a knot placement device. As the threader is pulled through the passage, the suture portions are drawn through the passage, and desirably positioned within a knot body positioned at a distal end of the shaft. Tension may be applied to the suture portions as the knot placement device is slid along the suture portions toward a pair of tissue portions. The knot placement device is advanced until the knot body or distal end of the device is in contact with a tissue portion. An actuator is depressed, which in one embodiment advances a push rod within the shaft against a plug and advances the plug into the knot body. This traps the suture between the plug and the knot body. In one preferred embodiment, continued depression of the actuator causes an intermediate tube to be advanced to sever the suture portions, eject the knot from the placement device, or both. The device is then retracted from the patient.

In one embodiment, after the knot is ejected and before the suture ends are severed, the push rod is positioned substantially flush with a distal end of the shaft. The distal end of the shaft is used to push the knot toward the tissue portions to further secure the knot and draw the tissue portions closer together.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a wound site having a pair of suture ends extending therefrom.

FIG. 2 is a side view of one embodiment of a knot placement device.

FIG. 3 is a side view of the shaft, cam, and distal end portion of the knot placement device of FIG. 2 with a knot shown within the shaft in phantom.

FIG. 4 is a partial cross-sectional side view of the handle of the knot placement device of FIG. 2.

FIG. 5 is a partial cross-sectional side view of the distal end of the shaft of the knot placement device of FIG. 2.

FIG. 6 is a perspective view of the distal end of the outer tube of the knot placement device of FIG. 2.

FIG. 7 is a perspective view of the distal end of the intermediate tube of the knot placement device of FIG. 2.

FIG. 8 is a side view of the outer tube of FIG. 6.

FIG. 9a is a top view of the intermediate tube of FIG. 7.

FIG. 9b is a side view of the intermediate tube of FIG. 7.

FIG. 10 is a perspective view of one embodiment of a knot.

FIG. 11 is a cross-sectional side view of another embodiment of a knot.

FIG. 12 is a cross-sectional side view of another embodiment of a knot.

FIG. 13 is a perspective view of another embodiment of a knot.

FIG. 14 is a transverse cross-sectional view of the knot of FIG. 13.

FIG. 15 is a cross-sectional side view of another embodiment of a knot.

FIG. 16a is a cross-sectional side view of another embodiment of a knot and illustrating a routing of a suture through the knot body.

FIG. 16b is a cross-sectional side view of the embodiment of the knot of FIG. 16a and illustrating an alternative routing of a suture through the knot body.

FIG. 17a is a perspective view of another embodiment of a knot.

FIG. 17b is a cross-sectional side view of the embodiment of a knot shown in FIG. 17.

FIG. 18a is a cross-sectional side view of another embodiment of a knot.

4

FIG. 18b is a cross-sectional side view of the knot of FIG. 8a.

FIG. 18c is a cross-sectional side view of the knot of FIGS. 18a-18b.

FIG. 19 is a partial cross-sectional view of a knot placement device, with suture ends passing through a threader.

FIG. 20 illustrates the device of FIG. 19 having two suture portions passing therethrough, with the distal end of the device in contact with a tissue portion.

FIG. 21 illustrates the device of FIGS. 19-20 with the push rod being advanced until the plug is inserted into the knot body, trapping the suture portions between the plug and knot body.

FIG. 22 illustrates the device of FIGS. 19-21, the push rod being further advanced, the intermediate tube also being advanced to eject the knot from the device and sever the suture portions.

FIG. 23 illustrates the knot of FIGS. 19-22, in its final placement.

FIGS. 24 and 25 illustrate another embodiment of a knot having an atraumatic tip.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The preferred embodiments of the present invention described below relate particularly to applying a knot to two portions of a suture. More particularly, the preferred embodiments relate to applying a knot to portions of a suture extending from a treatment location of a patient. The treatment location may be any desired location, such as an arterial vessel, a venous vessel, or any other body tissue. Suture ends may be the ends of the same suture or may be the ends of separate sutures.

FIG. 1 illustrates the wound site of a patient wherein it may be desired to apply a knot to a suture. More particularly, FIG. 1 shows an incision 30 in the patient's skin used to perform any sort of treatment on the patient. After the patient has been treated, a suture 34 is introduced into the patient through a catheter sheath introducer (CSI) 44 for the purpose of drawing together tissue portions 36 and 38 (shown in phantom in FIG. 1). Two end portions 40 and 42 of the suture 34 extend from the tissue portions 36, 38, respectively, which may, for example, be the result of a wound or an internal incision in a blood vessel or an organ. The suture 34 may be introduced into the patient by any suitable manner, including those described in U.S. Pat. No. 5,860,990, U.S. Pat. No. 6,117,144, U.S. Pat. No. 6,562,052, and Applicant's application Ser. No. 11/235,751 filed Sep. 27, 2005, now U.S. Publication No. 2006-0069397, all of which are hereby incorporated by reference in their entirety. Suture 34 may be, but is not limited to, 0.007" diameter biodegradable material or non-biodegradable materials, such as polypropylene. The suture 34 may also be braided or may be of other materials and have other configurations. The suture 34 in FIG. 1 is shown extending from a catheter sheath introducer 44. The suture 34 may also extend directly from an incision in a patient.

FIGS. 2-4 illustrate one embodiment of a knot placement device 100 that may be used to apply a knot to the suture 34. The knot placement device 100 comprises a handle 102 and a shaft 104 extending distally from the handle. The handle 102 preferably comprises an elongate tubular body extending from a proximal end to a distal end, and comprises an actuator 106 and a distal end portion 110. The handle 102 may further comprise a cam 108 and a spring 112, shown in its rest position, disposed between the cam 108 and end portion 110. The actuator 106 may be a thumb or finger button in contact

5

with the cam 108. End portion 110 may be fixedly attached to an outer tube 114 by glue, press fit, injection molding, or other suitable means known to one of ordinary skill in the art. An intermediate tube 116 may be concentrically and slidably disposed within the outer tube 114. A push rod 118 is concentrically and slidably disposed within the intermediate tube 116 and fixedly attached to the cam 108. It should be appreciated that it is contemplated that the knot placement device 100 does not necessarily comprise an intermediate tube 116; however its inclusion provides certain benefits.

As shown in FIG. 4, depression of the actuator 106 causes the cam 108 to move distally, compressing the spring 112 (not shown), thereby moving the push rod 108. After traveling for a certain desired distance, the cam 108 engages a proximal end of the intermediate tube 116, causing the intermediate tube 116 to also move distally. Upon release of the actuator 106, the spring 112 expands to move the cam 108 and the push rod 118 proximally. In the illustrated embodiment, the intermediate tube 116 is freely slidable over the push rod 118.

In one embodiment, not shown, the cam 108 comprises a detent in the surface which contacts the actuator 106. The detent may signal to the user a specific degree of advancement of the push rod 118, the intermediate tube 116, or both. For example, the detent may signal that the push rod has been advanced sufficiently far to insert the plug into the knot body, as described below. The detent may also indicate travel up until, but not including, the point at which the cam 108 engages the intermediate tube 116. The detent may be shaped so as to prevent the actuator 106 from returning to its original position. The cam may comprise multiple detents to indicate multiple increments of travel. To return the actuator to its initial position, the actuator and cam may include a mechanism such that after the actuator is fully depressed, the actuator may automatically return to its initial position. Alternatively, the actuator may have a locked configuration, either at one of the detents or in a fully depressed configuration, and the handle may include a mechanism by which a second actuator is used to release the cam and actuator to return to their initial positions. Further details of such mechanisms are found in application Ser. No. 11/235,751 filed Sep. 27, 2005, the entirety of which is hereby incorporated by reference.

In one embodiment, not shown, the intermediate tube 116 may comprise a keyway and the outer tube 114, the end portion 110, or both may comprise a key. Alternatively, the intermediate tube 116 may comprise a key and the outer tube 114, the end portion 110, or both may comprise a keyway. Providing such a key and keyway may be used to keep the intermediate tube 116 aligned with the outer tube. Other embodiments are contemplated to maintain rotational alignment of the intermediate tube, such as rotationally fixing the intermediate tube relative to the push rod. Providing such a key and keyway may also be used to constrain the range of sliding movement of the intermediate tube 116.

As shown in FIG. 5, a knot, comprising a knot body 124 and a plug 126, is disposed within the outer tube 114 at its distal end. The knot body 124 may be retained in the outer tube 114 by a net fit or press fit. Alternatively, the fit between the knot body 124 and the outer tube 114 may not retain the knot body 124 in the outer tube 114. The knot body 124 is preferably at the distal end of the outer tube 114, and may protrude slightly distal to the distal end of outer tube 114. The plug 126 is positioned proximal to the knot body 124, and may be slidably disposed within the intermediate tube 116, having a distal end located proximally from the knot body and distally from the push rod 118. The plug 126 has an outer dimension configured to be inserted into an inner cavity of the

6

knot body 124. The intermediate tube 116 is preferably sized and positioned such that its distal end may abut knot body 124.

As shown in FIGS. 5, 6 and 8, the outer tube 114 may include a side hole 120 near its distal end. As shown in FIGS. 5, 7, 9a and 9b, the intermediate tube 116 may include a slot 122 extending proximally from its distal end, forming a C-shaped cross section. At a proximal end of the slot 122, a sharpened cutting surface 123 may be provided to cut suture 34, as described below. The slot 122 is preferably rotationally aligned with the opening 120, such as by using a key/keyway arrangement as described above. The slot 122 is also preferably axially aligned with the opening 120, although it will be appreciated that because of the ability of the intermediate tube 116 to slide relative to push rod 118, the intermediate tube may be positioned with the slot 122 proximal to the opening 120 and its distal end proximal to the plug 126. The slot 122 may also be spaced from the distal end of the intermediate tube, such that the distal end of the tube still forms a complete circle in cross-section. The outer tube 114, intermediate tube 116 and push rod 118 may be made of any suitable material, including but not limited to metals, plastics, and a combination of metals and plastics.

As shown in FIG. 5, in a preloaded configuration, the knot placement device 100 may include a threader 128 comprising a tab 132 and a looped wire 130 passing through the side hole 120 in the outer tube 114. The wire 130 preferably extends through the slot 122 located in the intermediate tube 116, and through knot body 124, exiting through opening 136 at the distal end of the knot body 124. The threader 128 is used to load the suture into the knot placement device as described below. The threader 128 also prevents the knot body 124 from escaping from the placement device 100 when the knot body is provided with an outer dimension of the same or smaller size than the inner wall of the outer tube 114.

With reference to FIGS. 5 and 10, the knot body 124 may be generally tubular and comprise a proximal end, a distal end, and a longitudinal axis. The knot body 124 preferably further defines an inner cavity and comprises an opening 136 at its distal end. The knot body may be of a generally constant inner diameter and outer diameter. Alternatively, the inner diameter, the outer diameter, or both may generally taper along the longitudinal axis of the knot body. Alternatively, the inner diameter, the outer diameter, or both may generally taper along a portion of the longitudinal axis and may be of a generally constant inner diameter, outer diameter or both over a portion of the longitudinal axis.

The opening 136 at the distal end of the knot body may, in some embodiments, be of a reduced diameter relative to an inner cavity of the knot body 124. The knot body also comprises an opening 138 at the proximal end. The opening 138 at the proximal end may, in some embodiments, be of a reduced diameter relative to an inner cavity of the knot body 124. The knot body may further comprise protrusions 134 extending from the inner surface of the knot body 124 toward the longitudinal axis. Protrusions 134 may be formed as rings as illustrated, or as spirals, spikes, bumps, or other suitable structures or combinations of structures.

Referring to FIGS. 5 and 10, in one embodiment, the knot body 124 may be located distally from the plug 126 within the outer tube 114. The plug is preferably sized to be inserted into the inner cavity of the knot body 124, and may have a tapered configuration as shown in FIG. 10. Alternatively, the plug 126 may have a constant cross-section over a majority of its length, such as shown in FIG. 5, with a tapered, chamfered or rounded distal end for facilitating insertion into the knot body 124. The outer dimension of the plug 126 may be slightly

larger than the inner dimension of the cavity of the knot body **124**, such that when the plug is inserted into the cavity, a relatively secure fit is provided between the two. The protrusions **134** within the knot body further facilitate the relative securement. The plug **126** may also comprise indentations, not shown, for receiving the protrusions **134** to secure the plug **126** more surely in the knot body **124**. Other embodiments are contemplated wherein protrusions are formed on the plug **126** with or without indentations formed in the inner cavity of the knot body **124**. It is also contemplated that in some embodiments both the plug **126** and the knot body **124** may comprise protrusions and indentations, respectively. In certain embodiments, insertion of the plug **126** into the knot body **124** may cause the knot body **124** to slightly expand. Both the knot and the knot body may be formed of any suitable resilient materials, and in one embodiment, are made from the same material as the suture, more preferably polypropylene.

FIGS. **19-23** illustrate one embodiment for placing a knot utilizing the knot placement device **100** described above. With reference to FIG. **19**, a pair of sutures ends **40** and **42** may be passed through the loop **130** of threader **128**. The threader is preloaded into the knot placement device **100** as described above. The tab **132** of threader **128** may be pulled proximally to dispose suture **34** in the device, as shown in FIG. **20**. Suture **34** may be held in tension, by hand or otherwise, while the device **100** is advanced until the knot body **124** or shaft **104** contacts at least one of tissue portions **36** and **38**, as illustrated in FIG. **20**. The actuator **106** may be depressed to advance the push rod **118**, thereby forcing the plug **126** distally into the knot body **124** and trapping suture **34** there between the plug **126** and the knot body **124**, as shown in FIG. **21**. The actuator may be further depressed until the cam **108** contacts the proximal end of intermediate tube **116**, causing the intermediate tube **116** to contact knot body **124** and eject the knot from the shaft **104**. As shown in FIG. **22**, advancement of intermediate tube **116** may also cause cutting surface **123** to sever suture **34** where it extends out of opening **120**. The knot placement device may then be removed, leaving the knot in place against the tissue portions, as shown in FIG. **23**.

In one embodiment, the knot may be ejected from the shaft **104** while leaving the sutures **34** un-severed. For example, the knot may be ejected before the cutting surface **123** reaches the suture **34**. In another embodiment, no intermediate tube is provided, and the suture may be cut manually.

In an embodiment including the intermediate tube, the device **100** may be configured such that the distal ends of the outer tube **114**, intermediate tube **116**, and the push rod **118** lie generally flush relative to one another and are held relatively in position. This position may be held, for example, by depressing the actuator until it rests in a detent in cam **108**. The detent may signal to the user that the plug **126** has been inserted into knot body **124**, but also that the sutures **34** have not been cut. At such time, the placement device may be used to further advance the knot against tissue portions **36** and **38** using the distal end surface of the shaft. The actuator may be further depressed to advance the push rod **118** and intermediate tube **116** to sever sutures **34**.

The actuator **106** and cam **108** may also be provided with locking mechanisms that prevent the actuator **106** from returning to its original position. Further details are provided in application Ser. No. 11/235,751 filed Sep. 27, 2005, the entirety of which is hereby incorporated by reference. Such an embodiment may be advantageous to hold the push rod flush with the distal end of the outer tube to provide a surface

that can be utilized to further advance and position the knot against tissue portions **36** and **38**.

It will be appreciated that other embodiments are contemplated without use of the intermediate tube, but are still capable of severing the suture. For example, the push rod may be provided with portions of differing diameter. A distal, smaller diameter may be sized to engage the plug **126** to push the plug into the knot body **124**. A proximal, larger diameter may be provided on the push rod, which includes a sharpened surface at the transition between the larger and smaller diameter sections. Once the smaller portion of the push rod pushes the plug **126** into the knot body **124**, the larger portion of the push rod may engage the knot body **124** to push the knot out of the placement device, while the sharpened surface on the push rod may sever the suture.

In the embodiment described above, when the knot body **124** and the plug **126** as described above are secured together, suture portions extending through the inner cavity of the knot body from opening **136** to opening **138** will be fixedly secured therein, forming a knot. It will be appreciated that many other embodiments are possible for forming a knot, including various other shapes and configurations for the knot body and plug, as well as embodiments wherein only one component may be used to provide securement relative to a suture. It will also be appreciated that in those embodiments in which the knot comprises a knot body and plug, the plug may be located within the shaft proximally from the knot body or the knot body may be located within the shaft proximally from the plug.

For example, in another embodiment of a knot, shown in FIG. **11**, a plug **146** is provided having a pair of holes **148** extending divergently from one end of the plug (e.g., a proximal end) to the diametrically opposed, outer surfaces of the plug. A shoulder **149** of increased outer diameter may be located at one end of plug **146** (e.g., the proximal end). When the plug **146** is inserted into a hollow knot body, the plug **146** and knot body **144** cooperate to secure the suture **34** therebetween.

In another embodiment, shown in FIG. **12**, a plug **156** may comprise two sections having different outer diameters. A knot body **154** has an opening **136** with an inner surface **160**. A surface **162** of plug **156** may have a smaller diameter than an interior surface **164** of knot body **154**. A surface **158** of plug **156** may have a diameter such that surface **158** engages surface **160** of knot body **154** and cooperate to hold suture portions securely therein.

In another embodiment, shown in FIGS. **13** and **14**, a plug **176** comprises a longitudinally-extending slot **178** such that plug **176** is generally fork-shaped. The slot **178** extends from the distal end partially to the proximal end. Suture **34** extends through the knot body **174**, through the slot **178**, and out from the plug **176**, preferably on opposite sides of the plug **176**. Insertion of the plug **176** into knot body **174** preferably causes compression of the slot to securely fix the suture portions within the slot. It will be appreciated that in this embodiment, the knot placement device can either be actuated to move the plug distally into the knot body, or alternatively, may be actuated to move the knot body distally over the plug.

In another embodiment, shown in FIG. **15**, a pair of side holes **188** are provided at spaced locations along the length of a plug **186**. Suture portions pass from an end hole at one end of the plug **186**, outwardly through one of the side holes, and then inwardly back into the body of the plug and out an opposite end hole. When the knot body **184** is slid over the plug, either by being advanced distally over the plug or by

having the plug advanced distally into the knot body, the suture **34** is secured relatively between the plug and the knot body.

In another embodiment, shown in FIGS. **16a** and **16b**, a knot body **194** comprises two side holes **198**. Suture **34** may be routed through knot body **194** either from within the body, out through one of the side holes, and back into the body through the other side hole, as shown in FIG. **16a**, or may be routed into one of the side holes from outside the body, into the body, and then out the other side hole, as shown in FIG. **16b**. In either embodiment, a plug **196** may then be used to secure the suture relative to the knot body.

In another embodiment, shown in FIGS. **17a** and **17b**, a knot **200** comprises a single component or knot body. A plate, ring or other structure, such as a flat resilient member, may be provided with two holes **202**. As shown in FIG. **17b**, the plate is bent to form a "U" shape, to allow the suture **34** to be passed therethrough. The plate may be made of an elastic or shape memory material which springs back to its flattened configuration, shown in FIG. **17a**, which locks the suture in place relative to the plate. Other embodiments are also contemplated in which suture portions are provided through a tortuous path of a knot body. A threader as described above may be used to guide the suture portions through the knot body while it is positioned within a knot placement device. Once ejected from the knot placement device, the knot body may assume a different configuration which locks the suture in place relative to the knot body.

In another embodiment, shown in FIGS. **18a**, **18b**, and **18c**, a knot **204** comprises a tube having an upper wall **206** and a lower wall **208**. The upper wall comprises three linearly-spaced apertures **210**. The lower wall comprises two apertures **212** to create a displaceable section **214** in the lower wall **208**. The displaceable section **208** is displaced toward the center of the knot **204** by any suitable means, such as a curved rod **216** as illustrated in FIG. **18b**. A suture **34** is threaded in and out of the apertures **210** in the upper wall and around the displaceable section **214** of the lower wall. As the knot **204** is ejected from the knot placement device, the displaceable section **214** is allowed to move toward its original position to more surely secure the suture **34** within the knot **204** as illustrated in FIG. **18c**.

In another embodiment, shown in FIGS. **24** and **25**, a knot comprises a knot body **124** and a plug **126** such as described above, but with the knot body having an atraumatic tip **300**. The tip **300** may be rounded and have an outer diameter about the same as that of the outer tube **114**. As shown more particularly in FIG. **25**, the tip may have a flat transition **302** as well. The tip **300** may be integrally formed with the knot body **124** or may be separately attached. As illustrated, the tip **300** may have an aperture **304** extending axially through the tip, opening to the cavity inside the knot body. When the knot is delivered into a patient as described above, the atraumatic tip prevents damage to the patient.

Various other embodiments are contemplated for the knot. For example, a knot may simply comprise a tube with a sufficiently small inner diameter through which suture portions may be positioned and held. In another embodiment not shown, the plug may comprise a shoulder located near its proximal end having an increased outer diameter. The shoulder may not be inserted into the knot body, but may be used to push the knot out of the placement device once the plug has been inserted into the knot body.

It should be understood that certain variations and modifications of this invention will suggest themselves to one of ordinary skill in the art. The scope of the present invention is not to be limited by the illustrations or the foregoing descriptions thereof.

What is claimed is:

1. A knot placement device comprising:

a handle;

an elongate shaft with proximal and distal ends and a lumen extending therethrough, the proximal end of said shaft coupled to said handle, the elongate shaft further comprising a side hole near its distal end;

an intermediate tube, having proximal and distal ends and a lumen extending therethrough, slidably disposed in the lumen of said elongate shaft, the proximal end of said intermediate tube extending through the proximal end of said elongate shaft into said handle, the intermediate tube further comprising a cutting surface;

a push rod having proximal and distal ends slidably disposed in the lumen of said intermediate tube, the proximal end of said push rod extending through the proximal end of said intermediate tube into said handle;

an actuator located on said handle, said actuator configured to distally advance said push rod and said intermediate tube relative to said elongate shaft; and

a knot comprising a knot body and a plug positioned in the lumen of the elongate shaft at the distal end thereof;

wherein at least one of the knot body and the plug is configured to receive at least one suture portion extending into the lumen of the elongate shaft at the distal end, the at least one suture portion exiting the shaft through the side hole;

wherein distal advancement of the push rod moves the plug relatively into the knot body to secure the at least one suture portion, and further distal advancement of the push rod causes the cutting surface of the intermediate tube to sever the at least one suture portion and eject the knot from the lumen of the shaft.

2. The knot placement device of claim 1, wherein the plug is positioned proximally of the knot body within the lumen of the shaft, such that distal advancement of the push rod pushes the plug into the knot body.

* * * * *