

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
26 June 2008 (26.06.2008)

PCT

(10) International Publication Number  
WO 2008/076525 A1

## (51) International Patent Classification:

B05B 7/02 (2006.01)

## (21) International Application Number:

PCT/US2007/082768

## (22) International Filing Date: 29 October 2007 (29.10.2007)

## (25) Filing Language:

English

## (26) Publication Language:

English

## (30) Priority Data:

11/640,569 18 December 2006 (18.12.2006) US

(71) Applicant (for all designated States except US): ILLINOIS TOOL WORKS INC. [US/US]; 3600 West Lake Avenue, Glenview, IL 60026 (US).

## (72) Inventor; and

(75) Inventor/Applicant (for US only): BURNS, Marvin, D. [US/US]; 3600 West Lake Avenue, Glenview, IL 60026 (US).


(74) Agent: HAUPTMAN, Benjamin, J.; Lowe Hauptman Ham &amp; Berner, LLP, 1700 Diagonal Road, Suite 300, Alexandria, VA 22314 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

## (54) Title: FLUID APPLICATOR COLOR IDENTIFICATION



(57) Abstract: A fluid applicator. The fluid applicator includes a body having a nozzle (20) and trigger (40) and optionally at least one part connected to the body, the body having a groove (60) therein; and a removable color-coded identification clip (65) made of a flexible material positioned in the groove (60) in the body. The invention also involves a method of identifying a fluid applicator.



**Published:**

— *with international search report*

## FLUID APPLICATOR COLOR IDENTIFICATION

### BACKGROUND OF THE INVENTION

5 The present invention is directed generally to a fluid applicator, and more particularly to a fluid applicator having an identification system.

Many spray painting businesses employ more than one painter. This results in more than one spray gun being used. Even when there is only one painter, there may be more than one spray gun because painters often use one spray gun for the 10 base coat and another for the clear coat. In these situations, it can be desirable to identify a particular spray gun as belonging to a particular individual or to a particular product.

One method of identifying spray guns involves permanently engraving the spray gun with a person's initials. However, if the person changes jobs or leaves 15 the company, the initials cannot be changed. Another set of initials would have to be added. The limited space on the spray gun for engraving could make it difficult to identify the current user. In addition, a special tool must be used for engraving.

Another method involves a plastic ring which is permanently attached at the factory to the connection between the nozzle and the gun body. If a customer 20 receives two guns having the same color ring, there is no way to distinguish between the guns because the ring is permanently attached.

Another method involves attaching a colored molded plastic pad to the bottom of the spray gun using a screw. A package with a variety of colors is provided. However, attaching or changing the plastic pad requires the use of a tool.

25 Therefore, there remains a need for a simple, easy to use, identification system for fluid applicators.

## SUMMARY OF THE INVENTION

The present invention meets this need by providing an identification clip which can be attached to the fluid applicator without the use of a tool. The fluid applicator includes a body having a nozzle and trigger and optionally at least one

- 5 part connected to the body, the body having a groove therein; and a removable color-coded identification clip made of a flexible material positioned in the groove in the body. By "removable," we mean removable without the use of a tool.

Another aspect of the invention is a fluid applicator including a body having a nozzle, a trigger, and optionally at least one part connected to the body; and a

- 10 removable color-coded identification clip made of a flexible material, the identification clip being snapped onto the body.

Another aspect of the invention is a method of identifying a fluid applicator. The method includes providing a fluid applicator having a groove therein; selecting a removable color-coded identification clip made of a flexible material; and

- 15 inserting the identification clip in the groove in the fluid applicator.

## BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is side elevation view of a gravity-feed paint sprayer with the identification clip of the present invention.

- 20 Fig. 2 is a top plan view of the identification clip according to the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

A fluid applicator with a fluid supply assembly attached is shown in Fig. 1.

- 25 In one embodiment, the fluid applicator can be a paint sprayer. The present invention will be described for a paint sprayer, such as a gravity feed or suction feed paint sprayer for use in applying paint to coat substrate surfaces. The paint sprayer can be used in the automotive refinishing market, such as automobile body shops,

for repainting automobiles. Although the fluid supply assembly is described for a paint sprayer, it is not limited to such use. It can be used for supplying other flowable liquids, including, but not limited to, beverages, foods, condiments (such as ketchup), gasoline, petrochemicals and hydrocarbons, water, water-based 5 solutions, solvent-based solutions, emulsions, adhesives, and the like.

Referring to Fig. 1, a paint sprayer 10 is shown. It includes a body 15, a nozzle assembly 20 secured to a front end 25 of body 15, and a handle 30 depending from a rear end 35 of body 15. A trigger 40 is pivotally secured to body 15 for the manual actuation of sprayer 10. A top-mounted paint supply assembly 45 10 is mounted to body 15 near front end 25 for feeding paint to nozzle assembly 20. An air inlet fitting 50 is connected to an air hose (not shown) for the delivery of pressurized air to nozzle assembly 20, wherein the delivery of pressurized air is controlled by trigger 40. There can be one or more parts, including, but not limited to, the knob for the fan control valve 70, and the adjusting knob 75, connected to 15 the body. Fan control valve 70 controls the size of the spray pattern. Adjusting knob 75 controls how far the fluid needle opens, which controls how much fluid is sprayed. The parts can be connected to the body in any suitable way, including but not limited to, using threaded connections.

Compressed air from air inlet fitting 50 is delivered through an internal 20 passage (not shown) to nozzle assembly 20 and the compressed air acts to atomize paint and deliver it through nozzle assembly 20 to spray paint about paint axis 55. Paint is delivered to nozzle assembly 20 from paint supply assembly 45.

The air inlet fitting 50 includes a groove 60. The identification clip 65 is placed in the groove 60. The identification clip 65 can be made of a flexible 25 material. Suitable flexible materials include, but are not limited, to plastic, and rubber. The plastic can be any suitable plastic, including, but not limited to, acetal, polyethylene, nylon, and the like.

The shape of the identification clip will depend on where it is to be attached. The identification clip can be slipped over various parts of the spray gun. The 30 identification clip could be a continuous ring (or other continuous shape).

Alternatively, the ring could be split or have a space between the ends to allow it to be placed around a part more easily. One embodiment of the identification clip is shown in Fig. 2. A C-shaped identification clip is suitable for many locations and is easy to make. The space between the ends allows the identification clip 65 to flex 5 so that it can be inserted and removed from the groove easily. Other locations for the groove, such as on a hex head, would call for a different shape for the identification clip. Suitable shapes include, but are not limited to, square, hexagonal, and circular.

Alternatively, the groove can be located elsewhere on the spray gun, 10 including, but not limited to, on any round part or any hexagonal shaped part. Examples include, but not limited to, the trigger, the handle, the nozzle, the body bushing, the air valve, and hexagonal heads on parts which are threaded into the body. The groove should be wide enough so that the identification clip can be easily placed in the groove. The groove is typically in the range of about 0.5 to 15 about 5 mm, although it could be narrower or wider if desired.

The identification clip could also be positioned on various parts of the spray gun without being placed in a groove. In this arrangement, the identification clip would be around a portion of the fan control valve, for example. The head of the fan control valve could retain the identification clip. In some arrangements (for 20 example, where the identification clip is placed on the head of the fan control valve or on the trigger), the identification clip may be more likely to be removed inadvertently than when the groove is used because there is no groove or other means of retaining the identification clip.

Alternatively, the identification clip can be in the shape of a cap that fits 25 over the end of a part. The cap could include a snap fitting on the inside that will prevent the cap from being removed inadvertently. The snap fitting could be retained by the groove. Alternatively, the snap fitting could be retained by the part itself (without the necessity of a groove). For example, if the cap was placed over the back of the fan control valve 70 or adjusting knob 75, the snap fitting could be 30 retained by the edge of the head.

The identification clip 65 can be made in a variety of colors so that a particular color can be associated with a particular user and/or with a particular use for the spray gun, such as for the base coat and the clear coat. One or more identification clips can be used to identify a particular spray gun. For example, one 5 user may have a blue identification clip, while another user has red identification clip, and a third user has a green identification clip. If desired, a second identification clip can be used to identify the type of gun, for example, base coat guns and clear coat guns. For example in this situation, the base coat gun for the first user would have a blue ring (user) and a black ring (use), while the clear coat 10 gun would have a blue ring (user) and a white ring (use).

The identification clip should be wide enough that so that it can be easily seen by the user. The identification clip is typically in the range of about 0.5 and about 5.0 mm, although it could be narrower or wider if desired. If the identification clip has a space between the ends (for example, a C-shaped 15 identification clip), the space should be large enough that it can be placed around the air inlet fitting, but not so large that it could fall off or be removed inadvertently. Alternatively, it could have a slit (without any space) so that it can be slipped around the part.

While certain representative embodiments and details have been shown for 20 purposes of illustrating the invention, it will be apparent to those skilled in the art that various changes in the compositions and methods disclosed herein may be made without departing from the scope of the invention, which is defined in the appended claims.

What is claimed is:

1. A fluid applicator comprising:  
a body having a nozzle and trigger and optionally at least one part connected to the body, the body having a groove therein; and  
a removable color-coded identification clip made of a flexible material positioned in the groove in the body.
2. The fluid applicator of claim 1 wherein the flexible material is selected from plastic, rubber, or combinations thereof.
3. The fluid applicator of claim 2 wherein the plastic is selected from acetal, polyethylene, nylon, or combinations thereof.
4. The fluid applicator of claim 1 wherein the part connected to the body comprises an air inlet fitting, and wherein the groove is located on the air inlet fitting.
5. The fluid applicator of claim 1 wherein the groove is located on a part selected from the trigger, a handle, the nozzle, a body bushing, or an air valve, or combinations thereof.
6. The fluid applicator of claim 1 wherein there are at least two identification clips positioned in the groove.
7. The fluid applicator of claim 1 wherein the identification clip has a shape selected from C-shaped, square, hexagonal, or circular.
8. The fluid applicator of claim 1 wherein the identification clip has a continuous shape.

9. A method of identifying a fluid applicator comprising:  
providing a fluid applicator having a groove therein,  
selecting a removable color-coded identification clip made of a flexible  
material; and  
inserting the identification clip in the groove in the fluid applicator.
10. The method of claim 9 wherein the flexible material is selected from plastic,  
rubber, or combinations thereof.
11. The method of claim 10 wherein the plastic is selected from acetal,  
polyethylene, nylon, or combinations thereof.
12. The method of claim 9 wherein the groove is located on an air inlet fitting, a  
trigger, a handle, a nozzle, a body bushing, or an air valve, or combinations thereof.
13. The method of claim 9 wherein the identification clip has a shape selected  
from C-shaped, square, hexagonal, or circular.
14. The method of claim 9 wherein the identification clip has a continuous  
shape.
15. The method of claim 9 wherein providing a fluid applicator having a groove  
therein comprises providing a fluid applicator and machining a groove in the fluid  
applicator.

1 / 2




FIG. 1

2 / 2




FIG. 2

# INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2007/082768

**A. CLASSIFICATION OF SUBJECT MATTER**  
INV. B05B7/02

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
B05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 232 797 A (ITW LTD [GB]) 21 August 2002 (2002-08-21) the whole document	1,9
A	US 4 545 534 A (SCHAEFER GERALD O [US]) 8 October 1985 (1985-10-08) the whole document	1,9
A	US 3 318 627 A (DE LONG ALLEN R) 9 May 1967 (1967-05-09) the whole document	1,9
A	EP 0 419 731 A (SCHLEICHER & SCHUELL GMBH [DE]) 3 April 1991 (1991-04-03) the whole document	1,9

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

28 February 2008

06/03/2008

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Eberwein, Michael

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No

PCT/US2007/082768

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
EP 1232797	A 21-08-2002	AU	760937 B2		22-05-2003
		AU	1564602 A		22-08-2002
		CN	1376541 A		30-10-2002
		GB	2372226 A		21-08-2002
		JP	2002273288 A		24-09-2002
		US	2002176944 A1		28-11-2002
US 4545534	A 08-10-1985	NONE			
US 3318627	A 09-05-1967	NONE			
EP 0419731	A 03-04-1991	DE	58906719 D1		24-02-1994
		JP	3118807 A		21-05-1991
		US	5108709 A		28-04-1992