



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
29.02.2012 Bulletin 2012/09

(51) Int Cl.:
G02F 1/35 (2006.01)

(21) Application number: **11188832.7**

(22) Date of filing: **12.02.2003**

(84) Designated Contracting States:
DE FR GB

(30) Priority: **13.02.2002 JP 2002035957**
23.01.2003 JP 2003014328

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
03003046.4 / 1 336 895

(71) Applicant: **Canon Kabushiki Kaisha**
Tokyo 146-8501 (JP)

(72) Inventors:
• **FURUKAWA, Yukio**
Tokyo, Tokyo 146-8501 (JP)
• **SAKATA, Hajime**
Tokyo, Tokyo 146-8501 (JP)

(74) Representative: **TBK**
Bavariaring 4-6
80336 München (DE)

Remarks:


This application was filed on 11.11.2011 as a divisional application to the application mentioned under INID code 62.

(54) **Optical wavelength converting apparatus and optical wavelength converting method**

(57) There is provided an optical wavelength converting apparatus comprising a first and second light sources (11,19) and a nonlinear optical material (29) so that beams (17,25) from the two light sources are allowed to be incident on the nonlinear optical material to generate sum frequency light (35) of these beams, wherein the nonlinear optical material is provided with a periodic structure (31) that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of the beams from

the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of parameters defining the efficiency of conversion into sum frequency light, whereby an inexpensive LD having poor wavelength stability can be used as a pumping light source, and is suitable for size reduction, and enables high-speed modulation.

FIG. 1



Description

BACKGROUND OF THE INVENTION

5 Field of the Invention

[0001] The present invention relates to an optical wavelength converting apparatus and an optical wavelength converting method that carries out wavelength conversion by subjecting two beams from different light sources such as different semiconductor lasers (Laser Diodes: LDs) to sum frequency generation. More specifically, the present invention relates to an optical wavelength converting apparatus which can be utilized as a light source for laser display, optical recording, or optical measurement, which can be driven for high-speed modulation, and which can emit green laser light.

Related Background Art

[0002] Many attempts have been made to use nonlinear optical material to convert LD light so as to have a different wavelength. This technique provides a light source that generates laser light with a wavelength region with which no LDs have been successfully put to practical use, for example, a green or ultraviolet region. This light source is expected to be used for laser display or optical recording.

[0003] A combination of a diode pumped solid state laser (DPSS laser) and nonlinear optical material is a known method of generating green laser light using nonlinear optical material. With this method, a laser crystal such as Nd:YAG is pumped using LD light of wavelength 808 nm to oscillate laser light of wavelength 1,064 nm (DPSS laser). Then, nonlinear optical material such as KTP (KTiOPO₄) is irradiated with this light to generate a second-harmonic to emit laser light of wavelength 532 nm.

[0004] It is contemplated that nonlinear optical material may be directly irradiated with LD light of wavelength about 1,060 nm to generate a second-harmonic (530 nm). In this case, output light can be modulated by directly modulating the LD. As a result, high-speed modulation can be accomplished.

[0005] On the other hand, with a so-called sum frequency generating method, two LD -beams of wavelengths λ_1 and λ_2 are allowed to be incident on nonlinear optical material to generate light with a wavelength λ_3 having a frequency equal to the sum of the two frequencies. This method is described in Japanese Patent Application Laid-Open No. 6-175180, for example. FIG. 15 shows an optical system used for this method. In the figures, reference numerals 401, 402, and 417 denote a modulation signal, a signaling LD, and an pumping LD, respectively. Two

[0006] LD beams are incident, via an optical fiber 403 and a dichroic mirror 418, on nonlinear optical element 414 provided with a periodically poled layer 420. The two LD beams are converted into sum frequency light by the nonlinear optical element 414, and this light is emitted.. Further, reference numerals 412, 413, 415, and 416 denote an optical parametric sum frequency converting device, a light receiving device, and a LiTaO₃ substrate, and an optical waveguide respectively. Reference numerals 419, 421, and 422 denote a lens, emitting section of the optical waveguide (from which sum frequency light P3 is output), and a filter (that absorbs pumping light P2 that has not been converted) respectively. Reference character P1 denotes signal light.

[0007] However, with this type of method using an DPSS laser, the fluorescence lifetime of YAG is about 0.23 ms. Accordingly, modulation is limited to several kHz, and this method is unsuitable for high-speed modulation. Consequently, an external modulator is required for modulation, thus limiting the reduction of size of the apparatus and increasing power consumption.

[0008] Further, with the method of generating a second-harmonic using LD light of wavelength 1,060 nm, the efficiency of conversion into a second-harmonic is sensitive to the wavelength of LD light and also depends on input power. Accordingly, the LD light source must provide high power and high wavelength stability (1 nm or less). Furthermore, to modulate light so as to obtain output light with high power, a modulation current with a large amplitude must be injected into the LD light source. This requires a laser driver compatible with a large current, thus increasing costs.

[0009] Moreover, also with the sum frequency generating method, the efficiency of conversion into sum frequency light is sensitive to the wavelength of LD light. Consequently, the two LD light sources must provide high wavelength stability (1 nm or less). Furthermore, the exciting LD must provide high power.

[0010] Accordingly, with the second-harmonic generating method or the sum frequency generating method, to allow the LD light source to provide high power and high wavelength stability, it is necessary to have a DFB (Distributed Feedback), DBR (Distributed Bragg Reflector), or other laser which is grated and which has a special device configuration that enables the injection of a large current. This increases laser production costs.

[0011] Further, in general, with the second-harmonic generating method or the sum frequency generating method, the conversion efficiency is sensitive to the temperature of the nonlinear optical material. Thus, a variation in the temperature of the nonlinear optical material must be limited to several °C or less. This requires special means such as a temperature control device, thus limiting the reduction of size of the apparatus and increasing costs and power con-

sumption.

SUMMARY OF THE INVENTION

[0012] It is thus an object of the present invention to provide an optical wavelength converting apparatus having a configuration which allows an inexpensive LD having poor wavelength stability to be used as an pumping light source, which is suitable for size reduction, and which enables high-speed modulation to be carried out easily.

[0013] To accomplish this object, the present invention provides an optical wavelength converting apparatus comprising a first and second light sources (typically a first and second semiconductor lasers that can emit coherent light waves with high energy densities) and nonlinear optical material so that beams from the two light sources are allowed to be incident on the nonlinear optical material to generate sum frequency light of these beams; wherein the nonlinear optical material is provided with a periodic structure (a periodically poled structure, a periodic refractive index modulating structure, or the like) that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of a plurality of parameters (of these parameters, the wavelength of one of the light sources and the temperature (T) of the nonlinear optical material are important) defining the efficiency of conversion into sum frequency light.

[0014] Further, to accomplish the above object, the present invention provides a an optical wavelength converting method of using a first and second light sources and nonlinear optical material to allow beams from the two light sources to be incident on the nonlinear optical material to generate sum frequency light of these beams, wherein the nonlinear optical material is provided with a periodic structure that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of a plurality of parameters defining the efficiency of conversion into sum frequency light.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015]

FIG. 1 is a schematic diagram of a configuration of an optical wavelength converting apparatus according to a first example of the present invention.

FIGS. 2A, 2B, 2C, 2D, 2E and 2F are graphs showing the dependence of conversion efficiency on the wavelength of a second semiconductor laser.

FIG. 3 is a graph showing the correlationship between the wavelengths of two semiconductor lasers according to the first example.

FIG. 4 is a schematic diagram of a configuration of an optical wavelength converting apparatus according to a second example of the present invention.

FIG. 5 is a graph showing the correlationship between the wavelengths of two semiconductor lasers according to the second example.

FIG. 6 is a schematic diagram of a configuration of an optical wavelength converting apparatus according to a third example of the present invention.

FIG. 7 is a graph showing the direction of propagation vs. the wavelengths of two semiconductor lasers according to the third example.

FIG. 8 is a graph showing the direction of propagation vs. the wavelengths of two semiconductor lasers according to a fourth example.

FIG. 9 is a graph in which FIGS. 7 and 8 are superimposed on each other to describe a fifth example.

FIG. 10 is a graph showing the direction of propagation vs. the wavelengths of two semiconductor lasers according to a fifth example.

FIG. 11 is a schematic diagram of an optical wavelength converting apparatus according to a sixth example of the present invention.

FIG. 12 is a graph showing the correlationship between the wavelengths of two semiconductor lasers according to a seventh example.

FIG. 13 is a graph showing the correlationship between the wavelengths of two semiconductor lasers according to an eighth example.

FIG. 14 is a graph showing the correlation between the wavelengths of two semiconductor lasers according to a ninth example.

FIG. 15 is a schematic diagram of a configuration of a conventional optical wavelength converting apparatus.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0016] The action and principle of the present invention will be described taking by way of example the case in which a biaxial crystal such as KTP is used as nonlinear optical material. This description is also applicable to a uniaxial crystal in which two of the three refractive indices described below are equal.

[0017] The principal axes in the nonlinear optical material are an x, y, and z axes. In general, for a biaxial crystal, the axes are set so that refractive indices n_x , n_y , and n_z for the principal axes are such that $n_x < n_y < n_z$. Furthermore, it is assumed that light propagates through the nonlinear optical material in a certain propagation direction (in a polar coordinate expression, an angle with the z axis is defined as θ and an axis with the x axis is defined as ϕ). The wavelength of light from a first LD (light source) and the refractive index of the nonlinear optical material for this light are defined as λ_1 and n_1 , respectively. The wavelength of light from a second LD (light source) and the refractive index of the nonlinear optical material for this light are defined as λ_2 and n_2 , respectively. The wavelength of sum frequency light of these two beams and the refractive index of the nonlinear optical material for this light are defined as λ_3 and n_3 , respectively.

[0018] Here, phase mismatch amount Δk is defined by:

$$\Delta k = n_3(2\pi / \lambda_3) - n_1(2\pi / \lambda_1) - n_2(2\pi / \lambda_2) \quad (1).$$

Moreover, the nonlinear optical material is provided with a periodic structure such as a periodically poled structure which matches the phases of beams from the two LDs (light sources) with the phase of sum frequency light of these beams. This period Λ has only to be:

$$\Lambda = 2\pi / |\Delta k| = 1 / |n_3 / \lambda_3 - n_1 / \lambda_1 - n_2 / \lambda_2| \quad (2)$$

However, if the periodic structure is such that the refractive index is modulated periodically, the refractive index n_i and others are assumed to be averaged along the propagation direction.

[0019] Light with a wavelength λ_i propagating through a biaxial crystal in a certain propagation direction can assume two basic propagation modes depending on the propagation direction. These propagation modes are referred to as modes 1 and 2, and their refractive indices are defined as $n^{(1)}$ and $n^{(2)}$. Here, the modes 1 and 2 are determined so that $n^{(1)} < n^{(2)}$.

[0020] It is arbitrary to set which propagation mode each of the wavelengths λ_1 , λ_2 , and λ_3 assumes. Specifically, light with a certain wavelength λ_i may be propagated through the nonlinear optical material in a polarization state that provides a propagation mode to be selected. Then, the period of the periodic structure may be determined so as to the corresponding refractive index $n_i(m)$ ($i = 1, 2, 3$, m (mode) = 1, 2). In general, the propagation mode is selected for each wavelength so that the largest component of a nonlinear optical coefficient tensor contributes to the conversion efficiency. In the present invention, however, the propagation mode of each wavelength is selected so that the efficiency of conversion into sum frequency light does not change even with a change in at least one of the parameters (λ_i , T , θ , ϕ , and the like) defining the conversion efficiency.

[0021] Phase shift caused by a change in parameter is expressed by:

$$\delta = |\Delta k| - 2\pi / \Lambda \quad (3).$$

Without any changes, $\delta = 0$. Here, propagation distance is defined as L . Then, as is well known, the conversion efficiency is proportional to:

$$\sin (\delta L / 2) / (\delta L / 2) \quad (4).$$

Thus, the conversion efficiency decreases with increasing absolute value of δ . In the present invention, Δk does not change even with a change in at least one of the parameters defining the conversion efficiency. That is, typically, the propagation mode of each beam with the wavelength λ_1 , λ_2 , or λ_3 is selected so that for the wavelength λ_2 of the second LD (light source),

$$\partial \Delta k / \partial \lambda_2 = 0 \text{ (approximately 0)} \quad (5)$$

or for the temperature T of the nonlinear optical material,

$$\partial \Delta k / \partial T = 0 \text{ (approximately 0)} \quad (6).$$

Thus, Δk and δ do not substantially change even with a change in λ_2 , i.e. the wavelength of the second LD (light source) or the temperature (T) of the nonlinear optical material. Therefore, the conversion efficiency is stabilized.

[0022] In short, the present invention is configured so that although the efficiency of conversion into sum frequency light depends on the phase shift δ (defined to include Δk as shown in Equation (3)), Δk does not substantially change even with a change in at least one of the parameters defining the conversion efficiency. As a result, the conversion efficiency is stabilized.

[0023] The right side of Equation (5) is approximately 0. However, specifically, the following condition is preferable:

$$|\partial \Delta k / \partial \lambda_2| \leq 0.05 \text{ } (\mu\text{m}^{-2})$$

For example, FIG. 2 shows the dependence of λ_2 on the efficiency of conversion into sum frequency light which dependence was observed when $\partial \Delta k / \partial \lambda_2$ was changed from 0 to $0.05 \text{ } (\mu\text{m}^{-2})$ step by step on condition that a KTP crystal of crystal length 10 mm, the first semiconductor laser having an oscillation wavelength (λ_1) of about 1,610 nm and the second semiconductor laser having an oscillation wavelength (λ_2) of about 790 nm were used. As $\partial \Delta k / \partial \lambda_2$ increases, a wavelength band (wavelength tolerance required for λ_2) narrows. However, even if $\partial \Delta k / \partial \lambda_2 = 0.05 \text{ } (\mu\text{m}^{-2})$, the wavelength tolerance is 10 nm or more with the full width at half maximum. This is sufficient in a practical sense.

[0024] Furthermore, the conversion efficiency is substantially fixed for a wavelength width of 10 nm or more provided that:

$$|\partial \Delta k / \partial \lambda_2| \leq 0.01 \text{ } (\mu\text{m}^{-2}).$$

This is more advantageous in a practical sense.

[0025] Likewise, the right side of Equation (6) is approximately 0. However, specifically, the following condition is preferable:

$$|\partial \Delta k / \partial T| \leq 0.5 \text{ } (\text{K}^{-1}\text{cm}^{-1})$$

In this case, the temperature tolerance is 10°C or more with the full width at half maximum. This is sufficient in a practical sense.

[0026] Moreover, the conversion efficiency is substantially fixed for a temperature width of 10°C or more provided that:

$$|\partial \Delta k / \partial T| \leq 0.1 \text{ } (\text{K}^{-1}\text{cm}^{-1}).$$

This is more advantageous in a practical sense.

[0027] Thus, with the optical wavelength converting apparatus and the optical wavelength converting method according

to the present invention, typically, the phase shift δ from a designed value does not substantially change even with a change in the wavelength of the second LD or the temperature of the nonlinear optical material changes. Accordingly, the pumping second LD need not provide high wavelength stability and may thus be composed of a multi-longitudinal-mode LD, i.e. an inexpensive LD. Further, since the conversion efficiency does not substantially change even with a change in the temperature of the nonlinear optical material, the output can be stabilized even without any special temperature control devices.

[0028] The examples described below can be provided on the basis of the above described basic configuration.

[0029] The first LD may oscillate in a single-longitudinal mode, while the second LD may oscillate in a multi-longitudinal mode. Furthermore, the first LD may be a DFB or DBR laser, while the second LD may be a Fabry Perot laser or a broad area laser. With this configuration, if the second light source is used as a pumping LD, it desirably provides as high power as possible because the conversion efficiency depends on pumping light power. It is easy to realize a multi-longitudinal-mode LD with high power.

[0030] The first LD can be adapted to under modulation driving. The second LD can be adapted to be driven continuously. For modulation driving, one of the two light sources has only to be modulated. However, it is desirable that the first LD require smaller driving current and the first LD side be under modulation driving.

[0031] In particular, if the first LD is subjected to pulse modulation driving, output light is obtained only when beams from the two LDs are simultaneously incident on a nonlinear optical crystal. Consequently, the rise and fall times of output light depend on the rise and fall times of the LD beams. Thus, the optical pulse width of the output light can be determined accurately, thus making it possible to determine the safety class specified in the laser safety standard. Therefore, when the apparatus is mounted in a product, adequate safety means can be provided according to the class (if an external modulator such as an audio optical modulator is used, it provides analog modulation with slow rises and falls, and the optical pulse width of modulated light cannot be accurately determined easily).

[0032] Alternatively, an optical waveguide may be formed in the nonlinear optical material so as to extend along the propagation direction. That is, since the conversion efficiency depends on power density, the power density may be increased by using the optical waveguide structure to reduce the cross section of the propagation beam.

[0033] Typically, the nonlinear optical material may be KTiOPO_4 (KTP). If KTP is used to obtain green (wavelength region: $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$) output light, then in order to meet Equation (5) to avoid changing the conversion efficiency in response to a change in the wavelength of the second LD (light source), the propagation modes of beams from the first and second LDs (light sources) and of the sum frequency light of these beams may be selected so as to use a component d_{24} or d_{15} or both of a nonlinear optical coefficient tensor d_{ij} . Further, the appropriate wavelength of the first LD (light source) may be selected from the wavelength region $1,220 \text{ nm} \leq \lambda_1 \leq 1,745 \text{ nm}$. The appropriate wavelength of the second LD (light source) may be selected from the wavelength region $701 \text{ nm} \leq \lambda_2 \leq 1,002 \text{ nm}$. In this case, if the principal axes in the KTP are assumed to be an x, y, and z axes and if angles with the z and x axes are defined as θ and ϕ , respectively, when the propagation direction is represented using a polar coordinate system, then the propagation directions of the beams from the first and second LDs (light sources) and of the sum frequency light of these beams may be such that $64^\circ \leq \theta \leq 90^\circ$ and $0^\circ \leq \phi \leq 90^\circ$. In particular, for wavelength regions close to 1300 or 1550 nm, many DFB and DBR lasers with stable wavelengths have been developed for optical communication. These lasers can be used properly as the first LD (light source). Further, many high-power type LDs (Fabry Perot laser and broad area lasers) operating at a wavelength close to 800 nm have been widely developed for solid pumping. These lasers can be used properly as the second LD (light source).

[0034] More specifically, $\theta = 90^\circ$ and $\phi = 0^\circ$, and the wavelengths of beams from the first and second LDs (light sources) and of the sum frequency light of these beams may be $1,519 \text{ nm} \leq \lambda_1 \leq 1,745 \text{ nm}$, $701 \text{ nm} \leq \lambda_2 \leq 862 \text{ nm}$, and $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$, respectively. Further, light from the first LD (light source) may be polarized in the direction of the y axis, light from the second LD (light source) may be polarized in the direction of the z axis, and sum frequency light may be polarized in the direction of the y axis. In this case, the component d_{24} of the nonlinear optical coefficient tensor is used.

[0035] Alternatively, $\theta = 90^\circ$ and $\phi = 90^\circ$, and the wavelengths of beams from the first and second LDs (light sources) and of the sum frequency light of these beams may be $1,220 \text{ nm} \leq \lambda_1 \leq 1,421 \text{ nm}$, $772 \text{ nm} \leq \lambda_2 \leq 1,002 \text{ nm}$, and $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$, respectively. Further, light from the first LD (light source) may be polarized in the direction of the x axis, light from the second LD (light source) may be polarized in the direction of the z axis, and sum frequency light may be polarized in the direction of the y axis. In this case, the component d_{15} of the nonlinear optical coefficient tensor is used.

[0036] When the direction (θ, ϕ) of propagation in the nonlinear optical material is 0° or 90° , $\partial \Delta k / \partial \theta = 0$ and $\partial \Delta k / \partial \phi = 0$. Accordingly, substantially no phase shifts occur even with an angular shift, so that the conversion efficiency does not substantially change. Thus, angular tolerance is high, thus relaxing the requirements for the accuracy of processing (cutting, polishing etc.) of the nonlinear optical material and for the alignment accuracy of each optical element. As a result, yield is improved.

[0037] Further, in particular, if KTP is used as the nonlinear optical material, then when the temperature of the nonlinear optical material is defined as T, the wavelengths of beams from the first and second LDs (light sources) and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and

propagation directions of these three beams in the nonlinear optical material may be determined so that $|\partial \Delta k / \partial T| \leq 0.5$ ($K^{-1}cm^{-1}$) (more desirably, ≤ 0.1 ($K^{-1}cm^{-1}$)). In this case, the conversion efficiency does not substantially change even with a change in the temperature of the nonlinear optical material, the output can be stabilized even without any special temperature control devices.

[0038] More specifically, in order to obtain green (wavelength region: $500\text{ nm} \leq \lambda_3 \leq 550\text{ nm}$) output light, the wavelengths of beams from the first and second LDs (light sources) and of the sum frequency light of these beams and the propagation and polarization directions of these three beams may be determined so as to use the component d_{24} or d_{15} or both of the nonlinear optical coefficient tensor d_{ij} nonlinear optical material (KTP). Further, the propagation directions of beams from the first and second LDs (light sources) and of the sum frequency light of these beams may be set so that $79.1^\circ \leq \theta \leq 90^\circ$ and $20.4^\circ \leq \phi \leq 27.6^\circ$, respectively. The wavelengths of beams from the first and second LDs (light sources) and of the sum frequency light of these beams may be set to be $1,460\text{ nm} \leq \lambda_1 \leq 1,745\text{ nm}$, $701\text{ nm} \leq \lambda_2 \leq 882\text{ nm}$, and $500\text{ nm} \leq \lambda_3 \leq 550\text{ nm}$, respectively.

[0039] Furthermore, the nonlinear optical material may be $KNbO_3$ (KN), $LiNbO_3$ (LN), or $LiTaO_3$ (LT) or the like.

[0040] The present invention will be described below using examples.

(First Example)

[0041] A first example of the present invention will be described below with reference to the drawings.

[0042] FIG. 1 is a schematic diagram of a configuration of an optical wavelength converting apparatus according to the first example of the present invention. In FIG. 1, reference numerals 11 and 19 denote a first and second LDs, reference numerals 13 and 21 denote collimate lenses, and reference numerals 15 and 23 denote half wavelength plates. Reference numerals 27 and 29 denote a dichroic mirror and nonlinear optical material consisting of a KTP crystal, respectively. Reference numerals 31 and 33 denote a periodically poled structure provided in the KTP and a wavelength filter, respectively.

[0043] In the present example, a yz face of the optically polished KTP crystal 29 is set as a light incoming and outgoing surface. In this case, the principal axes (x , y , and z axes) are set so that refractive indices n_x , n_y , and n_z are such that $n_x < n_y < n_z$. Light propagates in the direction of the x axis. In the polar coordinate expression, θ (angle with the z axis) $= 90^\circ$ and ϕ (angle with the x axis) $= 0^\circ$.

[0044] If light propagates in this direction, two propagation modes are present: a propagation mode 1 having electric field components in the y axis direction and a propagation mode 2 having electric field components in the z axis direction. In this case, if a beam from the first LD (wavelength λ_1) is propagated in the propagation mode 1, a beam from the second LD (wavelength λ_2) is propagated in the propagation mode 2, and the sum frequency light of these beams (wavelength λ_3) is propagated in the propagation mode 1, then a wavelength range is present which meets Equation (5), described above.

[0045] This is shown in FIG. 3. For example, to obtain a green laser light ($500\text{ nm} \leq \lambda_3 \leq 550\text{ nm}$) output, the wavelengths may be selected so that $1,519\text{ nm} \leq \lambda_1 \leq 1,745\text{ nm}$ and $701\text{ nm} \leq \lambda_2 \leq 862\text{ nm}$. Then, an optical wavelength converting apparatus can be provided in which the conversion efficiency does not substantially change even with a change in the wavelength of the second LD 19. In this case, the component d_{24} of the nonlinear optical coefficient tensor of KTP is used.

[0046] In the present example, the first LD 11 is a DFB laser of oscillation wavelength $1,610\text{ nm}$ and power 30 mW . The second LD 19 is a Fabry Perot laser of oscillation wavelength 790 nm and power 5 W . The first LD 11 oscillates in the single-longitudinal mode and has a variation in wavelength limited to 0.3 nm or less by temperature control. Further, the second LD 19 oscillates in the multi-longitudinal mode and has a spectral width of about 3 nm .

[0047] An LD beam 17 from the first LD 11 is adjusted by the half wavelength plate 15 so as to be polarized in the direction of y axis of the KTP crystal 29. Further, an LD beam 25 from the second LD 19 is adjusted by the half wavelength plate 23 so as to be polarized in the direction of z axis of the KTP crystal 29. The dichroic mirror 27 is designed to allow the LD beam 17 to pass through, while reflecting the LD beam 25.

[0048] The KTP crystal 29 is provided with the periodically poled structure 31 having a period (A) of $28.7\text{ }\mu\text{m}$ so as to match the phases of the LD beams 17 and 25 with the phase of the sum frequency light of these beams 35 (wavelength: 530 nm). The length of the crystal (L) is 20 mm . The wavelength filter 33 is designed to pass only light with a wavelength close to 530 nm to obtain only the sum frequency light 35.

[0049] As a result, it was possible to obtain green sum frequency light of power 1 mW and central wavelength 530 nm . The spectral width was about 1.3 nm , indicating that sum frequency conversion occurred on all wavelengths of the second LD beam 25 within a spectral width of 3 nm .

[0050] Further, when the wavelength of the second LD 19 was changed by $\pm 10\text{ nm}$, the conversion efficiency decreased to half. Thus, the wavelength tolerance width (full width at half maximum) of the second LD 19 was 20 nm , which is a sufficient value in a practical sense.

[0051] Furthermore, when the first LD 11 was subjected to pulse modulation driving at 500 MHz , sum frequency light 35 modulated at 500 MHz was obtained correspondingly.

[0052] Further, the configuration of the present example is characterized in that the KTP crystal has a relatively large temperature tolerance width (that is, in the present example, $|\partial \Delta k / \partial T|$ is relatively close to 0). When measurements were actually carried out while varying the temperature of the crystal, the conversion efficiency reached its peak at a crystal temperature of about 15°C. The conversion efficiency decreased to half of the peak value at a crystal temperature of 0°C and 28°C. Thus, the temperature tolerance width (full width at half maximum) of the crystal was 28°C. This is a large value compared to the wavelength conversion method based on second-harmonic generation using LiNbO₃ wherein the temperature tolerance width is 1°C·cm. That is, the configuration of the present example requires no adjustments of the crystal temperature or does not require strict temperature control. It has been found that this configuration is advantageous in producing apparatuses. In the present example, the first LD 11 is composed of a DFB laser that suppresses a variation in wavelength by controlling the temperature. However, the present invention is not limited to this aspect. For example, the first LD 11 may be, for example, a DBR laser of a multiple-electrode structure provided with a phase control area used to adjust the wavelength.

(Second Example)

[0053] A second example of the present invention will be described below with reference to the drawings.

[0054] FIG. 4 is a schematic diagram of a configuration of an optical wavelength converting apparatus according to the second example of the present invention. In FIG. 4, reference numerals 111 and 119 denote a first and second LDs, reference numerals 113 and 121 denote collimate lenses, and reference numerals 115 and 123 denote half wavelength plates. Reference numerals 127 and 129 denote a dichroic mirror and nonlinear optical material consisting of a KTP crystal, respectively. Reference numerals 131 and 133 denote a periodically poled structure provided in the KTP and a wavelength filter, respectively.

[0055] In the present example, an xz face of the optically polished KTP crystal is used as a light incoming and outgoing surface. Light propagates in the direction of the y axis. In the polar coordinate expression, θ (angle with the z axis) = 90° and ϕ (angle with the x axis) = 90°.

[0056] If light propagates in this direction, two propagation modes are present: a propagation mode 1 having electric field components in the x axis direction and a propagation mode 2 having electric field components in the z axis direction. In this case, if a beam from the first LD 111 (wavelength λ_1) is propagated in the propagation mode 1, a beam from the second LD 119 (wavelength λ_2) is propagated in the propagation mode 2, and the sum frequency light of these beams (wavelength λ_3) is propagated in the propagation mode 1, then a wavelength range is present which meets Equation (5), described above.

[0057] This is shown in FIG. 5. For example, to obtain green laser light ($500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$) output, the wavelengths may be selected so that $1,220 \text{ nm} \leq \lambda_1 \leq 1,421 \text{ nm}$ and $772 \text{ nm} \leq \lambda_2 \leq 1002 \text{ nm}$. Then, an optical wavelength converting apparatus can be provided in which the conversion efficiency does not substantially change even with a change in the wavelength of the second LD 119. In this case, the component d_{15} of the nonlinear optical coefficient tensor of KTP is used.

[0058] In the present example, the first LD 111 is a DFB laser of oscillation wavelength 1,303 nm and power 30 mW. The second LD 119 is a Fabry Perot laser of oscillation wavelength 893 nm and power 5 W. The first LD 111 oscillates in the single-longitudinal mode and has a variation in wavelength limited to 0.3 nm or less by temperature control. Further, the second LD 119 oscillates in the multi-longitudinal mode and has a spectral width of about 3 nm.

[0059] An LD beam 117 from the first LD 111 is adjusted by the half wavelength plate 115 so as to be polarized in the direction of x axis of the KTP crystal 129. Further, an LD beam 125 from the second LD 119 is adjusted by the half wavelength plate 123 so as to be polarized in the direction of z axis of the KTP crystal 129. The dichroic mirror 127 is designed to allow the LD beam 117 to pass through, while reflecting the LD beam 125.

[0060] The KTP crystal 129 is provided with the periodically poled structure 131 having a period of 32.9 μm so as to match the phases of the LD beams 117 and 125 with the phase of the sum frequency light 135 (wavelength: 530 nm of these beams). The length of the crystal is 20 mm. The wavelength filter 133 is designed to pass only light with a wavelength close to 530 nm to obtain only the sum frequency light 135.

[0061] As a result, it was possible to obtain green sum frequency light 135 of power 0.2 mW and central wavelength 530 nm. The spectral width was about 1.0 nm, indicating that sum frequency conversion occurred on all wavelengths of the second LD beam 125 within a spectral width of 3 nm.

[0062] Further, when the wavelength of the second LD 119 was changed by $\pm 12 \text{ nm}$, the conversion efficiency decreased to half. Thus, the wavelength tolerance width (full width at half maximum) of the second LD 119 was 24 nm, which is a sufficient value in a practical sense.

[0063] Furthermore, when the first LD 111 was subjected to pulse modulation driving at 500 MHz, sum frequency light modulated at 500 MHz was obtained correspondingly.

[0064] With the configuration of the present example, the crystal 129 has a temperature tolerance width (full width at half maximum) of 7°C. This value is worse than that in the first example. However, it is still larger than that obtained with the wavelength conversion method based on second-harmonic generation using LiNbO₃. That is, the configuration of

the present example does not require the crystal temperature to be controlled strictly.

[0065] The present example indicates that a wavelength range different from that in the first example also enables the provision of an optical wavelength converting apparatus according to the present invention.

5 (Third Example)

[0066] In the first and second example, the light propagation direction (θ, ϕ) is 0° or 90° . However, the present invention is not limited to this aspect. A third example of the present invention relates to a configuration of another propagation direction using a KTP crystal.

10 **[0067]** FIG. 7 shows the relationship between LD wavelengths (λ_1, λ_2) meeting Equation (5) and a certain propagation direction (θ, ϕ) in the case in which a first LD beam (wavelength λ_1) is propagated in the polarization direction of a mode 1, while the a second LD beam (wavelength λ_2) is propagated in the polarization direction of a mode 2, with the sum frequency light of these beams propagated in the polarization direction of the mode 1. In this case, $\lambda_3 = 530$ nm.

15 **[0068]** In FIG. 7, curve a1 indicates an example in which $\lambda_1 = 1,610$ nm and $\lambda_2 = 790$ nm. Curve b1 indicates an example in which $\lambda_1 = 1,560$ nm and $\lambda_2 = 803$ nm. Curve c1 indicates an example in which $\lambda_1 = 1,447$ nm and $\lambda_2 = 836$ nm. Curve d1 indicates an example in which $\lambda_1 = 1,344$ nm and $\lambda_2 = 875$ nm. Curve e1 indicates an example in which $\lambda_1 = 1,303$ nm and $\lambda_2 = 893$ nm.

20 **[0069]** This graph indicates that by selecting the appropriate propagation direction and wavelength regions from $64^\circ \leq \theta \leq 90^\circ, 0^\circ \leq \phi \leq 90^\circ, 1,303 \text{ nm} \leq \lambda_1 \leq 1,610 \text{ nm}$, and $790 \text{ nm} \leq \lambda_2 \leq 893 \text{ nm}$, an optical wavelength converting apparatus can be provided in which the conversion efficiency does not substantially change even with a change in the wavelength of the second LD. FIG. 7 shows the case in which $\lambda_3 = 530$ nm. If the range of λ_3 is widened to $500 \text{ nm} \leq \lambda \leq 550 \text{ nm}$, the wavelength regions of λ_1 and λ_2 will be $1,220 \text{ nm} \leq \lambda_1 \leq 1,745 \text{ nm}$ and $701 \text{ nm} \leq \lambda_2 \leq 1,002 \text{ nm}$. Thus, the selectable wavelength ranges increase compared to the first and second examples. This enables the selection of an advantageous wavelength band in producing apparatuses and conditions required for more excellent performance.

25 **[0070]** In the specific example described below, two LDs are selected so that $\lambda_1 = 1,550$ nm and $\lambda_2 = 808$ nm. These wavelengths are commonly used for optical communication and solid pumping. They are expected to enable mass production to reduce costs.

30 **[0071]** Description will be given with reference to FIG. 6. FIG. 6 is a schematic diagram of a configuration of an optical wavelength converting apparatus according to the third example of the present invention. In FIG. 6, reference numerals 211 and 219 denote a first and second LDs, reference numerals 213 and 221 denote collimate lenses, and reference numerals 215 and 223 denote half wavelength plates. Reference numerals 227 and 229 denote a dichroic mirror and nonlinear optical material consisting of a KTP crystal, respectively. Reference numerals 231 and 233 denote a periodically poled structure provided in the KTP and a wavelength filter, respectively.

35 **[0072]** In the present example, the propagation direction is set so that $\theta = 90^\circ$ and $\phi = 23.7^\circ$. Then, according to this setting, the periodically poled structure 231 is formed and the KTP crystal 229 has its light incoming and outgoing surface optically polished. The first LD 211 is a DFB laser of oscillation wavelength 1,550 nm and power 30 mW. The second LD 219 is a Fabry Perot laser of oscillation wavelength 808 nm and power 5 W. The first LD 211 oscillates in a single-longitudinal mode. It has a variation in wavelength limited to 0.3 nm or less by temperature control. Further, the second LD 219 oscillates in a multi-longitudinal mode and has a spectral width of about 3 nm.

40 **[0073]** An LD beam 217 from the first LD 211 is adjusted by the half wavelength plate 215 so as to be polarized parallel with an xy face of the KTP crystal 229. Further, an LD beam 225 from the second LD 219 is adjusted by the half wavelength plate 223 so as to be polarized in the direction of z axis of the KTP crystal 229. The dichroic mirror 227 is designed to allow the LD beam 217 to pass through, while reflecting the LD beam 225.

45 **[0074]** The KTP crystal 229 is provided with the periodically poled structure 231 having a period of $29.4 \mu\text{m}$ so as to match the phases of the LD beams 217 and 225 with the phase of the sum frequency light 235 of these beams (wavelength: 531 nm). The length of the crystal is 20 nm. The wavelength filter 233 is designed to pass only light with a wavelength close to 531 nm to obtain only the sum frequency light 235.

[0075] With such a configuration, both components d_{24} and d_{15} of nonlinear optical coefficient tensor of KTP are used.

50 **[0076]** As a result, it was possible to obtain green sum frequency light of power 0.8 mW and central wavelength 531 nm. The wavelength width was about 1.25 nm, indicating that sum frequency conversion occurred on all wavelengths of the second LD beam 225 within a wavelength width of 3 nm.

55 **[0077]** Further, the configuration of the present example is characterized in that the temperature tolerance width of the KTP crystal 229 is very large (that is, the present example corresponds to a fifth example, described later, in which the conversion efficiency does not substantially change even with a change in crystal temperature). When measurements were actually carried out while varying the crystal temperature, the conversion efficiency reached its peak at a crystal temperature of 26°C . It then decreased to half at a crystal temperature of -5°C and 55°C . Thus, the temperature tolerance width (full width at half maximum) of the crystal was 60°C . This indicates that the configuration of the present example substantially eliminates the need for the adjustment of the crystal temperature and is advantageous in producing appa-

ratus.

(Fourth Example)

[0078] A fourth example of the present invention relates to such an optical wavelength converting apparatus that the conversion efficiency does not substantially change even with a change in the temperature of the KTP crystal.

[0079] The configuration of this example is substantially the same as that shown in FIG. 6. FIG. 8 shows an example of the relationship between LD wavelengths (λ_1 , λ_2) meeting Equation (6) and a certain propagation direction (θ , ϕ) in the case in which a first LD beam (wavelength λ_1) is propagated in the polarization direction of a mode 1, while the a second LD beam (wavelength λ_2) is propagated in the polarization direction of a mode 2, with the sum frequency light of these beams propagated in the polarization direction of the mode 1. In this case, $\lambda_3 = 530$ nm.

[0080] In FIG. 8, curve a2 indicates an example in which $\lambda_1 = 1,610$ nm and $\lambda_2 = 790$ nm. Curve b2 indicates an example in which $\lambda_1 = 1,560$ nm and $\lambda_2 = 803$ nm. Curve c2 indicates an example in which $\lambda_1 = 1,447$ nm and $\lambda_2 = 836$ nm. Curve d2 indicates an example in which $\lambda_1 = 1,344$ nm and $\lambda_2 = 875$ nm. Curve e2 indicates an example in which $\lambda_1 = 1,303$ nm and $\lambda_2 = 893$ nm.

[0081] This graph indicates that by selecting the appropriate propagation direction and wavelength regions from $28.3^\circ \leq \theta \leq 90^\circ$, $19.2^\circ \leq \phi \leq 90^\circ$, $1,303 \text{ nm} \leq \lambda_1 \leq 1,610 \text{ nm}$, and $790 \text{ nm} \leq \lambda_2 \leq 893 \text{ nm}$, an optical wavelength converting apparatus can be provided in which the conversion efficiency does not substantially change even with a change in the wavelength of the KTP crystal. FIG. 8 shows the case in which $\lambda_3 = 530$ nm. However, widening the range of λ_3 enables the wavelength regions of λ_1 and λ_2 to be widened.

(Fifth Example)

[0082] A fifth example of the present invention relates to such an optical wavelength converting apparatus that the conversion efficiency does not substantially increase even with a change in the wavelength of the second LD or in the temperature of the KTP crystal. As already described, the third example constitutes such an optical wavelength converting apparatus. This will be described below with reference to the graph in FIG. 9 in which FIGS. 7 and 8 are superimposed on each other.

[0083] In FIG. 9, the present example corresponds to the intersection between a line (for example, a1) indicating that the conversion efficiency does not substantially change even with a change in wavelength and a line (for example, a2) indicating that the conversion efficiency does not substantially change even with a change in temperature for certain wavelength λ_1 and λ_2 . The third example is also an example corresponding to this intersection. In this case, $\lambda_3 = 530$ nm. However, widening the range of λ_3 to $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$ results in an area of intersections such as that shown in FIG. 10.

[0084] As shown in FIG. 10, in the third example, the polarization direction of beams from the first and second LDs and the sum frequency light of these beams is set so that $79.1^\circ \leq \theta \leq 90^\circ$ and $20.40^\circ \leq \phi \leq 27.6^\circ$. Further, the wavelengths of the beams from the first and second LDs and the sum frequency light of these beams are set so that $1,460 \text{ nm} \leq \lambda_1 \leq 1,745 \text{ nm}$, $701 \text{ nm} \leq \lambda_2 \leq 882 \text{ nm}$, and $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$. Thus, these values are within the area in FIG. 10. Consequently, an optical wavelength converting apparatus is provided in which the conversion efficiency does not substantially change even with a change in the wavelength of the second LD or in the temperature of the KTP crystal.

(Sixth Example)

[0085] Now, a sixth example according to the present invention will be described with reference to the drawings.

[0086] FIG. 11 is a schematic diagram showing a configuration of an optical wavelength converting apparatus according to the sixth example of the present invention. This configuration is substantially the same as the first example. Detailed description is omitted. The same members are denoted by the same reference numerals.

[0087] A difference from the first example is that a KTP crystal 329 is provided with a periodically poled structure 331 and an optical waveguide 332. The optical waveguide 332 has a sectional area of $80 \mu\text{m}^2$. A condensing lens 301 is provided to couple the LD beams 17 and 25 to the optical waveguide 332.

[0088] The optical power density of LD beams in the KTP crystal 329 in the present example is higher than that in the first example. Since the conversion efficiency is proportional to the optical power density, the optical waveguide structure serves to increase the conversion efficiency.

[0089] In the present example, light was allowed to be incident by using a DFB laser of oscillation wavelength 1,610 nm and power 30 W as the first LD 11 and a Fabry Perot laser of oscillation wavelength 790 nm and output 5 W as the second LD 19. Then, it was possible to obtain green sum frequency light 35 of power 30 mW and central wavelength 530 nm.

[0090] Further, the wavelength tolerance width (full width at half maximum) of the second LD 19 was 18 nm, which is

a sufficient value in a practical sense. Furthermore, with the configuration of the present example, the KTP crystal 329 had a temperature tolerance width (full width at half maximum) of 24°C, which is a relatively large value.

(Seventh Example)

[0091] In the above described plurality of examples, the KTP crystal is shown as nonlinear optical material. However, other nonlinear optical material may be used. Description of the seventh example will be given of the case in which a KN(KNbO₃) crystal is used as nonlinear optical material.

[0092] KN is a biaxial crystal. The principal axes (x, y, and z axes) are set so that the refractive indices n_x , n_y , and n_z are such that $n_x < n_y < n_z$. Further, in the polar coordinate expression, an angle with the z axis is defined as θ . An angle with the x axis is defined as ϕ . If light propagates in this direction, two propagation modes are present: a propagation mode 1 having electric field components in the x axis direction and a propagation mode 2 having electric field components in the z axis direction. In this case, if a beam from the first LD (wavelength λ_1) is propagated in the propagation mode 2, a beam from the second LD (wavelength λ_2) is propagated in the propagation mode 2, and the sum frequency light of these beams (wavelength λ_3) is propagated in the propagation mode 1, then a wavelength range is present which meets Equation (5), described above. This is shown in FIG. 12. For example, to obtain a green laser light ($500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$) output, the wavelengths may be selected so that $1,751 \text{ nm} \leq \lambda_1 \leq 1,939 \text{ nm}$ and $674 \text{ nm} \leq \lambda_2 \leq 802 \text{ nm}$. Then, an optical wavelength converting apparatus can be provided in which the conversion efficiency does not substantially change even with a change in the wavelength of the second LD.

[0093] In this case, the component d_{13} of nonlinear optical coefficient tensor of KN is used. Since KN has a larger nonlinear optical coefficient than KTP, the present example is advantageous in that the crystal length (L) required to obtain the same conversion efficiency can be reduced compared to the first example.

[0094] In this regard, the principal axes of the KN crystal may be set so that $n_x > n_y > n_z$. In this case, the propagation and polarization directions may be determined correspondingly.

(Eighth Example)

[0095] Description will be given of the case in which an LN(LiNbO₃) crystal is used as nonlinear optical material.

[0096] LN is a negative uniaxial crystal (with which extraordinary light has a smaller refractive index than ordinary light). The principal z axis is set so that the refractive index for extraordinary light is n_z . Further, in the polar coordinate expression, an angle with the z axis is defined as θ . Since the LN is a uniaxial crystal, a plane perpendicular to the z axis is optically equivalent to this axis. As a result, the angle ϕ is meaningless.

[0097] Light is assumed to propagate in a direction perpendicular to the z axis ($\theta = 90^\circ$). For convenience, this direction is assumed to be the y axis direction. If light propagates in this direction, two propagation modes are present: a propagation mode 1 (corresponding to extraordinary light) having electric field components in the z axis direction and a propagation mode 2 (corresponding to ordinary light) having electric field components in a direction perpendicular to the z axis direction. In this case, if a beam from the first LD (wavelength λ_1) is propagated in the propagation mode 2 (ordinary light), a beam from the second LD (wavelength λ_2) is propagated in the propagation mode 2 (ordinary light), and the sum frequency light of these beams (wavelength λ_3) is propagated in the propagation mode 1 (extraordinary light), then a wavelength range is present which meets Equation (5), described above.

[0098] This is shown in FIG. 13. Selecting the wavelengths from these ranges provides an optical wavelength converting apparatus in which the conversion efficiency does not substantially change even with a change in the wavelength of the second LD. In this case, the component d_{31} of the nonlinear optical coefficient tensor of LN is used.

[0099] For example, the first LD may have a wavelength of 1,900 nm. The second LD may have a wavelength of 1,300 nm. In this case, the sum frequency light has a wavelength of 772 nm. A wavelength band around a wavelength of 1,900 nm is expected to be used as a light source for gas detection. By reducing the wavelength by the sum frequency conversion, the wavelength region can be shifted to one in which an Si photodetector, which is commonly used as a light receiving element, sensitively receives light. This reduces the costs of the light receiving section.

(Ninth Example)

[0100] Description will be given of the case in which an LT(LiTaO₃) crystal is used as nonlinear optical material.

[0101] LT is a positive uniaxial crystal (with which extraordinary light has a smaller refractive index than ordinary light). The principal z axis is set so that the refractive index for extraordinary light is n_z . Further, in the polar coordinate expression, an angle with the z axis is defined as θ . Since the LT is a uniaxial crystal, a plane perpendicular to the z axis is optically equivalent to this axis. As a result, the angle ϕ is meaningless.

[0102] Light is assumed to propagate in a direction perpendicular to the z axis ($\theta = 90^\circ$). For convenience, this direction is assumed to be the y axis direction. If light propagates in this direction, two propagation modes are present: a propagation

mode 1 (corresponding to ordinary light) having electric field components in the z axis direction and a propagation mode 2 (corresponding to extraordinary light) having electric field components in a direction perpendicular to the z axis direction. In this case, if a beam from the first LD (wavelength λ_1) is propagated in the propagation mode 2 (extraordinary light), a beam from the second LD (wavelength λ_2) is propagated in the propagation mode 2 (extraordinary light), and the sum frequency light of these beams (wavelength λ_3) is propagated in the propagation mode 2 (extraordinary light), then a wavelength range is present which meets Equation (5), described above.

[0103] This is shown in FIG. 14. Selecting wavelengths from these ranges provides an optical wavelength converting apparatus in which the conversion efficiency does not substantially change even with a change in the wavelength of the second LD. In this case, the component d_{33} of the nonlinear optical coefficient tensor of LT is used.

[0104] The present invention is not limited to the nonlinear optical material shown in the above described plurality of examples. Of course, other nonlinear optical material may be used. Further, the nonlinear optical material may have different compositions, impurity concentrations, and the like and thus different wavelength or temperature distributions of the refractive indices, depending on the manner in which it is grown. However, in this case, the optimum wavelength, propagation direction, and propagation modes may be selected depending on the conditions. Further, in the above examples, the periodically poled structure is used as a periodic structure for phase matching. However, the present invention is not limited to this aspect. It is possible to use a refractive index modulating structure in which the refractive indices are periodically modulated or a structure having the functions of both periodically poled structure and refractive index modulating structure.

[0105] As described above, according to the optical wavelength converting apparatus and the optical wavelength converting method according to the present invention, the conversion efficiency does not substantially change even with a change in at least one of the parameters (typically, the wavelength of the exciting light source or the temperature of the nonlinear optical material) defining the efficiency of conversion into sum frequency light. Accordingly, an inexpensive LD not requiring wavelength stability, or the like can be used as an exciting light source. Further, an optical wavelength converting apparatus with high efficiency can be provided which is adapted to be suitable for size reduction and to enable high-speed modulation.

[0106] There is provided an optical wavelength converting apparatus comprising a first and second light sources and a nonlinear optical material so that beams from the two light sources are allowed to be incident on the nonlinear optical material to generate sum frequency light of these beams, wherein the nonlinear optical material is provided with a periodic structure that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of parameters defining the efficiency of conversion into sum frequency light, whereby an inexpensive LD having poor wavelength stability can be used as a pumping light source, and is suitable for size reduction, and enables high-speed modulation.

[0107] This application is a divisional application of European patent application no. 03 003 046.4 (the "parent application"), also published as EP 1 336 895. Based on the original claims of the parent application, the following aspects form part of the content of this divisional application as filed.

1. An optical wavelength converting apparatus comprising a first and second light sources and a nonlinear optical material so that beams from the two light sources are allowed to be incident on the nonlinear optical material to generate sum frequency light of these beams, wherein the nonlinear optical material is provided with a periodic structure that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of parameters defining the efficiency of conversion into sum frequency light.

2. The optical wavelength converting apparatus according to aspect 1, wherein wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of an oscillation wavelength of the second light source and the temperature of the nonlinear optical material.

3. The optical wavelength converting apparatus according to aspect 1, wherein the first and second light sources are a first and second semiconductor lasers, respectively.

4. The optical wavelength converting apparatus according to aspect 1, wherein the periodic structure is a periodically poled structure.

5. The optical wavelength converting apparatus according to aspect 1, wherein the periodic structure is a periodic refractive index modulating structure in which a refractive index is modulated periodically.

6. The optical wavelength converting apparatus according to aspect 2, wherein when wavelengths of a beam from the first light source, a beam from the second light source, and a sum frequency light of these beams are defined as λ_1 , λ_2 , and λ_3 , refractive indices of the nonlinear optical material for the beams and light (or refractive indices averaged along the light propagation direction) are defined as n_1 , n_2 , and n_3 , respectively, and a phase mismatch amount Δk is defined as follows:

$$\Delta k = n_3 (2\pi / \lambda_3) - n_1 (2\pi / \lambda_1) - n_2 (2\pi / \lambda_2),$$

the periodic structure has a period Λ given by:

$\Lambda = 2\pi / |\Delta k| = 1 / |n_3 / \lambda_3 - n_1 / \lambda_1 - n_2 / \lambda_2|$, and the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:

$$|\partial \Delta k / \partial \lambda_2| \leq 0.05 \text{ } (\mu\text{m}^{-2}).$$

7. The optical wavelength converting apparatus according to aspect 6, wherein the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:

$$|\partial \Delta k / \partial \lambda_2| \leq 0.01 \text{ } (\mu\text{m}^{-2}).$$

8. The optical wavelength converting apparatus according to aspect 3, wherein the first semiconductor laser oscillates in a single-longitudinal mode.

9. The optical wavelength converting apparatus according to aspect 8, wherein the first semiconductor laser is a DFB or DBR laser.

10. The optical wavelength converting apparatus according to aspect 3, wherein the second semiconductor laser oscillates in a multi-longitudinal mode.

11. The optical wavelength converting apparatus according to aspect 10, wherein the second semiconductor laser is a Fabry Perot laser or a broad area laser.

12. The optical wavelength converting apparatus according to aspect 3, wherein the first semiconductor laser is configured to undergo modulation driving, and the second semiconductor laser is configured to be continuously driven.

13. The optical wavelength converting apparatus according to aspect 12, wherein the first semiconductor laser is configured to undergo pulse modulation driving.

14. The optical wavelength converting apparatus according to aspect 1, wherein an optical waveguide is formed in the nonlinear optical material so as to extend along the propagation direction.

15. The optical wavelength converting apparatus according to aspect 2, wherein when wavelengths of a beam from the first light source, a beam from the second light source, and a sum frequency light of these beams are defined as λ_1 , λ_2 , and λ_3 , refractive indices of the nonlinear optical material for the beams and light (or refractive indices averaged along the light propagation direction) are defined as n_1 , n_2 , and n_3 , respectively, and a phase mismatch amount Δk is defined as follows:

$$\Delta k = n_3 (2\pi / \lambda_3) - n_1 (2\pi / \lambda_1) - n_2 (2\pi / \lambda_2),$$

the periodic structure has a period A given by:

$A = 2\pi / |\Delta k| = 1 / |n_3 / \lambda_3 - n_1 / \lambda_1 - n_2 / \lambda_2|$, and when a temperature of the nonlinear optical material is defined as T , the wavelengths of beams from the first and second semiconductor lasers and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:

$$|\partial \Delta k / \partial T| \leq 0.5 \text{ (K}^{-1}\text{cm}^{-1}\text{)}.$$

16. The optical wavelength converting apparatus according to aspect 15, wherein the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:

$$|\partial \Delta k / \partial T| \leq 0.1 \text{ (K}^{-1}\text{cm}^{-1}\text{)}.$$

17. The optical wavelength converting apparatus according to aspect 1, wherein the nonlinear optical material is KTiOPO_4 (KTP).

18. The optical wavelength converting apparatus according to aspect 17, wherein the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to use a component d_{24} or d_{15} or both of a nonlinear optical coefficient tensor d_{ij} of the nonlinear optical material.

19. The optical wavelength converting apparatus according to aspect 18, wherein when an x , y , and z axes are set as principal axes in the nonlinear optical material and when an angle with the z axis is defined as θ and an angle with the x axis is defined as ϕ , the propagation direction of beams from the first and second light sources and of the sum frequency light of these beams are set so as to be $64^\circ \leq \theta \leq 90^\circ$ and $0^\circ \leq \phi \leq 90^\circ$, and the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams are set so as to be $1,220 \text{ nm} \leq \lambda_1 \leq 1,745 \text{ nm}$, $701 \text{ nm} \leq \lambda_2 \leq 1,002 \text{ nm}$, and $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$.

20. The optical wavelength converting apparatus according to aspect 19, wherein the propagation direction of beams from the first and second light sources and of the sum frequency light of these beams are $\theta = 90^\circ$ and $\phi = 0^\circ$, the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams are $1,519 \text{ nm} \leq \lambda_1 \leq 1,745 \text{ nm}$, $701 \text{ nm} \leq \lambda_2 \leq 862 \text{ nm}$, and $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$, and the beam from the first light source is polarized along the y axis, the beam from the second light source is polarized along the z axis, and the sum frequency light is polarized along the y axis.

21. The optical wavelength converting apparatus according to aspect 19, wherein the propagation direction of beams from the first and second light sources and of the sum frequency light of these beams are $\theta = 90^\circ$ and $\phi = 90^\circ$, the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams are $1,220 \text{ nm} \leq \lambda_1 \leq 1,421 \text{ nm}$, $772 \text{ nm} \leq \lambda_2 \leq 1,002 \text{ nm}$, and $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$, and the beam from the first light

source is polarized along the x axis, the beam from the second light source is polarized along the z axis, and the sum frequency light is polarized along the x axis.

22. The optical wavelength converting apparatus according to aspect 18, wherein when the x, y, and z axes are set as principal axes in the nonlinear optical material and when an angle with the z axis is defined as θ and an angle with the x axis is defined as ϕ , the propagation direction of beams from the first and second light sources and of the sum frequency light of these beams are set so as to be $79.1^\circ \leq \theta \leq 90^\circ$ and $20.4^\circ \leq \phi \leq 27.6^\circ$, and the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams are set so as to be $1,460 \text{ nm} \leq \lambda_1 \leq 1,745 \text{ nm}$, $701 \text{ nm} \leq \lambda_2 \leq 882 \text{ nm}$, and $500 \text{ nm} \leq \lambda_3 \leq 550 \text{ nm}$.

23. The optical wavelength converting apparatus according to aspect 1, wherein the nonlinear optical material is KNbO_3 (KN) .

24. The optical wavelength converting apparatus according to aspect 1, wherein the nonlinear optical material is LiNbO_3 (LN) .

25. The optical wavelength converting apparatus according to aspect 1, wherein the nonlinear optical material is LiTaO_3 (LT).

26. An optical wavelength converting method of using a first and second light sources and nonlinear optical material to allow beams from the two light sources to impinge against the nonlinear optical material to generate sum frequency light of these beams, wherein the nonlinear optical material is provided with a periodic structure that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of parameters defining the efficiency of conversion into sum frequency light.

27. The optical wavelength converting method according to aspect 26, wherein wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of an oscillation wavelength of the second light source and the temperature of the nonlinear optical material.

28. The optical wavelength converting method according to aspect 27, wherein when wavelengths of a beam from the first light source, a beam from the second light source, and a sum frequency light of these beams are defined as λ_1 , λ_2 , and λ_3 , refractive indices of the nonlinear optical material for the beams and light (or refractive indices averaged along the light propagation direction) are defined as n_1 , n_2 , and n_3 , respectively, and a phase mismatch amount Δk is defined as follows:

$$\Delta k = n_3 (2\pi / \lambda_3) - n_1 (2\pi / \lambda_1) - n_2 (2\pi / \lambda_2) ,$$

the periodic structure has a period A given by:

$A = 2\pi / |\Delta k| = 1 / |n_3 / \lambda_3 - n_1 / \lambda_1 - n_2 / \lambda_2|$, and the wavelengths of beams from the first and second light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:

$$|\partial \Delta k / \partial \lambda_2| \leq 0.05 \text{ } (\mu\text{m}^{-2}) .$$

29. The optical wavelength converting method according to aspect 28, wherein the wavelengths of beams from the

first and second light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:

$$|\partial \Delta k / \partial \lambda_2| \leq 0.01 \text{ } (\mu\text{m}^{-2}) .$$

30. The optical wavelength converting method according to aspect 27, wherein when wavelengths of a beam from the first light source, a beam from the second light source, and a sum frequency light of these beams are defined as λ_1 , λ_2 , and λ_3 , refractive indices of the nonlinear optical material for the beams and light (or refractive indices averaged along the light propagation direction) are defined as n_1 , n_2 , and n_3 , respectively, and a phase mismatch amount Δk is defined as follows:

$$\Delta k = n_3 (2\pi / \lambda_3) - n_1 (2\pi / \lambda_1) - n_2 (2\pi / \lambda_2) ,$$

the periodic structure has a period Λ given by:

$\Lambda = 2\pi / |\Delta k| = 1 / |n_3 / \lambda_3 - n_1 / \lambda_1 - n_2 / \lambda_2|$, and when a temperature of the nonlinear optical material is defined as T , the wavelengths of beams from the first and second semiconductor lasers and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:

$$|\partial \Delta k / \partial T| \leq 0.5 \text{ } (\text{K}^{-1}\text{cm}^{-1}) .$$

31. The optical wavelength converting method according to aspect 30, the wavelengths of beams from the first and second semiconductor lasers and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined so as to be:


$$|\partial \Delta k / \partial T| \leq 0.1 \text{ } (\text{K}^{-1}\text{cm}^{-1}) .$$

Claims

1. An optical wavelength converting apparatus comprising first and second light sources and a nonlinear optical material so that beams from the two light sources are allowed to be incident on the nonlinear optical material to generate sum frequency light of these beams, wherein the nonlinear optical material is provided with a periodic structure that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of parameters defining the efficiency of conversion into sum frequency light, wherein wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of an oscillation wavelength of the second light source and the temperature of the nonlinear optical material.

2. The optical wavelength converting apparatus according to claim 1, wherein the first and second light sources are first and second semiconductor lasers, respectively.
3. The optical wavelength converting apparatus according to claim 1, wherein the periodic structure is a periodically poled structure.
4. The optical wavelength converting apparatus according to claim 2, wherein the first semiconductor laser oscillates in a single-longitudinal mode.
5. The optical wavelength converting apparatus according to claim 2, wherein the second semiconductor laser oscillates in a multi-longitudinal mode.
6. The optical wavelength converting apparatus according to claim 2, wherein the first semiconductor laser is configured to undergo modulation driving, and the second semiconductor laser is configured to be continuously driven.
7. An optical wavelength converting method of using first and second light sources and nonlinear optical material to allow beams from the two light sources to impinge against the nonlinear optical material to generate sum frequency light of these beams, wherein the nonlinear optical material is provided with a periodic structure that matches phases of the beams from the two light sources with a phase of the sum frequency light of these beams, and wavelengths of beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of parameters defining the efficiency of conversion into sum frequency light, wherein wavelengths of the beams from the two light sources and of the sum frequency light of these beams, polarization directions of these three beams in the nonlinear optical material, and propagation directions of these three beams in the nonlinear optical material are determined such that an efficiency of conversion into sum frequency light does not change even with a change in at least one of an oscillation wavelength of the second light source and the temperature of the nonlinear optical material.

FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 12**FIG. 13**

FIG. 14





FIG. 15





EUROPEAN SEARCH REPORT

Application Number
EP 11 18 8832

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	AWDAH ARRAF ET AL: "Large-Bandwidth Frequency Conversion in High-NA Step Index Optical Fibers", IEEE JOURNAL OF QUANTUM ELECTRONICS, IEEE SERVICE CENTER, PISCATAWAY, NJ, USA, vol. 34, no. 4, 1 April 1998 (1998-04-01), XP011051892, ISSN: 0018-9197	1,7	INV. G02F1/35
Y	* Chapter "I. Introduction", "III.B Sum Frequency Mixing", V.B Sum Frequency Generation"; page 665, left-hand column, paragraph 2 * -----	2-6	
X	XU C -Q ET AL: "AlGaAs semiconductor quasiphase-matched wavelength converters", JAPANESE JOURNAL OF APPLIED PHYSICS, PART 1 (REGULAR PAPERS, SHORT NOTES & REVIEW PAPERS) PUBLICATION OFFICE, JAPANESE JOURNAL APPL. PHYS JAPAN, vol. 37, no. 3A, March 1998 (1998-03), pages 823-831, XP002500139, ISSN: 0021-4922	1,7	
Y	* abstract; figures 1,5,11 * * Chapter "I. Introduction", "2.1 Mathematical model", "2.2 Sum-frequency generation (SFG) from a periodical structure", "3.4 SFG measurements" * ----- -/--	2-6	TECHNICAL FIELDS SEARCHED (IPC) G02F
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 19 January 2012	Examiner Wahl, Martin
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

1
EPO FORM 1503 03.82 (P04C01)



EUROPEAN SEARCH REPORT

Application Number
EP 11 18 8832

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	WANG ET AL: "Frequency-tunable sum- and difference-frequency generation by using two diode lasers in a KTP crystal", OPTICS COMMUNICATIONS, NORTH-HOLLAND PUBLISHING CO. AMSTERDAM, NL, vol. 102, no. 3-4, 1 October 1993 (1993-10-01), pages 304-308, XP022570779, ISSN: 0030-4018 * abstract * * page 305, left-hand column, lines 2-6 * -----	1-7	TECHNICAL FIELDS SEARCHED (IPC)
A	US 5 734 494 A (XU CHANG QING [JP] ET AL) 31 March 1998 (1998-03-31) * column 1, line 44 - column 2, line 32 * * column 3, line 4 - column 4, line 42 * * column 5, line 7 - line 27 * * column 6, line 3 - column 7, line 33; figures 1,2 * -----	1-7	
A	US 5 436 757 A (OKAZAKI YOJI [JP] ET AL) 25 July 1995 (1995-07-25) * column 2, line 39 - column 3, line 42 * * column 4, line 57 - column 5, line 55 * * column 8, line 35 - line 48 * * column 10, line 44 - line 47; figures 1-4 * -----	1-7	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 19 January 2012	Examiner Wahl, Martin
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

 1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 11 18 8832

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-01-2012

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5734494 A	31-03-1998	JP 3187290 B2	11-07-2001
		JP 9033962 A	07-02-1997
		US 5734494 A	31-03-1998

US 5436757 A	25-07-1995	JP 5333395 A	17-12-1993
		US 5436757 A	25-07-1995

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 6175180 A [0005]
- EP 03003046 A [0107]
- EP 1336895 A [0107]