



(86) Date de dépôt PCT/PCT Filing Date: 2012/11/02
 (87) Date publication PCT/PCT Publication Date: 2013/05/10
 (85) Entrée phase nationale/National Entry: 2014/04/29
 (86) N° demande PCT/PCT Application No.: US 2012/063174
 (87) N° publication PCT/PCT Publication No.: 2013/067263
 (30) Priorité/Priority: 2011/11/04 (US61/555,696)

(51) Cl.Int./Int.Cl. *E21B 7/26* (2006.01),
E21B 7/04 (2006.01)
 (71) Demandeur/Applicant:
SCHLUMBERGER CANADA LIMITED, CA
 (72) Inventeurs/Inventors:
LEE, GRANT, US;
JENSEN, MICHAEL, US;
HERBST, NEIL, US;
BLAKE, SARAH, US
 (74) Agent: SMART & BIGGAR

(54) Titre : PROCÉDE ET SYSTEME POUR UNE OPERATION DE BROYAGE AUTOMATIQUE
 (54) Title: METHOD AND SYSTEM FOR AN AUTOMATIC MILLING OPERATION




Fig. 1

(57) **Abrégé/Abstract:**

A method (50) and an assembly (10) for milling an obstruction disposed within a wellbore (W) includes a milling module (12) having a motor (22) rotating a milling bit (14), a first electronics cartridge (26) for controlling the motor based upon a motor torque value, a tractor module (16, 18) for engaging with the wellbore and providing a push force against the wellbore to urge the milling assembly in a direction of the milling bit, and a second electronics cartridge (28) for controlling a push force value of tractor module. The method involves rotating the milling bit (54) and engaging the tractor module with the wellbore (56), and adjusting, iteratively, the operation (58) based on a calculated torque value and a calculated push force value to maintain the calculated values at around a target torque value and below a push force limit value (66, 70).



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(43) International Publication Date
10 May 2013 (10.05.2013)(10) International Publication Number
WO 2013/067263 A3

- (51) **International Patent Classification:**
E21B 7/26 (2006.01) *E21B 7/04* (2006.01)
- (21) **International Application Number:**
PCT/US2012/063174
- (22) **International Filing Date:**
2 November 2012 (02.11.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/555,696 4 November 2011 (04.11.2011) US
- (71) **Applicant (for CA only):** SCHLUMBERGER CANADA LIMITED [CA/CA]; 525-3rd Avenue Southwest, Calgary, Alberta T2P-0G4 (CA).
- (71) **Applicant (for FR only):** SERVICES PETROLIERS SCHLUMBERGER [FR/FR]; 42 rue Saint Dominique, F-75007 Paris (FR).
- (71) **Applicant (for GB, JP, NL only):** SCHLUMBERGER HOLDINGS LIMITED [GB/GB]; P.O. Box 71, Craigmuir Chambers, Road Town, Tortola, Virgin Islands, British, 1110 (VG).
- (71) **Applicant (for AL, AM, AT, AU, AZ, BF, BG, BJ, BN, BY, CF, CG, CH, CI, CL, CM, CO, CY, CZ, DE, DK, EG, GA, GE, GN, GQ, GR, GW, HR, HU, ID, IE, IL, IT, KE, KG, KP, KR, KZ, LT, MD, MG, ML, MR, MX, MY, NE, NO, NZ, OM, PL, QA, RO, RU, SI, SK, SN, TD, TG, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, ZA only):** SCHLUMBERGER TECHNOLOGY B.V. [NL/NL]; Parkstraat 83-89m, NL-2514 JG The Hague (NL).
- (71) **Applicant (for all designated States except AL, AM, AT, AU, AZ, BG, BN, BY, CA, CH, CL, CO, CY, CZ, DE, DK, EG, FR, GB, GE, GR, HR, HU, ID, IE, IL, IT, JP, KE, KG, KP, KR, KZ, LT, MG, MX, MY, NL, NO, NZ, OM, PL, QA, RO, RU, SI, SK, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, ZA):** PRAD RESEARCH AND DEVELOPMENT LIMITED [GB/GB]; P.O. Box 71, Craigmuir Chambers, Road Town, Tortola, Virgin Island, British, 1110 (VG).
- (71) **Applicant (for US only):** SCHLUMBERGER TECHNOLOGY CORPORATION [US/US]; 300 Schlumberger Drive, Sugar Land, Texas 77478 (US).
- (72) **Inventors:** LEE, Grant; 6363 San Felipe St. #132, Houston, Texas 77057 (US). JENSEN, Michael; 1711 Quarterpath Dr., Richmond, Texas 77406 (US). HERBST, Neil; 1703 Cheshire Ln, Houston, Texas 77018 (US). BLAKE, Sarah; 1315 Deerfield Road, Richmond, Texas 77406 (US).
- (74) **Agents:** HEWITT, Cathy et al.; 10001 Richmond Avenue, IP Administration Center of Excellence, Room 4720, Houston, Texas 77042 (US).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR AN AUTOMATIC MILLING OPERATION




Fig. 1

(57) **Abstract:** A method (50) and an assembly (10) for milling an obstruction disposed within a wellbore (W) includes a milling module (12) having a motor (22) rotating a milling bit (14), a first electronics cartridge (26) for controlling the motor based upon a motor torque value, a tractor module (16, 18) for engaging with the wellbore and providing a push force against the wellbore to urge the milling assembly in a direction of the milling bit, and a second electronics cartridge (28) for controlling a push force value of tractor module. The method involves rotating the milling bit (54) and engaging the tractor module with the wellbore (56), and adjusting, iteratively, the operation (58) based on a calculated torque value and a calculated push force value to maintain the calculated values at around a target torque value and below a push force limit value (66, 70).

WO 2013/067263 A3 

UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

11 July 2013

METHOD AND SYSTEM FOR AN AUTOMATIC MILLING OPERATION

BACKGROUND

[0001] The present disclosure is related in general to wellsite equipment such as oilfield surface equipment, downhole assemblies, and the like.

[0002] Milling systems are utilized to mill scale deposits that have formed on interior portions of a wellbore or other wellbore obstructions. A benefit of using a wireline milling system is the ability to provide precision milling without mobilizing coiled tubing or heavy surface equipment for circulating and handling fluids. Without controlling the torque on bit, however, the rotary movement may cause to damage weak points in the tool-string or wellbore completion when producing too much torque on bit. Also, when the push force is not strong enough, the user may not realize that the rotary module is not cutting the scale, spinning freely. It is desirable to be able to conduct a milling operation automatically because even with real-time measurement of torque on bit, it may be difficult to operate the tool if the user has to change tractor push force manually. The operation may be time-consuming and cumbersome.

[0003] It is desirable to provide a convenient and intuitive tool control that provides tool protection at the same time. It remains desirable to provide improvements in oilfield surface equipment and/or downhole assemblies.

SUMMARY

[0004] The method according to the disclosure involves an algorithm to perform an efficient and intuitive milling operation in a wellbore, such as a cased-hole environment. The automatic milling algorithm achieves controlled material removal operation while minimizing unnecessary human interactions.

[0005] The automatic milling algorithm controls a milling assembly that utilizes at least one wheeled tractor module to push the bit of a milling module against the scale to generate weight on the bit. The automatic milling algorithm monitors a torque measurement from the motor in the milling module as a feedback to generate an appropriate push force from the tractor module. The algorithm tries to achieve a target torque value on the bit set by the user by automatically adjusting the tractor push force within predetermined limits also set by the user. The algorithm achieves efficient scale removal by minimizing stalling of the bit due to high reactive torque and allows the user to take appropriate actions (or make automatic adjustments) in cases of bit stall.

[0006] The milling assembly includes a first electronics cartridge that drives the motor rotating the bit and senses the motor torque to generate the real-time feedback signal. The milling assembly may include a second electronics cartridge that drives the tractor module to control the push force in response to the torque feedback signal. The milling assembly is connected to a suitable well access line such as a wireline cable, a length of coiled tubing or the like. The well access line extends from a surface of the wellbore and is in communication with surface equipment, control equipment, and the like. The automatic milling algorithm can be implemented as firmware and/or software located in one or more of the first electronics cartridge, the second electronics cartridge and the control equipment on the surface.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] These and other features and advantages will be better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings.

[0008] Fig. 1 is a cross-sectional view through a wellbore showing a milling or bottom hole assembly according to the disclosure.

[0009] Fig. 2 is a perspective view of the milling or bottom hole assembly shown in Fig. 1.

[0010] Fig. 3 is a flow diagram of the method for performing an automatic milling procedure according to the disclosure.

[0011] Fig. 4 is a log of a test of the milling assembly and procedure according to the disclosure.

DETAILED DESCRIPTION OF SOME ILLUSTRATIVE EMBODIMENTS

[0012] Referring now to Figs. 1 and 2, there is disclosed a milling assembly or bottom hole assembly, indicated generally at **10**. The assembly **10** comprises a rotary or milling module **12** for driving a mill bit **14** and a pair of tractor modules **16** and **18** for advancing the assembly **10** in a wellbore **W** and for providing force to the mill bit **14** during operation of the assembly **10**, discussed in more detail below.

[0013] The rotary or milling module **12** comprises a compensator **20**, a motor **22** and a gearbox **24**, which is coupled to or in communication with the mill bit **14**. An electronics cartridge **26** provides power and telemetry to and acquires or receives telemetry from the various components **14**, **20**, **22**, **24** of the rotary module **12**, and controls the operation of the rotary module. The motor **22** may comprise a three-phase permanent magnetic synchronous motor which is driven by the electronics cartridge **26**. The cartridge **26** may implement field-oriented control in its firmware.

[0014] An electronics cartridge **28** provides power and telemetry to and acquires or receives telemetry from the tractor modules **16** and **18**. The tractor modules **16** and **18** may each comprise pivotally extending arms **30** and **32** having wheels **34** and **36** on free ends thereof for rotating and engaging with the walls of the wellbore, such as an open hole or the cased wellbore **W** shown in Fig. 1, as will be appreciated by those skilled in the art. The tractor modules **16** and **18** may comprise a motor (not shown) such as an electric motor, a hydraulic motor or the like, for extending and retracting the arms **30** and **32** and for rotating and driving the wheels **34** and **36**. The assembly **10** may also comprise a compensator module **27** as a hydraulic oil reservoir used for opening the tractor arms **30** and **32**. When the wheels **34** and **36** are engaged with the wellbore, the tractor modules **16** and **18** provide a push force for the assembly **10** in the direction of the bit **14**. The electronic cartridges **26** and **28** are in communication with one another, which aids in the operation of the assembly **10**, discussed in more detail below. While the embodiments illustrated show a plurality of electronic cartridges **26** and **28**, those skilled in the art will appreciate that the electronics of the cartridges **26** and **28** may be combined into a single cartridge with the same functionality of each of the cartridges **26** and **28**. The assembly **10** may further comprise an additional push module or modules for providing a push force for the assembly **10** in the direction of the bit **14**, such as a linear actuator and anchor assembly for engaging with the wellbore in addition to or in lieu of the tractor modules **16** and **18** during operation of the assembly **10** discussed in more detail below.

[0015] The assembly **10** further comprises a logging head **38** on an end thereof opposite the end of the mill bit **14** and a telemetry cartridge **40** connected to the logging head **38**. The logging head **38** may be attached to a suitable well access line **42** such as a wireline cable, a length of coiled tubing or the like. The well access line **42** extends from a surface of the wellbore and is in communication with surface equipment, control equipment, and the like identified as a surface unit **44** for communication of power, telemetry and control signals. A user can direct operation of the assembly **10** from the surface unit **44** including setting a target torque value,

setting a push force limit value, starting rotation of the bit 14 and starting an automatic milling algorithm.

[0016] In operation, the assembly **10** is deployed into the wellbore on the well access line and maneuvered into a desired location within the wellbore. In those wellbores, such as horizontal or deviated wellbores or the like, the tractor modules **16** and **18** may be utilized to propel the assembly **10** to the desired location by engaging with the walls of the wellbore. At the desired location, an obstruction, such as a scale deposit or the like is disposed within the wellbore and the assembly **10** is utilized to remove the scale deposit, as outlined further hereinbelow.

[0017] The milling module **12** is engaged to rotate the bit **14**, and the arms **30** and **32** and the wheels **34** and **36** of the tractor modules **16** and **18** are engaged with the wellbore to move the assembly **10** such that the bit **14** engages with the obstruction or scale deposit. During operation of the milling module, the electronics cartridge **26** controls the speed of the motor **22**, and phase current samples from the motor **22** are used to control the torque output of the motor **22**. Based on the phase current samples, firmware in the electronics cartridge **26** calculates a torque value experienced on the shaft of the motor **22**. The calculated torque value is used to report real-time torque measurements to the surface via the telemetry cartridge **40** or the like. This calculated torque value is also used to request push force adjustment from the electronics cartridge **28** and the tractor modules **16** and **18**. The real-time torque measurement is available from the electronics cartridge **26** as it is driving the motor **22** in the rotary module **12**, and the torque information is communicated to the cartridge **28** at a fast enough rate to adjust a push force from the tractor modules **16** and **18**, as detailed further below.

[0018] There is shown in Fig. 3 a method for performing the automatic milling algorithm, or auto-mill algorithm, indicated generally at **50**. At a step **52**, a target torque on the bit and push force limit is set by the user, such as at a graphical user interface (not shown) or the like at the surface unit **44**. At a step **54**, the milling bit **14** is rotated at a desired speed. At a step **56**, the auto-mill algorithm is started. At

a decision point **58**, the auto-mill algorithm is evaluated to continue. If the algorithm is to stop (branch “No”), such as from a command from the user entered at the graphical user interface or the like, the algorithm is stopped at a step **60**. If the algorithm is to continue (branch “Yes”), at a decision point **62** the torque (calculated from the milling module **12**) is evaluated to determine if the target torque has been reached. If the target torque has been reached (branch “Yes”), then at a decision point **64**, the torque is evaluated to determine if it is greater than the target torque. If the calculated torque is not more than the target torque (branch “No”), the method **50** returns to the decision point **58** to evaluate if the auto-mill algorithm is to continue. If the target torque is greater than the target torque (branch “Yes”), the push force (on the tractor modules **16** and **18**, and/or on the linear actuator and anchor assembly or the like) is decreased at a step **66**, and the method **50** returns to the decision point **58** to evaluate if the auto-mill algorithm is to continue. If at the decision point **62** the target torque has not been reached (branch “No”), then, at a decision point **68**, the push force (on the tractor modules **16** and **18**) is evaluated to determine if the push force limit has been reached. If the push force limit has been reached (branch “Yes”), then the method **50** returns to the decision point **58** to evaluate if the auto-mill algorithm is to continue. If the push force limit has not been reached (branch “No”), then the push force (on the tractor modules **16** and **18**) is increased at a step **70**, after which the method **50** returns to the decision point **58** to evaluate if the auto-mill algorithm is to continue.

[0019] The electronics module **28** (such as with firmware or the like) adjusts the push force from the tractors **16** and **18** utilizing, for example, proportional-derivative control to regulate push force from the tractors **16** and **18** in response to rapidly varying torque values provided from the electronics module **26** of the rotary module **12**.

[0020] There is shown in Fig. 4 a log archived from testing of the milling operation in a flow-loop test fixture. The log demonstrates the automatic milling algorithm in action when the tool is cutting a rock located inside a test pipe. The line **80** in the middle column shows the tractor modules **16** and **18** automatically

adjusting the push force (e.g. point **82**) to achieve milling at around the target torque on the bit **14** set by the user (point **81**). However, as the tractor push force limit is also set by the user (as noted at step **52** in Fig. 3) the tractor push force is at the limit (maximum set by user shown at point **84**) when the torque on the bit is less than its target (point **83**). In such a case, the user may choose to increase the push force limit to try to increase the cutting speed of the bit **14** again.

[0021] If the bit **14** stalls during an operation (see point **85**), the automatic milling algorithm senses the stall condition and may take a few actions to free up the bit **14** again and thereby counteract the stall condition. For example, the automatic milling algorithm may pull the tractor modules **16** and **18** backward (such as by rotating the wheels **34** and **36** in an opposite direction to provide a push force for the assembly **10** in a direction away from the bit **14**) to reduce or reverse the push force (see point **86**) while the bit **14** is still locked into the scale. If reversing or pulling of the tractor modules **16** and **18** alone does not free up the bit **14**, the bit **14** may be rotated in the opposite direction to unlock the bit **14**. In some cases, pulling the tractor modules **16** and **18** backward and turning the bit **14** in the opposite direction may be applied simultaneously to unlock the bit. Some of these actions may be automated in firmware as part of the algorithm upon the detection of a stalled bit **14**.

[0022] The present disclosure describes an algorithm to perform an efficient and intuitive milling operation in a wellbore, such as a cased-hole environment. The automatic milling algorithm achieves controlled material removal operation while minimizing unnecessary human interactions.

[0023] The automatic milling algorithm utilizes a wheeled tractor to push the bit of the rotary module against the scale to generate weight on bit. The automatic milling algorithm monitors torque measurement from the rotary module as a feedback to generate an appropriate push force from the tractor tool. The algorithm tries to achieve a target torque on the bit set by the user by automatically adjusting the tractor push force within predetermined limits also set by the user. The algorithm achieves efficient material removal by minimizing stalling of the bit due to

high reactive torque and allows the user to take appropriate actions (or make automatic adjustments) in cases of bit stall. The automatic milling algorithm can be implemented as firmware and/or software located in one or more of the first electronics cartridge **26**, the second electronics cartridge **28** and the surface unit **44**.

[0024] The preceding description has been presented with reference to present embodiments. Persons skilled in the art and technology to which this disclosure pertains will appreciate that alterations and changes in the described structures and methods of operation can be practiced without meaningfully departing from the principle, and scope of this invention. Accordingly, the foregoing description should not be read as pertaining only to the precise structures described and shown in the accompanying drawings, but rather should be read as consistent with and as support for the following claims, which are to have their fullest and fairest scope.

We claim:

1. A method (50) for milling an obstruction disposed within a wellbore (W), comprising:

providing a milling assembly (10) for use in the wellbore (W), the milling assembly including a milling module (12) having a motor (22) rotating a milling bit (14), an electronics cartridge (26, 28) for controlling the motor and calculating a torque value based on data received from the motor, at least one push module (16, 18) for engaging with the wellbore and providing a push force against the wellbore to urge the milling assembly in a direction of the milling bit, the electronics cartridge further configured for controlling the at least one module and calculating a push force value for the at least one module;

setting a target torque value for the milling module and setting a push force limit value for the at least one module (52);

disposing the milling assembly into the wellbore;

disposing the milling bit adjacent the obstruction in the wellbore;

operating the milling assembly by rotating the milling bit and engaging the at least one module with the wellbore (54); and

adjusting, iteratively, operation (56, 58) of the milling module and the at least one push module based on the calculated torque value and the calculated push force value to maintain the calculated values at about the target torque value and at or below the push force limit value (66, 70).

2. The method according to Claim 1 wherein the milling module motor (22) is an electric motor.

3. The method according to Claim 1 wherein the at least one push module comprises at least two push modules (16, 18).

4. The method according to Claim 1 wherein the at least one module comprises a tractor module (16, 18) comprising a wheeled tractor assembly having wheels (34, 36) disposed on arms (30, 32) pivotally extending from the at least one tractor module, and including operating the at least one tractor module to engage the wheels with the wellbore (W).

5. The method according to Claim 1 including determining a stall condition (64) of the milling bit (14) and adjusting the operation (66) of at least one of the milling module (12) and the at least one module (16, 18) to counteract the stall.

6. The method according to Claim 5 wherein the step of adjusting the operation to counteract the stall includes moving the at least one module (16, 18) backward to provide a push force (66) in a direction away from the milling bit (14).

7. The method according to Claim 5 wherein the step of adjusting the operation to counteract the stall includes reversing a direction of rotation of the milling bit (14).

8. The method according to Claim 5 wherein the step of adjusting the operation includes moving the at least one module (16, 18) backward to provide a push force (66) in a direction away from the milling bit (14) and simultaneously reversing a direction of rotation of the milling bit (14).

9. The method according to Claim 1 wherein the step of adjusting the operation includes the following steps:

comparing the calculated torque value with the target torque value (62);

if the target torque value has been reached, determining whether the calculated torque value is greater than the target torque value (64);
and

if the calculated torque value is greater than the target torque value, decreasing the push force (66).

10. The method according to Claim 1 wherein the step of adjusting the operation includes the following steps:

comparing the calculated torque value with the target torque value (62);

if the target torque value has not been reached, determining whether the push force limit value has been reached (68); and

if the push force limit value has not been reached, increasing the push force (70).

11. An assembly (10) for milling an obstruction disposed within a wellbore (W), comprising:

a milling module (12) having a motor (22) rotating a milling bit (14) mounted at one end of the assembly (10);

a first electronics cartridge (26) for calculating a torque value based on data received from the motor (22) and operating the motor (22) in response to a comparison of the calculated torque value with a target torque value;

at least one push module (16, 18) for engaging with the wellbore (W) and providing a push force against the wellbore to urge the milling assembly in a direction of the milling bit (14); and

a second electronics cartridge (28) for calculating a push force value based on data received from the at least one module (16, 18) and operating the at least one push module in response to a comparison of the calculated push force with a push force limit value, the first and

second electronics cartridges communicating for performing the comparisons iteratively to maintain the calculated torque value and the calculated push force value at about the target torque value and below the push force limit value respectively.

12. The assembly according to Claim 11 wherein the motor (22) is an electric motor.

13. The assembly according to Claim 11 including a gearbox (24) connected between the motor (22) and the milling bit (14).

14. The assembly according to Claim 11 wherein the at least one push module comprises at least two push modules (16, 18).

15. The assembly according to Claim 11 wherein the at least one push module (16, 18) comprises a wheeled tractor assembly having wheels (34, 36) disposed on arms (30, 32) pivotally extending from the at least one tractor module.

16. The assembly according to Claim 11 including a compensator module (27) connected between the at least one push module (16, 18) and the first electronics cartridge (26).

17. The assembly according to Claim 16 wherein the compensator module (27) is a hydraulic oil reservoir for use with a hydraulic motor to pivot arms (30, 32) of the at least one tractor module (16, 18).

18. The assembly according to Claim 11 including a logging head (38) mounted at an opposite end of the assembly (10) from the one end at which the milling bit (14) is mounted.

19. The assembly according to Claim 18 including a telemetry cartridge (40) connected to the logging head (38).

20. The assembly according to Claim 19 including an access line (42) connecting the logging head (38) with a surface unit (44) for communication of power, telemetry and control signals.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 1