PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: C11B 11/00, C08L 91/06, A23D 9/00, 9/02

(11) International Publication Number:

WO 98/45390

(43) International Publication Date:

15 October 1998 (15.10.98)

(21) International Application Number:

PCT/AU98/00234

A1

(22) International Filing Date:

7 April 1998 (07.04.98)

(30) Priority Data:

PO 6050

7 April 1997 (07.04.97)

ΑU

(71) Applicants (for all designated States except US): JAMES COOK UNIVERSITY OF NORTH QUEENSLAND [AU/AU]; Townsville, QLD 4811 (AU). CSR LIMITED [AU/AU]; Level 6, Hall Chadwick Building, 46 Edward Street, Brisbane, QLD 4000 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VALIX, Marjorie, Gan [AU/AU]; 26 Andrews Street, West Ryde, NSW 2114 (AU).

(74) Agent: CULLEN & CO.; Level 12, 240 Queen Street, Brisbane, QLD 4000 (AU).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: FOOD GRADE WAX AND PROCESS FOR PREPARING SAME

(57) Abstract

The invention provides a wax composition which can be used in comestibles. The wax composition is obtained from sugar cane and comrpises wax esters, aldehydes, tri-glycerides, alcohols, free fatty acids, sterols and polar lipids. A process for preparing a wax composition from crude sugar cane wax, the process comprising the steps of: (i) heating a solution of the crude wax with a lower alcohol as sovlent at the boiling point of the solvent; (ii) allowing phase separation of the solution from (i) and decanting the upper phase while hot; (iii) allowing the separated phase from (ii) to cool and separating crystallised wax from the solvent; (iv) repeating steps (i) to (iii) using the wax from (iii) until all pitch has been removed from the wax; (v) heating the wax to between 90 and 140 °C and oxidising molten wax with oxidising material; and (vi) continuing the heating under and inert gas on completion of the oxidation step until intermediate peroxide products are removed.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
ВJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	$\mathbf{z}\mathbf{w}$	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

WO 98/45390 PCT/AU98/00234

FOOD GRADE WAX AND PROCESS FOR PREPARING SAME TECHNICAL FIELD

This invention relates to a wax composition suitable for use in comestibles. The invention also relates to a process for preparing the composition.

BACKGROUND ART

5

10

15

20

25

30

Many comestibles include waxes added during preparation of the comestible. For example, wax is a component of chewing gum base. Waxes can also be used as protective coatings on comestibles such as cheeses and fruits. The waxes used for such purposes are typically mineral waxes such as montan wax extracted from lignites, peat waxes, ceresin wax and petroleum waxes. Among these mineral waxes, it appears that only petroleum based waxes are used in food applications: microcrystalline waxes, high melting point waxes and high sulfur microcrystalline waxes in particular. The US Food and Drug Administration (FDA) has established regulations for the use of petroleum wax (see 21 CFR 172.886 and 178.3710) and Japanese authorities consider petroleum waxes to be natural products and allows their use in products such as chewing gum. Although montan wax is not used directly in food applications, it is used in plastic processing such as plastic containers and wrappings which will come or may come into contact with food.

Use of mineral waxes in comestibles is undesirable. Mineral waxes are extracted from coal and crude petroleum oil. These raw materials contain organic chemicals which are toxic to humans. The food applicability of the waxes depends on the degree of refining or purification achieved and its usage has been regulated according to the specifications provided by authorities such as Ministry of Agriculture, Fisheries and Food, UK (The Mineral Hydrocarbons in Food Regulation, SI 1966 No. 1073. This regulation applies to England and Wales only, though similar regulations apply to Scotland and Northern Ireland). The refining achieved has been acceptable to food regulating authorities. However, recent studies have suggested toxicological effects of petroleum based waxes ("Recommendations on the use of mineral hydrocarbon in food", Food Advisory Committee 8/93, UK) and

10

15

20

25

30

the hydrocarbon imparted by packaging using mineral hydrocarbon waxes on food (Progress Report of the Working Party on Chemical Contaminants from Food Contact Materials: 1988 to 1992; Food Surveillance Paper No. 38, Ministry of Agriculture of Fisheries and Food). The Ministry of Agriculture, Fisheries and Food is at present reviewing studies on the toxicological impact of using petroleum based waxes as food additives and as a processing aid to update regulation of the usage of these waxes in food applications (Ministry of Agriculture of Fisheries and Food News Release 278/93 of 19 August 1993).

Waxes of plant origin are known. Indeed, the palm *Copernicia cerifera* is a source of the common wax, carnauba. Waxes can also be extracted from sugar cane and rice. Subject to the conditions used for extraction, waxes of plant origin should provide an alternative to mineral waxes for use in comestibles.

Sugar production results in a number of by-products, one of which is mill mud. Mill mud comprises crude wax and fats, fibre, sugar, crude protein and ash (SiO_2 , CaO, P_2O_5 and MgO). A crude cane wax can be extracted from mill mud. However, the crude wax is unsuitable for use in comestibles as it has a foul odour and taste and is dark green to brown in colour due to the presence of contaminants. US Patent No. 2,464,189 describes a process for the refining of sugar cane wax. However, wax produced by this process is unsuitable for use in comestibles for the following reasons:

- 1) The refining process is not complete. The process is only a fractionation step which removes a resinous fraction (pitch) from the sugar cane wax. The wax colour still has to be removed and stabilised. The patentees suggested further processing—for example, bleaching with acid, decolourisation, emulsification (see Example 3, line 40).
 - 2) The reagent used in the process (acetone) is not food grade.
- 3) Bleaching uses reagents such as chromic and sulfuric acid which are not food grade reagents.

Since by-products of sugar production are plentiful in countries such as Australia, it would be desirable to have a process for producing a wax from such by-product (i.e., mill mud) suitable for use in comestibles.

10

20

25

SUMMARY OF THE INVENTION

The object of this invention is to provide a sugar cane wax composition, and a process for preparing the composition, which wax is suitable for use in comestibles.

In one aspect, the invention provides a wax composition comprising on a weight basis: wax esters, 6.2–11%; aldehydes, 2.8–9.5%; triglycerides, 0–3.0%; alcohols, 1.8–44.5%; and, free fatty acids, sterols and polar lipids, 36.8–87.2%.

In a second aspect, the invention provides a process for preparing a wax composition from crude sugar cane wax, the process comprising the steps of:

- i) heating a solution of the crude wax with a lower alcohol as solvent at the boiling point of the solvent;
- ii) allowing phase separation of the solution from (i) and decanting15 the upper phase while hot;
 - iii) allowing the separated phase from (ii) to cool and separating crystallised wax from the solvent;
 - iv) repeating steps (i) to (iii) using the wax from (iii) until all pitch has been removed from the wax:
 - v) heating the wax to between 90 and 140°C and oxidising molten wax with oxidising material; and
 - vi) continuing the heating under an inert gas on completion of the oxidation step until intermediate peroxide products are removed.

In other aspects, the invention provides the wax composition product of the process according to the second aspect and comestibles which include a wax composition according to the first aspect or as the product of the process according to the second aspect.

BEST MODE AND OTHER MODES FOR CARRYING OUT THE INVENTION

The inventor has found that a wax composition suitable for inclusion in comestibles can be obtained from sugar cane. The composition is essentially odourless and colourless, desirable properties for compositions used as a comestible base or for coating comestibles.

Typical components of the wax composition according to the first aspect of the invention are set out in Table I below. The numbers in the table are the numbers of carbon atoms typically found in a member of a functional group. However, it will be appreciated that a member of a group may have a number of carbon atoms falling outside the indicated range. Members of groups are mostly straight chain saturated and unsaturated hydrocarbons.

Table I
Components of Groups of The Wax Composition

Functional Groups	Typical Components
Wax Esters	C16 (fatty acid)–C24(alcohol)–C16 (fatty acid)–C36 (alcohol)
Aldehydes	C28-C36
Tri-Glycerides	T48–T54 (total number of carbon in the acyl group) or C16–C18 (number of carbons in each acyl group)
Alcohols	C24-C36
Free Fatty Acid	C24-C36
Alkanes	C25-C35

10

15

The polar lipids in the wax are essentially amphipathic molecules, having a hydrophobic fatty acid part and a hydrophilic domain. The three which are commonly found are *phosphoglycerides*, in which fatty acids are esterified with an alcohol (glycerol) which contain a phosphate group, *glycosyl diglycerides* in which the fatty acids are esterified with an alcohol (glycerol) which contains a carbohydrate (sugars) and *sphingolipids* in which the fatty acids are esterified with an alcohol (glycerol) which contains amino groups.

As indicated above in the description of the second aspect, the method

the oil which remains soluble in the organic solvent. The wax is filtered until

of refining the crude sugar cane wax involves heating the crude wax with an organic solvent to allow the pitch and the paler wax fraction to separate.

These form two distinct phases, which can be separated by decantation. The paler wax fraction is cooled to allow the wax to crystallise and separate from

10

15

20

25

30

dry. The wax is melted over a hot bath and oxidised by blowing fine air bubbles through a sparger. This is continued until oxidation is complete noticeable by lack of any further increase in temperature—arising from the exothermic nature of the reaction—and colour change.

The solvent used in step (i) of the process is typically ethanol or isopropanol which have boiling points of 78.5°C and 82.4°C, respectively. The crude wax is typically combined with solvent at a ratio of one part (by weight) wax to nine parts solvent although ratios of 1:8 to 1:20 can also be used. Heating can be for 5 to 60 minutes although a heating time of about 30 minutes is usually adequate.

As indicated above, the upper phase formed in step (ii) contains the wax of interest. The lower phase is a resinous fraction referred to as "pitch" which contains wax of lower quality.

In step (iii), filtration or centrifugation are advantageously used to separate wax from oil-containing solvent. However, other methods known to those of skill in the art can be used.

Steps (i) to (iii) are repeated from 2 to typically no more than 5 times. The number of times the steps are repeated largely depends on the amount of pitch present in the crude wax, the rate with which the pitch settles and the rate of wax crystallisation. It appears that pitch that does not settle fast enough is occluded within the wax crystals.

The heating of the wax in step (v) of the process is advantageously carried out under an oxygen-free gas. This allows better control over the oxidation of the wax which is not initiated until the composition reaches the desired temperature. The oxygen-free gas is typically an inert gas such as nitrogen.

The oxidising material used in step (V) can be chromic acid, potassium permanganate, transition metals such as salts of noble metals such as platinum and palladium, pentavalent vanadium, cobalt (III), cerium (IV) thallium (III), mercury (II), cupric solutions, specific enzymes, and oxygen gas (see R. Stewart, "Oxidation Mechanisms, Application to Organic Chemistry", W.A. Benjamin Inc., 1964). Preferred oxidising materials are air, oxygen, or mixtures of oxygen, nitrogen and ozone.

10

15

20

25

30

With regard to the final step of the process, step (vi), one of skill in the art would be able to determine when removal of the intermediate peroxide products is complete. Completion typically takes from 30 minutes to 2 hours. However, longer or shorter periods can be used depending on the degree of oxidation achieved. The inert gas used in this step is typically nitrogen.

In step (v) of the process, oxidation can be enhanced by using a catalyst. Suitable catalysts include cobalt or manganese borates and resinates (A.J.C. Andersen, *Refining of Oils and Fats for Edible Purposes*, Second Revised Edition, P.N. Williams, ed., Pergamon Press, 1962), ferrous salts, and Fenton's reagent which consists of ferrous salts and H₂0₂ (Roger A Sheldon and Jay K. Kochi, *Metal Catalyzed Oxidations of Organic Compounds*, Academic Press, 1981).

The wax compositions obtained from step (vi) of the process according to the second aspect of the invention can be further decolourised, if desired, with adsorbents or by pitch inducement. Each of these methods will now be briefly described.

Use of Adsorbents

Suitable adsorbents include activated carbons, resins, activated alumina and silica. Carbons obtained from commercial sources are satisfactory and with a wax to carbon ratio of 1:3 white wax can be produced. It is also possible to manufacture carbons that are selective towards a particular colour.

The following are typical steps in the decolourisation of the wax composition with activated carbon:

- a) Wax from step (v) is heated with a lower alcohol as solvent at the boiling point of the solvent for 30 to 60 minutes with wax to activated carbon ratios of between 1:0.5 and 1:3.
- b) The molten slurry is filtered hot.
- c) The wax and solvent recovered is cooled until the wax crystallises and is separated by filtration.

Pitch Inducement

In the pitch inducement method, colour can be removed without the use of adsorbents. The method involves heat treatment and fractionation

which results in waxes of various intensity of colour from a golden yellow to cream.

Typical steps in the reduction of the colour of the wax composition with pitch inducement follow.

5

- (a) Wax from step (v) is heated with a lower alcohol as solvent at the boiling point of the solvent for 30 to 60 minutes.
- (b) The phases of the solution from (a) are separated and the upper phase decanted while hot.

10

- (c) The separated upper phase from (b) is allowed to cool and the crystallised wax separated from the solvent.
- (d) Wax from (c) is heat treated at 80 to 110°C in the absence of solvent for typically 15 minutes to 3 hours.
- (e) Steps (a) to (d) are repeated until the desired colour grade is achieved.

15

The crude sugar cane wax can be prepared by methods known to those of skill in the art. A suitable method is described, for example, in US Patent No. 2,508,002, the entire content of which is incorporated herein by cross-reference. A brief description of a suitable process follows.

Crude Wax Extraction

20

25

Sugar filter cake is steam heated and charged to a continuous reactor where it is mixed with solvent (naphtha) and held at the desired temperature and pressure. Wax is extracted into the solvent, which is subsequently separated from the filter cake. The separated wax-containing solvent is then passed through a flash drum and an evaporator to separate the crude wax from the solvent. The resulting filter cake is then steam stripped to recover residual solvent.

The composition of crude sugar cane wax is typically as presented in Table II.

Table II

Composition of Crude Sugar Cane Wax

Component	Composition
	(% w/w)
Wax Ester	5.9–8.5
Alkyl Ketone	3.2–1.6
Tri-Glyceride	0–1.6
Alcohol	7.9–8.3
Free Fatty Acid/Sterol	5.9–7.8
Polar Lipid	73.2–76.1

Advantages of the wax composition according to the invention and the process for preparing the composition are as follows:

- 1) The process produces a potential food grade vegetable wax product, which can be used as a replacement for mineral waxes in a number of food or non-food applications, including (but not limited to) chewing gum base, cheese coating, and fruit coating.
- 10 2) The process is simple and of low cost and enables economic use of wax for applications indicated in (1).
 - 3) The wax product is colourless or has low colour (pale yellow) and little or no odour and taste.
 - 4) The wax product has a hardness comparable to carnauba wax.
- 15 5) The wax product has good temperature stability as compared to other vegetable waxes, such as carnauba and rice wax.

Having broadly described the invention, examples of the preparation of wax composition will now be given.

Example 1

Multiple portions of wax composition were prepared as follows: one hundred grams of crude sugar cane wax was combined with 900 grams of ethanol in a round bottom flask. The mixture was heated in a heating mantle

10

15

20

to 78.5°C for 30 minutes under reflux. The solution was removed from the heating mantle and the phases of pitch and the paler wax were allowed to separate. The paler wax was decanted into another round bottom flask while the wax mixture was still in solution or only partially crystallised at 65 to 75°C. The mixture was again heated to 78.5°C for 10 minutes. The paler wax was decanted to separate it from the pitch. The heating and separation processes were repeated about four times or until no visible pitch separated from the paler wax. The pitch was reheated with about 100 grams of ethanol to recover additional paler wax. This was combined with the previously collected paler wax. The paler wax was then cooled slowly to room temperature and then in an ice bath. The cooled wax was filtered and remelted in a hot bath, in the presence of nitrogen, at a temperature between 90 and 140°C. Air or ozone was blown into the molten wax by means of a sparger until the temperature of the wax stabilised to a constant value or until there was no further visible change in the colour of the wax. The overall process was executed within several hours depending on the temperature and air distribution.

Wax composition produced by the above process had the following properties: pale yellow in colour with a sweet smell and little or no taste. The compositions of waxes are summarised in the following table.

Table III

Components of Wax Compositions of Example 1

Component	Composition (% w/w)			
	Ethanol fractionated then oxidised with air	Ethanol fractionated then oxidised with ozone		
Wax Ester	6.2–11	6.2–7.7		
Aldehyde	8.1–9.5	2.5–9.5		
Tri-Glyceride	0.5–3.0	0.5–3		
Alcohols	11.5–44.5	1.8–44.5		
Free Fatty Acid + Sterol + Polar Lipid	36.8–70	36.8–87.2		

15

20

The make-up of the composition obtained following the oxidation step depends on the extent of oxidation. If complete oxidation is achieved, the only substantial component left will be free fatty acid. However, oxidation needs to be only to the extent that sufficient colour is removed.

5 Example 2

Multiple portions of wax composition were again prepared. One hundred grams of crude sugar cane wax was combined with 900 grams of isopropanol in a round bottom flask. The mixture was heated in a heating mantle to 82.4°C. The mixture was cooled slowly to room temperature and then in an ice bath. The wax was filtered and transferred into another round bottom flask. To the wax, 450 grams of ethanol was added and the mixture heated to 78.5°C for 30 minutes. Fractionation and oxidation of this wax was carried out as in Example 1.

Wax composition produced by the above process had the following properties: pale yellow in colour with a sweet smell and little or no taste. Compositions obtained are summarised in the following table.

Table IV

Components of Wax Compositions of Example 2

Component	Composition (% w/w)
Wax Ester	10.5–11
Aldehyde	7.4–8.1
Tri-Glyceride	0–0.6
Alcohols	11.5–18.8
Free Fatty Acid + Sterol + Polar Lipid	63.4–70

Yields of fractions produced using processes such as described in Examples 1 and 2 are presented in Table V.

Table V
Fractionation Yield

Fraction	Yield (%)		
	Example 1	Example 2	
Oil	24–30	53–55	
Pitch	26–35	20–25	
Wax Composition	34–48	20–25	

It will be appreciated that many changes can be made to the processes and compositions as exemplified above without departing from the broad ambit and scope of the invention.

CLAIMS

- 1. A wax composition comprising on a weight basis: wax esters, 6.2-11%; aldehydes, 2.8–9.5%; tri-glycerides, 0–3%; alcohols, 1.8–44.5%; and, free fatty acids, sterols and polar lipids, 36.8-87.2%.
- 2. 5 A process for preparing a wax composition from crude sugar cane wax, the process comprising the steps of:
 - heating a solution of the crude wax with a lower alcohol as i) solvent at the boiling point of the solvent;
- allowing phase separation of the solution from (i) and decanting 10 the upper phase while hot:
 - iii) allowing the separated phase from (ii) to cool and separating crystallised wax from the solvent;
 - iv) repeating steps (i) to (iii) using the wax from (iii) until all pitch has been removed from the wax;
 - V) heating the wax to between 90 and 140°C and oxidising molten wax with oxidising material; and

15

- vi) continuing the heating under an inert gas on completion of the oxidation step until intermediate peroxide products are removed.
- 3. The process according to claim 2, wherein said lower alcohol is 20 ethanol or iso-propanol.
 - 4. The process according to claim 2, wherein said crude wax is combined with solvent at a ratio of 1:8 to 1:20 by weight.
 - 5. The process according to claim 4, wherein said ratio is 1:9.
- 6. The process according to claim 2 wherein in step (i) said solution is 25 heated for 5 to 60 minutes.
 - 7. The process according to claim 6, wherein said solution is heated for about 30 minutes.
 - The process according to claim 2, wherein in step (iii) said separation is by filtration or centrifugation.
- 30 9. The process according to claim 2, wherein steps (i) to (iii) are repeated from 2 to 5 times.
 - 10. The process according to claim 2, wherein in step (v) said heating is carried out under an oxygen-free gas.

- 11. The process according to claim 10, wherein said gas is nitrogen.
- 12. The process according to claim 2, wherein said oxidising material of step (v) is selected from the group consisting of air, oxygen, and mixtures of oxygen, nitrogen and ozone.
- 5 13. The process according to claim 2, wherein in step (v) said oxidation is carried out in the presence of a catalyst.
 - 14. The process according to claim 10, wherein said catalyst is selected from the group consisting of a borate or resinate of cobalt or manganese, ferrous salts, and Fenton's reagent.
- 10 15. The process according to claim 2 comprising the further steps of:
 - vii) heating wax from step (vi) with a lower alcohol as solvent at the boiling point of the solvent with activated carbon present at a wax to carbon ratio of 1:0.5 to 1:3;
 - viii) filtering the molten slurry while hot;
- 15 ix) allowing the recovered wax/solvent mixture to cool and separating crystallised wax therefrom.
 - 16. The process according to claim 2 comprising the further steps of:
 - (vii) heating wax composition from step (vi) with a lower alcohol as solvent at the boiling point of said solvent for 30 to 60 minutes;
- 20 (viii) allowing phase separation of the solution from (vi) and decanting the upper phase while hot;
 - (ix) allowing the separated upper phase from (viii) to cool and separating crystallised wax from said solvent;
 - (x) heating wax from (ix) in the absence of solvent for 15 minutes to 3 hours; and
 - (xi) repeating steps (vii) to (x) until the desired degree of decolourisation is achieved.
 - 17. A comestible which includes the wax composition of claim 1.

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/AU 98/00234

A.	CLASSIFICATION OF SUBJECT MATTER			
Int Cl ⁶ :	C11B 11/00; C08L 91/06; A23D 9/00, 9/02			
According to International Patent Classification (IPC) or to both national classification and IPC				
В.	FIELDS SEARCHED			
	mentation searched (classification system followed by C11B 11/00; A23D 9/00, 9/02	classification symbols)		
Documentation	searched other than minimum documentation to the ex	stent that such documents are included in	the fields searched	
Electronic data WPAT	base consulted during the international search (name of	of data base and, where practicable, search	terms used)	
C.	DOCUMENTS CONSIDERED TO BE RELEVAN	г		
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.	
A	Derwent Abstract Accession No: 92-111526 057894 A (KOBAYASHI KOSE KK) 25 Fe Abstract	, , , , ,	1	
A	Derwent Abstract Accession No: 51771C-30 (HENKEL KG AUF AKTIEN) 17 July 1980 Abstract		1	
A	Derwent Abstract Accession No: 95-085711 JP 07-011285 A (NISSHIN OIL MILLS LT Abstract		2-17	
X	Further documents are listed in the continuation of Box C	See patent family an	nex	
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention cannot be considered novel or cannot be considered to involve an inventive step when the document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document combined with one or more other such documents, such combination being obvious to a person skilled in the art document member of the same patent family			the application but cited to derlying the invention e claimed invention cannot sidered to involve an taken alone claimed invention cannot e step when the document is the documents, such on skilled in the art	
Date of the actual completion of the international search Date of mailing of the international search report			ch renort	
1 May 1998		6 May 1998		
AUSTRALIAN PATENT OFFICE PO BOX 200		Authorized officer GAYE HOROBIN		
WODEN ACT 2606 AUSTRALIA Faccimile No.: (02) 6285 3929		Telephone No.: (02) 6283 2069		

INTERNATIONAL SEARCH REPORT

i. rnational Application No.

PCT/AU 98/00234

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
	Derwent Abstract Accession No: 94-269708/33, Class D23, JP 06-200289 A (NIPPON			
	PETROCHEMICALS CO LTD) 19 July 1994			
A	Abstract	2-17		
	Derwent Abstract Accession No: 94-269706/33, Class D23, JP 06-200287 A (NIPPON PETROCHEMICALS CO LTD) 19 July 1994			
A	Abstract	2-17		
		<u> </u>		