




(86) Date de dépôt PCT/PCT Filing Date: 2001/10/30
(87) Date publication PCT/PCT Publication Date: 2002/06/06
(45) Date de délivrance/Issue Date: 2009/03/17
(85) Entrée phase nationale/National Entry: 2003/05/16
(86) N° demande PCT/PCT Application No.: US 2001/042844
(87) N° publication PCT/PCT Publication No.: 2002/044318
(30) Priorité/Priority: 2000/11/28 (US60/253,134)

(51) Cl.Int./Int.Cl. *C12M 1/32* (2006.01),
C12M 1/00 (2006.01), *C12M 1/12* (2006.01),
C12M 3/00 (2006.01), *C12M 3/06* (2006.01),
C40B 60/00 (2006.01)
(72) Inventeurs/Inventors:
HUBERMAN, TAMIR, IL;
SCHIFFENBAUER, Yael, IL
(73) Propriétaire/Owner:
CELL KINETICS LTD., IL
(74) Agent: INTEGRAL IP

(54) Titre : GRILLES PORTEUSES DE CELLULES AMELIOREES
(54) Title: IMPROVED CELL CARRIER GRIDS

20



(57) Abrégé/Abstract:

An improved cell carrier grid (20). The grid (20) is capable of containing and retaining individual living cells in an array discrete locations and includes a body (22) that defines having an ordered array (24) of holes (26) is identifiable. Each of said holes (26) can

(57) **Abrégé(suite)/Abstract(continued):**

contain at least a portion of an individual living cell. According to some embodiments of the invention, individual cells contained within said holes (26) reside substantially in a single focal plane so that accuracy of data collected is increased. According to some embodiments of the invention, said body (22) is at least partially coated with a biologically active material (58). According to some embodiments of the invention, said body (22) is designed and constructed such that the individual cells contained within said holes (26) are recoverable by a recovery device.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 June 2002 (06.06.2002)


PCT

(10) International Publication Number
WO 02/44318 A1

- (51) International Patent Classification⁷: **C12M 1/32**, 1/12
- (21) International Application Number: PCT/US01/42844
- (22) International Filing Date: 30 October 2001 (30.10.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/253,134 28 November 2000 (28.11.2000) US
- (71) Applicant (for all designated States except US): **MEDIS EL LTD.** [IL/IL]; Shabazi Street 14, Yehud (IL).
- (71) Applicant (for TJ only): **FRIEDMAN, Mark, M.** [US/IL]; Alharizi Street 1, Raanana (IL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HUBERMAN, Tamir** [IL/IL]; 3 David Kind Street, Rehovot (IL). **SCHIFFENBAUER, Yael** [IL/IL]; Poleg Street 152, Raosh Ha-ayin (IL).
- (74) Common Representative: **FRIEDMAN, Mark, M.**; c/o Discovery Dispatch, 9003 Florin Way, Upper Marlboro, MD 20772 (IL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report

[Continued on next page]

(54) Title: IMPROVED CELL CARRIER GRIDS



(57) **Abstract:** An improved cell carrier grid (20). The grid (20) is capable of containing and retaining individual living cells in an array discrete locations and includes a body (22) that defines having an ordered array (24) of holes (26) is identifiable. Each of said holes (26) can contain at least a portion of an individual living cell. According to some embodiments of the invention, individual cells contained within said holes (26) reside substantially in a single focal plane so that accuracy of data collected is increased. According to some embodiments of the invention, said body (22) is at least partially coated with a biologically active material (58). According to some embodiments of the invention, said body (22) is designed and constructed such that the individual cells contained within said holes (26) are recoverable by a recovery device.

WO 02/44318 A1

WO 02/44318 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments* *For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

IMPROVED CELL CARRIER GRIDS

FIELD AND BACKGROUND OF THE INVENTION

The present invention relates to improved cell carrier grids and, more particularly, to cell carrier grids coated with biologically active materials and to cell carrier grids designed and constructed to hold cells in a single focal plane for analysis. The present invention further relates to cell carrier grids which allow recovery of individual cells based upon the results of analyses conducted thereupon.

Because of the complex nature of biological systems, it is often desirable to conduct analyses on a specific sample to compare to normative values. For example, liver enzyme levels from a specific patient compared to normative values for the same enzyme may be used to diagnose diabetes.

Further, it is often desirable to assay cells taken from a specific organ or tissue in order to diagnose a condition in a patient. In some cases, a sample may contain a physiologically mixed population of cells, only a portion of which is to be analyzed. Machines such as a fluorescence activated cell sorter (FACS) were designed, in part, to overcome this problem. However, a FACS machine cannot reassay individual cells after sorting. This limitation precludes both kinetic studies of individual cells and recovery of individual cells after assay based upon assay results.

Therefore, a number of prior art devices were patented by Weinraub et al. to address some of these issues. (U.S. Pat. Nos. 4,729,949; 5,272,081; 5,310,674; and 5,506,141)

U.S. Pat. No. 4,729,949 teaches methods and apparatus for performing analyses on individual living cells. According to the teachings of this patent, individual cells are forced into holes in a grid so that each of the cells may be individually assayed and re-assayed. The teachings of this patent do not provide means for assuring that all cells are held in a single focal plane during their residence in the grid and subsequent assay. As a result, practice of the teachings of this patent introduces inaccuracy into the measurements. In addition, the grid taught by this patent is biologically inert.

U.S. Pat. No. 5,310,674 is similar except that it teaches an ordered array of holes of two different sizes so that sorting of cells by size into two subpopulations is theoretically feasible. Teachings of this patent do not explain why a large cell will not be retained in a small hole when suction is applied therethrough.

5 U.S. Pat. No. 5,272,081 teaches identification and subculture of a selected subgroup of cells residing in a grid of the type taught in U.S. Pat. No. 4,729,949. Therefore, the same inherent drawbacks are present in the teachings of this patent.

U.S. Pat. No. 5,506,141 is similar to U.S. Pat. No. 4,729,949 except that it teaches that "the positions on the carrier of the holes are identifiable."

10 U.S. Pat. No. 4,772,540 to Deutsch et al. teaches a method of manufacture for a rigid grid resistant to mechanical distortion. Despite the added strength, grids produced according to the teachings of Deutsch do not hold cells in a single focal plane.

U.S. Pat. No. 6,103,479 issued to Taylor teaches coating of miniaturized
15 cell arrays with biologically active compounds in conjunction with an apparatus for cell-based screening concerning the physiological response of the cells to the biologically active compounds. Teachings of this patent do not include keeping cells in a single focal plane to increase accuracy of analysis. Similarly, analysis and subsequent collection of individual cells based upon assay results is not taught
20 by this patent.

U.S. Pat. No. 5,635,363 issued to Altman et al. teaches the use of multimeric MHC-antigen complexes to form a stable structure with T-cells. Teachings of this patent do not include binding and subsequent assay of individual T-cells in order to allow for the labeling, identification and separation of specific
25 T cells.

There is thus a widely recognized need for, and it would be highly advantageous to have, cell carrier grids devoid of the above limitations.

SUMMARY OF THE INVENTION

According to one aspect of the present invention there is provided a cell carrier grid capable of containing and retaining individual living cells in an array of predefined discrete locations. The cell carrier grid comprises (a) a body that
5 defines a first and a second outer surface, the body having an ordered array of holes therethrough, each of the holes communicating between the first outer surface and the second outer surface; (b) an organizational plan, the plan being applied to the positioning of the holes on the body such that a position of each of the holes is identifiable so that the holes form the array of predefined discrete
10 locations. Each of the holes is sized to contain at least a portion of an individual living cell therewithin, in that each hole has: (i) a first cross section at the first outer surface of such dimensions that at least a portion of the individual living cell can pass through the first cross section without suffering substantial damage; (ii) a second cross section at a level intermediate between the first and the second outer
15 surfaces of such dimensions that the individual living cell cannot pass through the second cross section; (iii) a height between the first outer surface and the level of the second cross section such that at least a portion of the individual living cell is containable within the hole, and the individual cell is retained therein. The body is designed and constructed such that the individual cells contained within the
20 holes reside substantially in a single focal plane during analysis and accuracy of data collected from the individual cells within the holes is increased because the cells reside substantially in a single focal plane.

According to another aspect of the present invention there is provided a cell carrier grid capable of containing and retaining individual living cells in an
25 array of predefined discrete locations, the cell carrier grid comprising; (a) a body that defines a first and a second outer surface, the body having an ordered array of holes therethrough, each of the holes communicating between the first outer surface and the second outer surface; (b) an organizational plan, the plan being applied to the positioning of the holes on the body such that a position of each of
30 the holes is identifiable so that the holes form the array of predefined discrete locations; and (c) wherein each of the holes is sized to contain at least a portion of an individual living cell therewithin, in that each hole has (i) a first cross section at

the first outer surface of such dimensions that at least a portion of the individual living cell can pass through the first cross section without suffering substantial damage; (ii) a second cross section at a level intermediate between the first and the second outer surfaces said second cross section being no greater in size than
5 said first cross section; and (iii) a height between the first outer surface and the level of the second cross section such that at least a portion of the individual living cell is containable within the hole, and the individual cell is retained therein. The body is at least partially coated with a biologically active material.

According to yet another aspect of the present invention there is provided a
10 cell carrier grid capable of containing and retaining individual living cells in an array of predefined discrete locations, the cell carrier grid comprising; (a) a body that defines a first and a second outer surface, the body having an ordered array of holes therethrough, each of the holes communicating between the first outer surface and the second outer surface; (b) an organizational plan, the plan being
15 applied to the positioning of the holes on the body such that a position of each of the holes is identifiable so that the holes form the array of predefined discrete locations and (c) wherein each of the holes is sized to contain at least a portion of an individual living cell therewithin, in that each hole has (i) a first cross section at the first outer surface of such dimensions that at least a portion of the individual
20 living cell can pass through the first cross section without suffering substantial damage; (ii) a second cross section at a level intermediate between the first and the second outer surfaces said second cross section being no greater in size than said first cross section; and (iii) a height between the first outer surface and the level of the second cross section such that at least a portion of the individual living
25 cell is containable within the hole, and the individual cell is retained therein. The body is designed and constructed such that the individual cells contained within the holes are recoverable by a recovery device.

According to further features in preferred embodiments of the invention described below, the body is inherently rigid, such that the individual cells
30 contained within the holes reside substantially in a single focal plane during analysis.

According to still further features in the described preferred embodiments the cell carrier grid of claim 1, wherein the body is supported by at least one support, such that the individual cells contained within the holes reside substantially in a single focal plane during analysis.

5 According to still further features in the described preferred embodiments the cell carrier grid further includes a holder designed and constructed to: (i) facilitate manipulation of the cell carrier grid; (ii) allow application of suction through the holes in the grid such that cells in suspension applied to the first outer surface of the grid tend to move towards and into the holes; and (iii) permit
10 application and removal of solutions to cells residing in the holes.

According to still further features in the described preferred embodiments the biologically active material includes at least one material selected from the group consisting of a protein, a carbohydrate, a nucleic acid, and a lipid.

According to still further features in the described preferred embodiments the
15 protein is selected from the group consisting of an antibody, an antigen, biotin, avidin, streptavidin, an enzyme, a ligand, a receptor, a mitogen, a haptene, a multimeric MHC-antigen complex and a lectin.

According to still further features in the described preferred embodiments the nucleic acid is selected from the group consisting of DNA, RNA and
20 derivatives thereof.

According to still further features in the described preferred embodiments the lipid is selected from the group consisting of Lysophosphatidylcholine (polar phospholipid) and OxLDL

According to still further features in the described preferred embodiments
25 the biologically active material is used to coat the body at a location selected from the group consisting of within the holes and adjacent to the holes.

According to still further features in the described preferred embodiments the biologically active material comprises at least two separate biologically active materials, each of the at least two materials applied to a portion of the holes
30 comprising the array of predefined discrete locations.

According to still further features in the described preferred embodiments at least 20% of the individual living cell contained within a hole extends beyond a

plane defined by the first outer surface to render the cell recoverable by a recovery device.

According to still further features in the described preferred embodiments wherein at least 40% of the individual living cell contained within a hole extends
5 beyond a plane defined by the first outer surface to render the cell recoverable by a recovery device.

According to still further features in the described preferred embodiments wherein at least 50% of the individual living cell contained within a hole extends
10 beyond a plane defined by the first outer surface to render the cell recoverable by a recovery device.

The present invention successfully addresses the shortcomings of the presently known configurations by providing cell carrier grids which are coated with biologically active materials and cell carrier grids designed and constructed to hold cells in a single focal plane for analysis. The present invention further
15 relates to cell carrier grids which allow recovery of individual cells based upon the results of analyses conducted thereupon.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is herein described, by way of example only, with
20 reference to the accompanying drawings. With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of the preferred embodiments of the present invention only, and are presented in the cause of providing what is believed to be the most useful and readily understood
25 description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is necessary for a fundamental understanding of the invention, the description taken with the drawings making apparent to those skilled in the art how the several forms of the invention may be embodied in practice.

30 In the drawings:

FIG. 1 is a perspective view of a cell carrier grid according to the present invention;

FIG. 2 is a cross sectional view of a cell carrier grid of the present invention showing alternate embodiments of holes therein;

FIGs. 3a and 3b show two possible arrangements for an array of holes in a cell carrier grid according to the present invention;

5 FIGs. 3c and 3d show two possible ways in which different holes might be coated with different biologically active materials while some holes remain uncoated;

FIG. 4 is a cross sectional view of a cell carrier grid holder containing a cell carrier grid according to the present invention;

10 FIG. 5 is a cross sectional view of a cell carrier grid holder as in figure 4 in which supports for the grid are visible.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is of improved cell carrier grids which can be coated
15 with biologically active materials, can be designed and constructed to hold cells in a single focal plane for analysis and which allow recovery of individual cells based upon the results of analyses conducted thereupon.

Specifically, the present invention can be used to regulate a biological function in cells before or during assay, to increase the accuracy of
20 assays performed on cells contained in the cell carrier grid and to allow recovery of individual cells based upon the results of analyses conducted thereupon.

The principles and operation of improved cell carrier grids according to the present invention may be better understood with reference to the drawings and accompanying descriptions.

25 Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be
30 understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

Figure 1 shows a cell carrier grid **20** capable of containing and retaining individual living cells in an array **24** of predefined discrete locations **26**. Grid **20** may include, for example, a 100 X 100 2-dimensional array of holes **26**. Each of holes **26** may be, for example, approximately 7 microns in diameter and spaced about 20 microns apart. The cell carrier grid **20** includes a body **22** that defines a first and a second outer surface (**28** and **30**). Body **22** has an ordered array **24** of holes **26** therethrough. Each of holes **26** communicates between first outer surface **28** and second outer surface **30**. Grid **20** also includes an organizational plan (Figures 3a-d) applied to the positioning of holes **26** on body **22** such that a position of each of the holes is identifiable so that the holes form the array **24** of predefined discrete locations. Each of holes **26** is sized to contain at least a portion of an individual living cell therewithin (Figure 2). To that end, each hole **26** has a first cross section **32** at first outer surface **28** of such dimensions that at least a portion of the individual living cell can pass through first cross section **32** without suffering substantial damage. Each of holes **26** also has a second cross section **34** at a level intermediate between the first and the second outer surfaces (**28** and **30**). In some cases this second cross section **34** is of such dimensions that the individual living cell cannot pass therethrough. In other cases, second cross section **34** is similar to first cross section **32**. A height **36** is defined between first outer surface **28** and the level of second cross section **34** such that at least a portion of the individual living cell is containable within the hole, and the individual cell is retained therein. According to preferred embodiments of the invention, body **22** is designed and constructed such that the individual cells at least partially contained within holes **26** reside substantially in a single focal plane during analysis. This is achieved by imparting additional physical strength to grid **20**, which also serves to prevent damage to grid **20** during use. As a result, accuracy of data collected from the individual cells within holes **26** is increased relative to prior art teachings.

Holding of cells in a single focal plane may be achieved, for example, by constructing body **22** of inherently rigid materials. In order to accomplish this, a Grid diagram at 1,000:1 is drawn on a computer. This diagram is a map of array **24** of holes **26** of grid **20**. The diagram is then "inverted" and reduced by means

of a computer program or by photography. This produces a reduced size negative of the grid. A further downscaling is achieved by projecting the negative through a microscope in the opposite direction, thereby receiving the desired picture on the side of the objective. This process produces a picture in which holes 26 are in the
5 desired size (typically several microns). This picture of the grid is projected through the objective lens onto a thin metal paper (e.g. copper paper of 0.5-mm thickness) which is covered photo-emulsion. The emulsion changes its structure upon exposure to light. Typically several hundred grids are projected on a single sheet. The metal paper is then sequentially immersed in developer, fixer and a
10 wash solution. This produces metal paper with fixed pictures of grids. The developing chemicals that are used, which stay on the metal paper, are non-conductive. The metal paper is then electroplated with a metal such as Nickel, Gold or Silver. The areas that are covered with the developmental chemicals are not coated in this process since they do not conduct electricity. This
15 produces a metal picture of the projected. This process is repeated cyclically until holes 26 have the desired height 36 as detailed hereinbelow.

If, in each step the coating is applied in a bigger diameter over each of holes 26 conical wells are produced instead of cylindrical holes. If the diameter is held constant, cylindrical holes are produced.

20 Prior art grids are typically very thin. Since they are glued to the grid carrier as round circles, application of buffer to the grid carrier creates great pressure on the grid causing it to bulge. This bulging causes cells loaded on the grid to reside in a wide variety of focal planes causing inaccuracies in measurement. Bulging also effectively precludes automated retrieval of cells using programmed micromanipulators. .

25 According to the present invention, bulging is prevented by starting with a thicker starting material. Alternately, or additionally thicker grids can be produced by repeating the electroplating process cyclically. Alternately or additionally, body 22 may be supported by at least one support 42 (Figure 5) in order to keep individual cells contained within holes 26 substantially in a single focal plane during analysis.
30 Supports 42 may run in more than one direction so that they intersect and reinforce one another. Supports might be organized, for example, in two perpendicular arrays,

members of each array being parallel to one another. Alternately, supports might radiate outward from a single point, as spokes of a wheel.

According to preferred embodiments of the present invention, body **22** is at least partially coated with a biologically active material **58**. Biologically active material **58** may be present within holes **56**, or in proximity thereto, for example on first outer surface **28**. Biologically active material **58** may include, for example, proteins, carbohydrates, nucleic acids, or lipids. Suitable proteins include, but are not limited to, antibodies, antigens, biotin, avidin, streptavidin, enzymes, ligands, receptors, mitogens, haptens, a multimeric MHC-antigen complex and lectins. Suitable nucleic acids include, but are not limited DNA, RNA and derivatives thereof. Suitable lipids include, but are not limited to Lysophosphatidylcholine (polar phospholipid) and OxLDL. It is known that preincubation with OxLDL can alter fluorescence of cells stained with FDA (N. Zurgil et al. (1999) Clin. Cardiol 22:5260-532). Coating of cell carrier grids is therefore an improvement upon this technique for assaying atherosclerosis which is currently being developed. Similarly Lysophosphatidylcholine has been demonstrated to activate lymphocytes (N Zurgil, unpublished results). Coating of cell carrier grids with this material is a significant improvement upon this technique for assaying arteriosclerosis because it brings individual cells into a micro-environment with a higher local concentration of reagent than that achievable using prior art teachings. In addition, supply of coated grids makes the assay simpler to perform by eliminating the need for incubation of cells with the material employed in the coating. This, in turn, reduces the level of skill required of a user of grid **20**.

According to some embodiments of the invention, biologically active material **58** includes at least two separate biologically active materials, each of the at least two materials applied to a portion of holes **26** in array **24** of predefined discrete locations. Figures 3c and 3d show two possible arrangements of biologically active materials 1, 2, and 3 in holes **26**. It should be noted that each biologically active material may include a combination of materials. For example, 3 may represent a combination of 1 and 2. Such an embodiment allows rapid and easy discovery of synergy between different coating materials. 0 is used to represent holes with no biologically active material. Such holes would typically

serve to provide a baseline or negative control reading for an assay. This allows concurrent assay of more than one biologically active material on a single grid 20, something which is infeasible using prior art methods.

According to preferred embodiments of the present invention, body 22 is
 5 designed and constructed such that the individual cells contained within holes 26 are recoverable by a recovery device. This may be achieved, for example, by making height 36 less than the average radius of cells contained in holes 26. According to preferred embodiments of the invention at least 20%, more preferably at least 40%, most preferably at least 50% of the individual living cell
 10 contained within a hole extends beyond a plane defined by first outer surface 28 of body 22 to render the cell recoverable by a recovery device. Table 1 shows calculated well depths for cell types of research interest.

15 **Table 1: Well depths required for various percentages of selected cell types to protrude from a well.**

Cell type	Avg. diameter	20% depth	40% depth	50%depth
Lymphocytes	11.5 micron	9.2 micron	6.9 micron	5.75 micron
Monocytes	16 micron	12.8 micron	9.6 micron	8 micron
Neutrophils	13 micron	10.4 micron	7.8 micron	6.5 micron
Eosinophils	14 micron	11.2 micron	8.4 micron	7 micron
Basophils	12 micron	9.6 micron	7.2 micron	6 micron
platelets	7 micron	5.6 micron	4.2 micron	3.5 micron

According to preferred embodiments of the invention cell carrier grid 20 further includes a holder 44 (Figure 4) designed and constructed to facilitate manipulation of cell carrier grid 20. Holder 44 further allows application of
 20 suction through the holes in the grid such that cells in suspension applied to first outer surface 28 of grid 20 tend to move towards and into holes 26. Holder 44 **further** permits application and removal of solutions to cells residing in holes 26. Holder 44 includes a first port 50 and a second port 52, each communicating with

CELLKIN001-1CA

12

a space 48 which contacts second outer surface 30 of grid 20. Ports 50 and 52 serve for introduction and removal of liquids into space 48 and relative flow rates therethrough can create suction through holes 26 in grid 20.

Additional objects, advantages, and novel features of the present invention
5 will become apparent to one ordinarily skilled in the art upon examination of the following examples, which are not intended to be limiting. Additionally, each of the various embodiments and aspects of the present invention as delineated hereinabove and as claimed in the claims section below finds experimental support in the following examples. Although the invention has been described
10 in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad scope of the appended claims.

Citation or identification of any reference in this application shall not
15 be construed as an admission that such reference is available as prior art to the present invention.

CELLKIN001-1CA

13

What is claimed is:

1. A cell carrier grid holder having a cell carrier grid mounted thereupon, said cell carrier grid having a body that defines a first and a second outer surface, said body having an ordered array of holes therethrough at predefined discrete locations, each of said holes communicating
5 between said first outer surface and said second outer surface, characterized in that each of said holes has:
 - (i) a first cross section at said first outer surface of such dimensions that at least a portion of an individual living cell can pass through said first cross section without suffering substantial damage;
 - 10 (ii) a second cross section smaller than said first cross section which is located at a level intermediate between said first and said second outer surfaces and of such dimensions that said individual living cell cannot pass through said second cross section;
 - (iii) a maximum cross-sectional diameter ranging from 7 to 16 microns; and
 - (iv) a height between said first outer surface and the level of the second cross section
15 such that at least 50% of said individual living cell is containable within said hole but that no more than one individual cell is containable in said hole;wherein said holder has at least one inlet port and least one outlet port which enable application of suction through said holes in said grid, and
wherein said cell carrier grid is mounted on said holder above at least one structural
20 support which is arranged to transversely contact at least a portion of said second outer surface of said cell carrier grid to prevent bulging of said cell carrier grid upon loading with cells.
2. A cell carrier grid holder according to claim 1, wherein said height is less than 16 microns.
- 25 3. A cell carrier grid holder according to claim 1 or claim 2, wherein said height is at least 3.5 microns.

CELLKIN001-1CA

14

4. A cell grid holder according to any one of claims 1 to 3, wherein said cell carrier grid is at least partially coated with at least one biologically active material selected from the group consisting of a protein, a carbohydrate, a nucleic acid and a lipid.
5. A cell grid holder according to claim 4, wherein said at least one biologically active
5 material is selected from the group consisting of an antibody, biotin, avidin, streptavidin, an enzyme, a multimeric MHC-antigen complex, a lectin, DNA, RNA, a DNA derivative, an RNA derivative, lysophosphatidylcholine and oxidized low density lipoprotein.
6. A cell grid holder according to claim 4 or claim 5, wherein said cell carrier grid is at least partially coated with at least two biologically active materials, wherein each of said
10 biologically active materials is applied to at least some of the holes of said array of holes.

1/5

Figure 1
20




Figure 2

20









Figure 3a56Figure 3b56Figure 3c56Figure 3d56

WO 02/44318

PCT/US01/42844

4/5

Figure 4 44

5/5

