



US011073680B2

(12) **United States Patent**  
**Teranishi et al.**

(10) **Patent No.:** **US 11,073,680 B2**  
(45) **Date of Patent:** **Jul. 27, 2021**

(54) **CAMERA OPTICAL LENS COMPRISING SIX LENSES OF -+--+ REFRACTIVE POWERS**

(58) **Field of Classification Search**  
CPC ..... G02B 13/0045; G02B 1/041; G02B 9/62  
See application file for complete search history.

(71) Applicant: **AAC Technologies Pte. Ltd.**,  
Singapore (SG)

(56) **References Cited**

(72) Inventors: **Takaaki Teranishi**, Shenzhen (CN); **Lei Zhang**, Shenzhen (CN); **Yanmei Wang**, Shenzhen (CN); **Wenbo Hu**, Shenzhen (CN)

U.S. PATENT DOCUMENTS

4,806,001 A \* 2/1989 Okabe ..... G02B 9/60  
359/708  
2018/0196225 A1\* 7/2018 Chang ..... G02B 13/0045  
2019/0162935 A1\* 5/2019 Chen ..... G02B 9/64

(73) Assignee: **AAC Optics Solutions Pte. Ltd.**,  
Singapore (SG)

FOREIGN PATENT DOCUMENTS

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 156 days.

JP 06082696 A \* 3/1994

OTHER PUBLICATIONS

(21) Appl. No.: **16/531,142**

JP-06082696-A, machine translation (Year: 1994).\*

(22) Filed: **Aug. 5, 2019**

\* cited by examiner

(65) **Prior Publication Data**

US 2020/0057278 A1 Feb. 20, 2020

*Primary Examiner* — Wen Huang

(74) *Attorney, Agent, or Firm* — W&G Law Group LLP

(30) **Foreign Application Priority Data**

Aug. 14, 2018 (CN) ..... 201810924592.4  
Aug. 14, 2018 (CN) ..... 201810925278.8

(57) **ABSTRACT**

The present disclosure discloses a camera optical lens. The camera optical lens including, in an order from an object side to an image side, a first lens, a second lens having a positive refractive power, a third lens having a positive refractive power, a fourth lens, a fifth lens, and a sixth lens. The camera optical lens further satisfies specific conditions.

(51) **Int. Cl.**


**G02B 13/00** (2006.01)  
**G02B 1/04** (2006.01)  
**G02B 9/62** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G02B 13/0045** (2013.01); **G02B 1/041** (2013.01); **G02B 9/62** (2013.01)

**19 Claims, 7 Drawing Sheets**

10






Fig. 1

Longitudinal aberration




Fig. 2

Lateral color




Fig. 3




Fig. 4




Fig. 5

Longitudinal aberration




Fig. 6

Later color




Fig. 7




Fig. 8




Fig. 9

Longitudinal aberration




Fig. 10

Lateral color




Fig. 11




Fig. 12

## CAMERA OPTICAL LENS COMPRISING SIX LENSES OF --+--+-- REFRACTIVE POWERS

### FIELD OF THE PRESENT DISCLOSURE

The present disclosure relates to optical lens, in particular to a camera optical lens suitable for handheld devices such as smart phones and digital cameras and imaging devices.

### DESCRIPTION OF RELATED ART

With the emergence of smart phones in recent years, the demand for miniature camera lens is increasing day by day, but the photosensitive devices of general camera lens are no other than Charge Coupled Device (CCD) or Complementary Metal-Oxide Semiconductor Sensor (CMOS sensor), and as the progress of the semiconductor manufacturing technology makes the pixel size of the photosensitive devices shrink, coupled with the current development trend of electronic products being that their functions should be better and their shape should be thin and small, miniature camera lens with good imaging quality therefor has become a mainstream in the market. In order to obtain better imaging quality, the lens that is traditionally equipped in mobile phone cameras adopts a three-piece or four-piece lens structure. And, with the development of technology and the increase of the diverse demands of users, and under this circumstances that the pixel area of photosensitive devices is shrinking steadily and the requirement of the system for the imaging quality is improving constantly, the five-piece, six-piece and seven-piece lens structure gradually appear in lens design. There is an urgent need for ultra-thin wide-angle camera lenses which have good optical characteristics and the chromatic aberration of which is fully corrected.

### BRIEF DESCRIPTION OF THE DRAWINGS

Many aspects of the exemplary embodiments can be better understood with reference to the following drawings. The components in the drawing are not necessarily drawn to scale, the emphasis instead being placed upon clearly illustrating the principles of the present disclosure.

FIG. 1 is a schematic diagram of a camera optical lens in accordance with a first embodiment of the present invention;

FIG. 2 shows the longitudinal aberration of the camera optical lens shown in FIG. 1;

FIG. 3 shows the lateral color of the camera optical lens shown in FIG. 1;

FIG. 4 presents a schematic diagram of the field curvature and distortion of the camera optical lens shown in FIG. 1;

FIG. 5 is a schematic diagram of a camera optical lens in accordance with a second embodiment of the present invention;

FIG. 6 presents the longitudinal aberration of the camera optical lens shown in FIG. 5;

FIG. 7 presents the lateral color of the camera optical lens shown in FIG. 5;

FIG. 8 presents the field curvature and distortion of the camera optical lens shown in FIG. 5;

FIG. 9 is a schematic diagram of a camera optical lens in accordance with a third embodiment of the present invention;

FIG. 10 presents the longitudinal aberration of the camera optical lens shown in FIG. 9;

FIG. 11 presents the lateral color of the camera optical lens shown in FIG. 9;

FIG. 12 presents the field curvature and distortion of the camera optical lens shown in FIG. 9.

### DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

The present disclosure will hereinafter be described in detail with reference to several exemplary embodiments. To make the technical problems to be solved, technical solutions and beneficial effects of the present disclosure more apparent, the present disclosure is described in further detail together with the figure and the embodiments. It should be understood the specific embodiments described hereby is only to explain the disclosure, not intended to limit the disclosure.

#### Embodiment 1

As referring to FIG. 1, the present invention provides a camera optical lens 10. FIG. 1 shows the camera optical lens 10 of embodiment 1 of the present invention, the camera optical lens 10 comprises six lenses. Specifically, from the object side to the image side, the camera optical lens 10 comprises in sequence: a first lens L1, an aperture S1, a second lens L2, a third lens L3, a fourth lens L4, a fifth lens L5, and a sixth lens L6. Optical element like optical filter GF can be arranged between the sixth lens L6 and the image surface Si.

The first lens L1 is made of plastic material, the second lens L2 is made of plastic material, the third lens L3 is made of plastic material, the fourth lens L4 is made of plastic material, the fifth lens L5 is made of plastic material, the sixth lens L6 is made of glass material.

The second lens L2 has a positive refractive power and the third lens L3 has a positive refractive power.

Here, the focal length of the camera optical lens 10 is defined as  $f$ , the focal length of the first lens L1 is defined as  $f_1$ , the refractive power of the sixth lens L6 is defined as  $n_6$ , the thickness on-axis of the sixth lens L6 is defined as  $d_{11}$  and the total optical length of the camera optical lens is defined as TTL. The camera optical lens 10 satisfies the following conditions:  $-3 \leq f_1/f \leq -1$ ,  $1.7 \leq n_6 \leq 2.2$ ,  $0.03 \leq d_{11}/TTL \leq 0.075$ .

Condition  $-3 \leq f_1/f \leq -1$  fixes the negative refractive power of the first lens L1. If the upper limit of the set value is exceeded, although it benefits the ultra-thin development of lenses, the negative refractive power of the first lens L1 will be too strong, problem like aberration is difficult to be corrected, and it is also unfavorable for wide-angle development of lens. On the contrary, if the lower limit of the set value is exceeded, the negative refractive power of the first lens becomes too weak, it is then difficult to develop ultra-thin lenses. Preferably, the following condition shall be satisfied,  $-2.997 \leq f_1/f \leq -1.535$ .

Condition  $1.7 \leq n_6 \leq 2.2$  fixes the refractive power of the sixth lens L6, and refractive power within this range benefits the ultra-thin development of lenses, and it also benefits the correction of aberration. Preferably, the following condition shall be satisfied,  $1.701 \leq n_6 \leq 2.046$ .

Condition  $0.03 \leq d_{11}/TTL \leq 0.075$  fixes the ratio between the thickness on-axis  $d_{11}$  of the sixth lens L6 and the total optical length TTL of the camera optical lens, and it benefits the ultra-thin development of lenses. Preferably, the following condition shall be satisfied,  $0.0475 \leq d_{11}/TTL \leq 0.0745$ .

When the focal length of the camera optical lens 10 of the present invention, the focal length of each lens, the refractive power of the related lens, and the total optical length, the

thickness on-axis and the curvature radius of the camera optical lens satisfy the above conditions, the camera optical lens **10** has the advantage of high performance and satisfies the design requirement of low TTL.

In this embodiment, the object side surface of the first lens **L1** is a convex surface relative to the proximal axis, its image side surface is a concave surface relative to the proximal axis, and it has negative refractive power; the curvature radius of the object side surface of the first lens **L1** is defined as  $R1$ , the curvature radius of the image side surface of the first lens **L1** is defined as  $R2$ , the thickness on-axis of the first lens **L1** is defined as  $d1$  and the total optical length of the camera optical lens is defined as TTL, the condition  $1.01 \leq (R1+R2)/(R1-R2) \leq 5.68$  fixes the shape of the first lens **L1**, so that the first lens **L1** can effectively correct system spherical aberration; when the condition  $0.02 \leq d1/TTL \leq 0.07$  is met, it is beneficial for the realization of ultra-thin lenses. Preferably, the following conditions shall be satisfied:  $1.61 \leq (R1+R2)/(R1-R2) \leq 4.55$ ;  $0.04 \leq d1/TTL \leq 0.05$ .

In this embodiment, the object side surface of the second lens **L2** is a convex surface relative to the proximal axis, its image side surface is a concave surface relative to the proximal axis, and it has positive refractive power; the focal length of the camera optical lens **10** is defined as  $f$ , the focal length of the second lens **L2** is defined as  $f2$ , the curvature radius of the object side surface of the second lens **L2** is defined as  $R3$ , the curvature radius of image side surface of the second lens **L2** is defined as  $R4$ , the thickness on-axis of the second lens **L2** is defined as  $d3$  and the total optical length of the camera optical lens is defined as TTL, they satisfy the following condition:  $10.8 \leq f2/f \leq 275.23$ , when the condition is met, the positive refractive power of the second lens **L2** is controlled within reasonable scope, the spherical aberration caused by the first lens **L1** which has negative refractive power and the field curvature of the system then can be reasonably and effectively balanced; the condition  $17.49 \leq (R3+R4)/(R3-R4) \leq 89.21$  fixes the shape of the second lens **L2**, when beyond this range, with the development into the direction of ultra-thin and wide-angle lenses, problem like on-axis chromatic aberration is difficult to be corrected; if the condition  $0.02 \leq d3/TTL \leq 0.07$  is met, it is beneficial for the realization of ultra-thin lenses. Preferably, the following conditions shall be satisfied:  $17.28 \leq f2/f \leq 220.18$ ;  $27.99 \leq (R3+R4)/(R3-R4) \leq 71.37$ ;  $0.04 \leq d3/TTL \leq 0.05$ .

In this embodiment, the object side surface of the third lens **L3** is a convex surface relative to the proximal axis, its image side surface is a convex surface relative to the proximal axis, and it has positive refractive power; the focal length of the camera optical lens **10** is defined as  $f$ , the focal length of the third lens **L3** is defined as  $f3$ , the curvature radius of the object side surface of the third lens **L3** is defined as  $R5$ , the curvature radius of the image side surface of the third lens **L3** is defined as  $R6$ , the thickness on-axis of the third lens **L3** is defined as  $d5$  and the total optical length of the camera optical lens is defined as TTL, they satisfy the condition:  $0.35 \leq f3/f \leq 1.16$ , the appropriate distribution of refractive power makes it possible that the system has better imaging quality and lower sensitivity; the condition  $-1.57 \leq (R5+R6)/(R5-R6) \leq -0.51$  fixes the shape of the third lens **L3**, when beyond this range, with the development into the direction of ultra-thin and wide-angle lens, the problem like chromatic aberration is difficult to be corrected; when the condition  $0.05 \leq d5/TTL \leq 0.17$  is met, it is beneficial for the realization of ultra-thin lenses. Preferably, the fol-

lowing conditions shall be satisfied:  $0.56 \leq f3/f \leq 0.93$ ;  $-0.98 \leq (R5+R6)/(R5-R6) \leq -0.64$ ;  $0.08 \leq d5/TTL \leq 0.14$ .

In this embodiment, the object side surface of the fourth lens **L4** is a concave surface relative to the proximal axis, its image side surface is a convex surface relative to the proximal axis, and it has negative refractive power; the focal length of the camera optical lens **10** is defined as  $f$ , the focal length of the fourth lens **L4** is defined as  $f4$ , the curvature radius of the object side surface of the fourth lens **L4** is defined as  $R7$ , the curvature radius of the image side surface of the fourth lens **L4** is defined as  $R8$ , the thickness on-axis of the fourth lens **L4** is defined as  $d7$  and the total optical length of the camera optical lens is defined as TTL, they satisfy the condition:  $-3.77 \leq f4/f \leq -1.08$ , the appropriate distribution of refractive power makes it possible that the system has better imaging quality and lower sensitivity; the condition  $-5.99 \leq (R7+R8)/(R7-R8) \leq -1.62$  fixes the shape of the fourth lens **L4**, when beyond this range, with the development into the direction of ultra-thin and wide-angle lens, the problem like chromatic aberration is difficult to be corrected; when the condition  $0.03 \leq d7/TTL \leq 0.11$  is met, it is beneficial for realization of ultra-thin lenses. Preferably, the following conditions shall be satisfied:  $-2.36 \leq f4/f \leq -1.36$ ;  $-3.74 \leq (R7+R8)/(R7-R8) \leq -2.02$ ;  $0.04 \leq d7/TTL \leq 0.09$ .

In this embodiment, the object side surface of the fifth lens **L5** is a concave surface relative to the proximal axis, its image side surface is a convex surface relative to the proximal axis, and it has positive refractive power; the focal length of the camera optical lens **10** is defined as  $f$ , the focal length of the fifth lens **L5** is defined as  $f5$ , the curvature radius of the object side surface of the fifth lens **L5** is defined as  $R9$ , the curvature radius of the image side surface of the fifth lens **L5** is defined as  $R10$ , the thickness on-axis of the fifth lens **L5** is defined as  $d9$  and the total optical length of the camera optical lens is defined as TTL, they satisfy the condition:  $0.31 \leq f5/f \leq 1.06$ , the limitation on the fifth lens **L5** can effectively make the light angle of the camera lens flat and the tolerance sensitivity reduces; the condition  $0.79 \leq (R9+R10)/(R9-R10) \leq 2.47$  fixes the shape of the fifth lens **L5**, when beyond this range, with the development into the direction of ultra-thin and wide-angle lens, the problem like off-axis chromatic aberration is difficult to be corrected; when the condition  $0.05 \leq d9/TTL \leq 0.16$  is met, it is beneficial for the realization of ultra-thin lens. Preferably, the following conditions shall be satisfied:  $0.5 \leq f5/f \leq 0.85$ ;  $1.26 \leq (R9+R10)/(R9-R10) \leq 1.97$ ;  $0.08 \leq d9/TTL \leq 0.13$ .

In this embodiment, the object side surface of the sixth lens **L6** is a convex surface relative to the proximal axis, its image side surface is a concave surface relative to the proximal axis, and it has negative refractive power; the focal length of the camera optical lens **10** is defined as  $f$ , the focal length of the sixth lens **L6** is defined as  $f6$ , the curvature radius of the object side surface of the sixth lens **L6** is defined as  $R11$ , the curvature radius of the image side surface of the sixth lens **L6** is defined as  $R12$ , the thickness on-axis of the sixth lens **L6** is defined as  $d11$  and the total optical length of the camera optical lens is defined as TTL, they satisfy the condition:  $-2.13 \leq f6/f \leq -0.53$ , the appropriate distribution of refractive power makes it possible that the system has better imaging quality and lower sensitivity; the condition  $1.62 \leq (R11+R12)/(R11-R12) \leq 6.66$  fixes the shape of the sixth lens **L6**, when beyond this range, with the development into the direction of ultra-thin and wide-angle lenses, the problem like off-axis chromatic aberration is difficult to be corrected; when the condition  $0.03 \leq d11/TTL \leq 0.11$  is met, it is beneficial for the realization of

ultra-thin lens. Preferably, the following conditions shall be satisfied:  $-1.33 \leq f_6/f_5 \leq -0.66$ ;  $2.59 \leq (R_{11}+R_{12})/(R_{11}-R_{12}) \leq 5.32$ ;  $0.05 \leq d_{11}/TTL \leq 0.09$ .

In this embodiment, the focal length of the camera optical lens 10 is defined as f and the combined focal length of the first lens and the second lens is defined as f12, when the condition  $-5.72 \leq f_{12}/f \leq -1.34$  is met, the aberration and distortion of the camera lens can be eliminated, and the back focus of the camera lens can be suppressed and the miniaturization characteristics can be maintained. Preferably, the following conditions shall be satisfied:  $-3.58 \leq f_{12}/f \leq -1.67$ .

In this embodiment, the total optical length TTL of the camera optical lens 10 is less than or equal to 5.18 mm, it is beneficial for the realization of ultra-thin lenses. Preferably, the total optical length TTL of the camera optical lens 10 is less than or equal to 4.95 mm.

In this embodiment, the aperture F number of the camera optical lens 10 is less than or equal to 2.25. A large aperture has better imaging performance. Preferably, the aperture F number of the camera optical lens 10 is less than or equal to 2.20.

With such design, the total optical length TTL of the camera optical lens 10 can be made as short as possible, thus the miniaturization characteristics can be maintained.

In the following, an example will be used to describe the camera optical lens 10 of the present invention. The symbols recorded in each example are as follows. The unit of focal length, distance on-axis, curvature radius, thickness on-axis, inflexion point position and arrest point position is mm.

TTL: Optical length (the distance on-axis from the object side surface to the image surface of the first lens L1).

Preferably, inflexion points and/or arrest points can also be arranged on the object side surface and/or image side surface of the lens, so that the demand for high quality imaging can be satisfied, the description below can be referred for specific implementable scheme.

The design information of the camera optical lens 10 in the first embodiment of the present invention is shown in the tables 1 and 2.

TABLE 1

	R	d	nd	vd
R1	7.181	d0=	0.215	nd1 1.5352 v1 56.09
R2	2.412	d1=	0.062	
S1	$\infty$	d2=	0.030	
R3	1.379	d3=	0.215	nd2 1.6613 v2 20.37
R4	1.305	d4=	0.035	
R5	1.393	d5=	0.530	nd3 1.5352 v3 56.09
R6	-10.760	d6=	0.595	
R7	-1.985	d7=	0.257	nd4 1.6613 v4 20.37
R8	-3.976	d8=	0.230	
R9	-4.047	d9=	0.452	nd5 1.5352 v5 56.09
R10	-0.908	d10=	0.049	
R11	1.247	d11=	0.350	nd6 1.7015 v6 41.24
R12	0.659	d12=	1.380	
R13	$\infty$	d13=	0.210	ndg 1.5168 vg 64.17
R14	$\infty$	d14=	0.100	

In which, the meaning of the various symbols is as follows.

S1: Aperture;

R: The curvature radius of the optical surface, the central curvature radius in case of lens;

R1: The curvature radius of the object side surface of the first lens L1;

R2: The curvature radius of the image side surface of the first lens L1;

R3: The curvature radius of the object side surface of the second lens L2;

R4: The curvature radius of the image side surface of the second lens L2;

R5: The curvature radius of the object side surface of the third lens L3;

R6: The curvature radius of the image side surface of the third lens L3;

R7: The curvature radius of the object side surface of the fourth lens L4;

R8: The curvature radius of the image side surface of the fourth lens L4;

R9: The curvature radius of the object side surface of the fifth lens L5;

R10: The curvature radius of the image side surface of the fifth lens L5;

R11: The curvature radius of the object side surface of the sixth lens L6;

R12: The curvature radius of the image side surface of the sixth lens L6;

R13: The curvature radius of the object side surface of the optical filter GF;

R14: The curvature radius of the image side surface of the optical filter GF;

d: The thickness on-axis of the lens and the distance on-axis between the lens;

d0: The distance on-axis from aperture S1 to the object side surface of the first lens L1;

d1: The thickness on-axis of the first lens L1;

d2: The distance on-axis from the image side surface of the first lens L1 to the object side surface of the second lens L2;

d3: The thickness on-axis of the second lens L2;

d4: The distance on-axis from the image side surface of the second lens L2 to the object side surface of the third lens L3;

d5: The thickness on-axis of the third lens L3;

d6: The distance on-axis from the image side surface of the third lens L3 to the object side surface of the fourth lens L4;

d7: The thickness on-axis of the fourth lens L4;

d8: The distance on-axis from the image side surface of the fourth lens L4 to the object side surface of the fifth lens L5;

d9: The thickness on-axis of the fifth lens L5;

d10: The distance on-axis from the image side surface of the fifth lens L5 to the object side surface of the sixth lens L6;

d11: The thickness on-axis of the sixth lens L6;

d12: The distance on-axis from the image side surface of the sixth lens L6 to the object side surface of the optical filter GF;

d13: The thickness on-axis of the optical filter GF;

d14: The distance on-axis from the image side surface to the image surface of the optical filter GF;

nd: The refractive power of the d line;

nd1: The refractive power of the d line of the first lens L1;

nd2: The refractive power of the d line of the second lens L2;

nd3: The refractive power of the d line of the third lens L3;

nd4: The refractive power of the d line of the fourth lens L4;

nd5: The refractive power of the d line of the fifth lens L5;

nd6: The refractive power of the d line of the sixth lens L6;

ndg: The refractive power of the d line of the optical filter GF;  
 vd: The abbe number;  
 v1: The abbe number of the first lens L1;  
 v2: The abbe number of the second lens L2;  
 v3: The abbe number of the third lens L3;  
 v4: The abbe number of the fourth lens L4;  
 v5: The abbe number of the fifth lens L5;  
 v6: The abbe number of the sixth lens L6;  
 vg: The abbe number of the optical filter GF;  
 Table 2 shows the aspherical surface data of the camera optical lens **10** in the embodiment 1 of the present invention.

TABLE 2

Conic Index	Aspherical Surface Index							
	k	A4	A6	A8	A10	A12	A14	A16
R1	-5.5503E+01	-1.4700E-01	2.1937E-01	-3.7646E-01	3.1324E-01	4.8749E-02	-2.6040E-01	1.0601E-01
R2	-2.7532E+01	-3.3797E-01	2.1250E-01	-1.4635E-02	5.6901E-02	-3.2605E-01	2.9800E-01	-8.8697E-02
R3	-6.1613E+00	-2.2036E-01	-2.7491E-01	3.6987E-01	8.0348E-02	-2.2225E-01	-4.8561E-01	5.0454E-01
R4	-2.4321E+00	-2.6133E-01	-2.4029E-01	3.6076E-01	-5.3565E-02	-2.0523E-01	-1.3254E-02	1.3212E-01
R5	5.0230E-01	-2.4420E-01	1.0023E-01	-4.3782E-02	2.0302E-02	-2.0017E-01	2.3962E-01	-9.9321E-02
R6	9.9395E+01	-1.9755E-02	1.0023E-01	-5.5380E-02	8.9305E-03	-1.3540E-02	-4.3263E-02	3.4271E-02
R7	-1.8759E-01	-1.4763E-01	4.0500E-02	3.5562E-02	2.5052E-02	-1.7954E-02	-2.0469E-02	5.0169E-04
R8	3.0593E+00	-1.8379E-01	1.0666E-01	9.5575E-03	1.4726E-02	9.9784E-03	2.5622E-03	-6.3302E-03
R9	7.2219E+00	1.4736E-02	-1.7130E-02	2.3787E-02	-1.6426E-03	-5.8364E-03	-1.6503E-03	2.0736E-03
R10	-4.8837E+00	-2.1010E-02	5.2892E-02	-1.3563E-02	-3.5509E-03	5.2658E-04	3.5345E-04	-3.0884E-05
R11	-4.7780E+00	-4.6853E-02	9.8313E-03	-3.7390E-04	-1.2591E-04	2.7123E-06	4.0169E-06	-4.3226E-07
R12	-3.9337E+00	-4.0927E-02	8.5791E-03	-9.0113E-04	-2.5853E-05	1.4944E-05	-8.2964E-07	-3.7494E-08

Among them, K is a conic index, A4, A6, A8, A10, A12, A14, A16 are aspheric surface indexes.  
 IH: Image Height

$$y = \frac{(x^2/R) \sqrt{1 + \{1 - (k+1)(x^2/R^2)\}^{1/2}} + A4x^4 + A6x^6 + A8x^8 + A10x^{10} + A12x^{12} + A14x^{14} + A16x^{16}}{1} \quad (1)$$

For convenience, the aspheric surface of each lens surface uses the aspheric surfaces shown in the above condition (1). However, the present invention is not limited to the aspherical polynomials form shown in the condition (1).

Table 3 and table 4 show the inflexion points and the arrest point design data of the camera optical lens **10** lens in embodiment 1 of the present invention. In which, P1R1 and P1R2 represent respectively the object side surface and image side surface of the first lens L1, P2R1 and P2R2 represent respectively the object side surface and image side surface of the second lens L2, P3R1 and P3R2 represent respectively the object side surface and image side surface of the third lens L3, P4R1 and P4R2 represent respectively the object side surface and image side surface of the fourth lens L4, P5R1 and P5R2 represent respectively the object side surface and image side surface of the fifth lens L5, P6R1 and P6R2 represent respectively the object side surface and image side surface of the sixth lens L6. The data in the column named "inflexion point position" are the vertical distances from the inflexion points arranged on each lens surface to the optic axis of the camera optical lens **10**. The data in the column named "arrest point position" are the vertical distances from the arrest points arranged on each lens surface to the optic axis of the camera optical lens **10**.

TABLE 3

	inflexion point number	inflexion point position 1	inflexion point position 2	inflexion point position 3
P1R1	1	0.305		
P1R2	1	0.275		

TABLE 3-continued

	inflexion point number	inflexion point position 1	inflexion point position 2	inflexion point position 3	
5	P2R1	1	0.375		
	P2R2	1	0.415		
	P3R1	1	0.865		
	P3R2	0			
	P4R1	2	0.815	1.015	
	P4R2	1	0.825		
10	P5R1	1	1.225		
	P5R2	3	0.735	1.275	1.415

TABLE 3-continued

	inflexion point number	inflexion point position 1	inflexion point position 2	inflexion point position 3
P6R1	1	0.745		
P6R2	1	0.685		

TABLE 4

	arrest point number	arrest point position 1
P1R1	1	0.565
P1R2	1	0.525
P2R1	1	0.665
P2R2	1	0.715
P3R1	0	
P3R2	0	
P4R1	0	
P4R2	1	1.075
P5R1	0	
P5R2	0	
P6R1	1	2.325
P6R2	1	2.215

FIG. 2 and FIG. 3 show the longitudinal aberration and lateral color schematic diagrams after light with a wavelength of 470 nm, 555 nm and 650 nm passes the camera optical lens **10** in the first embodiment. FIG. 4 shows the field curvature and distortion schematic diagrams after light with a wavelength of 555 nm passes the camera optical lens **10** in the first embodiment, the field curvature S in FIG. 4 is a field curvature in the sagittal direction, T is a field curvature in the meridian direction.

Table 13 shows the various values of the examples 1, 2, 3 and the values corresponding with the parameters which are already specified in the conditions.

As shown in Table 13, the first embodiment satisfies the various conditions.

In this embodiment, the pupil entering diameter of the camera optical lens is 1.66 mm, the full vision field image height is 2.933 mm, the vision field angle in the diagonal direction is 83.19°, it has wide-angle and is ultra-thin, its on-axis and off-axis chromatic aberrations are fully corrected, and it has excellent optical characteristics.

Embodiment 2

Embodiment 2 is basically the same as embodiment 1, the meaning of its symbols is the same as that of embodiment 1, in the following, only the differences are described.

Table 5 and table 6 show the design data of the camera optical lens 20 in embodiment 2 of the present invention.

TABLE 5

	R	d	nd	vd
R1	3.843	d0= 0.213	nd1 1.5352	v1 56.09
R2	2.013	d1= 0.077		
S1	∞	d2= 0.027		
R3	1.387	d3= 0.213	nd2 1.6613	v2 20.37
R4	1.341	d4= 0.041		
R5	1.491	d5= 0.503	nd3 1.5352	v3 56.09
R6	-12.070	d6= 0.564		
R7	-1.997	d7= 0.312	nd4 1.6613	v4 20.37
R8	-4.717	d8= 0.153		
R9	-4.076	d9= 0.474	nd5 1.5352	v5 56.09
R10	-0.995	d10= 0.082		
R11	1.144	d11= 0.330	nd6 1.8340	v6 37.17
R12	0.715	d12= 1.401		
R13	∞	d13= 0.210	ndg 1.5168	vg 64.17
R14	∞	d14= 0.100		

Table 6 shows the aspherical surface data of each lens of the camera optical lens 20 in embodiment 2 of the present invention.

TABLE 6

	Conic Index		Aspherical Surface Index					
	k	A4	A6	A8	A10	A12	A14	A16
R1	-1.4763E-01	-1.5575E-02	2.0282E-01	-2.9237E-01	2.1497E-01	-1.5633E-03	-9.2641E-02	1.9335E-02
R2	-1.7721E-01	-2.9183E-01	1.4541E-01	-2.1356E-02	1.5842E-01	-3.7643E-01	1.0200E-01	1.1181E-01
R3	-5.7995E-00	-2.1240E-01	-2.2683E-01	3.2371E-01	-5.4094E-02	-1.4843E-01	-1.6983E-01	1.4502E-01
R4	-3.0899E-00	-2.3792E-01	-1.7426E-01	2.4093E-01	-6.0359E-02	-1.5370E-01	-3.6018E-02	1.2494E-01
R5	9.3942E-01	-2.2714E-01	8.6732E-02	-6.3850E-02	-1.6153E-02	-1.8238E-01	2.6512E-01	-1.4020E-01
R6	1.1325E-02	-2.0283E-02	8.6732E-02	-6.3565E-02	3.0916E-03	-8.9216E-03	-3.8152E-02	2.2923E-02
R7	-2.8166E-01	-1.3403E-01	2.9233E-02	5.6079E-02	7.5890E-03	5.3597E-04	4.3111E-03	-1.5133E-02
R8	1.2255E-01	-1.7139E-01	9.0380E-02	5.1857E-03	1.2014E-02	7.2537E-03	6.5507E-04	-3.1934E-03
R9	7.3921E-00	1.5925E-02	-8.5124E-03	2.2426E-02	-1.8237E-03	-5.1409E-03	-1.3690E-03	1.7332E-03
R10	-3.9443E-00	-8.0604E-03	4.7326E-02	-1.2600E-02	-3.2833E-03	4.6011E-04	3.2024E-04	-2.7622E-03
R11	-3.9399E-00	-4.6050E-02	8.4556E-03	-3.1812E-04	-1.0459E-04	2.4634E-06	3.6435E-06	-3.9614E-07
R12	-3.6220E-00	-4.1436E-02	8.2169E-03	-8.0412E-04	-3.7118E-05	1.4656E-05	-6.5783E-07	-3.8426E-03

Table 7 and table 8 show the inflexion points and the arrest point design data of the camera optical lens 20 in the second embodiment of the present invention.

TABLE 7

	inflexion point number	inflexion point position 1	inflexion point position 2	inflexion point position 3
P1R1	1	0.415		
P1R2	1	0.315		
P2R1	1	0.385		
P2R2	1	0.415		
P3R1	1	0.735		
P3R2	0			
P4R1	2	0.905	0.975	

TABLE 7-continued

	inflexion point number	inflexion point position 1	inflexion point position 2	inflexion point position 3
P4R2	1	0.855		
P5R1	2	1.205	1.345	
P5R2	3	0.745	1.295	1.435
P6R1	1	0.775		
P6R2	1	0.725		

TABLE 8

	arrest point number	arrest point position 1
P1R1	1	0.765
P1R2	1	0.605
P2R1	1	0.675
P2R2	1	0.715
P3R1	0	
P3R2	0	
P4R1	0	
P4R2	1	1.115
P5R1	0	
P5R2	0	
P6R1	1	2.295
P6R2	1	2.225

FIG. 6 and FIG. 7 show the longitudinal aberration and lateral color schematic diagrams after light with a wavelength of 470 nm, 555 nm and 650 nm passes the camera optical lens 20 in the second embodiment. FIG. 8 shows the field curvature and distortion schematic diagrams after light with a wavelength of 555 nm passes the camera optical lens 20 in the second embodiment.

As shown in Table 13, the second embodiment satisfies the various conditions.

In this embodiment, the pupil entering diameter of the camera optical lens is 1.508 mm, the full vision field image height is 2.933 mm, the vision field angle in the diagonal direction is 82.94°, it has wide-angle and is ultra-thin, its on-axis and off-axis chromatic aberrations are fully corrected, and it has excellent optical characteristics.

Embodiment 3

Embodiment 3 is basically the same as embodiment 1, the meaning of its symbols is the same as that of embodiment 1, in the following, only the differences are described.

The design information of the camera optical lens 30 in the third embodiment of the present invention is shown in the tables 9 and 10.

11

TABLE 9

	R	d	nd	vd
R1	3.586	d0=	0.215	nd1 1.5352 v1 56.09
R2	2.088	d1=	0.077	
S1	∞	d2=	0.031	
R3	1.458	d3=	0.215	nd2 1.6613 v2 20.37
R4	1.377	d4=	0.038	
R5	1.506	d5=	0.495	nd3 1.5352 v3 56.09
R6	-12.392	d6=	0.545	
R7	-1.972	d7=	0.339	nd4 1.6613 v4 20.37
R8	-4.738	d8=	0.135	
R9	-4.078	d9=	0.494	nd5 1.5352 v5 56.09
R10	-0.974	d10=	0.128	
R11	1.119	d11=	0.305	nd6 1.8919 v6 37.13
R12	0.707	d12=	1.375	
R13	∞	d13=	0.210	ndg 1.5168 vg 64.17
R14	∞	d14=	0.100	

Table 10 shows the aspherical surface data of each lens of the camera optical lens 30 in embodiment 3 of the present invention.

TABLE 10

	Conic Index		Aspherical Surface Index					
	k	A4	A6	A8	A10	A12	A14	A16
R1	-1.0381E-01	-1.5274E-01	1.9306E-01	-2.9638E-01	2.2371E-01	-6.9116E-04	-9.7343E-02	1.4653E-02
R2	-1.6906E-01	-2.9027E-01	1.3969E-01	-3.2986E-02	1.5256E-01	-3.5482E-01	1.2712E-01	6.7271E-02
R3	-5.9946E-00	-2.1443E-01	-2.2904E-01	3.2556E-01	-5.6957E-02	-1.4979E-01	-1.8741E-01	1.2041E-01
R4	-3.2256E+00	-2.3875E-01	-1.7055E-01	2.3626E-01	-6.7917E-02	-1.6267E-01	-3.2324E-02	1.2265E-01
R5	9.9736E-01	-2.2992E-01	3.1868E-02	-5.9900E-02	-1.7430E-02	-1.8313E-01	2.5917E-01	-1.4033E-01
R6	1.2978E-02	-2.5653E-02	8.1668E-02	-5.5203E-02	6.2182E-04	-1.1032E-02	-4.0558E-02	2.2092E-02
R7	-1.3114E-01	-1.4084E-01	3.2444E-02	5.7446E-02	1.1148E-02	1.6233E-03	4.7233E-03	-1.8970E-02
R8	1.1964E+01	-1.7089E-01	8.9682E-02	4.5408E-03	1.1853E-02	7.1596E-03	5.9293E-04	-3.3180E-03
R9	7.4846E-00	1.6780E-02	-7.5400E-03	2.2375E-02	-1.9574E-03	-5.2322E-03	-1.3769E-03	1.7641E-03
R10	-3.8277E-00	-8.4009E-03	4.7600E-02	-1.2553E-02	-3.2301E-03	4.7099E-04	3.1964E-04	-3.9546E-05
R11	-3.8133E-00	-4.5526E-02	8.2671E-03	-3.1610E-04	-1.0508E-04	2.4543E-06	3.6638E-06	-3.8674E-07
R12	-3.5077E-00	-4.1720E-02	8.3946E-03	-3.3439E-04	-1.6336E-05	1.4743E-05	-6.4076E-07	-3.6162E-03

Table 11 and table 12 show the inflexion points and the arrest point design data of the camera optical lens 30 in embodiment 3 of the present invention.

TABLE 11

	inflexion point number	inflexion point position 1	inflexion point position 2
P1R1	1	0.445	
P1R2	1	0.315	
P2R1	1	0.375	
P2R2	1	0.415	
P3R1	1	0.715	
P3R2	0		
P4R1	2	0.905	0.945
P4R2	1	0.865	
P5R1	2	1.215	1.335
P5R2	2	0.745	1.275
P6R1	1	0.785	
P6R2	1	0.735	

TABLE 12

	arrest point number	arrest point position 1
P1R1	1	0.775
P1R2	1	0.595
P2R1	1	0.665
P2R2	1	0.705
P3R1	0	
P3R2	0	

12

TABLE 12-continued

	arrest point number	arrest point position 1
P4R1	0	
P4R2	1	1.125
P5R1	0	
P5R2	0	
P6R1	1	2.315
P6R2	1	2.255

FIG. 10 and FIG. 11 show the longitudinal aberration and lateral color schematic diagrams after light with a wavelength of 470 nm, 555 nm and 650 nm passes the camera optical lens 30 in the third embodiment. FIG. 12 shows the field curvature and distortion schematic diagrams after light with a wavelength of 555 nm passes the camera optical lens 30 in the third embodiment.

The following table 13, in accordance with the above conditions, lists the values in this embodiment correspond-

40

ing with each condition expression. Apparently, the camera optical system of this embodiment satisfies the above conditions.

In this embodiment, the pupil entering diameter of the camera optical lens is 1.502 mm, the full vision field image height is 2.933 mm, the vision field angle in the diagonal direction is 82.96°, it has wide-angle and is ultra-thin, its on-axis and off-axis chromatic aberrations are fully corrected, and it has excellent optical characteristics.

TABLE 13

	Embodiment 1	Embodiment 2	Embodiment 3
f	3.319	3.280	3.273
f1	-6.871	-8.211	-9.799
f2	210.537	70.835	600.603
f3	2.333	2.503	2.533
f4	-6.264	-5.443	-5.325
f5	2.076	2.325	2.259
f6	-2.630	-3.499	-3.302
f12	-6.651	-8.657	-9.365
f12/f	-2.004	-2.639	-2.861
(R1 + R2)/(R1 - R2)	2.011	3.201	3.788
(R3 + R4)/(R3 - R4)	36.654	59.475	34.985
(R5 + R6)/(R5 - R6)	-0.771	-0.780	-0.783
(R7 + R8)/(R7 - R8)	-2.994	-2.469	-2.426
(R9 + R10)/(R9 - R10)	1.579	1.646	1.628
(R11 + R12)/(R11 - R12)	3.241	4.330	4.437
f1/f	-2.070	-2.503	-2.994
f2/f	63.433	21.595	183.484
f3/f	7.029E-01	7.631E-01	7.738E-01

45

50

55

60

65

13

TABLE 13-continued

	Embodiment 1	Embodiment 2	Embodiment 3
f4/f	-1.887	-1.659	-1.627
f5/f	0.625	0.709	0.690
f6/f	-0.793	-1.067	-1.009
f12/f	-2.004	-2.639	-2.861
d1	0.215	0.213	0.215
d3	0.215	0.213	0.215
d5	0.530	0.503	0.495
d7	0.257	0.312	0.339
d9	0.452	0.474	0.494
d11	0.350	0.330	0.305
Fno	2.000	2.175	2.180
TTL	4.713	4.701	4.701
d1/TTL	0.046	0.045	0.046
d3/TTL	0.046	0.045	0.046
d5/TTL	0.113	0.107	0.105
d7/TTL	0.055	0.066	0.072
d9/TTL	0.096	0.101	0.105
d11/TTL	0.074	0.070	0.065
n1	1.5352	1.5352	1.5352
n2	1.6613	1.6613	1.6613
n3	1.5352	1.5352	1.5352
n4	1.6613	1.6613	1.6613
n5	1.5352	1.5352	1.5352
n6	1.7015	1.8340	1.8919
v1	56.0934	56.0934	56.0934
v2	20.3729	20.3729	20.3729
v3	56.0934	56.0934	56.0934
v4	20.3729	20.3729	20.3729
v5	56.0934	56.0934	56.0934
v6	41.2394	37.1669	37.1340

It is to be understood, however, that even though numerous characteristics and advantages of the present exemplary embodiments have been set forth in the foregoing description, together with details of the structures and functions of the embodiments, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms where the appended claims are expressed.

What is claimed is:

1. A camera optical lens comprising, from an object side to an image side in sequence: a first lens, a second lens, a third lens, a fourth lens, a fifth lens and a sixth lens; wherein the second lens has a positive refractive power, the third lens has a positive refractive power; the camera optical lens further satisfies the following conditions:

$$-3 \leq f1/f \leq -1;$$

$$1.7 \leq n6 \leq 2.2;$$

$$0.03 \leq d11/TTL \leq 0.075;$$

$$1.61 \leq (R1+R2)/(R1-R2) \leq 4.55;$$

$$0.04 \leq d1/TTL \leq 0.05; \text{ where}$$

- f: the focal length of the camera optical lens;
- f1: the focal length of the first lens;
- n6: the refractive power of the sixth lens;
- d11: the thickness on-axis of the sixth lens;
- R1: the curvature radius of object side surface of the first lens;
- R2: the curvature radius of image side surface of the first lens;
- d1: the thickness on-axis of the first lens;
- TTL: the total optical length of the camera optical lens.

14

2. The camera optical lens as described in claim 1, wherein the first lens is made of plastic material, the second lens is made of plastic material, the third lens is made of plastic material, the fourth lens is made of plastic material, the fifth lens is made of plastic material, the sixth lens is made of glass material.

3. The camera optical lens as described in claim 1, wherein the camera optical lens further satisfies the following conditions:

$$-2.997 \leq f1/f \leq -1.535;$$

$$1.701 \leq n6 \leq 2.046;$$

$$0.0475 \leq d11/TTL \leq 0.0745.$$

4. A camera optical lens comprising, from an object side to an image side in sequence: a first lens, a second lens, a third lens, a fourth lens, a fifth lens and a sixth lens; wherein the second lens has a positive refractive power, the third lens has a positive refractive power;

wherein the second lens has a convex object side surface and a concave image side surface; the camera optical lens further satisfies the following conditions:

$$-3 \leq f1/f \leq -1;$$

$$1.7 \leq n6 \leq 2.2;$$

$$0.03 \leq d11/TTL \leq 0.075;$$

$$10.8 \leq f2/f \leq 275.23;$$

$$17.49 \leq (R3+R4)/(R3-R4) \leq 89.21;$$

$$0.02 \leq d3/TTL \leq 0.07; \text{ where}$$

- f: the focal length of the camera optical lens;
- f1: the focal length of the first lens;
- n6: the refractive power of the sixth lens;
- d11: the thickness on-axis of the sixth lens;
- f2: the focal length of the second lens;
- R3: the curvature radius of the object side surface of the second lens;
- R4: the curvature radius of the image side surface of the second lens;
- d3: the thickness on-axis of the second lens;
- TTL: the total optical length of the camera optical lens.

5. The camera optical lens as described in claim 4, wherein the camera optical lens further satisfies the following conditions:

$$17.28 \leq f2/f \leq 220.18;$$

$$27.99 \leq (R3+R4)/(R3-R4) \leq 71.37;$$

$$0.04 \leq d3/TTL \leq 0.05.$$

6. The camera optical lens as described in claim 1, wherein the third lens has a convex object side surface and a convex image side surface; the camera optical lens further satisfies the following conditions:

$$0.35 \leq f3/f \leq 1.16;$$

$$-1.57 \leq (R5+R6)/(R5-R6) \leq -0.51;$$

$$0.05 \leq d5/TTL \leq 0.17; \text{ where}$$

- f: the focal length of the camera optical lens;
- f3: the focal length of the third lens;
- R5: the curvature radius of the object side surface of the third lens;

R6: the curvature radius of the image side surface of the third lens;  
 d5: the thickness on-axis of the third lens;  
 TTL: the total optical length of the camera optical lens.

7. The camera optical lens as described in claim 6, wherein the camera optical lens further satisfies the following conditions:

$$0.56 \leq f_3/f \leq 0.93;$$

$$-0.98 \leq (R_5+R_6)/(R_5-R_6) \leq -0.64;$$

$$0.08 \leq d_5/TTL \leq 0.14.$$

8. The camera optical lens as described in claim 1, wherein the fourth lens has a negative refractive power with a concave object side surface and a convex image side surface; the camera optical lens further satisfies the following conditions:

$$-3.77 \leq f_4/f \leq -1.08;$$

$$-5.99 \leq (R_7+R_8)/(R_7-R_8) \leq -1.62;$$

$$0.03 \leq d_7/TTL \leq 0.11; \text{ where}$$

f: the focal length of the camera optical lens;  
 f4: the focal length of the fourth lens;  
 R7: the curvature radius of the object side surface of the fourth lens;  
 R8: the curvature radius of the image side surface of the fourth lens;  
 d7: the thickness on-axis of the fourth lens;  
 TTL: the total optical length of the camera optical lens.

9. The camera optical lens as described in claim 8, wherein the camera optical lens further satisfies the following conditions:

$$-2.36 \leq f_4/f \leq -1.36;$$

$$-3.74 \leq (R_7+R_8)/(R_7-R_8) \leq -2.02;$$

$$0.04 \leq d_7/TTL \leq 0.09.$$

10. The camera optical lens as described in claim 1, wherein the fifth lens has a positive refractive power with a concave object side surface and a convex image side surface; the camera optical lens further satisfies the following conditions:

$$0.31 \leq f_5/f \leq 1.06;$$

$$0.79 \leq (R_9+R_{10})/(R_9-R_{10}) \leq 2.47;$$

$$0.05 \leq d_9/TTL \leq 0.16; \text{ where}$$

f: the focal length of the camera optical lens;  
 f5: the focal length of the fifth lens;  
 R9: the curvature radius of the object side surface of the fifth lens;  
 R10: the curvature radius of the image side surface of the fifth lens;  
 d9: the thickness on-axis of the fifth lens;  
 TTL: the total optical length of the camera optical lens.

11. The camera optical lens as described in claim 10, wherein the camera optical lens further satisfies the following conditions:

$$0.5 \leq f_5/f \leq 0.85;$$

$$1.26 \leq (R_9+R_{10})/(R_9-R_{10}) \leq 1.97;$$

$$0.08 \leq d_9/TTL \leq 0.13.$$

12. The camera optical lens as described in claim 1, wherein the sixth lens has a negative refractive power with a convex object side surface and a concave image side surface; the camera optical lens further satisfies the following conditions:

$$-2.13 \leq f_6/f \leq -0.53;$$

$$1.62 \leq (R_{11}+R_{12})/(R_{11}-R_{12}) \leq 6.66;$$

$$0.03 \leq d_{11}/TTL \leq 0.11; \text{ where}$$

f: the focal length of the camera optical lens;  
 f6: the focal length of the sixth lens;  
 R11: the curvature radius of the object side surface of the sixth lens;  
 R12: the curvature radius of the image side surface of the sixth lens;  
 d11: the thickness on-axis of the sixth lens;  
 TTL: the total optical length of the camera optical lens.

13. The camera optical lens as described in claim 12, wherein the camera optical lens further satisfies the following conditions:

$$-1.33 \leq f_6/f \leq -0.66;$$

$$2.59 \leq (R_{11}+R_{12})/(R_{11}-R_{12}) \leq 5.32;$$

$$0.05 \leq d_{11}/TTL \leq 0.09.$$

14. The camera optical lens as described in claim 1, wherein the camera optical lens further satisfies the following conditions:

$$-5.72 \leq f_{12}/f \leq -1.34; \text{ where}$$

f: the focal length of the camera optical lens;  
 f12: the combined focal length of the first lens and the second lens.

15. The camera optical lens as described in claim 14, wherein the camera optical lens further satisfies the following conditions:

$$-3.58 \leq f_{12}/f \leq -1.67.$$

16. The camera optical lens as described in claim 1, wherein the total optical length TTL of the camera optical lens is less than or equal to 5.18 mm.

17. The camera optical lens as described in claim 1, wherein the aperture F number of the camera optical lens is less than or equal to 2.25.

18. The camera optical lens as described in claim 1, wherein the aperture F number of the camera optical lens is less than or equal to 2.20.

19. The camera optical lens as described in claim 4, wherein the aperture F number of the camera optical lens is less than or equal to 2.20.

\* \* \* \* \*