



US 20020079106A1

(19) **United States**

(12) **Patent Application Publication**
SIMPSON

(10) **Pub. No.: US 2002/0079106 A1**

(43) **Pub. Date: Jun. 27, 2002**

(54) **PROCEDURES AND EQUIPMENT FOR
PROFILING AND JOINTING OF PIPES**

(52) **U.S. Cl. 166/380; 166/55.8; 166/207;
72/119**

(76) **Inventor: NEIL ANDREW ABERCROMBIE
SIMPSON, ABERDEEN (GB)**

(57) **ABSTRACT**

Correspondence Address:

**W BRUCE PATTERSON
THOMASON MOSER & PATTERSON LLP
3040 POST OAK BLVD SUITE 1500
HOUSTON, TX 77056**

(*) **Notice:** This is a publication of a continued prosecution application (CPA) filed under 37 CFR 1.53(d).

(21) **Appl. No.: 09/469,690**

(22) **Filed: Dec. 22, 1999**

(30) **Foreign Application Priority Data**


Dec. 22, 1998	(GB)	9828234.6
Jan. 15, 1999	(GB)	9900835.1
Oct. 8, 1999	(GB)	9923783.6
Oct. 13, 1999	(GB)	9924189.5


Publication Classification

(51) **Int. Cl.⁷ E21B 23/02**

Methods and apparatus for shaping pipes, tubes, liners, or casing at downhole locations in wells. Use is made of rollers bearing radially outwards against the inside wall of the pipe (etc.), the rollers being rolled around the pipe to cause outward plastic deformation which expands and shapes the pipe to a desired profile. Where one pipe is inside another, the two pipes can be joined without separate components (except optional seals). Landing nipples and liner hangers can be formed in situ. valves can be deployed to a selected downhole location and there sealed to the casing or liner without separate packers. Casing can be deployed downhole in reduced-diameter lengths and then expanded to case a well without requiring larger diameter bores and casing further uphole.

The invention enables simplified downhole working, and enables a well to be drilled & produced with the minimum downhole bore throughout its depth, obviating the need for large bores. When expanding lengths of casing, the casing does not need to be anchored or made pressure-tight. The profiling/expansion tools of the invention can be deployed downhole on coiled tubing, and operated without high tensile loads on the coiled tubing.










Fig. 4






Fig. 9A




Fig. 9B




Fig. 10A




Fig. 10B

FIG. 10A and FIG. 10B are schematic diagrams of a container assembly.




Fig. 11A




Fig. 11B




Fig. 12A







Fig. 12B








Fig. 15 A




Fig. 15 B
Pulse - 150 MHz, B




Fig. 16B




Fig. 16A




Fig. 17B




Fig. 17A





Fig. 19





Fig. 20











Fig. 21A




















Fig. 29B





Fig. 29A

NOTES

CAD RELEASE CHECK		
DESIGNER APPROVAL	DESIGNING APPROVAL	RELEASE DATE

Fig. 7



PROCEDURES AND EQUIPMENT FOR PROFILING AND JOINTING OF PIPES

BACKGROUND OF THE INVENTION

[0001] This invention relates to procedures and equipment for profiling and jointing of pipes, and relates more particularly but not exclusively to methods and apparatus for the shaping and/or expansion and/or conjoining of tubular casings in wells.

[0002] In the hydrocarbon exploration and production industry there is a requirement to deploy tubular casings in relatively narrow-bore wells, and to expand the deployed casing in situ. The casing may require to be expanded throughout its length in order to line a bore drilled through geological material; the casing may additionally or alternatively require to be expanded at one end where it overlaps and lies concentrically within another length of previously deployed casing in order to form a swaged joint between the two lengths of casing. Proposals have been made that a slotted metal tube be expanded by mechanically pulling a mandrel through the tube, and that a solid-walled steel tube be expanded by hydraulically pushing a part-conical ceramic plunger through the tube. In both of these proposals, very high longitudinal forces would be exerted throughout the length of the tubing, which accordingly would require to be anchored at one end. Where mechanical pulling is to be employed, the pulling force would require to be exerted through a drillstring (in relatively large diameter wells) or through coiled tubing (in relatively small diameter wells). The necessary force would become harder to apply as the well became more deviated (i.e. more non-vertical), and in any event, coiled tubing may not tolerate high longitudinal forces. Where hydraulic pushing is to be employed, the required pressure may be hazardously high, and in any event the downhole system would require to be pressure-tight and substantially leak-free. (This would preclude the use of a hydraulically pushed mandrel for the expansion of slotted tubes). The use of a fixed-diameter mandrel or plug would make it impracticable or impossible to control or to vary post-deformation diameter after the start of the expansion procedure.

[0003] It is therefore an object of the invention to provide new and improved procedures and equipment for the profiling or jointing of pipes or other hollow tubular articles, which obviate or mitigate at least some of the disadvantages of the prior art.

[0004] In the following specification and claims, references to a "pipe" are to be taken as references to a hollow tubular pipe and to other forms of hollow tubular article, and references to "profiling" are to be taken as comprising alteration of shape and/or dimension(s) which alteration preferably takes place substantially without removal of material.

BRIEF SUMMARY OF THE INVENTION

[0005] According to a first aspect of the present invention there is provided a profiling method for profiling a pipe or other hollow tubular article, the profiling method comprising the steps of applying a roller means to a part of the pipe bore selected to be profiled, translating the roller means across the bore in a direction including a circumferential component while applying a force to the roller means in a radially

outwards direction with respect to the longitudinal axis of the pipe, and continuing such translation and force application until the pipe is plastically deformed substantially into the intended profile.

[0006] The deformation of the pipe may be accomplished by radial compression of the pipe wall or by circumferential stretching of the pipe wall, or by a combination of such radial compression and circumferential stretching.

[0007] Said direction may be purely circumferential, or said direction may partly circumferential and partly longitudinal.

[0008] Said roller means is preferably peripherally profiled to be complementary to the profile into which the selected part of the pipe bore is intended to be formed.

[0009] The selected part of the pipe bore may be remote from an open end of the pipe, and the profiling method then comprises the further steps of inserting the roller means into the open end of the pipe (if the roller means is not already in the pipe), and transferring the roller means along the pipe to the selected location. Transfer of the roller means is preferably accomplished by the step of actuating traction means coupled to or forming part of the roller means and effective to apply along-pipe traction forces to the roller means by reaction against parts of the pipe bore adjacent the roller means.

[0010] The profiling method according to the first aspect of the present invention can be applied to the profiling of casings and liners deployed in a well (e.g. a hydrocarbon exploration or production well), and the profile created by use of the method may be a liner hanger, or a landing nipple, or another such downhole profile of the type which previously had to be provided by inserting an annular article or mechanism into the well, lowering it to the required depth, and there anchoring it (which required either a larger diameter of well for a given through diameter, or a restricted through diameter for a given well diameter, together with the costs and inconvenience of manufacturing and installing the article or mechanism). Additionally or alternatively, the profiling method according to the first aspect of the present invention can be applied to increasing the diameter of a complete length of pipe; for example, where a well has been cased to a certain depth (the casing having a substantially constant diameter), the casing can be extended downwardly by lowering a further length of pipe (of lesser diameter such that it freely passes down the previously installed casing) to a depth where the top of the further length lies a short way into the lower end of the previously installed casing and there expanding the upper end of the further length to form a joint with the lower end of the previously installed casing (e.g. by using the method according to the second aspect of the present invention), followed by circumferential expansion of the remainder of the further length to match the bore of the previously installed casing.

[0011] According to a second aspect of the present invention there is provided a conjoining method for conjoining two pipes or other hollow tubular articles, said conjoining method comprising the steps of locating one of the two pipes within and longitudinally overlapping one of the other of the two pipes, applying roller means to a part of the bore of the inner of the two pipes at a location where it is intended that the two pipes be conjoined, translating the roller means

across the bore in a direction including a circumferential component while applying a radially outwardly directed force to the roller means, and continuing such translation and force application until the inner pipe is plastically deformed into permanent contact with the outer pipe and is thereby conjoined thereto.

[0012] Said deformation may be accomplished by radial compression of the pipe wall or by circumferential stretching of the pipe wall, or by a combination of such radial compression and circumferential stretching.

[0013] Said direction may be purely circumferential, or said direction may be partly circumferential and partly longitudinal.

[0014] The location where the pipes are intended to be conjoined may be remove from an accessible end of the bore, and the conjoining method then comprises the further steps of inserting the roller means into the accessible end of the bore (if the roller means is not already in the bore), and transferring the roller means to the intended location. Transfer of the roller means is preferably accomplished by the step of actuating traction means coupled to or forming part of the roller means and effective to apply along-bore traction forces to the roller means by reaction against parts of the pipe bore adjacent the roller means.

[0015] The conjoining method according to the second aspect of the present invention can be applied to the mutual joining of successive lengths of casing or liner deployed in a well (e.g. a hydrocarbon exploration or production well), such that conventional screw-threaded connectors are not required.

[0016] According to third aspect of the present invention, there is provided expansion apparatus for expanding a pipe or other hollow tubular article, said expansion apparatus comprising roller means constructed or adapted for rolling deployment against the bore of the pipe, said roller means comprising at least one set of individual rollers each mounted for rotation about a respective rotation axis which is generally parallel to the longitudinal axis of the apparatus, the rotation axes of said at least one set of rollers being circumferentially distributed around the expansion apparatus and each being radially offset from the longitudinal axis of the expansion apparatus, the expansion apparatus being selectively rotatable around its longitudinal axis.

[0017] The rotation axes of said at least one set of rollers may conform to a first regime in which each said rotation axis is substantially parallel to the longitudinal axis of the expansion apparatus in a generally cylindrical configuration, or the rotation axes of said at least one set of rollers may conform to a second regime in which each said rotation axis lies substantially in a respective radial plane including the longitudinal axis of the expansion apparatus and the rotation axes each converge substantially towards a common point substantially on the longitudinal axis of the expansion apparatus in a generally conical configuration, or the rotation axes of said at least one set of rollers may conform to third regime in which each said rotation axis is similarly skewed with respect to the longitudinal axis of the expansion apparatus in a generally helical configuration which may be non-convergent (cylindrical) or convergent (conical). Rollers in said first regime are particularly suited to profiling and finish expansion of pipes and other hollow tubular articles,

rollers in said second regime are particularly suited to commencing expansion in, and to flaring of pipes, and other hollow tubular articles, while rollers in said third regime are suited to providing longitudinal traction in addition to such functions of the first or second regimes as are provided by other facets of the roller axes besides skew. The expansion apparatus may have only a single such set of rollers, or the expansion apparatus may have a plurality of such sets of rollers which may conform to two or more of the aforesaid regimes of roller axis alignments; in a particular example where the expansion apparatus has a set of rollers conforming to the second regime located at leading end of the exemplary expansion apparatus and another set of rollers conforming to the first regime located elsewhere on the exemplary expansion apparatus, this exemplary expansion apparatus is particularly suited to expanding complete lengths of hollow tubular casing by reason of the conically disposed leading set of rollers opening up previously unexpanded casing and the following set of cylindrically disposed rollers finish-expanding the casing to its intended final diameter; if this exemplary expansion apparatus were modified by the addition of a further set of rollers conforming to third regime with non-convergent axes, this further set of rollers could be utilised for the purpose of applying traction forces to the apparatus by means of the principles described in the present inventor's previously published PACT patent application W/24728-A, the concerns of which are incorporated herein by reference.

[0018] The rollers of said expansion apparatus may each be mounted for rotation about its respective rotation axis substantially without freedom of movement along its respective rotation axis, or the rollers may each be mounted for rotation about its respective rotation axis with freedom of movement along its respective rotation axis, preferably within predetermined limits of movement. In the latter case (freedom of along-axis movement within predetermined limits), this is advantageous in the particular case of rollers conforming to the afore-mentioned second regime (i.e. a conical array of rollers) in that the effective maximum outside diameter of the rollers depends on the position of the rollers along the axis of the expansion apparatus and this diameter is thereby effectively variable; this allows relief of radially outwardly directed forces by longitudinally retracting the expansion apparatus to allow the rollers collectively to move longitudinally in the convergent direction and hence collectively to retract radially inwards away from the bore against which they were immediately previously pressing.

[0019] According to a fourth aspect of the present invention, there is provided profiling/conjoining apparatus for profiling or conjoining pipes or other hollow tubular articles, said profiling/conjoining apparatus comprising roller means and radial urging means selectively operable to urge the roller means radially outwards of a longitudinal axis of the profiling/conjoining apparatus, the radial urging means causing or allowing the roller means to move radially inwards towards the longitudinal axis of the profiling/conjoining apparatus when the radial urging means is not operated, the roller means comprising a plurality of individual rollers each mounted for rotation about a respective rotation axis which is substantially parallel to the longitudinal axis of the profiling/conjoining apparatus, the rotation axes of the individual rollers being circumferentially distributed around the apparatus and each said rotation axis being radially offset from the longitudinal axis of the pro-

filig/conjoining apparatus, the profiling/conjoining apparatus being selectively rotatable around its longitudinal axis to translate the roller means across the bore of a pipe against which the roller means is being radially urged.

[0020] The radial urging means may comprise a respective piston on which each said roller is individually rotatably mounted, each said piston being slidably sealed in a respective radially extending bore formed in a body of the profiling/conjoining apparatus, a radially inner end of each said bore being in fluid communication with fluid pressure supply means selectively pressurisable to operate said radial urging means.

[0021] Alternatively, the radial urging means may comprise bi-conical race means upon which each said individual roller rolls in use of the profiling/conjoining apparatus, and separation variation means selectively operable controllably to vary the longitudinal separation of the two conical races of the bi-conical race means whereby correspondingly to vary the radial displacement of each said roller rotation axis from the longitudinal axis of the profiling/conjoining apparatus. The separation variation means may comprise hydraulic linear motor means selectively pressurisable to drive one of said two cones longitudinally towards and/or away from the other said cone.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0022] Embodiments of the invention will now be described by way of example, with reference to the accompanying drawings wherein:

[0023] **FIG. 1** is a plan view of a first embodiment of profiling tool;

[0024] **FIG. 2** is an elevation of the profiling tool of **FIG. 1**;

[0025] **FIG. 3** is a sectional perspective view of the profiling tool of **FIGS. 1 & 2**, the section being taken on the line III-III in **FIG. 2**;

[0026] **FIG. 4** is an exploded perspective view of the profiling tool of **FIGS. 1-4**;

[0027] **FIGS. 5A, 5B, & 5C** are simplified sectional views of three successive stages of operation of the profiling tool of **FIGS. 1-4**;

[0028] **FIG. 6** is a schematic diagram illustrating the metallurgical principle underlying the operational stage depicted in **FIG. 5C**;

[0029] **FIGS. 7A & 7B** are illustrations corresponding to **FIGS. 5A & 5B** but in respect of a variant of the **FIGS. 1-4** profiling tool having two rollers instead of three;

[0030] **FIGS. 8A & 8B** are illustrations corresponding to **FIGS. 5A & 5B** but in respect of a variant of the **FIGS. 1-4** profiling tool having five rollers instead of three;

[0031] **FIGS. 9A & 9B** respectively illustrate starting and finishing stages of a first practical application of the profiling tool of **FIGS. 1-4**;

[0032] **FIGS. 10A & 10B** respectively illustrate starting and finishing stages of a second practical application of the profiling tool of **FIGS. 1-4**;

[0033] **FIGS. 11A & 11B** respectively illustrate starting and finishing stages of a third practical application of the profiling tool of **FIGS. 1-4**;

[0034] **FIGS. 12A & 12B** respectively illustrate starting and finishing stages of a fourth practical application of the profiling tool of **FIGS. 1-4**;

[0035] **FIGS. 13A & 13B** respectively illustrate starting and finishing stages of a fifth practical application of the profiling tool of **FIGS. 1-4**;

[0036] **FIGS. 14A & 14B** respectively illustrate starting and finishing stages of a sixth practical application of the profiling tool of **FIGS. 1-4**;

[0037] **FIGS. 15A & 15B** respectively illustrate starting and finishing stages of a seventh practical application of the profiling tool of **FIGS. 1-4**;

[0038] **FIGS. 16A & 16B** respectively depict starting and finishing stages of an eighth practical application of the profiling tool of **FIGS. 1-4**;

[0039] **FIGS. 17A & 17B** respectively depict starting and finishing stages of a ninth practical application of the profiling tool of **FIGS. 1-4**;

[0040] **FIG. 18** schematically depicts a tenth practical application of the profiling tool of **FIGS. 1-4**;

[0041] **FIG. 19** schematically depicts an eleventh practical application of the profiling tool of **FIGS. 1-4**;

[0042] **FIG. 20** is a longitudinal elevation of a first embodiment of expansion tool in accordance with the present invention;

[0043] **FIG. 21** is a longitudinal elevation, to an enlarged scale, of part of the expansion tool of **FIG. 20**;

[0044] **FIG. 21A** is an exploded view of the tool part illustrated in **FIG. 20**;

[0045] **FIG. 22** a longitudinal section of the tool part illustrated in **FIG. 20**;

[0046] **FIG. 23** is a longitudinal section of the expansion tool illustrated in **FIG. 21**;

[0047] **FIG. 24** is an exploded view of part of the expansion tool illustrated in **FIG. 20**;

[0048] **FIG. 25** is a longitudinal section of an alternative form of the tool part illustrated in **FIG. 21**;

[0049] **FIG. 26** is a longitudinal section of a technical variant of the tool part illustrated in **FIG. 21**;

[0050] **FIG. 27** is a longitudinal elevation of a second embodiment of expansion tool in accordance with the present invention;

[0051] **FIGS. 28A, 28B, & 28C** are respectively a longitudinal section, a longitudinal elevation, and a simplified end view of a third embodiment of expansion tool in accordance with the present invention;

[0052] **FIGS. 29A & 29B** are longitudinal sections of a fourth embodiment of expansion tool in accordance with the present invention, respectively in expanded and contracted configurations; and

[0053] FIG. 30 is a longitudinal section of a fifth embodiment of expansion tool in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS OF THE INVENTION

[0054] Referring first to FIGS. 1 & 2, these depict a three-roller profiling tool 100 in accordance with the present invention. The tool 100 has a body 102 which is hollow and generally tubular, with conventional screw-threaded end connectors 104 & 106 for connection to other components (not shown) of a downhole assembly. The end connectors 104 & 106 are of reduced diameter (compared to the outside diameter of the longitudinally central body part 108 of the tool 100), and together with three longitudinal flutes 110 on the central body part 108, allow the passage of fluids along the outside of the tool 100. The central body part 108 has three lands 112 defined between the three flutes 110, each land 112 being formed with a respective recess 114 to hold a respective roller 116 (see also FIGS. 3 & 4). Each of the recesses 114 has parallel sides and extends radially from the radially perforated tubular core 115 of the tool 100 to the exterior of the respective land 112. Each of the mutually identical rollers 116 is near-cylindrical and slightly barrelled (i.e. of slightly greater diameter in its longitudinally central region than at either longitudinal end, with a generally convex profile having a discontinuity-free transition between greatest and least diameters). Each of the rollers 116 is mounted by means of a bearing 118 at each end of the respective roller for rotation about a respective rotation axis which is parallel to the longitudinal axis of the tool 100 and radially offset therefrom at 120-degree mutual circumferential separations around the central part 108. The bearings 118 are formed as integral end members of radially slidable pistons 120, one piston 120 being slidably sealed within each radially extending recess 114. The inner end of each piston 120 is exposed to the pressure of fluid within the hollow core of the tool 100 by way of the radial perforations in the tubular core 115; in use of the tool 100, this fluid pressure will be the downhole pressure of mud or other liquid within a drillstring or coiled tubing at or near the lower end of which the tool 100 will be mounted. Thus by suitably pressurising the core 115 of the tool 100, the pistons 120 can be driven radially outwards with a controllable force which is proportional to the pressurisation, and thereby the piston-mounted rollers 116 can be forged against a pipe bore in a manner to be detailed below. Conversely, when the pressurisation of the core 115 of the tool 100 is reduced to below whatever is the ambient pressure immediately outside the tool 100, the pistons 120 (together with the piston-mounted rollers 116) are allowed to retract radially back into their respective recesses 114. (Such retraction can optionally be encouraged by suitably disposed springs (not shown)).

[0055] The principles by which the profiling tool 100 functions will now be detailed with reference to FIGS. 5 and 6.

[0056] FIG. 5A is a schematic end view of the three rollers 116 within the bore of an inner pipe 180, the remainder of the tool 100 being omitted for the sake of clarity. The pipe 180 is nested within an outer pipe 190 whose internal diameter is somewhat greater than the outside diameter of the inner pipe 180. As depicted in FIG. 5A,

the core of the tool 100 has been pressurised just sufficiently to push the pistons 120 radially outwards and thereby to bring the piston-mounted rollers 116 into contact with the bore of the inner pipe 180, but without at first exerting any significant forces on the pipe 180.

[0057] FIG. 5B depicts the next stage of operation of the profiling tool 100, in which the internal pressurisation of the tool 100 is increased sufficiently above its external pressure (i.e. the pressure in the region between the exterior of the tool 100 and the bore of the pipe 180) such that the rollers 116 each exert a substantial outward force, as denoted by the arrow-headed vectors superimposed on each roller 116 in FIG. 5B. The effect of such outward forces on the rollers 116 is circumferentially to deform the wall of the inner pipe 180 (with concomitant distortion of the pipe 180 which is shown in FIG. 5B for the sake of clarity). When the roller-extended lobes touch the bore of the outer pipe 190, the inner pipe 180 is thereby anchored against rotation with respect to the outer pipe 190, or at least constrained against free relative rotation. By simultaneously rotating the tool 100 around its longitudinal axis (which will normally be substantially coincident with the longitudinal axis of the pipe 180), the circumferential deformation of the wall of the pipe 180 tends to become uniform around the pipe 180, and the pipe 180 circumferentially extends into substantially uniform contact with the bore of the outer pipe 190, as depicted in FIG. 5C. This occurs due to the rollers causing rolling compressive yield of the inner pipe wall to cause reduction in wall thickness, increase in circumference and consequent increase in diameter. (Rotation of the tool 100 can be undertaken by any suitable procedure, several of which will subsequently be described). Circumferential deformation of the pipe 180 is initially elastic and may subsequently be plastic. A secondary effect of the process is to generate compressive hoop stress in the internal portion of the inner tube and an interference fit between the inner tube and the outer tube.

[0058] From the stage depicted in FIG. 5C wherein the inner pipe 180 has initially been circumferentially deformed just into full contact with the bore of the outer pipe 190 (thus removing the previous clearance between the pipes 180 and 190) but without stretching or distortion of the outer pipe 190, continued (and possibly increased) internal pressurisation of the tool 100 in conjunction with continued rotation of the tool 100 (at the same rotational speed or at a suitably different rotational speed) forces the inner pipe 180 outwards against the resistance to deformation of the outer pipe 190. Since the inner pipe 180 is now backed by the outer pipe 190 with respect to the radially outward forces being applied by the rollers 116 such that the wall of the inner pipe 180 is now pinched between the rollers 116 and the outer pipe 190, the mechanism of deformation of the pipe 180 changes to compressive extension by rolling (i.e. the same thinning/extension principle as prevails in conventional steel rolling mills, as schematically depicted in FIG. 6 wherein the circular rolling of FIGS. 5A-5C has been opened out and developed into an equivalent straight-line rolling procedure to enhance the analogy with steel rolling mills).

[0059] When operation of the tool 100 is terminated and the rollers 116 are caused or allowed to retract radially into the body of the tool 100 thereby to relieve the pipes 180 of all contact with the rollers 116, the induced compressive hoop stress created in the wall of the inner pipe 180 due to

the rolling process causes the inner pipe **180** to remain in contact with the inner wall of the outer pipe **190** with very high contact stresses at their interface.

[0060] FIGS. 7A & 7B correspond to FIGS. 5A & 5B, and schematically depict the equivalent stages of operation of a two-roller profiling tool (not otherwise shown per se) in order to illustrate the effects of using a profiling tool having fewer than the three rollers of the profiling tool **100** detailed above.

[0061] FIGS. 8A & 8B also correspond to FIGS. 5A & 5B, and schematically depict the equivalent stages of operation of a five-roller profiling tool (not otherwise shown per se) in order to illustrate the effects of using a profiling tool having more than the three rollers of the profiling tool **100** detailed above.

[0062] It should be noted that though the very high contact stresses existing at the interface of the inner pipe **180** and outer pipe **190** may cause the outer pipe **190** to expand elastically or plastically, it is not a requirement of this process that the outer pipe **190** is capable of any expansion whatsoever. The process would still result in the high contact stresses between the inner pipe **180** and the outer pipe **190** even if the outer pipe **190** was incapable of expansion, eg by being thick walled, by being encased in cement, or being tightly embedded in a rock formation.

[0063] Various practical applications of profiling tools in accordance with the invention will now be described with reference to FIGS. 9-19. the profiling tool used in these practical applications may be the profiling tool **100** detailed above, or some variant of such a profiling tool which differs in one or more details without departing from the scope of the invention.

[0064] FIG. 5A schematically depicts the upper end of a first pipe or casing **200** concentrically nested within the lower end of a second pipe or casing **202** whose bore (internal diameter) is marginally greater than the outside diameter of the first pipe or casing **200**. A profiling tool (not shown) is located within the upper end of the first pipe or casing **200** where it is overlapped by the second pipe or casing **202**. The rollers of the profiling tool are then radially extended into contact with the bore of the inner pipe or casing **200** by means of internal pressurisation of the profiling tool (or by any other suitable means which may alternatively be utilised for forcing the rollers radially outwards of the profiling tool). The outward forces exerted by the rollers on the bore of the first pipe or casing **200** are schematically depicted by the force-vector-depicting arrows **204**.

[0065] From the starting situation depicted in FIG. 9A, combined with suitable rotation of the profiling tool about its longitudinal axis (which is substantially coincident with the longitudinal axis of the first pipe or casing **200**), the finish situation schematically depicted in FIG. 9B is arrived at, namely the upper end of the inner pipe or casing **200** is profiled by permanent plastic expansion into conjunction with the lower end of the second pipe or casing **202**. Thereby the two pipes or casings are permanently conjoined without the use of any form of separate connector and without the use of conventional joining techniques such as welding.

[0066] FIGS. 10A & 10B correspond to FIGS. 9A & 9B respectively, and schematically illustrate an optional modi-

fication of the profiling/conjoining technique described with respect to FIGS. 9A & 9B. The modification consists of applying an adherent coating **206** of hard particulate material to the exterior of the upper end of the first (inner) pipe or casing **200** prior to its location within the lower end of the second (outer) pipe or casing **202**. The hard particulate material may consist of carbide granules, e.g. tungsten carbide granules such as are commonly used to coat down-hole reamers. In the application depicted in FIGS. 10A & 10B, the hard particulate material is selected for its crush resistance rather than for its abrasive qualities, and in particular the material is selected for its ability to interpenetrate the meeting surfaces of two sheets of steel which are pressed together with the hard particulate material sandwiched between the steel components. Such sandwiching is schematically depicted in FIG. 10B. Tests have shown a surprising increase in resistance to separation forces of pipes or other articles conjoined by a profiling tool in accordance with the invention to withstand, where a coating of hard particulate material was first interposed between the parts being conjoined. It is preferred that of the whole area to be coated, only a majority of the area is actually covered with the particulate material, e.g. 10% of the area. (It is believed that a higher covering factor actually reduces the interpenetration effect and hence diminishes the benefits below the optimum level).

[0067] Referring now to FIGS. 11A & 11B, these schematically depict an optional modification of the FIG. 9 conjoining procedure to achieve improved sealing between the two conjoined pipes or casings. As depicted in FIG. 11A, the modification comprises initially fitting the exterior of the first (inner) pipe or casing **200** with a circumferentially extending and part-recessed ductile metal ring **208**, which may (for example) be formed of a suitable copper alloy or a suitable tin/lead alloy. The modification also comprises initially fitting the exterior of the first (inner) pipe or casing **200** with a circumferentially extending and fully recessed elastomeric ring **210**. As depicted in FIG. 11B, the rings **208** and **210** become crushed between the two pipes or casings **200** & **202** after these have been conjoined by the profiling tool, and thereby a mutual sealing is achieved which may be expected to be superior to the basic FIG. 9 arrangement in otherwise equal circumstances. In suitable situations, one or other of the sealing rings **208** and **210** may be omitted or multiplied to achieve a necessary or desirable level of sealing (e.g. as in FIG. 12).

[0068] Referring now to FIGS. 12A & 12B, these schematically depict an arrangement in which the lower end of the second (outer) casing **202** is pre-formed to have a reduced diameter so as to function as a casing hanger. The upper end of the first (inner) casing **200** is correspondingly pre-formed to have an increased diameter which is complementary to the reduced diameter of the casing hanger formed at the lower end of the outer casing **202**, as depicted in FIG. 12A. Optionally, the upper end of the first (inner) casing **200** may be provided with an external seal in the form of an elastomeric ring **212** flush-mounted in a circumferential groove formed in the outer surface of the first casing **200**. The arrangement of FIG. 12A differs from the arrangement of FIG. 9A in that the latter arrangement requires the pipe or casing **200** to be positively held up (to avoid dropping down the well our of its intended position) until joined to the upper pipe or casing as in FIG. 9B, whereas in the FIG. 12A arrangement the casing hanger allows the inner/lower casing

200 to be lowered into position and then released without the possibility of dropping out of position prior to the two casings being conjoined by the profiling tool, as depicted in **FIG. 12B**.

[0069] Referring now to **FIGS. 13A & 13B**, these schematically depict another optional modification of the **FIG. 9** conjoining procedure in order to achieve a superior resistance to post-conjunction separation. As depicted in **FIG. 13A**, the modification consists of initially forming the bore (inner surface) of the second (outer) pipe or casing **202** with two circumferentially extending grooves **214** each having a width which reduces with increasing depth. As depicted in **FIG. 13B**, when the two pipes or casings **200** and **202** have been conjoined by the profiling tool (as detailed with respect to **FIGS. 9A & 9B**), the first (inner) pipe or casing **200** will have been plastically deformed into the grooves **214**, thereby increasing the interlocking of the conjoined pipes or casings and extending their resistance to post-conjunction separation. While two grooves **214** are shown in **FIGS. 13A & 13B** by way of example, this procedure can in suitable circumstances be carried with one such groove, or with three or more such grooves. While each of the grooves **214** has been shown with a preferred trapezoidal cross-section, other suitable groove cross-sections can be substituted.

[0070] The superior joint strength of the **FIG. 13** arrangement can be combined with the superior sealing function of the **FIG. 11** arrangement, as shown in **FIG. 14**. **FIG. 14A** schematically depicts the pre-jointing configuration, in which the exterior of the first (inner) pipe or casing **200** is fitted with a longitudinally spaced pair of circumferentially extending and part-recessed ductile metal rings **208**, while the bore (inner surface) of the second (outer) pipe or casing **202** is formed with two circumferentially extending grooves **214** each having a width which reduces with increasing depth. The longitudinal spacing of the two grooves **214** is substantially the same as the longitudinal spacing of the seal rings **208**. When the two pipes or casings are conjoined by use of the profiling tool (as schematically depicted in **FIG. 14B**), the first (inner) pipe or casing **200** is not only plastically deformed into the corresponding grooves **214** (as in **FIG. 13B**), but the metal rings **208** are crushed into the bottoms of these grooves **214** thereby to form high grade metal-to-metal seals.

[0071] In the arrangements of **FIGS. 9-14**, it is assumed that the second (outer) pipe or casing **202** undergoes little or no permanent deformation, which may either be due to the outer pipe or casing **202** being inherently rigid compared to the first (inner) pipe or casing **200**, or be due to the outer pipe or casing being rigidly backed (e.g. by cured concrete filling the annulus around the outer pipe or casing **202**), or be due to a combination of these and/or other reasons. **FIG. 15** schematically depicts an alternative situation in which the second (outer) pipe or casing **202** does not have the previously assumed rigidity. As schematically depicted in **FIG. 15A**, the pre-jointing configuration is merely a variant of the previously described pipe-joining arrangements, in which the exterior of the upper end of the first (inner) pipe or casing **200** is provided with two part-recessed metal seal rings **208** (each mounted in a respective circumferential groove), neither pipe being otherwise modified from its initial plain tubular shape. To conjoin the casings **200** and **202**, the profiling tool is operated in a manner which forces the second (outer) casing **202** through its elastic limit and into

a region of plastic deformation, such that when the conjoining process is completed, both casings retain a permanent outward set as depicted in **FIG. 15B**.

[0072] In each of the arrangements described with reference to **FIGS. 9-15**, the bore of the first pipe or casing **200** was generally smaller than the bore of the second pipe or casing **202**. However, there are situations where it would be necessary or desirable that these bores be about mutually equal following conjoining, and this requires variation of the previously described arrangements, as will now be detailed.

[0073] In the arrangement schematically depicted in **FIG. 16A**, the lower end of the second (outer) pipe or casing **202** is pre-formed to have an enlarged diameter, the bore (inside diameter) of this enlarged end being marginally greater than the outside diameter of the first (inner) pipe or casing **200** intended to be conjoined thereto. The first (inner) pipe or casing **200** has initial dimensions which are similar or identical to those of the second pipe or casing **202** (other than for the enlarged end of the pipe or casing **202**). Following use of the profiling tool to expand the overlapping ends of the two pipes or casings, both bores have about the same diameter (as depicted in **FIG. 16B**) which has certain advantages (e.g. a certain minimum bore at depth in a well no longer requires a larger or much larger bore at lesser depth in the well). While surface-level pipes can be extended in this manner without difficulties in adding extra lengths of pipe, special techniques may be necessary for feeding successive lengths of casing to downhole locations when extending casing in a downhole direction. (One possible solution to this requirement may be provide successive lengths of casing with a reduced diameter, and to expand the entire length of each successive length of casing to the uniform bore of previously installed casing, this being achievable by further aspects of the invention to be subsequently described by way of example with reference to **FIGS. 20 et seq**).

[0074] A modification of the procedure and arrangement of **FIG. 16** is schematically depicted in **FIG. 17** wherein the end of the outer pipe or casing is not pre-formed to an enlarged diameter (**FIG. 17A**). It is assumed in this case that the profiling tool is capable of exerting sufficient outward force through its rollers as to be capable of sufficiently extending the diameter of the outer pipe or casing simultaneously with the diametral extension of the inner pipe or casing during forming of the joint (**FIG. 17B**).

[0075] As well as conjoining pipes or casings, the profiling tool in accordance with the invention can be utilised for other useful purposes such as will now be detailed with reference to **FIGS. 18 and 19**.

[0076] In the situation schematically depicted in **FIG. 18**, a riser **220** has a branch **222** which is to be blocked off while continuing to allow free flow of fluid along the riser **220**. To meet this requirement, a sleeve **224** is placed within the riser **220** in position to bridge the branch **222**. The sleeve **224** initially has an external diameter which is just sufficiently less than the internal diameter of the riser **220** as to allow the sleeve **224** to be passed along the riser to its required location. Each end of the sleeve **224** is provided with external seals **226** of any suitable form, e.g. the seals described with reference to **FIG. 11**. When the sleeve **224** is correctly located across the branch **222**, a profiling tool (not shown in **FIG. 18**) is applied to each end of the sleeve **224**

to expand the sleeve ends into mechanically anchoring and fluid-sealing contact with the bore of the riser **220**, thus permanently sealing the branch (until such time as the sleeve may be milled away or a window may be cut through it).

[0077] FIG. 19 schematically depicts another alternative use of the profiling tool in accordance with the invention, in which a valve requires to be installed within plain pipe or casing **240** (i.e. pipe or casing free of landing nipples or other means of locating and anchoring downhole equipment). A valve **242** of a size to fit within the pipe or casing **240** has a hollow tubular sleeve **244** welded or otherwise secured to one end of the valve. The sleeve **244** initially has an external diameter which is just sufficiently less than the internal diameter of the pipe or casing **240** as to allow the mutually attached valve **242** and sleeve **244** to passed down the pipe or casing **240** to the required location. The end of the sleeve **244** opposite to the end attached to the valve **242** is provided with external seals **246** of any suitable form, e.g. the seals described with reference to FIG. 11. When the valve **242** is correctly located where it is intended to be installed, a profiling tool (not shown in FIG. 19) is applied to the end of the sleeve opposite the valve **242** to expand that end of the sleeve **244** into mechanically anchoring and fluid-sealing contact with the bore of the pipe or casing **240**. An optional modification of the FIG. 19 arrangement is to attach an expandable sleeve to both sides of the valve such that the valve can be anchored and sealed on either side instead of one side only as in FIG. 19.

[0078] Turning now to FIG. 20, this illustrates a side elevation of an embodiment of expansion tool **300** in accordance with the present invention. The expansion tool **300** is an assembly of a primary expansion tool **302** and a secondary expansion tool **304**, together with a connector sub **306** which is not essential to the invention but which facilitates mechanical and hydraulic coupling of the expansion tool **300** to the downhole end of a drillstring (not shown) or to the downhole end of coiled tubing (not shown). The primary expansion tool **302** is shown separately and to an enlarged scale in FIG. 21 (and again, in exploded view, in FIG. 21A). The expansion tool **300** is shown in longitudinal section in FIG. 22, the primary expansion tool **302** is shown separately in longitudinal section in FIG. 23, and the secondary expansion tool **304** is shown separately in an exploded view in FIG. 24.

[0079] From FIGS. 20-24 it will be seen that the general form of the primary expansion tool **302** is that of a roller tool externally presenting a conical array of four tapered rollers **310** tapering towards an imaginary point (not denoted) ahead of the leading end of the expansion tool **300**, i.e. the right end of the tool **300** as viewed in FIGS. 20 & 21. As may be more clearly seen in FIGS. 21A, 22, & 23, the rollers **310** run on a conical race **312** integrally formed on the surface of the body of the primary expansion tool **302**, the rollers **310** being constrained for true cracking by a longitudinally slotted cage **314**. An end retainer **316** for the rollers **310** is secured on the screw-threaded leading end **318** of the primary expansion tool **302** by means of a ring nut **320**. The trailing end **322** of the primary expansion tool **302** is screw-threaded into the leading end **106** of the secondary expansion tool **304** to form the composite expansion tool **300**. Functioning of the primary expansion tool **300** will be detailed subsequently.

[0080] The secondary expansion tool **304** is substantially identical to the previously detailed profiling tool **100** (except for one important difference which is described below), and accordingly those parts of the secondary expansion tool **304** which are the same as corresponding parts of the profiling tool **100** (or which are obvious modifications thereof) are given the same reference numerals. The important difference in the secondary expansion tool **304** with respect to the profiling tool **100** is that the rotation axes of the rollers **116** are no longer exactly parallel to the longitudinal axis of the tool, but are skewed such that each individual roller rotation axis is tangential to a respective imaginary helix, though making only a small angle with respect to the longitudinal direction (compare FIG. 24 with FIG. 4). As particularly shown in FIGS. 20 and 24, the direction (or "hand") of the skew of the rollers **116** in the secondary expansion tool **304** is such that the conventional clockwise rotation of the tool (as viewed from the uphole end of the tool, i.e. the left end as viewed in FIGS. 20 & 22) is such as to induce a reaction against the bore of the casing (not shown in FIGS. 20-24) which tends not only to rotate the tool **300** around its longitudinal axis but also to advance the tool **300** in a longitudinal direction, i.e. to drive the tool **300** rightwards as viewed in FIGS. 20 & 22. (The use of skewed bore-contacting rollers to cause a rotating downhole tool to drive itself along a casing is detailed in the above-mentioned WO93/24728-A1).

[0081] In use of the expansion tool **300** to expand casing (not shown) previously deployed to a selected downhole location in a well, the tool **300** is lowered on a drillstring (not shown) or coiled tubing (now shown) until the primary expansion tool **302** at the leading end of the tool **300** engages the uphole end of the unexpanded casing. The core of the tool **300** is pressurised to force the roller-carrying pistons **120** radially outwards and hence to force the rollers **116** into firm contact with the casing bore. The tool **300** is simultaneously caused to rotate clockwise (as viewed from its uphole end) by any suitable means (e.g. by rotating the drillstring (if used), or by actuating a downhole mud motor (not shown) through which the tool **300** is coupled to the drillstring or coiled tubing), and this rotation combines with the skew of the rollers **116** of the secondary tool **304** to drive the tool **300** as a whole in the downhole direction. The conical array of rollers **310** in the primary expansion tool **302** forces its way into the uphole end of the unexpanded casing where the combination of thrust (in a downhole direction) and rotation rolls the casing into a conical shape that expands until its inside diameter is just greater than the maximum diameter of the array of rollers **310** (i.e. the circumscribing diameter of the array of rollers **310** at its upstream end). Thereby the primary expansion tool **302** functions to bring about the primary or initial expansion of the casing.

[0082] The secondary expansion tool **304** (which is immediately uphole of the primary expansion tool **302**) is internally pressurised to a pressure which not only ensures that the rollers **116** contact the casing bore with sufficient force as to enable the longitudinal traction force to be generated by rotation of the tool about its longitudinal axis but also forces the pistons **120** radially outwards to an extent that positions the piston-carried rollers **116** sufficiently radially distant from the longitudinal axis of the tool **304** (substantially coincident with the centreline of the casing) as to complete the diametral expansion of the casing to the intended final

diameter of the casing. Thereby the secondary expansion tool **304** functions to bring about the secondary expansion of the casing. (This secondary expansion will normally be the final expansion of the casing, but if further expansion of the casing is necessary or desirable, the expansion tool **300** can be driven through the casing again with the rollers **116** of the secondary expansion tool set at a greater radial distance from the longitudinal axis of the tool **304**, or a larger expansion tool can be driven through the casing). While the primary expansion tool **302** with its conical array of rollers **310** is preferred for initial expansion of casing, the secondary expansion tool **304** with its radially adjustable rollers has the advantage that the final diameter to which the casing is expanded can be selected within a range of diameters. Moreover, this final diameter can not only be adjusted while the tool **304** is static but can also be adjusted during operation of the tool by suitable adjustment of the extent to which the interior of the tool **304** is pressurised above the pressure around the outside of the tool **104**. This feature also gives the necessary compliance to deal with variances in wall thickness.

[0083] FIG. 25 is a longitudinal section of a primary expansion tool **402** which is a modified version of the primary expansion tool **302** (detailed above with reference to FIGS. 20-24). Components of the tool **402** which correspond to components of the tool **302** are given the same reference numeral except that the leading "3" is replaced by a leading "4". The tool **402** is essentially the same as the tool **302** except that the rollers **410** are longer than the rollers **310**, and the conical race **412** has a cone angle which is less than the cone angle of the race **312** (i.e. the race **412** tapers less and is more nearly cylindrical than the race **312**). As shown in FIG. 25, the trailing (uphole) end of the tool **402** is broken away. For details of other parts of the tool **402**, reference should be made to the foregoing description of the tool **302**. In contrast to FIGS. 20-24, FIG. 25 also shows a fragment of casing **480** which is undergoing expansion by the tool **402**.

[0084] FIG. 26 is a longitudinal section of a primary expansion tool **502** which is a further-modified version of the primary expansion tool **302**. Components of the tool **502** which correspond to components of the tool **302** are given the same reference numeral except that the a leading "3" is replaced by a leading "5". The tool **502** is identical to the tool **402** except that the rollers **510** have a length which is somewhat less than the length of the rollers **410**. This reduced length allows the rollers **510** some longitudinal freedom within their windows in the cage **514**. Consequently, although expansion operation of the primary expansion tool **502** is essentially identical to operation of the primary expansion tool **410** (and similar to operation of the primary expansion tool **310** except for functional variations occasioned by the different conicities of the respective races), reversal of longitudinal thrust on the tool **502** (i.e. pulling the tool **502** uphole instead of pushing the tool **502** downhole) will cause or allow the rollers **510** to slide along the conical race **512** in the direction of its reducing diameter, thus allowing the rollers **510** radially to retract from the casing bore as illustrated in FIG. 26. Such roller retraction frees the tool **502** from the casing **480** and permits free withdrawal of the tool **502** in an uphole direction whereas the non-retracting rollers **410** of the tool **402** might possibly jam the tool **402** within the casing **480** in the event of attempted withdrawal of the tool **402**.

[0085] Turning now to FIG. 27, this is a simplified longitudinal elevation of a casing expander assembly **600** for use in downhole expansion of a solid, slotted or imperforate metal tube **602** within a casing **604** which lines a well. The casing expander assembly **600** is a three-stage expansion tool which is generally similar (apart from the number of expansion stages) to the two-stage expansion tool **300** described above with reference to FIGS. 20-24.

[0086] In order from its leading (downhole) end, the expander assembly **600** comprises a running/guide assembly **610**, a first-stage conical expander **612**, an inter-stage coupling **614**, a second-stage conical expander **616**, a further inter-stage coupling **618**, and a third-stage cylindrical expander **620**.

[0087] The first-stage conical expander **612** comprises a conical array of tapered rollers which may be the same as either one of the primary expansion tools **302** or **402**, or which differs therefrom in respect of the number of rollers and/or in respect of the cone angles of the rollers and their race.

[0088] The second-stage conical expander **616** is an enlarged-diameter version of the first-stage conical expander **612** dimensioned to provide the intermediate expansion stage of the three-stage expansion assembly **600**. The diameter of the leading (narrow) end of the second-stage expander **616** (the lower end of the expander **616** as viewed in FIG. 27) is marginally less than the diameter of the trailing (wide) end of the first-stage expander **612** (the upper end, of the expander **612** as viewed in FIG. 27) such that the second-stage expander **616** is not precluded from entering initially expanded tube **602** resulting from operation of the first-stage expander **612**.

[0089] The third-stage expander **620** is a generally cylindrical expander which may be similar either to the profiling tool **100** or to the secondary expansion tool **304**. (Although the rollers of the third-stage expander **620** may be termed "cylindrical" in order to facilitate distinction over the conical rollers of the first-stage and second-stage expanders **612** & **616**, and although in certain circumstances such so-called "cylindrical" rollers may in fact be truly cylindrical, the rollers of the cylindrical expander will usually be barrelled to avoid excessive end stresses). The rollers of the third-stage expander **620** will normally be radially extended from the body of the expander **620** by an extent that the third-stage expander **620** rolls the tube **602** into its final extension against the inside of casing **604**, such that no further expansion of the tube **602** is required in the short term.

[0090] The interstage couplings **614** and **618** can be constituted by any suitable arrangement that mechanically couples the three expander stages, and (where necessary or desirable) also hydraulically couples the stage.

[0091] The rollers of the third-stage expander **620** may be skewed such that rotation of the assembly **600** drives the assembly in a downhole direction; alternatively, the rollers may be unskewed and forward thrust on the expanders be provided by suitable weights, e.g. by drill collars **630** immediately above the assembly **600**. Where the third-stage rollers are skewed, drill collars can be employed to augment the downhole thrust provided by rotation of the assembly **600**.

[0092] As depicted in FIG. 27, the three-stage expander assembly **600** is suspended from a drillstring **640** which not

only serves for transmitting rotation to the assembly 600 but also serves for transmitting hydraulic fluid under pressure to the assembly 600 for radial extension of the third-stage rollers, for cooling the assembly 600 and newly deformed tube 602, and for flushing debris out of the work region.

[0093] In suitable circumstances, the drillstring 640 may be substituted by coiled tubing (not shown) of a form known per se.

[0094] Turning now to FIG. 28 which is divided into three mutually related FIGS. 28A, 28B, & 28C, these illustrate a primary expansion tool 702 which may be summarised as being the primary expansion tool 402 (FIG. 25) with hard steel bearing balls 710 substituted for the rollers 410. Each of the balls 710 runs in a respective circumferential groove 712, and is located for proper tracking by a suitably perforated cage 714. As with the tool 402, the cage 714 is retained by a retainer 716 secured on the screw-threaded leading end 718 of the tool 702 by means of a ring nut 720. Operation of the tool 702 is functionally similar to operation of the tool 402, as is illustrated by the expansion effect of the tool 702 on casing 480.

[0095] The primary expansion tool 702 as shown in FIGS. 28A-28C could be modified by the substitution of the series of circumferential ball tricks 712 with a single spiral track (not shown) around which the balls 710 would circulate at ever-increasing radii to create the requisite expansion forces on the casing. At the point of maximum radius, the balls 710 would be recirculated back to the point of minimum radius (near the leading end of the tool 702, adjacent the retainer 716) by means of a channel (not shown) formed entirely within the central body of the tool 702 in a form analogous to a recirculating ball-screw (known per se).

[0096] FIGS. 29A & 29B illustrate a modification 802 of the ball-type expansion primary expansion tool 702 of FIG. 28 analogous to the FIG. 26 modification 502 of the FIG. 25 roller-type primary expansion tool 402. In the modified ball-type primary expansion tool 802, the hard steel bearing balls 810 run in longitudinally-extending grooves 812 instead of the circumferential grooves 712 of the tool 702. The ball-guiding perforations in the cage 814 are longitudinally extended into slots which allow individual balls 810 to take up different longitudinal positions (and hence different effective radii) according to whether the tool 802 is being pushed downhole (FIG. 28A) or being pulled uphole (FIG. 28B). In the latter case, the balls 810 are relieved from pressure on the surrounding casing 480 and thereby obviate any risk of the tool 802 becoming jammed in partly-expanded casing.

[0097] In the profiling and expansion tools with controllably displaceable rollers as previously described, e.g. with reference to FIGS. 4 and 24, the ability to obtain and to utilise hydraulic pressure may place practical limits on the forces which can be exerted by the rollers. FIG. 30 illustrates a roller-type expansion/profiling tool 900 which utilises a mechanical force-multiplying mechanism to magnify a force initially produced by controlled hydraulic pressure, and to apply the magnified force to profiling/expanding rollers 902. Each of the plurality of rollers 902 (only two being visible in FIG. 30) has a longitudinally central portion which is near-cylindrical and slightly barrelled (i.e. slightly convex), bounded on either side by end portions which are conical, both end portions tapering from conjunction with

the central portion to a minimum diameter at each end. Rotation of each roller 902 about a respective rotation axis which is parallel to the longitudinal axis of the tool 900 and at a controllably variable radial displacement therefrom is ensured by a roller-guiding cage 904 of suitable form.

[0098] The effective working diameter of the tool 900 is dependent on the (normally equal) radial displacements of the rollers 902 from the longitudinal axis of the tool 900 (such displacement being shown at a minimum in FIG. 30). The conical end portions of each roller 902 each run on a respective one of two conical races 906 and 908 whose longitudinal separation determines the radial displacement of the rollers 902. The conical races 906 and 909 are coupled for synchronous rotation but variable separation by means of a splined shaft 910 which is rigid with the upper race 906 and non-rotatably slidable in the lower race 908. The tool 900 has a hollow core which hydraulically couples through an upper sub 912 to a drillstring (not shown) which both selectively rotates the tool 900 within surrounding casing 990 which is to be profiled/expanded by the tool 900 and transmits controllable hydraulic pressure to the core of the tool 900 for controlling the roller displacement as will now be detailed.

[0099] The lower end of the tool 900 (with which the lower race 908 is integral) is formed as hollow cylinder 914 within which a piston 916 is slidably sealed. The piston 916 is mounted on the lower end of a downward extension of the shaft 910 which is hollow to link through the tool core and the drillstring to the controlled hydraulic pressure. The piston 916 divides the cylinder 914 into upper and lower parts. The upper part of the cylinder 914 is linked to the controlled hydraulic pressure by way of a side port 918 in the hollow shaft 910, just above the piston 916. The lower part of the cylinder 914 is vented to the outside of the tool 900 through a hollow sub 920 which constitutes the lower end of the tool 900 (and which enables further components, tools, or drillstring (not shown)) to be connected below the tool 900). Thereby a controllable hydraulic pressure differential can be selectively created across the piston 916, with consequent control of the longitudinal separation of the two roller-supporting conical races 906 and 908 which in turn controls the effective rolling diameter of the tool 900.

[0100] While certain modifications and variations of the invention have been described above, the invention is not restricted thereto, and other modifications and variations can be adopted without departing from the scope of the invention as defined in the appended claims.

1. A method of profiling a pipe or other hollow tubular article, the method comprising the steps of applying a roller means to a part of the pipe bore selected to be profiled, translating the roller means across the bore in a direction including a circumferential component while applying a force to the roller means in a radially outwards direction with respect to the longitudinal axis of the pipe, and continuing such translation and force application until the pipe is plastically deformed substantially into the intended profile.

2. A method according to claim 1 wherein the deformation of the pipe is accomplished by radial compression of the pipe wall, or by circumferential stretching of the pipe wall, or by a combination of such radial compression and circumferential stretching.

3. A method according to claim 1 wherein said direction is purely circumferential.

4. A method according to claim 1 wherein said direction is partly circumferential and partly longitudinal.

5. A method according to claim 1 wherein said roller means is peripherally profiled to be complementary to the profile into which the selected part of the pipe bore is intended to be formed.

6. A method according to claim 1 wherein the selected part of the pipe bore is remote from an open end of the pipe, and the method comprises the further steps of inserting the roller means into the open end of the pipe (if the roller means is not already in the pipe), and transferring the roller means along the pipe to the selected location.

7. A method as claimed in claim 6 wherein transfer of the roller means is accomplished by the step of actuating traction means coupled to or forming part of the roller means and effective to apply along-pipe traction forces to the roller means by reaction against parts of the pipe bore adjacent the roller means.

8. A method of conjoining two pipes or other hollow tubular articles, said method comprising the steps of locating one of the two pipes within and longitudinally overlapping one of the other of the two pipes, applying roller means to a part of the bore of the inner of the two pipes at a location where it is intended that the two pipes be conjoined, translating the roller means across the bore in a direction including a circumferential component while applying a radially outwardly directed force to the roller means, and continuing such translation and force application until the inner pipe is plastically deformed into permanent contact with the outer pipe and is thereby conjoined thereto.

9. A method according to claim 8 wherein said deformation is accomplished by radial compression of the pipe wall, or by circumferential stretching of the pipe wall, or by a combination of such radial compression and circumferential stretching.

10. A method according to claim 8 wherein said direction is purely circumferential.

11. A method according to claim 8 wherein said direction is partly circumferential and partly longitudinal.

12. A method according to claim 8 wherein the location where the pipes are intended to be conjoined is remote from an accessible end of the bore, and the method comprises the further steps of inserting the roller means into the accessible end of the bore (if the roller means is not already in the bore), and transferring the roller means to the intended location.

13. A method according to claim 12 wherein transfer of the roller means is accomplished by the step of actuating traction means coupled to or forming part of the roller means and effective to apply along-bore traction forces to the roller means by reaction against parts of the pipe bore adjacent the roller means.

14. Apparatus for expanding a pipe or other hollow tubular article, said apparatus comprising roller means constructed or adapted for rolling deployment against the bore of the pipe, said roller means comprising at least one set of individual rollers each mounted for rotation about a respective rotation axis which is generally parallel to the longitudinal axis of the apparatus, the rotation axes of said at least one set of rollers being circumferentially distributed around the expansion apparatus and each being radially offset from

the longitudinal axis of the expansion apparatus, the expansion apparatus being selectively rotatable around its longitudinal axis.

15. Apparatus according to claim 14 wherein the rotation axes of said at least one set of rollers conform to a first regime in which each said rotation axis is substantially parallel to the longitudinal axis of the apparatus in a generally cylindrical configuration.

16. Apparatus according to claim 14 wherein the rotation axes of said at least one set of rollers conform to a second regime in which each said rotation axis lies substantially in a respective radial plane including the longitudinal axis of the apparatus and the rotation axes each converge substantially towards a common point substantially on the longitudinal axis of the apparatus in a generally conical configuration.

17. Apparatus according to claim 14 wherein the rotation axes of said at least one set of rollers conform to a third regime in which each said rotation axis is similarly skewed with respect to the longitudinal axis of the apparatus in a generally helical configuration which is either non-convergent (cylindrical) or convergent (conical).

18. Apparatus according to claim 14 wherein the apparatus has only a single such set of rollers.

19. Apparatus according to claim 14 wherein the apparatus has a plurality of such sets of rollers.

20. Apparatus according to claim 19 wherein the sets of rollers conform to two or more different ones of the three regimes of roller axis alignments defined in claims 15-17.

21. Apparatus according to claim 20 wherein the apparatus has a set of rollers conforming to the second regime located at leading end of the apparatus and another set of rollers conforming to the first regime located elsewhere on the apparatus.

22. Apparatus according to claim 21 modified by the addition of a further set of rollers conforming to third regime with non-convergent axes, this further set of rollers being utilised for the purpose of applying traction forces to the apparatus.

23. Apparatus according to claim 14 wherein the rollers of said apparatus are each mounted for rotation about its respective rotation axis substantially without freedom of movement along its respective rotation axis.

24. Apparatus according to claim 14 wherein the rollers of said apparatus are each mounted for rotation about its respective rotation axis with freedom of movement along its respective rotation axis.

25. Apparatus according to claim 23 wherein said rollers have freedom of movement which is constrained within predetermined limits of movement.

26. Apparatus for profiling or conjoining pipes or other hollow tubular articles, said apparatus comprising roller means and radial urging means selectively operable to urge the roller means radially outwards of a longitudinal axis of the apparatus, the radial urging means causing or allowing the roller means to move radially inwards towards the longitudinal axis of the apparatus when the radial urging means is not operated, the roller means comprising a plurality of individual rollers each mounted for rotation about a respective rotation axis which is substantially parallel to the longitudinal axis of the apparatus, the rotation axes of the individual rollers being circumferentially distributed around the apparatus and each said rotation axis being radially offset from the longitudinal axis of the apparatus, the apparatus

being selectively rotatable around its longitudinal axis to translate the roller means across the bore of a pipe against which the roller means is being radially urged.

26. Apparatus according to claim 25 wherein the radial urging means comprises a respective piston on which each said roller is individually rotatably mounted, each said piston being slidably sealed in a respective radially extending bore formed in a body of the apparatus, a radially inner end of each said bore being in fluid communication with fluid pressure supply means selectively pressurisable to operate said radial urging means.

27. Apparatus according to claim 25 wherein the radial urging means comprises bi-conical race means upon which each said individual roller rolls in use of the apparatus, and separation variation means selectively operable controllably to vary the longitudinal separation of the two conical races of the bi-conical race means whereby correspondingly to vary the radial displacement of each said roller rotation axis from the longitudinal axis of the apparatus.

28. Apparatus according to claim 27 wherein the separation variation means comprises hydraulic linear motor means selectively pressurisable to drive one of said two cones longitudinally towards and/or away from the other said cone.

29. A method of expanding an inner pipe into an outer pipe, said method comprising effecting rolling compressive yield of the wall of the inner pipe wall to cause reduction in wall thickness and subsequent increase in circumference resulting in diameter increase.

30. A method as claimed in claim 29, wherein the method generates compressive hoop stress in the inner pipe resulting in an interference fit of the inner pipe within the outer pipe.

31. A method as claimed in claim 30, wherein the resulting interference fit can withstand a high level of longitudinal force resulting from tensile or compressive stress.

32. A method of creating a high pressure seal between an inner pipe and an outer pipe by creating a metal to metal interface between the pipes by effecting rolling compressive yield of the inner pipe within the outer pipe.

33. A method as claimed in claim 32, including the addition of elastomer or ductile metal seals between the inner pipe and outer pipe.

* * * * *