




US 20170085843A1

(19) **United States**(12) **Patent Application Publication**
Scalisi et al.(10) **Pub. No.: US 2017/0085843 A1**(43) **Pub. Date: Mar. 23, 2017**(54) **DOORBELL COMMUNICATION SYSTEMS
AND METHODS**(60) Provisional application No. 62/400,611, filed on Sep.
27, 2016.(71) Applicant: **SkyBell Technologies, Inc.**, Irvine, CA
(US)**Publication Classification**(72) Inventors: **Joseph Frank Scalisi**, Yorba Linda, CA
(US); **Seton Paul Kasmir**, San Diego,
CA (US); **Jeremy Norberg**, Irvine, CA
(US)(51) **Int. Cl.**
H04N 7/18 (2006.01)
G08B 13/196 (2006.01)
H04L 29/08 (2006.01)(73) Assignee: **SkyBell Technologies, Inc.**, Irvine, CA
(US)(52) **U.S. Cl.**
CPC **H04N 7/186** (2013.01); **H04L 67/12**
(2013.01); **H04N 7/188** (2013.01); **G08B**
13/1966 (2013.01); **H04W 84/12** (2013.01)(21) Appl. No.: **15/341,125**(57) **ABSTRACT**(22) Filed: **Nov. 2, 2016****Related U.S. Application Data**(63) Continuation-in-part of application No. 15/167,831,
filed on May 27, 2016, now Pat. No. 9,508,239,
Continuation-in-part of application No. 14/861,613,
filed on Sep. 22, 2015.

The disclosure includes a doorbell system having a doorbell, a doorbell housing, a visitor detection system, and a chime. The visitor detection system can be coupled to the doorbell housing and can include at least one of a camera and a motion detector. The doorbell can also comprise a first low-energy transceiver and a first high-energy transceiver that can be coupled to the doorbell housing. The first and second low-energy transceivers and the first and second high-energy transceivers can be configured to transmit data.






Figure 1




Figure 2




Figure 3





Figure 4

**Figure 5**




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13

600 table

type of event	certainty	severity	alarm type
fire	20%	high	sound
gas leak	50%	high	red flash w/ sound
glass breaking	80%	medium	white light
baby crying	95%	low	play music

Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24






Figure 25

**Figure 26****Figure 27**




Figure 28




Figure 29




Figure 30




Figure 31




Figure 32




Figure 33




Figure 34




Figure 35




Figure 36




Figure 37




Figure 38




Figure 39




Figure 40




Figure 41




Figure 42




Figure 43




Figure 44




Figure 45




Figure 46




Figure 47

DOORBELL COMMUNICATION SYSTEMS AND METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 62/400,611; filed Sep. 27, 2016; and entitled DOORBELL COMMUNICATION SYSTEMS AND METHODS; the entire contents of which are incorporated herein by reference.

[0002] This application claims the benefit of and is a continuation-in-part of U.S. Nonprovisional patent application Ser. No. 15/167,831; filed May 27, 2016; and entitled DOORBELL PACKAGE DETECTION SYSTEMS AND METHODS; the entire contents of which are incorporated herein by reference.

[0003] This application claims the benefit of and is a continuation-in-part of U.S. Nonprovisional patent application Ser. No. 14/861,613; filed Sep. 22, 2015; and entitled DOORBELL COMMUNICATION SYSTEMS AND METHODS; the entire contents of which are incorporated herein by reference.

BACKGROUND

[0004] Field

[0005] Various embodiments disclosed herein relate to doorbells. Certain embodiments relate to communication between a person near a doorbell and a person in another location.

[0006] Description of Related Art

[0007] Homes, offices, and other buildings sometimes include communication and surveillance systems to enable friendly visitors to summon occupants of the buildings and to deter unwanted visitors. Communication and surveillance systems can include video cameras and doorbells.

[0008] Doorbells can enable a person located outside of an entry point, such as a door, to alert a person inside of an entry point that someone outside would like to talk to someone inside. Doorbells sometimes include a button located near a door, such as a front door, side door, or back door of a home, office, dwelling, warehouse, building, or structure. Doorbells are sometimes used near a gate or some other entrance to a partially enclosed area. Pushing the doorbell sometimes causes a chime or other alerting sound to be emitted. In some cases, this alerting sound can typically be heard within a short distance from the entry point or sound source. For example, a homeowner located remotely from her home likely would not be able to hear the alerting sound, and thus, would not be aware that someone is ringing her doorbell. Thus, there is a need for devices and methods to alert remotely located individuals that someone seeks the attention of the homeowner, tenant, building guardian, or steward.

SUMMARY

[0009] In some embodiments, a doorbell system can comprise a doorbell. The doorbell can comprise a doorbell housing and a visitor detection system that can be coupled to the doorbell housing. The visitor detection system can include at least one of a camera and a motion detector. The doorbell can also comprise a first low-energy transceiver that can be coupled to the doorbell housing. Additionally, the doorbell can comprise a first high-energy transceiver that

can be coupled to the doorbell housing. The first low-energy transceiver and the first high-energy transceiver can be configurable to transmit data.

[0010] In several embodiments, the doorbell system can further comprise a chime that can be communicatively coupled to the doorbell. The chime can comprise a chime housing, a second low-energy transceiver coupled to the chime housing, and a second high-energy transceiver coupled to the chime housing. The second low-energy transceiver and the second high-energy transceiver can be configurable to transmit data to the first low-energy transceiver and the first high-energy transceiver.

[0011] In some embodiments, the doorbell system can further comprise a Wi-Fi communication hub that can be communicatively coupled to at least one of the doorbell and the chime. The Wi-Fi communication hub can comprise a Wi-Fi router.

[0012] In several embodiments, the first low-energy transceiver can comprise a first Bluetooth low-energy transceiver. The second low-energy transceiver can comprise a second Bluetooth low-energy transceiver. The first high-energy transceiver can comprise a first Wi-Fi transceiver. The second high-energy transceiver can comprise a second Wi-Fi transceiver. In some embodiments, the doorbell can be powered by a battery located within the doorbell housing. In several embodiments, the doorbell system can further comprise a remote computing device that can be communicatively coupled to at least one of the doorbell, the chime, and the Wi-Fi communication hub.

[0013] In some embodiments of the doorbell system, at least one of the first low-energy transceiver and the second low-energy transceiver can be configured to activate in response to a first request from the remote computing device. The first high-energy transceiver and the second high-energy transceiver can be configured to activate in response to a second request from the remote computing device.

[0014] In several embodiments of the doorbell system, the first high-energy transceiver and the second high-energy transceiver can be configured to activate in response to a second event detected by the visitor detection system. In some embodiments, the doorbell can comprise a light source that can illuminate light. At least one of the first low-energy transceiver and the second low-energy transceiver can be configured to activate in response to a request from the remote computing device to change a color of the light. In several embodiments, at least one of the first high-energy transceiver and the second high-energy transceiver can be configured to activate in response to the doorbell detecting a presence of a visitor.

[0015] In some embodiments, a doorbell system can comprise a doorbell having a visitor detection system, a first low-energy transceiver, and a first high-energy transceiver. The doorbell system can comprise a chime that can be communicatively coupled to the doorbell. The chime can have a second low-energy transceiver and a second high-energy transceiver. The method for using the doorbell system can comprise activating at least one of the first low-energy transceiver and the second low-energy transceiver. This activation can be in response to a first event. At least one of the first high-energy transceiver and the second high-energy transceiver can be activated in response to a second event.

[0016] In several embodiments, the doorbell system can further comprise a remote computing device that can be communicatively coupled to at least one of the doorbell and the chime. The first event can comprise a first request from the remote computing device. The second event can comprise a second request from the remote computing device.

[0017] In some embodiments, the method of using the doorbell system can further comprise activating both the first low-energy transceiver and the second low-energy transceiver in response to the first event. The first high-energy transceiver and the second high-energy transceiver can be deactivated in response to activating both the first low-energy transceiver and the second low-energy transceiver.

[0018] In several embodiments, the method of using the doorbell system can further comprise activating both the first high-energy transceiver and the second high-energy transceiver, in response to the second event. The method can then comprise deactivating the first low-energy transceiver and the second low-energy transceiver in response to activating both the first high-energy transceiver and the second high-energy transceiver.

[0019] In some embodiments, a doorbell system can comprise a doorbell having a visitor detection system, a first low-energy transceiver, and a first high-energy transceiver. The doorbell system can comprise a chime communicatively coupled to the doorbell. The chime can have a second low-energy transceiver and a second high-energy transceiver. The method for using the doorbell system can comprise activating the first low-energy transceiver, activating the second low-energy transceiver, and transmitting data between the first low-energy transceiver and the second low-energy transceiver. This method can thereby enable communication between the doorbell and the chime.

[0020] In several embodiments, the method of using the doorbell system can further comprise deactivating the first high-energy transceiver in response to activating the first low-energy transceiver. The second high-energy transceiver can be deactivated in response to activating the second low-energy transceiver.

[0021] In some embodiments, the method of using the doorbell system can further comprise activating the first low-energy transceiver. The first low-energy transceiver can be activated in response to the doorbell performing at least one of sending a first transmission that is less than a predetermined transmission threshold, and receiving a second transmission that is less than the predetermined transmission threshold, and activating the second low-energy transceiver. The activation of the second low-energy transceiver can be in response to the chime performing at least one of sending the first transmission that is less than the predetermined transmission threshold and receiving the second transmission that is less than the predetermined transmission threshold.

[0022] In several embodiments, a doorbell system can comprise a doorbell having a camera, a motion detector, a first low-energy transceiver, and a first high-energy transceiver. The doorbell system can comprise a chime that can be communicatively coupled to the doorbell. The chime can have a second low-energy transceiver and a second high-energy transceiver. The method for using the doorbell system can comprise activating the first high-energy transceiver, activating the second high-energy transceiver, and transmitting data between the first high-energy transceiver

and the second high-energy transceiver. This method can thereby enable communication between the doorbell and the chime.

[0023] In some embodiments, the method of using the doorbell can further comprise deactivating the first low-energy transceiver in response to activating the first high-energy transceiver, and deactivating the second low-energy transceiver in response to activating the second high-energy transceiver.

[0024] In several embodiments, the method of using the doorbell can further comprise activating the first high-energy transceiver in response to the doorbell performing at least one of sending a first transmission that is greater than a predetermined transmission threshold and receiving a second transmission that is greater than the predetermined transmission threshold. The method can also comprise activating the second high-energy transceiver in response to the chime performing at least one of sending the first transmission that can be greater than the predetermined transmission threshold and receiving the second transmission that can be greater than the predetermined transmission threshold.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] These and other features, aspects, and advantages are described below with reference to the drawings, which are intended to illustrate, but not to limit, the invention. In the drawings, like reference characters denote corresponding features consistently throughout similar embodiments.

[0026] FIG. 1 illustrates a front view of a communication system, according to some embodiments.

[0027] FIG. 2 illustrates a computing device running software, according to some embodiments.

[0028] FIG. 3 illustrates an embodiment in which a security system is connected to a building, according to some embodiments.

[0029] FIG. 4 illustrates a communication system that includes a security system, a doorbell button, a wireless router, a server, and users, according to some embodiments.

[0030] FIG. 5 illustrates a flow diagram showing a method of operating a security system, according to some embodiments.

[0031] FIG. 6 illustrates a flow diagram showing another method of operating a security system, according to some embodiments.

[0032] FIGS. 7, 8, 9 and 10 illustrate visitors being detected by security systems, according to various embodiments.

[0033] FIG. 11 illustrates a block diagram of a security system that is communicatively coupled to a communication system, according to some embodiments.

[0034] FIG. 12 illustrates a block diagram of various event detection devices that are communicatively coupled to a communication system, according to some embodiments.

[0035] FIG. 13 illustrates a flowchart of a method of monitoring for an event through a communication system, according to some embodiments.

[0036] FIG. 14 illustrates an example of various alarm types that may be used based on the certainty and severity of the event, according to some embodiments.

[0037] FIGS. 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27 and 28 illustrate flow diagrams showing methods of operating a security system, according to various embodiments.

[0038] FIG. 29 illustrates a back view of the doorbell from FIG. 1 without a mounting bracket, according to some embodiments.

[0039] FIG. 30 illustrates a diagrammatic view of a doorbell and a doorbell control software application running on a computing device, according to some embodiments.

[0040] FIG. 31 illustrates a front view of a doorbell chime, according to some embodiments.

[0041] FIG. 32 illustrates a side perspective view of a doorbell chime, according to some embodiments.

[0042] FIG. 33 illustrates a front view of a doorbell chime coupled to a power outlet, according to some embodiments.

[0043] FIGS. 34, 35, and 36 illustrate diagrammatic views of doorbell systems, according to some embodiments.

[0044] FIG. 37 illustrates a back view of a chime without a back cover to show various components of the chime's electrical system, according to some embodiments.

[0045] FIGS. 38, 39, 40, 41, 42, and 43 illustrate method flowcharts, according to some embodiments.

[0046] FIGS. 44 and 45 illustrate diagrammatic views of doorbell systems, according to some embodiments.

[0047] FIG. 46 illustrates a front view of a doorbell, according to some embodiments.

[0048] FIG. 47 illustrates wireless communication between the transceivers of the doorbell and the chime, according to some embodiments.

DETAILED DESCRIPTION

[0049] Although certain embodiments and examples are disclosed below, inventive subject matter extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses, and to modifications and equivalents thereof. Thus, the scope of the claims appended hereto is not limited by any of the particular embodiments described below. For example, in any method or process disclosed herein, the acts or operations of the method or process may be performed in any suitable sequence and are not necessarily limited to any particular disclosed sequence. Various operations may be described as multiple discrete operations in turn, in a manner that may be helpful in understanding certain embodiments; however, the order of description should not be construed to imply that these operations are order dependent. Additionally, the structures, systems, and/or devices described herein may be embodied as integrated components or as separate components.

[0050] For purposes of comparing various embodiments, certain aspects and advantages of these embodiments are described. Not necessarily all such aspects or advantages are achieved by any particular embodiment. Thus, for example, various embodiments may be carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other aspects or advantages as may also be taught or suggested herein.

Introduction

[0051] Communication systems can provide a secure and convenient way for a remotely located individual to communicate with a person who is approaching a sensor, such as a proximity sensor or motion sensor, or with a person who rings a doorbell, which can be located in a doorway, near an entrance, or within 15 feet of a door. Some communication systems allow an individual to hear, see, and talk with visitors who approach at least a portion of the communica-

tion system and/or press a button, such as a doorbell's button. For example, communication systems can use a computing device to enable a remotely located person to see, hear, and/or talk with visitors. Computing devices can include computers, laptops, tablets, mobile devices, smartphones, cellular phones, and wireless devices (e.g., cars with wireless communication). Example computing devices include the iPhone, iPad, iMac, MacBook Air, and MacBook Pro made by Apple Inc. Communication between a remotely located person and a visitor can occur via the Internet, cellular networks, telecommunication networks, and wireless networks.

[0052] FIG. 1 illustrates a front view of a communication system embodiment. The communication system 200 can include a security system 202 (e.g., a doorbell) and a computing device 204. Although the illustrated security system 202 includes many components in one housing, several security system embodiments include components in separate housings. The security system 202 can include a camera assembly 208 and a doorbell button 212. The camera assembly 208 can be a video camera, which in some embodiments is a webcam.

[0053] The security system 202 can include a diagnostic light 216 and a power indicator light 220. In some embodiments, the diagnostic light 216 is a first color (e.g., blue) if the security system 202 and/or the communication system 200 is connected to a wireless Internet network and is a second color (e.g., red) if the security system 202 and/or the communication system 200 is not connected to a wireless Internet network. In some embodiments, the power indicator 220 is a first color if the security system 202 is connected to a power source. The power source can be power supplied by the building 300 to which the security system 202 is attached. In some embodiments, the power indicator 220 is a second color or does not emit light if the security system 202 is not connected to the power source.

[0054] The security system 202 (e.g., a doorbell) can receive power and/or information from an Ethernet cable 221 that can be electrically coupled to the doorbell. The Ethernet cable 221 can exit a hole in an exterior of a building near an entryway to enable electrically coupling the doorbell to the Ethernet cable 221.

[0055] As well, the security system 202 can include at least one speaker 488. The speaker 488 can be located along any portion of the security system 202. For example, the speaker 488 can be located within an inner portion of the security system 202 or along an outer portion of the security system 202. The speaker 488 can be any type of sound output device configured to emit sound, such as a digital speaker, an analog speaker, and the like.

[0056] Furthermore, the security system 202 (e.g., a doorbell) can include an outer housing 224, which can be water resistant and/or waterproof. The outer housing can be made from metal or plastic, such as molded plastic with a hardness of 60 Shore D. In some embodiments, the outer housing 224 is made from brushed nickel or aluminum.

[0057] Rubber seals can be used to make the outer housing 224 water resistant or waterproof. The security system 202 can be electrically coupled to a power source, such as wires electrically connected to a building's electrical power system. In some embodiments, the security system 202 includes a battery for backup and/or primary power.

[0058] Wireless communication 230 can enable the security system 202 (e.g., a doorbell) to communicate with the

computing device **204**. Some embodiments enable communication via cellular and/or WiFi networks. Some embodiments enable communication via the Internet. Several embodiments enable wired communication between the security system **202** and the computing device **204**. The wireless communication **230** can include the following communication means: radio, WiFi (e.g., wireless local area network), cellular, Internet, Bluetooth, telecommunication, electromagnetic, infrared, light, sonic, and microwave. Other communication means are used by some embodiments. In some embodiments, such as embodiments that include telecommunication or cellular communication means, the security system **202** can initiate voice calls or send text messages to a computing device **204** (e.g., a smartphone, a desktop computer, a tablet computer, a laptop computer).

[0059] Several embodiments use near field communication (NFC) to communicate between the computing device **204** and the doorbell **202**. The doorbell **202** and/or the computing device **204** can include a NFC tag. Some NFC technologies include Bluetooth, radio-frequency identification, and QR codes.

[0060] Some embodiments include computer software (e.g., application software), which can be a mobile application designed to run on smartphones, tablet computers, and other mobile devices. Software of this nature is sometimes referred to as “app” software. Some embodiments include software designed to run on desktop computers and laptop computers.

[0061] The computing device **204** can run software with a graphical user interface. The user interface can include icons or buttons. In some embodiments, the software is configured for use with a touch-screen computing device such as a smartphone or tablet.

[0062] FIG. 2 illustrates a computing device **204** running software. The software includes a user interface **240** displayed on a display screen **242**. The user interface **240** can include a security system indicator **244**, which can indicate the location of the security system that the user interface is displaying. For example, a person can use one computing device **204** to control and/or interact with multiple security systems, such as one security system located at a front door and another security system located at a back door. Selecting the security system indicator **244** can allow the user to choose another security system (e.g., the back door security system rather than the front door security system).

[0063] The user interface **240** can include a connectivity indicator **248**. In some embodiments, the connectivity indicator can indicate whether the computing device is in communication with a security system, the Internet, and/or a cellular network. The connectivity indicator **248** can alert the user if the computing device **204** has lost its connection with the security system **202**; the security system **202** has been damaged; the security system **202** has been stolen; the security system **202** has been removed from its mounting location; the security system **202** lost electrical power; and/or if the computing device **204** cannot communicate with the security system **202**. In some embodiments, the connectivity indicator **248** alerts the user of the computing device **204** by flashing, emitting a sound, displaying a message, and/or displaying a symbol.

[0064] In some embodiments, if the security system **202** loses power, loses connectivity to the computing device **204**, loses connectivity to the Internet, and/or loses connectivity

to a remote server, a remote server **206** sends an alert (e.g., phone call, text message, image on the user interface **240**) regarding the power and/or connectivity issue. In several embodiments, the remote server **206** can manage communication between the security system **202** and the computing device. In some embodiments, information from the security system **202** is stored by the remote server **206**. In several embodiments, information from the security system **202** is stored by the remote server **206** until the information can be sent to the computing device **204**, uploaded to the computing device **204**, and/or displayed to the remotely located person via the computing device **204**. The remote server **206** can be a computing device that stores information from the security system **202** and/or from the computing device **204**. In some embodiments, the remote server **206** is located in a data center.

[0065] In some embodiments, the computing device **204** and/or the remote server **206** attempts to communicate with the security system **202**. If the computing device **204** and/or the remote server **206** is unable to communicate with the security system **202**, the computing device **204** and/or the remote server **206** alerts the remotely located person via the software, phone, text, a displayed message, and/or a website. In some embodiments, the computing device **204** and/or the remote server **206** attempts to communicate with the security system **202** periodically; at least every five hours and/or less than every 10 minutes; at least every 24 hours and/or less than every 60 minutes; or at least every hour and/or less than every second.

[0066] In some embodiments, the server **206** can initiate communication to the computer device **204** and/or to the security system **202**. In several embodiments, the server **206** can initiate, control, and/or block communication between the computing device **204** and the security system **202**.

[0067] In several embodiments, a user can log into an “app,” website, and/or software on a computing device (e.g., mobile computing device, smartphone, tablet, desktop computer) to adjust the security system settings discussed herein.

[0068] In some embodiments, a computing device can enable a user to watch live video and/or hear live audio from a security system due to the user’s request rather than due to actions of a visitor. Some embodiments include a computing device initiating a live video feed (or a video feed that is less than five minutes old).

[0069] In some embodiments, the user interface **240** displays an image **252** such as a still image or a video of an area near and/or in front of the security system **202**. The image **252** can be taken by the camera assembly **208** and stored by the security system **202**, server **206**, and/or computing device **204**. The user interface **240** can include a recording button **256** to enable a user to record images, videos, and/or sound from the camera assembly **208**, microphone of the security system **202**, and/or microphone of the computing device **204**.

[0070] In several embodiments, the user interface **240** includes a picture button **260** to allow the user to take still pictures and/or videos of the area near and/or in front of the security system **202**. The user interface **240** can also include a sound adjustment button **264** and a mute button **268**. The user interface **240** can include camera manipulation buttons such as zoom, pan, and light adjustment buttons. In some embodiments, the camera assembly **208** automatically adjusts between Day Mode and Night Mode. Some embodiments include an infrared camera and/or infrared lights to

illuminate an area near the security system **202** to enable the camera assembly **208** to provide sufficient visibility (even at night).

[0071] In some embodiments, buttons include diverse means of selecting various options, features, and functions. Buttons can be selected by mouse clicks, keyboard commands, and touching a touch screen. Many embodiments include buttons that can be selected without touch screens.

[0072] In some embodiments, the user interface **240** includes a quality selection button, which can allow a user to select the quality and/or amount of the data transmitted from the security system **202** to the computing device **204** and/or from the computing device **204** to the security system **202**.

[0073] In some embodiments, video can be sent to and/or received from the computing device **204** using video chat protocols such as FaceTime (by Apple Inc.) or Skype (by Microsoft Corporation). In some embodiments, these videos are played by videoconferencing apps on the computing device **204** instead of being played by the user interface **240**.

[0074] The user interface **240** can include a termination button **276** to end communication between the security system **202** and the computing device **204**. In some embodiments, the termination button **276** ends the ability of the person located near the security system **202** (i.e., the visitor) to hear and/or see the user of the computing device **204**, but does not end the ability of the user of the computing device **204** to hear and/or see the person located near the security system **202**.

[0075] In some embodiments, a button **276** is both an answer button (to accept a communication request from a visitor) and is a termination button (to end communication between the security system **202** and the computing device **204**). The button **276** can include the word “Answer” when the system is attempting to establish two-way communication between the visitor and the user. Selecting the button **276** when the system is attempting to establish two-way communication between the visitor and the user can start two-way communication. The button **276** can include the words “End Call” during two-way communication between the visitor and the user. Selecting the button **276** during two-way communication between the visitor and the user can terminate two-way communication. In some embodiments, terminating two-way communication still enables the user to see and hear the visitor. In some embodiments, terminating two-way communication causes the computing device **204** to stop showing video from the security system and to stop emitting sounds recorded by the security system.

[0076] In some embodiments, the user interface **240** opens as soon as the security system detects a visitor (e.g., senses indications of a visitor). Once the user interface **240** opens, the user can see and/or hear the visitor even before “answering” or otherwise accepting two-way communication, in several embodiments.

[0077] Some method embodiments include detecting a visitor with a security system. The methods can include causing the user interface to display on a remote computing device **204** due to the detection of the visitor (e.g., with or without user interaction). The methods can include displaying video from the security system and/or audio from the security system before the user accepts two-way communication with the visitor. The methods can include displaying video from the security system and/or audio from the security system before the user accepts the visitor’s com-

munication request. The methods can include the computing device simultaneously asking the user if the user wants to accept (e.g., answer) the communication request and displaying audio and/or video of the visitor. For example, in some embodiments, the user can see and hear the visitor via the security system before opening a means of two-way communication with the visitor.

[0078] In some embodiments, the software includes means to start the video feed on demand. For example, a user of the computing device might wonder what is happening near the security system **202**. The user can open the software application on the computing device **204** and instruct the application to show live video and/or audio from the security device **202** even if no event near the security system **202** has triggered the communication.

[0079] In several embodiments, the security device **202** can be configured to record when the security device **202** detects movement and/or the presence of a person. The user of the computing device **204** can later review all video and/or audio records when the security device **202** detected movement and/or the presence of a person.

[0080] Referring now to FIG. 1, in some embodiments, the server **206** controls communication between the computing device **204** and the security system **202**, which can be a doorbell with a camera, a microphone, and a speaker. In several embodiments, the server **206** does not control communication between the computing device **204** and the security system **202**.

[0081] In some embodiments, data captured by the security system and/or the computing device **204** (such as videos, pictures, and audio) is stored by another remote device such as the server **206**. Cloud storage, enterprise storage, and/or networked enterprise storage can be used to store video, pictures, and/or audio from the communication system **200** or from any part of the communication system **200**. The user can download and/or stream stored data and/or storage video, pictures, and/or audio. For example, a user can record visitors for a year and then later can review conversations with visitors from the last year. In some embodiments, remote storage, the server **206**, the computing device **204**, and/or the security system **202** can store information and statistics regarding visitors and usage.

[0082] FIG. 3 illustrates an embodiment in which a doorbell **202** is connected to a building **300**, which can include an entryway **310** that has a door **254**. A visitor **388** can approach the doorbell **202** and then can be detected by the doorbell **202**. The visitor **388** can press the doorbell button **212**. The user of the doorbell **202** can configure the doorbell **202** such that when the visitor **388** presses the doorbell button **212**, the user receives a notification regarding the visitor **388**.

[0083] Electrical wires **304** can electrically couple the doorbell **202** to the electrical system of the building **300** such that the doorbell **202** can receive electrical power from the building **300**. The building can include a door lock **250** to lock the door **254**.

[0084] A wireless network **308** can allow devices to wirelessly access the Internet. The security system **202** can access the Internet via the wireless network **308**. The wireless network **308** can transmit data from the security system **202** to the Internet, which can transmit the data to remotely located computing devices **204**. The Internet and wireless networks can transmit data from remotely located comput-

ing devices **204** to the security system **202**. In some embodiments, a security system **202** connects to a home's WiFi.

[0085] As illustrated in FIG. 3, one computing device **204** (e.g., a laptop, a smartphone, a mobile computing device, a television) can communicate with multiple security systems **202**. In some embodiments, multiple computing devices **204** can communicate with one security system **202**.

[0086] In some embodiments, the security system **202** can communicate (e.g., wirelessly **230**) with a television **306**, which can be a smart television. Users can view the television **306** to see a visitor and/or talk with the visitor.

[0087] FIG. 4 illustrates a communication system **310** that includes a security system **320**, a doorbell button **212**, a WiFi router **328**, a server **332**, and users **336**. In step **340**, a visitor initiates a communication request by pressing the doorbell button **212** or triggering a motion or proximity sensor. The visitor can trigger the motion or proximity sensor by approaching the security system **320**. In step **350**, the security system **320** connects or otherwise communicates with a home WiFi router **328**. In step **360**, the server **332** receives a signal from the WiFi router **328** and sends video and/or audio to the users **336** via a wireless network **364**. In step **370**, the users see the visitor, hear the visitor, and talk with the visitor. Step **370** can include using a software application to see, hear, and/or talk with the visitor. The visitor and users **336** can engage in two-way communication **374** via the internet or other wireless communication system even when the visitor and the users **336** are located far away from each other. Some embodiments enable users to receive communication requests and communicate with visitors via diverse mobile communication standards including third generation ("3G"), fourth generation ("4G"), long term evolution ("LTE"), worldwide interoperability for microwave access ("WiMAX"), and WiFi.

[0088] In some cases, the users **336** utilize the communication system **310** to communicate with visitors who are in close proximity to the users **336**. For example, a user **336** located inside her home can communicate with a visitor located just outside the home via the communication system **310**.

[0089] FIG. 29 illustrates an internal view of the doorbell **202**. Doorbells **202** can include a chip **480** (e.g., integrated circuits, microprocessor, computer) and a memory **492**. Doorbells **202** can also include a microphone **484** and a speaker **488**. The speaker **488** can comprise a flat speaker and a sound chamber **460** configured to amplify an emitted sound. The flat speaker can be located in the sound chamber. Some doorbell embodiments include a proximity sensor **500**. In several embodiments, doorbells **202** include a wireless communication module **504**, such as a WiFi module. The communication module **504** can have an integrated antenna. In some embodiments, an antenna is contained within the outer housing **224**.

[0090] The doorbell **202** can include one or more heating elements **508** configured to regulate the temperature of the doorbell **202**. For example, doorbells **202** can be used in very cold environments, such as in Alaska. The heating element **508** can be used in various methods to protect temperature sensitive portions of the doorbell **202** from cold weather.

[0091] While protecting the doorbell **202** from cold weather can be important in some embodiments, protecting visitors from excessive heat can also be important in some embodiments. Excessive heat could burn visitors as they

"ring" the doorbell (e.g., press the doorbell button **212** shown in FIG. 35). The doorbell **202** can include a thermometer **512** to enable the system to determine the temperature inside a portion of the doorbell **202** and/or outside the doorbell **202**.

[0092] Several embodiments can be configured for 9 to 40 volts alternating current ("VAC") and/or 9 to 40 volts direct current ("VDC"). Some embodiments convert input electricity into direct current (DC), such as 12 VDC. Several embodiments include a converter **494** for power conversion (e.g., converting electrical energy from one form to another). The converter **494** can convert input power (e.g., from wiring in a building) to a suitable power form for the doorbell **202**. The power conversion can convert between AC and DC, change the voltage, and/or change the frequency. The converter **494** can include a transformer and/or a voltage regulator. In several embodiments, the converter **494** can include a DC to DC converter, a voltage stabilizer, a linear regulator, a surge protector, a rectifier, a power supply unit, a switch, an inverter, and/or a voltage converter. In some embodiments, the converter **494** converts 50 Hertz ("Hz") power into 60 Hz power.

[0093] The electrical components of the doorbell **202** (e.g., the camera assembly **208**, the memory **492**, the chip **480**, the speaker **488**, the converter **494**, the microphone **484**, the lights **458**, the rectifier **524**, the proximity sensor **500**, the communication module **504**, the heating element **508**, the electrical connectors **510**, the thermometer **512**, the image analysis system **520**, and the battery **642**) can be electrically coupled to a printed circuit board ("PCB") **516** and can receive electrical power from the PCB **516**.

[0094] The PCB **516** and the electrical components of the doorbell **202** can be the electrical system **456** of the doorbell **202**. Additional details regarding the PCB **516** and the electrical components of the doorbell **202** are described in U.S. Nonprovisional patent application Ser. No. 14/612,376; filed Feb. 3, 2015; and entitled DOORBELL COMMUNICATION SYSTEMS AND METHODS. The entire contents of patent application Ser. No. 14/612,376 are incorporated by reference herein.

[0095] Although some embodiments are described in the context of methods, the method embodiments can also be formulated as devices and systems. Methods described herein can be applied to the devices and systems incorporated by references herein.

Video Embodiments

[0096] Referring now to FIGS. 1 and 2, software can start the video feed on demand. For example, a user of the computing device might wonder what is happening near the security system **202**. The user can open the software application (e.g., an "app") on the computing device **204** and instruct the application to show live video and/or audio from the security device **202** even if no event near the security system **202** has triggered the communication.

[0097] Several embodiments include "on-demand" service. For example, a user can initiate communication via a doorbell and/or can initiate live video from the doorbell by pressing a button **260** on a user interface (shown in FIG. 2). Pressing the on-demand button **260** again can terminate the communication and/or the live video.

Situational Sound Embodiments

[0098] The security system 202 may be configured to play unique sounds in response to detecting specific situations and/or during certain times of day. The sounds may be preprogrammed sounds or completely customizable by a user of the security system 202. As well, the security system 202 may be configured to play any of the sounds according to specific situations. For example, the security system 202 may be configured to play a specific message for a specific visiting individual, and/or may be configured to play a specific message when a potential visitor is identified as a specific person or is included in a list of specific people.

[0099] The security system 202 may include a speaker 488 configured to emit any type of sound. The security system 202 may also include a visitor detection system that may include at least one of a button 212, a camera 208, and a motion detector 218. Accordingly, the visitor detection system may be configurable to receive various indications of a visitor's presence. As well, the speaker 488 and the visitor detection system may be directly or indirectly coupled to the security system 202. Even still, the speaker 488 and the visitor detection system may be mechanically, electrically, and/or communicatively coupled to the security system 202.

[0100] The security system 202 may detect different indications of a visitor's presence. As shown in FIG. 5, the security system 202 can be configured to receive a first indication of a visitor's presence (at step 560). In response to receiving the first indication of the visitor's presence, the security system 202 can emit a first sound with the speaker 488 (at step 562). The security system 202 can be configured to receive a second indication of a visitor's presence (at step 564). In response to receiving the second indication of the visitor's presence, the security system 202 can emit a second sound with the speaker 488 (at step 566). The first sound can be audibly different than the second sound.

[0101] Some of the indications can be interpreted as being associated with a friendly or welcome visitor, while other indications can be interpreted as being associated with an unfriendly or unwelcome visitor. According to these different indications, the security system 202, by the speaker 488, can emit different sounds.

[0102] With reference to FIG. 7, when the security system 202 receives an indication that a visitor 580 has pressed the button 212 (at step 582), this can be interpreted as an indication of a friendly, or welcome visitor. In response to receiving the indication that the button 212 has been pressed, the speaker 488 can emit a first sound (at step 584), such as a friendly sound (e.g. "Welcome to our humble abode.").

[0103] As illustrated in FIG. 8, when the security system 202 receives an indication that a visitor 586 has been moving in front of the security system 202 for a prolonged or predetermined time (e.g. 15 seconds or any time that indicates that the visitor is loitering) without pressing the button 212 (at step 588), this can be interpreted as an unfriendly or unwelcome visitor. In response to receiving the indication that the visitor has been moving in front of the security system 202 without pressing the button 212, the speaker 488 can emit a second sound (at step 590). The second sound can be an alert sound (e.g. a warning to move away from the building 300—"Step away from the house!"). It should be appreciated that the security system 202 can be configured to emit any number of sounds, such as a third sound, a fourth sound, a fifth sound, and any number of additional sounds.

[0104] The security system 202 can be configured to receive any number of indications. For example, in addition to a button press and a motion of a visitor, the indications can include indications of a remote computing device 204, a noise, a thermal signature (such as a thermal gradient indicating the presence of a person or animal), a retina scan, a fingerprint scan, a ground vibration, and the like. It should be appreciated that the indication can include any indication of a presence of any visitor, such as a person or animal.

[0105] In some embodiments, the security system 202 can emit different sounds for a first visitor. For example, as the first visitor approaches the building 300, the security system 202 can emit a first sound based upon the motion of the first visitor. As well, the security system 202 can emit a second sound once the first visitor pushes the button 212 of the security system 202.

[0106] Furthermore, any of the indications described in this disclosure can be associated with a visitor that is either welcome or unwelcome at the building. Accordingly, the security system 202 can be configured to any environment in which the building 300 is situated. For example, some buildings 300 can be located in high traffic areas where it is common for people to walk by the front of the security system 202 without pressing the button 212. In this regard, the security system 202 can be configured to ignore indications of motion and only emit sounds in response to affirmative indications that the visitor is visiting the building 300, such as an indication that the button 212 has been pressed. In some embodiments, the security system 202 can be configured to only respond to motion in certain zones. For example, if the security system 202 is located 20 feet from a busy sidewalk, then the security system 202 can be configured to ignore all motion that occurs more than 15 feet from the security system 202. In this manner, the security system 202 can only respond to movements occurring on the building property.

[0107] As well, combinations of indications can be interpreted in various manners. For example, a combination of an indication of motion (i.e. movement) of a visitor in front of the security system 202 and an indication that the visitor has pressed the button 212 can indicate that the visitor is welcome at the building 300. As previously described, the speaker 488 of the security system 202 can emit a friendly message in response to the combination of indications.

[0108] Even still, the security system 202 can be configured to emit different sounds in response to a positive detection of one indication and a negative detection of another indication. For example, if the security system 202 detects motion of a visitor but does not detect sound, this can be interpreted as an unwelcome visitor, such as a prowler sneaking around the outside of the building 300. In response, the speaker 488 of the security system 202 can emit an alert sound (e.g. a warning to exit the premise before the authorities are notified).

[0109] Furthermore, the time of day and/or day when a visitor approaches the building 300 can also indicate whether the visitor is welcome or not. As shown in FIG. 6, the security system 202 can be configured to receive an indication of a visitor's presence at a first time of day (at step 570). The first time of day can occur between sunrise and sunset, or any other time of day. In response to receiving the indication of the visitor's presence at the first time of day, the security system 202 can emit a first sound with the speaker 488 (at step 572). In some embodiments, the first sound

comprises an audible message spoken by a female voice, while some embodiments may comprise an audible message spoken by a male voice.

[0110] Furthermore, the security system 202 can be configured to receive an indication of the visitor's presence at a second time of day (at step 574). It should be appreciated that the second time of day can occur between sunset and sunrise, or any other time of day. In response to receiving the indication of the visitor's presence at the second time of day, the security system 202 can emit a second sound with the speaker 488 (at step 576). In some embodiments, the second sound comprises an audible message spoken by a male voice, while some embodiments may comprise an audible message spoken by a female voice.

[0111] To illustrate a more specific example, such as the one shown in FIG. 9, if a visitor 592 presses the button 212 at noon on a weekend day (at step 594), the speaker 488 can emit a welcome message (e.g. "Welcome. We'll be right there.") (at step 596). In another example, as illustrated in FIG. 10, if a visitor 597 presses the button 212 at midnight on a workday (at step 598), the speaker 488 can emit a do not disturb message or a message instructing the visitor to come back another time (e.g. "Please come back tomorrow!").

[0112] Combinations of indications can be interpreted differently depending on the time of day. For example, in response to an indication of a motion and a noise during the day, the speaker 488 of the security system 202 can emit a friendly message. However, in response to an indication of a motion and a noise during the night, the speaker 488 can emit a warning message.

[0113] Even still, the security system 202 can be configured to respond differently based on the unique circumstances of the indication. For example, if the motion detector 218 of the security system 202 detects a slow movement versus a faster movement, then the speaker 488 can emit different sounds based upon these various circumstances. A slow movement can be interpreted as a prowler approaching the building, while a faster movement, such as a movement of a person walking at 3.5 miles per hour, can be interpreted as a friendly visitor approaching the building 300.

[0114] The time of day can be any selected time of day and any number of time ranges can be used. For example, the security system 202 can emit a welcome message during sunrise to sunset and an alert or warning message during sunset to sunrise. Accordingly, because sunrise and sunset change on a daily basis, the security system 202 can be communicatively coupled to an outside database(s) to allow the security system 202 to thereby automatically respond to these ever-changing conditions.

[0115] The security system 202 (e.g. doorbell) can elect to emit a particular sound, such as a first sound or a second sound, based on a time at which the security system 202 detects an indication of a presence of a visitor. In some embodiments, the security system 202 is configured to detect an amount of light, which may indicate a time of day. In response to detecting the amount of light, the security system 202 can elect to emit the first sound or the second sound based on the amount of light.

[0116] As well, the security system 202 can be configured to provide unique responses during different time ranges on specific days. For example, the user may have a bowling league every third Monday of the month. Accordingly, during that time, (e.g. from 6 pm-8:30 pm) on the third

Monday of the month, in response to detecting an indication of a presence of a friendly visitor, the speaker 488 of the security system 202 can emit a friendly message telling the visitor that their presence is appreciated but the visitor should come back another time. In another example, the user may be on vacation from the 1st to the 10th and the user may wish to emit more intimidating warnings to secure the building 300. Generally speaking, the security system 202 can be configured to emit any type of sound in response to any time of day and/or day.

[0117] The security system 202 can be configured to detect specific visitors and emit certain sounds in response to detecting the specific visitors. For example, if the security system 202 detects a first visitor, such as a relative of the homeowner, the security system 202 can always emit a friendly sound, no matter how the first visitor approaches the home, or during what time of day. As well, if the security system 202 detects a second visitor, such as an unknown party (e.g. a solicitor), the security system 202 can emit an unfriendly sound, no matter how the second visitor approaches the home, or during what time of day.

[0118] To determine the identity of a visitor, the security system 202 can use any type of identity recognition technology, such as facial recognition, to determine an indication of an identity of a visitor. Some of these types of identity recognition technologies are disclosed in U.S. Nonprovisional patent application Ser. No. 14/612,376; filed Feb. 3, 2015; and entitled DOORBELL COMMUNICATION SYSTEMS AND METHODS. The entire contents of patent application Ser. No. 14/612,376 are incorporated by reference herein.

[0119] The different types of sounds emitted by the speaker 488 can be configured to match the appropriate indication as detected by the security system 202. For example, if the security system 202 detects an unfriendly visitor, the speaker 488 can emit a message spoken by a male voice to thereby intimidate the unfriendly visitor. Contra, if the security system 202 detects a friendly visitor, the speaker 488 can emit a message spoken by a female voice to thereby welcome the visitor. As well, the security system 202 can be configured to emit any other type of sound. For example, a welcome visitor can be greeted by a pleasant melody or a ding-dong, while an unwelcome visitor can be greeted by an alarm sound or a warning message.

[0120] As well, messages can be spoken in any language, volume, pitch, accent, and the like. Users may find that various combinations of vocal characteristics to be useful in different situations. For example, if a user is hosting a Mardi gras party, the user can configure the security system 202 to emit a message spoken by a person with a southern accent. Generally, it should be appreciated that the speaker 488 of the security system 202 can be configured to emit any type of sound for any type of specific situation.

[0121] Likewise, the security system 202 can be configured to play a specific message if the potential visitor is not included in a list. For example, where a potential visitor is not included in a list of the resident's contacts, the security system 202 can be configured to indicate that the resident does not accept solicitors and/or request the visitor to provide identifying information or describe the purpose of the visit.

[0122] In some embodiments, the security system 202 can be configured to play a specific message if the potential visitor has a criminal background. For example, a user can

configure the security system **202** to play a specific message where a potential visitor is a registered sex offender.

[0123] The sounds emitted by the security system **202** can be recorded by the user him/herself. As well, the sounds can be downloaded from another source, such as a remote computer (e.g. a remote server), a remote computing device (e.g. a smart phone), a website, a database (e.g. iTunes®), and the like. Also, methods can include selecting the first sound and the second sound with a remote computing device that is configured to receive alerts from the doorbell. The selected sounds can be wirelessly transmitted to the doorbell.

[0124] As well, the sounds can be recorded with a remote computing device **204** and the sounds can be set up for temporary use whereby the sounds can expire upon a predetermined time. For example, a user can enter an expiration date of the recorded sound with the remote computing device **204**. Furthermore, the user can wirelessly send the first sound and the expiration date from the remote computing device to the doorbell. Once the expiration date passes, the security system **202** can then cease to emit the recorded sound from the security system **202**.

[0125] As well, the security system **202** can be configured to receive sound emitting parameters from a remote computing device **204**. The security system **202** can emit a predetermined sound based upon the sound emitting parameter. In some embodiments, the sound emitting parameter includes at least one of an identity of the first visitor, data associated with the first visitor, a time, a location of a user of the remote computing device. In some embodiments, the security system **202** can automatically download a third sound based on the sound emitting parameters. The security system **202** can emit the third sound from the speaker according to rules associated with the third sound.

Alert Communication Embodiments

[0126] Embodiments of the security system **202** can be configured to alert individuals located outside of a building (e.g. a home). For example, the security system **202** can be configured to flash a light, emit a sound (e.g. alternating high pitch and low pitch sounds), initiate a communication session with a remote computing device **204**, and the like. These various alerts can be useful to individuals, such as first responders, seeking to identify the location of an event, such as an emergency event(s) occurring within or outside the home. Home, as used herein, may refer to a building whereby one or more occupants sleep in the building on a permanent basis. Home may distinguishable from an office building by the lack of permanent occupants that sleep in the office building. Home may refer to an apartment building due to the permanent nature of an occupant for the duration of a lease. Home may be distinguishable from a hotel due to the lack of permanent occupants.

[0127] FIG. 11 illustrates an embodiment in which a security system **202** is communicatively coupled to a communication device **416**. The security system **202** may be part of a communication system **400**. The communication system **400** can be similar to that of the communication system **200** except, the communication system **400** may also be configured to allow communication between the security system **202** and the communication device **416**.

[0128] In various embodiments, the security system **202** can be communicatively coupled, directly and/or via the cloud, to a communication device **416**, such as a hub device,

a communication system, and/or an event detection device **418**, such as a sensor, (e.g., a peripheral device, such as a Nest Protect® (registered by Google Inc.), Nest Learning Thermostat® (registered by Google Inc.), DropCam® (registered by Google Inc.), and the like. The communication device **416**, event detection device **418** and/or the security system **202** can be used to monitor various events within the building **300** (e.g., home). Specifically, the communication device **416** and/or event detection device **418** can detect emergency events and then notify the security system **202**. In some embodiments, the communication device **416** is communicatively coupled to the event detection device **418** that detects the emergency event or adverse event (which is discussed further herein). In this manner, the security system **202** may directly or indirectly receive a notification of the emergency event from the event detection device **418** and/or the communication device **416**.

[0129] The security system **202** can communicate with the communication device **416** via a communication network **414**. The communication network **414** can be similar to the wireless communication **230**, however, the communication network **414** can be wired or wireless. In embodiments, the communication network **414** can utilize the existing electrical wires in the doorbell wires to communicate with the security system **202** (e.g., powerline networking). The communication network **414** can also utilize a wired Local Area Network. In embodiments, the communication network **414** can include a Wide Area Network (WAN) that connects the communication device **416** to the security system **202** over the Internet.

[0130] In embodiments, the communication device **416** is a type of device that is configured to connect multiple devices and facilitate communication between the multiple devices. The security system **202** may be a device that also is communicatively coupled to the communication device **416**. The communication device **416** may receive a transmission from one device (i.e., an event detection device **418**), make a determination on what type of communication to perform (e.g., an alert), and transmit the communication to a second device (e.g., the security system **202**) to take further action.

[0131] The security system **202** can be configured to communicate with remote computing devices (i.e., the computing device **204**). The computing device **204** may refer to a remote computing device in embodiments. The security system **202** can initiate a communication session through the communication network **414** by sending a request to the computing device **204** to establish a secure connection (e.g., a virtual private network) to enhance security. In embodiments, the communication session may also include an indication that an event (as discussed further herein) has been initiated.

[0132] The security system **202** can have an outer housing **224**. The outer housing **224** may be configurable to attach to a building **300**. The outer housing **224** of the security system **202** can attach to the building **300** using a variety of permanent or temporary mounting mechanisms. In embodiments, the permanent mounting mechanism may prevent the removal of the security system **202**. The building **300** may include a variety of structures. For example, the building **300** includes a home, which is a type of building **300**. The home can include various types of structures in various square footages. For example, a home can be a wooden framed building with an exterior of stucco, brick, or siding.

In embodiments, a home can be distinguished from other types of buildings based on the livable area (e.g., 500 square feet to 5000 square feet). In embodiments, a home can also be defined as being a freestanding structure without shared walls. A home may also be defined by zoning constraints. For example, the home may be zoned residential instead of commercial or industrial.

[0133] The outer housing 224 can also include a visitor detection system 412 coupled to the outer housing 224. The visitor detection system 412 can be an assembly of components that are collectively configured to detect visitors in the immediate vicinity (e.g., within 0.5 to 50 feet) of the security system 202. The visitor detection system 412 can include the doorbell button 212, the camera assembly 208, and an audio input device 410. In addition, the visitor detection system 412 can also include the motion detector 218 and fingerprint sensor 210. The audio input device 410 can be a device that captures audio (e.g., a microphone). The audio input device 410 can have various sensitivity ranges depending on the application. In embodiments, the audio input device 410 can include multiple microphones to extend the coverage area of audio capture. For example, the audio input device can have one microphone on board the outer housing 224 and receive input from another microphone located within the house (e.g., through the communication network 414).

[0134] The outer housing 224 may also include a deactivation unit 411. The deactivation unit 411 can be a component that is communicatively coupled to the security system 202. The deactivation unit 411 may be responsible for disabling the alert communication system 402. In embodiments, the deactivation unit 411 is part of the alert communication system 402. The alert communication system 402 may work passively or actively. In an active configuration, the security system 202 can actively monitor for a command to deactivate. For example, the security system 202 can send "activation status requested" signal to a deactivation unit 411 in regular intervals along with a unique randomized code and receive an "activation=True" signal from the deactivation unit 411 along with the unique randomized code. When communication is interrupted, then a non-response of the activation status may indicate "activation=False". When deactivated, the deactivation unit 411 transmits an "activation=False" signal along with the unique randomized code. The actively monitoring for the command can be advantageous where communication is lost with the deactivation unit 411 (i.e., the communication is modified or the deactivation is spoofed by an intruder).

[0135] The deactivation unit 411 may also passively monitor for the command. For example, an occupant may input a command through the deactivation unit 411 that is transmitted to the security system 202. The security system 202 can receive the command passively. In embodiments, the deactivation unit 411 may also be communicatively coupled with a remote computing device 204. The deactivation command may originate from the remote computing device 204 to deactivate the alert communication system 402 in either actively or passively.

[0136] The outer housing 224 can also include an alert communication system 402 coupled to the outer housing 224. The alert communication system 402 can be configurable to activate in response to an initiation of an event. For example, an alert from the communication device 416 that is transmitted to the security system 202 can activate various components on the security system 202 through the alert

communication system 402. The alert communication system 402 can include components to communicate alerts to a user (e.g., an occupant of the home). In embodiments, the alert communication system 402 is the security system 202 or part of the security system 202. In embodiments, the alert communication system 402 includes a light 406 and a speaker 404. The light 406 can comprise the diagnostic light 216 and/or the power indicator light 220, as shown in FIG. 1, and/or any other light coupled to the security system 202. As well, the speaker 404 may comprise the speaker 488, as illustrated in FIG. 1, and/or any other speaker coupled to the security system 202.

[0137] In embodiments, the alert communication system 402 refers to a collection of components for the purpose of alerting an occupant of the building 300. The alert communication system 402 can also refer to a control unit for the components that alert an occupant of the building 300. The control of the alert communication system 402 can be separate from the control for the security system 202. In embodiments, the alert communication system 402 is attached to an exterior surface of the home (i.e., a building 300). The outer housing 224 may be attached to an interior surface of the home (i.e., a building 300). The remote computing device 204 can be operated by the homeowner (i.e., a type of occupant).

[0138] The speaker 404 of the alert communication system 404 can be configured to emit a sound in response to the initiation of the event. For example, if the communication device 416 transmits an alert that indicates an emergency, then the security device 202 can emit a sound in the speaker 404 that indicates danger. The speaker 404 can be configured to emit a wide-range of sounds and various decibel levels depending on the application. For example, a more severe alert can be louder than a less severe alert. The security system 202 can alert an occupant of suspicious smoke by saying the location of the smoke and the time the smoke was detected.

[0139] The speaker 404 can simply emit a voice that says "Danger, Danger, Danger" to alert an occupant of the building 300. The sound emitted by the security device 202 can be unique to the type of alert. For example, if a fire alert is transmitted by the communication device 416, then the security device 202 can emit a voice that says "Fire, Fire, Fire" and repeats at a set interval. Various sounds can also be used to selectively alert other occupants. For example, a high frequency sound of 24 kHz to 45 kHz can selectively alert canine occupants of the building 300 without alerting a human. In another example, a sound from 17 kHz to 23 kHz may selectively alert children but not adults. Various patterns of sounds can also be produced. For example, the "SOS" Morse code pattern may be used to indicate distress.

[0140] The light 406 of the security system 202 may be configurable to illuminate in response to the initiation of the event. The light 406 can emit a variety of colors in a variety of patterns. For example, the light 406 can emit both a green light, a white light, and a red light. A green light can be lit during normal operation. A white light color can be used for ordinary alerts, such as a power outage. A red light color can be used to indicate an imminent emergency that alerts the occupant to leave the building 300 immediately. For example, the red light color can be used to alert the occupant of a gas leakage or a fire or armed intruders.

[0141] In embodiments, the light 406 can flash at various frequencies to indicate a pattern. For example, three short

flashes, followed by three long flashes, followed by three short flashes, can indicate distress. While rapid flashes can indicate a higher priority than slower flashes of light. The light **406** can be coordinated with the speaker **404**. For example, the light **406** can flash at the same time that the speaker **404** makes a sound. The light **406** can also flash before or after the emission of sound from the speaker **404**.

[0142] The alert communication system **402** can also include emission of an odor. The odor can be discernable by an occupant to know that something is wrong or can ward away an intruder. For example, if the communication device **416** alerts the security system **202** of an intruder, then a strong smell (such as that of a skunk) can trigger a silent alarm. Various smells can be used. For example, flowery odors can be used for non-urgent alerts (such as a water leak) while mercaptan-based odors can be used for urgent alerts.

[0143] The alert communication system **402** can include remote communication **407**. The remote communication **407** can be responsible for communicating with a remote computing device **204** the status of the alarm. In embodiments, the remote communication **407** can be a module that communicates with a security monitoring service, which can also have a dedicated communication channel that is different than the communication network **414** in order to alert authorities in the event of a power outage.

[0144] In embodiments, the security system **202** is powered by an electrical power input **408**. The electrical power input **408** can be a battery. The electrical power input **408** can also be from an electrical source such as from a household Alternating Current. The electrical power input **408** can also be configured to receive a step-down voltage (e.g., around 8V to 24V) from doorbell wires **304**. The alert communication system **402** may be electrically coupled to electrical wires **409** (through the electrical power input **408**). The electrical wires **409** can be configurable to be coupled to the doorbell wires **304** of a home (e.g., the building **300**). The alert communication system **402** can be configurable to activate in response to a determination that an event has been initiated through the electrical wires **409**. In embodiments, the communication can happen over powerline networking. Various spikes in electrical signals from the electrical wires **409** can also signal the alert communication system **402**. In embodiments, a lack of electrical signal from the electrical wires **409** can also activate the alert communication system **402**. For example, the lack of electrical power input **408** from the electrical wires **409** can activate the alert communication system **402**. The alert communication system **402** can further utilize a backup battery system through the electrical power input **408** and cause the light **406** to emit white colored light so that an occupant can see.

[0145] The security system **202** may be configured as a passive or active device. As a passive device, the security system **202** may receive notifications of emergency events from the communication device and/or the event detection device **418**. For example, a smoke detector event detection device **418** can transmit a smoke event to the communication device, which may communicate to the security system **202** an indication that the smoke event is occurring. The security system **202** can be monitoring for notifications from the communication device whenever a communication channel is established.

[0146] As an active device, the security system **202** may be configured to actively monitor whether the communication device and/or event detection device **418** has detected

the occurrence or initiation of an emergency event (or adverse event). For example, the security system **202** can periodically request from the communication device a status of events. If there is no status, then the security system **202** can wait until another request is filled.

[0147] FIG. 12 illustrates a block diagram of an enhanced view of various event detection devices **418**, according to some embodiments. The event detection devices **418** can be communicatively coupled to the communication device. Types of event detection device **418** can include a smoke alarm **420** or a burglar alarm **422**. The event detection device **418** can be configured to communicate with a communication device or to the remote device **204** through the communication network **414**. In embodiments, the event detection device **418** can be “smart” and communicate with a variety of devices. The event detection device **418** can connect via the Internet of Things (IoT) and may each have a unique network identifier. The IoT may encompass various standards. For example, standards may include ALLJOYN® (Registered by Qualcomm Innovation Center Inc.), Thread Group, IEEE® (Registered by the Institute of Electronic and Electrical Engineers, Inc.) P2413 working group, IoTivity® (Registered by Samsung Electronics Co., Ltd.), or Representational State Transfer.

[0148] The security system **202** may comprise an alert communication system **402** that may include a light **406**, a speaker **404**, and a wireless communication system **230** that may be configured to initiate a transmission with a remote computing device **204**. For example, the communication device may comprise a smart smoke detector **420** (e.g. Nest Protect®, registered by Google Inc.), and in response to the smart smoke detector detecting elevated levels of smoke **434**, or elevated levels of other toxic gases, the security system **202** may activate its alert communication system **402** (e.g. flashing a light and/or emit a sound). This may thereby alert individuals outside the home as to the location of the home where the emergency event is occurring.

[0149] As well, it should be appreciated that the emergency event can comprise any type of event **424** that may require the attention of another party. As used, event can refer to an emergency event or an adverse event, which indicates harm to an occupant or requires the attention of a party other than the occupant. For example, the emergency event may comprise at least one of a fire **426**, a gas leak **428**, a break-in **436**, elevated levels of smoke **434**, elevated levels of radon **432**, elevated levels of carbon monoxide **430**, and the like.

[0150] The alert communication system **402** can be configured to alert individuals located outside the home in any variety of ways. For example, the alert communication system **402** can flash a bright light emitting diode and/or a light located behind the doorbell button **212**, such as the diagnostic light **216**, on the security system **202**. In some examples, the alert communication system **402** can emit a loud sound from the speaker **404**. For example, the loud sound can be alternating high and low pitch sounds that may be heard by individuals located within 300 feet of the home. The high and low pitch sounds can be of high and low frequencies that may be heard by individuals located within a neighboring home and/or a vehicle passing by. The loud sound can be a unique sound easily detectable by individuals. As well, the sound can comprise a noise that indicates danger or help is required.

[0151] Furthermore, the alert communication system 402 can be configured to initiate a transmission to a remote computing device 204. For example, if the security system 202 determines that a break-in has occurred, the security system 202 may initiate a computing session and/or a notification with the remote computing device 204 to alert an individual that is operating the remote computing device 204 of the break-in 436 at the home. As well, it should be appreciated that the security system 202 can initiate a transmission to any other party, such as an emergency dispatcher (e.g. 911).

[0152] The security system 202 may be configured to activate its alert communication system 402 after a predetermined amount of time. The predetermined amount of time may be 0 seconds, 10 seconds, 20 seconds, 1 minute, and the like. Generally, it should be appreciated that the alert communication system 402 may activate nearly at the same time as the communication device 416 detecting the emergency event 424 or any time thereafter.

[0153] FIG. 13 illustrates a flowchart of a method 500 of monitoring for an event through a communication device 416, according to some embodiments. The method 500 can generally involve connecting to a communication device 416 and receiving a notification of an event from the communication device 416. The security system 202 can react based on the event from the communication system. The method 500 begins at block 510.

[0154] In block 510, the security system 202 can establish a connection with the communication system. As mentioned herein, the communication device 416 may utilize either a wired or wireless connection 230 to communicate with the security system 202. For example, a wireless home network that utilizes Wi-Fi may be used or local Bluetooth™ pairing may be used. Once connection is established, then the communication device 416 may be configured to only communicate with security system 202 at the ID provided by the security system 202. For example, the security system 202 may have a unique IPv6 address that the communication device 416 transmits to. The communication device 416 may also have a unique IPv6 address that the security system 202 transmits to. The security system 202 may also be configured to receive alerts from only the IPv6 address that belongs to the communication device 416, thus preventing spoofing type alarms. Various permissions may be set up using an Application Programming Interface (API) of the communication device 416. For example, the security system 202 can be set up as a client with read/write permissions which identifies the security system 202 that has permission to share data with the communication device 416.

[0155] In block 512, the security system 202 may monitor for an event. In embodiments, the security system 202 monitors for an event from the communication device 416. For example, the communication device 416 may receive a notification of an event from an event detection device 418. In embodiments, the security system 202 can monitor for an event using localized components. For example, the security system 202 may have a camera that is used to monitor for suspicious activity. The event may be communicated with the communication device 416 and the communication device 416 may take appropriate action (e.g., notify emergency services). As mentioned herein, the types of events may be selected from at least one of a fire, a gas leak, a break-in, elevated levels of smoke, elevated levels of radon, elevated levels of carbon monoxide, and the like.

[0156] The event detection device 418 may detect an event using a variety of methods. For example, various thresholds may be employed to detect an event 424. For example, the elevated levels of smoke event 434 can be based off of optical obscuration or electrostatic precipitation. The smoke can be based off of a threshold of parts per million or percentage of optical transmittance. The radon event 432 can be based off of PicoCuries per Liter reading from a radon detection unit. The gas leak event 428 can be based off of an 80% Lower Explosive Limit. Various gas detectors can be used (e.g., electrochemical, infrared point, infrared imaging, semiconductor, ultrasonic, holographic, etc.). A fire event 426 may be detected using temperature or a combination of readings from a smoke event 434 and a carbon monoxide event 430. The break-in event 436 may utilize various sensors present in the security system 202 or external sensors to the security system 202 (e.g., motion sensors). The event 424 is associated with a home (i.e., building 300), and the doorbell (i.e., security system 202) is attached to the home of a homeowner.

[0157] In block 514, the security system 202 can determine whether an event has been initiated. The event may be initiated whenever the security system 202 receives a transmission from a communication device 416 communicatively coupled to the security system. The transmission may be over various forms of communication and provide an indication that the event has been initiated. The security system 202 may monitor the communication system to detect whether the event has been initiated. In embodiments, the security system 202 (e.g., the doorbell) can interface with a remote computing device 204 to further communicate to an occupant that there is an alert at the home. Communicating via the remote computing device 204 may have the benefit of keeping occupants informed while away from the home. The security device 202 can establish a communication session with a remote computing device 204 in a similar manner as to the communication device 416. The communication session may include an indication that the event that has been initiated. For example, an occupant can receive a communication of a fire alert on a local application on their remote computing device 204 from the security system 202.

[0158] In block 516, the security system 202 can determine the alarm type. In embodiments, block 516 may be optional. Despite a variety of devices available to the security system 202, not all devices or tools may be appropriate in certain settings. For example, a non-urgent alert (such as elevated radon levels) may not warrant a high-pitched, high-volume noise in the middle of the night. The security system 202 can balance the severity of the alert with the certainty for the alert. For example, significant amounts of dust can trigger a smoke detector but the certainty of a fire can be determined using a carbon monoxide detector in conjunction with the smoke detector. The severity of a fire may be high but if the certainty that a fire is occurring is low, then the security system 202 can determine that another alarm type is more appropriate. Examples of determining an alarm type are described further herein.

[0159] In block 518, the security system 202 can activate the alert communication system 402 in response to determining that the event has been initiated in block 514. In embodiments, activating the alert communication system 402 can include activating selected components of the alert communication system 402 (e.g., the speaker 404 or the light 406). As mentioned herein, the alert communication system

402 can include a light **406** which, when the alert communication system **402** is activated, can cause the light **406** to illuminate in a variety of patterns and colors. The alert communication system **402** can also include a speaker **404** that emits a sound in a variety of intensities, frequencies, and patterns. The activating can also include activating a control element for the alert communication system **402**. The control element for the alert communication system **402** can instigate a variety of patterns and alerts for multiple components (e.g., a flashing light followed by emission of selected sound frequencies).

[0160] In block **520**, once the alert communication system **402** is activated, the security system **202** can monitor for a command to deactivate the alert communication system **402**. In embodiments, block **520** may be optional. For example, a user of the security system **202** may not desire the security system **202** to alert occupants (e.g., a false positive). The command can be a sequence of instructions that is understood by the security system **202** to deactivate the alert communication system **402**. In embodiments, the command can be a button press and an audible predetermined message. For example, an occupant can push a button (e.g., the door bell button **220**) and speak an audible predetermined message such as “Alarm Deactivate” to deactivate the alert communication system **402**. In various embodiments, the deactivation unit **411** can be configured to perform vocal recognition in order to distinguish between the voice of the occupant with the voice of a non-occupant, such as a prowler. Once the command is received, then the method **500** can continue to operation **522**.

[0161] In block **522**, the security system **202** can deactivate the alert communication system **402** in response to receiving the command to deactivate the alert communication system. The alert communication system **402** may be deactivated in a variety of ways. For example, the alert communication system **402** may deactivate (e.g. turn off the current alert) in response to the security system **202** receiving an indication that the doorbell button **212** has been pressed. In some embodiments, the security system **202** may be configured to turn off the alert communication system **402** in response to receiving an audible predetermined message, such as a spoken safety message or a spoken password that indicates that the event is being attended to or has ended. In some embodiments, the security system **202** can receive a deactivation command from the remote computing device **204**. In this manner, the individual operating the remote computing device **204** may send a command through the remote computing device **204** to terminate the ongoing alert. The deactivation of the alert communication system **402** can include selectively deactivating less than all of the components of the alert communication system **402**. For example, the deactivating of the alert communication system **402** can include deactivating only the localized communication (i.e., the speaker **404** and the light **406**) but not the remote communication **407** with law enforcement (e.g., a silent alarm).

[0162] FIG. **14** illustrates an example table **600** of various alarm types that are used based on the certainty and severity of the event, according to some embodiments. The table **600** can correspond to block **516** in FIG. **13** where a security system **202** can determine the alarm type. In embodiments, the alarm type may be pre-assigned depending on the certainty and the severity of the event. For example, an

occupant may desire that a gas leak is always associated with an audible alarm and a red light, despite a low certainty.

[0163] The alarm type can also be based on threshold values. For example, if the certainty of a fire is 20% but the severity is high, the security system **202** can create a score that is based on the severity and the certainty. The security system **202**, based on the score, can determine the type of alarm. For example, a high severity event with a low certainty may (such as the fire) may be associated with a sound to invite an occupant to investigate further. A high severity event such as a gas leak but with a higher certainty may trigger a red flash along with the sound. A low severity event such as a baby crying can trigger a different set of alarm types such as playing comforting music.

Customized Sound Embodiments

[0164] The security system **202**, or doorbell **202**, may be configured to receive a custom sound(s) from a user and thereby emit the custom sound in response to a particular situation(s). For example, as illustrated in FIG. **15**, a doorbell system **200** may receive a custom message (at step **1500**). A user of the system may then optionally assign the custom message to a select visitor (at step **1502**). Thereby when an indication of a presence of the select visitor is detected by the doorbell **202** (at step **1504**), the doorbell **202** may then respond by emitting the custom message with a speaker **404**, **488** of the doorbell **202** (at step **1506**). It should be appreciated that the term “detecting” may be defined as discovering or identifying the presence or existence of a visitor. As such, the term “detecting” may be used interchangeably with the term “determining.”

[0165] The custom sound, or custom message, may be received by the doorbell system **200** in a variety of ways. As shown in FIG. **16**, the doorbell system **200** may download the custom message from a remote computer, such as a remote computing device (e.g. a smart phone) (at step **1600**). As well, the doorbell system **200** may record the custom message (at step **1602**). For example, a user of the doorbell system **200** may record the custom message on his or her remote computing device, such as a smart phone, (at step **1602**) and then download the custom message from the smart phone onto the doorbell system **200**. In some embodiments, the custom message may be directly recorded by the doorbell **202** (at step **1602**), such as recorded by a microphone of the doorbell **202**. Generally, it should be appreciated that the custom message may be recorded by any type of recording device that is communicatively coupled to the doorbell system **200** (at step **1602**). In this manner, the doorbell system **200** may download the custom message from the recording device.

[0166] As further illustrated in FIG. **16**, any number of custom messages may be recorded and/or downloaded by the doorbell system **200**. For example, the doorbell system may record and/or download a second custom message (at step **1604**), a third custom message, a fourth custom message, and any number of additional custom messages.

[0167] The doorbell system **200** may also be configured to interact with a visitor whereby the doorbell system **200** gives and receives audible information. In this manner, the doorbell system **200** may interpret information from the visitor. With reference to FIG. **17**, the doorbell system **200** (e.g. a speaker **404**, **488** of the the doorbell **202**) may be configured to emit an audible question(s) (at step **1700**). The doorbell system **200** (e.g. via a microphone of the doorbell **202**) may

then receive an audible response from the visitor (at step 1702). The doorbell system 200 may thereby determine the meaning of the audible response given by the visitor. For example, the doorbell system 200 may determine whether the audible response comprises a first meaning or a second meaning (at step 1704). For example, if the doorbell system 200 determines that the audible response comprises the first meaning, the doorbell 202 may then emit a first audible response, via the speaker 404, 488, (at step 1706). As well, if the doorbell system 200 determines that the audible response comprises the second meaning, the doorbell 202 may then emit a second audible response, via the speaker 404, 488, (at step 1708). In this manner, the doorbell system 200 may be a smart system that is able to interpret and respond to different responses given by the visitor.

[0168] The doorbell system 200 may also be configured to initiate a communication session with a remote computing device 204, such as a remote computing device 204 associated with the visitor and/or a user of the doorbell system 200 (e.g. a resident of the building 300). For example, the doorbell system 200 may detect an indication of a presence of a visitor (at step 1800). The doorbell system 200 may then initiate a communication session with the remote computing device of the visitor and/or the resident (at step 1802). The communication session may comprise any type of communication and/or transmission to the remote computing device, such as a text message, phone call, voicemail, email, and the like. For example, the communication session may comprise a written message that substantially matches a content of the custom message as emitted by the speaker 404, 488. In this manner, hearing impaired visitors may be able to receive the message.

[0169] Furthermore, in some embodiments, the doorbell system 200 may be configured to determine an identity of a first visitor and/or a second visitor. Accordingly, the doorbell system 200 may initiate a communication session, such as transmit a text message, to a remote computing device 204 that includes at least one of the identity of the first visitor and/or the identity of the second visitor. Generally, it should be appreciated that the communication session may include any type of information relating to the visitor and/or the visitor's presence at the doorbell 200.

[0170] The doorbell system 200 may also be configured to detect various types of visitors. In some embodiments, as illustrated in FIG. 19, the doorbell system 200 may be referred to as a first doorbell system 200a, which may be configured to detect an indication of a presence of a criminal (at step 1900). The first doorbell system 200a may detect the indication of the presence of a visitor, such as a criminal, by receiving a notification from a second doorbell system 200b that is communicatively coupled to the first doorbell system 200a and remotely located with respect to the first doorbell system 200a. For example, the second doorbell system 200b may determine that a criminal is in the area and then alert all other doorbell systems 200 located within the vicinity, including the first doorbell system 200a.

[0171] With reference to FIG. 19, in response to the doorbell 202 and/or doorbell system 200 detecting the indication of the presence of the criminal, the doorbell 202 may emit a warning message with a speaker 404, 488 of the doorbell 202 (at step 1902). The doorbell system 200 may then initiate a communication session with a law enforcement agency to notify the agency of the presence of the criminal (at step 1904). It should be appreciated that the

warning message may include a message to scare away the criminal and/or inform the criminal that the law enforcement agency has been contacted.

[0172] As shown in FIG. 20, the doorbell system 200 may also be configured to identify a visitor, such as a criminal or suspicious person, by taking a picture of the visitor (at step 2000). The doorbell system 200 may then determine, based on the picture, that the visitor is included in a database of suspicious visitors, such as a database of criminals, that previously visited other doorbells 202 (at step 2002). The doorbell system 200, and/or a remote computer, may use facial recognition software to match the facial data of the criminal with facial data from a law enforcement database. As well, the doorbell system 200 may detect the indication of the presence of the criminal by detecting body language of the criminal, such as detecting evasive or suspicious moves, detecting a fingerprint of the criminal, detecting a retina of the criminal, and the like.

[0173] As well, the doorbell system 200 may be configured to determine various types of visitors. As shown in FIG. 21, for example, the doorbell system 200 may determine that a visitor is a predetermined visitor type (at step 2100). The predetermined visitor type may comprise any type of visitor, such as a known visitor (e.g. a friend, a family member, and/or anyone included on a smart phone contact list of a user), a known visitor, a suspicious visitor, a criminal, and the like. In response to determining that the visitor is the predetermined visitor type, the doorbell system 200, via the doorbell 202, can select a custom message from a first message and a second message (at step 2102). In response to determining that the visitor is a known person, the doorbell system 200 may emit the first message (at step 2104). In some embodiments, the first message optionally includes a name of the known person. For example, the doorbell system 200 may determine that a known person named Tim, who is a friend of the resident, is present. Accordingly, the doorbell 202 may audibly announce, "Welcome, Tim."

[0174] Likewise, in response to determining that the visitor is a stranger, the doorbell 202 may emit the second message (at step 2106). For example, if the doorbell system 200 determines that the stranger is a solicitor, the doorbell 202 may emit an audible message informing the solicitor that the resident does not purchase items from solicitors, an apology, and an invitation to exit the premise. Generally, it should be appreciated that the doorbell system 200 may be configured to determine any type of visitor and emit any type of custom message in response to the type of visitor.

[0175] The doorbell system 200 may also be configured to emit custom messages in response to the occurrence of predetermined conditions. As illustrated in FIG. 22, the doorbell system 200 may detect an indication of a presence of a visitor (at step 2200). The doorbell system 200 may thereby determine that a predetermined condition has occurred (at step 2202). For example, the predetermined condition may be a time of day, a period of days, such as a time when the resident(s) is on vacation, an event (e.g. a birthday party, during a football game, etc.), and the like. Accordingly, in response to the indication of the presence of the visitor and the occurrence of the predetermined condition, the doorbell 202 may thereby emit a custom message (at step 2204). It should be appreciated that the custom message may correspond with the occurrence of the predetermined condition. For example, if the predetermined con-

dition is the occurrence of a game in which the resident's favorite football team is competing, then the custom message may be the fight song for the football team.

[0176] The predetermined condition may also be an occurrence when the resident(s) is away from the building **300** or when the resident(s) is located within the building **300**. With specific reference to FIG. **23**, the doorbell system **200** may be configured to record and/or download more than one custom message, such as a first custom message and/or a second custom message, and then emit the respective custom message in particular situations (at step **2300**). Accordingly, the method may thereby include determining whether a resident is located within the building **300** or whether the resident is not located within the building **300** (at step **2302**). In response to determining that the resident is present within the building **300**, the doorbell **202** may thereby emit the first custom message (at step **2304**). For example, the first custom message may be a message informing the visitor that the resident will be right there, such as, "Please wait a moment. Mr. Banks will be right there" (whereby Mr. Banks is the resident). In response to determining that the resident is not present within the building, the doorbell **202** may thereby emit the second custom message (at step **2306**). The second custom message may include a message informing the visitor that the resident is busy (if the visitor is a suspicious person—to avoid a robbery) or away from the building **300** (if the visitor is a known person). For example, the second custom message may state, "I'm sorry. Mr. Banks is currently occupied. Please come back another time."

[0177] The doorbell system **200**, via the doorbell **202**, may be configured to receive the custom message in response to a variety of inputs as received by the doorbell system **200**. For example, as shown by FIG. **24**, the doorbell **202** may receive an indication of a first button press from a button **212** of the doorbell **202** (at step **2400**). In response to receiving the first button press, the doorbell **202** may thereby record the custom message and store the custom message within a memory of the doorbell system **200** (at step **2402**). As well, the doorbell system **200** may be configured to receive an input, such as receive an indication of a second button press from the doorbell **202** (at step **2404**). In response to receiving the second button press, the doorbell system **200** can thereby erase the custom message from the memory of the doorbell system **200** (at step **2406**).

[0178] It should be appreciated that any reference to first button press, second button press, and the like, can refer to any number of button presses or duration of respective button presses. For example, the first button press can comprise two button presses and the second button press can comprise one button press. As well, the first button press can comprise one button press and the second button press can comprise two button presses. In some embodiments, the first button press can comprise the button **212** being pressed for a first duration and the second button press can comprise the button **212** being pressed for a second duration. It should be appreciated that the first duration can be greater than, equal to, or less than the second duration.

[0179] However, it should be appreciated that the inputs may be any type of inputs into the doorbell system **200**. For example, in conjunction or instead of a first and second button press, the doorbell system **200** may be configured to receive various motions from the user. In some embodiments, the camera **208** of the doorbell **202** may detect a first motion from the user, such as the user waving a hand once.

In response to detecting the first motion, the doorbell **202** may thereby record the custom message and store the custom message within a memory of the doorbell system **200**. As well, the camera **208** may detect a second motion from the user, such as the user waving a hand twice. In response to detecting the second motion, the doorbell **202** may thereby erase the custom message from the memory of the doorbell system **200**. Generally, it should be appreciated that any type of input, such as a bodily motion, may be received by the doorbell system **200**.

[0180] The doorbell system **200** may also be configured to provide security and anonymity to a user of the doorbell system **200**. For example, as shown in FIG. **25**, the doorbell system **200** may record and/or download a first custom message (at step **2500**). The first custom message may be spoken by a first voice. The doorbell system **200** may be configured to effectively convert the first message into a second message, whereby the second message is spoken by a second voice that is different from the first voice. The content of the first custom message can substantially match the content of the second custom message. As such, the doorbell system **200** may emit the second custom message (at step **2502**) that is spoken by the second voice. In this manner, the doorbell system **200** may effectively protect the identity of the user (e.g. resident) of the doorbell system **200**.

[0181] With respect to the various predetermined conditions, as shown in FIG. **26**, the doorbell system **200** may create a schedule of a first timeframe to emit a first sound, a second timeframe to emit a second sound, and a third timeframe to emit a third sound (at step **2600**). The doorbell system **200** may thereby determine that a visitation time of the visitor is within the first timeframe (at step **2602**), and in response to determining that the visitation time of the visitor is within the first timeframe, the doorbell **202** may emit the first sound (at step **2604**). Accordingly, if the doorbell system **200** determines that the visitation time of the visitor is within the second timeframe, the doorbell **202** may emit the second sound. Likewise, if the doorbell system **200** determines that the visitation time of the visitor is within the third timeframe, the doorbell **202** may emit the third sound.

[0182] For example, the first timeframe might include overnight and morning hours when the resident is either sleeping or getting ready for work. The first sound may thereby inform a visitor that the resident is busy and that the visitor should come back another time. As well, the second timeframe might include daytime hours, when the resident is away at work. The second sound might include a message that the resident is not available and that the visitor can reach the resident at work or on the resident's smart phone, if the visitor is a known or trusted visitor. Finally, the third timeframe might include a time during evening hours when the resident is home from work. The third sound may thereby inform the visitor that the resident will answer the door shortly. Generally, it should be appreciated that the doorbell system **200** may be configured to accommodate any timeframe or number of timeframes. As well, the doorbell system **200** may be configured to receive and thereby emit any sound in response to any of the respective timeframes.

[0183] With reference to FIG. **27**, the doorbell system **200** may be configured to receive any number of custom messages and then emit respective messages in response to the doorbell system **200** (e.g. the doorbell **202**) detecting an indication of a presence of any number of respective visitors. The doorbell **202** may emit a first custom audible message

with a speaker **404, 488** in response to the doorbell system **200** detecting an indication of a presence of a first visitor (at step **2700**). As well, the doorbell **202** may emit a second custom audible message with the speaker **404, 488** in response to the doorbell system **200** detecting an indication of a presence of a second visitor (at step **2702**). Likewise, the doorbell **202** may emit a third custom audible message with the speaker **404, 488** in response to the doorbell system **200** detecting an indication of a presence of a third visitor (at step **2704**).

[**0184**] The first, second and third custom audible messages can be assigned to specific visitors or groups of visitors. For example, the first custom audible message may be assigned to a specific first visitor. As well, the first custom audible message may be assigned to a specific group or type of visitor, such as any known visitor.

[**0185**] As shown in FIG. **28**, the doorbell system **200** may be referred to as a first doorbell system **200a** that is attached to a first building **300a**. The first doorbell system **200a** may be communicatively coupled to a second doorbell system **200b** that is attached to an exterior of a second building **300b** that is remotely located with respect to the first building **300a**. Accordingly, the first doorbell **202a** may also be communicatively coupled to the second doorbell **202b**. Thereby, the first doorbell system **202a** may detect an indication of a presence of a first visitor by receiving a first notification from the second doorbell system **202b** (at step **2800**). As well, the first doorbell system **202a** may detect an indication of a presence of a second visitor by receiving a second notification from the second doorbell system **202b** (at step **2802**). In this manner, the first doorbell system **202a** and the second doorbell system **202b** may be networked. This may allow doorbell systems **200** that are located within a specific area, such as a neighborhood, to communicate and transmit data to each other. The network of doorbell systems may exchange information and/or data to thereby monitor the entire neighborhood.

Chime Embodiments

[**0186**] Chimes **302** (shown in FIGS. **3** and **31-37**) can include all of the features, assemblies, parts, systems, and components of any doorbell **202** described herein or incorporated by reference. Chimes **302** can include all the items shown in FIG. **12**.

[**0187**] The chime **302** is a remote communication device that can be configured to communicate with any doorbell **202** described herein or incorporated by reference.

[**0188**] Referring now to FIGS. **31-37**, a user can use the remote computing device **204** to select a sound emitted by the chime **302** (e.g., a remote communication device) located inside the building or silence the chime **302** located inside the building. Several embodiments include many different sounds that the chime **302** can emit when someone “rings” the doorbell **202** or is detected by the doorbell **202**.

[**0189**] As illustrated in FIG. **31**, the chime **302** may receive backup or primary power from a power source of a building **300** and/or a battery **462b** located within the chime. As well, the chime **302** may include various components to detect different events within the vicinity of the chime **302**. For example, embodiments may include a motion detector **218** configurable to detect motion along an inside portion of the building **300**. The chime **302** may also include a camera assembly **208b** configurable to capture an image along the inside portion of the building **300**. As well, the chime **302**

may include a speaker **488b** configurable to emit sounds and a microphone **484b** configurable to receive an audible message spoken by a user.

[**0190**] Even still, in embodiments, the chime **302** (e.g., a remote communication device) may include additional components including, but not limited to, a thermometer **512b** configurable to determine temperature along the inside portion of the building **300** and a humidity sensor **305** configurable to determine humidity along the inside portion of the building **300**. The chime **302** may include a detection system **528b** that may include miscellaneous detection components to monitor and detect various other events. As well, the chime **302** may include a communication system **504b** configurable to communicatively couple the chime to the doorbell **202**, the remote computing device **204**, and/or any other communication device. The communication system **504b** may communicate via WiFi, Bluetooth, Bluetooth Low Energy, Thread, ZigBee, and the like. It should be appreciated that the chime **302** may utilize none, some, or all the same components as utilized by the doorbell **202**.

[**0191**] A user can select a sound to be emitted by the chime **302** on her remote computing device **204** by using a control application **600**. The remote computing device **204** can then send the sound to the chime **302** via the doorbell **202** (and/or via a server **206** and a wireless network **308**). The sound can be a song, a greeting recorded by the user, or any other type of sound. Some embodiments include using a remote computing device **204** to download a sound from the Internet, sending the sound (or data associated with the sound) to the doorbell **202** (e.g., in response to using the remote computing device **204** to select the sound), sending the sound (or data associated with the sound) from the doorbell **202** to the chime **302**, and/or emitting the sound from the chime **302**.

[**0192**] As shown in FIGS. **32** and **33**, the chime **302** can include an electrical plug **307**. The plug **307** can be mechanically and electrically coupled to a power outlet **309** (as shown in FIG. **33**).

[**0193**] As illustrated in FIG. **34**, the doorbell **202** can serve as a communication bridge between the remote computing device **204** and the chime **302**. The doorbell **202** can be used to enable the remote computing device **204** to control the chime **302**. A user can select an option (e.g., a song or a chime setting) on the remote computing device **204**, then the system can send information regarding the option to and/or from the computing device **204**. Then, the system can send information regarding the option from the doorbell **202** to the chime **302** in response to the user selecting the option via the remote computing device **204**. The communication **230** between the computing device **204** and the doorbell **202** can be wireless. The communication **230** between the doorbell **202** and the chime **302** can be wireless.

[**0194**] As illustrated in FIG. **36**, the chime **302** (e.g., a remote communication device) can serve as a communication bridge between the remote computing device **204** and the doorbell **202**. This can be especially helpful when the doorbell **202** cannot access the wireless network **308** of the building **300** to which the doorbell is mechanically and/or electrically coupled. The chime **302** can be located inside the building **300**, and thus, is more likely to access the wireless network **308** of the building **300** (due to a superior signal strength of the wireless network **308** at the chime **302** compared to the signal strength at the doorbell **202**, which

can be located much farther from a router of the wireless network 308). Some embodiments include configuring the chime 302 to serve as a communication bridge between the remote computing device 204 and the doorbell 202 in response to a first wireless signal strength of the wireless network 308 at a first location of the chime 302 being greater than a second wireless signal strength of the wireless network 308 at a second location of the doorbell 202.

[0195] As illustrated in FIG. 3, the chime 302 (e.g., a remote communication device) can serve as a communication bridge between the doorbell 202 and a wireless network 308 of a building 300.

[0196] FIG. 32 illustrates embodiments of the chime 302 (e.g., a remote communication device) that include at least one plug 307 that may be electrically, mechanically and/or communicatively coupled to a power outlet 309. The one plug 307 can thereby electrically and/or communicatively couple the doorbell 202 to the wires of the power outlet 309.

[0197] The system 200 can be configured to communicate in various manners. In some embodiments, the remote computing device 204 communicates directly with the doorbell 202, while the doorbell 202 communicates directly with the chime 302. In some embodiments, the remote computing device 204 communicates directly with the chime 302, while the doorbell 202 communicates directly with the chime. Generally, it should be understood that the system 200 can be configured in any manner by the user.

Methods of Using a Chime

[0198] According to various embodiments, the doorbell system 200 can emit sounds from a chime 302. As illustrated in FIG. 38, the method can include selecting the sound by a remote computing device 204 (at step 1300). For example, the remote computing device 204 can allow a user to select the sound by toggling a radio button (not shown) as displayed on a screen of the remote computing device 204. In some examples, the user can select the sound by selecting a song or any type of audio file from a database, such as a music database (e.g. iTunes®), that is accessible through the remote computing device 204. In some embodiments, the remote computing device 204 can be a server 206, a communication device with a user interface (e.g. smart phone, tablet, etc.), and the like.

[0199] With continued reference to FIG. 38, methods can also include sending a data file, which can include a first data file 213 and/or a second data file 211, to a doorbell 202 that is communicatively coupled to the remote computing device 204 (at step 1302). The data file 211, 213 can include information that can represent the sound. The data file 211, 213 can be sent by the remote computing device 204 to the server 206 to the doorbell 202. However, in some embodiments the data file 211, 213 can be sent by the remote computing device 204 to the doorbell 202. As shown in FIG. 30, the remote computing device 204 can instruct the server 206, via a wireless communication 230 including a signal 604, to send the data file 211, 213 to the doorbell 202.

[0200] As well, methods can include the doorbell 202 sending the data file 211, 213 to the chime 302 that is communicatively coupled to the doorbell 202 and remotely located with respect to the doorbell 202 (at step 1304). In embodiments, the data file 211, 213 is transmitted wirelessly to the chime 302. As well, in embodiments, the data file 211, 213 is transmitted via a wire, such as wire 304b, as shown

in FIG. 38. In this manner, the data file 211, 213 is transmitted via a sound file communication 209.

[0201] There are various ways that the chime 302 can receive the data file 211, 213. In some methods, the data file can be downloaded from a web server, by at least one of the doorbell and the chime. Even still, in some embodiments, the remote computing device 204 can download the data file from the web server.

[0202] Methods can also include emitting the sound from a speaker 488b of the chime 302 at least partially in response to the chime 302 receiving the data file 211, 213 and at least partially in response to the doorbell 202 detecting an indication of a presence of a visitor. In this manner, when a visitor visits the building 300, the doorbell system 200 can alert the user by playing any type of customized or pre-recorded sound through the speaker 488b of the chime 302.

[0203] As well, users of the doorbell system 200 may configure the system 200 to emit the sound in accordance with certain parameters, such as sound emission parameters. Accordingly, methods may include receiving, by the doorbell 202, a sound emission parameter from the remote computing device 204. Methods may also include emitting the sound from a speaker 488b of the chime 302 in response to the doorbell system 202 determining that the sound emission parameter has been met. In some embodiments, the sound emission parameters may comprise predetermined timeframes. For example, the user may elect a sound emission parameter, such as a “do not disturb” parameter, so that the chime 302 does not emit the sound during predetermined hours of the day. As well, in embodiments, the sound emission parameters 302 may comprise specific visitors. For example, if an unknown visitor or unwelcome visitor (e.g. a door-to-door salesperson) visits the building 300, the sound emission parameters can instruct the chime 302 not to emit the sound when the doorbell system 200 detects the presence of the unknown or unwelcome visitor.

[0204] The chime 302 may also be configured to emit an audible message from a speaker 488b of the chime 302. The audible message may be a message that is spoken by a user and recorded by the doorbell 202, the remote computing device 204, and/or the chime 302 itself. In embodiments, a user of the system 200 may wish to transmit an audible message through the chime 302. For example, a first resident may speak an audible message such as, “Honey, I’ll be home in 30 minutes,” into his/her remote computing device 204. Accordingly, the system 200 may emit the audible message from the chime 302. Furthermore, in embodiments, the first resident may type a message into his/her remote computing device 204, and the system 200 may thereby announce an audible message that comprises the contents of the typed message.

[0205] The chime 302 may also be used to detect motion and capture audio and video recordings along an inside portion of a building 300. Specifically, the method may include the motion detector 218b of the chime 302 detecting a first motion within the inside portion of the building 300. Methods may also include initiating a first communication session with the remote computing device 204 in response to the motion detector 218b of the chime 302 detecting the first motion. The first communication session may include a first notification of the first motion detected by the motion detector of the chime. For example, the chime 302 may detect a prowler within the inside portion of the building 300

and the system **200** may thereby send an alert to the remote computing device **204** of the user.

[0206] In embodiments, the method may also include the motion detector **218b** of the chime **302** detecting a second motion within an inside portion of the building **300**. It should be appreciated that the second motion may be different from the first motion, or the same. The system **200** may thereby initiate a second communication session with a second remote computing device **204b** in response to the motion detector **218b** of the chime **302** detecting the second motion. The second communication session can comprise a second notification of the second motion detected by the chime **302**. In this regard, the first remote computing device **204a** may not receive the second communication session. Accordingly, the system **200** can be configured to alert different users based on different motions within the building **300**. For example, the chime **302** may detect suspicious motions and thereby alert the police. In some examples, the chime **302** may detect non-suspicious motions within the building **300**, such as the dog walking around, whereupon an alert is sent to the remote computing device **204** of the resident.

[0207] As well, methods may include selecting more than one sound and sending the more than one sound to the chime **302**. For example, methods may include selecting a second sound by the remote computing device **204** and thereby sending a second data file comprising second information to the doorbell **202**. The second information may represent the second sound. As well, methods may include sending the second data file to the chime **302**.

[0208] In embodiments, the chime **302** may be configured to emit different sounds in response to different motions detected by the motion detector **218** of the doorbell along an outside portion of the building **300**. For example, methods may include detecting a first motion, by a motion detector **218** of the doorbell **202**, along the outside portion of the building **300**. In response to the doorbell **202** detecting the first motion, the chime may thereby emit the first sound from a speaker **488b** of the chime **302**. As well, the motion detector **218** of the doorbell **202** may detect a second motion along the outside portion of the building **300**. It should be appreciated that the second motion may be different from the first motion, or the same. Accordingly, methods may include emitting the second sound from the speaker **488** of the chime **302** in response to the doorbell **202** detecting the second motion. In this manner, the chime **302** may be configured to audibly alert people within the building **300** as to whether various motions have been detected by the doorbell **202**. In embodiments, the chime **302** may emit an audible alarm if the doorbell **202** detects a suspicious motion. In embodiments, the chime **302** may emit a more friendly sound (e.g. “ding-dong”) if the doorbell **202** detects a non-suspicious motion.

[0209] As illustrated in FIG. 39, this disclosure also includes a method of using a doorbell system **200** to emit a sound from a chime **302**. The method may include selecting a sound by a remote computing device **204** (at step **1400**) and sending a data file **211**, **213** comprising information to the chime **302** (at step **1402**). It should be appreciated that the information may represent the sound. As well, the data file **211**, **213** may be sent to the chime **302** by the remote computing device **204** and/or the server **206**. Furthermore, methods may include detecting an indication of a presence of a visitor with a doorbell **202** (at step **1404**) and emitting

the sound from a speaker **488b** of the chime **302** in response to detecting the indication of the presence of the visitor (at step **1406**).

[0210] In addition to detecting motion, the chime **302** and/or the doorbell **202** may also capture audio, images and/or video. For example, as shown in FIGS. 35 and 36, in response to detecting a motion with the motion detector **218b** of the chime **302**, methods may include using the camera **208b** of the chime **302** to capture an image and/or video within the inside portion of the building **300**. It should be appreciated that the image and/or video may correspond to the motion detected by the chime **302**. The image and/or video may thereby be sent to the doorbell **202** and/or the remote computing device **204** where the image and/or video can be viewed via a control application **600** viewed on a display **603** of the computing device **204**.

[0211] As well, the method may use a microphone **484b** of the chime to detect and record audio within the inside portion of the building **300**. The audio recording may thereby be transmitted to the doorbell **202** and/or the remote computing device **204**, where it can be played back.

[0212] As well, the system **200** may be configured to respond in other various ways in response to detecting a motion. For instance, in embodiments, in response to detecting a motion with the motion detector **218b** of the chime **302**, the doorbell **202** may flash a light **216**, **220** to thereby indicate to people passing by the building **300** that there is an event underway at the building **300**. This may serve useful to personnel (e.g. law enforcement) to thereby determine the exact location of the building **300**.

[0213] The chime **302** may be configured to emit any various type of sound in response to any of the previously mentioned components detecting various events. In embodiments, the chime **302** may emit a first sound in response to the doorbell detecting an indication of a presence of a visitor. As well, the chime **302** may emit a second sound in response to the motion detector **218b** detecting motion along the inside portion of the building **300**. Furthermore, if thermometer **512b** detects that the temperature has exceeded a predetermined threshold, the chime **302** may emit a third sound, such as an announcement of the temperature as detected by the thermometer **528b**. Even still, the chime **302** may be configured to emit a fourth sound in response to the humidity sensor **305** detecting that a predetermined humidity has been met.

[0214] As illustrated in FIG. 40, the disclosure also includes methods of identifying visitors and emitting different sounds according to the visitor detected. For example, methods may include recognizing, by a doorbell **202**, a first visitor (at step **1500**). The method may include emitting the first sound from the chime **302** in response to recognizing the first visitor (at step **1502**). As well, the method may include emitting a second sound from the chime in response to not recognizing, by the doorbell **202**, a second visitor (at step **1506**). It should be appreciated that the first sound and the second sounds can be different, or the same.

[0215] In order to detect the visitor, methods may include recognizing the first visitor and/or the second visitor by detecting various traits, such as a physical trait of the respective visitor. Physical traits can include traits such as a fingerprint, gait, body type, height, silhouette traits, silhouette volume, silhouette dimensions, other physical characteristics, and the like. As well, the system **200** may be configured to recognize the first visitor and/or the second

visitor by the doorbell **202** detecting a trait of an electronic device in the possession of the first visitor and/or the second visitor. For example, the system **200** may be configured to detect a first remote computing device **204d** associated with the first visitor and/or a second remote computing device **204e** associated with the second visitor. In response to detecting a visitor by physical traits and/or electronic traits, the chime **302** may emit a sound associated with the particular visitor.

[0216] The following patent applications, which are incorporated by reference herein, describe additional embodiments of recognizing visitors: U.S. Provisional Patent Application No. 62/135,133; filed Mar. 18, 2015; and entitled DOORBELL COMMUNICATION SYSTEMS AND METHODS; U.S. Provisional Patent Application No. 62/016,050; filed Jun. 23, 2014; and entitled IDENTITY VERIFICATION USING A SOCIAL NETWORK; U.S. Provisional Patent Application No. 62/016,053; filed Jun. 23, 2014; and entitled IDENTITY VERIFICATION USING A SOCIAL NETWORK AND A NAME OF A VISITOR; and U.S. Provisional Patent Application No. 62/016,057; filed Jun. 23, 2014; and entitled IDENTITY VERIFICATION OF FREQUENT AND NON-FREQUENT VISITORS.

Wired Communication Embodiments

[0217] In addition to the doorbell system **200** being configured to be electrically and communicatively coupled via any wireless communication standard, the doorbell system **200** may also be electrically and communicatively coupled via any type of wired communication standard (e.g. wires). In embodiments, the wires may be the copper wires of the building **300**.

[0218] As shown in FIG. 36, the doorbell system **200** may be coupled to a doorbell power supply **312** of a building **300**. Accordingly, the doorbell system **200** may include a first wire **304c** that may electrically couple the doorbell **202** to the power supply **312** of the building **300**. As well, the doorbell system **200** may include a second wire **304b** that may electrically and/or communicatively couple the chime **302** to the doorbell **202**. As well, the doorbell system **200** may include a third wire **304a** that may electrically couple the chime **302** to the power supply **312** to form a circuit comprising the first wire **304c**, the doorbell **202**, the second wire **304b**, the chime **302**, the third wire **304a**, and the power supply **312**.

[0219] Because the doorbell **202** may be communicatively coupled to the chime **302** via the second wire **304b**, the chime **302** may be configured to receive a first data file from the doorbell **202** via the second wire **304b**. As well, the doorbell system **200** may include a sound file communication **209** that may be sent from the doorbell **202** to the chime **302** via the second wire **304b**. In some embodiments, the sound file communication **209** may comprise at least one thousand bytes. As well, in embodiments, the sound file communication **209** may comprise less than one thousand bytes. It should also be appreciated that the second wire **304b** may enable two-way communication from the doorbell **202** to the chime **302** and/or from the chime **302** to the doorbell **202**.

[0220] In embodiments, the first data file may comprise commands to perform various operations or put the doorbell system **200** into various settings. For example, the first data file may comprise a command configured to place the chime

302 into silent mode, such that the chime **302** does not emit a sound. Likewise, the first data file may comprise a command configured to adjust a volume setting of the chime **302**. Even still, the first data file may comprise a command configured to adjust a duration of a notification sound emitted by the chime **302**. Generally, it should be appreciated that the first data file may command the chime **302** to perform any such operation.

[0221] Even still, the data file may comprise data gathered by the doorbell system **200**, such as a video recorded by the doorbell **202**. Accordingly, the data file may include information regarding an event that occurred outside the chime **302**, such as the presence of a prowler or an image of an object associated with a motion detected by the system **200**. In this regard, the data file may comprise identifying information regarding the person and/or object detected by the chime **302**. For example, the doorbell **202** and/or chime **302** may detect a person located outside or inside the building **300**. The chime may then receive the data file that comprises the identity of the person as detected by the doorbell **202** and/or chime **302**. As well, the doorbell **202** may wirelessly receive the first data file from the remote computing device **204**. In this manner, the doorbell **202** may receive various files, such as audio, and an image and/or video as recorded by the chime via the first wire. It should also be appreciated that the chime **302** may receive the various files from the doorbell **202** and/or the remote computing device **204**.

[0222] As illustrated in FIG. 41, the disclosure also includes a method of electrically coupling a doorbell system **200** to a doorbell power supply **312** of a building **300**. The method may include coupling a doorbell **202** to a remote chime **302** via a first wire **304c** (at step **1600**). As well, the method may include receiving, by the doorbell **202**, a first data file comprising information (at step **1602**). As further shown in FIG. 41, the method may include sending a second data file comprising the information from the doorbell to the remote chime via the first wire (at step **1604**).

[0223] The information may represent a sound that was unknown to the chime **302** prior to receiving the second data file. In this regard, the method may include emitting the sound from the chime **302** at least partially in response to receiving the second data file. In this regard, the method may include the chime using the second data file to emit a sound. In some embodiments, the second data file may comprise at least one thousand bytes. As well, in embodiments, the second data file may comprise less than one thousand bytes. [0224] As well, the method may include emitting the sound from the chime **302** at least partially in response to the chime **302** receiving a sound emission parameter from the doorbell **202** and/or the remote computing device **204**. For example, the chime **302** may receive a sound emission parameter to only emit the sound between the hours of 9 am and 9 pm. Accordingly, if the system **200** detects a presence of a visitor between 9 am and 9 pm, and in response to the chime **302** having received the data file, the chime **302** may emit a sound in response to the doorbell system **200** having determined that the sound emission parameter has been met.

Chime-Hub Communication Embodiments

[0225] In embodiments, the chime **302** can serve as the communication hub that links the doorbell **202** to the remote computing device **204**, and vice versa. The chime **302** can be configured as the communication hub for a variety of reasons. For example, in certain situations, the doorbell

system can be configured to detect whether the doorbell 202 comprises inadequate wireless performance to communicate with a remote computing device 204 via at least one of the wireless network and a cellular network. Accordingly, when the doorbell 202 receives inadequate wireless performance, the doorbell 202 can thereby communicate with the chime 302, which in turn communicates with the remote computing device 204 to thereby communicatively couple the doorbell 202 to the remote computing device 204.

[0226] Accordingly, and as illustrated in FIG. 42, methods of using the doorbell system can include coupling communicatively the chime 302 to a wireless network of the building 300 (at step 1700). The chime 302 can thereby be communicatively coupled to the doorbell 202 and to a remote computing device 204 (at step 1700).

[0227] In embodiments, the doorbell system can be used to detect an indication of a presence of a visitor and thereby transmit the indication from the doorbell 202 to the remote computing device 204 via the chime 302. The presence of the visitor can be detected via a variety of indications. For example, methods can include detecting, by the doorbell 202, a trigger of a button 212 of the doorbell 202 (at step 1702).

[0228] As further illustrated in FIG. 42, methods can also include sending an alert 232a, such as a visitor alert 232a, from the doorbell 202 to the chime 302 and thereby sending the visitor alert 232a from the chime 302 to the remote computing device 204 (at step 1706). In this manner, the chime 302 can communicatively couple the doorbell 202 to the remote computing device 204. As such, the chime 302 can serve as the hub that communicatively couples the doorbell 202 to the remote computing device 204. In some embodiments, the visitor alert 232a, 232b can be transmitted via the data file 213, first data file 213b, second data file 213a, and/or the data file 211.

[0229] Accordingly, the visitor alert 232a can be sent from the doorbell 202 to the chime 302 and/or the remote computing device 204 by a variety of methods. For example, in some embodiments, the doorbell 202 can be communicatively coupled to the chime 302 via a wire, a wireless network of the building 300, and/or a cellular network. As well, the chime 302 can be communicatively coupled to the remote computing device 204 via the wireless network of the building 300 and/or a cellular network. Methods can thereby include sending the visitor alert 232a from the doorbell 202 to the chime 302 via any combination of transmission systems including the wire, wireless network of the building 300, and/or cellular network (at step 1708). As well, methods can include sending the visitor alert 232a from the chime 302 to the remote computing device 204 via any combination including the wireless network of the building 300 and/or cellular network (at step 1708).

[0230] In some situations, the doorbell 202 may receive a wireless signal, but the wireless signal may be inadequate to transmit specific communications from the doorbell 202 to the remote computing device 204. In these situations, the chime 302 may serve as the communication hub between the doorbell 202 and the remote computing device 204. Accordingly, methods may include sending the visitor alert 232a from the chime 302 to the remote computing device 204 in response to the doorbell system detecting that the doorbell 202 comprises inadequate wireless performance to send the visitor alert 232a to the remote computing device 204 via at least one of the wireless network and a cellular network (at

step 1710). Described differently, some methods can include sending the visitor alert 232a from the chime 302 to the remote computing device 204 in response to the doorbell system detecting that a wireless signal of the doorbell 202 is below a threshold (at step 1712).

[0231] The doorbell 202, remote computing device 204, and the chime 302 may be located in different locations with respect to each other. For example, the doorbell 202 may be located outside of the building 300, the chime 302 may be located inside the building 300, and the remote computing device 204 can be remotely located with respect to the building 300. As illustrated in FIG. 43, methods may include sending the visitor alert 232a from the doorbell 202 to the chime 302 while the doorbell 202 is located outside the building 300 and while the chime 302 is located inside the building 300 (at step 1800). As well, methods may include sending the visitor alert 232a from the chime 302 to the remote computing device 204 that may be located inside or outside of the building 300.

[0232] The visitor alert 232a can take various forms that alert a user that a visitor is present at the doorbell 202 or that a visitor has left a message for the user via the doorbell 202. In this regard, the visitor alert 232a can comprise a video, an image, a sound, a text message, an email, a phone call, and the like. With reference to FIG. 42, methods can include capturing the video and/or image via a camera assembly 208 of the doorbell 202 (at step 1704). As well, in embodiments where the visitor alert 232a comprises a sound, methods can include recording the sound with a microphone 484 of the doorbell 202. Methods can even include the visitor making a phone call through the doorbell 202 to the remote computing device 204, whereby the chime 302 communicatively couples the doorbell 202 to the remote computing device 204 to enable the phone call.

[0233] Upon the doorbell 202 capturing video, images, sounds, and the like, the doorbell system can thereby include various communications between the doorbell 202 and the chime 302, and between the chime 302 and the remote computing device 204. For example, the doorbell system can include a first communication from the doorbell 202 to the chime 302. The first communication can include a video and/or image taken by a camera 208 of the doorbell 202. Accordingly, the doorbell system can include a second communication from the chime 302 to the remote computing device 204. The second communication can also comprise the video.

[0234] Even still, the chime 302 can be communicatively coupled via the wireless network and/or cellular network to other peripheral devices, such as a door lock (e.g. a smart door lock) (at step 1802), a remote sensor (e.g. a fire alarm, a smoke alarm, a carbon monoxide detector, and a burglar alarm) (at step 1804), and the like. In this regard, the chime 302 can serve as the communication hub, not only between the doorbell 202 and the remote computing device 204, but also between the doorbell 202, the remote computing device 204, the door lock, the remote sensor, and any other peripheral device.

[0235] By configuring the chime 302 as the communication hub between such devices, the chime 302 may be used to transmit and communicate messages and instructions between devices. For example, a user may enter an instruction on a remote computing device 204 to lock a front door lock. The instruction may then be sent from the remote computing device 204 to the chime 302 whereby the chime

302 sends the instruction to the front door lock to move to a locked position. In response, the front door lock may lock the front door.

[0236] In another example, the chime **302** may detect an indication of an adverse event and/or receive the indication of the adverse event from the remote sensor. The adverse event can comprise various events, such as a motion, breaking glass, fire, a fire alarm sound, smoke, and the like. Accordingly, methods can include directly detecting an adverse event with the chime **302** (at step **1806**), such as detecting the sound of glass breaking via a microphone of the chime **302**. As well, methods can include the chime **302** receiving an indication of the adverse event from the remote sensor that is communicatively coupled to the chime **302**, whereby the remote sensor is configured to detect adverse events. As illustrated in FIG. **43**, methods can include sending an alert **232b** of the adverse event (e.g. an adverse event alert **232b**) to the remote computing device **204** in response to detecting the adverse event (at step **1808**). As should be appreciated, the adverse event alert **232b** can comprise a notification of the adverse event to thereby put the user on notice of the adverse event.

[0237] The chime **302** can be configured to communicate with other devices, such as the remote computing device **204**, remote sensors, and the like, via any wireless personal area network. For example, the chime **302** can be configured to communicate via Bluetooth, Bluetooth low energy, and the like. In this manner the chime **302** can communicate with Bluetooth low energy tags.

[0238] In various embodiments, the chime **302** may include a light configurable to illuminate an area or provide ambient lighting for comfort, such as a nightlight. The light may comprise the diagnostic light **216**, the power indicator light **220**, and/or any other light electrically coupled to the chime **302**. As well, the light may be activated by various means, such as in response to an audible message from a user (e.g. “Max, turn on the light”). Even still, the light may be configurable to activate in response to external conditions, such as darkness of an adjacent area, much like a nightlight.

[0239] Referring now to FIG. **36**, a system can include a remote sensor **418** that is located outside of the doorbell **202**, outside of the chime **302**, and outside of the remote computing device **204**. The remote sensor **418** can be located inside or outside of the building **300**. The remote sensor **418** can include a speaker **488c** that can emit sounds **236** (e.g., alarm sounds). A microphone **484b** (shown in FIG. **31**) of the chime **302** can detect (e.g., “hear”) the sounds **236**. Then, the chime **302** can send a notification to the remote computing device **204** in response to detecting the sounds **236** and/or in response to receiving a wireless communication **230** from the remote sensor **418**.

[0240] Remote sensors **418** can include a fire alarm, a smoke alarm, a carbon monoxide detector, a motion sensor, a glass-break sensor, and a burglar alarm. For example, the chime **302** can listen for a smoke alarm. Then, the chime **302** can send a notification to the remote computing device **204** in response to hearing the alarm sound of the smoke alarm.

[0241] Some embodiments include sending a second alert from the chime **302** to the remote computing device **204** in response to receiving, by the chime **302**, a communication from the remote sensor **418**. Several embodiments include coupling communicatively the chime **302** to a remote sensor **418**. The remote sensor **418** can comprise at least one of a

fire detector, a smoke detector, and a carbon monoxide detector. Embodiments can also include sending a second alert from the chime **302** to the remote computing device **204** in response to receiving, by the chime **302**, a communication from the remote sensor **418**.

[0242] Several embodiments comprise detecting, by a microphone **484b** (shown in FIG. **31**) of the chime **302**, an alarm sound emitted by a remote sensor **418**, and then sending a second alert from the chime **302** to the remote computing device **204** in response to detecting the alarm sound. Some embodiments include detecting, by a microphone **484b** of the chime **302**, an alarm sound emitted by a remote smoke detector (e.g., **418**), and then sending a second alert from the chime **302** to the remote computing device **204** in response to detecting the alarm sound. Several embodiments include detecting, by a microphone **484b** of the chime **302**, an alarm sound emitted by a remote motion sensor device (e.g., **418**), and then sending a second alert from the chime **302** to the remote computing device **204** in response to detecting the alarm sound.

[0243] Burglars often break glass windows and glass doors to enter homes and other buildings. Some embodiments include detecting, by a microphone **484b** of the chime **302**, glass breaking, and then sending a second alert from the chime **302** to the remote computing device **204** in response to detecting the glass breaking.

[0244] Some systems include a remote sensor **418** having at least one of a fire detector, a smoke detector, a carbon monoxide detector, a motion detector, and a glass-break detector. The remote sensor **418** can be communicatively coupled to the chime **302** (e.g., via wireless communication **230**). Systems can include a third communication from the remote sensor **418** to the chime **302**.

[0245] Several systems include a chime **302** that has a microphone **484b** (shown in FIG. **31**). Systems can also include a remote sensor **418**, an alarm sound **236** emitted by the remote sensor **418**, and a third communication sent from the chime **302** to the remote computing device **204** in response to the microphone **484b** of the chime **302** detecting the alarm sound **236**.

[0246] FIG. **36** illustrates a doorbell system configured to be coupled to a building **300** having a wireless network **308**. The doorbell system can include a doorbell **202** having a button **212** configured to be pressed by a visitor to notify occupants of the building **300**. The doorbell **202** can comprise a first wireless communication system **503** and a second wireless communication system **507** (as shown in FIG. **44**). The first wireless communication system **503** can consume less energy per unit of operating time than the second wireless communication system **507**.

[0247] The doorbell system also includes a remote communication device (e.g., the chime **302**) coupled to a power outlet **309** (as shown in FIG. **33**) of the building **300** and located remotely relative to the doorbell **202**. The remote communication device **302** comprises a speaker **488b** configured to emit a sound in response to the visitor pressing the button **212**. The remote communication device **302** comprises a third wireless communication system **509** and a fourth wireless communication system **511** (as shown in FIG. **44**). The third wireless communication system **509** can consume less energy per unit of operating time than the fourth wireless communication system **511**.

[0248] In some embodiments, the second **507** and fourth **511** wireless communication systems can be Wi-Fi systems.

The first **503** and third **509** wireless communication systems can be Bluetooth, Bluetooth Low Energy, Thread, ZigBee, and or any other suitable system. An advantage of some embodiments is that more power-hungry communication systems are used less often than more energy efficient systems. This can be especially helpful when the doorbell **202** runs on battery power.

[0249] As shown in FIG. 44, the remote communication system **302** is communicatively coupled with the wireless network **308** via the fourth wireless communication system **511**, and is communicatively coupled with the first wireless communication system **503** of the doorbell **202** via the third wireless communication system **509**. The doorbell **202** is communicatively coupled with the wireless network **308** via the second wireless communication system **507** in response to receiving a communication from the remote communication device **302** via the first wireless communication system **503**.

[0250] FIG. 45 illustrates how a remote computing device **204** can send a communication to a wireless network **308** of a building, which can then send a wireless communication to the fourth wireless communication system **511**. The remote communication device **302** can then use its third wireless communication system **509** to send a communication to the first wireless communication system **503** of the doorbell. The doorbell **202** can then use its second wireless communication system **507** to send a communication to the wireless network **308** and/or to the remote computing device **204**.

[0251] The communication can be a doorbell setting parameter that a user “sets” by selecting an option on an “app” run by the remote computing device **204**. The doorbell **202** can update a doorbell setting (e.g., power management settings, camera settings, notification preferences, doorbell light settings) in response to receiving the doorbell setting parameter.

[0252] In some embodiments, the doorbell **202** “wakes up” in response to receiving a communication from the remote communication device **302**. The remote communication device **302** can send the doorbell **202** a wake up command in response to receiving a wake up command from the remote computing device **204**. The doorbell **202** can “wake up” by turning on the camera, starting to record a video, and/or beginning wireless communication with the wireless network **308**.

[0253] FIG. 46 illustrates a front view of another doorbell **202m**. This doorbell **202m** includes a battery **462**. The battery **462** can provide electrical power such that the doorbell **202m** does not need to be connected to a building’s electrical system to receive electricity. This doorbell **202m** can include any of the items described in the context of other doorbells **202** illustrated herein or incorporated by reference.

Transceiver Embodiments

[0254] A transceiver is a device that can both transmit and receive data. These devices are used to send or receive a variety of wireless signals, or transmissions, over radio waves. Some examples of technologies that use wireless signals include AM or FM radio, cellular phones, Wi-Fi, Bluetooth devices, satellite signals, and two-way radios. In some embodiments, transceivers can be used in doorbell systems to send and receive wireless communications to and/or from a user. This can allow a user to view and/or communicate with a visitor who is approaching a doorbell

system at a location, such as their home or business. The user can then communicate with a visitor through a remote computing device, even though the user may be at a different location than the visitor. Remote computing devices can include smartphones, tablets, computers, or other devices that can connect to a wireless network, such as the internet and cellular networks.

[0255] Referring to FIG. 29, in some embodiments, a doorbell system **200** can include a doorbell **202** that can comprise a doorbell housing **560**, a visitor detection system **528**, a first low-energy transceiver **550**, and a first high-energy transceiver **552**. The visitor detection system **528** can be coupled to the doorbell housing **560** and can include at least one of a camera **208** and a motion detector **218**. Both the first low-energy transceiver **550** and the first high-energy transceiver **552** can be coupled to the doorbell housing **560** and be configurable to transmit data **213**, as shown in FIG. 47.

[0256] In several embodiments, the doorbell system **200** can comprise a doorbell **202** and a chime **302**. Referring to FIG. 31, The chime **302** can comprise a chime housing **558**, a second low-energy transceiver **554**, and a second high-energy transceiver **556**. The second low-energy transceiver **554** and the second high-energy transceiver **556** can be coupled to the chime housing **558** and can be configured to transmit data **213** to the first low-energy transceiver **550** and the first high-energy transceiver **552**, as illustrated in FIG. 47.

[0257] As illustrated in FIG. 47, the doorbell system **201** can comprise a doorbell **202**, a chime **302**, and a Wi-Fi communication hub **330**. The Wi-Fi communication hub **330** can be coupled to at least one of the doorbell **202** and the chime **302**. In some embodiments the Wi-Fi communication hub **330** can comprise a Wi-Fi router **328**.

[0258] In several embodiments of the doorbell system **200**, the first low-energy transceiver **550** can comprise a first Bluetooth low-energy transceiver **550a**, as illustrated in FIG. 31. The second low-energy transceiver **554** can comprise a second Bluetooth low-energy transceiver **554a**. The first high-energy transceiver **552** can comprise a first Wi-Fi transceiver and the second high-energy transceiver **556** can comprise a second Wi-Fi transceiver **556a**.

[0259] In some embodiments, a battery **462** located within the doorbell housing **560** can power the doorbell **202**, as shown in FIG. 29. In several embodiments with a battery **462**, it may be beneficial to conserve power. This can ensure that the battery **462** is not drained and the doorbell **202** can operate for an extended period of time. In these embodiments, Bluetooth low energy, or BLE, transceivers can lend themselves well to energy preservation and may allow a longer operation period before it is necessary to recharge the battery. Operations that require low-energy can use BLE transceivers to complete tasks, while doorbell functions that may require a high-energy can utilize Wi-Fi signals. For example, if a user would like to upload a new chime sound or change the LED color on the doorbell, the doorbell system can assign BLE transceivers to complete these tasks. For functions that require high-energy, such as streaming video from the doorbell camera to a computing device, a high-energy Wi-Fi transceiver can be employed.

[0260] Referring to FIG. 47, in several embodiments, the doorbell system **200** can further comprise a remote computing device **204**. This remote computing device **204** can be

communicatively coupled to at least one of the doorbell 202, the chime 302, and the Wi-Fi communication hub 330.

[0261] In some embodiments, at least one of the first low-energy transceiver 550 and the second low-energy transceiver 554 can be configured to activate in response to a first request 211a from the remote computing device 204. The first high-energy transceiver 552 and the second high-energy transceiver 556 can be configured to activate in response to a second request 211b from the remote computing device 204. The different doorbell system 201 functions can be assigned to different doorbell 202 tasks. For example, doorbell 202 functions that require a high-energy signal can be assigned to a Wi-Fi transceiver, while tasks requiring or a low-energy signal would use a BLE transceiver.

[0262] In some embodiments, the first high-energy transceiver 552 and the second high-energy transceiver 556 can be configured to activate in response to a second event 424b detected by the visitor detection system 528. For example, the high-energy Wi-Fi transceivers can activate in response to a motion at the door. On the other hand, in some embodiments where the doorbell 202 can comprise an illuminated light source, at least one of the first low-energy transceiver 550 and the second low-energy transceiver 554 can be configured to activate in response to a request 211 from the remote computing device 204 to change a color of the light. For example, a low-energy BLE transceiver may activate if the user requests a color change of the doorbell light.

[0263] In several embodiments, at least one of the first high-energy transceiver 552 and the second high-energy transceiver 556 can be configured to activate in response to the doorbell 202 detecting a presence of a visitor 580 (shown in FIG. 7). In this case, a Wi-Fi transceiver can activate to complete the doorbell 202 function.

[0264] Referring to FIG. 29, in some embodiments, a doorbell system 200 can comprise a doorbell 202 having a visitor detection system 528. This doorbell detection system 528 can comprise of at least one of a camera 208, motion detector 218 (shown in FIG. 3), or microphone 484. In several embodiments with a first low-energy transceiver 550 and a first high-energy transceiver 552, the doorbell system 200 can comprise a chime 302 that can be communicatively coupled to the doorbell 202. As illustrated in FIG. 31, the chime 301 can have a second low-energy transceiver 554 and a second high-energy transceiver 556. FIG. 47 illustrates a method for activating the transceivers that can comprise activating at least one of the first low-energy transceiver 550 and the second low-energy transceiver 554 in response to a first event 424a. Then, in response to a second event 424b, at least one of the first high-energy transceiver 552 and the second high-energy transceiver 556 can be activated. In other words, different events 424 can activate different transceivers. Events 424 may include a variety of wireless communications or alarms. These wireless communications can include, but are not limited to, the detection of a visitor 580, communication with a visitor 580, and requests 211 made by the user 336 to the doorbell system 200 from a remote computing device 204. Events 424 may also include requests 211 to change the chime sound and doorbell button light color, or alarms, such as fire or security alarms.

[0265] In several embodiments, the doorbell system 200 can further comprise a remote computing device 204 such as a computer or smartphone. The remote computing device 204 can be communicatively coupled to at least one of the

doorbell 202 and the chime 302. The first event 424a can comprise a first request 211a from the remote computing device 204, and the second event 424b can comprise a second request 211b from the remote computing device 204.

[0266] FIG. 47 illustrates a methods of wireless communications in response to events for several embodiments of doorbell systems. In some embodiments, the activation of the first low-energy transceiver 550 and the second low-energy transceiver 554, in response to the first event 424a, can deactivate the first high-energy transceiver 552 and the second high-energy transceiver 556. The high-energy transceiver can be deactivated when at least one of the low-energy transceivers is activated.

[0267] In several embodiments, the low-energy transceivers can be deactivated when at least one of the high-energy transceivers is activated. The method of using the doorbell 202 can entail activating both the first high-energy transceiver 552 and the second high-energy transceiver 556 in response to the second event 424a. The first low-energy transceiver 550 and the second low-energy transceiver 554 can be deactivated in response to activating both the first high-energy transceiver 552 and the second high-energy transceiver 556.

[0268] Referring to FIG. 47, in some embodiments, the method of using a doorbell system 200 can comprise a doorbell 202 having a visitor detection system 528, a first low-energy transceiver 550, and a first high-energy transceiver 552. The doorbell system 200 can comprise a chime 302 communicatively coupled to the doorbell 202. The chime 302 can have a second low-energy transceiver 554 and a second high-energy transceiver 556. The method for using the doorbell system 200 can comprise activating the first low-energy transceiver 550, activating the second low-energy transceiver 554, and transmitting data 213 between the first low-energy transceiver 550 and the second low-energy transceiver 554. This method can thereby enable communication between the doorbell 202 and the chime 302.

[0269] In several embodiments, the method for operating the doorbell 202 can further comprise deactivating the first high-energy transceiver 552 in response to activating the first low-energy transceiver 550, and deactivating the second high-energy transceiver 556 in response to activating the second low-energy transceiver 554. In other words, high-energy transceivers can be deactivated in response to activating the low-energy transceivers.

[0270] In some embodiments, the method for operating the doorbell system 200 can further comprise activating the first low-energy transceiver 550 in response to the doorbell 202 either the sending or receiving a transmission 231 that is less than a predetermined transmission threshold, or both. The second low-energy transceiver 554 can be activated in response to the chime 302 performing at least one of sending the first transmission 233 that is less than the predetermined transmission threshold and receiving the second transmission 234 that is less than the predetermined transmission threshold.

[0271] Referring to FIG. 47, in some embodiments the doorbell system 200 can comprise a doorbell 202. The doorbell 202 can have a camera 208, a motion detector 218, a first low-energy transceiver 550, and a first high-energy transceiver 552. The doorbell system 200 can comprise a chime 302 communicatively coupled to the doorbell 202. The chime 302 can have a second low-energy transceiver

554 and a second high-energy transceiver 556. As illustrated in FIG. 47, the method for operating a doorbell system 202 can comprise activating the first high-energy transceiver 552, activating the second high-energy transceiver 556, and transmitting data 213 between the first high-energy transceiver 552 and the second high-energy transceiver 556. This transmission of data 213 can thereby enable communication between the doorbell 202 and the chime 302.

[0272] In several embodiments, operating the doorbell system 200 can include deactivating the first low-energy transceiver 550 in response to activating the first high-energy transceiver 552 and deactivating the second low-energy transceiver 554 in response to activating the second high-energy transceiver 556. Low energy transceivers can be deactivated when high energy transceivers are activated.

[0273] In some embodiments, operating the doorbell system 200 can consist of activating the first high-energy transceiver 552 when the doorbell 202 either sends or receives a transmission 231 that is greater than a predetermined transmission threshold and activates the second high-energy transceiver 556 in response to the chime 302 either sending or receiving the first transmission 233 that is greater than the predetermined transmission threshold.

Interpretation

[0274] None of the steps described herein is essential or indispensable. Any of the steps can be adjusted or modified. Other or additional steps can be used. Any portion of any of the steps, processes, structures, and/or devices disclosed or illustrated in one embodiment, flowchart, or example in this specification can be combined or used with or instead of any other portion of any of the steps, processes, structures, and/or devices disclosed or illustrated in a different embodiment, flowchart, or example. The embodiments and examples provided herein are not intended to be discrete and separate from each other.

[0275] The section headings and subheadings provided herein are nonlimiting. The section headings and subheadings do not represent or limit the full scope of the embodiments described in the sections to which the headings and subheadings pertain. For example, a section titled "Topic 1" may include embodiments that do not pertain to Topic 1 and embodiments described in other sections may apply to and be combined with embodiments described within the "Topic 1" section.

[0276] Some of the devices, systems, embodiments, and processes use computers. Each of the routines, processes, methods, and algorithms described in the preceding sections may be embodied in, and fully or partially automated by, code modules executed by one or more computers, computer processors, or machines configured to execute computer instructions. The code modules may be stored on any type of non-transitory computer-readable storage medium or tangible computer storage device, such as hard drives, solid state memory, flash memory, optical disc, and/or the like. The processes and algorithms may be implemented partially or wholly in application-specific circuitry. The results of the disclosed processes and process steps may be stored, persistently or otherwise, in any type of non-transitory computer storage such as, e.g., volatile or non-volatile storage.

[0277] The various features and processes described above may be used independently of one another, or may be combined in various ways. All possible combinations and subcombinations are intended to fall within the scope of this

disclosure. In addition, certain method, event, state, or process blocks may be omitted in some implementations. The methods, steps, and processes described herein are also not limited to any particular sequence, and the blocks, steps, or states relating thereto can be performed in other sequences that are appropriate. For example, described tasks or events may be performed in an order other than the order specifically disclosed. Multiple steps may be combined in a single block or state. The example tasks or events may be performed in serial, in parallel, or in some other manner. Tasks or events may be added to or removed from the disclosed example embodiments. The example systems and components described herein may be configured differently than described. For example, elements may be added to, removed from, or rearranged compared to the disclosed example embodiments.

[0278] Conditional language used herein, such as, among others, "can," "could," "might," "may," "e.g.," and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment. The terms "comprising," "including," "having," and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations and so forth. Also, the term "or" is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term "or" means one, some, or all of the elements in the list. Conjunctive language such as the phrase "at least one of X, Y, and Z," unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain embodiments require at least one of X, at least one of Y, and at least one of Z to each be present.

[0279] The term "and/or" means that "and" applies to some embodiments and "or" applies to some embodiments. Thus, A, B, and/or C can be replaced with A, B, and C written in one sentence and A, B, or C written in another sentence. A, B, and/or C means that some embodiments can include A and B, some embodiments can include A and C, some embodiments can include B and C, some embodiments can only include A, some embodiments can include only B, some embodiments can include only C, and some embodiments include A, B, and C. The term "and/or" is used to avoid unnecessary redundancy.

[0280] While certain example embodiments have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions disclosed herein. Thus, nothing in the foregoing description is intended to imply that any particular feature, characteristic, step, module, or block is necessary or indispensable. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions, and

changes in the form of the methods and systems described herein may be made without departing from the spirit of the inventions disclosed herein.

The following is claimed:

1. A doorbell system comprising a doorbell, wherein the doorbell comprises:

- a doorbell housing;
- a visitor detection system coupled to the doorbell housing, the visitor detection system including at least one of a camera and a motion detector;
- a first low-energy transceiver coupled to the doorbell housing; and
- a first high-energy transceiver coupled to the doorbell housing, wherein the first low-energy transceiver and the first high-energy transceiver are configurable to transmit data.

2. The doorbell system of claim 1, further comprising a chime communicatively coupled to the doorbell, the chime comprising:

- a chime housing;
- a second low-energy transceiver coupled to the chime housing; and
- a second high-energy transceiver coupled to the chime housing, wherein the second low-energy transceiver and the second high-energy transceiver are configurable to transmit data to the first low-energy transceiver and the first high-energy transceiver.

3. The doorbell system of claim 2, further comprising a Wi-Fi communication hub communicatively coupled to at least one of the doorbell and the chime.

4. The doorbell system of claim 3, wherein the Wi-Fi communication hub comprises a Wi-Fi router.

5. The doorbell system of claim 3, wherein the first low-energy transceiver comprises a first Bluetooth low-energy transceiver and the second low-energy transceiver comprises a second Bluetooth low-energy transceiver, and the first high-energy transceiver comprises a first Wi-Fi transceiver and the second high-energy transceiver comprises a second Wi-Fi transceiver.

6. The doorbell system of claim 5, wherein the doorbell is powered by a battery located within the doorbell housing.

7. The doorbell system of claim 3, further comprising a remote computing device communicatively coupled to at least one of the doorbell, the chime, and the Wi-Fi communication hub.

8. The doorbell system of claim 7, wherein at least one of the first low-energy transceiver and the second low-energy transceiver are configured to activate in response to a first request from the remote computing device, and the first high-energy transceiver and the second high-energy transceiver are configured to activate in response to a second request from the remote computing device.

9. The doorbell system of claim 3, wherein the first high-energy transceiver and the second high-energy transceiver are configured to activate in response to a second event detected by the visitor detection system.

10. The doorbell system of claim 3, wherein the doorbell comprises a light source that illuminates light, and wherein at least one of the first low-energy transceiver and the second low-energy transceiver are configured to activate in response to a request from the remote computing device to change a color of the light.

11. The doorbell system of claim 3, wherein at least one of the first high-energy transceiver and the second high-

energy transceiver are configured to activate in response to the doorbell detecting a presence of a visitor.

12. A method of using a doorbell system comprising a doorbell having a visitor detection system, a first low-energy transceiver, and a first high-energy transceiver, the doorbell system comprising a chime communicatively coupled to the doorbell, the chime having a second low-energy transceiver and a second high-energy transceiver, the method comprising:

- activating at least one of the first low-energy transceiver and the second low-energy transceiver in response to a first event; and
- activating at least one of the first high-energy transceiver and the second high-energy transceiver in response to a second event.

13. The method of claim 12, wherein the doorbell system further comprises a remote computing device communicatively coupled to at least one of the doorbell and the chime, and wherein the first event comprises a first request from the remote computing device and the second event comprises a second request from the remote computing device.

14. The method of claim 12, further comprising:

- activating both the first low-energy transceiver and the second low-energy transceiver in response to the first event; and
- deactivating the first high-energy transceiver and the second high-energy transceiver in response to activating both the first low-energy transceiver and the second low-energy transceiver.

15. The method of claim 12, further comprising:

- activating both the first high-energy transceiver and the second high-energy transceiver in response to the second event; and
- deactivating the first low-energy transceiver and the second low-energy transceiver in response to activating both the first high-energy transceiver and the second high-energy transceiver.

16. A method of using a doorbell system comprising a doorbell having a visitor detection system, a first low-energy transceiver, and a first high-energy transceiver, the doorbell system comprising a chime communicatively coupled to the doorbell, the chime having a second low-energy transceiver and a second high-energy transceiver, the method comprising:

- activating the first low-energy transceiver;
- activating the second low-energy transceiver; and
- transmitting data between the first low-energy transceiver and the second low-energy transceiver to thereby enable communication between the doorbell and the chime.

17. The method of claim 16, further comprising:

- deactivating the first high-energy transceiver in response to activating the first low-energy transceiver; and
- deactivating the second high-energy transceiver in response to activating the second low-energy transceiver.

18. The method of claim 17, further comprising:

- activating the first low-energy transceiver in response to the doorbell performing at least one of sending a first transmission that is less than a predetermined transmission threshold and receiving a second transmission that is less than the predetermined transmission threshold; and

activating the second low-energy transceiver in response to the chime performing at least one of sending the first transmission that is less than the predetermined transmission threshold and receiving the second transmission that is less than the predetermined transmission threshold.

19. A method of using a doorbell system comprising a doorbell having a camera, a motion detector, a first low-energy transceiver, and a first high-energy transceiver, the doorbell system comprising a chime communicatively coupled to the doorbell, the chime having a second low-energy transceiver and a second high-energy transceiver, the method comprising:

activating the first high-energy transceiver;
activating the second high-energy transceiver; and
transmitting data between the first high-energy transceiver and the second high-energy transceiver to thereby enable communication between the doorbell and the chime.

20. The method of claim **19**, further comprising:
deactivating the first low-energy transceiver in response to activating the first high-energy transceiver; and
deactivating the second low-energy transceiver in response to activating the second high-energy transceiver.

21. The method of claim **20**, further comprising:
activating the first high-energy transceiver in response to the doorbell performing at least one of sending a first transmission that is greater than a predetermined transmission threshold and receiving a second transmission that is greater than the predetermined transmission threshold; and

activating the second high-energy transceiver in response to the chime performing at least one of sending the first transmission that is greater than the predetermined transmission threshold and receiving the second transmission that is greater than the predetermined transmission threshold.

* * * * *