

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 February 2004 (12.02.2004)

PCT

(10) International Publication Number  
WO 2004/012618 A1

(51) International Patent Classification<sup>7</sup>: A61B 008/06

(21) International Application Number:  
PCT/AU2003/000946

(22) International Filing Date: 25 July 2003 (25.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2002950611 6 August 2002 (06.08.2002) AU

(71) Applicant (for all designated States except US): USCOM  
PTY LTD [AU/AU]; 323 Old Coast Road, Korora, NSW  
2450 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): PHILLIPS, Robert,  
Allan [AU/AU]; P O Box J241, Coffs Harbour, NSW 2450  
(AU).

(74) Agent: BALDWIN SHELSTON WATERS; 60 Margaret  
Street, Sydney, NSW 2000 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted  
a patent (Rule 4.17(ii)) for the following designations AE,  
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES,  
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH,

[Continued on next page]

(54) Title: BLOOD FLOW ANALYSIS SYSTEM



(57) Abstract: A portable apparatus for conveying blood flow parameters to a user, the apparatus comprising: a transducer device for providing for Doppler monitoring of flows within a patient; a processing unit interconnected to the transducer unit and adapted to extract a blood flow signal from the operation of the transducer and process the blood flow signal so as to produce a video blood flow signal and an audio blood flow signal; a display unit interconnect to the processing unit for visualising the video blood flow signal; and at least one audio emission devices interconnected to the processing unit for emission of the audio blood flow signal to the ears of the user.

WO 2004/012618 A1



PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

TITLE: BLOOD FLOW ANALYSIS SYSTEM

### **Field of the Invention**

The present invention relates to the field of Doppler flow measurements of blood flow and, in particular, discloses a hand-held device, hereinafter called an  
5 “Echoscope” having functionality similar to that of an augmented stethoscope but further including visualisation and audiospatialisation capabilities.

### **Background of the Invention**

The operational characteristics of blood flow through the body has been an important parameter in medical studies for many years. Traditionally, stethoscopes  
10 have been used by medical professionals to listen to blood flows within the body in order to determine irregular characteristics. Further, the taking of blood pressure has traditionally relied upon monitoring blood flow utilising stethoscope devices to listen to the onset of flows.

Unfortunately, standard stethoscope techniques rely on simple mechanical  
15 transmission of audio information to the ears of a user which provide only limited information to the medical specialist. It would be desirable to provide for a more informative system of providing information on blood flows within the body to the medical specialist.

### **Summary of the Invention**

20 It is an object of the present invention to provide for an improved form of diagnostic monitoring of blood flows within the body including cardiac blood flow measurement.

- 2 -

In accordance with a first aspect of the present invention there is provided a portable apparatus for conveying blood flow parameters to a user, the apparatus comprising: a transducer device for providing for Doppler monitoring of flows within a patient; a processing unit interconnected to the transducer unit and adapted to extract  
5 a blood flow signal from the operation of the transducer and process the blood flow signal so as to produce a video blood flow signal and an audio blood flow signal; a display unit interconnect to the processing unit for visualising the video blood flow signal; and at least one audio emission devices interconnected to the processing unit for emission of the audio blood flow signal to the ears of the user.

10 Preferably, the processing unit and the display unit are packaged as a handheld device and the processing unit performs audio spatialisation of the audio blood flow signal and the number of audio emission devices is at least two. Preferably, the audio spatialisation includes a spatial separation of information in accordance with the depth from a transducer element.

15 In accordance with a first aspect of the present invention there is provided a method of transmission of information of blood flow characteristics within a patient, the method comprising the steps of (a) providing a Doppler flow signal indicative of blood flows within the body, (b) visualising the Doppler flow signal on a display device; and (c) simultaneously providing an audio output to the listener of the Doppler  
20 blood flow signal.

Preferably the step (c) includes providing an apparent spatialisation of the audio output to the listener.

The method can also including simultaneously recording the Doppler flow signal and related information for later analysis.

### **Brief Description of the Drawings**

The preferred and other embodiments of the present invention will now be described with reference to the accompanying drawings in which:

Fig. 1 illustrates an operational environment of the preferred embodiment;

5 Fig. 2 illustrates the processing and display unit of the preferred embodiment;

Fig. 3 illustrates a transducer device suitable for utilisation with the preferred embodiment;

Fig. 4 illustrates schematically a functional block diagram of the hardware portions of the preferred embodiment; and

10 Fig. 5 illustrates a functional block diagram of the software processing of the preferred embodiment.

### **Description of Preferred and Other Embodiments**

In the preferred embodiment, there is provided a stethoscope substitute, hereinafter called an "Echoscope". The Echoscope utilises a continuous wave  
15 Doppler beam to measure and image blood flows within the body. Further, the Echoscope also includes auralisation of the resultant measurements so as to provide for advanced stethoscope-type activities. Preferably, spatialisation of the audio is also provided.

Turning now to Fig. 1, there is illustrated an example of the operational  
20 environment of the preferred embodiment. In this example, a patient 2 is presented in a hospital-type environment. The patient 2 has a number of predetermined monitoring devices e.g. 11, 12 monitoring his physiological condition.

The Echoscope device is designed to be utilised by a physician 6 so as to gain information about the operation of the internal portions of blood flow within the body

- 4 -

of patient 2. The Echoscope device includes an interconnected hand-held transducer 3, a processing and display unit 4 and a set of headphones 5. The Echoscope is designed to utilise continuous wave (CW) Doppler processing techniques so as to process an ultrasound signal emitted by a transducer 3 so as to produce corresponding  
5 blood flow indicator information which is displayed on device 4 and aurally output via headphones 5.

Turning now to Fig. 2, there is illustrated an enlarged view of the processing and display unit 4. The processing and display unit interacts with input/output signals 7 which are transmitted and received from the transducer device. At the output 8, an  
10 audio signal is output to the headphone devices. The arrangement 4 includes a display 5 which displays information relating to the signal received by transducer 7. The display 5 and audio output is influenced by a series of control buttons e.g. 8 which control the information on the display.

The preferred embodiment utilises continuous wave (CW) Doppler to monitor  
15 the blood flow. The CW Doppler is a non-invasive technique in which ultrasonic signals from the transducer element are directed into a blood carrying vessel of a patient. Doppler shifts in the reflected signal provide an indication of the rate of blood flow. The principles of the CW Doppler flow measurement are known. For example, Patent Co-operation Treaty (PCT) Publication No. WO99/66835 entitled "Ultrasonic  
20 Cardiac Output Monitor" describes in more detail an ultrasonic transducer device suitable for measuring blood flow using the CW Doppler method. The contents of the aforementioned specification are hereby included by cross-reference.

Turning now to Fig. 3, there is illustrated an enlarged view of one form of the transducer element 3. The transducer element 3 includes an ultrasonic transducer 15

- 5 -

attached to a positioning device 16 which can be utilised to set the position of the transducer. Between the transducer 15 and a patient's skin 17, is placed a gel coupling layer 18 for coupling the ultrasonic transducer vibrations to the skin 17.

Turning now to Fig. 4, there is illustrated a schematic arrangement of the functional hardware of the processing and display unit 4. The arrangement of Fig. 4 illustrates merely one example hardware structure of the processing and display unit 4 and it will be obvious to those skilled in the field of construction of complex hardware devices that other arrangements are possible. For example, fully custom applications specific integrated circuit (ASIC) technology could be utilised to reduce the number of overall components of the unit 4. In any event, one arrangement can be based around a micro-controller 20 which has overall control of the unit 4. The micro-controller 20 communicates with other devices over a bus 21. Devices attached to the bus include a memory unit 22, a DSP unit 23, A to D and D to A converters 24 and a display driver 25 which interacts with the display 26. The micro-controller 20 is also preferably able to communicate with a series of other devices via an input/output communication port 28. The A to D converters 24 are responsible for controlling the transducer device 3 and headphones 5. The whole system 4 operates under the control of micro-controller 20 which runs programs stored in memory 22 with the DSP 23 performing real time signal processing operations in the normal manner.

Turning now to Fig. 5, there is illustrated the core overall portions of one possible software system of the preferred embodiment. In this arrangement, the signal received from the transducer is extracted 30 and subjected to video and audio enhancement processing 31, 32. The video enhancement can include standard image processing routines to enhance and display the received signal in accordance with

- 6 -

external control settings. The output signal is then processed for display 34 before  
being output 35. The audio signal is enhanced 32 utilising standard techniques such  
as noise cancelling or the like. Optionally, the output audio signal can also be  
spatialised around a listener. The spatialisation process can provide for depth cues of  
5 the audio signal received by the physician. Many different forms of spatialisation can  
be performed from the simple to the complex. In a simple technique, the left and right  
channel outputs can be manipulated in accordance with the depth of the signal  
received so as to produce a panning of the signal from the left ear to the right ear  
depending on the transducer delay monitored. Other methods can include the full  
10 binauralisation of the audio signal so as to spatialise portions of the signal around the  
listener. The binauralisation process is well known to those skilled in the art of audio  
digital signal processing and suitable techniques for spatialisation of the audio around  
listener are disclosed in PCT publication No. WO99/49574 entitled "Audio Signal  
Processing Method and Apparatus", the contents of which are hereby incorporated by  
15 cross-reference.

The audio signal can then be output 38 to the headphones.

Many other refinements are possible. For example, the information or signal  
parameters recorded by the physician can be stored for later download in addition to  
the case notes associated with the case. A microphone 40 can be optionally provided  
20 for recording and storing the physicians notes. Further, continual audio and video  
enhancements can be made and up-loaded to the system. Also, depending on the  
mode settings of the device, the audio and visual signal processing can be undertaken  
to highlight certain detected anomalous aspects of the received signals. For example, a

- 7 -

speed control could be provided so that particular portions of the audio signal are played at half speed etcetera.

Further modifications, obvious to those skilled in the art of advanced hardware/software design and medical instrumentation can be made thereto without  
5 departing from the scope of the present invention.

- 8 -

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. A portable apparatus for conveying blood flow parameters to a user, the apparatus comprising:
  - a transducer device for providing for a Doppler monitoring of flows within a  
5 patient;
  - a processing unit interconnected to said transducer unit and adapted to extract a blood flow signal from the operation of said transducer and process said blood flow signal so as to produce a video blood flow signal and an audio blood flow signal;
  - a display unit interconnect to said processing unit for visualising the video blood  
10 flow signal; and
  - at least one audio emission device interconnected to said processing unit for emission of an audible form of said audio blood flow signal to the ears of said user.
2. An apparatus as claimed in claim 1 wherein said processing unit and said display unit are packaged as a handheld device.
- 15 3. An apparatus as claimed in any previous claim wherein said processing unit performs audio spatialisation of said audio blood flow signal and the number of audio emission devices is at least two.
4. An apparatus as claimed in claim 3 wherein said audio spatialisation includes a spatial separation of information in accordance with the depth of the received signal  
20 from a transducer element.
5. An apparatus as claimed in any previous claim further comprising:
  - storage means for storing information associated with subjects on who the device is used.
6. An apparatus as claimed in claim 5 further comprising:

- 9 -

a microphone for use in recording audio commentary by the user for storage in said storage means.


7. A method of transmission of information of blood flow characteristics within a patient, the method comprising the steps of

- 5 (a) providing a Doppler flow signal indicative of blood flows within the body,  
(b) visualising the Doppler flow signal on a display device; and  
(c) simultaneously providing an audio output to said listener of the Doppler  
blood flow signal.

8. A method as claimed in claim 5 wherein said step (c) includes providing an  
10 apparent spatialisation of said audio output to said listener.

1/5

FIG. 1



2/5




FIG. 2




FIG. 3

4/5




FIG. 4

5/5




FIG. 5

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/00946

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>												
Int. Cl. <sup>7</sup> : A61B 008/06												
According to International Patent Classification (IPC) or to both national classification and IPC												
<b>B. FIELDS SEARCHED</b>												
Minimum documentation searched (classification system followed by classification symbols)												
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched												
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DWPI; IPC A61B 008/06, Keywords: Audio, speaker, headphone, stereo, channel, video, display, monitor, VDU												
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>												
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.										
X	WO 9632888 A1 (JONES) 24 October 1996 See page 4, line 8 - page 5, line 20	1-2, 5, 7-8										
X	US 5891036 A (ISUMI) 6 April 1999 See column 1, line 44 - column 2, line 62; column 4, lines 41-63; figure 1	1, 3-5, 7-8										
<input type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex												
<p>* Special categories of cited documents:</p> <table border="0"> <tr> <td>"A" document defining the general state of the art which is not considered to be of particular relevance</td> <td>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"E" earlier application or patent but published on or after the international filing date</td> <td>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"O" document referring to an oral disclosure, use, exhibition or other means</td> <td>"&amp;" document member of the same patent family</td> </tr> <tr> <td>"P" document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table>			"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family	"P" document published prior to the international filing date but later than the priority date claimed	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention											
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone											
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art											
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family											
"P" document published prior to the international filing date but later than the priority date claimed												
Date of the actual completion of the international search 12 September 2003	Date of mailing of the international search report 22 SEP 2003											
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaaustralia.gov.au Facsimile No. (02) 6285 3929	Authorized officer <b>Jagdish Bokil</b> Telephone No : (02) 6283 2371											

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

**PCT/AU03/00946**

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member			
WO	9632888	US	5640960		
US	5891036	DE	19739978	JP	10080424
END OF ANNEX					