



(43) International Publication Date  
25 November 2010 (25.11.2010)

PCT

(10) International Publication Number  
**WO 2010/135130 A1**

(51) International Patent Classification:  
**G09G 5/00** (2006.01)

(21) International Application Number:  
PCT/US2010/034655

(22) International Filing Date:  
13 May 2010 (13.05.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
61/180,400 21 May 2009 (21.05.2009) US  
12/574,857 7 October 2009 (07.10.2009) US

(71) Applicant (for all designated States except US): **Sony Computer Entertainment Inc.** [JP/JP]; 2-6-21 Minami-Aoyama, Minato-ku, Tokyo 107-0062 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ZALEWSKI, Gary M.** [US/US]; 919 Hillsdale Boulevard, Foster City, California 94404 (US). **NICHOLSON, Charles** [US/US]; 919 Hillsdale Boulevard, Foster City, California 94404 (US).

(74) Agent: **ISENBERG, Joshua D.**; Jdi Patent, 809 Corporate Way, Fremont, California 94539 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: TOUCH CONTROL WITH DYNAMICALLY DETERMINED BUFFER REGION AND ACTIVE PERIMETER




FIG. 7D

(57) Abstract: A hand-held electronic device, method of operation and computer readable medium are disclosed. The device may include a case having one or more major surfaces. A visual display and a touch interface are disposed on at least one of the major surfaces. A processor is operably coupled to the visual display and touch screen. Instructions executable by the processor may be configured to a) present an image on the visual display containing one or more active elements; b) correlate one or more active portions of the touch interface to one or more corresponding active elements in the image on the visual display; and c) re-purpose one or more portions of the touch interface outside the one or more active portions to act as inputs for commands associated with the one or more active elements

## **TOUCH CONTROL WITH DYNAMICALLY DETERMINED BUFFER REGION AND ACTIVE PERIMETER**

### **CLAIM OF PRIORITY BENEFIT**

This application claims the priority benefit of U.S. Provisional Patent Application Number  
5 61/180,400, filed May 21, 2009, the entire contents of which are incorporated herein by  
reference.

This application claims the priority benefit of U.S. Patent Application Number 12/574,857,  
filed October 07, 2009, the entire contents of which are incorporated herein by reference.

### **CROSS-REFERENCE TO RELATED APPLICATIONS**

10 This application is related to commonly assigned co-pending application number 12/574,828,  
(attorney docket number SCEA09019US00), to Charles Nicholson and Gary M. Zalewski  
entitled "CONTINUOUS AND DYNAMIC SCENE DECOMPOSITION FOR USER  
INTERFACE" filed October 07, 2009, the entire contents of which are incorporated herein  
by reference.

15 This application is related to commonly assigned co-pending application number 12/574,838,  
(attorney docket number SCEA09020US00), to Charles Nicholson and Gary M. Zalewski  
entitled "HAND-HELD DEVICE WITH ANCILLARY TOUCH ACTIVATED ZOOM"  
filed October 07, 2009, the entire contents of which are incorporated herein by reference.

This application is related to commonly assigned co-pending application number 12/574,846,  
20 (attorney docket number SCEA09021US00), to Charles Nicholson and Gary M. Zalewski  
entitled "HAND-HELD DEVICE WITH ANCILLARY TOUCH ACTIVATED  
TRANSFORMATION OF ACTIVE ELEMENT" filed October 07, 2009, the entire contents  
of which are incorporated herein by reference.

This application is related to commonly assigned co-pending application number 12/574,851,  
25 (attorney docket number SCEA09022US00), to Charles Nicholson and Gary M. Zalewski  
entitled "TOUCH SCREEN DISAMBIGUATION BASED ON PRIOR ANCILLARY  
TOUCH INPUT" filed October 07, 2009, the entire contents of which are incorporated herein  
by reference.

This application is related to commonly assigned co-pending application number 12/574,860,  
30 (attorney docket number SCEA09024US00), to Charles Nicholson and Gary M. Zalewski

entitled "HAND-HELD DEVICE WITH TWO-FINGER TOUCH TRIGGERED SELECTION AND TRANSFORMATION OF ACTIVE ELEMENTS" filed October 07, 2009, the entire contents of which are incorporated herein by reference.

This application is related to commonly assigned co-pending application number 12/574,869,  
5 (attorney docket number SCEA09043US00), to Charles Nicholson and Gary M. Zalewski  
entitled "DYNAMIC RECONFIGURATION OF GUI DISPLAY DECOMPOSITION  
BASED ON PREDICTIVE MODEL" filed October 07, 2009, the entire contents of which  
are incorporated herein by reference.

This application is related to commonly assigned co-pending application number 12/574,887,  
10 (attorney docket number SCEA09044US00), to Charles Nicholson and Gary M. Zalewski  
entitled "CUSTOMIZATION OF GUI LAYOUT BASED ON HISTORY OF USE" filed  
October 07, 2009, the entire contents of which are incorporated herein by reference.

#### FIELD OF THE INVENTION

Embodiments of the present invention are related to handheld devices and more particularly  
15 to hand-held devices that utilize a visual display and touch interface.

#### BACKGROUND OF THE INVENTION

Handheld consumer electronic devices such as cellular telephones, portable internet devices,  
portable music players, and hand held gaming devices often include some form of visual  
display, such as a flat screen video display or a touchscreen display. Touchscreens are  
20 displays which also have the ability to detect the location of touches within the display area.  
This allows the display to be used as an input device, removing the keyboard and/or the  
mouse as the primary input device for interacting with the display's content. Such displays  
can be attached to computers or, as terminals, to networks. Touchscreens also have assisted in  
recent changes in the design of personal digital assistant (PDA), satellite navigation and  
25 mobile phone devices, making these devices more usable.

Touchscreens have become commonplace since the invention of the electronic touch  
interface in 1971 by Dr. Samuel C. Hurst. They have become familiar in retail settings, on  
point of sale systems, on automatic teller machines (ATMs) and on PDAs where a stylus is  
sometimes used to manipulate a graphical user interface (GUI) and to enter data. The  
30 popularity of smart phones, PDAs, portable game consoles and many types of information  
appliances is driving the demand for, and the acceptance of, touchscreens.

The visual displays used in hand-held devices are relatively small compared to computer screens or television screens. This often makes it difficult to see information displayed on the screen. Some hand-held devices allow the display to zoom-in on a selected portion of a larger image so that the selected portion may be magnified and viewed in greater detail. To  
5 implement such a zoom feature typically requires the hand-held device to implement some way of selecting the portion to be magnified. Prior art solutions include the use of a touchscreen as the visual display and software that allows the user to select the portion of the display to be magnified with his fingers or a stylus. Unfortunately, because the screen is small, the user's fingers often obscure the part that is to be selected making selection  
10 difficult.

It is within this context that embodiments of the present invention arise.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

15 FIG. 1A is a schematic diagram illustrating a portion of content containing active elements on a visual display of a handheld device.

FIG. 1B is a schematic diagram illustrating decomposition of the portion of content displayed on the device in FIG. 1A into sensitive regions corresponding to active elements in accordance with an embodiment of the present invention.

20 FIGs. 1C-1I are schematic diagrams of possible handheld devices that may be used in conjunction with embodiments of the present invention.

FIG. 2A is a side view diagram of a hand-held device according to an embodiment of the present invention.

25 FIG. 2B is a block diagram of a hand-held device according to an embodiment of the present invention.

FIG. 3A is a flow diagram of illustrating operation of a hand-held device according to an embodiment of the present invention.

FIG. 3B is a three-dimensional schematic diagram of a hand-held device illustrating magnification of a selected displayed active element according to an embodiment of the present invention.

FIG. 4A is a flow diagram of illustrating operation of a hand-held device according to an  
5 embodiment of the present invention.

FIG. 4B is a three-dimensional schematic diagram illustrating selection of an active element with a touch pad on a handheld device according to an embodiment of the present invention.

FIG. 4C is a plan view schematic diagram illustrating magnification of an active element in response to activation of a corresponding region of the touch pad.

10 FIG. 4D is a three-dimensional schematic diagram illustrating selective magnification of a portion of content presented on a display of a handheld device using a touch pad according to an embodiment of the present invention.

FIG. 5 is a plan view schematic diagram of a handheld device illustrating an example of transformation of an active element presented on a visual display in accordance with an  
15 embodiment of the present invention.

FIGs. 6A-6E are plan view schematic diagrams of a hand-held device at different stages of operation according to an embodiment of the present invention.

FIGs. 7A-7E are plan view schematic diagrams of a hand-held device at different stages of operation according to an embodiment of the present invention.

20 FIGs. 8A-8C are plan view schematic diagrams of a hand-held device having a touch screen at different stages of operation according to an embodiment of the present invention.

FIGs. 9A is a flow diagram of illustrating operation of a hand-held device according to an embodiment of the present invention.

FIG. 9B is a plan view schematic diagram illustrating an example of how decomposition of  
25 displayed content may change as probability of subsequent actions change.

FIG. 10A is a flow diagram of illustrating operation of a hand-held device according to an embodiment of the present invention.

FIGs. 10B-10C are plan view schematic diagrams of a hand-held device at different stages of operation according to an embodiment of the present invention.

#### DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Although the following detailed description contains many specific details for the purposes of illustration, anyone of ordinary skill in the art will appreciate that many variations and alterations to the following details are within the scope of the invention. Accordingly, the exemplary embodiments of the invention described below are set forth without any loss of generality to, and without imposing limitations upon, the claimed invention.

#### CONTINUOUS AND DYNAMIC SCENE DECOMPOSITION FOR USER INTERFACE

- 10 According to certain embodiments of the present invention, content to be rendered on a hand held device may be decomposed into a number of regions that fill the area of a display screen. Each region may be associated with a different active element of the content that is displayed on the screen. These regions may be mapped to corresponding touch-sensitive regions of a user interface on the device. Each touch-sensitive region corresponds to a different active
- 15 element. In some embodiments, the user interface may be a touch pad that is separate from the display screen. In other embodiments, the display screen may be a touch screen and the user interface may therefore be part of the display screen. Depending on the type of touch screen, a user may interact with the touch screen with a touch of the user's finger or by touching the screen with a stylus.
- 20 By way of example, and not by way of limitation, content, such as a web page, rendered on a hand held device is decomposed into a number of regions. Each region may be associated with a different active element that is displayed. An entire area of a touch pad on the back of the device may be divided into touch sensitive regions. Each touch sensitive region may correspond to a different active element. The displayed web page can be broken into the
- 25 active regions for the back touch by performing a Voronoi decomposition on the browser-rendered html canvas. A user can then "select" one of the active elements shown on the front screen by touching the corresponding region on the back touch. Since each area on the back touch is much larger than the displayed active element, the active elements are easier to select using the back touch than with the front touch screen.
- 30 By way of a more detailed example, content in the form of an html document, such as a web page, may be decomposed into the active regions for the back touch by performing a

mathematical decomposition referred to generally as a tessellation on the browser-rendered html canvas. The html canvas determines how the html document is displayed on a screen. The tessellation divides the portion of the document that is to be displayed into a finite number of regions that divide up the area of the screen. Each region corresponds to an active element in the portion of the document that is to be displayed on the screen. According to one embodiment, these regions may be mapped to corresponding touch-sensitive regions of a touch pad. A user can then “select” an active element shown on the front screen by touching the corresponding touch-sensitive region on the touch pad. As a result of the tessellation, each touch-sensitive region may be significantly larger than the corresponding active element displayed on the screen. Consequently, where the screen is a touch screen, the active elements may be easier to select using the touch pad than with the touch screen.

There are a number of different ways in which the tessellation may be performed. In general, it is preferable for the tessellation to divide up the displayed portion of the document into convex regions. By way of example, and not by way of limitation, tessellation of the displayed portion into convex regions may be implemented as a Voronoi decomposition, sometimes also called a Voronoi tessellation, a Voronoi diagram, or a Dirichlet tessellation. The Voronoi decomposition is a kind of decomposition of a metric space determined by distances to a specified discrete set of objects in the space, e.g., by a discrete set of points. In a simplest case, a plane contains a set of points  $S$  referred to as Voronoi sites. Each Voronoi site  $s$  has a Voronoi cell, also called a Dirichlet cell,  $V(s)$  consisting of all points closer to  $s$  than to any other site. The segments of the Voronoi diagram (i.e., the edges of the Voronoi cells) are all the points in the plane that are equidistant to two sites. The Voronoi nodes (i.e., the corners of a cell where two edges meet) are the points equidistant to three (or more) sites.

Transformation of active elements may be context sensitive. For example, it may make sense to simply magnify a button to make it easier to use with the touch screen. However, it may be more convenient to transform a scroll bar to a form that is more convenient for a user to manipulate on a touch screen.

As an example, a web page might normally appear on the device's screen as depicted in FIG. 1A. In this example a portion of a web page **101** is displayed on a visual display of a device **102**. The web page **101** includes active elements. As used herein, an active element refers to a portion of the displayed web page that a user may interact with through a suitable user interface. Non-limiting examples of active elements include a radio button **104**, a text entry

box **106**, a link **108** (e.g., an html link or web link), and a scroll bar **110**. The web page may also include inactive content, such as normal text **112** or images.

As depicted in FIG. 1B, the area of the displayed web page **101** may be decomposed into a radio button region **114** that corresponds to the radio button **104**, a text entry box region **116** corresponding to the text entry box **106**, a link region **118** corresponding to the link **108**, and a scroll bar region **120** corresponding to the scroll bar **110**. It is noted that there is no region corresponding to the text **112** since the text is not an active element in this example.

According to some embodiments of the present invention, the radio button region **114**, text entry box region **116**, and link region **118** may be mapped to corresponding regions on a touch sensitive interface.

In some embodiments, the touch sensitive interface may be a touch screen that is part of the visual display. Alternatively, the touch sensitive interface may be a touch pad that is separate and apart from the visual display. There are a number of possible configurations for the visual display and touch pad. Possible examples of such configurations include one in which a visual display **V** and a touch pad **T** are on the same side of a case **C**, as shown in FIG. 1C, on adjacent sides of the case **C**, as shown in FIG. 1D, or on opposite sides of the case **C** as shown in FIG. 1E. Other examples include configurations in which the visual display **V** and touch pad **T** are located on separate case portions **C<sub>1</sub>** and **C<sub>2</sub>** respectively. By way of example, and not by way of limitation, the case portions **C<sub>1</sub>**, **C<sub>2</sub>** may be connected to each other in a sliding configuration, as shown in FIG. 1F, in a hinged configuration as shown, e.g., in FIG. 1G, FIG. 1H, or FIG. 1I. In FIG. 1F, the visual display **V** and touch pad **T** face inward when case portions **C<sub>1</sub>** and **C<sub>2</sub>** are in a closed position. Alternatively, as shown in FIG. 1G, the visual display **V** may face outward and the touch pad **T** may face inward (or vice versa) when the case portions **C<sub>1</sub>** and **C<sub>2</sub>** are in a closed position. Furthermore as shown in FIG. 1H, the visual display **V** and touch pad **T** face outward when case portions **C<sub>1</sub>** and **C<sub>2</sub>** are in a closed position.

According to an embodiment of the invention, as shown in FIG. 2A, a handheld electronic device **200** may include a case **201** with a visual display **202** located on a major surface **225A** of the case **201** referred to herein as the front surface. A touch pad **204** may be located on another major surface **225B** of the case **201** (referred to herein as the back surface) that is opposite the front surface. The case may be of sufficiently small size that it can be held in a user's hand.



As seen in FIG. 2B, the device may include a controller **203**, the components of which may be located within the case **201**. The controller **203** includes a processor **207** operably coupled to the visual display **202** and the touch pad **204**. In some embodiments, the device **200** may include multiple processors **207** if parallel processing is to be implemented. The device **200**  
5 may be configured for use as a game device, a phone, a portable media player, an email device, web browser device and the like.

The hand-held device **200** may also include well-known support functions, such as input/output (I/O) elements **211**, power supplies (P/S) **213**, a clock (CLK) **215** and cache **217**. The device **200** may optionally include a mass storage device **219** such as a disk drive, CD-ROM drive, flash drive, or the like to store programs and/or data. The touch screen **202**, touch pad **204**, processor **207**, memory **208** and other components of the device **200** may exchange signals (e.g., code instructions and data) with each other via a system bus **220** as shown in FIG. 2B. In some embodiments, the device **200** may include a network interface **216**, configured to allow the device to exchange signals with other devices over a network.  
10  
15 Furthermore, the hand-held device **200** may include one or more sensors **218**. Such sensors may include, e.g., an inertial sensor such as an accelerometer or tilt sensor, an optical sensor, an acoustic sensor such as a microphone or microphone array. The sensors may generate inputs to the program instructions **210** that reflect the environment in which the hand-held device operates.

20 The visual display **202** may be any suitable form of display capable of presenting visible symbols and/or graphical images. By way of example the visual display **202** may include a flat panel display, such as a liquid crystal display (LCD) or light emitting diode (LED) display. In some embodiments, the visual display **202** on the front surface may also incorporate a touch pad to provide an interface for receiving user commands. In some  
25 embodiments the touch pad **204** may optionally include a visual display. The touch pad **204** on the back surface may be based on any suitable touch screen technology, such as resistive, surface-acoustic wave (SAW) capacitive, infrared, strain gauge, optical imaging, dispersive signal technology, acoustic pulse recognition, frustrated total internal reflection or graphics tablet based on magneto-strictive technology that responds to the proximity of a user's  
30 fingers. Any of these same technologies may also be incorporated into the visual display **202** on the front surface if desired. In a preferred embodiment, the visual display **202** includes a

resistive touch screen coupled to the controller **203** and the touch pad **204** includes a capacitive touch screen.

By way of example a resistive touch screen panel may be composed of several layers including two thin metallic electrically conductive and resistive layers separated by thin  
5 space. When some object touches this kind of touch panel, the layers are connected at a certain point. The panel then electrically acts similar to two voltage dividers with connected outputs. This causes a change in the electrical current which is registered as a touch event which may be sent to the processor **207** for processing.

Surface Acoustic Wave technology uses ultrasonic waves that pass over the touch screen  
10 panel. When the panel is touched, a portion of the wave is absorbed. This change in the ultrasonic waves registers the position of the touch event and sends this information to the controller for processing.

A capacitive touch screen panel may be coated with a material, e.g., indium tin oxide that conducts a continuous electrical current across the sensor. The sensor therefore exhibits a  
15 precisely controlled field of stored electrons in both the horizontal and vertical axes. When the capacitive touch screen's 'normal' capacitance field (its reference state) is altered by an externally applied electric field, e.g., from a user's finger, electronic circuits located at each corner of the panel measure a resultant 'distortion' in the characteristics of the reference field and send the information about the event to the processor **207** for mathematical processing.

20 An infrared touch screen panel may employ one of two different methodologies. One method uses thermal induced changes of the surface resistance. Another method is an array of vertical and horizontal IR sensors that detected interruption of a modulated light beam near the surface of the screen.

In a strain gauge configuration the screen is spring mounted on the four corners and strain  
25 gauges are used to determine deflection when the screen is touched. This technology may also measure movement of the screen **202** along the Z-axis.

In touch screen technology based on optical imaging, two or more image sensors may be placed around the edges (mostly the corners) of the screen. Infrared backlights may be placed in a camera's field of view on the other sides of the screen. A touch shows up as a shadow  
30 and each pair of cameras can then be triangulated to locate the touch.

Dispersive signal technology may use sensors to detect mechanical energy in the glass that occurs due to a touch. Complex algorithms then interpret this information and provide the actual location of the touch.

5 Touch screens based on acoustic pulse recognition may use more than two piezoelectric transducers located at some positions of the screen to turn the mechanical energy of a touch (vibration) into an electronic signal. This signal may then be converted into an audio file, and then compared to preexisting audio profile for every position on the screen.

10 Touch screens based on frustrated total internal reflection use the principle of total internal reflection to fill a refractive medium with light. When a finger or other soft object is pressed against the surface, the internal reflection light path is interrupted, making the light reflect outside of the medium and thus visible to a camera behind the medium.

15 In some embodiments, the device **200** may include one or more optional buttons coupled to the controller **203** to provide additional sources of input. There are a number of different possible locations for the optional buttons **206**. By way of example, and without loss of generality, one or more optional buttons **206** may be located on the front surface **225A**, the back surface **225B**, along a side edge **222** of the device **200** or on a beveled edge **224**.

20 The hand-held device **200** may further include a memory **208** (e.g., RAM, DRAM, ROM, and the like). A computer readable medium such as the memory **208** may store program instructions **210** for execution on the processor **207**. The program instructions **210** may be configured to respond to inputs from one or more input sources on the device (e.g., the visual display **202**, the touch pad **204**, or buttons **206**) or from remote input sources that are coupled to the device. The program instructions **210** may include display driver instructions **212** configured to generate images displayed on the visual display **202**. The program **210** may include touch pad driver instructions **213** that respond to inputs received from the touch pad  
25 **204**. It is noted that in some embodiments, the functions of the visual display **202** and touch pad **204** may be combined into a single touch screen interface that may serve as both an input and an output device.

HAND-HELD DEVICE WITH ANCILLARY TOUCH ACTIVATED  
TRANSFORMATION OF ACTIVE ELEMENT

By way of example, and not by way of limitation, in one version of this embodiment, a hand-held electronic device may have a case with one or more major surfaces. A visual display may be disposed on at least one of the major surfaces. A touch interface may be disposed on at least one of the major surfaces. A processor may be operably coupled to the display and the touch interface. An image containing content may be rendered on the display. The content may be divided into a number of regions. Each region may be associated with a different active element such as a link or check box that is displayed. The entire area of a touch interface may be divided into touch sensitive regions. Each touch sensitive region may correspond to a different active element shown on the display. A user may select an active element by touching the corresponding region on the touch interface. When the active element is selected its appearance and/or operation may be transformed so that the element is easier to manipulate with the touch interface. The transformation may be animated so that the user can easily see which active element is being transformed. After the user interacts with the transformed active element, the element may revert to its original form by a reverse animation.

There are a number of different ways in which the reversion of a transformed element may be triggered. By way of example, and not by way of limitation, if the transformation is triggered by a user's touch on a region of the touch interface **204** corresponding to an active element, the reversion may be triggered by removal of the touch.

By way of example and not by way of limitation, the program **210** may further include transformation instructions **214**, which may be configured, e.g., by appropriate software programming, to operate the device **200** according to a method illustrated generally in FIG. 3A. As indicated at **302** in FIG. 3A, a portion of content to be displayed on the display **202** may be decomposed, e.g., by Voronoi composition, as discussed above. Active elements within the displayed portion may be correlated corresponding portions of a touch interface, as indicated at **304**. The touch interface may be the touch pad **204** or the visual display **202**, if it includes a touch screen. As a user manipulates the touch interface, the program **210** may determine whether the user has selected any portion of the touch interface that corresponds to an active element, as indicated at **306**. If the user selects one of these active portions, a transformed view of the corresponding active element may then be presented on the visual display **202** as indicated at **308**.

There are a number of ways in which an active element may be transformed. For example, as illustrated in FIG. 3B, an icon **312** representing an active element may simply be presented in magnified form **314**. This allows the magnified form **314** to be more easily manipulated by the user if the visual display **202** is a touch screen. The transformation of the selected active  
5 element may be animated so that the user can easily see which active element is being transformed. After the user interacts with the transformed active element, the element may revert to its original form by a reverse animation. The re-transformation may also be animated. There are a number of variations on the transformation of active elements within the scope of embodiments of the present invention. A number of these are discussed below.

#### 10 HAND-HELD DEVICE WITH ANCILLARY TOUCH ACTIVATED ZOOM

In this embodiment, a hand-held electronic device may have a case with one or more major surfaces. A visual display may be disposed on at least one major surface. A touch pad may be disposed on at least one of the major surfaces. A processor may be operably coupled to the visual display and the touch screen. Instructions executable by the processor may be  
15 configured to: a) present an image on the visual display; b) identify an active portion of the touch pad in response to user interaction with the touch pad; c) correlate the active portion of touch pad to a corresponding region of display; and d) present a *magnified* view of the corresponding region on the visual display. As an example, a user may slide his finger over touch pad on a back side of the device. The location of the user's finger may be mapped to a  
20 corresponding region of the display on the front side. A magnified view of this region may be displayed in a window on the display.

In some versions of this embodiment, the transformation instructions **214** may be configured to track a user's manipulation of the touch pad **204** on the back surface as indicated at **402** in **FIG. 4A**. A magnified view of a corresponding portion of an image may be presented on the  
25 visual display **202**. For example, as shown in the flow diagram of FIG. 4A the program **210** may track a user's manipulation of the touch pad **204**, as indicated at **402**, e.g., using the touch pad driver **213**. Specifically, the touch pad driver **213** may determine which portion **412** of the touch pad **204** has been activated by a user's touch, as shown in FIG. 4B. The active portion **412** may be correlated to a corresponding region of the visual display **202**, as  
30 indicated at **404**. A magnified view of the content within the corresponding region **414** may be displayed on the display **202** as indicated at **406**.

In some embodiments, the touch pad **204** may be tessellated into regions that correspond to active elements shown on the display **202**. When a user activates one of the regions of the touch pad **204** that corresponds to an active element, that active element may be magnified on the touch screen as depicted in FIG. 4B. For instance, referring to the example described  
5 above with respect to FIG. 1A-1B, if the user presses the back touch region **118** corresponding to the link **108**, a magnified link **418** may be displayed on the touch screen as shown in FIG. 4C.

In alternative versions of embodiment described with respect to FIG. 4A-4B, it is not strictly necessary to perform a tessellation or similar decomposition of displayed portion of content.  
10 Instead, the program **210** may simply track the user's activation of a portion of the touch pad **204**, correlate the activated portion to a corresponding region of content displayed on the screen and present a magnified view **414** of the content in the corresponding region as shown in FIG. 4D. This makes it much easier to see and user the selected active elements shown on the screen. This also allows for an enhanced usability of the visual display **202** in the case  
15 where the visual display is also a touch screen.

It is noted that within the context of embodiments of the present invention there are many alternative ways in which an active element may be transformed once it has been selected through activation of a corresponding region of a touch interface. For example, in addition to, or instead of, altering the displayed size of an active element, the appearance and or nature  
20 of operation of an active element may be altered by the transformation.

By way of example, consider the case shown in FIGs. 1A-1B. It may be impractical to magnify the scroll bar **110**. It may also be awkward to manipulate the scroll bar displayed on a small touch screen in a conventional fashion by moving the small box or "clicking" on the up or down arrows at the ends of the scroll bar. Instead of magnifying the scroll bar **110**, a  
25 transformation may take place as depicted in FIG. 5. In this example, the scroll bar **110** may be transformed into a transformed scroll bar **130** that may operate differently from a conventional scroll bar. For example, the scroll speed and direction of the transformed scroll bar **130** may depend on where the user places a cursor **132** within the scroll bar, e.g., using a stylus. This makes it much easier to use the scroll bar on a touch screen. There are a number  
30 of ways in which the appearance and/or nature of operation of an active element may be transformed. For example, a check box may be transformed into a toggle switch, which may be more intuitive to operate on a hand-held device.

## TOUCH SCREEN DISAMBIGUATION BASED ON PRIOR ANCILLARY TOUCH INPUT

In this embodiment a hand-held electronic device may have a case with first and second major surfaces as discussed above. A touch screen display may be disposed on the first major surface and a touch pad may be disposed on another major surface. An image containing content is rendered on the display. The content can be divided into a number of regions. Each region may be associated with a different active element, e.g., as discussed above. An entire area of a touch pad may be divided into touch sensitive regions. Each touch sensitive region corresponds to a different active element shown on the touch screen. A user may select an active element by touching the corresponding region on the touch pad.

As discussed above, when an active element is selected its appearance and/or operation may be transformed so that the element is easier to manipulate with the touch screen. As noted above, the transformation can be animated so that the user can easily see which active element is being transformed. After the user interacts with the transformed active element, the element may revert to its original form by a reverse animation. For example, when a user selects an active element by pressing the corresponding region on the touch pad, the active element may be magnified on a front display that also acts as a touch screen. After the user has manipulated the transformed active element, the transformed element may revert to its normal appearance. However, the active element that was manipulated may be highlighted on the touch screen so that the user can tell which active element was most recently changed. If the user wants to re-use the highlighted active element, this element can be selected by pressing on the general area of the element on the front touch screen. If the user's finger touches several active elements, this action may be disambiguated as an activation of the highlighted active element.

By way of example, and not by way of limitation, as normally displayed, content, such as a web page containing multiple active elements, e.g., check boxes **602** may appear on a touch screen display **202** as shown in FIG. 6A. The area of the displayed page may be broken up into nine different regions **612** as shown in FIG. 6B.

In this example, each check box region **612** is mapped to a different corresponding region of a touch pad (not shown). The touch pad may be located on a different part of the device, e.g., on a back surface of a case **201** or in some other configuration, e.g., as depicted in FIGs. 1C-

11. A user may “select” one of the nine check boxes shown on the touch screen by touching the corresponding region on the touch pad. Since each area on the back touch is much larger than the displayed check boxes, the check boxes are easier for the user to select. When a user selects an active element by pressing the corresponding region on the touch pad, the active  
5 element may be magnified or otherwise transformed on the touch screen. The user can then more easily see the active element and/or interact more easily with it using the touch screen **202**.

For example, if the user presses a touch pad region **612C** corresponding to a center check box **602C**, a magnified center check **622C** box may be displayed on the touch screen **202** as  
10 shown in FIG. 6C. Portions of the displayed content that are associated with the text box, e.g., associated text **624C** may also be magnified so that they are easier to read.

If the user wants to check the center check box **602C**, this box can be selected by pressing on the corresponding magnified check box **622C** on the touch screen **202**, e.g., using a stylus or the user’s finger. After the user has selected the magnified center check box **622C**, the  
15 magnified check box **622C** may revert to its normal appearance on within the displayed content. However, the center check box **602C** may be highlighted on the display **202** so that the user may easily perceive that the center check box was the one that was most recently changed as shown in FIG. 6D.

The transform instructions **214** may filter input from the touch screen driver **213** based on the  
20 fact that the center check box **602C** was the active element that was most recently modified. For example, the tessellated regions corresponding to displayed active elements may be mapped to the touch screen **202** as well as the touch pad **204**. The transform instructions **214** may be configured to filter signals corresponding to touch activation of these regions such that a user’s touch of any one or more of these regions is interpreted as a touch of the most  
25 recently modified active element displayed. This way, an ambiguous input on the touch screen may be disambiguated based on previous user interaction with displayed active elements. Thus, e.g., if the user wants to un-check the center check box **602C**, this box can be selected or magnified by pressing on one or more of the check box regions **612** that are mapped to the touch screen **202**. Even if the user’s finger **F** touches several check box  
30 regions, as depicted in FIG. 6E, the transform instructions **214** may interpret this action as a selection of the center check box **602C**.



There are a number of possible variations on the embodiment described with respect to FIG. 6A-6E. These variations may address unforeseen problems associated with a handheld device that uses a touch screen on the front of the device and a touch pad on the back of the device. Many of these problems may arise since the user tends to primarily rely on the front side touch screen since the view of the position of the user's fingers on the backside touch pad is often obscured by the case.

#### TOUCH CONTROL WITH DYNAMICALLY DETERMINED BUFFER REGION AND ACTIVE PERIMETER

This embodiment deals with the problem of how to select multiple active elements on the touch screen of a hand-held device without the user having to hold down a control, e.g., on the backside touchpad, to keep the selected elements magnified or enhanced.

Certain implementations of this embodiment may be based on a modal dialog box format that uses a non-responsive or inactive region that wraps around a perimeter of a state input touch field, and, a dynamically sized accept and cancel region that wraps around the inactive buffer region of the modal dialog box. It is noted that this embodiment may be implemented in a device having a single touch screen. Although two touch interfaces are not necessary, this embodiment may be employed in devices that have two touch interfaces, e.g., a front touch screen and a back touch pad. In one example of this embodiment, select and cancel regions may be dynamically set to a thickness based on the size of a dialog box while preserving buffer region.

According to this embodiment, content rendered on a screen of a hand held device may be divided into a number of regions. Each region is associated with a different active element such as a link or check box that is displayed. The entire area of a touch interface, e.g., a touch screen onto which the content is rendered, or a separate touch pad on the back of the device may be divided into touch sensitive regions. Each touch sensitive region corresponds to a different active element. A user selects an active element by touching the corresponding touch sensitive region. A transformed or magnified active element may be displayed on the screen. The enhanced active element may be manipulated with the touch interface, e.g., a front touch screen or back touch pad. A buffer region surrounds the enhanced active element. Nothing happens if the user touches this area of the touch interface. The remaining region of the touch interface outside the buffer region is repurposed so that touching on this region can

either commit to the manipulation of the active element or cancel the manipulation of the active element.

By way of example, and not by way of limitation, content **701**, such as a web page, might normally be displayed a hand held device's touch screen as shown in FIG. 7A. In this  
5 example, the displayed content **701** includes a number of active elements, such as a radio button **702**, a text entry box **704**, a link **706** and a group of check boxes **708** and inactive elements, such as text **710**.

As depicted in FIG. 7B, the active elements may be to corresponding tessellated regions of a touch screen or touch pad, e.g., as described above. Specifically, the displayed content **701**  
10 may be decomposed into a radio button region **712** that corresponds to the radio button **702**, a text entry box region **714** corresponding to the text entry box **704**, a link region **716** corresponding to the link **706**, and a text box group region **718** corresponding to the text box group **708**. It is noted that there is no region corresponding to the text **710** since the text is not an active element in this example.

15 A user may select the check box group, e.g., by touching the corresponding region **718** on device's the touch screen or a separate touch pad. An enhanced (e.g., transformed or magnified) text box group **728** may then be displayed on the touch screen, e.g., as shown in FIG. 7C. Animation may be used to show the transformation or magnification of the text box group so that it will be clear that this is the particular active element that was selected. The  
20 transformation or magnification of the text box group **708** allows a user to more easily activate selected check boxes on the touch screen.

A buffer region **721** of the touch screen surrounds the enhanced check box region **728**. The program **210** may be configured such that nothing happens if the user touches the buffer region **721**. The remaining region **725** of the touch screen outside the buffer region **721** may  
25 be repurposed so that touching on this region can either commit to the selected boxes or cancel the text box selection and make the text boxes go away. For example, as depicted in FIG. 7D, one side of the remaining region **725A** of the touch screen may be repurposed as a "commit" button and another side of the remaining region **725B** may be repurposed as a "cancel" button. These regions may have different shading and icons may be displayed  
30 within each region as a guide to the user. Touching the "commit" region **725A** commits the selected check boxes and reverts the enhanced text box region **728** to the original form of the

text box group **708**. Touching the “cancel” region **725B** cancels the selection of the selected check boxes and reverts the enhanced text box region **728** to the original form of the text box group **708**.

5 The thickness of the remaining region **725** may be dynamically determined based on a size of the enhanced check box region **728** in such a way that the buffer region **721** is preserved. By way of example, and not by way of limitation, the buffer region **721** may be preserved if the thickness of the remaining region is adjusted so that the thickness of the buffer region **721** around the enhanced check box region **728** is greater than or equal to some minimum thickness. The minimum thickness may be determined empirically based on some criteria  
10 related to ease of use of the device. For example, a minimum thickness of the buffer region may be determined to reduce the likelihood that a user will inadvertently touch the “commit” region **725A** or cancel region **725B**.

There are a number of possible variations on the embodiment described above with respect to FIGs. 7A-7D. In one variation, the hand held device may include an inertial sensor (e.g., an  
15 accelerometer or tilt sensor), which may be used to detect a tilt of the device to toggle between commit and cancel. The user could then touch anywhere in the re-purposed region **725** to activate the commit or cancel. Alternatively, the user may commit or cancel by pressing on a separate touch pad, if the device includes one. A “commit” or “cancel” icon may be displayed on the touch screen depending on which way the device is tilted (as  
20 determined by a signal from the inertial sensor). According to another variation on this embodiment, the active element may be a color picker having two modes of operation that may be selected using a re-purposed region **725**. For example, the color picker may have a default mode that allows a user to select from among a limited number of colors (e.g., 16 colors). By touching the re-purposed region **725** a user may elect to enter an expanded mode  
25 that allows the user to select from a greater number of colors (e.g., 256 colors). The repurposed region **725** may include an icon or other indication to the user that this expanded mode is available.

Another variation addresses the situation where a user has some information copied to a temporary memory location sometimes called a “clipboard”. In conventional touch screen  
30 interfaces, if the user needs to enter information into the text entry box **704**, the device converts part of the touch screen to a virtual keyboard. In conventional hand-held devices,

the user must then enter the text with the virtual keyboard. This is often inconvenient, particularly if text can be copied using the device.

As shown in FIG. 7E, according to an embodiment of the invention, by contrast, a special icon **734** may be shown on the touch screen in conjunction with an enhanced text entry box **724** if the user selects the text entry box region **714** and data has been copied that may be pasted into the text entry box. In some embodiments portions of the touch screen may be repurposed as a virtual keyboard **744**, which may be displayed as part of or in conjunction with the enhanced text entry box **724**. The user may touch the icon **734** to paste the stored text into the text entry box **704**. The user may also enter text via the virtual keyboard. The user may then return the device to normal operation, e.g., through interaction with the touch screen or touch pad. For example, if the text entry box **704** is selected by touching the text entry box region **714** using the touch screen, the user may touch the text entry box region **714** to trigger a return to normal view. Alternatively, if the text entry box **704** is selected by touching and holding the text entry box region **714** on a touch pad on the back of the device, the user may touch the text entry box region **714** to trigger a return to normal view by releasing his touch the touchpad to go back to normal operation. This procedure avoids having to bring up the virtual keyboard for text entry.

Although a number of the embodiments described above relate to a device having a front touch screen and a back touch pad, embodiments of the present invention may be implemented in devices that utilize only a touch screen.

#### HAND-HELD DEVICE WITH TWO-FINGER TOUCH TRIGGERED SELECTION AND TRANSFORMATION OF ACTIVE ELEMENTS

According to this embodiment, content rendered on a display of a hand held device may be divided into a number of regions as discussed above. Each region may be associated with a different active element that is rendered on the display. The entire area of the display is divided into regions that correspond to touch sensitive regions of a touch interface. Each touch sensitive region corresponds to a different active element shown on the display. Touching the touch interface in a first mode (e.g., with a single finger) operates the touch interface normally. Touching one of the touch sensitive regions in another mode of touch (e.g., with two fingers) activates an enhancement (e.g., transformation or magnification) of the active element corresponding to that region. The first and second modes of operation

may be defined arbitrarily. However, in a preferred embodiment, a single finger touch operates the touch interface normally and a two-finger touch on a screen region corresponding to an active element initiates the enhancement of that element.

By way of example, and not by way of limitation, content **801**, such as a web page might normally appear on a touch screen **803** as shown in FIG. 8A. The content **801** may include active elements, such as a radio button **802**, a text entry box **804**, a link **806** and a check box **808**. Inactive normal text **810** or images may also be displayed. In a conventional mode of operation a single finger touch by operates the screen normally. For example, a “swipe” across the surface of the touch screen **803** with a finger **F** may be interpreted as an instruction to trigger scrolling of the displayed content **801**.

As discussed above, the area of the displayed content **801** may be broken up into four different regions as shown in FIG. 8B. These regions include a radio button region **812** that corresponds to the radio button **802**, a text entry box region **814** corresponding to the text entry box **804**, a link region **816** corresponding to the link **806**, and a check box region **818** corresponding to the check box group **808**. It is noted that there is no region corresponding to the text **810** since the text is not an active element in this example.

A user can then “select” one of the four active elements shown on the touch screen **803** by touching the corresponding region on the touch screen with a second touch mode, e.g., a two-fingered touch. Since each sensitive area is much larger than the displayed active element, the active elements are easier to select. When a user selects an active element by pressing the corresponding region on the touch screen with two fingers, the program **210** may interpret this action as an instruction to enhance the corresponding active element, which may then be enhanced, e.g., magnified or transformed, as discussed above. The user can then more easily see the active element and interact more easily with it using the touch screen **803**.

For example, as shown in FIG. 8C, if the user presses the touch screen region **816** for the link with two fingers **F<sub>1</sub>**, **F<sub>2</sub>** an enhanced link **826** may be displayed on the touch screen **803**. By way of example, the enhanced link **826** may show a pre-rendered image of the web page or other content to which the user may navigate by activating the link.

This embodiment facilitates viewing and using the active elements shown on the screen. This also allows for an enhancement of conventional use of a touch screen. Specifically, a two finger touch on one of the active element regions of the touch screen **803** may be interpreted

as equivalent to touch on a corresponding region of a touch pad on a backside of the device. Using two different touch modes, as opposed to two different touch interfaces, may simplify the design of a hand-held device and reduce the devices complexity and cost. Using two different touch modes, may also be advantageous even if the device includes both a touch  
5 screen and a separate touch pad. The dual mode touch screen may provide additional flexibility and ease of operation.

In some variations of this embodiment the program **210** may interpret two fingered touch mode actions by tracking the two fingers  $F_1$ ,  $F_2$  independently. For example, if the two fingers  $F_1$ ,  $F_2$  move in the same direction, the movement may be interpreted as a “swipe”  
10 command. If the two fingers  $F_1$ ,  $F_2$  move in different directions, this movement may be interpreted as a “pinch” command.

There are other variations on this embodiment. For example, two-fingered touch may be used to trigger element magnification/transformation and single finger touch may be used for scrolling or vice versa. This embodiment may also be combined with other embodiments  
15 described above, for example, touching a re-purposed region of the touch screen **803** outside the portion of the screen that displays an enhanced active element may cancel or close the active element. In addition, the concept in this embodiment may be extended to encompass tracking of three or more fingers and associating different modes of operation commands with the number of fingers that are determined to be touching the touch screen and/or touch  
20 pad.

The features of this embodiment may be combined the features of other embodiments. For example, use of different touch modes may be control the degree of magnification of an active element or portion of displayed content in the embodiments discussed above with respect to FIGs. 4A-4B. Specifically, the degree of magnification may be correlated to the  
25 number of fingers used in the mode of touch.

#### DYNAMIC RECONFIGURATION OF GUI DISPLAY DECOMPOSITION BASED ON PREDICTIVE MODEL

In this embodiment, content, e.g., a web page rendered on a display, may be decomposed into a number of regions, each of which is associated with a different active element shown on the  
30 display. An entire area of a related touch interface may be divided into touch sensitive regions, each of which corresponds to a different active element shown on the display. A

user may select one of the active elements by touching the corresponding touch sensitive region. The decomposition may be skewed according to a prediction of which active element is likely to be selected next. The prediction may be determined from a predictive model based on a history of use of the device **200** by the user. The predictive model may be  
5 continuously updated as the user uses the device. In some versions of this embodiment, the "skew" of the decomposition may decay over time to a "non-skewed" decomposition that is not based on a prediction. The features of the other embodiments described herein may be combined with the features of this embodiment.

By way of example and not by way of limitation, as noted above, the program **210** may  
10 further include a prediction engine **221**, which may be configured, e.g., by appropriate software programming, to operate the device **200** according to a method illustrated generally in FIG. 9A. As indicated at **902** in FIG. 9A, a portion of content to be displayed on the display **202** may be decomposed, e.g., by Voronoi composition, as discussed above. Active elements within the displayed portion may be correlated corresponding portions of a touch  
15 interface, as indicated at **904**. The touch interface may be the touch pad **204** or the visual display **202**, if it includes a touch screen. As a user manipulates the touch interface, the program **210** may optionally determine whether the user has taken an action as indicated at **906**. By way of example, the program **210** may detect that the user has selected any portion of the touch interface that corresponds to an active element. The program **210** may then  
20 adjust proportions of the decomposition of the content shown on the display according to a probability of one or more subsequent actions. The decomposition of the content and correlation of the active regions to corresponding portions of the touch interface may be repeated iteratively over time. By way of example, the prediction engine **221** may compute probabilities for subsequent actions based on past patterns of user behavior following an  
25 action of a given type with the device **200**. The past behavior may be correlated to a type of content displayed on the display **102**. The probabilities may be updated as the user uses the device **200**. The screen driver **212** may re-compute the decomposition of the displayed portion of the content according to the probabilities as indicated at **908**. The size and/or shape of the resulting active regions of the touch pad **204** may change as a result of the re-  
30 computation of the decomposition.

FIG. 9B illustrates an example of how the decomposition of the display may change as probability of subsequent actions change. By way of example, as depicted in FIG. 9B, the

device may display content such as a web page in response to an initial user action. In this example, the displayed content, e.g., a web page **101** displayed on a visual display of device **102** may include active elements, such as a radio button **104**, a text entry box **106**, a link **108** (e.g., an html link or web link), and a scroll bar **110**. The content may also include inactive content, such as normal text **112** or images. As described above, the area of the displayed content page **101** may be decomposed into a radio button region **114** corresponding to the radio button **104**, a text entry box region **116** corresponding to the text entry box **106**, a link region **118** corresponding to the link **108**, and a scroll bar region **120** corresponding to the scroll bar **110**. No region corresponds to the text **112** since, in this example, the text is not an active element. The radio button region **114**, text entry box region **116**, link region **118**, and scroll bar region **120** may be mapped to corresponding regions on a touch sensitive interface.

The prediction engine **221** may determine that, based on passed user behavior, the user is more likely than not to next use the scroll bar **110** than the radio button **104** once the content **101** is displayed. Consequently, the display driver **212** may compute a decomposition of the content **101** in which scroll bar region **120** is initially made larger and the radio button region **114**, text entry box region **116** and link region **118** may be made smaller than would otherwise be the case if these regions were determined from a simple unbiased decomposition of content **101**, e.g. by tessellation of an html canvas. The display driver **212** may compute the relative areas of the radio button region **114**, text entry box region **116**, link region **118**, and scroll bar region **120** in accordance with the relative probabilities that the user is likely to use these regions within a given time frame.

The likelihood that the user will next use the scroll bar **110** may change over time. Thus, e.g., as a result of iteration of the decomposition and correlation processes, the boundary between the scroll bar region **120** and the other three regions may move over time making the scroll bar region smaller and the other three regions larger until the boundary is located where it would be if determined from a simple unbiased decomposition of the content **101**. Other variations are possible based on the amount of information available to the prediction engine about past user behavior. For example, as time passes it may become more likely that the user will use the text box **106**. If so, the text box region **116** may grow relative to the other three regions. It is noted that the corresponding probabilities for each active region may decay over time to an unbiased probability. Consequently, the tessellation of the image may decay over time to an unbiased tessellation in such a case.



The features of this embodiment may be mixed with the features of other embodiments described herein. By way of further non-limiting example, the features of this embodiment may be mixed with the features described above with respect to FIGs. 6A-6E. Specifically, the decay of the skew in the decomposition of the displayed content may be applied where an ambiguous input on the touch interface is to be disambiguated based on previous user interaction with displayed active elements as described e.g., with respect to FIG. 6E. In general, the tessellation of the displayed content may decay from a biased tessellation in which a touch anywhere on the touch interface is interpreted as an activation of a most recently transformed active element to an unbiased tessellation. Specifically, the decomposition may decay over time from one in which the center check box **602C**, may be selected or magnified by pressing on one or more of the check box regions **612** that are mapped to the touch screen **202** to one in which the center check box can only be selected or magnified by pressing on the portion of the touch interface that corresponds to the center check box.

#### 15 CUSTOMIZATION OF GUI LAYOUT BASED ON HISTORY OF USE

In a variation on the embodiments described above, the layout of content on a display of a graphical user interface (GUI) may be arranged in a predictive fashion based on a history of use of the GUI. The "layout" may include which items are displayed, where they are displayed, in what order they appear, how they appear, and how they work. The layout may decay to a non-predictive layout over time. The features of the other embodiments described herein may be combined with the features of this embodiment.

If the GUI includes a touch interface, the entire area of a touch interface may be divided into touch sensitive regions, each of which corresponds to a different active element. A user can select one of the active elements by touching the corresponding touch sensitive region. The decomposition may be skewed according to a prediction of which active element is likely to be selected next. The prediction may be determined from a predictive model based on user behavior.

By way of example and not by way of limitation, as noted above, the program **210** may further include a prediction engine **221**, which may be configured, e.g., by appropriate software programming, to operate the device **200** according to a method illustrated generally in FIG. 10A. As indicated at **1002** in FIG. 10A, a portion of content to be displayed on the

display **202** may optionally be decomposed, e.g., by Voronoi composition, as discussed above. Active elements within the displayed portion may be correlated corresponding portions of a touch interface, as indicated at **1004**. The touch interface may be the touch pad **204** or the visual display **202**, if it includes a touch screen. As a user manipulates the touch interface, the program **210** may optionally determine whether the user has taken an action as indicated at **1006**. By way of example, the program **210** may detect that the user has selected any portion of the touch interface that corresponds to an active element. The program **210** may then adjust the layout of the content shown on the display according to a probability of one or more subsequent actions as indicated at **1008**. The adjustment of the content layout and subsequent decomposition of the content and correlation of the active regions to corresponding portions of the touch interface may be repeated iteratively over time.

By way of example, the prediction engine **221** may compute probabilities for subsequent actions based on past patterns of user behavior following an action of a given type with the device **200**. The past behavior may be correlated to a type of content displayed on the display **102**. The probabilities may be updated as the user uses the device **200**. The screen driver **212** may adjust the layout of the displayed portion of the content according to the probabilities. There are a number of different ways in which the layout may be adjusted. Preferably, the layout is adjusted in a way that facilitates one or more subsequent actions that are most probable. As noted above, this may include adjusting the placement of active elements, e.g., by locating active elements that are likely to be used in sequence closer together than in a default layout. In addition, the appearance of the active elements may be adjusted, e.g., active elements likely to be used may be highlighted or more brightly colored. Furthermore, operation of one or more of the active elements may be adjusted, e.g., the order of items in a list, such as a contact list may be ordered with the most commonly used items near the top of the list.

By way of example, in a “default” setting, absent any information regarding past user behavior, a device may display content, e.g., a web page, containing a radio button **802**, text entry box **804**, link **806**, check box **808**, and inactive normal text **810** as shown in FIG. 10B. The prediction engine **221** may determine, based on past user history, that when this page (or similarly configured content) is displayed the user has a high probability of checking the check box **808** and entering text in the text entry box **804**. Based on these probabilities, the display driver **212** may modify display of the web page so that the text entry box **808** and

check box **804** are made larger and/or more prominent and placed in close proximity to each other as shown in FIG. 10B.

In some implementations, the decomposition of the displayed content into regions and division of the touch interface into corresponding portions may change as a result of the modification of the display of the content. For example, the display driver **212** may modify the html canvas for the displayed content. After this happens the touch screen driver **212** may perform a new tessellation of the html canvas that the touch screen driver **213** may use to divide the touch interface into corresponding portions.

While the above is a complete description of the preferred embodiment of the present invention, it is possible to use various alternatives, modifications and equivalents. Therefore, the scope of the present invention should be determined not with reference to the above description but should, instead, be determined with reference to the appended claims, along with their full scope of equivalents. Any feature described herein, whether preferred or not, may be combined with any other feature described herein, whether preferred or not. In the claims that follow, the indefinite article “A”, or “An” refers to a quantity of one or more of the item following the article, except where expressly stated otherwise. The appended claims are not to be interpreted as including means-plus-function limitations, unless such a limitation is explicitly recited in a given claim using the phrase “means for.”

## WHAT IS CLAIMED IS:

- 1 1. A hand-held electronic device, comprising:  
2 a case having first and second major surfaces;  
3 a visual display disposed on the first major surface;  
4 a touch interface disposed on at least one of the major surfaces;  
5 a processor operably coupled to the visual display and the touch interface; and  
6 instructions executable by the processor configured such that, when executed, the  
7 instructions cause the device to:  
8 a) present an image on the visual display containing one or more active elements;  
9 b) correlate one or more active portions of the touch interface to one or more  
10 corresponding active elements in the image on the visual display; and  
11 c) re-purpose one or more portions of the touch interface outside the one or more active  
12 portions to act as inputs for commands associated with the one or more active elements.
- 1 2. The device of claim 1 wherein the one or more re-purposed portions of the touch screen  
2 include a buffer region between one or more re-purposed portions configured to act as  
3 inputs and the one or more active elements, wherein the instructions are configured such  
4 that a touch to the buffer region is ignored.
- 1 3. The device of claim 2 wherein the one or more re-purposed portions configured to act as  
2 inputs are dynamically set to a thickness based on a size of the one or more active  
3 elements while preserving the buffer region.
- 1 4. The device of claim 2 wherein the one or more re-purposed regions of the touch screen  
2 include a region configured to initiate a "cancel" or "commit" command.
- 1 5. The device of claim 2 wherein the one or more re-purposed regions of the touch screen  
2 include a region configured to initiate a "paste" command.
- 1 6. The device of claim 1 wherein b) includes performing a tessellation of the image so that  
2 the image is divided into one or more regions that fill the display, wherein each region  
3 corresponds to a different active element.

1 7. The device of claim 6 wherein the tessellation divides the image into one or more convex  
2 regions.

1 8. The device of claim 7, wherein the tessellation is a Voronoi decomposition.

1 9. The device of claim 1, wherein the visual display is a touch screen that includes the touch  
2 interface.

1 10. The device of claim 1 wherein the touch interface is a touch pad.

1 11. The device of claim 10 wherein the visual display is a touch screen that is separate from  
2 the touch pad.

1 12. The device of claim 11 wherein the visual display is located on first surface of a case and  
2 the touch pad is located on a second surface of the case that is opposite the first surface.

1 13. The device of claim 11 wherein the visual display and touch pad are disposed on the same  
2 side of the case.

1 14. The device of claim 11 wherein the visual display and touch pad are disposed on  
2 different sides of the case.

1 15. The device of claim 14 wherein the visual display is disposed on a front side of the case  
2 and the touch pad is disposed on a back side of the case.

1 16. The device of claim 11 wherein the case includes first and second case portions wherein  
2 the visual display is disposed on the first case portion and wherein the touch pad is  
3 disposed on the second case portion.

1 17. The device of claim 16 wherein the first and second case portions are slidably connected  
2 to each other.

1 18. The device of claim 16 wherein the first and second case portions are connected to each  
2 other in a hinged configuration.

1 19. The device of claim 18 wherein the visual display and touch pad face inward when the  
2 first and second portions are in a closed position.

1 20. The device of claim 18 wherein one of the visual display and touch pad faces inward and  
2 the other of the touch pad and visual display faces outward when the first and second  
3 portions are in a closed position.

1 21. The device of claim 18 wherein the visual display and touch pad face inward when the  
2 first and second portions are in a closed position.

1 22. The device of claim 1 wherein the visual display includes a touch screen and the touch  
2 interface includes the touch screen.

1 23. The device of claim 1 wherein the instructions further comprise instructions that activate  
2 one or more of the elements in response to a distinct mode of touch that is distinct from a  
3 normal mode of touch that does not activate the one or more active elements.

1 24. The device of claim 23 wherein the distinct mode of touch is a two finger touch and  
2 wherein the normal mode of touch is a single finger touch.

1 25. The device of claim 1 wherein the instructions are further configured to present a  
2 transformed element on the display in response to a user interaction with the touch  
3 interface, wherein the transformed element interacts with the touch screen in a different  
4 mode of operation than a mode of operation of the corresponding active element prior to  
5 its transformation.

1 26. The device of claim 25 wherein the transformed element appears magnified on the visual  
2 display compared to the active element prior to transformation into the transformed active  
3 element.

1 27. The device of claim 26 wherein the instructions are configured to control a degree of  
2 magnification of the transformed element according to a mode of touch on the touch  
3 interface.

1 28. The device of claim 25 wherein the instructions further comprise an instruction  
2 configured to revert the transformed element to a form the active element had prior to  
3 being transformed into the transformed element in response to a signal from the touch  
4 interface or after an interaction with the transformed element is completed.

1 29. The device of claim 28 wherein the instructions are configured to revert the transformed  
2 active element in response to a removal of a touch on the touch interface.

1 30. The device of claim 25, wherein the instructions further comprise an instruction to  
2 highlight an active element that was most recently transformed.

1 31. The device of claim 30 wherein the visual display is a touch screen and wherein the  
2 instructions are configured to interpret a touch anywhere on the touch screen as an  
3 activation of the most recently transformed active element.

1 32. The device of claim 25, wherein the visual display is a touch screen and wherein c)  
2 includes an instruction to re-purpose one or more portions of the touch screen outside the  
3 transformed element to act as inputs for commands associated with the transformed  
4 element.

1 33. A method for operating a hand-held electronic device having a case with one or more  
2 major surfaces, a visual display disposed on at least one of the first major surfaces, a  
3 touch interface disposed on at least one of the major surfaces, a processor operably  
4 coupled to the visual display and the touch interface; and instructions executable by the  
5 processor to implement the method, the method comprising:  
6 a) presenting an image on the visual display containing one or more active elements;  
7 b) correlating one or more active portions of the touch interface to one or more  
8 corresponding active elements in the image on the visual display; and  
9 c) re-purposing one or more portions of the touch interface outside the one or more active  
10 portions to act as inputs for commands associated with the one or more active elements.

1 34. The method of claim 33 wherein the one or more re-purposed portions of the touch screen  
2 include a buffer region between one or more re-purposed portions configured to act as  
3 inputs and the one or more active elements, wherein the instructions are configured such  
4 that a touch to the buffer region is ignored.


1 35. The method of claim 34 wherein the one or more re-purposed portions configured to act  
2 as inputs are dynamically set to a thickness based on a size of the one or more active  
3 elements while preserving the buffer region.

- 1 36. The method of claim 34 wherein the one or more re-purposed regions of the touch screen  
2 include a region configured to initiate a “cancel” or “commit” command.
- 1 37. The method of claim 34 wherein the one or more re-purposed regions of the touch screen  
2 include a region configured to initiate a “paste” command.
- 1 38. The method of claim 34 wherein b) includes performing a tessellation of the image so that  
2 the image is divided into one or more regions that fill the display, wherein each region  
3 corresponds to a different active element.
- 1 39. The method of claim 38 wherein the tessellation divides the image into one or more  
2 convex regions.
- 1 40. The method of claim 39, wherein the tessellation is a Voronoi decomposition.
- 1 41. The method of claim 34 further comprising transforming one or more of the active  
2 elements to a transformed element, wherein the transformed element interacts with the  
3 touch interface in a different mode of operation than a mode of operation of the  
4 corresponding active element prior to its transformation.
- 1 42. The method of claim 41 wherein c) includes activating one or more of the elements in  
2 response to a distinct mode of touch that distinct from a normal mode of touch that does  
3 not activate the one or more active elements.
- 1 43. The method of claim 42 wherein the distinct mode of touch is a two finger touch and  
2 wherein the normal mode of touch is a single finger touch.
- 1 44. The method of claim 42 wherein the transformed element interacts with the touch screen  
2 in a different mode of operation than a mode of operation of the corresponding active  
3 element prior to its transformation.
- 1 45. The method of claim 44 wherein the transformed element appears magnified on the visual  
2 display compared to the active element prior to transformation into the transformed active  
3 element.
- 1 46. The method of claim 45 wherein a mode of touch on the touch interface controls a degree  
2 of magnification of the transformed element.




- 1 47. The method of claim 42, further comprising reverting the transformed element to a form  
2 the active element had prior to being transformed into the transformed element in  
3 response to a signal from the touch interface.
- 1 48. The method of claim 47 wherein a removal of a touch on the touch interface triggers  
2 reverting the transformed element.
- 1 49. The method of claim 42, further comprising highlighting an active element that was most  
2 recently transformed.
- 1 50. The method of claim 49 wherein a touch anywhere on the touch interface activates the  
2 most recently transformed active element.
- 1 51. A computer readable medium programmed with computer executable instructions for  
2 operating a hand-held electronic device having a case with one or more major surfaces, a  
3 visual display disposed on at least one of the first major surfaces, a touch interface  
4 disposed on at least one of the major surfaces, a processor operably coupled to the visual  
5 display and the touch interface, wherein the instructions are executable by the processor  
6 to implement a method comprising:  
7 a) presenting an image on the visual display containing one or more active elements;  
8 b) correlating one or more active portions of the touch interface to one or more  
9 corresponding active elements in the image on the visual display; and  
10 c) re-purposing one or more portions of the touch interface outside the one or more active  
11 portions to act as inputs for commands associated with the one or more active elements.

1/13



**FIG. 1A**  
**(Prior Art)**



**FIG. 1B**




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 1G




FIG. 1H




FIG. 1I

3/13




Fig. 2A






Fig. 2B

4/13

**Fig. 3A****Fig. 3B**

5/13

Fig. 4A




Fig. 4B





FIG. 4C

6/13

Fig. 4D





Fig. 5




Fig. 6A




Fig. 6B




Fig. 6C






Fig. 6D




Fig. 6E




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E

11/13




FIG. 8A




FIG. 8B




FIG. 8C

12/13




Fig. 9A




FIG. 9B

13/13




FIG. 10A




FIG. 10B




FIG. 10C

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 10/34655

A. CLASSIFICATION OF SUBJECT MATTER  
IPC(8) - G09G 5/00 (2010.01)  
USPC - 345/156

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: G09G 5/00 (2010.01)

USPC: 345/156

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
IPC: G09G 5/00 (2010.01); USPC: 345/156, 173, 175-177 (keyword limited; terms below)

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
pubWEST(USPT,PGPB,EPAB,JPAB,USOCR); Google(Web); Search terms used: repurpose transform magnify adjust size area region  
border boundary dead inactive buffer reject neutral ignor zone non-responsive keypad input entry box touch screen pad interface

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2008/0318635 A1 (Yoon et al.) 25 December 2008 (25.12.2008), entire document especially Fig. 1-7A; para [0049]-[0121], [0169]	1-51
Y	US 2005/0237308 A1 (Autio et al.) 27 October 2005 (27.10.2005), para [00311]-[0040]	1-51
Y	US 2008/0036743 A1 (Westerman et al.) 14 February 2008 (14.02.2008), para [0100]-[0104], [0204]	4, 5, 36, 37
Y	US 2005/0253816 A1 (Himberg et al.) 17 November 2005 (17.11.2005), para [0030], [0031]	8, 40

☐ Further documents are listed in the continuation of Box C.



## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

15 June 2010 (15.06.2010)

Date of mailing of the international search report

09 JUL 2010

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents  
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Lee W. Young

PCT Helpdesk: 571-272-4300  
PCT OSP: 571-272-7774