



US011900361B2

(12) **United States Patent**
Taylor et al.

(10) **Patent No.:** **US 11,900,361 B2**
(45) **Date of Patent:** **Feb. 13, 2024**

(54) **RESOURCE PROVIDER ACCOUNT TOKEN PROVISIONING AND PROCESSING**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **VISA INTERNATIONAL SERVICE ASSOCIATION**, San Francisco, CA (US)

5,613,012 A 3/1997 Hoffman et al.
5,781,438 A 7/1998 Lee et al.
(Continued)

(72) Inventors: **Mary Taylor**, San Francisco, CA (US);
Laura A. Long, San Mateo, CA (US);
Michael Mori, San Mateo, CA (US);
Rajat Das, San Mateo, CA (US)

FOREIGN PATENT DOCUMENTS

EP 2156397 A1 2/2010
WO 0135304 A1 5/2001
(Continued)

(73) Assignee: **Visa International Service Association**, San Francisco, CA (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

“Petition for Inter Partes Review of U.S. Pat. No. 8,533,860 Challenging Claims 1-30 Under 35 U.S.C. § 312 and 37 C.F.R. § 42.104”, USPTO Patent Trial and Appeal Board, IPR 2016-00600, Feb. 17, 2016, 65 pages.

(Continued)

(21) Appl. No.: **17/953,244**

Primary Examiner — Patrick McAtee

(22) Filed: **Sep. 26, 2022**

Assistant Examiner — Nakia Leffall-Allen

(65) **Prior Publication Data**

US 2023/0013648 A1 Jan. 19, 2023

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

Related U.S. Application Data

(62) Division of application No. 15/019,842, filed on Feb. 9, 2016, now Pat. No. 11,501,288.

(51) **Int. Cl.**
G06Q 20/36 (2012.01)
H04L 9/40 (2022.01)

(52) **U.S. Cl.**
CPC **G06Q 20/367** (2013.01); **H04L 63/0807** (2013.01); **H04L 63/123** (2013.01)


(58) **Field of Classification Search**
CPC A63F 13/79; G07F 17/32; G06K 7/14; G06Q 20/40; G06Q 20/367; H04L 63/0807; H04L 63/123

See application file for complete search history.

(57) **ABSTRACT**

Embodiments are directed to issuing tokens for identifiers associated with a resource provider account specific to the resource provider issuing the account. A resource provider processor system interfaces with a resource provider computer to validate account eligibility upon receiving a token request message. If the account is eligible for token generation, the resource provider processor system generates a universal identifier corresponding to the identifier associated with the resource provider account and returns the universal identifier to the token requestor. The token requestor may send a token request message to a token issuer for obtaining a token using the universal identifier. Accordingly, the universal account identifier can be used to provision a token into a digital wallet. Transactions using the token may be processed with the resource provider processor system acting as an account issuer.

14 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,883,810	A	3/1999	Franklin et al.	7,844,550	B2	11/2010	Walker et al.
5,953,710	A	9/1999	Fleming	7,848,980	B2	12/2010	Carlson
5,956,699	A	9/1999	Wong et al.	7,849,020	B2	12/2010	Johnson
6,000,832	A	12/1999	Franklin et al.	7,853,529	B1	12/2010	Walker et al.
6,014,635	A	1/2000	Harris et al.	7,853,995	B2	12/2010	Chow et al.
6,044,360	A	3/2000	Picciallo	7,865,414	B2	1/2011	Fung et al.
6,163,771	A	12/2000	Walker et al.	7,873,579	B2	1/2011	Hobson et al.
6,227,447	B1	5/2001	Campisano	7,873,580	B2	1/2011	Hobson et al.
6,236,981	B1	5/2001	Hill	7,890,393	B2	2/2011	Talbert et al.
6,267,292	B1	7/2001	Walker et al.	7,891,563	B2	2/2011	Oder, II et al.
6,341,724	B2	1/2002	Campisano	7,896,238	B2	3/2011	Fein et al.
6,385,596	B1	5/2002	Wiser et al.	7,908,216	B1	3/2011	Davis et al.
6,422,462	B1	7/2002	Cohen	7,922,082	B2	4/2011	Muscato
6,425,523	B1	7/2002	Shem-Ur et al.	7,931,195	B2	4/2011	Mullen
6,592,044	B1	7/2003	Wong et al.	7,937,324	B2	5/2011	Patterson
6,636,833	B1	10/2003	Flitcroft et al.	7,938,318	B2	5/2011	Fein et al.
6,748,367	B1	6/2004	Lee	7,954,705	B2	6/2011	Mullen
6,805,287	B2	10/2004	Bishop et al.	7,959,076	B1	6/2011	Hopkins, III
6,879,965	B2	4/2005	Fung et al.	7,996,288	B1	8/2011	Stolfo
6,891,953	B1	5/2005	DeMello et al.	8,025,223	B2	9/2011	Saunders et al.
6,901,387	B2	5/2005	Wells et al.	8,046,256	B2	10/2011	Chien et al.
6,931,382	B2	8/2005	Laage et al.	8,060,448	B2	11/2011	Jones
6,938,019	B1	8/2005	Uzo	8,060,449	B1	11/2011	Zhu
6,941,285	B2	9/2005	Sarcanin	8,074,877	B2	12/2011	Mullen et al.
6,980,670	B1	12/2005	Hoffman et al.	8,074,879	B2	12/2011	Harris
6,990,470	B2	1/2006	Hogan et al.	8,082,210	B2	12/2011	Hansen et al.
6,991,157	B2	1/2006	Bishop et al.	8,095,113	B2	1/2012	Kean et al.
7,051,929	B2	5/2006	Li	8,104,679	B2	1/2012	Brown
7,069,249	B2	6/2006	Stolfo et al.	RE43,157	E	2/2012	Bishop et al.
7,103,576	B2	9/2006	Mann, III et al.	8,109,436	B1	2/2012	Hopkins, III
7,113,930	B2	9/2006	Eccles et al.	8,121,942	B2	2/2012	Carlson et al.
7,136,835	B1	11/2006	Flitcroft et al.	8,121,956	B2	2/2012	Carlson et al.
7,177,835	B1	2/2007	Walker et al.	8,126,449	B2	2/2012	Beenau et al.
7,177,848	B2	2/2007	Hogan et al.	8,132,723	B2	3/2012	Hogg et al.
7,194,437	B1	3/2007	Britto et al.	8,171,525	B1	5/2012	Pelly et al.
7,209,561	B1	4/2007	Shankar et al.	8,175,973	B2	5/2012	Davis et al.
7,264,154	B2	9/2007	Harris	8,190,523	B2	5/2012	Patterson
7,287,692	B1	10/2007	Patel et al.	8,196,813	B2	6/2012	Vadhri
7,292,999	B2	11/2007	Hobson et al.	8,205,791	B2	6/2012	Randazza et al.
7,350,230	B2	3/2008	Forrest	8,219,489	B2	7/2012	Patterson
7,353,382	B2	4/2008	Labrou et al.	8,224,702	B2	7/2012	Mengerink et al.
7,379,919	B2	5/2008	Hogan et al.	8,225,385	B2	7/2012	Chow et al.
RE40,444	E	7/2008	Linehan	8,229,852	B2	7/2012	Carlson
7,415,443	B2	8/2008	Hobson et al.	8,265,993	B2	9/2012	Chien et al.
7,444,676	B1	10/2008	Asghari-Kamrani et al.	8,280,777	B2	10/2012	Mengerink et al.
7,469,151	B2	12/2008	Khan et al.	8,281,991	B2	10/2012	Wentker et al.
7,548,889	B2	6/2009	Bhambri et al.	8,328,095	B2	12/2012	Oder, II et al.
7,567,934	B2	7/2009	Flitcroft et al.	8,336,088	B2	12/2012	Raj et al.
7,567,936	B1	7/2009	Peckover et al.	8,346,666	B2	1/2013	Lindelsee et al.
7,571,139	B1	8/2009	Giordano et al.	8,376,225	B1	2/2013	Hopkins, III
7,571,142	B1	8/2009	Flitcroft et al.	8,380,177	B2	2/2013	Laracey
7,580,898	B2	8/2009	Brown et al.	8,387,873	B2	3/2013	Saunders et al.
7,584,153	B2	9/2009	Brown et al.	8,401,539	B2	3/2013	Beenau et al.
7,593,896	B1	9/2009	Flitcroft et al.	8,401,898	B2	3/2013	Chien et al.
7,606,560	B2	10/2009	Labrou et al.	8,402,555	B2	3/2013	Grecia
7,627,531	B2	12/2009	Breck et al.	8,403,211	B2	3/2013	Brooks et al.
7,627,895	B2	12/2009	Gifford et al.	8,412,623	B2	4/2013	Moon et al.
7,650,314	B1	1/2010	Saunders	8,412,837	B1	4/2013	Emigh et al.
7,685,037	B2	3/2010	Reiners et al.	8,417,642	B2	4/2013	Oren
7,702,578	B2	4/2010	Fung et al.	8,433,116	B2	4/2013	Butler et al.
7,707,120	B2	4/2010	Dominguez et al.	8,447,699	B2	5/2013	Batada et al.
7,712,655	B2	5/2010	Wong	8,453,223	B2	5/2013	Svigals et al.
7,734,527	B2	6/2010	Uzo	8,453,925	B2	6/2013	Fisher et al.
7,753,265	B2	7/2010	Harris	8,458,487	B1	6/2013	Palgon et al.
7,770,789	B2	8/2010	Oder, II et al.	8,484,134	B2	7/2013	Hobson et al.
7,784,685	B1	8/2010	Hopkins, III	8,485,437	B2	7/2013	Mullen et al.
7,793,851	B2	9/2010	Mullen	8,494,959	B2	7/2013	Hathaway et al.
7,801,826	B2	9/2010	Labrou et al.	8,498,908	B2	7/2013	Mengerink et al.
7,805,376	B2	9/2010	Smith	8,504,475	B2	8/2013	Brand et al.
7,805,378	B2	9/2010	Berardi et al.	8,504,478	B2	8/2013	Saunders et al.
7,818,264	B2	10/2010	Hammad	8,510,816	B2	8/2013	Quach et al.
7,828,220	B2	11/2010	Mullen	8,533,860	B1	9/2013	Grecia
7,835,960	B2	11/2010	Breck et al.	8,538,845	B2	9/2013	Liberty
7,841,523	B2	11/2010	Oder, II et al.	8,555,079	B2	10/2013	Shablygin et al.
7,841,539	B2	11/2010	Hewton	8,566,168	B1	10/2013	Bierbaum et al.
				8,567,670	B2	10/2013	Stanfield et al.
				8,571,939	B2	10/2013	Lindsey et al.
				8,577,336	B2	11/2013	Mechaley, Jr.
				8,577,803	B2	11/2013	Chatterjee et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,577,813	B2	11/2013	Weiss		2005/0269402	A1	12/2005	Spitzer et al.
8,578,176	B2	11/2013	Mattsson		2006/0235795	A1	10/2006	Johnson et al.
8,583,494	B2	11/2013	Fisher		2006/0237528	A1	10/2006	Bishop et al.
8,584,251	B2	11/2013	McGuire et al.		2006/0278704	A1	12/2006	Saunders et al.
8,589,237	B2	11/2013	Fisher		2007/0107044	A1	5/2007	Yuen et al.
8,589,271	B2	11/2013	Evans		2007/0129955	A1	6/2007	Dalmia et al.
8,589,291	B2	11/2013	Carlson et al.		2007/0136193	A1	6/2007	Starr
8,595,098	B2	11/2013	Starai et al.		2007/0136211	A1	6/2007	Brown et al.
8,595,812	B2	11/2013	Bomar et al.		2007/0170247	A1	7/2007	Friedman
8,595,850	B2	11/2013	Spies et al.		2007/0179885	A1	8/2007	Bird et al.
8,606,638	B2	12/2013	Dragt		2007/0208671	A1	9/2007	Brown et al.
8,606,700	B2	12/2013	Carlson et al.		2007/0245414	A1	10/2007	Chan et al.
8,606,720	B1	12/2013	Baker et al.		2007/0288377	A1	12/2007	Shaked
8,615,468	B2	12/2013	Varadarajan		2007/0291995	A1	12/2007	Rivera
8,620,754	B2	12/2013	Fisher		2008/0015988	A1	1/2008	Brown et al.
8,635,157	B2	1/2014	Smith et al.		2008/0029607	A1	2/2008	Mullen
8,646,059	B1	2/2014	von Behren et al.		2008/0035738	A1	2/2008	Mullen
8,651,374	B2	2/2014	Brabson et al.		2008/0052226	A1	2/2008	Agarwal et al.
8,656,180	B2	2/2014	Shablygin et al.		2008/0054068	A1	3/2008	Mullen
8,751,391	B2	6/2014	Freund		2008/0054079	A1	3/2008	Mullen
8,762,263	B2	6/2014	Gauthier et al.		2008/0054081	A1	3/2008	Mullen
8,793,186	B2	7/2014	Patterson		2008/0065554	A1	3/2008	Hogan et al.
8,838,982	B2	9/2014	Carlson et al.		2008/0065555	A1	3/2008	Mullen
8,856,539	B2	10/2014	Weiss		2008/0201264	A1	8/2008	Brown et al.
8,887,308	B2	11/2014	Grecia		2008/0201265	A1	8/2008	Hewton
9,065,643	B2	6/2015	Hurry et al.		2008/0228646	A1	9/2008	Myers et al.
9,070,129	B2	6/2015	Sheets et al.		2008/0243702	A1	10/2008	Hart et al.
9,100,826	B2	8/2015	Weiss		2008/0245855	A1	10/2008	Fein et al.
9,160,741	B2	10/2015	Wentker et al.		2008/0245861	A1	10/2008	Fein et al.
9,229,964	B2	1/2016	Stevelinck		2008/0283591	A1	11/2008	Oder, II et al.
9,245,267	B2	1/2016	Singh		2008/0302869	A1	12/2008	Mullen
9,249,241	B2	2/2016	Dai et al.		2008/0302876	A1	12/2008	Mullen
9,256,871	B2*	2/2016	Anderson	G06Q 20/382	2008/0313264	A1	12/2008	Pestoni
9,280,765	B2	3/2016	Hammad		2009/0006262	A1	1/2009	Brown et al.
9,524,501	B2*	12/2016	Weber	G06Q 20/38	2009/0010488	A1	1/2009	Matsuoka et al.
9,530,137	B2	12/2016	Weiss		2009/0037333	A1	2/2009	Flitcroft et al.
9,792,611	B2*	10/2017	Hammad	G06Q 20/385	2009/0037388	A1	2/2009	Cooper et al.
9,846,861	B2*	12/2017	Weber	H04L 67/02	2009/0043702	A1	2/2009	Bennett
9,978,094	B2*	5/2018	Gaddam	G06Q 30/0637	2009/0048971	A1	2/2009	Hathaway et al.
10,255,591	B2*	4/2019	Makhotin	G06Q 20/20	2009/0106112	A1	4/2009	Dalmia et al.
10,552,834	B2*	2/2020	Dimmick	G06Q 20/382	2009/0106160	A1	4/2009	Skowronek
10,878,422	B2*	12/2020	Sheets	G06Q 20/401	2009/0134217	A1	5/2009	Flitcroft et al.
2001/0029485	A1	10/2001	Brody et al.		2009/0157555	A1	6/2009	Biffle et al.
2001/0034720	A1	10/2001	Armes		2009/0159673	A1	6/2009	Mullen et al.
2001/0054003	A1	12/2001	Chien et al.		2009/0159700	A1	6/2009	Mullen et al.
2002/0007320	A1	1/2002	Hogan et al.		2009/0159707	A1	6/2009	Mullen et al.
2002/0016749	A1	2/2002	Borecki et al.		2009/0173782	A1	7/2009	Muscato
2002/0029193	A1	3/2002	Ranjan et al.		2009/0200371	A1	8/2009	Kean et al.
2002/0035548	A1	3/2002	Hogan et al.		2009/0248583	A1	10/2009	Chhabra
2002/0073045	A1	6/2002	Rubin et al.		2009/0276347	A1	11/2009	Kargman
2002/0116341	A1	8/2002	Hogan et al.		2009/0281948	A1	11/2009	Carlson
2002/0133467	A1	9/2002	Hobson et al.		2009/0294527	A1	12/2009	Brabson et al.
2002/0147913	A1	10/2002	Lun Yip		2009/0307139	A1	12/2009	Mardikar et al.
2003/0028481	A1*	2/2003	Flitcroft	G07F 7/122 705/39	2009/0308921	A1	12/2009	Mullen
2003/0130955	A1	7/2003	Hawthorne		2009/0327131	A1	12/2009	Beenau et al.
2003/0191709	A1	10/2003	Elston et al.		2010/0008535	A1	1/2010	Abulafia et al.
2003/0191945	A1	10/2003	Keech		2010/0063895	A1*	3/2010	Dominguez
2004/0010462	A1	1/2004	Moon et al.		2010/0088237	A1	4/2010	Wankmueller
2004/0050928	A1	3/2004	Bishop et al.		2010/0094755	A1	4/2010	Kloster
2004/0059682	A1	3/2004	Hasumi et al.		2010/0106644	A1	4/2010	Annan et al.
2004/0093281	A1	5/2004	Silverstein et al.		2010/0120408	A1	5/2010	Beenau et al.
2004/0139008	A1	7/2004	Mascavage, III		2010/0133334	A1	6/2010	Vadhri
2004/0143532	A1	7/2004	Lee		2010/0138347	A1	6/2010	Chen
2004/0158532	A1	8/2004	Breck et al.		2010/0145860	A1	6/2010	Pelegero
2004/0210449	A1	10/2004	Breck et al.		2010/0161433	A1	6/2010	White
2004/0210498	A1	10/2004	Freund		2010/0185545	A1	7/2010	Royyuru et al.
2004/0232225	A1	11/2004	Bishop et al.		2010/0211505	A1	8/2010	Saunders et al.
2004/0260646	A1	12/2004	Berardi et al.		2010/0223186	A1	9/2010	Hogan et al.
2005/0037735	A1	2/2005	Coutts		2010/0228668	A1	9/2010	Hogan et al.
2005/0080730	A1	4/2005	Sorrentino		2010/0235284	A1	9/2010	Moore
2005/0108178	A1	5/2005	York		2010/0258620	A1	10/2010	Torreyson et al.
2005/0199709	A1	9/2005	Linlor		2010/0291904	A1	11/2010	Musfeldt et al.
2005/0246293	A1	11/2005	Ong		2010/0299267	A1	11/2010	Faith et al.
2005/0269401	A1	12/2005	Spitzer et al.		2010/0306076	A1	12/2010	Taveau et al.
					2010/0325041	A1	12/2010	Berardi et al.
					2011/0010292	A1	1/2011	Giordano et al.
					2011/0016047	A1	1/2011	Wu et al.
					2011/0016320	A1	1/2011	Bergsten et al.

G06Q 20/40
705/26.1

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0040640	A1	2/2011	Erikson	2012/0316992	A1	12/2012	Oborne
2011/0047076	A1	2/2011	Carlson et al.	2012/0317035	A1	12/2012	Royyuru et al.
2011/0083018	A1	4/2011	Kesanupalli et al.	2012/0317036	A1	12/2012	Bower et al.
2011/0087596	A1	4/2011	Dorsey	2013/0017784	A1	1/2013	Fisher
2011/0093397	A1	4/2011	Carlson et al.	2013/0018757	A1	1/2013	Anderson et al.
2011/0125597	A1	5/2011	Oder, II et al.	2013/0019098	A1	1/2013	Gupta et al.
2011/0153437	A1	6/2011	Archer et al.	2013/0031006	A1	1/2013	McCullagh et al.
2011/0153498	A1	6/2011	Makhotin et al.	2013/0054337	A1	2/2013	Brendell et al.
2011/0154466	A1	6/2011	Harper et al.	2013/0054466	A1	2/2013	Muscato
2011/0161233	A1	6/2011	Tieken	2013/0054474	A1	2/2013	Yeager
2011/0178926	A1	7/2011	Lindelsee et al.	2013/0081122	A1	3/2013	Svigals et al.
2011/0191244	A1	8/2011	Dai	2013/0091028	A1	4/2013	Oder, II et al.
2011/0238511	A1	9/2011	Park et al.	2013/0110658	A1	5/2013	Lyman et al.
2011/0238573	A1	9/2011	Varadarajan	2013/0111599	A1	5/2013	Gargiulo
2011/0246317	A1	10/2011	Coppinger	2013/0117185	A1	5/2013	Collison et al.
2011/0258111	A1	10/2011	Raj et al.	2013/0124290	A1	5/2013	Fisher
2011/0272471	A1	11/2011	Mullen	2013/0124291	A1	5/2013	Fisher
2011/0272478	A1	11/2011	Mullen	2013/0124364	A1	5/2013	Mittal
2011/0276380	A1	11/2011	Mullen et al.	2013/0138525	A1	5/2013	Bercaw
2011/0276381	A1	11/2011	Mullen et al.	2013/0144888	A1	6/2013	Faith et al.
2011/0276424	A1	11/2011	Mullen	2013/0145148	A1	6/2013	Shablygin et al.
2011/0276425	A1	11/2011	Mullen	2013/0145172	A1	6/2013	Shablygin et al.
2011/0295745	A1	12/2011	White et al.	2013/0159178	A1	6/2013	Colon et al.
2011/0302081	A1	12/2011	Saunders et al.	2013/0159184	A1	6/2013	Thaw
2012/0016731	A1*	1/2012	Smith G06Q 20/20 705/17	2013/0166402	A1	6/2013	Parento et al.
2012/0028609	A1	2/2012	Hruska	2013/0166456	A1	6/2013	Zhang et al.
2012/0030047	A1	2/2012	Fuentes et al.	2013/0173736	A1	7/2013	Krzeminski et al.
2012/0035998	A1	2/2012	Chien et al.	2013/0185202	A1	7/2013	Goldthwaite et al.
2012/0041881	A1	2/2012	Basu et al.	2013/0191227	A1	7/2013	Pasa et al.
2012/0047237	A1	2/2012	Arvidsson et al.	2013/0191286	A1	7/2013	Cronic et al.
2012/0066078	A1	3/2012	Kingston et al.	2013/0191289	A1	7/2013	Cronic et al.
2012/0072350	A1	3/2012	Goldthwaite et al.	2013/0198071	A1	8/2013	Jurss
2012/0078735	A1	3/2012	Bauer et al.	2013/0198080	A1	8/2013	Anderson et al.
2012/0078798	A1	3/2012	Downing et al.	2013/0200146	A1	8/2013	Moghadam
2012/0078799	A1	3/2012	Jackson et al.	2013/0204787	A1	8/2013	Dubois
2012/0095852	A1	4/2012	Bauer et al.	2013/0204793	A1	8/2013	Kerridge et al.
2012/0095865	A1	4/2012	Doherty et al.	2013/0212007	A1	8/2013	Mattsson et al.
2012/0116902	A1	5/2012	Cardina et al.	2013/0212017	A1	8/2013	Bangia
2012/0123882	A1	5/2012	Carlson et al.	2013/0212019	A1	8/2013	Mattsson et al.
2012/0123940	A1	5/2012	Killian et al.	2013/0212024	A1	8/2013	Mattsson et al.
2012/0129514	A1	5/2012	Beenau et al.	2013/0212026	A1	8/2013	Powell et al.
2012/0143767	A1	6/2012	Abadir	2013/0212666	A1	8/2013	Mattsson et al.
2012/0143772	A1	6/2012	Abadir	2013/0218698	A1	8/2013	Moon et al.
2012/0158580	A1	6/2012	Eram et al.	2013/0218769	A1	8/2013	Pourfallah et al.
2012/0158593	A1	6/2012	Garfinkle et al.	2013/0226799	A1	8/2013	Raj
2012/0173431	A1	7/2012	Ritchie et al.	2013/0226813	A1	8/2013	Voltz
2012/0185386	A1	7/2012	Salama et al.	2013/0246199	A1	9/2013	Carlson
2012/0197807	A1	8/2012	Schlesser et al.	2013/0246202	A1	9/2013	Tobin
2012/0203664	A1	8/2012	Torossian et al.	2013/0246203	A1	9/2013	Laracey
2012/0203666	A1	8/2012	Torossian et al.	2013/0246258	A1	9/2013	Dessert
2012/0215688	A1	8/2012	Musser et al.	2013/0246259	A1	9/2013	Dessert
2012/0215696	A1	8/2012	Salonen	2013/0246261	A1	9/2013	Purves et al.
2012/0221421	A1	8/2012	Hammad	2013/0246267	A1	9/2013	Tobin
2012/0226582	A1	9/2012	Hammad	2013/0254028	A1	9/2013	Salci
2012/0231844	A1	9/2012	Coppinger	2013/0254052	A1	9/2013	Royyuru et al.
2012/0233004	A1	9/2012	Bercaw	2013/0254102	A1	9/2013	Royyuru
2012/0234912	A1*	9/2012	Yankovich G06Q 20/36 705/41	2013/0254117	A1	9/2013	von Mueller et al.
2012/0246070	A1	9/2012	Vadhri	2013/0262296	A1	10/2013	Thomas et al.
2012/0246071	A1	9/2012	Jain et al.	2013/0262302	A1	10/2013	Lettow et al.
2012/0246079	A1	9/2012	Wilson et al.	2013/0262315	A1	10/2013	Hruska
2012/0265631	A1	10/2012	Cronic et al.	2013/0262316	A1	10/2013	Hruska
2012/0271697	A1*	10/2012	Gilman G06Q 20/387 705/26.35	2013/0262317	A1	10/2013	Collinge et al.
2012/0271770	A1	10/2012	Harris et al.	2013/0275300	A1	10/2013	Killian et al.
2012/0297446	A1	11/2012	Webb et al.	2013/0275307	A1	10/2013	Khan
2012/0300932	A1	11/2012	Cambridge et al.	2013/0275308	A1	10/2013	Paraskeva et al.
2012/0303425	A1*	11/2012	Katzin G06Q 20/4016 705/16	2013/0282502	A1	10/2013	Jooste
2012/0303503	A1	11/2012	Cambridge et al.	2013/0282575	A1	10/2013	Mullen et al.
2012/0303961	A1	11/2012	Kean et al.	2013/0282588	A1	10/2013	Hruska
2012/0304273	A1	11/2012	Bailey et al.	2013/0297501	A1	11/2013	Monk et al.
2012/0310725	A1	12/2012	Chien et al.	2013/0297504	A1	11/2013	Nwokolo et al.
2012/0310831	A1	12/2012	Harris et al.	2013/0297508	A1	11/2013	Belamant
				2013/0304649	A1	11/2013	Cronic et al.
				2013/0308778	A1	11/2013	Fosmark et al.
				2013/0311382	A1	11/2013	Fosmark et al.
				2013/0317982	A1	11/2013	Mengerink et al.
				2013/0332344	A1	12/2013	Weber
				2013/0339253	A1	12/2013	Sincai
				2013/0346305	A1	12/2013	Mendes
				2013/0346314	A1	12/2013	Mogollon et al.

(56)	References Cited	2015/0360131 A1*	12/2015	Tsuchida	A63F 13/216 463/29
	U.S. PATENT DOCUMENTS	2016/0019536 A1*	1/2016	Ortiz	G06Q 20/36 705/67
2014/0007213 A1	1/2014 Sanin et al.	2016/0028550 A1	1/2016	Gaddam et al.	
2014/0013106 A1	1/2014 Redpath	2016/0042263 A1	2/2016	Gaddam et al.	
2014/0013114 A1	1/2014 Redpath	2016/0065370 A1	3/2016	Le Saint et al.	
2014/0013452 A1	1/2014 Aissi et al.	2016/0092696 A1	3/2016	Guglani et al.	
2014/0019352 A1	1/2014 Shrivastava	2016/0092870 A1*	3/2016	Salama	G06Q 20/3226 705/44
2014/0025581 A1	1/2014 Calman	2016/0092872 A1	3/2016	Prakash et al.	
2014/0025585 A1	1/2014 Calman	2016/0103675 A1	4/2016	Aabye et al.	
2014/0025958 A1	1/2014 Calman	2016/0119296 A1	4/2016	Laxminarayanan et al.	
2014/0032417 A1	1/2014 Mattsson	2016/0140545 A1	5/2016	Flurscheim et al.	
2014/0032418 A1	1/2014 Weber	2016/0148197 A1	5/2016	Dimmick	
2014/0040137 A1	2/2014 Carlson et al.	2016/0148212 A1	5/2016	Dimmick	
2014/0040139 A1	2/2014 Brudnicki et al.	2016/0171479 A1	6/2016	Prakash et al.	
2014/0040144 A1	2/2014 Plomske et al.	2016/0173483 A1	6/2016	Wong et al.	
2014/0040145 A1	2/2014 Ozvat et al.	2016/0203352 A1*	7/2016	Marsico	G06K 7/1417 235/375
2014/0040628 A1	2/2014 Fort et al.	2016/0210628 A1	7/2016	McGuire	
2014/0041018 A1	2/2014 Bomar et al.	2016/0218875 A1	7/2016	Le Saint et al.	
2014/0046853 A1	2/2014 Spies et al.	2016/0224976 A1	8/2016	Basu et al.	
2014/0047551 A1	2/2014 Nagasundaram et al.	2016/0224977 A1	8/2016	Sabba et al.	
2014/0052532 A1	2/2014 Tsai et al.	2016/0232527 A1	8/2016	Patterson	
2014/0052620 A1	2/2014 Rogers et al.	2016/0239842 A1	8/2016	Cash et al.	
2014/0052637 A1	2/2014 Jooste et al.	2017/0046696 A1	2/2017	Powell et al.	
2014/0068706 A1	3/2014 Aissi	2017/0103387 A1	4/2017	Weber	
2014/0074637 A1	3/2014 Hammad	2017/0220818 A1	8/2017	Nagasundaram et al.	
2014/0108172 A1	4/2014 Weber et al.	2017/0228723 A1	8/2017	Taylor et al.	
2014/0114857 A1	4/2014 Griggs et al.				
2014/0122331 A1*	5/2014 Vaish	G06Q 20/3674 705/41			
2014/0143137 A1	5/2014 Carlson				
2014/0164243 A1	6/2014 Aabye et al.				
2014/0188586 A1	7/2014 Carpenter et al.				
2014/0195425 A1*	7/2014 Campos	G06K 19/06206 705/41			
2014/0294701 A1	10/2014 Dai et al.				
2014/0297534 A1	10/2014 Patterson				
2014/0310183 A1	10/2014 Weber				
2014/0324690 A1	10/2014 Allen et al.				
2014/0330721 A1	11/2014 Wang				
2014/0330722 A1	11/2014 Laxminarayanan et al.				
2014/0331265 A1	11/2014 Mozell et al.				
2014/0337236 A1	11/2014 Wong et al.				
2014/0344153 A1	11/2014 Raj et al.				
2014/0372308 A1	12/2014 Sheets				
2015/0019443 A1	1/2015 Sheets et al.				
2015/0032625 A1	1/2015 Dill et al.				
2015/0032626 A1	1/2015 Dill et al.				
2015/0032627 A1	1/2015 Dill et al.				
2015/0046338 A1	2/2015 Laxminarayanan et al.				
2015/0046339 A1	2/2015 Wong et al.				
2015/0052064 A1	2/2015 Karpenko et al.				
2015/0081544 A1	3/2015 Schulz et al.				
2015/0088756 A1	3/2015 Makhotin et al.				
2015/0106239 A1	4/2015 Gaddam et al.				
2015/0112870 A1	4/2015 Nagasundaram et al.				
2015/0112871 A1	4/2015 Kumnick				
2015/0120472 A1	4/2015 Aabye et al.				
2015/0127529 A1	5/2015 Makhotin et al.				
2015/0127547 A1	5/2015 Powell et al.				
2015/0140960 A1	5/2015 Powell et al.				
2015/0142673 A1	5/2015 Nelsen et al.				
2015/0161597 A1	6/2015 Subramanian et al.				
2015/0178724 A1*	6/2015 Ngo	G06Q 20/3672 705/71			
2015/0180836 A1	6/2015 Wong et al.				
2015/0186864 A1	7/2015 Jones et al.				
2015/0193222 A1	7/2015 Pirzadeh et al.				
2015/0195133 A1	7/2015 Sheets et al.				
2015/0199679 A1	7/2015 Palanisamy et al.				
2015/0199689 A1	7/2015 Kumnick et al.				
2015/0220917 A1	8/2015 Aabye et al.				
2015/0269566 A1	9/2015 Gaddam et al.				
2015/0312038 A1	10/2015 Palanisamy				
2015/0319158 A1	11/2015 Kumnick				
2015/0332262 A1	11/2015 Lingappa				
2015/0356560 A1	12/2015 Shastry et al.				
				FOREIGN PATENT DOCUMENTS	
		WO	0135304 A9	5/2002	
		WO	2004042536 A2	5/2004	
		WO	2006113834 A2	10/2006	
		WO	2009032523 A1	3/2009	
		WO	2010078522 A1	7/2010	
		WO	2012068078 A2	5/2012	
		WO	2012098556 A1	7/2012	
		WO	2012142370 A2	10/2012	
		WO	2012167941 A1	12/2012	
		WO	2013048538 A1	4/2013	
		WO	2013056104 A1	4/2013	
		WO	2013119914 A1	8/2013	
		WO	2013179271 A2	12/2013	
				OTHER PUBLICATIONS	
				U.S. Appl. No. 15/265,282 , "U.S. Patent Application No.", Self-Cleaning Token Valut, Sep. 14, 2016, 52 pages.	
				U.S. Appl. No. 15/462,658 , "U.S. Patent Application No.", Replacing Token On a Multi-Token User Device, Mar. 17, 2017, 58 pages.	
				U.S. Appl. No. 61/738,832 , "U.S. Provisional Application No.", Management of Sensitive Data, Dec. 18, 2012, 22 pages.	
				U.S. Appl. No. 61/751,763 , "U.S. Provisional Application No.", Payments Bridge, Jan. 11, 2013, 64 pages.	
				U.S. Appl. No. 61/892,407 , "U.S. Provisional Application No.", Issuer Over-the-Air Update Method and System, Oct. 17, 2013, 28 pages.	
				U.S. Appl. No. 61/894,749 , "U.S. Provisional Application No.", Methods and Systems for Authentication and Issuance of Tokens in a Secure Environment, Oct. 23, 2013, 67 pages.	
				U.S. Appl. No. 61/926,236 , "U.S. Provisional Application No.", Methods and Systems for Provisioning Mobile Devices With Payment Credentials and Payment Token Identifiers, Jan. 10, 2014, 51 pages.	
				U.S. Appl. No. 62/000,288 , "U.S. Provisional Application No.", Payment System Canonical Address Format, May 19, 2014, 58 pages.	
				U.S. Appl. No. 62/003,717 , "U.S. Provisional Application No.", Mobile Merchant Application, May 28, 2014, 58 pages.	
				U.S. Appl. No. 62/024,426 , "U.S. Provisional Application No.", Secure Transactions Using Mobile Devices, Jul. 14, 2014, 102 pages.	

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. No. 62/037,033 , “U.S. Provisional Application No.”, Sharing Payment Token, Aug. 13, 2014, 36 pages.

U.S. Appl. No. 62/038,174 , “U.S. Provisional Application No.”, Customized Payment Gateway, Aug. 15, 2014, 42 pages.

U.S. Appl. No. 62/042,050 , “U.S. Provisional Application No.”, Payment Device Authentication and Authorization System, Aug. 26, 2014, 120 pages.

U.S. Appl. No. 62/053,736 , “U.S. Provisional Application No.”, Completing Transactions Without a User Payment Device, Sep. 22, 2014, 31 pages.

U.S. Appl. No. 62/054,346 , “U.S. Provisional Application No.”, Mirrored Token Vault, Sep. 23, 2014, 38 pages.

U.S. Appl. No. 62/103,522 , “U.S. Provisional Application No.”, Methods and Systems for Wallet Provider Provisioning, Jan. 14, 2015, 39 pages.

U.S. Appl. No. 62/108,403 , “U.S. Provisional Application No.”, Wearables With NFC HCE, Jan. 27, 2015, 32 pages.

U.S. Appl. No. 62/117,291 , “U.S. Provisional Application No.”, Token and Cryptogram Using Transaction Specific Information, Feb. 17, 2015, 25 pages.

U.S. Appl. No. 62/128,709 , “U.S. Provisional Application No.”, Tokenizing Transaction Amounts, Mar. 5, 2015, 30 pages.

White, “How Computers Work”, Que Publishing, 7th Edition, 2003.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

RESOURCE PROVIDER ACCOUNT TOKEN PROVISIONING AND PROCESSING

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a divisional application of U.S. application Ser. No. 15/019,842, filed Feb. 9, 2016, which is herein incorporated by reference in its entirety for all purposes.

BACKGROUND

As digital wallets gain increasing popularity and wide spread use, users would like to provision various types of accounts on their digital wallets. For example, users may wish to provision resource provider accounts on their digital wallets. A resource provider account may be an account that is only valid at (e.g. can be used at) the resource provider that created the account. For example, a merchant-specific account is an example of a resource provider account.

However, resource provider accounts (e.g., gift card accounts, prepaid accounts, entity-specific accounts, etc.) are susceptible to being compromised and used fraudulently. This poses a security risk for the resource provider accounts. In addition, the resource provider accounts cannot currently be provisioned into digital wallets.

Embodiments of the present invention solve these problems and other problems, individually and collectively.

BRIEF SUMMARY

Embodiments of the present invention enable issuing a token for a resource provider account specific to (e.g. exclusively valid at) the resource provider issuing the account. A resource provider processor system interfaces with a resource provider computer to validate account eligibility for tokenization upon receiving a token request message from a token requestor. If the account is eligible for token generation (e.g. tokenization), the resource provider processor system generates a universal identifier corresponding to the identifier associated with the resource provider account and returns the universal identifier to the token requestor. The token requestor may send a token request message to a token issuer for obtaining a token using the universal identifier. Accordingly, the universal account identifier can be used to provision a token into a digital wallet. According to various embodiments, one or more limitations may be associated with the resource provider account (e.g. transaction limits or restrictions). In such embodiments, the limitations may be provided to the token issuer to be associated with the generated token. The token may be subject to the same limitations associated with the resource provider account.

Transactions using the token may be processed by the resource provider processor system acting as an account issuer. That is, when a transaction processing system receives a transaction request including the token, the transaction processing system may contact the resource provider processor that issued the universal identifier to process the transaction.

Embodiments provide a method including receiving, by a resource provider processor system, a token request message from a token requestor. The token request message includes a first identifier associated with a resource provider account. The resource provider processor system identifies a resource provider computer associated with the first identifier. The

resource provider processor system validates the first identifier with the resource provider computer. In some embodiments, the resource provider processor system may determine that the resource provider account is eligible for tokenization. The resource provider processor system generates a universal identifier associated with the resource provider account, the universal identifier identifying the resource provider account and the resource provider processor system. In some embodiments, a format of the universal identifier is attributed to the resource provider processor system. A format of the first identifier included in the token request message may be different than the format of the universal identifier generated by the resource provider processor system. The method further includes transmitting, by the resource provider processor system, the universal identifier to the token requestor. The token requestor requests a token for the universal identifier from a token issuer server computer. In some embodiments, the token issuer server computer includes a universal account processor server computer. In some embodiments, a mapping between the universal identifier and the first identifier associated with the resource provider account may be stored at a token vault.

In some embodiments, the method may also include determining, by the resource provider processor system, one or more restrictions associated with the resource provider account; and transmitting, by the resource provider processor system, the one or more restrictions to the token issuer server computer such that the token generated by the token issuer server computer is associated with the one or more restrictions. According to various embodiments, the resource provider processor system may contact the resource provider computer to inactivate the first identifier associated with the resource provider account.

In some embodiments, the resource provider processor system may receive identification and verification data associated with account holder of the resource provider account. The resource provider processor system may verify an identity of the account holder using the identification and verification data.

Embodiments may also provide a system including a processor and a computer readable medium coupled to the processor. The computer readable medium comprises code, executable by the processor, to implement the above-described method.

Embodiments further provide a method including receiving, by a token issuer server computer, a token request message including a first identifier from a token requestor. The token issuer server computer determines that the first identifier is associated with a resource provider account. The token issuer server computer transmits a universal identifier request to a resource provider processor system. The universal identifier request includes the first identifier and requests a universal identifier corresponding to the first identifier. The token issuer server computer receives the universal identifier corresponding to the first identifier from the resource provider processor system. The method also includes generating, by the token issuer server computer, a token for the universal identifier. The token represents the universal identifier. The token issuer server computer stores a mapping between the token and the universal identifier at a token vault. The method further includes transmitting, by the token issuer server computer, the token to the token requestor.

In some embodiments, the token issuer server computer includes an universal account processing server computer. In such embodiments, the method further includes receiving, at the universal account processing server computer, a trans-

action request including the token. The universal account processing server computer retrieves the universal identifier represented by the token from the token vault. The universal account processing server modifies the transaction request to include the universal identifier represented by the token, and transmits the modified transaction request including the universal identifier to the resource provider processor system for processing.

In some embodiments, the token issuer server computer may receive one or more restrictions associated with the resource provider account. The token issuer server computer may store the one or more restrictions along with the generated token at the token vault such that the generated token is subject to the one or more restrictions. In embodiments where the token issuer server computer includes the universal account processing server computer, the universal account processing server computer may determine the one or more restrictions associated with the resource provider account. The universal account processing server computer may apply the restrictions to the resource provider account.

These and other embodiments are described in further detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram including a token generation system for resource provider account(s) in accordance with embodiments of the present application.

FIG. 2 shows a block diagram of a system for processing a transaction using a token associated with a resource provider account in accordance with embodiments of the present application.

FIG. 3 shows a block diagram of an exemplary resource provider processor system in accordance with some embodiments of the invention.

FIG. 4 illustrates a system and a flow diagram for generating a token associated with a resource provider account in accordance with some embodiments of the invention.

FIG. 5 illustrates another system and a flow diagram for generating a token associated with a resource provider account in accordance with some embodiments of the invention.

FIG. 6 shows an exemplary computer system according to embodiments of the present invention.

DETAILED DESCRIPTION

Embodiments are directed to methods, apparatuses, computer readable media and systems for issuing tokens for identifiers associated with a resource provider-specific account. The resource provider account may be exclusively valid at the resource provider that issued the account. For example, a resource provider account may be a closed-loop account, e.g. a retail store account. Upon receiving a token request message from a token requestor, a resource provider processor system interfaces with a resource provider computer to validate account eligibility for tokenization. If the account is eligible for token generation (e.g. tokenization), the resource provider processor system generates a universal identifier corresponding to the identifier associated with the resource provider account and returns the universal identifier to the token requestor. The token requestor may send a token request message to a token issuer system for obtaining a token using the universal identifier. Accordingly, the universal account identifier can be used to provision a resource provider account into a digital wallet. Transactions using the token may be processed with the resource provider proces-

sor system acting as an account issuer. That is, when a transaction processing system receives a transaction request including the token, the transaction processing system may contact the resource provider processor that issued the universal identifier to process the transaction.

According to various embodiments, one or more limitations (e.g. transaction limits or restrictions) may be associated with the resource provider account. In such embodiments, the limitations may be provided to the token issuer to be associated with the generated token. The token may be subject to the same limitations associated with the resource provider account.

In an exemplary embodiment, the resource provider may be a merchant. Accordingly, the resource provider account may be a user account at the merchant. Multiple merchants may work with a processing system (e.g. the resource provider processor system) to process transactions using the merchant accounts. When the user wishes to provision the user's merchant account onto the user's mobile device, the user needs to provide a valid account identifier (e.g. a universal identifier) to a token issuer system. Conventionally, tokens are not issued for merchant-specific accounts, e.g. closed-loop accounts. Thus, the user needs to obtain a valid account identifier (e.g. a universal identifier, an open-loop account identifier) associated with the user's merchant account.

The user may contact the processing system to request a token for the user's merchant account. For example, the user may send a token request message including an account identifier identifying the user's merchant account to the processing system. The processing system may identify the specific merchant based on the format of the account identifier provided in the token request message. The processing system may contact the merchant to ensure that the user's merchant account is eligible for tokenization (e.g. token generation). Upon confirming eligibility, the processing system may generate a universal identifier for the user's merchant account. A format of the universal identifier may indicate that the universal identifier is generated by the processing system as opposed to issuers that conventionally generate the universal identifiers. The processing system may return the universal identifier to the user or may contact a token issuer system to request a token with the universal identifier. If the processing system receives the token from a token issuer on behalf of the user, the processing system provides the token to the user. The user's merchant account may then be provisioned on the user's digital wallet.

Continuing with the foregoing exemplary embodiment, at a later time, the user initiates a transaction using the token associated with the merchant account. When the transaction is initiated using the user's digital wallet, a transaction request message including the token may be sent to a transaction processing system. The transaction processing system may process the transaction request message and identify that the token is associated with a merchant account. The transaction processing system may also identify that the universal account identifier represented by the token is issued by the resource provider processor system. Accordingly, the resource provider processor system may act as an account issuer for the purposes of this transaction. The transaction processing system may interact with the resource provider processor system to process the transaction request initiated using the token.

Before discussing specific embodiments and examples, some descriptions of terms used herein are provided below.

As used herein, a "user device" may comprise any suitable electronic device that may be transported and/or oper-

ated by a user, which may also provide remote communication capabilities to a network. Examples of remote communication capabilities include using a mobile phone (wireless) network, wireless data network (e.g. 3G, 4G or similar networks), Wi-Fi, Wi-Max, or any other communication medium that may provide access to a network such as the Internet or a private network. Examples of user devices include mobile phones (e.g. cellular phones), PDAs, tablet computers, net books, laptop computers, personal music players, hand-held specialized readers, game consoles, etc. Further examples of user devices may also include wearable devices, such as smart watches, fitness bands, ankle bracelets, rings, earrings, etc., as well as automobiles with remote communication capabilities. A user device may comprise any suitable hardware and software for performing such functions, and may also include multiple devices or components (e.g. when a device has remote access to a network by tethering to another device—i.e. using the other device as a modem—both devices taken together may be considered a single mobile device).

A “server computer” may typically be a powerful computer or cluster of computers. For example, the server computer can be a large mainframe, a minicomputer cluster, or a group of servers functioning as a unit.

A “user” may include an individual or an entity that uses a system. A user may be associated with one or more accounts and/or user devices. In some cases, the user may also be referred to as an account holder, or consumer.

A “wallet” may refer to a digital wallet or an e-wallet which is a software application that allows an individual to conduct electronic commerce transactions. A digital wallet may store payment credentials, bank account information, one or more digital wallet identifiers and/or the like and can be used in a variety of transactions, such as but not limited to eCommerce, social networks, money transfer/personal payments, mobile commerce, proximity payments, and/or the like for retail purchases, digital goods purchases, utility payments, transferring funds between users, and/or the like. A digital wallet may be designed to streamline the purchase and payment process. A digital wallet may also store transaction records (e.g., electronic receipts).

A “credential” may be any suitable information that serves as reliable evidence of worth, ownership, identity, or authority. A credential may be a string of numbers, letters, or any other suitable characters that may be present or contained in any object or document that can serve as confirmation.

A “resource provider” may be an entity that can provide a resource such as goods, services, information, and/or access. Examples of a resource provider includes merchants, access devices, secure data access points, etc. A merchant may typically be an entity that engages in transactions and can sell goods or services, or provide access to goods or services.

“Account identifier” or “identifier” may include any suitable information associated with an account (e.g. a payment account, a resource access account, etc. and/or a device associated with the account). Such information may be directly related to the account or may be derived from information related to the account. Examples of account information may include an account number (e.g. a primary account number (PAN)), user name, expiration date, CVV (card verification value), dCVV (dynamic card verification value), CVV2 (card verification value 2), CVC3 card verification values, etc. CVV2 is generally understood to be a static verification value associated with a payment device. CVV2 values are generally visible to a user (e.g., a con-

sumer), whereas CVV and dCVV values are typically embedded in memory or authorization request messages and are not readily known to the user (although they are known to the issuer and payment processors). Account identifiers may include resource provider specific account identifiers or universal identifiers. A resource provider specific account identifier may identify an account issued by a resource provider computer. A universal identifier may identify an account issued by account issuers (e.g. open loop issuers). A universal identifier may have a different format than a resource provider specific account identifier. An issuer of the account may be identified by analyzing the format of the account identifier. In some embodiments, a universal identifier associated with a resource provider specific account may be generated by a resource provider processor system. In such embodiments, the resource provider processor system may act as the issuer for the generated universal identifier.

A “digital wallet” can include an electronic device that allows an individual to conduct electronic commerce transactions. A digital wallet may store user profile information, account credentials, one or more digital wallet identifiers and/or the like and can be used in a variety of transactions, such as but not limited to eCommerce, social networks, money transfer/personal payments, mobile commerce, proximity payments, access transactions, and/or the like. A digital wallet may be designed to streamline the transaction process. A digital wallet may allow the user to load one or more account identifiers onto the digital wallet so as to conduct a transaction without having to enter an account identifier or present a physical identification.

A “digital wallet provider” may include an entity, such as an issuing entity or third party service provider, that issues a digital wallet to a user that enables the user to conduct transactions. A digital wallet provider may provide stand-alone user-facing software applications that store account numbers, or representations of the account numbers (e.g., tokens), on behalf of an account holder (or other user) to facilitate transactions at more than one unrelated transacting entity, perform person-to-person transactions, or load value into the digital wallet. A digital wallet provider may enable a user to access its account via a personal computer, mobile device or access device.

A “token” may be a substitute value for a credential. A token may be a string of numbers, letters, or any other suitable characters. Examples of tokens include payment tokens, access tokens, personal identification tokens, etc. For example, a payment token may include an identifier for a payment account that is a substitute for an account identifier, such as a primary account number (PAN). For example, a token may include a series of alphanumeric characters that may be used as a substitute for an original account identifier. For example, a token “4900 0000 0000 0001” may be used in place of a PAN “4147 0900 0000 1234.” In some embodiments, a token may be “format preserving” and may have a numeric format that conforms to the account identifiers used in existing transaction processing networks (e.g., ISO 8583 financial transaction message format). In some embodiments, a token may be used in place of a PAN to initiate, authorize, settle or resolve a transaction or represent the original credential in other systems where the original credential would typically be provided. In some embodiments, a token value may be generated such that the recovery of the original PAN or other account identifier from the token value may not be computationally derived. Further, in some embodiments, the token format may be configured to

allow the entity receiving the token to identify it as a token and recognize the entity that issued the token.

A “token provider” or “token service system” can include a system that that services tokens. In some embodiments, a token service system can facilitate requesting, determining (e.g., generating) and/or issuing tokens, as well as maintaining an established mapping of tokens to primary account numbers (PANs) in a repository (e.g. token vault). In some embodiments, the token service system may establish a token assurance level for a given token to indicate the confidence level of the token to PAN binding. The token service system may include or be in communication with a token vault where the generated tokens are stored. The token service system may support token processing of transactions submitted using tokens by de-tokenizing the token to obtain the actual PAN. In some embodiments, a token service system may include a tokenization computer alone, or in combination with other computers such as a transaction processing system.

A “token request message” may be an electronic message for requesting a token. A token request message may include information usable for identifying an account or digital wallet, and/or information for generating a token. For example, a token request message may include credentials, mobile device identification information (e.g. a phone number or MSISDN), a digital wallet identifier, information identifying a tokenization service provider, a merchant identifier, a cryptogram, and/or any other suitable information. Information included in a token request message can be encrypted (e.g., with an issuer-specific key). In some embodiments, a token request message may be formatted as an authorization request message (e.g., an ISO 8583 message format). In some embodiments, the token request message may include a flag or other indicator specifying that the message is a token request message.

A “token response message” may be a message that responds to a token request. A token response message may include an indication that a token request was approved or denied. A token response message may also include a token, mobile device identification information (e.g. a phone number or MSISDN), a digital wallet identifier, information identifying a tokenization service provider, a merchant identifier, a cryptogram, and/or any other suitable information. Information included in a token response message can be encrypted (e.g., with an issuer-specific key). In some embodiments, a token response message may be formatted as an authorization response message (e.g., an ISO 8583 message format). In some embodiments, the token response message may include a flag or other indicator specifying that the message is a token response message.

An “acquirer” may typically be a business entity (e.g., a commercial bank) that has a business relationship with a particular merchant or other entity. Some entities can perform both issuer and acquirer functions. Some embodiments may encompass such single entity issuer-acquirers. An acquirer may operate an acquirer computer, which can also be generically referred to as a “transport computer”.

An “authorizing entity” may be an entity that authorizes a request. Examples of an authorizing entity may be an issuer, a governmental agency, a document repository, an access administrator, etc. An “issuer” may typically refer to a business entity (e.g., a bank) that maintains an account for a user. An issuer may also issue credentials stored on a user device, such as a cellular telephone, smart card, tablet, or laptop to the consumer.

An “authorization request message” may be an electronic message that requests authorization for a transaction. In

some embodiments, it is sent to a transaction processing computer and/or an issuer of an account to request authorization for a transaction. An authorization request message according to some embodiments may comply with ISO 8583, which is a standard for systems that exchange electronic transaction information associated with a payment made by a user using a payment device or payment account. The authorization request message may include an issuer account identifier that may be associated with an account. An authorization request message may also comprise additional data elements corresponding to “identification information” including, by way of example only: a service code, a CW (card verification value), a dCVV (dynamic card verification value), an account number, a token, a user name, an expiration date, etc. An authorization request message may also comprise “transaction information,” such as any information associated with a current transaction, such as the transaction amount, transacting entity identifier, transacting entity location, acquirer bank identification number (BIN), card acceptor ID, information identifying items being purchased, etc., as well as any other information that may be utilized in determining whether to identify and/or authorize a transaction.

An “authorization response message” may be a message that responds to an authorization request. In some cases, it may be an electronic message reply to an authorization request message generated by an account issuing institution or a transaction processing computer. The authorization response message may include, by way of example only, one or more of the following status indicators: Approval—transaction was approved; Decline—transaction was not approved; or Call Center—response pending more information. The authorization response message may also include an authorization code, which may be a code that an account issuing entity returns in response to an authorization request message in an electronic message (either directly or through the transaction processing computer) to the transacting entity that indicates approval of the transaction. The code may serve as proof of authorization. As noted above, in some embodiments, a transaction processing computer may generate or forward the authorization response message to the transacting entity.

Embodiments enable provisioning a resource provider account on a digital wallet. When the user of the resource provider account wishes to provision the resource provider account on the digital wallet, the digital wallet may send an account identifier to a resource provider processor system to request the provisioning of the account on the digital wallet. The resource provider processor system may analyze the account identifier and identify the resource provider that issued the resource provider account. The resource provider processor system may send a status request message to the resource provider computer to ensure that the resource provider account is eligible for tokenization and/or for being provisioned on user’s digital wallet. Based on the response received from the resource provider computer, the resource provider processor system may generate a universal account identifier for the resource provider account. That is, the resource provider processor system may become an issuer or act as a proxy issuer for the universal account identifier. In some embodiments, the resource provider processor system may send the universal account identifier to the user. The user may then request a token from a token issuer computer using the universal account identifier. Alternatively, the resource provider processor system may contact the token issuer computer to request the token for the universal account identifier and may return the token to the user.

FIG. 1 shows a block diagram including a token generation system **100** for resource provider account(s) in accordance with embodiments of the present application. The token generation system includes a resource provider processor system **125**, a token issuer computer **140** in communication with a token vault **150**, and a resource provider computer **130**.

The resource provider processor system **125** may be an entity that processes transactions using account(s) issued by the resource provider(s) computer **130**. In some embodiments, the accounts issued by the resource provider computer **130** may be “closed-loop” accounts. A closed-loop account may only be used with the resource provider of that account. For example, an account generated by a specific merchant or service provider may be a closed-loop account where the user may conduct transactions using the account only with the merchant or the service provider.

One or more users **110**, **120** may be in communication with the resource provider processor system **125** to request the provisioning of their resource provider account(s) **112**, **114**, **122**, **124** on their user devices. For example, the resource provider processor system **125** may receive an account provisioning request message or a token request message from the user **110** or **120**. The account provisioning request message or a token request message may include an account identifier identifying a resource provider account **112**, **114** of the user **110** (and/or resource provider account **122**, **124** of the user **120**).

In some embodiments, the resource provider processor system **125** may also receive identification and verification data from the user **110** or **120**. The identification and verification data may be associated with account holder of the resource provider account (e.g. user **110** or **120**). The resource provider processor system **125** may verify an identity of the user **110** or **120** using the identification and verification data.

Upon receiving the provisioning request message or a token request message, the resource provider processor system **125** may identify the resource provider computer **130** that issued the resource provider account. The resource provider processor system **125** may contact the resource provider computer **130** to request the status of the resource provider account. For example, if the account is a payment account, the resource provider processor system **125** may request the balance on the payment account. Alternatively, if the account is an access account, the resource provider processor system **125** may ensure that the account is still active or belongs to an active user of the account. Based on the status of the resource provider account, the resource provider processor system **125** may determine that the resource provider account is eligible for tokenization. The resource provider processor system **125** may then generate a universal account identifier identifying the resource provider account.

A universal account identifier may have a different format than the account identifier generated by the resource provider computer **130**. For example, the universal account identifier may be globally recognized. An exemplary universal account identifier may be a 16-digit primary account number (PAN) such as 4147 0900 0000 1234. The universal account identifier may be used for processing transactions by entities other than the resource provider computer **130**.

In some embodiments, the resource provider processor system **125** may send a token request message including the universal account identifier to the token issuer computer **140**. The token issuer computer **140** may generate a token corresponding to the universal account identifier associated

with the resource provider account of the user. The token issuer computer **140** may store a mapping between the token and the universal account identifier in the token vault **150**. The token issuer computer **140** may return the token to the resource provider processor system **125**. The resource provider processor system **125** may send the token to the user device of the user **110**, **120**.

In other embodiments, the resource provider processor system **125** may send the universal account identifier to the user **110**, **120**. The user **110**, **120** may then send the provisioning request message or the token request message including the universal account identifier to the token issuer computer **140**. The token issuer computer **140** may generate a token corresponding to the universal account identifier associated with the resource provider account **112**, **114** of the user **110** (or resource provider account **122**, **124** of the user **120**). The token issuer computer **140** may store a mapping between the token and the universal account identifier in the token vault **150**. The token issuer computer **140** may return the token to the user device of the user **110**, **120**.

When the token is returned to the user device, the resource provider account may be provisioned on the user device. The user may then initiate a transaction using the token. FIG. 2 shows a block diagram of a system **200** for processing a transaction using a token associated with a resource provider account in accordance with embodiments of the present application. The system **200** includes a user **110**, a transacting entity computer **210**, an acquirer computer **220**, a universal account processor system **230**, a resource provider processor system **125**, and a token vault **150**. An acquirer may operate the acquirer computer **220**. An “acquirer” is typically a business entity that has a business relationship with a particular merchant or other entity.

The system **200** comprises a user **110** who may operate a user device. The user **110** may use the user device to conduct a transaction (e.g., a payment transaction) at a transacting entity computer **210**. The transacting entity computer **210** may be connected to an acquirer computer **220**. The acquirer computer **220** may be connected to the resource provider processor system **125** via the universal account processor system **230**. Of course, some or all of these entities depicted as connected may be connected across one or more communication networks or may be directly connected.

A “transacting entity” may typically be an entity that engages in transactions and may sell goods and/or services. A “resource provider” may typically refer to a business entity (e.g., a bank, a merchant, an online portal, an employer, an access control system, etc.) that maintains accounts for users and may issue credentials to be stored on the user device (e.g., a cellular telephone, smart card, tablet, laptop, wearable computing devices, etc.) of the user **110**. The user device may interact with the transacting entity computer **210** (e.g., via the Internet to access a website or utilize an application provided by transacting entity computer **210**) to initiate and/or conduct a transaction. Each of the entities (e.g., transacting entity computer **210**, acquirer computer **220**, universal account processor system **230**, resource provider processor system **125**, and token vault **150**) may comprise one or more computer apparatuses to enable communications or to perform one or more of the functions described herein.

The universal account processor system **230** may include data processing subsystems, networks, and operations used to support and deliver certificate authority services, authorization services, exception file services, and clearing and settlement services. An exemplary universal account processor system **230** may include a payment processing net-

work such as VisaNet™. VisaNet™, in particular, includes a VIP system (Visa Integrated Payments system) that processes authorization requests and a Base II system that performs clearing and settlement services. In some embodiments, the universal account processor system **230** may conduct transactions in substantially real-time (e.g., in fewer than a few seconds or fractions of a second). The universal account processor system **230** may include one or more server computers (as described above). The universal account processor system **230** may use any suitable wired or wireless network, including the Internet. In some embodiments, the universal account processor system **230** may be the same as or may be associated with a token issuer system.

In an exemplary purchase transaction, the user **110** purchases a good or service at from a transacting entity using a user device (e.g., a mobile phone). The user device can interact with the transacting entity computer **210**. For example, the user **110** may tap the user device against an NFC reader coupled to the transacting entity computer **210** to present the token stored on the user device to the transacting entity computer **210** (step **1**). Alternatively, the user **110** may provide credentials to the transacting entity electronically, such using a digital wallet or in through an online transaction.

To cause the transaction to be performed, an authorization request message is generated by the transacting entity computer **210** and is forwarded to the acquirer computer **220** (step **2**). Such an “authorization request message” may be an electronic message that is sent to a universal account processor system **230** and/or an resource provider processor system **125** of an account used in the transaction to request authorization for the transaction. An authorization request message, according to some embodiments, may comply with a message type defined by the International Organization for Standardization (ISO) 8583 standard, which is a standard for systems that exchange electronic transaction information associated with payments made by users using a payment account. The authorization request message may include the token provided by the user **110** to the transacting entity computer **210**. An authorization request message may also comprise additional data elements corresponding to “identification information” including, by way of example only: a service code, a CW (card verification value), a dCVV (dynamic card verification value), an expiration date, etc. An authorization request message may also include “transaction information,” such as any information associated with a current transaction, such as the transaction amount, transacting entity identifier, transacting entity location, etc., as well as any other information that may be utilized in determining whether to identify and/or authorize a transaction.

After receiving the authorization request message, the acquirer computer **220** will send the authorization request message to the universal account processor system **230** (step **3**). The universal account processor system **230** may recognize that the authorization request message includes a token. The universal account processor system **230** may send the token to the token vault **150** for de-tokenization, e.g. to receive a universal account identifier corresponding to the token (step **4**). Upon receiving the universal account identifier (e.g. a 16-digit PAN) represented by the token, the universal account processor system **230** may recognize that the universal account identifier is generated by the resource provider processor system **125**. For example, the universal account processor system **230** may identify the resource provider processor system **125** based on a format of the universal account identifier, e.g. the universal account identifier

may include a symbol or alphanumeric character that is associated with or indicative of the resource provider processor system **125**. For example, the universal account identifier may be a 16-digit PAN such as 4147 0900 0000 1234. The first four digits 4147 may identify a specific resource provider processor system **125** that issued this specific PAN.

Upon receiving the universal account identifier from the token vault **150**, the universal account processor system **230** may modify the authorization request message to include the universal account number (in addition to or in lieu of the token) and forward the authorization request message to the resource provider processor system **125** (step **5**). The universal account number received from the token vault **150** may be used by the universal account processor system **230** to identify the appropriate resource provider processor system **125** for the purpose routing or processing (e.g., determining a risk of the authorization request, which may be based upon known rules of the involved resource provider) the message.

After the resource provider processor system **125** receives the authorization request message, the resource provider processor system **125** sends an authorization response message back to the universal account processor system **230** to indicate whether or not the current transaction is authorized (step **6**). An “authorization response message” may be an electronic message reply to an authorization request message generated by the universal account processor system and may comply with the ISO 8583 standard. The authorization response message may include, by way of example only, one or more of the following status indicators: Approval—transaction was approved; Decline—transaction was not approved; or Call Center—response pending more information.

The universal account processor system **230** receives the authorization response message from the resource provider processor system **125** and transmits the authorization response message back to the acquirer computer **220**. The acquirer computer **220** then sends the authorization response message back to the transacting entity computer **210**, where the transacting entity can determine whether to proceed with the transaction.

If the transaction is a financial transaction, a normal clearing and settlement process can be conducted by the universal account processor system **230** at the end of the day. A clearing process is a process of exchanging financial details between an acquirer and an issuer to facilitate posting to a user’s payment account and reconciliation of the user’s settlement position. However, it should be noted that embodiments of the invention are not limited to a single settlement process.

FIG. **3** shows a block diagram of a resource provider processor system **125** in accordance with embodiments of the present application. The resource provider processor system **125** comprises a processor **314**, a memory or storage **312**, an external communication interface **310** (e.g. a network interface), and a computer readable medium **302**.

The computer readable medium **302** may comprise an analysis module **304**, a validation module **306**, an account identifier generation module **308**, and any other suitable software module(s). The computer readable medium **201** may also comprise code, executable by the processor **314** for implementing a method comprising receiving a token request message from a token requestor, where the token request message includes a first identifier associated with a resource provider account. The method also includes identifying a resource provider computer associated with the first

13

identifier, and validating the first identifier with the resource provider computer. The method further comprises generating a universal identifier associated with the resource provider account, the universal identifier identifying the resource provider account and the resource provider processor system, and transmitting the universal identifier to the token requestor, where the token requestor requests a token for the universal identifier from a token issuer server computer.

The resource provider processor system **125** receives a token request message or a provisioning request message from a user via the external communication interface **310**. The message includes an account identifier associated with a resource provider account issued by a resource provider. The analysis module **304** may comprise code that causes the processor **314** to analyze the received account identifier to identify the resource provider that issued (e.g. created) the account identifier and/or the resource provider account identified by the account identifier. In some embodiments, the analysis module **304** may determine the resource provider based on a format of the account identifier. For example, the analysis module **304** may determine that the account identifier is associated with a given resource provider computer if the account identifier starts with (or ends with, contains at a predetermined location, etc.) a specific character.

Upon identifying the resource provider associated with the account identifier, the validation module **306** may send a message to the resource provider computer via the external communication interface **310** to determine whether the resource provider account identified by the account identifier is eligible for tokenization and/or provisioning. In some embodiments, the validation module **306** may determine whether the resource provider account is eligible for tokenization. For example, the resource provider account may be a prepaid account storing value. The validation module **306** may ensure that the account has a positive balance to determine that the account is eligible for tokenization and/or provisioning.

In some embodiments, the token request message or a provisioning request message received from the user may include user identification and verification data such as user name, address, a passcode, etc. The validation module **306** may validate that the user sending the token request message is the authorized user of the resource provider account identified in the token request message.

When the validation module **306** determines that the resource provider account is a valid account, the validation module **306** may inform the account identifier generation module **308**. The account identifier generation module **308** may generate a universal account identifier for the resource provider account. The universal account identifier may identify the resource provider account and may replace the account identifier provided by the user in the token request message or the provisioning request message.

The universal account identifier may have a format that is different than a format of the account identifier provided by the user. In some embodiments, the format of the universal account identifier may be recognized and processed by universal transaction processing entities other than the resource provider that issued the resource provider account. The format of the universal account identifier may identify the resource provider that issued the resource provider account identified by the universal account identifier. The format of the universal account identifier may also identify the resource provider processor system **125** as the issuer of the universal account identifier. For example, the universal account identifier may start with (or end with, include at a

14

predetermined location, etc.) a symbol or an alphanumeric character (e.g. an indicator) that is associated with the resource provider and/or the resource provider processor system **125**. Accordingly, when the universal account identifier is analyzed and/or processed by a universal transaction processing entity, the universal transaction processing entity may identify the resource provider processor system **125** as the issuer of the universal account identifier.

According to various embodiments, the account identifier generation module **308** may generate additional information associated with the resource provider account. For example, the account identifier generation module **308** may generate a validation code, an expiration date, etc. associated with the resource provider account.

In some embodiments, upon generating the universal account identifier, the resource provider processor system **125** may send an account closure request to the resource provider computer via the external communication interface **310**. The account closure request may inactivate the account identifier initially provided to the resource provider processor system **125** by the user.

FIGS. **4** and **5** illustrate methods for generating a token associated with a resource provider account and returning the token to the user according to embodiments of the invention. The steps shown in any method herein may be performed sequentially or in any suitable order in embodiments of the invention. In some embodiments, one or more of the steps may be optional. The various messages described below may use any suitable form of communication. In some embodiments, a request or response may be in an electronic message format, such as an e-mail, a short messaging service (SMS) message, a multimedia messaging service (MMS) message, a hypertext transfer protocol (HTTP) request message, a transmission control protocol (TCP) packet, a web form submission. The request or response may be directed to any suitable location, such as an e-mail address, a telephone number, an internet protocol (IP) address, or a uniform resource locator (URL). In some embodiments, a request or response may comprise a mix of different message types, such as both email and SMS messages.

Referring now to FIG. **4**, at **S402**, the user **110** may send a token request message or an account provisioning request message to the resource provider processing system **125** requesting a token for a resource provider account of the user **110**. The token request message or the account provisioning request message may include an account identifier identifying the resource provider account of the user. The account identifier included in the request message may have a format.

At **S404**, the resource provider processing system **125** may analyze the account identifier and identify the resource provider that issued the resource provider account of the user. For example, the resource provider processing system **125** may identify the resource provider based on the format of the account identifier. In some embodiments, the account identifier may include an indicator identifying the resource provider that issued the resource provider account.

At **S406**, the resource provider processing system **125** may contact the resource provider computer **130** (e.g. a system of the identified resource provider) to request the status of the resource provider account. At **S408**, the resource provider processing system **125** may receive a response from the resource provider computer **130** regarding the status of the resource provider account.

At **S410**, the resource provider processing system **125** may determine whether the resource provider account eli-

15

gible for token generation and/or provisioning on a user device based on the status of the resource provider account. For example, the resource provider account may be an account that stores value. If there is positive balance on the resource provider account, the account may be deemed to be

active or to have favorable status (e.g. account is eligible for tokenization or for provisioning on a user device). In some embodiments, at S410, the resource provider processing system 125 may request the resource provider computer 130 to close the resource provider account or deactivate the account identifier associated with the resource provider account when the resource provider account is deemed eligible for being provisioned on the user device.

At S412, the resource provider processing system 125 may generate a universal account identifier identifying the resource provider account. The universal account identifier may replace the account identifier provided to the resource provider processing system 125 by the user 110 at S402. The universal account identifier may be recognized and processed by universal transaction processing entities other than the resource provider who issued the resource provider account. The universal account identifier has a format, different from the format of the account identifier provided at S402, that is recognized by entities such as universal transaction processing entities or token issuing entities. The universal account identifier format may include a first indicator identifying the resource provider processing system 125 as the issuer of the universal account identifier. The universal account identifier format may also include a second indicator identifying the resource provider as the issuer of the resource provider account. For example, the universal account identifier may be a 16-digit PAN such as 4147 0900 0000 1234. The first four digits 4147 may identify a specific resource provider processor system 125 that issued this specific PAN. The next four digits 0900 may identify a specific source provider as the issuer of this PAN. This way, the universal transaction processing entity or token issuing entity may determine that the universal account identifier is associated with a resource provider account which would not be eligible for tokenization and/or provisioning without the universal account identifier.

At S414, the resource provider processing system 125 may send the universal account identifier to the user 110. The user 110 may request the resource provider account to be provisioned on their user device using the universal account identifier.

At S416, the user 110 may send a token request or a resource account provisioning request to a token issuer computer 140. The token issuer computer 140 may determine that the universal account identifier is associated with a resource provider account based on the format of the universal account identifier. However, since the format of the universal account identifier is recognizable (e.g. eligible for parsing) by the token issuer computer 140, the token issuer computer 140 may determine that a token can be generated for the universal account identifier.

At S418, the token issuer computer 140 may generate a token for the universal account identifier. At S420, the token issuer computer 140 may store the token and a mapping between the token and the universal account identifier at a token vault 150. At S422, the token issuer computer 140 may provide the token to the user 110. The token can be used to provision the resource provider account on the user device of the user 110.

In some embodiments, the resource provider processing system 125 may also receive, from the resource provider computer 130, restrictions associated with the resource

16

account. In some embodiments, the restrictions may be applied by the user, the resource provider, the resource provider processor, the token issuer or the universal account processor system. For example, the resource account may be associated with access restrictions, spending restrictions, location-based restrictions, use-base restrictions, etc. The resource provider processing system 125 may provide (e.g. transmit) the restrictions associated with the resource provider account to the user 110 along with the universal account identifier. Such restrictions are passed (e.g. transmitted) to the token issuer computer 140 so that the generated token is associated with same or similar restrictions.

In some embodiments, at S414, instead of providing the universal account identifier to the user 110, the resource provider processing system 125 may send the universal account identifier directly to the token issuer computer 140 in a token request message. The token issuer computer 140 may generate the token and send it to the user 110 as described above in connection with S418-S422. In some embodiments, the token issuer computer 140 may send the token to the user via the resource provider processing system 125. Once the resource provider account is provisioned on the user device (e.g. on a digital wallet stored on the user device), the user 110 may conduct transactions with the resource provider account using the user device.

Referring now to FIG. 5, another method for generating a token associated with a resource provider account and returning the token to the user is described next. At S502, the user 110 may send a token request message or an account provisioning request message to the token issuer computer 140 requesting a token for a resource provider account of the user 110. The token request message or the account provisioning request message may include an account identifier identifying the resource provider account of the user. The account identifier included in the request message may have a format.

At S504, the token issuer computer 140 may analyze the account identifier and determine that the account identifier is associated with a resource provider account that is not eligible for token generation. In some embodiments, the token issuer computer 140 may determine that the account identifier is associated with a resource provider account based on the format of the account identifier.

At S506, the token issuer computer 140 may contact the resource provider processing system 125 and request a universal account identifier for the resource provider account associated with the account identifier received from the user 110 at S502. The universal account identifier request message sent from the token issuer computer 140 to the resource provider processing system 125 may include the account identifier provided to the token issuer computer 140 by the user 110 at S502.

At S508, the resource provider processing system 125 may analyze the account identifier and identify the resource provider that issued the resource provider account of the user. For example, the resource provider processing system 125 may identify the resource provider based on the format of the account identifier. In some embodiments, the account identifier may include an indicator identifying the resource provider that issued the resource provider account.

At S510, the resource provider processing system 125 may contact the resource provider computer 130 (e.g. a system of the identified resource provider) to request the status of the resource provider account. At S512, the resource provider processing system 125 may receive a response from the resource provider computer 130 regarding the status of the resource provider account.

At **S514**, the resource provider processing system **125** may determine whether the resource provider account eligible for token generation and/or provisioning on a user device based on the status of the resource provider account. For example, the resource provider account may be an account that stores value. If there is positive balance on the resource provider account, the account may be deemed to be active or to have favorable status (e.g. account is eligible for tokenization or for provisioning on a user device).

In some embodiments, at **S516**, the resource provider processing system **125** may request the resource provider computer **130** to close the resource provider account or deactivate the account identifier associated with the resource provider account when the resource provider account is deemed eligible for being provisioned on the user device. That is, once the account is deemed to be eligible for provisioning and a token is provisioned for that account, the actual account number can no longer be used because it is being replaced by the token.

At **S518**, the resource provider processing system **125** may generate a universal account identifier identifying the resource provider account. The universal account identifier may replace the account identifier provided to the resource provider processing system **125** by the token issuer computer **140** at **S506**. The universal account identifier may be recognized and processed by universal transaction processing entities other than the resource provider who issued the resource provider account. The universal account identifier has a format, different from the format of the account identifier provided to the resource provider processing system **125** at **S506**, that is recognized by entities such as universal transaction processing entities or token issuing entities. The universal account identifier format may include a first indicator identifying the resource provider processing system **125** as the issuer of the universal account identifier. The universal account identifier format may also include a second indicator identifying the resource provider as the issuer of the resource provider account. This way, the universal transaction processing entity or token issuing entity may determine that the universal account identifier is associated with a resource provider account which would not be eligible for tokenization and/or provisioning without the universal account identifier.

At **S520**, the resource provider processing system **125** may send the universal account identifier to the token issuer computer **140**. At **S522**, the token issuer computer **140** may generate a token for the universal account identifier. At **S524**, the token issuer computer **140** may store the token and a mapping between the token and the universal account identifier at a token vault **150**. At **S526**, the token issuer computer **140** may provide the token to the user **110**. The token can be used to provision the resource provider account on the user device of the user **110**. Once the resource provider account is provisioned on the user device (e.g. on a digital wallet stored on the user device), the user **110** may conduct transactions with the resource provider account using the user device.

In some embodiments, the resource provider processing system **125** may also receive, from the resource provider computer **130**, restrictions associated with the resource account. In some embodiments, the restrictions may be applied by the user, the resource provider, the resource provider processor, the token issuer or the universal account processor system. For example, the resource account may be associated with access restrictions, spending restrictions, location-based restrictions, use-base restrictions, etc. In embodiments, where the user determines the restrictions, the

user may select or create the restrictions (e.g. different spending restrictions) via a graphical user interface (GUI) on a user device (e.g. user computer, user mobile device, etc.). The resource provider processing system **125** may provide (e.g. transmit) the restrictions associated with the resource provider account to the token issuer computer **140** along with the universal account identifier. The token generated by the token issuer computer **140** is subject to (e.g. is associated with) the same or similar restrictions.

Embodiments of the invention have a number of advantages. For example, in embodiments of the invention, non-universal accounts, such as resource provider specific accounts, can be provisioned into user devices (e.g. into digital wallets) by creating a universal account identifier for a non-universal account. In connection with the provisioning, embodiments enable token generation for the non-universal accounts, such as resource provider specific accounts. Accordingly, users may not need to store or carry different identification proof for various non-universal accounts, and all account identifiers may be stored and/or provisioned on user's mobile device, for example on a digital wallet.

Embodiments further allow for the system to be replicated for many closed-loop systems. Specifically, systems **100** and **200** may be used in connection with any resource provider and/or resource provider processor.

Embodiments further allow a universal transaction processing entity to be able to process transactions initiated with resource provider accounts which are not traditionally eligible for processing by the universal transaction processing entity.

The various participants and elements shown in FIGS. **1-5** may operate one or more computer apparatuses (e.g., a server computer) to facilitate the functions described herein. Any of the elements in FIGS. **1-5** may use any suitable number of subsystems to facilitate the functions described herein. Examples of such subsystems or components are shown in FIG. **6**. The subsystems such as a printer **608**, keyboard **614**, fixed disk **616** (or other memory comprising computer readable media), monitor **620**, which is coupled to a display adapter **610**, and others are shown. Peripherals and input/output (I/O) devices, which couple to I/O controller **602**, can be connected to the computer system by any number of means known in the art, such as serial port **612**. For example, serial port **612** or external interface **618** can be used to connect the computer apparatus to a wide area processing server computer, such as the Internet, a mouse input device, or a scanner. The interconnection via system bus **600** allows the central processor **606** to communicate with each subsystem and to control the execution of instructions from system memory **604** or the fixed disk **616**, as well as the exchange of information between subsystems.

Specific details regarding some of the above-described aspects are provided below. The specific details of the specific aspects may be combined in any suitable manner without departing from the spirit and scope of embodiments of the invention.

Storage media and computer readable media for containing code, or portions of code, may include any appropriate media known or used in the art, including storage media and communication media, such as but not limited to volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage and/or transmission of information such as computer readable instructions, data structures, program modules, or other data, including RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disk (DVD)

or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, data signals, data transmissions, or any other medium which may be used to store or transmit the desired information and which may be accessed by the computer. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art may appreciate other ways and/or methods to implement the various embodiments.

It may be understood that the present invention as described above may be implemented in the form of control logic using computer software in a modular or integrated manner. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art may know and appreciate other ways and/or methods to implement the present invention using hardware and a combination of hardware and software

Any of the software components or functions described in this application, may be implemented as software code to be executed by a processor using any suitable computer language such as, for example, Java, Objective C, C/C++ or Perl using, for example, conventional or object-oriented techniques. The software code may be stored as a series of instructions, or commands on a computer readable medium, such as a random access memory (RAM), a read only memory (ROM), a magnetic medium such as a hard-drive or a floppy disk, or an optical medium such as a CD-ROM. Any such computer readable medium may reside on or within a single computational apparatus, and may be present on or within different computational apparatuses within a system or processing server computer.

The above description is illustrative and is not restrictive. Many variations of the invention may become apparent to those skilled in the art upon review of the disclosure. The scope of the invention may, therefore, be determined not with reference to the above description, but instead may be determined with reference to the pending claims along with their full scope or equivalents.

One or more features from any embodiment may be combined with one or more features of any other embodiment without departing from the scope of the invention.

A recitation of “a”, “an” or “the” is intended to mean “one or more” unless specifically indicated to the contrary.

What is claimed is:

1. A method comprising:

receiving, by the token issuer server computer, a token request message including a first identifier from a token requestor;

analyzing, by the token issuer server computer, the first identifier;

determining, by the token issuer server computer and based on the analyzing, that (1) the first identifier is associated with a resource provider account that is exclusive to the resource provider, and (2) the first identifier is in a first format that is ineligible for tokenization and provisioning on a digital wallet of a user device;

transmitting, by the token issuer server computer, a universal identifier request to a resource provider processor system, wherein the universal identifier request includes the first identifier and requests a universal identifier corresponding to the first identifier;

receiving, by the token issuer server computer, the universal identifier corresponding to the first identifier from the resource provider processor system, wherein the universal identifier is in a second format that is eligible for tokenization and provisioning on the digital wallet of the user device, wherein the second format is

attributed to the resource provider processor system such that the resource provider processing system is identifiable based at least on the second format;

generating, by the token issuer server computer, a token for the universal identifier, wherein the token represents the universal identifier;

storing, by the token issuer server computer, a mapping between the token and the universal identifier at a token vault; and

transmitting, by the token issuer server computer, the token to the token requestor, wherein the token is provisioned on the digital wallet stored on the user device associated with an account holder of the resource provider account.

2. The method of claim 1, wherein the token issuer server computer includes an universal account processing server computer.

3. The method of claim 2, further comprising:

receiving, at the universal account processing server computer, a transaction request including the token;

retrieving, by the universal account processing server computer, the universal identifier represented by the token from the token vault;

modifying, by the universal account processing server computer, the transaction request to include the universal identifier represented by the token;

identifying the resource provider processing system based at least on the second format; and

transmitting, by the universal account processing server computer, the modified transaction request including the universal identifier to the resource provider processor system for processing.

4. The method of claim 1, further comprising:

receiving, by the token issuer server computer, one or more restrictions associated with the resource provider account; and

storing the one or more restrictions along with the generated token at the token vault such that the generated token is subject to the one or more restrictions.

5. The method of claim 1, wherein a format of the first identifier included in the token request message is different than a format of the universal identifier generated by the resource provider processor system.

6. The method of claim 1, wherein the token requestor is the user device of a user.

7. The method of claim 6, wherein prior to receiving the universal identifier from the resource provider processor system, the resource provider processor system performs an identification and verification process with the user and validates that the user is an account holder of the resource provider account.

8. The method of claim 1, wherein the first identifier is deactivated upon issuance of the token or the universal identifier.

9. A token issuer server computer, comprising:

one or more processors; and

a non-transitory computer readable storage medium communicatively coupled with the one or more processors and storing instructions which, when executed by the one or more processors, cause the server computer to: receive a token request message including a first identifier from a token requestor;

analyze the first identifier;

determine, based on the analyzing, that (1) the first identifier is associated with a resource provider account that is exclusive to the resource provider, and (2) the first identifier is in a first format that is

21

ineligible for tokenization and provisioning on a digital wallet of a user device;
 transmit a universal identifier request to a resource provider processor system, wherein the universal identifier request includes the first identifier and requests a universal identifier corresponding to the first identifier;
 receive the universal identifier corresponding to the first identifier from the resource provider processor system, wherein the universal identifier is in a second format that is eligible for tokenization and provisioning on the digital wallet of the user device, wherein the second format is attributed to the resource provider processor system such that the resource provider processing system is identifiable based at least on the second format;
 generate a token for the universal identifier, wherein the token represents the universal identifier;
 store a mapping between the token and the universal identifier at a token vault; and
 transmit the token to the token requestor, wherein the token is provisioned on the digital wallet stored on the user device associated with an account holder of the resource provider account.

10. The token issuer server computer of claim 9, wherein the token issuer server computer includes a universal account processing server computer and wherein the non-transitory computer readable storage medium stores instructions which, when executed by the one or more processors, cause the server computer to:

22

receive a transaction authorization request including the token;
 retrieve the universal identifier represented by the token from the token vault;
 modify the transaction authorization request to include the universal identifier represented by the token;
 identify the resource provider processing system based at least on the second format; and
 transmit the modified transaction authorization request including the universal identifier to the resource provider processor system for processing.

11. The token issuer server computer of claim 9, further storing instructions which, when executed by the one or more processors, cause the server computer to:

receive one or more restrictions associated with the resource provider account; and
 store the one or more restrictions along with the generated token at the token vault such that the generated token is subject to the one or more restrictions.

12. The token issuer server computer of claim 9, wherein the token requestor is the user device of a user.

13. The token issuer server computer of claim 12, wherein prior to receiving the universal identifier from the resource provider processing system, the resource provider processing system performs an identification and verification process with the user and validates that the user is an account holder of the resource provider account.

14. The token issuer server computer of claim 9, wherein the first identifier is deactivated upon issuance of the token or the universal identifier.

* * * * *