



US011668619B2

(12) **United States Patent**
Golub et al.

(10) **Patent No.:** **US 11,668,619 B2**
(45) **Date of Patent:** **Jun. 6, 2023**

(54) **LEAK DETECTION SYSTEM AND METHOD OF MAKING AND USING THE SAME**

(71) Applicant: **SAINT-GOBAIN PERFORMANCE PLASTICS CORPORATION**, Solon, OH (US)

(72) Inventors: **Charles S. Golub**, Westford, MA (US); **Raymond Alan Carr**, Lutz, FL (US); **Stéphane Domy**, Chaumontel (FR); **Mark Kelly**, Wesley Chapel, FL (US); **Robert Moreno**, Zephyrhills, FL (US)

(73) Assignee: **SAINT-GOBAIN PERFORMANCE PLASTICS CORPORATION**, Solon, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 206 days.

(21) Appl. No.: **17/136,658**

(22) Filed: **Dec. 29, 2020**

(65) **Prior Publication Data**

US 2021/0199532 A1 Jul. 1, 2021

Related U.S. Application Data

(60) Provisional application No. 62/955,655, filed on Dec. 31, 2019.

(51) **Int. Cl.**

G01M 3/18 (2006.01)
G06F 3/041 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G01M 3/18** (2013.01); **G06F 3/041** (2013.01); **G06F 3/0488** (2013.01); **G08B 21/20** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G01M 3/18; G01M 3/165; G01M 3/182; G08B 21/20; G06F 3/041; G06F 3/0488;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,285,290 B2 3/2016 Chatzigeorgiou et al.
10,121,353 B1 * 11/2018 Billman H04W 4/80
(Continued)

FOREIGN PATENT DOCUMENTS

CN 106441745 A 2/2017
CN 206754822 U 12/2017

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2020/067310, dated Apr. 23, 2021, 9 pages.


Primary Examiner — Ojiako K Nwugo

(74) *Attorney, Agent, or Firm* — Abel Schillinger, LLP; Chi Suk Kim

(57) **ABSTRACT**

A method of monitoring at least one leak detection sensor, the method including the steps of: determining via a communication hub a first state of a sensor comprising a first condition when the sensor is dry and a second condition when the sensor is wet; determining via the communication hub a second state representing an operability of the sensor; communicating via the communication hub each of the states of the sensor to a Graphical User Interface (GUI); and displaying, via the GUI, a representation of the first and second states of the sensor.

13 Claims, 11 Drawing Sheets



- | | | |
|------|---|--|
| (51) | Int. Cl.
<i>H04Q 9/02</i> (2006.01)
<i>G06F 3/0488</i> (2022.01)
<i>G08B 21/20</i> (2006.01) | 2017/0003192 A1 1/2017 Ling et al.
2019/0027013 A1* 1/2019 Sale G08B 21/182
2019/0162625 A1 5/2019 Carr et al.
2019/0234786 A1 8/2019 Klicpera
2019/0281370 A1* 9/2019 Struhsaker H04W 4/80
2019/0339159 A1 11/2019 Israelsen
2019/0358387 A1* 11/2019 Elbadry A61M 1/3663
2020/0116894 A1* 4/2020 Sale G01V 11/00
2020/0159399 A1* 5/2020 Sundermeyer H04L 12/281
2020/0314606 A1* 10/2020 Stevens A41D 1/002
2021/0130197 A1* 5/2021 Fraser F24F 8/30
2021/0319687 A1* 10/2021 Vilajosana Guillén
G08B 21/20 |
| (52) | U.S. Cl.
CPC <i>H04Q 9/02</i> (2013.01); <i>H04Q 2209/823</i>
(2013.01); <i>H04Q 2213/002</i> (2013.01) | |
| (58) | Field of Classification Search
CPC H04Q 9/02; H04Q 2209/823; H04Q
2213/002; H04Q 2209/43; H04Q 9/00
See application file for complete search history. | |

(56) **References Cited**

U.S. PATENT DOCUMENTS

10,232,206 B2	3/2019	Nelson et al.	
2010/0045471 A1	2/2010	Meyers	
2012/0086581 A1*	4/2012	Marsell	H04Q 9/00 340/870.02
2015/0056909 A1*	2/2015	Chien	F24F 11/30 454/187
2016/0320282 A1*	11/2016	Dingman	G05D 1/0088
2017/0000379 A1*	1/2017	Thomas	A61B 5/742

FOREIGN PATENT DOCUMENTS

CN	108626582 A	10/2018
CN	109358542 A	2/2019
CN	209054343 U	7/2019
CN	110081224 A	8/2019
KR	101764127 B1	8/2017
KR	20180116762 A	10/2018
KR	20190014937 A	2/2019
WO	2014078298 A1	5/2014
WO	2017004002 A1	1/2017

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17






FIG. 18B




FIG. 18C




FIG. 18D




FIG. 19

1

LEAK DETECTION SYSTEM AND METHOD OF MAKING AND USING THE SAME

CROSS-REFERENCE TO RELATED APPLICATION(S)

This application claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Application No. 62/955,655, entitled "LEAK DETECTION SYSTEM AND METHOD OF MAKING AND USING THE SAME," by Charles S. GOLUB et al., filed Dec. 31, 2019, which is assigned to the current assignee hereof and incorporated herein by reference in its entirety.

FIELD OF THE DISCLOSURE

The present disclosure relates to a leak detection system and method of making and using the same.

RELATED ART

Many industrial and commercial applications involve the use of fluids which may be used, for example, in processing steps, fabrication functions such as masking or etching, or temperature control. Some fluids may be particularly harmful or require special attention in light of adverse environmental or biological effects. Other fluids may be exceptionally valuable, such as for example, semiconductor preparation materials.

Many industries continue to demand a way to effectively and accurately monitor for leakage of harmful or valuable fluids in more sustainable and economical ways.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments are illustrated by way of example and are not intended to be limited in the accompanying figures.

FIG. 1 includes a perspective view of an example leak detection system in accordance with an embodiment.

FIG. 2 includes a side elevation view of a plurality of example leak detection systems in accordance with embodiments disposed on a fluid interface between joining fluid components.

FIG. 3 includes a schematic view of a sensor including a sensing element in accordance with an embodiment.

FIG. 4 includes a cross-sectional elevation view of a sensor including a sensing element in accordance with an embodiment.

FIG. 5 includes a cross-sectional elevation view of a sensor including a sensing element in accordance with another embodiment.

FIG. 6 includes a cross-sectional elevation view of a sensor including a sensing element in accordance with another embodiment.

FIG. 7 includes a schematic view of a sensor including a sensing element in accordance with another embodiment.

FIG. 8 includes a cross-sectional elevation view of a sensor including a sensing element sensor in accordance with an embodiment.

FIG. 9 includes a schematic view of another sensor including a sensing element in a dry condition in accordance with an embodiment.

FIG. 10 includes a schematic view of the sensor of FIG. 9 in a wet condition in accordance with an embodiment.

FIG. 11 includes a schematic view of another sensor including a sensing element having an electric circuit in accordance with an embodiment.

2

FIG. 12 includes a schematic view of another sensor including a sensing element having an electric circuit in accordance with an embodiment.

FIG. 13 includes a cross-sectional elevation view of a sensor including a sensing element having two detection elements in accordance with an embodiment.

FIG. 14 includes a perspective view of a fluid conduit having a plurality of sensors coupled thereto, each sensor having a different attachment element in accordance with an embodiment.

FIG. 15 includes a perspective view of a leak detection system in accordance with an embodiment.

FIG. 16 includes a perspective view of an attachment element in accordance with an embodiment.

FIG. 17 includes a perspective view of a leak detection array in accordance with an embodiment.

FIG. 18A includes a depiction of a number of variable displays of an exemplary graphical user interface (GUI) according to embodiments of the leak detection system disclosed herein.

FIG. 18B includes a depiction of a number of variable displays of an exemplary graphical user interface (GUI) according to embodiments of the leak detection system disclosed herein.

FIG. 18C includes a depiction of a number of variable displays of an exemplary graphical user interface (GUI) according to embodiments of the leak detection system disclosed herein.

FIG. 18D includes a depiction of a number of variable displays of an exemplary graphical user interface (GUI) according to embodiments of the leak detection system disclosed herein.

FIG. 19 includes a flow chart of an exemplary process for locating and correcting a fluid leak in accordance with the principles of the present invention.

DETAILED DESCRIPTION

The following description in combination with the figures is provided to assist in understanding the teachings disclosed herein. The following discussion will focus on specific implementations and embodiments of the teachings. This focus is provided to assist in describing the teachings and should not be interpreted as a limitation on the scope or applicability of the teachings. However, other embodiments can be used based on the teachings as disclosed.

The terms "comprises," "comprising," "includes," "including," "has," "having" or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a method, article, or apparatus that comprises a list of features is not necessarily limited only to those features but may include other features not expressly listed or inherent to such method, article, or apparatus. Further, unless expressly stated to the contrary, "or" refers to an inclusive-or and not to an exclusive-or. For example, a condition A or B is satisfied by any one of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present).

Also, the use of "a" or "an" is employed to describe elements and components described herein. This is done merely for convenience and to give a general sense of the scope of the invention. This description should be read to include one, at least one, or the singular as also including the plural, or vice versa, unless it is clear that it is meant otherwise. For example, when a single item is described herein, more than one item may be used in place of a single

item. Similarly, where more than one item is described herein, a single item may be substituted for that more than one item.

Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. The materials, methods, and examples are illustrative only and not intended to be limiting. To the extent not described herein, many details regarding specific materials and processing acts are conventional and may be found in textbooks and other sources within the fluid transport arts.

A leak detection system in accordance with one or more of the embodiments described herein may generally include at least one sensor, a communication device coupled to the sensor, and an attachment element adapted to operatively couple the leak detection system to an area for monitoring fluid leakage. In an embodiment, the leak detection system may be disposed adjacent to a fluid interface on a fluid component. According to certain embodiments, the fluid component may include a junction whereby fluid may leak from the fluid interface such as, for example, a pipe junction, a pipe coupling, a pipe, a pipe bend, a manifold, an elbow, a valve, a pump, a regulator, a seam or weld line, a nozzle or sprayer, a threaded port, a sampling valve, an exhaust line, a fluid inlet or outlet, or any other similar junction. In another embodiment, the sensor can have a first state having a first condition when dry and a second condition when wet. In an embodiment, the sensor can have a second state adapted to monitor the operability of the sensor. In an embodiment, the sensor can have a third state adapted to monitor a measure of the battery life of the sensor. In an embodiment, the sensor can have a fourth state adapted to monitor signal strength of the sensor. The communication device may transmit the condition (first, second, third, or fourth) through a wireless protocol or wired connection to a communication hub or receiving device adapted to communicate the condition of the area being monitored to a user or system which may respond to the leakage. In a particular embodiment, the attachment element may be removable, reusable, or both. That is, the attachment element may be selectively engaged with a fluid component or area or surface of the fluid component being monitored and selectively disengaged therefrom.

According to certain embodiments, leak detection systems as described herein may be positioned to monitor leakage on fluid component spanning several different technical specialties. For example, a leak detection system in accordance with one or more embodiments described herein may be utilized in electronic device fabrication such as in the semiconductor and superconductor industry; medical devices such as fluid transport lines and pumps; pipe couplings such as those found in the oil and gas industry, potable water and sewer systems; aerospace industry in fabrication, maintenance, and design; food and beverage industry; and in the automotive industry. In specific embodiments, the leak detection system may be attached to a fluid component housing a semiconductor fluid which may include at least one of HF, H₂SO₄, HNO₃, NaClO, H₂O₂, H₃PO₄, CMP, HCL, deionized water, ethanol, ethanol IPA, acetone, a hydrocarbon solvent, toluene, or may be another semiconductor fluid. According to yet other embodiments, leak detection systems described herein may reduce response time to leaks by quickly and accurately detecting small fluid leakages, allowing an operator to address a possible leak before it has an opportunity to grow larger.

In accordance with an embodiment, the sensor may be adapted to perceive a particular fluid leakage. For example, the sensor may be adapted to perceive a fluid leakage of about 0.0001 mL to about 1 mL. In a number of embodiments, the sensor may be adapted to perceive a fluid leakage of at least about 0.0001 mL, such as, at least 0.001 mL, or at least 0.01 mL, or at least 0.05 mL, or at least 0.1 mL.

FIG. 1 includes an illustration of a leak detection system **1000** including a sensor **100**. As shown in FIG. 1, a leak detection system **1000** and/or sensor **100** may generally include at least one sensing element **102** and a communication device **104**. The sensing element **102** and communication device **104** may be coupled to a common carrier, such as a substrate **106**, which can maintain the sensing element **102** and communication device **104** spatially coupled to one another. In another embodiment, described below, the sensing element **102** and communication device **104** may be coupled to one another or to another object of the leak detection system **1000**, allowing for removal of substrate **106**. In a number of embodiments, optionally, the leak detection system **1000** may include a salt puck **107** to dissolve components of the fluid for better monitoring through the sensing element **102**.

FIG. 2 includes a side elevation view of a plurality of exemplary leak detection systems **1000** in accordance with embodiments disposed on a fluid interface **114** between joining fluid components **121**. As illustrated in FIG. 2, at least one leak detection system **1000** may be operatively coupled to a fluid component **121** having a surface with a fluid interface **114**, such as for example, between axial ends of a first fluid conduit **116** and a second fluid conduit **118**, for monitoring fluid leakage therebetween. A plurality of leak detection systems **1000** may be placed anywhere on the surface or fluid interface **114** of the fluid component **121**. Each leak detection system **1000** may monitor an area **108**, **110**, and **112** for fluid leakage. In an embodiment, the areas **108**, **110**, and **112** may each be at least 1 cm², such as at least 2 cm², or at least 3 cm², or at least 4 cm², or at least 5 cm², or at least 10 cm², or at least 20 cm², or at least 30 cm², or at least 40 cm², or at least 50 cm², or at least 75 cm², or at least 100 cm². In an embodiment, the areas **108**, **110**, and **112** may be equal in size and have the same relative shape as one another. In another embodiment, the areas **108**, **110**, and **112** need not have the same shape or size. That is, area **108** may be larger than area **110**. Alternatively, area **112** may have a generally circular shape whereas area **108** may be generally rectangular. The shape and size of the area **108**, **110**, and **112** may depend on several factors such as, for example, the size or sensitivity of the sensing element **102**, the relative location of the sensing element **102**, or even the type of fluid being monitored. For example, a sensing element **102** disposed at a lower position of a fluid conduit may monitor a larger area as fluid might pool or collect at the bottom of the fluid conduit, whereas a sensing element **102** disposed at an upper position of the fluid conduit might monitor only a small area as fluid may be less likely to collect at the upper position. In a particular embodiment, a single leak detection system **1000** may be positioned at a vertically lowest location along the fluid conduit.

In a particular instance, the areas **108**, **110**, and **112** may be adjacent to one another, such as immediately adjacent to one another or slightly spaced apart from one another. That is, the areas **108**, **110**, and **112** may not overlap each other. In another instance, at least two of the areas **108**, **110**, and **112** may at least partially overlap. That is, the at least two areas **108**, **110**, and **112** may share a common area. For example, by way of a non-limiting embodiment, areas **108**

5

and **110** may each be 10 cm² with at least 2 cm² overlap therebetween. Thus, the effective monitored area (as covered by areas **108** and **110**) is 18 cm².

According to certain embodiments, at least two of the leak detection systems **1000** may overlap by a particular amount. For example, at least two of the leak detection systems **1000** can overlap by at least 1%, or at least 2%, or at least 3%, or at least 4%, or at least 5%, or at least 10%, or at least 25%. In another particular embodiment, the at least two leak detection systems **1000** can overlap by no greater than 99%, or no greater than 98%, or no greater than 97%, or no greater than 96%, or no greater than 95%, or no greater than 90%, or no greater than 75%. In an embodiment, the two leak detection systems **1000** can overlap by at least about 1% and no greater than about 99%. Overlapping at least two of the areas **108**, **110**, and **112** may reduce the rate of failure to detect a leakage that might otherwise occur if one of the leak detection systems **1000** were to fail.

FIG. 3 includes a schematic view of a sensor **100** including a sensing element **102** in accordance with an embodiment. As illustrated in FIG. 3, in an embodiment, the sensing element **102** may include a substrate **302**. In a number of embodiments, the sensing element **102** may include a detection element **304**. The detection element **304** may be attached to the substrate **302**, such as for example, by an adhesive, a threaded or non-threaded fastener, a surface roughness interface, a tie layer, a mechanical fastener, or another suitable method.

In an embodiment, the detection element **304** may be adapted to change in response to fluid contact. In an embodiment, the detection element **304** may be adapted to monitor the operability of the sensing element **102** or the leak detection system **1000**. In an embodiment, the detection element **304** may have a first state having a first condition that may be adapted to change in response to fluid contact, and a second state that may be adapted to monitor the operability of the sensing element **102** or the leak detection system **1000**. In an embodiment, the detection element **304** may include an electrical circuit. More particularly, the detection element **304** may include a broken circuit in the dry condition and a closed circuit in the wet condition (i.e., upon fluid contact). In a particular embodiment, the electrical circuit can include a plurality of first fingers or traces **306** and a plurality of second fingers or traces **308**, where the first and second plurality of fingers **306** and **308** are spaced apart by a gap **314** having a distance, D, so as to be electrically disconnected from one another. The distance, D, may be uniform between a length of the fingers **306** and **308** or nonuniform (e.g., wavering or changing). In a number of embodiments, the distance D between the sensor traces or fingers **306**, **308** may be a range of about 5 mm to about 25 mm. Fluid interaction with the substrate **302** may bridge the gap **314**, creating a closed circuit through which current may flow. A power source **132** (discussed in greater detail below) electrically biasing the detection element **304** may permit current flow when the circuit is closed. Upon such occurrence, the detection element **304** may switch from a first condition (indicating the sensing element **102** is dry) to a second condition (indicating the sensing element **102** is wet), causing the communication device **104** (FIG. 1) to transmit a signal relaying occurrence of a fluid leakage. Such action may occur, for example, by a change in voltage, current, or resistance as measured by an appropriate element **312** electrically coupled to the detection element **304**. The signal may be digital or analog.

In an embodiment, the detection element **304** may include a wire having one or more disconnected segments along a

6

length thereof. Upon contacting a fluid, the disconnected segments may be bridged, creating a closed circuit through which current may flow. In an embodiment, at least one of the disconnected segments may have a length, as measured by a shortest distance between two segments of the wire which, if bridged, would complete the circuit, of at least 0.001 inches, such as at least 0.01 inches, or at least 0.1 inches, or even at least 1 inch. In another embodiment, the length of the disconnected segments may be no greater than 10 inches, such as no greater than 5 inches, or even no greater than 2 inches. Shorter disconnected segment lengths may decrease the time required to close the circuit, accelerating the rate of leak detection.

In an embodiment, leak detection elements **304** may be particularly suitable for applications where the fluid being monitored is conductive. That is, closing the circuit is performed by bridging the gap **314**, which in turn requires a conductive medium. Exemplary conductive fluids include distilled water, salt water, alcohol, acid, and liquid metal.

In a particular embodiment, the substrate **302** may include a material adapted to rapidly transfer fluid from the surface being monitored to the detection element **304**. For example, the substrate **302** may include a wicking material or other suitable material having a high fluid transfer rate. Exemplary materials include closed or open-cell foam, woven or non-woven mesh, textiles, and polymers. It is believed that the use of materials having high fluid transfer rates may accelerate transfer of fluid from the fluid interface to the detection element **304**, reducing sensing time and, in turn, accelerating leak detection.

In an embodiment, the substrate **302** may have a thickness, as measured in the installed state, of no greater than 10 inches, such as no greater than 5 inches, or no greater than 1 inch, or no greater than 0.75 inches, or no greater than 0.5 inches, or no greater than 0.1 inches, or even no greater than 0.01 inches. In another embodiment, the substrate **302** may have a thickness, as measured in the installed state, of at least 0.001 inches. In an embodiment, the substrate **302** may have a thickness, as measured in the installed state, of at least about 0.001 inches to about 10 inches. In a particular instance, the substrate **302** may deform during installation. That is, the substrate **302** may elastically or plastically deform from its uninstalled shape. Such deformation may permit the substrate **302** to better fit with contours and undulations of the surface onto which the leak detection system **1000** is being installed. Deformation may occur through flexure, compression, or expansion of the substrate as caused, for example, by forces necessary to secure the leak detection system **1000** to the surface.

In an embodiment, prior to installation, in a relaxed state, the substrate **302** may be generally planar. That is, the substrate **302** may deviate from a plane by no greater than 2 inches, 1.5 inches, 1 inch, 0.5 inches, or 0.25 inches at any location therealong. In another embodiment, the substrate **302** can be sufficiently flexible such that when positioned on a planar surface the substrate **302** assumes a generally planar shape.

In another embodiment, prior to installation, in a relaxed state, the substrate **302** may have a generally arcuate cross section. For example, the substrate **302** may have a radius of curvature, R, of at least 1 inch, such as at least 2 inches, or at least 3 inches, or at least 4 inches, or at least 5 inches, or at least 6 inches, or at least 12 inches, or at least 24 inches, or even at least 48 inches. In an embodiment, R can be no less than 0.001 inches. In an embodiment, R can be no less than 0.001 inches and no greater than 48 inches. Such arcuate-shaped substrates **302** may be suitable for engage-

ment, for example, with fluid conduits (e.g., pipes and tubing) having circular cross-sections. The radius of curvature of the substrate **302** may be selected to best fit the shape and size of the fluid conduit or surface being monitored. In a particular embodiment, the substrate **302** can have an arcuate cross section in the relaxed state and may flex upon occurrence of a sufficient loading condition. This may permit low-strain usage of the substrate **302** with fluid conduits while simultaneously permitting flexure to accommodate deviations in the surface profile and texture of the fluid conduit.

In a particular instance, the substrate **302** may have an initial thickness, T_I , different from an installed thickness, T_E . T_I may be greater than T_E . For example, T_I may be at least 1.01 T_E , or at least 1.05 T_E , or at least 1.1 T_E , or at least 1.2 T_E , or at least 1.3 T_E , or at least 1.4 T_E , or at least 1.5 T_E , or at least 2.0 T_E , or at least 5.0 T_E . In an embodiment, T_I may be no greater than 100 T_E , or no greater than 50 T_E , or no greater than 25 T_E . In an embodiment, T_I may be at least 1.01 T_E and no greater than about 100 T_E . T_I and T_E may be measures of absolute thickness (thickness at a particular location) or average thickness of the substrate **302** as measured over select areas of the substrate **302** or the entire area of the substrate **302**.

The substrate **302** may define opposing major surfaces—i.e., a first major surface **316** and a second major surface **318**, spaced apart by the thickness of the substrate **302**. The detection element **304** may be disposed along one of the first and second major surfaces **316** and **318**. As illustrated, in an embodiment, the detection element **304** may be disposed centrally along the major surface **316** or **318**. Such central position may maximize the volume and speed of fluid interaction with the detection element **304** by displacing the detection element **304** equally from all edges of the substrate **302**. This may decrease detection regardless of the edge of the substrate **302** fluid first contacts. Alternatively, by way of an embodiment, the detection element **304** may be disposed at a peripheral portion of the substrate **302**, i.e., closer to one of the edges. Such position may be suitable for leak detection systems **1000** having particular applications with a nonsymmetrical interface.

In a particular embodiment, the detection element **304** can occupy less than 90% of a surface area of the substrate **302**, or less than 80% of the surface area of the substrate **302**, or less than 70% of the surface area of the substrate **302**, or less than 60% of the surface area of the substrate **302**, or less than 50% of the surface area of the substrate, or less than 40% of the surface area of the substrate, or less than 30% of the surface area of the substrate, or less than 20% of the surface area of the substrate, or less than 10% of the surface area of the substrate, or less than 1% of the surface area of the substrate. In another particular embodiment, the detection element **304** can occupy at least 0.001% of the surface area of the substrate **302**. In another particular embodiment, the detection element **304** can occupy at least about 0.001% of the surface area of the substrate **302** and no greater than 90% of the surface area of the substrate **302**.

FIG. 4 includes a cross-sectional elevation view of a sensor **100** including a sensing element **102** in accordance with an embodiment. As illustrated in FIG. 4, in accordance with a particular embodiment, the detection element **304** may be at least partially embedded within the substrate **302**. That is, at least a portion of the detection element **304** may be disposed between the major surfaces **316** and **318** of the substrate **302**. In a more particular embodiment, at least a portion of at least one of the first or second plurality of fingers **306** or **308** may be embedded within the substrate

302. In another embodiment, all of at least one of the first or second plurality of fingers **306** or **308** may be embedded within the substrate **302**. In yet a further embodiment, all of the first and second plurality of fingers **306** and **308** may be embedded within the substrate **302**. Disposition of at least a portion of the detection element **304** between the major surfaces **316** and **318** may accelerate leak detection by reducing a distance, as measured in a direction normal to the major surfaces **316** and **318**, fluid is required to travel to bridge the gap **314** (FIG. 3) and close the circuit.

As illustrated, in an embodiment, at least one of the first plurality of fingers **306** may be vertically offset (in a direction normal to the major surfaces **316** and **318**) from at least one of the second plurality of fingers **308**. Such positioning may accelerate detection timing by further reducing a distance between the detection element **304** and, at **1** the surface being monitored. In another embodiment, the first and second plurality of fingers **306** and **308** may be disposed at a same relative position with respect to the major surfaces **316** and **318**.

FIG. 5 shows a cross-sectional elevation view of a sensor **100** including a sensing element **102** in accordance with another embodiment. As illustrated in FIG. 5, the detection element **304** may be disposed at least partially on both major surfaces **316** and **318**. For example, a first detection element **502** may be disposed on the first major surface **316** and a second detection element **504** may be disposed on the second major surface **318**. Disposition of the first detection system **502** on the first major surface **316** and the second detection element **504** on the second major surface **318** may permit reversible installation of the detection element **304** on a surface for fluid monitoring. In an embodiment, the leak detection elements **502** and **504** may share a single power source **132**. In an embodiment, the leak detection elements **502** and **504** and may each utilize separate power sources. Lithium batteries or rechargeable batteries or other battery forms can be used as part of the power source **132**.

FIG. 6 includes a cross-sectional elevation view of a sensor **100** including a sensing element **102** in accordance with another embodiment. As illustrated in FIG. 6, in an embodiment, a single leak detection element **304** can be disposed on the substrate **302** such that at least one of the first plurality of fingers **306** may be adjacent to the first major surface **316** and at least one of the second plurality of fingers **308** may be adjacent to the second major surface **318**. As illustrated, the first and second plurality of fingers **306** and **308** may be disposed on the first and second major surfaces **316** and **318**, respectively. In another particular embodiment, at least one of the first and second plurality of fingers **306** and **308** may be at least partially embedded within the substrate **302** adjacent to the first and second major surfaces **316** and **318**, respectively.

Referring again to FIG. 4, in an embodiment, the power source **132** may be disposed adjacent to one of the major surfaces **316** or **318**. In a particular embodiment, the power source **132** may be disposed on the major surface **316** or **318**. That is, the power source **132** may rest on the major surface **316** or **318**. In operation, the opposite major surface **316** or **318** (i.e., the major surface opposite the power source) may be disposed on the surface being monitored to permit flush contact therewith.

In another particular embodiment, the power source **132** may be partially embedded within the substrate **302** so as to extend into the substrate while being partially visible. In yet a further embodiment, such as illustrated in FIGS. 5 and 6, the power source **132** may be fully embedded within the

substrate **302**. Electrical contacts may extend from the substrate, allowing for coupling of the detection element and communication device.

FIG. 7 includes a schematic view of a sensor **100** including a sensing element **102** in accordance with another embodiment. As illustrated in FIG. 7, in an embodiment, the sensing element **102** may include a detection element **704** defining a closed circuit in the dry condition and a broken circuit in the wet condition (i.e., upon fluid contact). The detection element **704** may be coupled to a substrate **702**. In an embodiment, the substrate **702** can have any or all of the characteristics as described above with respect to substrate **302**. For example, the substrate **702** may have an initial thickness, T_I , different from an installed thickness, T_E . In another embodiment, the substrate **702** may be different from the substrate **302**. For example, as described below, application of the detection element **704** may be best suited for use with corrosive or deleterious fluids which may break or disrupt a continuous wire **706** upon exposure. Thus, it may be desirable to utilize a substrate adapted to withstand exposure to the damaging effects of the corrosive or deleterious fluid. As used herein, "wire" refers to a conductive member having a length and a thickness, where the length is greater than the thickness. Exemplary wires include cylindrical wires, wound wires, single-thread wires, ribbons, bands, sheets, cords, and other similar elements. The wire may be a conductive material. In a number of embodiments, the wire may be metal material comprising copper.

In an embodiment, it may be desirable for the substrate **702** to break down or become damaged upon contact with the corrosive or deleterious fluid. Specifically, the substrate **702** may break down upon contact with the fluid, causing more rapid advancement of the fluid through the substrate to the detection element.

In a particular instance, the wire **706** may have a total length, L_W , as measured by a length of the wire **706** on the substrate **702**, that may be greater than an effective length, L_E , of the wire **706**, as measured by a direct distance between the location the wire **706** enters **708** and exits **709** the substrate **702**. In an embodiment, the wire **706** may pass over the substrate **702** in a non-straight line. As illustrated, the wire **706** may form a plurality of straight segments interconnected at 90 degree angles. The disclosure is not intended to be limited to those embodiments having 90 degree angles, but instead further includes interconnection of line segments at both acute and obtuse angles. In another embodiment, the wire **706** may have a generally serpentine shape. The wire **706** may have other shapes, which may include concentric circles, concentric ovals, zigzags, spirals, and other arcuate or straight segmented shapes having total lengths, L_W , greater than the effective length, L_E , on the substrate **702**. It is believed that wires **706** with total lengths, L_W , greater than the effective length, L_E , may increase fluid sensitivity or even reduce sensing time.

In an embodiment, the detection element **704** may include portions at least partially embedded within the substrate **702**. FIG. 8 illustrates a cross-sectional view of the detection element **704** in accordance with an embodiment. As illustrated in FIG. 8, the wire **706** extends through the substrate **702** in a non-straight line. That is, the wire **706** extends through the substrate in a plurality of straight segments interconnected at 90 degree angles. The disclosure is not intended to be limited to those embodiments having 90 degree angles, but instead further includes interconnection of line segments at both acute and obtuse angles. Disposition of the wire **706** at various vertical elevations within the substrate **702** may permit reversible installation of the

detection element **704** with respect to the surface being monitored. Additionally, the wire **706** occupies a greater relative volume of the substrate **702**, which accelerates the rate at which a fluid contacting the substrate **702** will contact the wire **706**.

In an embodiment, the detection element may include a conductive structure having a two- or three-dimensional matrix, or quasi-matrix shape instead of, or in addition to, the wire **706**. In a particular instance, the conductive structure may have a low flexure modulus, permitting flexure of the detection element. A material may be positioned around the conductive structure, for example by overmolding or extruding, to protect the conductive structure or to facilitate easier attachment of the conductive structure to a surface for monitoring.

In a particular embodiment, the changing characteristic of the substrate **902** may be measured property of the substrate **902**. For example, FIGS. 9-10 illustrate a sensor **100** including a sensing element **102** as seen prior to fluid contact. As shown in FIG. 9, the substrate **902** has an initial length, L_I , and an initial width, W_I . After contacting fluid, the substrate **902** can change in measured property, having a final length, L_F , and a final width, W_F , as illustrated in FIG. 10. In an embodiment, L_I can be less than L_F and W_I can be less than W_F . In another embodiment, L_I can be greater than L_F and W_I can be greater than W_F . A wire **906** extending across a portion of the substrate **902** can permit detection of a change in a measured property of the substrate **902**. More particularly, an element **912** can measure conductivity, or another suitable characteristic, of the wire **906** as it changes with strain imposed by the substrate **902**. When conductivity, or other suitable characteristic, changes, the detection system **902** may change from a first condition (dry) to a second condition (wet), thus permitting notification of a fluid leakage. Although the wire **906** is illustrated as having a looping shape including a plurality of loops, the wire **906** may also have any shape as described above with respect to wire **706**.

In an embodiment, the substrate **902** may be formed from a material adapted to expand upon contact with fluid. For example, the substrate **902** may include, or consist essentially of, a fibrous material, a woven or non-woven material, a matrix or quasi-matrix based material, or any other suitable material adapted to expand upon contact with fluid.

The wire **906** may extend at least partially into the substrate **902**. In an embodiment, a majority of the wire **906** may be embedded in the substrate **902**. In a further embodiment, all of the wire **906** may be embedded in the substrate **902**. Partial or full embedment of the wire **906** may improve speed of fluid leakage detection as forces acting on the substrate **902** may be more readily transmitted to an embedded wire **906** as opposed to a wire disposed on a major surface of the substrate **902**.

Detection element **904** and substrate **902** may include any or all of the features discussed above with respect to detection elements **304** and **704**, and substrate **302** and **702**, respectively.

Referring now to FIGS. 11-12, in accordance with an embodiment, the sensor **100** including a sensing element **102** may include a detection element **304** coupled to a substrate **302**, where the sensing element **102** or detection element **904** may be adapted to have one or more changing characteristics or measured properties in response to fluid contact.

In a particular embodiment, as shown in FIGS. 11-12, the sensing element **102** may include an electrical circuit. As shown in FIG. 3, the electrical circuit may form a geometric parallel comb circuit design. FIG. 11 shows a schematic

11

view of another sensor having an electric circuit in accordance with an embodiment. As illustrated in FIG. 11, the electrical circuit that forms a geometric serpentine design between two wires 706 (between A and D), 706' (between B and C). FIG. 12 shows a schematic view of another sensor having an electric circuit in accordance with an embodiment. As illustrated in FIG. 12, the electrical circuit that forms a geometric spiral design between two wires 706 (between A and D), 706' (between B and C). The sensing element 102 may allow for series or parallel measurements of a measured property of the electrical circuit. The measured property may undergo a change in response to fluid contact that the sensing element 102 monitors and/or responds to via the communication device 104. The measured property may be at least one of resistance, impedance, capacitance, current, voltage, or another measured property of the detection element 304 or circuit. In a number of embodiments, the sensing element 102 may include two electrical circuits electrically connected in parallel. In a number of embodiments, the sensing element 102 may include two electrical circuits electrically connected in series.

In a number of embodiments, in a first state, the circuit of the sensing element 102 (and/or the sensor 100) may be monitored to have a first condition when dry and a second condition when wet. In a number of embodiments, in a second state, the sensing element 102 (and/or the sensor 100) may be adapted to monitor the operability of the sensing element 102, i.e., monitor the ability of the sensor to detect leaks in the first state. In a number of embodiments, the operation of the sensing element 102 and leak detection system 1000 to execute these two operations is as follows: 1) measure the measured property between A and D to ensure acceptable operability of the circuit, first detection element 304, and sensing element 102; 2) measure the measured property between B and C to ensure acceptable operability of the circuit, first detection element 304, and sensing element 102; and 3) measure the measured property between A and B with C and D open to detect the first state (i.e. whether the sensor is in a first condition when dry and a second condition when wet) of the circuit, first detection element 304, and sensing element 102. The order of these steps can be varied and may be done on a continuous basis. Alternatively, the operation of the sensing element 102 and leak detection system 1000 to execute these two operations is as follows: 1) short points C and D to ensure acceptable operability of the circuit, first detection element 304, and sensing element 102; and 3) measure the measured property between A and B with C and D open to detect the first state (i.e. whether the sensor is in a first condition when dry and a second condition when wet) of the circuit, first detection element 304, and sensing element 102. As such, a method of using a leak detection system 1000 may include: 1) providing at least one leak detection system 1000 having a sensing element 102 having a first state having a first condition when dry and a second condition when wet, and a second state adapted to monitor the operability of the sensor, a communication device 104 operatively connected to the sensing element 102, and an attachment element 120 adapted to attach the leak detection system 1000 to a fluid component 121 having a fluid for monitoring fluid leakage; and 2) attaching the at least one leak detection system 1000 to the fluid component 121 for monitoring fluid leakage.

It is contemplated in other embodiments, that the sensor can include a substrate adapted to produce luminescence, fluorescence, incandescence, a change in temperature, a change in pressure as a result of contacting fluid, or any other suitable changing characteristic in response to con-

12

tacting fluid. The detection element can be selected accordingly to detect the changing condition of the substrate. For example, the detection element may include an optical sensor, a thermocouple, or a pressure transducer. As the substrate changes in condition (luminescence, fluorescence, incandescence, temperature, or pressure) as a result of contacting fluid, the detection element can sense the changed condition and generate a signal to the communication device 104 in order to generate an alert of a leakage.

FIG. 13 shows a cross-sectional elevation view of a sensor 100 including a sensing element 102 sensing element 102 having two detection elements in accordance with an embodiment. As illustrated in FIG. 13, and in accordance with an embodiment, a sensing element 102 may include at least two detection elements 1304 and 1306 disposed on one or more substrates 1302. In a particular embodiment, the detection elements 1304 and 1306 may be disposed on a same substrate 1302. In another particular embodiment, the detection elements 1304 and 1306 may be disposed on adjoining substrates (collectively referred to as "the substrate"). The detection elements 1304 and 1306 may be disposed on the same or different major surfaces 316 or 318 of the substrate 1302. As illustrated, and in accordance with another embodiment, the detection elements 1304 and 1306 may also be at least partially embedded within the substrate 1302.

In an embodiment, the detection elements 1304 and 1306 can be different from one another. That is, each of the at least two detection elements 1304 and 1306 may be adapted to detect a different condition of the substrate 1302. For example, as illustrated, the detection element 1304 may be similar to detection element 304 described above, whereas detection element 1306 may be similar to detection element 1104. In a particular embodiment, the detection elements 1304 and 1306 can be spaced apart on the substrate 1302. This may facilitate easier assembly of the sensing element 102 and permit easier removal of broken or unsuitable detection elements. In another embodiment, the detection elements 1304 and 1306 can overlap vertically or horizontally. Vertical or horizontal overlap may reduce the size of the sensor, thus reducing the space necessary to install the sensor.

In a number of embodiments, in a third state, the sensing element 102 (or sensor 100) may be used to measure the battery life of the sensing element 102 and/or power source 132. As stated above Lithium batteries or rechargeable batteries or other battery forms can be used as part of the power source 132. The battery life may be measured and communicated to a user as described below.

In a number of embodiments, in a fourth state, the sensing element 102 (or sensor 100) may be used to measure the signal strength of the communication device 104 and/or the sensor 100 itself. The signal strength of the sensor 100 may be measured and communicated to a user as described below.

Any of the detection elements described above may further include an electronic component, such as: a resistor, a capacitor, an inductor, a transistor, another similar component, or any combination thereof. Such electronic components may be necessary to develop complete circuits for the detection elements described above.

Referring again to FIG. 1, the communication device 104 may be operatively coupled to the sensing element 102 and/or communication hub 105. In an embodiment, the communication device 104 may transmit a signal to the communication hub 105 on the four states of the leak detection sensing element 102. In an embodiment, the

13

communication device and/or communication hub **105** may include a controller or electronic control unit (ECU) adapted to manage the data received from the sensors, interpret the data, and organize the data to an end user in a format to monitor fluid leakage in the leak detection system **1000**. The communication device **104** and/or communication hub **105** may include a controller including a computer or other computational device capable of understanding, analyzing, and/or executing one or more programmable languages. The controller and/or computer may include a processing unit able to process the information provided by the sensing element **102** (or sensor **100**) (for example, leak detection, operability of the sensor, battery life, and signal strength). For example, a fluid leak signal from the sensing element **102** and may be received by the processing unit of the communication device **104**. In some embodiments, the processing unit may include a PPC-3060S 6.5" Fanless Panel PC with Intel® Celeron® N2807 Processor.

In a number of embodiments, the processing unit of the communication device **104** and/or communication hub **105** may receive the signal from the sensing unit **102** with data regarding the first or second states of the sensor **100**. Further, the processing unit of the communication device **104** and/or communication hub **105** may receive a signal with data regarding the third state from the power source **132**. Lastly, the processing unit of the communication device **104** and/or communication hub **105** may receive a signal with data regarding the signal strength of the communication device **104** itself. In a number of embodiments, the communication device **104** may transmit a master signal to the communication hub **105** transmitting either the data itself from each of the components listed above, or a calculation of whether each of the four states crossed a threshold from an acceptable reading to an unacceptable reading. The communication hub **105** may calculate the calculation of whether each of the four states crossed a threshold from an acceptable reading to an unacceptable reading from the data provided from the communication device **104** or compile the results of the calculations already done on whether each of the four states crossed a threshold from an acceptable reading to an unacceptable reading by the communication device **104**. The determination of whether an unacceptable reading has been achieved may be done by the controller in the communication device **104** and/or communication hub **105**. For the first state, for example an acceptable reading would be the first condition (dry) and an unacceptable reading would be the second condition (wet). For the second state, for example, an acceptable reading would be the sensor is healthy and an unacceptable reading would be the sensor is unhealthy. For the third state, for example, an acceptable reading would be where the battery has a life of greater than 15% of the charge of the battery in a fully charged state and an unacceptable reading would be where the battery has a life of less than 15% of the charge of the battery in a fully charged state. For the fourth state, for example, an acceptable reading would be where the signal has a strength of at least -120 dBm in RSSI value and an unacceptable reading would be where the signal has a strength of less than -120 dBm in RSSI value. All of these values are exemplary and do not necessarily limit the thresholds contemplated regarding the embodiments herein. The thresholds themselves and/or their severity can be modified as needed for a given application. If the data is sent directly to the communication hub **105**, then the communication hub **105** may calculate the threshold values and transmit the acceptable or unacceptable reading to a graphical user interface ("GUI") described in more detail below. In some embodiments, the thresholds may be further

14

divided into magnitudes in terms of severity, detectability and probability. These threshold magnitudes may be ranked by number in these three categories with 10 being a very dangerous or threshold value to 1 being a minimal effect threshold value. These may be indicated and/or modified by the user based on the leak detection system **1000** application.

In a particular embodiment, the communication device **104** may be wirelessly connected to the sensing element **102**, power source **132**, and/or communication hub **105**. This wireless communication may occur, for example, by Bluetooth or by another short range wireless protocol. In another particular embodiment, the communication device **104** may be connected to the sensing element **102** and/or communication hub **105** by a conductive wire. Care should be taken to ensure the conductive wire is not sensitive to the fluid being monitored. That is, the conductive wire should not be constructed from a material that will be destroyed upon fluid contact. Alternatively, the conductive wire may be insulated or otherwise protected against damaging fluid interaction by an outer layer or shield layer disposed between the wire and the suspected channel for fluid travel in the leak detection system **1000**. In a further embodiment, the communication device **104** may be integral to the sensing element **102** and/or communication hub **105**.

The communication device **104** and/or communication hub **105** may be a wireless or wired communication device. That is, the communication device **104** may operate wirelessly using wireless protocols, such as an HTML or HTMLS; a local area network (LAN); or may operate with a wired interface. The communication device **104** may be adapted to receive an incoming signal from the sensing element **102** and send an outgoing signal to a communication hub or receiving device **105** when the sensing element **102** senses a fluid leakage. In this way the communication device **104** may be operatively connected to the communication hub **105** that can compile and analyze information from the sensing element **102** and give feedback to a user or the sensing element **102** itself based on a first state (first condition or a second condition) or second state of the sensing element **102** as explained herein.

In an embodiment, the communication device **104** and/or communication hub **105** may use a wireless network using a LoRa (Long Range) protocol to communicate with at least one sensing element **102**. The LoRa wireless network may include a LoRa gateway. The communication device **104** and/or communication hub **105** may also connect with a Cloud Server. The communication device **104** and/or communication hub **105** may include a LoRa sensing node which may include a first LoRa controller and a LoRa wireless module, each connected to the power source **132** and optionally to a backup power source (not shown). Lithium batteries or rechargeable batteries or other battery forms can be used as part of the backup power source. The LoRa gateway may be included on at least one of the communication device **104** and/or the communication hub **105**. The communication device **104** or communication hub **105** may communicate with the other of the communication device **104** or communication hub **105** via the LoRa gateway.

Computer program code for carrying out operations for aspects of the invention (such as one or more embodiments of the sensing element **102**, communication device **104** or communication hub **105**) may be written in any combination of one or more programming languages, including an object oriented programming language such as Java, Smalltalk, C++ or the like and conventional procedural programming languages, such as the "C" programming language or similar

programming languages. The program code may execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer may be connected to the user's computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider). At least one of the sensing element 102, communication device 104, or communication hub 105 may include ROM or other existing storage organizations to include memory to record the data from the sensing element 102.

In an embodiment, the communication device 104 may continuously operate. As used herein, "continuously operate" refers to continuous, or uninterrupted, transmission of a signal from the communication device to, for example, a communication hub or receiving device 105. In an embodiment, the communication device 104 can passively operate. As used herein, "passively operate" refers to transmission of a signal, for example, to a communication hub or receiving device 105, only upon occurrence of a threshold condition—i.e., a fluid leak. For example, the communication device 104 may be powered by the power source 132. In an embodiment, only when the sensing element 102 senses a leakage might the communication device 104 receive power so as to transmit the signal to the communication hub or receiving device 105. This may increase operable lifetime of the leak detection system 1000 by reducing current draw from the power source 132, thus allowing for more remote positioning of the leak detection system 1000.

As illustrated, in an embodiment the communication device 104 may be exposed such that it extends beyond an outer surface of the substrate 106. Thus, the communication device 104 may be accessible such that a user can adjust or replace the communication device 104. In an embodiment, the communication device 104 may be at least partially, such as fully, embedded within the substrate 106. This may protect the communication device 104 from exposure to harmful fluids which may otherwise contact the communication device 104 if disposed on the surface of the substrate 106.

In an embodiment, the communication device 104 may be removable from the substrate 106. In another embodiment, the communication device 104 may be replaceable. An electrical interface may permit rapid replacement of the communication device 104. For example, the electrical interface may consist of one or more ports having electrical connection points which match electrical connection points on the communication device 104. The various communication devices 104 may have the same arrangement of electrical connection points, thereby enabling rapid replacement and interchanging therebetween.

Referring still to FIG. 1, the leak detection system 1000 may further include an attachment element 120 adapted to attach the leak detection system 1000 to a surface adjacent to the fluid interface 114 (FIG. 2).

In an embodiment, the attachment element 120 may include a unitary body. That is, the attachment element 120 can be formed from a single piece. In another embodiment, the attachment element 120 may include a multi-piece construction. For example, the attachment element 120 may include at least two components engageable together, or to the substrate 106 or one or more components disposed thereon, to form a single piece.

In an embodiment, the attachment element 120 may be directly coupled to the substrate 106. In an embodiment, the attachment element 120 may be indirectly coupled to the substrate 106 through the sensing element 102, the communication device 104, or some other suitable intermediary objection.

The attachment element 120 may releasably couple to the leak detection system 1000 to a surface for monitoring fluid leakage. That is, in an embodiment, the attachment element 120 may be removable from the leak detection system 1000. This may permit replacement or adjustment of the attachment element 120 with respect to the leak detection system 1000. Over extended periods of usage (particularly at high temperatures or in damp conditions) it is possible for the attachment element 120 to degrade or wear—a problem which can be greatly mitigated by periodically replacing the attachment element 120. In another embodiment, the attachment element 120 may be integral with the leak detection system 1000. For example, the attachment element 120 may be molded or otherwise fabricated into the substrate 106, sensing element 102, or communication device 104 so as to be inseparable therefrom, thus preventing accidental separation during installation or over extended usage.

As illustrated in FIG. 1, in an embodiment the attachment element 120 may include a band 122, an engagement element 124 extending from the band 122, and an opening 126 adapted to receive the engagement element 124. To install the leak detection system 1000 on a fluid conduit, the band 122 may be positioned around the fluid conduit until the engagement element 124 can engage with the opening 126. The engagement element 124 can then be inserted into the opening 126 to hold the leak detection system 1000 relative to the fluid conduit. For applications requiring more secure attachment protocol, one or more additional attachment elements (e.g., attachment elements 128 and 130) may be deployed along the substrate 106 or in another suitable manner, such as described above. The attachment elements 122, 128, and 130 may each include a same or similar attachment protocol as one another. For example, the attachment element 128 may include engagement element 124 and opening 126 into which the engagement element 124 may be insertable. In an embodiment, the attachment elements 122, 128, and 130 may be spaced apart along the surface of the leak detection system 1000 to enhance engagement with the surface and to spread loading conditions across the substrate 106.

FIG. 14 shows an installed leak detection system 1402 having a band 122, engagement element 124, and opening 126 installed around a fluid conduit 1400. In an embodiment, as shown in FIG. 14, the band 122 may be flexible or otherwise elastically deformable. The band 122 may be adapted to stretch around the fluid conduit, providing an inwardly oriented retention force that acts to pull the substrate 106 into the fluid conduit. Exemplary materials include woven fabrics, nonwoven fabrics, and polymers. Suitable polymers may include, for example, elastomers, such as rubber. In an embodiment, the attachment element 120 may have an unloaded size, S_U , as measured at rest, and a loaded size, S_L , as measured under loading conditions, where S_L may be at least 1.01 S_U , or at least 1.1 S_U , or at least 1.5 S_U , or at least 2.0 S_U , or at least 5.0 S_U , or at least 10.0 S_U , or at least 20.0 S_U . In another embodiment, S_L may be no greater than 200 S_U . In an embodiment, S_L may be at least about 1.01 S_U and no greater than about 200 S_U . The unloaded and loaded sizes may be a length of the attachment element 120—i.e., a length of the band 122—in the unloaded and loaded states, respectively.

In another embodiment, the attachment element **120** may include an elongated object **1404**, such as a rope, a cord, a string, or other similar device. The elongated object **1404** may be tied around the surface of the fluid conduit **1400** to secure the leak detection system **1000** thereto. An installed leak detection system **1406** having an elongated object **1404** as an attachment element **120** is illustrated in FIG. **14**. As illustrated, the ends of the elongated object **1404** may be tied together in a knot. In an embodiment, the leak detection system **1000** may be secured to the fluid conduit **1400** by a plurality of elongated objects **1404**. The longitudinal ends of the elongated objects **1404** may be tied together at a same relative circumferential position along the fluid conduit. Alternatively, the longitudinal ends may be staggered around the circumference of the fluid conduit. In an embodiment, the elongated object **1404** may have an engagement mechanism at longitudinal ends thereof. For example, the elongated object **1404** may terminate in a buckle, a ratchet, an eyelet, a ratcheting tie system, a cable tie, a threaded or non-threaded fastener, or any other suitable engagement element permitting connection of opposing longitudinal ends of the elongated object **1404**.

In yet a further embodiment, the attachment element **120** may include a hook and loop engagement system. Similar to the leak detection system **1000** described above with an elongated object **1404**, it is contemplated that the attachment element **120** may include a band of material **1408** having a hook and loop engagement. The band **1408** may be elastic or non-elastic and may be wrapped around the fluid conduit **1400** such that a first portion of the band **1408** having hooks which may be coupled to a second portion of the band **1408** having loops. Such engagement may be rapidly removable and not likely to degrade over prolonged usage. An installed leak detection system **1410** having a hook and loop engagement as an attachment element **120** is illustrated in FIG. **14**.

Still referring to FIG. **14**, in an embodiment, the attachment element **120** may include a system that does not extend around the entire circumference of the fluid conduit **1400**.

For example, the leak detection system **1000** may be secured to the fluid conduit by an adhesive-backed material **1412**. In a particular embodiment, the adhesive-backed material **1412** may be integral to the leak detection system **1000**. In another particular embodiment, the adhesive-backed material **1412** may be a discrete element attached to the leak detection system **1000**. As used herein, “discrete element” refers to a distinct component that is, or was at a previous time, separable from other objects upon application of a nominal force. An installed leak detection system **1414** having an adhesive-backed material **1412** as an attachment element **120** is illustrated in FIG. **14**.

In another embodiment, the attachment element **120** may include a securing layer (not illustrated) disposed between the leak detection system **1000** and the fluid conduit **1400**. The securing layer may include a paste, a gel, a putty, a material having a high plasticity, an epoxy, a solution, or any other substance which may be applied to one or both of the fluid conduit **1400** or leak detection system **1000**. Upon curing, the securing layer can prevent removal of the leak detection system **1000**. An installed leak detection system **1416** having a securing layer as an attachment element **120** is illustrated in FIG. **14**.

In an embodiment, the securing layer may be relaxable so as to permit removal of the leak detection system **1000**. For example, the securing layer may be softened or lose its adhesive properties upon introduction of a particular temperature, pressure, fluid interaction, or light type. Thus, a

user can selectively disengage the leak detection system **1000** from the fluid conduit **1400**.

In still another embodiment, the attachment element **120** may include a clamp **1418**. The clamp **1418** may extend at least partially over or partially through the leak detection system **1000**, providing a radially inward compressive force thereagainst. In an embodiment, the clamp **1418** may include two halves—a first half **1420** and a second half **1422**—adapted to couple together to secure the leak detection system **1000** relative to the fluid conduit **1400**. An installed leak detection system **1424** having a clamp **1418** as an attachment element **120** is illustrated in FIG. **14**.

FIG. **15** shows a perspective view of a leak detection system **1500** in accordance with an embodiment. As illustrated in FIG. **15**, in accordance with an embodiment, the attachment element **120** may form the substrate onto which the sensing element **102** and communication device **104** are disposed. That is, a leak detection system **1500** in accordance with an embodiment can include the sensing element **102** and communication device **104** directly coupled to the attachment element **120**. In a particular embodiment, direct coupling of the sensing element **102** and communication device **104** with the attachment element **120** may reduce weight of the leak detection system **1500** as compared to a previously described leak detection system **1000**. Additionally, the leak detection system **1500** may position the sensing element **102** closer to the fluid interface **114** (FIG. **2**) as compared to the leak detection system **1000**. In a particular embodiment, the attachment element **120** may include a material having a high fluid transfer rate as described above with respect to the substrate **302**. This may accelerate fluid transmission to the sensing element **102**, thus decreasing lag time from occurrence of a leak until notification to a user or system which may then take steps to correct the leak.

As illustrated, the leak detection system **1500** may be disposed along a surface of the attachment element **120**. In another embodiment, the leak detection system **1500** may be at least partially embedded in the attachment element **120**. In yet another embodiment, the leak detection system **1500** may be fully embedded in the attachment element **120** such that the sensing element **102** may not be visible. In a particular embodiment, at least one of the sensing element **102** and communication device **104** may be at least partially visible through the attachment element **120**.

FIG. **16** illustrates an attachment element **1620** having a plurality of frangible portions **1622**. As shown in FIG. **16**, the frangible portions **1622** may permit resizing of the attachment element **1620**. That is, the frangible portions may be selectively ruptured to adjust a length of the attachment element **1620**. In this regard, the attachment element **1620** may have an initial length, as measured prior to use, and an operational length, as measured prior to attachment, where the operational length may be no greater than the initial length, such as less than the initial length.

In an embodiment, the attachment element may include only one frangible portion. In other embodiments, the attachment element may include at least 2 frangible portions, such as at least 3 frangible portions, or at least 4 frangible portions, or at least 5 frangible portions, or at least 6 frangible portions, or at least 7 frangible portions, or at least 8 frangible portions, or at least 9 frangible portions, or at least 10 frangible portions. In an embodiment, the attachment element may include no more than 1000 frangible portions. In an embodiment, the attachment element may include at least 2 frangible portions and no more than 1000 frangible portions.

Each frangible portion may include a structurally weakened portion of the attachment element. For example, the frangible portion may be defined by one or more apertures passing through the attachment element. The apertures may extend at least partially through a thickness of the attachment element. In a more particular embodiment, the apertures may extend fully through the thickness of the attachment element. The apertures may transverse the attachment element, interspaced, for example, by portions of the attachment element. The frangible portion may rupture upon generation of sufficient force in a transverse, or generally transverse, direction with respect to the attachment element.

Referring again to FIG. 1, the leak detection system 1000 can include power source 132 coupled to at least one of the sensing element 102, the communication device 104, the substrate 106, or the attachment element 120. In a particular embodiment, the power source 132 may include a battery or other charge storing device. In a more particular embodiment, the power source 132 may be rechargeable, for example by 120V power supply. The power source 132 may be removable from the leak detection system 1000 to permit replacement thereof. Lithium batteries or rechargeable batteries or other battery forms can be used as part of the power source 132.

In an embodiment, the leak detection system 1000 can receive power from an electrical outlet. The leak detection system 1000 may include a conductive wire extending from an element on the leak detection system 1000 and terminating in a plug adapted to be inserted into a wall outlet. In this regard, the leak detection system 1000 can receive a constant flow of current, eliminating the need to charge or monitor electrical supply to the leak detection system 1000.

FIG. 17 shows a leak detection array 1700 having a plurality of leak detection systems 1702 disposed on a length of material 1710. As shown in FIG. 17, the material 1710 may include a fabric, such a woven or nonwoven fabric, a film, or another suitable substrate formed from a textile, polymer, metal, alloy, or other suitable material. In a particular embodiment, the material 1710 may be flexible, permitting the leak detection array 1700 to bend.

Each leak detection system 1702 may include one or more features from the previously described leak detection systems 100, 1402, 1406, 1410, 1414, 1416, 1424, and 1500. In particular, each leak detection system 1702 may include a sensor 1704 and a communication device 1706. In an embodiment, the leak detection systems 1702 may be identical to one another. For example, a first leak detection system and a second leak detection system of the leak detection systems 1702 may be identical to one another. In another embodiment, the leak detection systems 1702 may be different from one another. For example, a first leak detection system of the leak detection systems 1702 may be different from a third leak detection system of the leak detection systems 1702. In another embodiment, at least two of the leak detection systems 1702 may include different leak detection systems previously described herein. That is, the leak detection systems 1702 of the leak detection array 1700 may operate differently than one another. For example, a first leak detection system of the leak detection array 1700 may be similar to that illustrated in FIG. 4 while a second leak detection system of the leak detection array 1700 may be similar to that illustrated in FIGS. 11 and 12.

In an embodiment, the leak detection array 1700 may be dividable into n-divisible sections, where n is the number of leak detection systems 1702 in the leak detection array 1700. Thus, for example, leak detection arrays 1700 with four leak detection systems 1702 (as illustrated in FIG. 17) include 4

dividable sections. In a particular instance, the leak detection array 1700 can include at least 2 leak detection systems, such as at least 3 leak detection systems, or at least 4 leak detection systems, or at least 5 leak detection systems, or at least 10 leak detection systems, or at least 20 leak detection systems, or at least 50 leak detection systems, or at least 100 leak detection systems. In an embodiment, the leak detection array 1700 can include no greater than 10,000 leak detection systems 1702. In an embodiment, the leak detection array 1700 can include at least 2 leak detection systems 1702 and no greater than 10,000 leak detection systems 1702.

Frangible portions 1708 disposed between adjacent leak detection systems 1702 may facilitate easier division of the adjacent leak detection systems 1702 and 1702. That is, the frangible portions 1708 may permit a user to selectively tear off a discrete leak detection system 1702 from the leak detection array 1700. In an embodiment, the frangible portions 1708 may rupture upon application of a force of at least 1 N, such as at least 2 N, or at least 5 N, or at least 10 N, or at least 100 N. In another embodiment, the frangible portions 1708 may rupture upon application of a force of no greater than 10,000 N, such as no greater than 1000 N, or no greater than 125 N. In another embodiment, the frangible portions 1708 may rupture upon application of a force of at least 1N, and no greater than 10,000 N.

Each of the leak detection systems 1702 may be adapted to operate independently of the other leak detection systems 1702 of the leak detection array 1700. That is, each leak detection system 1702 may be self-sustaining and self-sufficient—requiring no further outside component for effective operation. In an embodiment, the leak detection systems 1702 may operate independently of one another or in smaller groups of leak detection arrays 1700, such as for example, two leak detection systems 1702 connected together.

In an embodiment, at least one of the leak detection systems 1702 can further include a power source 1712 coupled to at least one of the sensor 1704 and communication device 1706. In a particular embodiment, the power source 1712 may self-activate (i.e., generate current flow) upon rupture of the adjacent frangible portion 1708. This may preserve the power source 1712 until the at least one leak detection system 1702 is ready to be installed.

It is contemplated that the leak detection array 1700 may be rolled and stored in a housing, accessible through an opening therein. A user may grasp an exposed portion of the leak detection array to unwind the roll. Upon unwinding a suitable number of leak detection systems 1702, the user may tear the respective frangible portion 1708, separating the suitable leak detection systems 1702 from the remaining leak detection array 1700.

As stated above, data may be sent directly to the communication device 104 and/or communication hub 105 where the communication device 104 and/or communication hub 105 may calculate the threshold values and transmit the acceptable or unacceptable reading to a graphical user interface (“GUI”). FIGS. 18A-18D illustrate a number of variable displays of an exemplary graphical user interface (GUI) according to embodiments of the leak detection system disclosed herein. The recited GUI is exemplary and not meant to limit the different GUIs that could work in monitoring and using the leak detection system disclosed herein. In an embodiment, the GUI may be operable in a clean room environment. In an embodiment, the GUI may include an operable touch-screen adapted to be actuated through a material comprising a fabric or polymer or combination thereof. As shown in FIG. 18A, the leak detection

system **1000** (and/or GUI) may further include an electronic display **1800**. The electronic display **1800** may be located on the communication hub **105** itself, or may be located on another component of the leak detection system **1000** or another system altogether. The electronic display **1800** may be configured to display various screens of the graphical user interface (GUI) **1802**. The GUI **1802** may include a home screen **1804**, a status screen **1808**, and a device details screen **1810**. The GUI home screen **1804** may include an overall system indicator **1804a**. The overall system indicator **1804a** may indicate whether the system is operational or if there is an issue with the leak detection system, as explained in further detail below.

The GUI home screen **1804** may include a “configuration” soft button **1804b**. The GUI home screen **1804** may include a “status” soft button **1804c**. The GUI home screen **1804** may include a “commission” soft button **1804d**. The GUI home screen **1804** or any of the succeeding screens of the GUI may be password protected as discussed below. For example, a password screen may be shown to a user where the user must enter a predetermined password to see the GUI home screen **1804**.

Further, the GUI home screen **1804** or any of the succeeding screens of the GUI may include an alarm feature. The alarm may be adapted to alert a user of an undesirable change in at least one of the first, second, third and fourth states of the sensor **100**. The alarm may be indicated by an audible sound and/or a visual representation (e.g. color and flashing combination on the electronic display) indicating that a component of the leak detection system **1000** has an issue and is not working properly or is detecting a leak. The alarm effect may be modified in volume or visual appearance to indicate the severity of the issue. If multiple threshold levels are used for the different states, each may cause a different alarm, audible and/or visual, to be initiated. Depending on the level of threshold value, the color or pattern may change. In addition, an audible sound may be altered in response to the state value of one of the four states increasing or decreasing above or below a threshold level.

If a user actuates the “status” soft button **1804c**, the user will be taken to a status screen **1808**. The status screen may show a column **1808a** of sensors **100** or sensing elements **102**, a column **1808b** indicating whether each of the sensors **100** or sensing elements **102** is “enabled,” and a column **1808c** indicating the current status of each sensor **100** or sensing elements **102**. The column of enablement **1808b** may indicate whether the sensor is desired to be in use and may use a check to indicate this enablement. The column of the current status **1808c** may indicate whether each sensor has an issue with one of the four states (leak detection, operability of the sensor, battery life, and signal strength). The issue may be that the sensor **100** or sensing element **102** (or group of sensors **100** or sensing elements **102**) has crossed the threshold and has an unacceptable reading. Colors may be used to indicate the readings and the level of the threshold. The status screen **1808** may include a “disable all” soft button **1808d**, which may be actuated to turn off all the sensors **100** or sensing elements **102**. The “disable all” soft button **1808d** may be toggled to “enable all” to likewise turn on all the sensors **100** or sensing elements **102**. The status screen **1808** may include a “home” soft button **1808e**, which may be actuated to return the user to the GUI home screen **1804**. The status screen **1808** may include a “previous page” soft button **1808f**, which may be actuated to cycle through the list of sensors **100** or sensing elements **102** with respective inputs in each of their respective columns **1808b**, **1808c** for each sensor **100** or sensing element **102** in the

system. The status screen **1808** may include a “next page” soft button **1808g**, which may be actuated to cycle through the list of sensors **100** or sensing elements **102** with respective inputs in each of their respective columns **1808b**, **1808c** for each sensor **100** or sensing element **102** in the leak detection system **1000**. In addition, the current status column **1808c** may include soft buttons that may be actuated to bring up a device details screen **1810**. The device details screen **1810** may include a device name display **1810a**, indicating which sensor **100** or sensing element **102** in the leak detection system **1000** is being reviewed in detail. The device name display **1810a** may indicate a user given name for a particular sensor **100** or sensing element **102** or group of sensors **100** or sensing elements **102**. The device details screen **1810** may include a device enabled display **1810b**, indicating whether the indicated sensor **100** or sensing element **102** in the leak detection system **1000** is enabled. The device details screen **1810** may include a comments display **1810c**, allowing user entered input comments regarding the sensor **100** or sensing element **102** in the leak detection system **1000**. The device details screen **1810** may include a device ID display **1810d**, further indicating which sensor **100** or sensing element **102** in the leak detection system **1000** is being reviewed in detail. The device ID column **1810a** may indicate the scan code for a particular sensor **100** or sensing element **102** and be operatively connected to a scanning device able to scan a barcode on the sensor **100** or sensing element. The device details screen **1810** may include an install date display **1810e**, indicating when the sensor **100** or sensing element **102** in the leak detection system **1000** was installed in the leak detection system **1000**. The device details screen **1810** may include a last communication display **1810f**, indicating when the sensor **100** or sensing element **102** in the leak detection system **1000** communicated with the communication hub **105** in the leak detection system **1000**. The device details screen **1810** may include a device status display **1810g**, indicating whether each of the four states (leak detection, operability of the sensor, battery life, and signal strength) has crossed the threshold and has an unacceptable reading for that particular sensor **100** or sensing element **102** in the leak detection system **1000** communicated with the communication hub **105** in the leak detection system **1000**, resulting in an issue. The leak detection state may have an indicator box **1810g1** within the device status display **1810g**. The operability state may have an indicator box **1810g2** within the device status display **1810g**. The battery life state may have an indicator box **1810g3** within the device status display **1810g**. The signal strength state may have an indicator box **1810g4** within the device status display **1810g**. Colors may indicate whether the threshold for each state has been crossed. For example, a green color may indicate an acceptable reading and a red color may indicate an unacceptable reading for each of the four states indicated by a box in the device status display **1810g**. The device details screen **1810** may include a “cancel” soft button **1810h**, which may be actuated to cancel user inputs in the screen and return to the status screen **1808**. The device details screen **1810** may include a “remove” soft button **1810i**, which may be actuated to delete the device from the status screen **1808**. The device details screen **1810** may include a “replace” soft button **1810j**, which may be actuated to go to a commission scan device screen as described below. The device details screen **1810** may include an “edit” soft button **1810k**, which may be actuated to edit comments regarding the sensor in the comments display **1810c**. The comments may be saved once pressed and the user returned to the status

screen **1808**. Any and all user input actuators on any of the home screen **1804**, status screen **1808**, or device details screen **1810** may be password protected.

Referring now to FIG. **18B**, the “commission” soft button **1804d** on the home screen **1804** may be actuated to enter a “commission scan device” screen **1812**. However, before entering the “commission scan device” screen **1812**, a password screen **1806** may be shown to a user where the user must enter a predetermined password to see the GUI “commission scan device” screen **1812**. The commission scan device screen **1812** may include a device ID column **1812a**, a device name column **1812b**, and an active column **112c**. The device ID column **1812a** may indicate the scan code for a particular sensor **100** or sensing element **102**. The device ID column **1812a** may indicate the scan code for a particular sensor **100** or sensing element **102** and be operatively connected to a scanning device able to scan a barcode on the sensor **100** or sensing element. The device name column **1812b** may indicate a user given name for a particular sensor **100** or sensing element **102** or group of sensors **100** or sensing elements **102**. The active column **1812c** may indicate whether a particular sensor **100** or sensing element **102** or group of sensors **100** or sensing elements **102** are enabled and actively being monitored by the communication hub **105**. Pressing the active column **1812c** column may take the user to the device details screen **1810** for a particular sensor **100** or sensing element **102** or group of sensors **100** or sensing elements **102**. The commission scan device screen **1812** may include a “home” soft button **1812d**. The home soft button when actuated may return the user to the home screen **1804**. The commission scan device screen **1812** may include a “new device” soft button **1812e**. The new soft button **1812e** when actuated may take the user to a commission barcode screen discussed below. The commission scan device screen **1812** may include a “previous page” soft button **1812f**, which may be actuated to cycle through the list of sensors **100** or sensing elements **102** with respective inputs in each of their respective columns **1812b**, **1812c** for each sensor **100** or sensing element **102** in the system. The commission scan device screen **1812** may include a “next page” soft button **1812g**, which may be actuated to cycle through the list of sensors **100** or sensing elements **102** with respective inputs in each of their respective columns **1812b**, **1812c** for each sensor **100** or sensing element **102** in the leak detection system **1000**.

Pressing the new device **1812e** soft button may take a user to a “commission screen” **1814**. The commission screen **1814** may include a device ID display **1814a**, further indicating which sensor **100** or sensing element **102** in the leak detection system **1000** is being reviewed in detail. The device ID display **1814a** may indicate the scan code for a particular sensor **100** or sensing element **102** and be operatively connected to a scanning device able to scan a barcode on the sensor **100** or sensing element. The commission screen **1814** may include a device name display **1814b**, indicating which sensor **100** or sensing element **102** in the leak detection system **1000** named by the user. The commission screen **1814** may include a comments display **1814c**, allowing user entered input comments regarding the sensor **100** or sensing element **102** in the leak detection system **1000**. The commission screen **1814** may include an “import device file” soft button **18014d**, which may be actuated to input data or a device file for a particular sensor **100** or sensing element **102**. The commission screen **1814** may include a “add” soft button **18014e**, which may be actuated to add a particular sensor **100** or sensing element

102. In addition, an “exit” soft-button **1814f** may be available to the user to exit the screen **1814** and return to the home screen **1804**.

Referring now to FIG. **18C**, the “configuration” soft button **1804b** on the home screen **1804** may be actuated to enter a “configuration” screen **1816**. However, before entering the “configuration” screen **1816**, a password screen **1806** may be shown to a user where the user must enter a predetermined password to see the GUI “configuration” screen **1816**. The configuration screen **1816** may include a “group selection” drop down menu **1816a** where a user may select a group of sensors **100** or sensing elements **102** that a user wants to monitor. The configuration screen **1816** may include a “alarm device settings” region **1816b** where a user may select a number of alarm parameters (e.g. Protocol, Host IP, Port) for the alarm device for a group of sensors **100** or sensing elements **102**. The configuration screen **1816** may include a “network settings” region where a user may select a number of network parameters **1816c** (e.g. IP address, Net Mask, Gateway) for the network for a group of sensors **100** or sensing elements **102** that a user wants to monitor discussed in more detail above. The configuration screen **1816** may include a “set time” region **1816d** where a user may select an appropriate date and time.

Referring now to FIG. **18D**, the home screen **1804** may include different displays indicating the health of the leak detection system **1000**. As shown in home screen **1804(i)** the overall system indicator **1804a** (see FIG. **18A**) may display “configure system” when the system needs to be configured to contain the sensors **100** and their parameters. Once the system is configured by selecting the “configuration” soft button **1804b** and uploading, entering, and assigning required information to the sensors **100** in the leak detection system **1000**. As shown in home screen **1804(ii)** the overall system indicator **1804a** may display “system disabled” when all sensors **100** are disabled, such as when the disable all soft button **1184b** on the status screen **1808** is actuated. As shown in home screen **1804(iii)** the overall system indicator **1804a** may display “system operation” when at least one sensor **100** or sensing unit **102** or a plurality of sensors **100** or sensing units **102** are operational and within acceptable thresholds for at least one of the four states (leak detection, operability of the sensor, battery life, and signal strength). As shown in home screen **1804(iv)** the overall system indicator **1804a** may display “no devices commission” when the leak detection system **1000** does not include or does not receive a signal from at least one sensor **100** or sensing unit **102**. As shown in home screen **1804(v)** the overall system indicator **1804a** may display “leak detected” when at least one sensor **100** or sensing unit **102** or a plurality of sensors **100** or sensing units **102** are detecting a leak as crossing a threshold for the first state. An alarm may sound when this threshold is crossed as discussed above. As shown in home screen **1804(vi)** the overall system indicator **1804a** may display “lost communication” when at least one sensor **100** or sensing unit **102** or a plurality of sensors **100** or sensing units **102** are detecting a lost communication as crossing a threshold for the fourth state. An alarm may sound when this threshold is crossed as discussed above. As shown in home screen **1804(vii)** the overall system indicator **1804a** may display “battery low” when at least one sensor **100** or sensing unit **102** or a plurality of sensors **100** or sensing units **102** are detecting a low battery as crossing a threshold for the third state. An alarm may sound when this threshold is crossed as discussed above. As shown in home screen **1804(viii)** the overall system indicator **1804a** may display “sensor failure” when at least one sensor **100** or sensing unit

25

102 or a plurality of sensors 100 or sensing units 102 are detecting an operability failure for the sensor/sensors as crossing a threshold for the second state. An alarm may sound when this threshold is crossed as discussed above. The overall system indicator 1804a may change colors and/or flash to further alert a user.

As stated above, the leak detection system may be monitored by the following steps: 1) determining via a controller a first state of a sensor comprising a first condition when the sensor is dry and a second condition when the sensor is wet; 2) determining via the controller a second state representing an operability of the sensor; 3) communicating via the controller each of the states of the sensor to a Graphical User Interface (GUI); and 4) displaying, via the GUI, a representation of the first and second states of the sensor. Optionally the method may further include determining via the controller a third state of the sensor comprising a measure of the battery life of the sensor, and wherein the displaying step further comprises displaying, via the GUI, a representation of the third state of the sensor. Further, optionally, the method may further include determining via the controller a fourth state of the sensor comprising a measure of the signal strength of the sensor to the controller, and wherein the displaying step further comprises displaying, via the GUI, a representation of the fourth state of the sensor. FIG. 19 illustrates an exemplary process of monitoring the leak detection system for the first state (leak detection) to follow these steps. In further detail regarding FIG. 19, an exemplary process for locating and correcting an unacceptable reading for a state (e.g. leak detection) regarding the leak detection system is provided. The process starts at step 902, where sensors or sensing units are monitored. At step 904, a determination as to whether the leak detection threshold level is exceeded is made by the communication device 104 and/or communication hub 105. If the leak detection threshold level is not exceeded, then the process returns to step 902. If the leak detection threshold level is exceeded, then the process continues at step 906, where a user is notified (for example via an audible and visual fluid leak alarm activated or otherwise initiated on the GUI and/or electronic display). The process continues at step 908, where an audible and visual representation of leak magnitude may be activated to show a fluid leak level, or indication thereof from a sensor or sensing unit or group of sensors or sensing units in a location where the leak is occurring and the severity of the leak. The process continues at step 910, where the fluid leak alarm is reset by a user once the leak issue has been attended to. Any of the four states may be monitored using a similar process as shown for the first state (e.g. leak detection) in FIG. 19.

Leak detection systems and arrays as described herein may be used on various fluid component for fluid leakage monitoring. Exemplary fluid component may be found in electronic device fabrication such as in the semiconductor and superconductor industry; medical devices such as fluid transport lines and pumps; pipe couplings such as those found in the oil and gas industry, potable water systems, and sewers; aerospace industry; food and beverage industry; and automotive industry. Use of the graphical user interface (GUI) and or LoRa protocol in monitoring leak detection may lead to longer battery life and enable more robust sensor technologies that might not be viable with other wireless technologies.

Many different aspects and embodiments are possible. Some of those aspects and embodiments are described below. After reading this specification, skilled artisans will appreciate that those aspects and embodiments are only

26

illustrative and do not limit the scope of the present invention. Embodiments may be in accordance with any one or more of the embodiments as listed below.

Embodiment 1: A method of monitoring at least one leak detection sensor, the method comprising the steps of: determining via a communication hub a first state of a sensor comprising a first condition when the sensor is dry and a second condition when the sensor is wet; determining via the communication hub a second state representing an operability of the sensor; communicating via the communication hub each of the states of the sensor to a Graphical User Interface (GUI); and displaying, via the GUI, a representation of the first and second states of the sensor.

Embodiment 2: The method of embodiment 1, further comprising determining via the communication hub a third state of the sensor comprising a measure of the battery life of the sensor, and wherein the displaying step further comprises displaying, via the GUI, a representation of the third state of the sensor.

Embodiment 3: The method of embodiment 2, further comprising determining via the communication hub a fourth state of the sensor comprising a measure of the signal strength of the sensor to the communication hub, and wherein the displaying step further comprises displaying, via the GUI, a representation of the fourth state of the sensor.

Embodiment 4: The method of embodiment 3, wherein at least one of the determining steps further comprises receiving sensor data from the sensor and determining at least one of the first, second, third and fourth states of the sensor via the communication hub.

Embodiment 5: The method of embodiment 1, wherein the communicating step comprises communicating via a communication hub configured to communicate to the sensor via a wireless protocol.

Embodiment 6: The method of embodiment 5, wherein the wireless protocol comprises a LoRa network protocol.

Embodiment 7: The method of embodiment 1, wherein the GUI comprises an operable touch-screen adapted to be actuated through a material comprising a fabric or polymer or combination thereof.

Embodiment 8: The method of embodiment 1, wherein the GUI is operable in a clean room environment.

Embodiment 9: The method of embodiment 3, wherein the GUI comprises an alarm adapted to alert a user of an undesirable change in at least one of the first, second, third and fourth states of the sensor.

Embodiment 10: The method of embodiment 9, wherein the alarm is adapted to alert a user if the first state of the sensor measures fluid contact to the sensor.

Embodiment 11: The method of embodiment 9, wherein the alarm is adapted to alert a user if the second state of the sensor measures inoperability.

Embodiment 12: The method of embodiment 9, wherein the alarm is adapted to alert a user if the third state of a sensor measures outside an acceptable battery life range of the sensor.

Embodiment 13: The method of embodiment 9, wherein the alarm is adapted to alert a user if the fourth state of the sensor measures outside an acceptable signal range of the sensor.

Embodiment 14: The method of embodiment 1, wherein the sensor is located on a pipe housing a fluid.

Embodiment 15: The method of embodiment 14, wherein the fluid is a corrosive fluid.

Embodiment 16: The method of embodiment 14, wherein the at least one sensor comprises a plurality of leak detection sensors.

27

Embodiment 17: A leak detection system comprising: a sensor having a first state comprising a first condition when the sensor is dry and a second condition when the sensor is wet, and a second state representing an operability of the sensor; a communication device operatively connected to the sensor; and an attachment element adapted to attach the leak detection system to a fluid component for monitoring fluid leakage, wherein the communication device is adapted to receive the first state from the sensor via a wireless protocol, wherein the communication device is adapted to communicate the first and second states of the sensor to a Graphical User Interface (GUI).

Embodiment 18: The leak detection system of embodiment 17, wherein the communicating device comprises a communication hub configured to communicate with the sensor via a wireless protocol.

Embodiment 19: The leak detection system of embodiment 18, wherein the wireless protocol comprises a LoRa network.

Embodiment 20: The leak detection system of embodiment 17, wherein the sensor comprises: a substrate; and a first detection element in communication with the substrate, wherein the first detection element is adapted to change in response to fluid contact with the sensor.

Note that not all of the features described above are required, that a portion of a specific feature may not be required, and that one or more features may be provided in addition to those described. Still further, the order in which features are described is not necessarily the order in which the features are installed.

Certain features are, for clarity, described herein in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features that are, for brevity, described in the context of a single embodiment, may also be provided separately or in any subcombinations.

Benefits, other advantages, and solutions to problems have been described above with regard to specific embodiments. However, the benefits, advantages, solutions to problems, and any feature(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential feature of any or all the claims.

The specification and illustrations of the embodiments described herein are intended to provide a general understanding of the structure of the various embodiments. The specification and illustrations are not intended to serve as an exhaustive and comprehensive description of all of the elements and features of apparatus and systems that use the structures or methods described herein. Separate embodiments may also be provided in combination in a single embodiment, and conversely, various features that are, for brevity, described in the context of a single embodiment, may also be provided separately or in any subcombination. Further, reference to values stated in ranges includes each and every value within that range. Many other embodiments may be apparent to skilled artisans only after reading this specification. Other embodiments may be used and derived from the disclosure, such that a structural substitution, logical substitution, or any change may be made without departing from the scope of the disclosure. Accordingly, the disclosure is to be regarded as illustrative rather than restrictive.

The invention claimed is:

1. A method of monitoring at least one leak detection sensor, the method comprising the steps of:

28

determining via a communication hub a first state of a sensor comprising a first condition when the sensor is dry and a second condition when the sensor is wet; determining via the communication hub a second state representing an operability of the sensor; communicating via the communication hub each of the first and second states of the sensor to a Graphical User Interface (GUI); and displaying, via the GUI, a representation of the first and second states of the sensor, wherein the GUI comprises an alarm adapted to alert a user of an undesirable change in at least one of the first and second states of the sensor, wherein the alarm is adapted to alert a user if the first state of the sensor measures fluid contact to the sensor, further comprising determining via the communication hub a third state of the sensor comprising a measure of a battery life of the sensor, and wherein the displaying further comprises displaying, via the GUI, a representation of the third state of the sensor, and further comprising determining via the communication hub a fourth state of the sensor comprising a measure of a signal strength of the sensor to the communication hub, and wherein the displaying further comprises displaying, via the GUI, a representation of the fourth state of the sensor.

2. The method of claim 1, wherein at least one of determining the third state and determining the fourth state further comprises receiving sensor data from the sensor and determining at least one of the first, second, third and fourth states of the sensor via the communication hub.

3. The method of claim 1, wherein the communicating comprises communicating via a communication hub configured to communicate to the sensor via a wireless protocol.

4. The method of claim 3, wherein the wireless protocol comprises a LoRa network protocol.

5. The method of claim 1, wherein the GUI comprises an operable touch-screen adapted to be actuated through a material comprising a fabric or polymer or combination thereof.

6. The method of claim 1, wherein the GUI is operable in a clean room environment.

7. The method of claim 1, wherein the alarm is adapted to alert a user if the second state of the sensor measures inoperability.

8. The method of claim 1, wherein the alarm is adapted to alert a user if the third state of the sensor measures outside an acceptable battery life range of the sensor.

9. The method of claim 1, wherein the alarm is adapted to alert a user if the fourth state of the sensor measures outside an acceptable signal range of the sensor.

10. A leak detection system comprising:
a sensor having a first state comprising a first condition when the sensor is dry and a second condition when the sensor is wet, and a second state representing an operability of the sensor;
a communication device operatively connected to the sensor; and
an attachment element adapted to attach the leak detection system to a fluid component for monitoring fluid leakage, wherein the communication device is adapted to receive the first state from the sensor via a wireless protocol, wherein the communication device is adapted to communicate the first and second states of the sensor to a Graphical User Interface (GUI), wherein the GUI comprises an alarm adapted to alert a user of an undesirable change in at least one of the first and second states of the sensor, wherein the alarm is

adapted to alert a user if the first state of the sensor measures fluid contact to the sensor, further comprising determining via the communication hub a third state of the sensor comprising a measure of a battery life of the sensor, and wherein the displaying further comprises displaying, via the GUI, a representation of the third state of the sensor, and further comprising determining via the communication hub a fourth state of the sensor comprising a measure of a signal strength of the sensor to the communication hub, and wherein the displaying further comprises displaying, via the GUI, a representation of the fourth state of the sensor.

11. The leak detection system of claim **10**, wherein the communicating device comprises a communication hub configured to communicate with the sensor via a wireless protocol.

12. The leak detection system of claim **11**, wherein the wireless protocol comprises a LoRa network.

13. The leak detection system of claim **10**, wherein the sensor comprises: a substrate; and a first detection element in communication with the substrate, wherein the first detection element is adapted to change in response to fluid contact with the sensor.

* * * * *