



(86) Date de dépôt PCT/PCT Filing Date: 2006/04/12

(87) Date publication PCT/PCT Publication Date: 2006/10/19

(45) Date de délivrance/Issue Date: 2014/04/08

(85) Entrée phase nationale/National Entry: 2007/09/28

(86) N° demande PCT/PCT Application No.: US 2006/014146

(87) N° publication PCT/PCT Publication No.: 2006/110901

(30) Priorité/Priority: 2005/04/12 (US60/670,437)

(51) Cl.Int./Int.Cl. *C12P 19/02* (2006.01)

(72) Inventeurs/Inventors:

DUNSON, JAMES B., US;
TUCKER, MELVIN, US;
ELANDER, RICHARD, US;
HENNESSEY, SUSAN M., US


(73) Propriétaires/Owners:

E.I. DU PONT DE NEMOURS AND COMPANY, US;
ALLIANCE FOR SUSTAINABLE ENERGY, LLC, US

(74) Agent: TORYS LLP

(54) Titre : TRAITEMENT DE BIOMASSE EN VUE D'OBTENIR DES SUCRES FERMENTESCIBLES

(54) Title: TREATMENT OF BIOMASS TO OBTAIN FERMENTABLE SUGARS



(57) Abrégé/Abstract:

Biomass is pretreated using a low concentration of aqueous ammonia at high biomass concentration. Pretreated biomass is further hydrolyzed with a saccharification enzyme consortium. Fermentable sugars released by saccharification may be utilized for the production of target chemicals by fermentation.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
19 October 2006 (19.10.2006)

PCT

(10) International Publication Number
WO 2006/110901 A3

(51) International Patent Classification:

C12P 19/02 (2006.01)

(21) International Application Number:

PCT/US2006/014146

(22) International Filing Date: 12 April 2006 (12.04.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/670,437 12 April 2005 (12.04.2005) US

(71) Applicant (for all designated States except US): **E. I. DU PONT DE NEMOURS AND COMPANY** [US/US]; 1007 Market Street, Wilmington, Delaware 19898 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DUNSON, James B.** [US/US]; 202 Winslow Road, Newark, Delaware 19711 (US). **TUCKER, Melvin** [US/US]; 2570 Garland Street, Lakewood, Colorado 80215 (US). **ELANDER, Richard** [US/US]; 9229 S. William Cody Drive, Evergreen, Colorado 80439 (US). **HENNESSEY, Susan, M.** [US/US]; 32 Truman Lane, Avondale, Pennsylvania 19311 (US).(74) Agent: **LHULIER, Christine, M.**; E. I. du Pont de Nemours and Company, Legal Patent Records Center, 4417 Lancaster Pike, Wilmington, Delaware 19805 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(88) Date of publication of the international search report:

29 March 2007

[Continued on next page]

(54) Title: TREATMENT OF BIOMASS TO OBTAIN FERMENTABLE SUGARS



(57) Abstract: Biomass is pretreated using a low concentration of aqueous ammonia at high biomass concentration. Pretreated biomass is further hydrolyzed with a saccharification enzyme consortium. Fermentable sugars released by saccharification may be utilized for the production of target chemicals by fermentation.

WO 2006/110901 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

TITLE

TREATMENT OF BIOMASS TO OBTAIN FERMENTABLE SUGARS

5

STATEMENT OF GOVERNMENT RIGHTS

10

This invention was made with United States government support under Contract No. 04-03-CA-70224 awarded by the Department of Energy. The government has certain rights in this invention.

15

FIELD OF THE INVENTION

Methods for treating biomass to obtain fermentable sugars are provided. Specifically, fermentable sugars are obtained by pretreating biomass under conditions of high solids and low ammonia concentration, followed by saccharification.

20

BACKGROUND OF THE INVENTION

Cellulosic and lignocellulosic feedstocks and wastes, such as agricultural residues, wood, forestry wastes, sludge from paper manufacture, and municipal and industrial solid wastes, provide a potentially large renewable feedstock for the production of chemicals, plastics, fuels and feeds. Cellulosic and lignocellulosic feedstocks and wastes, composed of carbohydrate polymers comprising cellulose, hemicellulose, glucans and lignin are generally treated by a variety of chemical, mechanical and enzymatic means to release primarily hexose and pentose sugars, which can then be fermented to useful products.

30

Pretreatment methods are used to make the carbohydrate polymers of cellulosic and lignocellulosic materials more readily available to saccharification enzymes. Standard pretreatment methods have historically utilized primarily strong acids at high temperatures; however

35

due to high energy costs, high equipment costs, high pretreatment catalyst recovery costs and incompatibility with saccharification enzymes, alternative methods are being developed, such as enzymatic pretreatment, or the use of acid or base at milder temperatures where
5 decreased hydrolysis of biomass carbohydrate polymers occurs during pretreatment, requiring improved enzyme systems to saccharify both cellulose and hemicellulose.

A number of pretreatment methods utilizing base have been proposed. Gould (Biotech. and Bioengr. (1984) 26:46-52) discloses a
10 pretreatment method for lignocellulosic biomass using hydrogen peroxide (H_2O_2). The treatment is most efficient using H_2O_2 in an amount of at least 0.25 wt/wt with respect to substrate.

Teixeira, L., *et al.* (Appl. Biochem. and Biotech. (1999) 77-79:19-34) disclosed a series of biomass pretreatments using stoichiometric amounts
15 of sodium hydroxide and ammonium hydroxide, with very low biomass concentration. The ratio of solution to biomass is 14:1.

Elshafei, A. *et al.* (Bioresource Tech. (1991) 35:73-80) examined the pretreatment of corn stover utilizing NaOH.

Kim, T. and Y. Lee (Bioresource Technology (2005) 96:2007-2013)
20 report the use of high amounts of aqueous ammonia for the pretreatment of corn stover.

Patent Application WO2004/081185 discusses methods for hydrolyzing lignocellulose, comprising contacting the lignocellulose with a chemical; the chemical may be a base, such as sodium carbonate or
25 potassium hydroxide, at a pH of about 9 to about 14, under moderate conditions of temperature, pressure and pH.

U.S. Patent Nos. 5,916,780 and 6,090,595, describe a pretreatment process wherein a specified ratio of arabinoxylan to total nonstarch polysaccharides (AX/NSP) is assessed and used to select the feedstock.

30 In order to be an economically competitive process, a commercial process for the production of fermentable sugars from a renewable resource biomass requires the hydrolysis of carbohydrates in lignocellulosic biomass to provide high yields of sugars at high

concentrations, using low amounts of chemicals, to produce a source of fermentable sugars with low toxicity toward fermentative organisms that convert sugars to value-added chemicals and fuels.

5

SUMMARY OF THE INVENTION

The present invention provides a method for treating biomass to produce fermentable sugars. The process of the invention involves a pretreatment step wherein biomass at relatively high concentration is
10 treated with a low concentration of ammonia relative to the dry weight of biomass. Following pretreatment, the biomass is treated with a saccharification enzyme consortium to produce fermentable sugars. In one embodiment of the invention, the process comprises:

- a) contacting biomass with an aqueous solution comprising
15 ammonia to form a biomass-aqueous ammonia mixture, wherein the ammonia is present at a concentration at least sufficient to maintain alkaline pH of the biomass-aqueous ammonia mixture but wherein said ammonia is present at less than about 12 weight percent relative to dry weight of biomass, and further wherein the
20 dry weight of biomass is at a high solids concentration of at least about 15 weight percent relative to the weight of the biomass-aqueous ammonia mixture; and
- b) contacting the product of step (a) with a saccharification enzyme consortium under suitable conditions, to produce fermentable
25 sugars.

Biomass refers to any cellulosic or lignocellulosic material, for example, bioenergy crops, agricultural residues, municipal solid waste, industrial solid waste, yard waste, wood, forestry waste and combinations thereof. The aqueous solution comprising ammonia may be derived from
30 ammonia gas, ammonium hydroxide, urea, and combinations thereof. According to the process of the invention, the aqueous solution comprising ammonia may comprise at least one additional base. In addition, according to the process of the invention, vacuum may be applied to the biomass prior to contacting the biomass with an aqueous solution

comprising ammonia. Ammonia may also be removed prior to step (b); ammonia may be recycled back to the pretreatment reactor. The ammonia and biomass may be reacted in the process of the invention at a temperature that is between about 4 °C and about 200 °C. A plasticizer, softening agent or combination thereof may be used in the process of the invention. In addition, energy may be applied to the biomass before or during step (a), before or during step (b), or a combination thereof in order to reduce the size, increase the exposed surface area, and/or increase the accessibility of cellulose, hemicellulose and/or oligosaccharides present in the biomass.

The saccharification enzyme consortium may comprise one or more glycosidases; the glycosidases may be selected from the group consisting of cellulose-hydrolyzing glycosidases, hemicellulose-hydrolyzing glycosidases, and starch-hydrolyzing glycosidases. Other enzymes in the saccharification enzyme consortium may include peptidases, lipases, ligninases and feruloyl esterases.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows the growth of *Zymomonas mobilis* 8b (described in US Patent Application Publication 2003/0162271 A1, examples IV, VI and XII) in the presence or absence of acetamide and acetic acid.

DETAILED DESCRIPTION OF THE INVENTION

Further, when an amount, concentration, or other value or parameter is given as either a range, preferred range, or a list of upper preferable values and lower preferable values, this is to be understood as specifically disclosing all ranges formed from any pair of any upper range limit or preferred value and any lower range limit or preferred value, regardless of whether ranges are separately disclosed. Where a range of numerical values is recited herein, unless otherwise stated, the range is intended to include the endpoints thereof, and all integers and fractions within the range. It is not intended that the scope of

the invention be limited to the specific values recited when defining a range.

The present invention provides a process for the treatment of biomass to produce fermentable sugars; the process involves a pretreatment step wherein biomass at relatively high concentration is treated with a relatively low concentration of ammonia relative to the dry weight of the biomass. The ammonia-treated biomass is then digested with a saccharification enzyme consortium to produce fermentable sugars.

Definitions:

In this disclosure, a number of terms are used. The following definitions are provided:

The term "fermentable sugar" refers to oligosaccharides and monosaccharides that can be used as a carbon source by a microorganism in a fermentation process.

The term "lignocellulosic" refers to a composition comprising both lignin and cellulose. Lignocellulosic material may also comprise hemicellulose.

The term "cellulosic" refers to a composition comprising cellulose.

By "dry weight" of biomass is meant the weight of the biomass having all or essentially all water removed. Dry weight is typically measured according to American Society for Testing and Materials (ASTM) Standard E1756-01 (Standard Test Method for Determination of Total Solids in Biomass) or Technical Association of the Pulp and Paper Industry, Inc. (TAPPI) Standard T-412 om-02 (Moisture in Pulp, Paper and Paperboard).

The term "target chemical" refers to a chemical produced by fermentation. Chemical is used in a broad sense and includes molecules such as proteins, including, for example, peptides, enzymes and antibodies.

A target chemical that is "derivable from biomass" is a target chemical produced by a process whereby biomass is hydrolyzed to release fermentable sugars, and the fermentable sugars are fermented using at least one biocatalyst to produce a desired target chemical.

The terms "plasticizer" and "softening agent" refer to materials that cause a reduction in the cohesive intermolecular forces along or between polymer chains. Such materials may act, for example, to decrease crystallinity, or disrupt bonds between lignin and non-lignin carbohydrate
5 fibers (e.g., cellulose or hemicellulose).

The term "saccharification" refers to the production of fermentable sugars from polysaccharides.

The term "pretreated biomass" means biomass that has been subjected to pretreatment prior to saccharification.

10 "Biomass" refers to any cellulosic or lignocellulosic material and includes materials comprising cellulose, and optionally further comprising hemicellulose, lignin, starch, oligosaccharides and/or monosaccharides. Biomass may also comprise additional components, such as protein and/or lipid. According to the invention, biomass may be derived from a
15 single source, or biomass can comprise a mixture derived from more than one source; for example, biomass could comprise a mixture of corn cobs and corn stover, or a mixture of grass and leaves. Biomass includes, but is not limited to, bioenergy crops, agricultural residues, municipal solid waste, industrial solid waste, sludge from paper manufacture, yard waste,
20 wood and forestry waste. Examples of biomass include, but are not limited to, corn grain, corn cobs, crop residues such as corn husks, corn stover, grasses, wheat, wheat straw, barley, barley straw, hay, rice straw, switchgrass, waste paper, sugar cane bagasse, sorghum, soy, components obtained from milling of grains, trees, branches, roots, leaves,
25 wood chips, sawdust, shrubs and bushes, vegetables, fruits, flowers and animal manure. In one embodiment, biomass that is useful for the invention includes biomass that has a relatively high carbohydrate value, is relatively dense, and/or is relatively easy to collect, transport, store and/or handle. In one embodiment of the invention, biomass that is useful
30 includes corn cobs, corn stover and sugar cane bagasse.

For the purposes of this invention, an "aqueous solution comprising ammonia" refers to the use of ammonia gas (NH_3), compounds comprising ammonium ions (NH_4^+) such as ammonium hydroxide or ammonium

sulfate, compounds that release ammonia upon degradation such as urea, and combinations thereof in an aqueous medium.

The concentration of ammonia used in the present method is minimally a concentration that is sufficient to maintain the pH of the biomass-aqueous ammonia mixture alkaline and maximally less than about 12 weight percent relative to dry weight of biomass. This low concentration of ammonia is sufficient for pretreatment, and the low concentration may also be less than about 10 weight percent relative to dry weight of biomass. A very low concentration of 6 percent ammonia relative to dry weight of biomass, or less, also may be used for pretreatment. By alkaline is meant a pH of greater than 7.0. Particularly suitable is a pH of the biomass-aqueous ammonia mixture that is greater than 8. In one embodiment, ammonia is present at less than about 10 weight percent relative to dry weight of biomass. Particularly suitable is ammonia at less than about 6 weight percent relative to dry weight of biomass.

Ammonia as used in the present process provides advantages over other bases. Ammonia partitions into a liquid phase and vapor phase. Gaseous ammonia can diffuse more easily through biomass than a liquid base, resulting in more efficacious pretreatment at lower concentrations. Ammonia also is shown herein in Example 11 to compete with hydrolysis, via ammonolysis, of acetyl esters in biomass to form acetamide. Acetamide is less toxic than acetate to certain fermentation organisms, such as *Zymomonas mobilis* (as demonstrated herein in Example 12). Thus conversion of acetyl esters to acetamide rather than to acetic acid reduces the need to remove acetic acid. The use of ammonia also reduces the requirement to supplement growth medium used during fermentation with a nitrogen source. In addition, ammonia is a low-cost material and thus provides an economical process. Ammonia can also be recycled to the pretreatment reactor during pretreatment or following pretreatment, thus enabling a more economical process. For example, following pretreatment, as the temperature is decreased to that suitable for saccharification, ammonia gas may be released, optionally in the presence

of a vacuum, and may be recycled. In a continuous process, ammonia may be continuously recycled.

According to the present method, the aqueous solution comprising ammonia may optionally comprise at least one additional base, such as sodium hydroxide, sodium carbonate, potassium hydroxide, potassium carbonate, calcium hydroxide and calcium carbonate. The at least one additional base may be added in an amount that is combined with ammonium to form an amount of total base that is less than about 20 weight percent relative to dry weight of biomass. Preferably the total second base plus ammonia is in an amount that is less than about 15 weight percent. Additional base(s) may be utilized, for example, to neutralize acids in biomass, to provide metal ions for the saccharification enzymes, or to provide metal ions for the fermentation growth medium.

In the present method, the dry weight of biomass is at an initial concentration of at least about 15% up to about 80% of the weight of the biomass-aqueous ammonia mixture. More suitably, the dry weight of biomass is at a concentration of from about 15% to about 60% of the weight of the biomass-aqueous ammonia mixture. The percent of biomass in the biomass-aqueous ammonia mixture is kept high to minimize the need for concentration of sugars resulting from saccharification of the pretreated biomass, for use in fermentation. The high biomass concentration also reduces the total volume of pretreatment material, making the process more economical.

The biomass may be used directly as obtained from the source, or energy may be applied to the biomass to reduce the size, increase the exposed surface area, and/or increase the availability of cellulose, hemicellulose, and/or oligosaccharides present in the biomass to ammonia and to saccharification enzymes used in the second step of the method. Energy means useful for reducing the size, increasing the exposed surface area, and/or increasing the availability of cellulose, hemicellulose, and/or oligosaccharides present in the biomass to ammonia and to saccharification enzymes include, but are not limited to, milling, crushing, grinding, shredding, chopping, disc refining, ultrasound, and microwave.

This application of energy may occur before or during pretreatment, before or during saccharification, or any combination thereof.

Pretreatment of biomass with ammonia solution is carried out in any suitable vessel. Typically the vessel is one that can withstand pressure, has a mechanism for heating, and has a mechanism for mixing the contents. Commercially available vessels include, for example, the Zipperclave[®] reactor (Autoclave Engineers, Erie, PA), the Jaygo reactor (Jaygo Manufacturing, Inc., Mahwah, NJ), and a steam gun reactor ((described in General Methods Autoclave Engineers, Erie, PA). Much larger scale reactors with similar capabilities may be used. Alternatively, the biomass and ammonia solution may be combined in one vessel, then transferred to another reactor. Also biomass may be pretreated in one vessel, then further processed in another reactor such as a steam gun reactor (described in General Methods; Autoclave Engineers, Erie, PA).

Prior to contacting the biomass with an aqueous solution comprising ammonia, vacuum may be applied to the vessel containing the biomass. By evacuating air from the pores of the biomass, better penetration of the ammonia into the biomass may be achieved. The time period for applying vacuum and the amount of negative pressure that is applied to the biomass will depend on the type of biomass and can be determined empirically so as to achieve optimal pretreatment of the biomass (as measured by the production of fermentable sugars following saccharification).

The contacting of the biomass with an aqueous solution comprising ammonia is carried out at a temperature of from about 4 °C to about 200 °C. Initial contact of the biomass with ammonia at 4 °C, allowing impregnation at this temperature, was found to increase the efficiency of saccharification over non-pretreated native biomass. In another embodiment, said contacting of the biomass is carried out at a temperature of from about 75 °C to about 150 °C. In still another embodiment, said contacting of the biomass is carried out at a temperature of from greater than 90 °C to about 150 °C.

The contacting of the biomass with an aqueous solution comprising ammonia is carried out for a period of time up to about 25 hrs. Longer periods of pretreatment are possible, however a shorter period of time may be preferable for practical, economic reasons. Typically a period of ammonia contact treatment is about 8 hours or less. Longer periods may provide the benefit of reducing the need for application of energy for breaking-up the biomass, therefore, a period of time up to about 25 hrs. may be preferable.

In one embodiment, the pretreatment process may be performed at a relatively high temperature for a relatively short period of time, for example at from about 100 °C to about 150 °C for about 5 min to about 2 hr. In another embodiment, the pretreatment process may be performed at a lower temperature for a relatively long period of time, for example from about 75 °C to about 100 °C for about 2 hr to about 8 hr. In still another embodiment, the pretreatment process may be performed at room temperature (approximately 22-26 °C) for an even longer period of time of about 24 hr. Other temperature and time combinations intermediate to these may also be used.

For the pretreatment process, the temperature, time for pretreatment, ammonia concentration, concentration of one or more additional bases, biomass concentration, biomass type and biomass particle size are related; thus these variables may be adjusted as necessary to obtain an optimal product to be contacted with a saccharification enzyme consortium.

A plasticizer, softening agent, or combination thereof, such as polyols (e.g., glycerol, ethylene glycol), esters of polyols (e.g., glycerol monoacetate), glycol ethers (e.g., diethylene glycol), acetamide, ethanol, and ethanolamines, may be added in the pretreatment process (i.e., step (a)). A plasticizer may be added as a component of the aqueous ammonia solution, as a separate solution, or as a dry component.

The pretreatment reaction may be performed in any suitable vessel, such as a batch reactor or a continuous reactor. One skilled in the art will recognize that at higher temperatures (above 100°C), a pressure vessel is

required. The suitable vessel may be equipped with a means, such as impellers, for agitating the biomass-aqueous ammonia mixture. Reactor design is discussed in Lin, K.-H., and Van Ness, H. C. (in Perry, R.H. and Chilton, C. H. (eds), Chemical Engineer's Handbook, 5th Edition (1973) Chapter 4, McGraw-Hill, NY). The pretreatment reaction may be carried out as a batch process, or as a continuous process.

It is well known to those skilled in the art that a nitrogen source is required for growth of microorganisms during fermentation; thus the use of ammonia during pretreatment provides a nitrogen source and reduces or eliminates the need to supplement the growth medium used during fermentation with a nitrogen source. If the pH of the pretreatment product exceeds that at which saccharification enzymes are active, or exceeds the range suitable for microbial growth in fermentation, acids may be utilized to reduce pH. The amount of acid used to achieve the desired pH may result in the formation of salts at concentrations that are inhibitory to saccharification enzymes or to microbial growth. In order to reduce the amount of acid required to achieve the desired pH and to reduce the raw material cost of NH_3 in the present pretreatment process, ammonia gas may be evacuated from the pretreatment reactor and recycled. Typically, at least a portion of the ammonia is removed, which reduces the pH but leaves some nitrogen that provides this nutrient for use in subsequent fermentation.

In order to obtain sufficient quantities of sugars from biomass, the biomass may be pretreated with an aqueous ammonia solution one time or more than one time. Likewise, a saccharification reaction can be performed one or more times. Both pretreatment and saccharification processes may be repeated if desired to obtain higher yields of sugars. To assess performance of the pretreatment and saccharification processes, separately or together, the theoretical yield of sugars derivable from the starting biomass can be determined and compared to measured yields.

Saccharification:

Following pretreatment, the product comprises a mixture of ammonia, partially degraded biomass and fermentable sugars. Prior to further processing, ammonia may be removed from the pretreated biomass by applying a vacuum. Removing ammonia lowers the pH, and thus less neutralizing acid is used to obtain the desired pH for saccharification and fermentation. This results in a lower salt load in the pretreatment mixture. Typically some ammonia remains, which is desired to provide a nitrogen source for fermentation.

The pretreatment mixture is then further hydrolyzed in the presence of a saccharification enzyme consortium to release oligosaccharides and/or monosaccharides in a hydrolyzate. Saccharification enzymes and methods for biomass treatment are reviewed in Lynd, L. R., *et al.* (Microbiol. Mol. Biol. Rev. (2002) 66:506-577). In one preferred embodiment, the entire pretreatment mixture comprising both soluble and insoluble fractions is utilized in the saccharification reaction.

In another embodiment, prior to saccharification, the aqueous fraction comprising ammonia and solubilized sugars may be separated from insoluble particulates remaining in the mixture. Methods for separating the soluble from the insoluble fractions include, but are not limited to, decantation and filtration. The insoluble particulates may be recycled to the pretreatment reactor. The insoluble particulates may optionally be washed with an aqueous solvent (e.g., water) to remove adsorbed sugars prior to being recycled to the pretreatment reactor. The insoluble fraction may then be subjected to additional treatment with aqueous ammonia solution as described above for pretreatment, followed by saccharification with a saccharification enzyme consortium. The soluble fraction may also be concentrated prior to saccharification using a suitable process, such as evaporation.

Prior to saccharification, the pretreatment product may be treated to alter the pH, composition or temperature such that the enzymes of the saccharification enzyme consortium will be active. The pH may be altered through the addition of acids in solid or liquid form. Alternatively, carbon

dioxide (CO₂), which may be recovered from fermentation, may be utilized to lower the pH. For example, CO₂ may be collected from a fermenter and fed, such as by bubbling, into the pretreatment product while monitoring the pH, until the desired pH is achieved. The temperature may be brought
5 to a temperature that is compatible with saccharification enzyme activity, as noted below. Any cofactors required for activity of enzymes used in saccharification may be added.

The saccharification enzyme consortium comprises one or more enzymes selected primarily, but not exclusively, from the group
10 "glycosidases" which hydrolyze the ether linkages of di-, oligo-, and polysaccharides and are found in the enzyme classification EC 3.2.1.x (Enzyme Nomenclature 1992, Academic Press, San Diego, CA with Supplement 1 (1993), Supplement 2 (1994), Supplement 3 (1995, Supplement 4 (1997) and Supplement 5 [in Eur. J. Biochem. (1994) 223:1-
15 5, Eur. J. Biochem. (1995) 232:1-6, Eur. J. Biochem. (1996) 237:1-5, Eur. J. Biochem. (1997) 250:1-6, and Eur. J. Biochem. (1999) 264:610-650, respectively]) of the general group "hydrolases" (EC 3.). Glycosidases useful in the present method can be categorized by the biomass component that they hydrolyze. Glycosidases useful for the present
20 method include cellulose-hydrolyzing glycosidases (for example, cellulases, endoglucanases, exoglucanases, cellobiohydrolases, β -glucosidases), hemicellulose-hydrolyzing glycosidases (for example, xylanases, endoxylanases, exoxylanases, β -xylosidases, arabinoxylanases, mannases, galactases, pectinases, glucuronidases),
25 and starch-hydrolyzing glycosidases (for example, amylases, α -amylases, β -amylases, glucoamylases, α -glucosidases, isoamylases). In addition, it may be useful to add other activities to the saccharification enzyme consortium such as peptidases (EC 3.4.x.y), lipases (EC 3.1.1.x and 3.1.4.x), ligninases (EC 1.11.1.x), and feruloyl esterases (EC 3.1.1.73) to
30 help release polysaccharides from other components of the biomass. It is well known in the art that microorganisms that produce polysaccharide-hydrolyzing enzymes often exhibit an activity, such as cellulose degradation, that is catalyzed by several enzymes or a group of enzymes

having different substrate specificities. Thus, a "cellulase" from a microorganism may comprise a group of enzymes, all of which may contribute to the cellulose-degrading activity. Commercial or non-commercial enzyme preparations, such as cellulase, may comprise numerous enzymes depending on the purification scheme utilized to obtain the enzyme. Thus, the saccharification enzyme consortium of the present method may comprise enzyme activity, such as "cellulase", however it is recognized that this activity may be catalyzed by more than one enzyme.

Saccharification enzymes may be obtained commercially, such as Spezyme[®] CP cellulase (Genencor International, Rochester, NY) and Multifect[®] xylanase (Genencor). In addition, saccharification enzymes may be produced biologically, including using recombinant microorganisms.

One skilled in the art would know how to determine the effective amount of enzymes to use in the consortium and adjust conditions for optimal enzyme activity. One skilled in the art would also know how to optimize the classes of enzyme activities required within the consortium to obtain optimal saccharification of a given pretreatment product under the selected conditions.

Preferably the saccharification reaction is performed at or near the temperature and pH optima for the saccharification enzymes. The temperature optimum used with the saccharification enzyme consortium in the present method ranges from about 15 °C to about 100 °C. In another embodiment, the temperature optimum ranges from about 20 °C to about 80 °C. The pH optimum can range from about 2 to about 11. In another embodiment, the pH optimum used with the saccharification enzyme consortium in the present method ranges from about 4 to about 10.

The saccharification can be performed for a time of about several minutes to about 120 hr, and preferably from about several minutes to about 48 hr. The time for the reaction will depend on enzyme concentration and specific activity, as well as the substrate used and the environmental conditions, such as temperature and pH. One skilled in the art can readily determine optimal conditions of temperature, pH and time

to be used with a particular substrate and saccharification enzyme(s) consortium.

The saccharification can be performed batch-wise or as a continuous process. The saccharification can also be performed in one
5 step, or in a number of steps. For example, different enzymes required for saccharification may exhibit different pH or temperature optima. A primary treatment can be performed with enzyme(s) at one temperature and pH, followed by secondary or tertiary (or more) treatments with different enzyme(s) at different temperatures and/or pH. In addition, treatment with
10 different enzymes in sequential steps may be at the same pH and/or temperature, or different pHs and temperatures, such as using hemicellulases stable and more active at higher pHs and temperatures followed by cellulases that are active at lower pHs and temperatures.

The degree of solubilization of sugars from biomass following
15 saccharification can be monitored by measuring the release of monosaccharides and oligosaccharides. Methods to measure monosaccharides and oligosaccharides are well known in the art. For example, the concentration of reducing sugars can be determined using the 1,3-dinitrosalicylic (DNS) acid assay (Miller, G. L., Anal. Chem. (1959)
20 31:426-428). Alternatively, sugars can be measured by HPLC using an appropriate column as described herein in the General Methods section.

Fermentable sugars released from biomass can be used by suitable microorganisms to produce target chemicals. Following saccharification, but prior to fermentation, the saccharification mixture may
25 be concentrated by evaporation, for example, to increase the concentration of fermentable sugars. Optionally, liquid in the saccharification product may be separated from solids in a batch or continuous method. Optionally, the liquid or the entire saccharification product may be sterilized prior to fermentation. Depending on the
30 microorganism(s) used during fermentation and the pH used during saccharification, the pH may be adjusted to that suitable for fermentation. In addition, the saccharification mixture may be supplemented with additional nutrients required for microbial growth. Supplements may

include, for example, yeast extract, specific amino acids, phosphate, nitrogen sources, salts, and trace elements. Components required for production of a specific product made by a specific biocatalyst may also be included, such as an antibiotic to maintain a plasmid or a cofactor
5 required in an enzyme catalyzed reaction. Also additional sugars may be included to increase the total sugar concentration. The saccharification mixture may be used as a component of a fermentation broth, for example, making up between about 100% and about 10% of the final medium.

10 Temperature and/or headspace gas may also be adjusted, depending on conditions useful for the fermentation microorganism(s). Fermentation may be aerobic or anaerobic. Fermentation may occur subsequent to saccharification, or may occur concurrently with saccharification by simultaneous saccharification and fermentation (SSF).
15 SSF can keep the sugar levels produced by saccharification low, thereby reducing potential product inhibition of the saccharification enzymes, reducing sugar availability for contaminating microorganisms, and improving the conversion of pretreated biomass to monosaccharides and/or oligosaccharides.

20 Target chemicals that may be produced by fermentation include, for example, acids, alcohols, alkanes, alkenes, aromatics, aldehydes, ketones, biopolymers, proteins, peptides, amino acids, vitamins, antibiotics, and pharmaceuticals. Alcohols include, but are not limited to methanol, ethanol, propanol, isopropanol, butanol, ethylene glycol,
25 propanediol, butanediol, glycerol, erythritol, xylitol, and sorbitol. Acids include acetic acid, lactic acid, propionic acid, 3-hydroxypropionic, butyric acid, gluconic acid, itaconic acid, citric acid, succinic acid and levulinic acid. Amino acids include glutamic acid, aspartic acid, methionine, lysine, glycine, arginine, threonine, phenylalanine and tyrosine. Additional target
30 chemicals include methane, ethylene, acetone and industrial enzymes.

The fermentation of sugars to target chemicals may be carried out by one or more appropriate biocatalysts in single or multistep fermentations. Biocatalysts may be microorganisms selected from

bacteria, filamentous fungi and yeast. Biocatalysts may be wild type microorganisms or recombinant microorganisms, and include *Escherichia*, *Zymomonas*, *Saccharomyces*, *Candida*, *Pichia*, *Streptomyces*, *Bacillus*, *Lactobacillus*, and *Clostridium*. In another embodiment, biocatalysts may
5 be selected from the group consisting of recombinant *Escherichia coli*, *Zymomonas mobilis*, *Bacillus stearothermophilus*, *Saccharomyces cerevisiae*, *Clostridia thermocellum*, *Thermoanaerobacterium saccharolyticum*, and *Pichia stipitis*

Many biocatalysts used in fermentation to produce target chemicals
10 have been described and others may be discovered, produced through mutation, or engineered through recombinant means. Any biocatalyst that uses fermentable sugars produced in the present method may be used to make the target chemical(s) that it is known to produce, by fermentation in the present method.

15 Fermentation of carbohydrates to acetone, butanol, and ethanol (ABE fermentation) by solventogenic *Clostridia* is well known (Jones and Woods (1986) Microbiol. Rev. 50:484-524). A fermentation process for producing high levels of butanol, also producing acetone and ethanol, using a mutant strain of *Clostridium acetobutylicum* is described in US
20 5192673. The use of a mutant strain of *Clostridium beijerinckii* to produce high levels of butanol, also producing acetone and ethanol, is described in US 6358717. Genetically modified strains of *E. coli* have also been used as biocatalysts for ethanol production (Underwood et al., (2002) Appl. Environ. Microbiol.68:6263-6272). A genetically modified strain of
25 *Zymomonas mobilis* that has improved production of ethanol is described in US 2003/0162271 A1.

Lactic acid has been produced in fermentations by recombinant strains of *E. coli* (Zhou et al., (2003) Appl. Environ. Microbiol. 69:399-407), natural strains of *Bacillus* (US20050250192), and *Rhizopus oryzae*
30 (Tay and Yang (2002) Biotechnol. Bioeng. 80:1-12). Recombinant strains of *E. coli* have been used as biocatalysts in fermentation to produce 1,3 propanediol (US 6013494, **US 6514733**), and adipic acid (Niu et al., (2002) Biotechnol. Prog. 18:201-211). Acetic acid has been made by

fermentation using recombinant *Clostridia* (Cheryan et al., (1997) Adv. Appl. Microbiol. 43:1-33), and newly identified yeast strains (Freer (2002) World J. Microbiol. Biotechnol. 18:271-275). Production of succinic acid by recombinant *E. coli* and other bacteria is disclosed in US 6159738, and by
5 mutant recombinant *E. coli* in Lin et al., (2005) Metab. Eng. 7:116-127). Pyruvic acid has been produced by mutant *Torulopsis glabrata* yeast (Li et al., (2001) Appl. Microbiol. Technol. 55:680-685) and by mutant *E. coli* (Yokota et al., (1994) Biosci. Biotech. Biochem. 58:2164-2167). Recombinant strains of *E. coli* have been used as biocatalysts for
10 production of para-hydroxycinnamic acid (US20030170834) and quinic acid (US20060003429).

A mutant of *Propionibacterium acidipropionici* has been used in fermentation to produce propionic acid (Suwannakham and Yang (2005) Biotechnol. Bioeng. 91:325-337), and butyric acid has been made by
15 *Clostridium tyrobutyricum* (Wu and Yang (2003) Biotechnol. Bioeng. 82:93-102). Propionate and propanol have been made by fermentation from threonine by *Clostridium* sp. strain 17cr1 (Janssen (2004) Arch. Microbiol. 182:482-486). A yeast-like *Aureobasidium pullulans* has been used to make gluconic acid (Anantassiadis et al., (2005) Biotechnol.
20 Bioeng. 91:494-501), by a mutant of *Aspergillus niger* (Singh et al., (2001) Indian J. Exp. Biol. 39:1136-43). 5-keto-D-gluconic acid was made by a mutant of *Gluconobacter oxydans* (Elfari et al., (2005) Appl Microbiol. Biotech. 66:668-674), itaconic acid was produced by mutants of
25 *Aspergillus terreus* (Reddy and Singh (2002) Bioresour. Technol. 85:69-71), citric acid was produced by a mutant *Aspergillus niger* strain (Ikram-Ul-Haq et al., (2005) Bioresour. Technol. 96:645-648), and xylitol was produced by *Candida guilliermondii* FTI 20037 (Mussatto and Roberto (2003) J. Appl. Microbiol. 95:331-337). 4-hydroxyvalerate-containing biopolyesters, also containing significant amounts of 3-hydroxybutyric acid
30 3-hydroxyvaleric acid, were produced by recombinant *Pseudomonas putida* and *Ralstonia eutropha* (Gorenflo et al., (2001) Biomacromolecules 2:45-57). L-2,3-butanediol was made by recombinant *E. coli* (Ui et al., (2004) Lett. Appl. Microbiol. 39:533-537).

Production of amino acids by fermentation has been accomplished using auxotrophic strains and amino acid analog-resistant strains of *Corynebacterium*, *Brevibacterium*, and *Serratia*. For example, production of histidine using a strain resistant to a histidine analog is described in Japanese Patent Publication No. 8596/81 and using a recombinant strain is described in EP 136359. Production of tryptophan using a strain resistant to a tryptophan analog is described in Japanese Patent Publication Nos. 4505/72 and 1937/76. Production of isoleucine using a strain resistant to an isoleucine analog is described in Japanese Patent Publication Nos. 38995/72, 6237/76, 32070/79. Production of phenylalanine using a strain resistant to a phenylalanine analog is described in Japanese Patent Publication No. 10035/81. Production of tyrosine using a strain requiring phenylalanine for growth, resistant to tyrosine (Agr. Chem. Soc. Japan 50 (1) R79-R87 (1976), or a recombinant strain (EP263515, EP332234), and production of arginine using a strain resistant to an L-arginine analog (Agr. Biol. Chem. (1972) 36:1675-1684, Japanese Patent Publication Nos. 37235/79 and 150381/82) have been described. Phenylalanine was also produced by fermentation in *Escherichia coli* strains ATCC 31882, 31883, and 31884. Production of glutamic acid in a recombinant coryneform bacterium is described in US 6962805. Production of threonine by a mutant strain of *E. coli* is described in Okamoto and Ikeda (2000) J. Biosci Bioeng. 89:87-79. Methionine was produced by a mutant strain of *Corynebacterium lilium* (Kumar et al, (2005) Bioresour. Technol. 96: 287-294).

Useful peptides, enzymes, and other proteins have also been made by biocatalysts (for example, in US6861237, US6777207, US6228630).

The pretreatment and saccharification of biomass to fermentable sugars, followed by fermentation of the sugars to a target chemical is exemplified in Example 9 herein for the production of ethanol from pretreated corn cobs using *Z. mobilis* as the biocatalyst for the fermentation of sugars to ethanol. The method of the present invention can also be used for the production of 1,3-propanediol from biomass. Biomass undergoes pretreatment and saccharification according to the

present invention; following (or during) saccharification, *E. coli* is used to produce 1,3-propanediol as described in Example 10 herein.

Target chemicals produced in fermentation by biocatalysts may be recovered using various methods known in the art. Products may be separated from other fermentation components by centrifugation, filtration, microfiltration, and nanofiltration. Products may be extracted by ion exchange, solvent extraction, or electrodialysis. Flocculating agents may be used to aid in product separation. As a specific example, bioproduced 1-butanol may be isolated from the fermentation medium using methods known in the art for ABE fermentations (see for example, Durre, *Appl. Microbiol. Biotechnol.* 49:639-648 (1998), Groot et al., *Process. Biochem.* 27:61-75 (1992), and references therein). For example, solids may be removed from the fermentation medium by centrifugation, filtration, decantation, or the like. Then, the 1-butanol may be isolated from the fermentation medium using methods such as distillation, azeotropic distillation, liquid-liquid extraction, adsorption, gas stripping, membrane evaporation, or pervaporation. Purification of 1,3-propanediol from fermentation media may be accomplished, for example, by subjecting the reaction mixture to extraction with an organic solvent, distillation, and column chromatography (U.S. 5,356,812). A particularly good organic solvent for this process is cyclohexane (U.S. 5,008,473). Amino acids may be collected from fermentation medium by methods such as ion-exchange resin adsorption and/or crystallization.

EXAMPLES

25 GENERAL METHODS AND MATERIALS

The following abbreviations are used:

“HPLC” is High Performance Liquid Chromatography, “C” is Centigrade, “kPa” is kiloPascal, “m” is meter, “mm” is millimeter, “kW” is kilowatt, “μm” is micrometer, “μL” is microliter, “mL” is milliliter, “L” is liter, “min” is minute, “mM” is millimolar, “cm” is centimeter, “g” is gram, “kg” is kilogram, “wt” is weight, “hr” is hour, “temp” or “T” is temperature, “theoret” is theoretical, “pretreat” is pretreatment, “DWB” is dry weight of biomass.

Sulfuric acid, ammonium hydroxide, acetic acid, acetamide, yeast extract, 2-morpholinoethanesulfonic acid (MES), potassium phosphate, glucose, xylose, tryptone, sodium chloride and citric acid were obtained from Sigma-Aldrich (St. Louis, MO).

5 Pretreatment reactors

Zipperclave[®] reactor

The 4-liter Zipperclave[®] reactor (Autoclave Engineers, Erie, PA) is a batch pressure vessel equipped with a 2.5-liter Hastelloy[®] pail for the biomass charge and an agitator to mix the biomass. The reactor vessel is
10 encircled by an electrical heater controlled at the desired pretreatment temperature. Direct steam injection is also used to rapidly bring the biomass up to pretreatment temperature. Steam pressure is adjusted and controlled to maintain the desired pretreatment temperature. Steam condensate formed by heating the Zipperclave[®] reactor head plate, vessel
15 and outside of the pail drain to a reservoir formed between the pail and the inner wall of the reactor to prevent excessive dilution of the pretreated slurry.

Jaygo reactor

The Jaygo reactor is a 130-liter (approximately 51 cm diameter x 91
20 cm length), horizontal paddle type reactor (Jaygo Manufacturing, Inc., Mahwah, NJ) fabricated of Hastelloy[®] C-22 alloy. The reactor is equipped with a steam jacket capable of heating to approximately 177 °C (862 kPa). Direct steam injection is also used to rapidly bring the biomass up to pretreatment temperature. Steam pressure is adjusted and controlled to
25 maintain the desired pretreatment temperature. Numerous ports allow injection of other solvents and hot liquids.

Steam gun reactor batch digestion system

The 4-liter steam gun reactor (Autoclave Engineers, Erie, PA) is a steam-jacketed reactor consisting of a length of 102 mm schedule 80
30 Hastelloy[®] pipe closed by two ball valves. Additional electrical heaters are

placed on all exposed, non-jacketed surfaces of the reactor and controlled to the pretreatment set point temperature. Direct steam injection is also used to rapidly bring the biomass up to pretreatment temperature. Steam pressure is adjusted and controlled to maintain the desired pretreatment
5 temperature. The bottom of the reactor is necked down to 51 mm. All pretreated material exits through a replaceable die at the bottom of the reactor and is collected in a nylon (Hotfill®) 0.21 m³ bag supported within a heavy walled, jacketed, and cooled flash tank.

Disc refiner

10 The disc refiner is a Sprout Waldron model 30.5 cm refiner (Andritz, Inc., Muncy, PA) equipped with a 11 kW electric motor. The gap between the stationary and rotating plates is variable. The feed auger speed is also variable, from 0-88 rpm. The inlet to the refiner was modified with six
15 injection ports to allow the introduction of steam, hot water, or other sweep gases and liquids just ahead of the rotating refiner plate. The refiner was equipped with plates (Durametal, Corp., Tulatin, OR) in either pattern D2A506 in Ni-Hard or pattern 18034-A in Ni-Hard.

Pretreatment and Enzymatic Hydrolysis Reactor (PEHR)

20 The 9L PEHReactor (constructed at NREL, Golden, CO; see co-pending US patent application CL3447) has an approximately 15 cm x 51 cm stainless steel reaction vessel with an injection lance for introduction of processing reactants. The injection lance is connected using a rotary joint to a port in a cover on one end of the vessel, which has an additional port
25 for vessel access. Four baffles run the length of the vessel wall, and are attached perpendicularly to the wall. The baffles and twenty-two ceramic attrition media cylinders of 3.2 cm X 3.2 cm (E.R. Advanced Ceramics, East Palestine, OH), free floating in the vessel, apply mechanical mixing of biomass and reactant as the vessel is rotated, promoting assimilation of
30 reactant into the biomass. The PEHReactor is placed on a Bellco Cell-Production Roller Apparatus (Bellco Technology, Vineland, NJ) which provides a mechanism for rotation, and the reactor with roller apparatus is

housed in a temperature controlled chamber which provides heat. Vacuum and pressure may be applied to the reaction vessel by attaching external sources to the lance-connected port in the cover.

5 Analytical methods

Cellulose quantitation

The amount of cellulose in each starting biomass sample was determined using methods well known in the art, such as ASTM E1758-01 "Standard method for the determination of carbohydrates by HPLC".

10

Measurement of sugar, acetamide, lactic acid and acetic acid content

Soluble sugars (glucose, cellobiose, xylose, galactose, arabinose and mannose), acetamide, lactic acid and acetic acid in saccharification liquor were measured by HPLC (Agilent Model 1100, Agilent

15

Technologies, Palo Alto, CA) using Bio-Rad HPX-87P and Bio-Rad HPX-87H columns (Bio-Rad Laboratories, Hercules, CA) with an appropriate guard columns. The sample pH was measured and adjusted to 5-6 with sulfuric acid if necessary. The sample was then passed through a 0.2 μ m syringe filter directly into an HPLC vial. The HPLC run conditions were as

20

follows:

Biorad Aminex HPX-87P (for carbohydrates):

Injection volume: 10 – 50 μ L, dependent on concentration and detector limits

Mobile phase: HPLC grade water, 0.2 μ m filtered and degassed

25

Flow rate: 0.6 mL / minute

Column temperature: 80 – 85 °C, guard column temperature <60°C

Detector temperature: as close to main column temperature as possible

Detector: refractive index

30

Run time: 35 minute data collection plus 15 minute post run (with possible adjustment for later eluting compounds)

Biorad Aminex HPX-87H (for carbohydrates, acetamide, lactic acid, acetic acid, and ethanol)

Injection volume: 5-10 μ L, dependent on concentration and detector limits

5 Mobile phase: .01N Sulfuric acid, 0.2 μ m filtered and degassed

Flow rate: 0.6 mL / minute

Column temperature: 55 °C

Detector temperature: as close to column temperature as possible

Detector: refractive index

10 Run time: 25 - 75 minute data collection

After the run, concentrations in the sample were determined from standard curves for each of the compounds.

15 Example 1

Stover Pretreatment at High Biomass Concentration, High Temperature
and Comparison of Ammonia Concentrations

The Zipperclave[®] reactor vessel and head plate were preheated to the target pretreatment temperature before introduction of the biomass charge by cycling steam into the reactor and venting several times. Condensate formed during preheating was removed by vacuum aspiration before pretreatment. The Hastelloy[®] pail was loaded with 0.635-cm (1/4-in.) milled stover (100 g, dry weight basis) and inserted into the pre-warmed reactor. The reactor agitator was set to 20 rpm while a vacuum (approximately 85 kPa) was applied to the vessel interior and biomass charge. Ammonium hydroxide solution of the necessary strength to give a dry weight of biomass concentration of 30 weight percent relative to the weight of the biomass-aqueous ammonia mixture, as well as the desired ammonia concentration listed in Table 1, was injected near the bottom of the vessel with a spray type nozzle. Test samples had a final ammonia concentration of 12% relative to dry weight of biomass, while samples with a final ammonia concentration of 35% relative to dry weight of biomass were used as a comparison. When the temperature of the biomass charge

reached 50 °C, steam was introduced near the bottom of the reactor to fluidize and raise the temperature of the biomass charge to either 140 °C or 170 °C. At the end of pretreatment, the reactor was depressurized through a vent condenser, and a vacuum (approximately 85 kPa) was applied for 3 minutes to lower the temperature and remove additional ammonia from the pretreated slurry prior to opening the reactor and recovering the pretreated biomass.

Whole, unwashed pretreatment slurry containing 0.5 g of cellulose (based on initial feedstock composition) was added in a final volume of 50 mL to a 125-mL shake flask. Acetic acid (10-100 µL) was added, to titrate the pH of the ammonia-pretreated biomass to 5.0 before enzyme addition because of the sensitivity of the enzymes to high pH environments. The pH was controlled at 5.0 during saccharification by the addition of 50 mM citrate buffer, and the temperature was maintained at 50 °C. Spezyme® CP cellulase (Genencor International, Rochester, NY) was added to the concentration listed for each sample in Table 1. The sugar content of the resulting saccharification liquor was determined after 96 hr saccharification according to the sugar measurement protocol described in the General Methods. Sugar release after 96 hr is shown in Table 2. Controls for this experiment were 1) untreated corn stover, which yielded 23% of the theoretical yield of glucose (using 56 mg cellulase /g cellulose) and 2) steam (140 °C) pretreated corn stover, which yielded 40% of the theoretical yield of glucose (using 56 mg cellulase /g cellulose); xylose was not measured for the controls.

Table 1: Sugar release from pretreated corn stover with 96 hr saccharification

DWB: dry weight of biomass.

Ammonia (g /100 g DWB)	Pretreat Temp (°C)	Pretreat Time	Cellulase (mg/g cellulose)	Glucose Release (% theoret)	Xylose Release (% theoret)
35	170	5 min	56	68.0	60.0
12	170	5 min	56	58.5	45.3

12	170	5 min	11	40.8	27.1
35	140	5 min	56	54.5	41.5
12	140	5 min	56	53.0	31.4
12	140	5 min	11	38.9	17.1
12	140	15 min	56	62.4	49.6
12	140	15 min	11	41.7	33.6

These results indicate that a pretreatment using ammonia at 12% for 15 minutes at 140 °C, followed by saccharification, releases more glucose and xylose than when pretreatment is using 35% ammonia for 5 minutes at 140 °C. Thus, advantages of using lower ammonia can be
5 incorporated by a small increase in pretreatment time.

Example 2

Stover Pretreatment at High Biomass Concentration, Low Temperature, and Very Low Ammonia

The Jaygo reactor was charged with 0.635-cm milled stover (13 kg, dry weight basis). A vacuum (67.7 kPa) was applied to the vessel, and dilute ammonium hydroxide solution was injected to give an ammonia concentration of 6.2 g ammonia/100 g dry weight of biomass and a dry weight of biomass concentration 30 weight percent relative to total weight of the biomass-aqueous ammonia mixture. The vacuum was relieved, and
10 steam was applied to the jacket to heat the stover to 100 °C. The soaked stover was held at temperature for 8 hr with constant mixing at 32 rpm, then allowed to cool overnight with continued mixing of the resulting slurry.

Whole, unwashed pretreatment slurry containing 0.5 g of cellulose (based on initial feedstock composition) was added in a final volume of 50 mL to a 125-mL shake flask. Acetic acid (10-100 µL) was added, if
20 necessary, to titrate the pH of the ammonia-pretreated biomass to 5.0 before enzyme addition because of the sensitivity of the enzymes to high pH environments. The pH was controlled at 5.0 during saccharification by the addition of 50 mM citrate buffer, and the temperature was maintained at 50 °C. Spezyme® CP cellulase (Genencor International, Rochester, NY)
25 was added to 56 mg/g cellulose. The sugar content of the resulting saccharification liquor was determined after 96 hr saccharification

according to the sugar measurement protocol described in the General Methods and is shown in Table 2.

Table 2. Sugar release from pretreated corn stover at 96 hr

Ammonia (g /100 g DWB)	Pretreat Temp (°C)	Pretreat Time	Cellulase (mg/g cellulose)	Glucose Release (% theoret)	Xylose Release (% theoret)
6.2	100	8 hr	56	63.9	44.8

5

The results indicate that these very low ammonia concentrations and low temperature pretreatment conditions, (for a period of 8 hr) are as effective as using 12% ammonia at 140 °C for 15 min.

10

Example 3

Cob Pretreatment at High Biomass Concentration, Low Temperature, and Very Low Ammonia Concentration Followed by High Biomass Concentration Saccharification

Whole or fractured corn cobs (approximately 13 kg, dry weight basis) were loaded into the Jaygo reactor. Cobs were fractured by passing through the disk refiner (General Methods) equipped with plates C-2975. Resulting fractured cobs were passed through a 1.27 cm screen. Any pieces retained were passed through the disk refiner again with a 0.5 cm smaller gap. A vacuum was applied to the reactor, and dilute ammonium hydroxide solution was injected to give the final desired ammonia concentration (2% or 6%) and concentration of dry biomass (30% or 40%), as given in Table 3. The vacuum was relieved and steam was applied to the jacket to heat the cobs while soaking to a temperature of 93 °C for the whole cob sample and 85 °C for fractured cob samples. Short periods of increased agitator speeds (up to 96 rpm) were applied in an effort to increase the heating rate. The soaked cobs were held at temperature for 4 or 8 hr with constant mixing at 32 rpm then allowed to cool overnight with continued mixing.

25

Before pretreated biomass was removed from the reactor, the reactor was put under vacuum at 90 °C to strip ammonia out of the pretreated biomass. Before saccharification, the pH of the pretreated cob biomass was adjusted to 5.5 with solid citric acid. About 10 kg of

5 pretreated whole cob was saccharified in the Jaygo reactor at 50 °C. About 1400 g of pretreated fractured cob was added to the PEHReactor, along with 22 ceramic attrition cylinders (3.2 cm diameter x 3.2 cm long; E. R. Advanced Ceramics, East Palestine, OH), for saccharification. An enzyme mixture of 28 mg Spezyme CP[®]/g cellulose in untreated stover

10 plus 28 mg/g cellulose Multifect Xylanase[®] was used for each saccharification reaction. The final dry weight of biomass concentration at the beginning of each saccharification was 30% relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture. The PEHReactor was rotated axially at 19 rpm while maintaining a

15 temperature of 50 °C. The sugar content of the resulting saccharification liquor was determined according to the sugar measurement protocol in the General Methods. Sugar release after 96 hr is shown in Table 3.

Table 3: Sugar release from pretreated corn cobs using a high

20 concentration of biomass (by dry weight) during saccharification.

DWB: dry weight of biomass (percent is calculated relative to the total weight of the mixture)

Feed-stock	Pretreat time (hr)	Pretreat-ment temp. (°C)	Ammonia (g/100 g DWB)	DWB (Pretreat)	DWB (Saccharif.)	Glucose Release (% theore)	Xylose Release (% theore)
Whole cob	8 hr	93	6	40%	30%	54.4	46.1
Fractured cob	4 hr	85	2	30%	30%	42.1	19.1

Example 4

Cob Pretreatment at High Biomass Concentration, High Temperature, and Very Low Ammonia Concentration Followed by High Biomass

5 Concentration Saccharification

Fractured corn cobs (13 kg, dry basis) were loaded into the Jaygo reactor. After pulling a vacuum on the reactor, ammonium hydroxide solution of the proper strength to give 2% ammonia and 30% dry weight of biomass concentration was pumped into the reactor with 32 rpm mixing at
10 room temperature. The contents of the reactor were then heated to 95 °C using low-pressure jacket steam. Once the reactor reached 95 °C, direct steam injection was used to heat the contents of the reactor to 145 °C. When the reactor reached 145 °C, the reactor contents were held at that temperature for 20 minutes using jacket steam and some direct steam
15 injection. After 20 minutes, a vacuum was pulled on the vent to the reactor and the shredder motor was turned on for 5 minutes. After 1 hr the cooling water to the jacket was turned on. The contents of the Jaygo reactor were cooled to between 33 °C and 37 °C; then CO₂ was used to pressurize the reactor to 138 kPa. The pressurized CO₂ atmosphere was
20 maintained for 30 min. The final temperature of the reactor contents was between 27 °C to 31 °C. The pH of the soaked/pretreated biomass was approximately 7.5.

Pretreated biomass was removed from the Jaygo reactor and transferred to the PEHReactor for saccharification at a final dry weight of
25 biomass concentration at the beginning for saccharification of 30% relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture. The pH was then adjusted to 5.5 with solid citric acid, and the material digested with 28 mg Spezyme CP[®]/g cellulose and 28 mg Multifect Xylanase[®]/g cellulose in untreated cob as described in Example
30 3. The sugar content of the resulting saccharification liquor was determined according to the sugar measurement protocol in the General Methods. The sugar release after 96 hr digestion is shown in Table 4.

Table 4. Sugar release from pretreated corn cobs using a high concentration of biomass (by dry weight) during saccharification.

Feed-stock	Pretreat time (hr)	Pretreatment temperature (°C)	Ammonia (g/100 g DWB)	DWB (Pretreat)	DWB (Saccharif.)	Glucose Release (% theorel)	Xylose Release (% theorel)
Fractured cob	20 min	145	2	30%	30%	35.9	45.4

Example 5

5 Pretreatment with Addition of Plasticizer

Whole cob was pretreated as described in Example 3 at a dry weight of biomass concentration of about 30% relative to the total weight of the biomass-aqueous ammonia mixture, 2 weight percent ammonia relative to dry weight of biomass, 100 °C, for 8 hr in the Jaygo reactor with
 10 3 weight percent relative to dry weight of biomass of glycerol added to act as a plasticizer. After pretreatment, the pH of the resulting material was adjusted to 5 with solid citric acid. Pretreated cob was then digested as described in Example 3. An enzyme mixture of 28 mg Spezyme CP®/g cellulose in untreated stover plus 28 mg/g cellulose Multifect Xylanase® in
 15 untreated cob was used. After 96 hr digestion, glucose concentration was 92.3 g/L and xylose concentration was 54.4 g/L.

Example 6

Disc Refining of Pretreated Biomass

Stover was pretreated in the manner described in Example 1, with
 20 different samples having low ammonia (12%) or comparative ammonia (35%) concentrations, and temperature, time, and enzyme conditions as listed in Table 5. Whole cob was pretreated as described in Example 3 with different samples having very low ammonia (3% or 6%), and other conditions as listed in Table 5. Following pretreatment, the samples were
 25 passed through a Sprout Waldron disc refiner. The gap between the stationary plate and rotating plate was set at 0.254 mm (0.010 inch) and the feed auger speed at 7 rpm. Refined material was saccharified as

described in Example 2 and the sugar content of the resulting saccharification liquor was determined according to the sugar measurement protocol in the General Methods. Results of the saccharification at 96 hr are shown in Table 5. The results showed that
 5 with disc refining prior to saccharification, better digestibility was attained, or use of lower enzyme concentrations was effective.

Table 5: Digestibility of pretreated material that was disc refined prior to saccharification

Feed-stock	Pretreat time	Pretreat Temp (°C)	Ammonia (g/100 g DWB)	Cellulase (mg/g cellulose)	Xylanase Added (mg/g cellulose)	Glucose Release (% theorel)	Xylose Release (% theorel)
Stover	5 min	170	35	56	0	87.3	72.5
Stover	5 min	140	35	56	0	76.9	59.4
Stover	5 min	170	12	56	0	58.8	39.9
Stover	5 min	170	12	28	28	68.4	62.3
Stover	5 min	140	12	56	0	69.1	48.6
Stover	5 min	140	12	11	0	52.6	31.5
Stover	15 min	140	12	56	0	61.8	40.1
Stover	15 min	140	12	28	28	66.7	54.1
Stover	8 hr	100	6	56	0	79.9	59.6
Cob	8 hr	93	6	56	0	82.4	51.7
Cob	8 hr	93	6	28	28	83.1	58.6
Cob	8 hr	100	2	56	0	68.0	38.5
Cob	8 hr	100	2	28	28	81.0	57.3

10

Example 7

Steam Gun Treatment of Pretreated Biomass

Stover was pretreated as described in Example 1 using conditions of 30% dry weight of biomass relative to total weight of biomass-aqueous ammonia mixture, 6 weight percent ammonia relative to DWB, 100 °C, 8
 15 hr, in the Jaygo reactor. Cob was pretreated as described in Example 3 using conditions of 40% dry weight of biomass relative to total weight of biomass-aqueous ammonia mixture, 6 weight percent ammonia relative to

DWB, 93 °C, 8 hr, in the Jaygo reactor. Samples of each pretreated biomass were separately loaded into a 4-liter steam gun reactor.

Pretreated material was subjected to 170 °C for 5 min, or 140 °C for 20 min before being released through a die. The resulting material was
 5 saccharified as described in Example 2. Results are given in Table 6 below. The results showed that steam gun treatment prior to saccharification improved release of glucose.

Table 6: Digestibility of pretreated material after steam gun treatment

Feedstock	Steam Gun Temp (°C)	Steam Gun Time (min)	Cellulase (mg/g cellulose)	Xylanase Added (mg/g cellulose)	Glucose Release (% theoret)	Xylose Release (% theoret)
Stover	170	5	56	0	77.5	37.5
Stover	170	5	28	28	82.5	64.4
Stover	140	20	56	0	73.4	43.4
Stover	140	20	28	28	82.2	66.9
Cob	170	5	28	28	70.7	47.4
Cob	170	5	11	11	49.1	38.9
Cob	140	20	28	28	55.7	39.0
Cob	140	20	11	11	32.9	24.0

10

Example 8

Modeling of Pretreatment with Ammonia Recycle

Advantages of ammonia recycle were examined with Aspen models (Aspen Technologies, Cambridge, MA, version 12.1) for two pretreatment
 15 schemes: low temperature (85 °C), long residence time (4 hr) and high temperature (130 °C), short residence time (20 min). In each model there was a series of three flash tanks operating at successively lower pressures after the pretreatment reactor to provide a means for ammonia
 20 recycle. As the feed stream entered into each tank, it split into vapor and liquid fractions due to the reduction in pressure. The vapor fraction was recycled to pretreatment, while the liquid fraction went on to the next step in the process. Assuming 2 weight percent ammonia relative to DWB and

approximately 27% dry weight of biomass relative to the total weight of the biomass-aqueous ammonia mixture in pretreatment, ammonia supplied fresh and from the recycle streams for each process are shown in Table 7. In both models, the flash tanks operated in similar fashion so that

5 ammonia recycle was similar. For both scenarios, more than half of the required ammonia was supplied through recycle, reducing the need for and cost of fresh ammonia.

Table 7: Ammonia recycle in pretreatment - Aspen model results.

	High T/ short residence time		Low T/ long residence time	
	Ammonia flow rate into pretreatment (kg/hr)	Fraction total ammonia in pretreatment	Ammonia flow rate into pretreatment (kg/hr)	Fraction total ammonia in pretreatment
Fresh NH ₃	518.6	43.5%	520.2	43.7%
From 1 st flash	371.2	31.2%	374.4	31.4%
From 2 nd flash	137.2	11.5%	135.4	11.4%
From 3 rd flash	164.1	13.8%	161.2	13.5%
Total	1191.2	100%	1191.2	100%

10

Example 9

Ethanol Production from Low Ammonia-Pretreated and Saccharified Cob Biomass, and Comparison to High Ammonia-Pretreated and Saccharified Stover

Cob hydrolyzate was generated by pretreating whole cobs in the

15 Jaygo reactor for 8 hr at 93 °C with 6 weight percent ammonia relative to dry weight of biomass at a dry weight of biomass concentration of 40 weight percent relative to the total weight of the biomass-aqueous ammonia mixture, as described in Example 3. After pretreatment, ammonia was removed by heating the reactor to 90 °C under vacuum.

20 The pH of the pretreated biomass was then adjusted to 5 with sulfuric acid. The pretreated biomass was saccharified in the Jaygo reactor at 30% dry weight of biomass relative to the total weight of the pretreated

biomass-saccharification enzyme consortium mixture with 28 mg/g cellulose Spezyme[®] cellulase and 28 mg/g cellulose Multifect[®] xylanase for 168 hr at 50 °C and pH 5. The resulting hydrolyzate was used for fermentation of *Zymomonas mobilis* 8b in Sixfors fermentors (INFORS AG, Switzerland). *Zymomonas mobilis* 8b is a strain of *Zymomonas mobilis* that has been genetically engineered to give improved, over wild type, production of ethanol and is described in US Patent Application Publication 2003/0162271 A1 (Examples IV, VI and XII). The cob hydrolyzate comprised 78 g/L glucose, 51 g/L xylose, 6 g/L acetamide, and 7 g/L acetic acid. The cob hydrolyzate was used at 40% and 80% strength, with the balance of the medium being concentrated aqueous medium consisting of yeast extract, and KH₂PO₄ in quantities such that their concentrations in the final slurry were about 5 g/L, and 2 g/L respectively. Additionally, in the 40% hydrolyzate slurry, glucose and xylose were added in quantities sufficient to bring their concentrations to their same levels as in the 80% hydrolyzate slurry. The fermentation was carried out at 37 °C. Agitation in the fermentors was 100 rpm, and pH was maintained at 5.5 by addition of 2 N KOH. The results are shown in Table 8. Sugars and ethanol were analyzed as described in General Methods.

For comparison, stover hydrolyzate was generated by pretreating stover with 35 weight percent ammonia relative to dry weight of biomass at a dry weight of biomass concentration of about 30 weight percent relative to the total weight of the biomass-aqueous ammonia mixture at 170 °C for 5 min in the Zipperclave[®] reactor, as described in Example 1. The pretreated biomass was enzymatically digested at 30% dry weight of biomass relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture with 224 mg/g cellulose Spezyme CP[®] cellulase at 50 °C and pH 5 to generate a high sugar concentration hydrolyzate for fermentation testing. The resulting hydrolyzate comprised 88 g/L glucose, 52 g/L xylose, 9 g/L acetic acid and 15 g/L lactic acid. For ethanol production, *Zymomonas mobilis* 8b was fermented on either 40% or 80% (v/v) hydrolyzate slurry. The remaining volume was made up of concentrated aqueous medium consisting of

yeast extract, KH_2PO_4 and MES buffer in quantities such that their concentrations in the final slurry would be about 10 g/L, 2 g/L and 0.1 M, respectively. Additionally, in the 40% hydrolyzate slurry, glucose and xylose were added in quantities sufficient to bring their concentrations to the same levels as in the 80% hydrolyzate slurry. Fermentation was done at 30 °C and pH 6 in 25 ml shake flasks with 20 ml working volume. Agitation was maintained at 150 rpm. Analysis was as for the cob hydrolyzate fermentation sample and results are given in Table 8.

Table 8: Sugar utilization and ethanol yields in fermentation on cob and stover hydrolyzates.

	Stover (120 hr endpoint)		Cob (72 hr endpoint)	
	40% Hydrolyzate	80% Hydrolyzate	40% Hydrolyzate	80% Hydrolyzate
Glucose Utilized	100%	97%	99%	97%
Xylose Utilized	90%	16%	96%	57%
Ethanol Yield	77%	53%	98%	87%

These results showed that fermentation to produce ethanol from cob hydrolyzate pretreated with low ammonia was more efficient than from stover pretreated with high ammonia.

15

Example 10

1-3 Propanediol Production from Very Low Ammonia-Pretreated and Saccharified Cob Biomass

Hydrolyzate generated from pretreatment and saccharification of cob was fermented to produce 1,3-propanediol. Hydrolyzate was generated by pretreating cob pieces in the steam gun reactor. First cob biomass was loaded in the PEHReactor (described in General Methods), a vacuum applied, and dilute ammonium hydroxide solution was injected to give an ammonia concentration of 4 g ammonia/100 g dry weight biomass and a dry weight of biomass concentration of 30 g dry weight of biomass/100 g total biomass-aqueous ammonia mixture. The reactor vessel charged with ammonia and cob was rotated at 4°C for 30 min. The

contents were transferred to the steam gun reactor (described in General Methods), the temperature increased to 145°C, and the mixture was held at temperature for 20 minutes. Material from the steam gun was discharged into a flash tank, and vacuum was maintained on the flash tank to aid ammonia removal. After pH adjustment, the pretreated biomass was saccharified at 30 g dry weight of biomass/100 g pretreated biomass-saccharification enzyme consortium mixture with 28.4 mg/g cellulose Spezyme CP[®] cellulase and 10.1 mg active protein /g cellulose enzyme consortium consisting of β -glucosidase, xylanase, β -xylosidase and arabinofuranosidase for 72 hr at 50°C and pH 5.5. The resulting hydrolyzate was used as a source of fermentable sugar for conversion to 1,3-propanediol by recombinant *E. coli* strain RJ8n pBE93-k1. The construction of strain RJ8n pBE93-k1 is described in detail in PCT application WO/ 2004/018645 (Example 7), and it is a derivative of strain RJ8n, described in US 6358716. The hydrolyzate was used at 10% with the balance being aqueous medium consisting of 7.5 g/L KH₂PO₄, 2.0 g/L citric acid*H₂O, 4.0 ml/L 28% NH₄OH, 3.0 g/L(NH₄)₂SO₄, 2.0 g/L MgSO₄*7H₂O, 0.2 g/L CaCl₂*2H₂O, 0.33 g/L ferric ammonium citrate, 0.5 g/L yeast extract, 0.1 mg/L vitamin B12, 1.0 mg/L FeSO₄*7H₂O, 1 mg/L ZnSO₄*7H₂O, 0.1 g/L CuSO₄*5H₂O, 1 mg/L CoCl₂*6H₂O, 0.3 mg/L MnSO₄*7H₂O, 0.1 g/L H₃BO₄, 0.10 g/L NaMoO₄*2H₂O, 10 mg/L NaCl with the final pH adjusted to 6.8. Cultures were started from frozen stocks (15% glycerol as cryoprotectant) in 50 mL of medium in a 250 mL baffled flask. The cultures were incubated at 34 °C and 300 rpm shaking for 24 hours. The amount of 1,3-propanediol produced was measured by HPLC under the following conditions:

Column: Showdex SH1011

Sample volume: 20 μ L

Mobile phase: 0.01 N H₂SO₄

Flow rate: 0.5 ml/min

Column temperature 50°C

Detector: Waters 996 photodiode array

Detector temperature: 40°C

Run time: 40 min

Results are shown in Table 9 below. Products from glucose fermentation by the RJ8n pBE93-k1 strain of *E. coli* include glycerol (an intermediate metabolite) and 1,3-propanediol. Experiments were conducted in duplicate flasks and assayed at 24 hr. In this system, glucose in the hydrolysate was converted to both glycerol and 1,3-propanediol.

Table 9: Substrate utilization and product formation by fermentation with *E. coli*.

	Broth at time zero	Flask 1, 24 hr	Flask 2, 24 hr
Glucose (g/L)	7.39	2.12	2.10
Glycerol (g/L)	0	3.14	3.14
1,3-propanediol (g/L)	0	1.03	1.07
Glucose use	0	71%	72%

Example 11

Formation of Acetamide During Pretreatment

Samples derived from cobs pretreated according to the processes described in Example 3 and Example 4 were analyzed to determine the fate of the acetyl groups in the biomass. The pretreatment liquors (pretreatment mixture with insoluble solids removed) were assayed for acetic acid and acetamide content as follows. The pH of each sample was adjusted to about 3 with H₂SO₄ (72%). For measurement of acetamide, the sample was passed through a 0.2 µm filter and analyzed by HPLC according to the conditions listed below. For measurement of total acetate (includes acetate present as acetic acid and acetamide), the acidified sample was autoclaved for 1 hr at 121 °C; acetamide was quantitatively converted to acetic acid during this step. After autoclaving, the sample was allowed to cool. The sample was then passed through a 0.2 µm filter into a sample vial and analyzed according to the conditions listed below.

Acetic acid and acetamide concentrations were determined from standard curves generated for each.

Mobile phase: 0.01 N H₂SO₄, 0.2 μm filtered and degassed

5 Flow rate: 0.6 mL/min

Column temperature: 55-65 °C

Detector temperature: As close to column temperature as possible

Detector: Refractive index

Run time: 60 min

10 Column: Biorad Aminex HPX-87H column with corresponding guard column

Results for the 3 different pretreatment conditions assayed are shown in Table 10. In each case, all of the acetyl groups were solubilized
15 to either acetic acid or acetamide.

Table 10. Conversion of acetyl groups in biomass to acetamide during pretreatment.

DWB, dry weight of biomass. (percent is calculated relative to the
20 total weight of the biomass-aqueous ammonia mixture)

Feed-stock	Pretreat time (hr)	Pretreat temp (°C)	Ammonia (g/100 g DWB)	DWB (Pretreat)	Fraction of initial acetyl recovered in liquor	Fraction of recovered acetyl as acetamide	Fraction of recovered acetyl as acetic acid
Whole cob	8 hr	93	6	40%	100%	44%	56%
Fractured cob	4 hr	85	2	30%	90%	10%	90%
Fractured cob	20 min	145	2	30%	99%	9%	91%

Using an ammonia concentration of 6%, nearly half of the acetyl groups were converted to acetamide, which is non-inhibitory for biocatalyst growth as shown in Example 12.

Example 12

Effect of Acetamide and Acetic acid on *Zymomonas* Growth

To test the toxicity of acetamide and acetic acid, *Z. mobilis* strain 8b (described in Example 9) was grown in fermentation medium at pH 6.0 with and without acetamide or acetic acid. Fermentation medium was composed of 10 g/L yeast extract, 2 g/L KH_2PO_4 , 70 g/L glucose, 40 g/L xylose and 0.1 M MES buffer. *Z. mobilis* 8b was grown in 25-mL baffled Erlenmeyer shake flasks rotating at 150 rpm at 30 °C in unsupplemented medium (control), medium supplemented with 6 g/L acetamide, or medium supplemented with 7.2 g/L acetic acid. As shown in Figure 1, the presence of acetamide had no influence on the growth rate or final density of *Z. mobilis*, whereas the presence of acetic acid resulted in a reduced growth rate and lower cell yield (as measured by dry cell mass).

15

Example 13

Pretreatment of Bagasse at High Biomass Concentration, High Temperature, and Very Low Ammonia, and Saccharification at Low and High Concentration

The PEHReactor (described in General Methods), with no attrition media, was charged with 1.27 cm-milled bagasse (370 g, dry weight basis). This sugar cane bagasse was NIST Reference Material RM8491, from sugar cane clone H65-7052, originally obtained from the Hawaii Sugar Planters Association, Kunia substation, Oahu, HI. It was milled in a Wiley mill to pass through a 2 mm screen, with the fines (+74 mesh) removed. The PEHReactor vessel was cooled to 4°C by rotation in contact with ice on the outer surface. A vacuum was applied to the reactor vessel, and dilute ammonium hydroxide solution, that was pre-cooled in a cold room at 4°C and passed through tubing immersed in an ice-water bath, was injected to give an ammonia concentration of 4 g/100 g dry weight of biomass and a dry weight of biomass concentration of 45 g/100 g total biomass-aqueous ammonia mixture. The reactor vessel charged with ammonia and bagasse was cooled to 4°C by applying ice to the surface of the rotating reactor vessel, and rotated at 4°C for 30 min. At this time the

contents were transferred to the steam gun reactor that is described in General Methods. Once the steam gun reactor was charged with the ammonia-bagasse mixture, the temperature was increased to 145°C and the mixture was held at temperature for 20 minutes. At the end of the pretreatment time, the bagasse was discharged from the steam gun reactor through a 1-in circular die into a flash tank. A sample of pretreated bagasse was subsequently saccharified in a shake flask and another sample (approximately 163 g dry weight) was saccharified in the PEHReactor. The shake flask saccharification was carried out at 5% dry weight of biomass relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture, while the PEHReactor saccharification was carried out at 30% dry weight of biomass relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture. The temperature was maintained at 50 °C.

For the PEHReactor saccharification, about 476 g (~163 g dry weight) pretreated biomass and 22 ceramic attrition cylinders were added to the reactor vessel. The pH was adjusted to 5.0-5.5 with solid citric acid. The reactor vessel was kept inside an incubator chamber controlled to 50 °C and rotated axially at 19 rpm. Unpretreated bagasse was also saccharified at 5% dry weight of biomass relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture in a shake flask. All saccharifications were done with 28.4 mg/g cellulose Spezyme CP[®] cellulase and 28.4 mg/g cellulose Multifect[®] xylanase at 50°C and pH 5.5 for 96 hr. Yields given in Table 11 below are the release as percent of theoretical yield.

Table 11: Yields following pretreatment and saccharification of bagasse.

	No pretreatment 5% saccharification	Pretreated 5% DWB saccharification	Pretreated 30% DWB saccharification
Monomer glucose	0.5%	16.6%	23.3%
Total glucose	ND	ND	36.4%
Monomer xylose	1.3%	15.6%	17.2%
Total xylose	ND	ND	37.4%

ND: not determined

The results demonstrate that pretreatment of bagasse with very low ammonia allows substantial sugar release as compared to the
 5 unpretreated control, and that saccharification at high dry biomass concentration in the PEHReactor is very effective in releasing sugars.

Example 14

Pretreatment of Yellow Poplar Sawdust at High Biomass Concentration, 10 High Temperature, and Very Low Ammonia, and Saccharification at Low and High Concentration

The PEHReactor, without attrition media, was charged with yellow poplar sawdust (596 g, dry weight basis; purchased from Sawmiller Inc., Haydenville, OH). A vacuum was applied to the reactor vessel, and dilute
 15 ammonium hydroxide solution was injected to give an ammonia concentration of 6 g/100 g dry weight of biomass and a dry weight of biomass concentration of 44 g/100 g total biomass-aqueous ammonia mixture. The reactor vessel charged with ammonia and yellow poplar sawdust was brought to 4°C as described in Example 13, and rotated at
 20 4°C for 30 min. At this time the contents were transferred to the steam gun reactor. Once the steam gun reactor was charged with the ammonia-poplar mixture, the temperature was increased to 145°C and the mixture was held at temperature for 20 minutes. At the end of the pretreatment time, the yellow poplar sawdust was discharged from the steam gun
 25 reactor through a 1-in circular die into a flash tank. A sample of pretreated

yellow poplar sawdust was subsequently saccharified as described in Example 13 in a shake flask, and another sample was saccharified in the PEHReactor. The shake flask saccharification was carried out at 5% dry weight of biomass relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture, while the PEHReactor saccharification (using ~279 g dry weight pretreated sawdust) was carried out at 30% dry weight of biomass relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture. Unpretreated yellow poplar sawdust was also saccharified at 5% dry weight of biomass relative to the total weight of the pretreated biomass-saccharification enzyme consortium mixture in a shake flask. All saccharifications were done with 28.4 mg/g cellulose Spezyme CP[®] cellulase and 28.4 mg/g cellulose Multifect[®] xylanase at 50°C and pH 5.5 for 96 hr. Yields given in Table 12 below are the release of each sugar as a percentage of theoretical yield.

Table 12: Yields following pretreatment and saccharification of yellow poplar sawdust.

Component	No pretreatment 5% DWB saccharification	Pretreated 5% DWB saccharification	Pretreated 30% DWB saccharification
Monomer glucose	2.7%	11.1%	20.6%
Total glucose	ND	ND	30.0%
Monomer xylose	0%	17.9%	18.9%
Total xylose	ND	ND	40.2%

ND: not determined

The results demonstrate that pretreatment of yellow poplar sawdust with very low ammonia allows substantial sugar release as compared to the unpretreated control, and that saccharification at high dry weight of

biomass in the PEHReactor is more effective in releasing sugars than the shake flask.

Example 15

5 Ethanol Production by Yeast Fermentation on Hydrolyzate from Very Low Ammonia-Pretreated and Saccharified Cob Biomass

10 The same hydrolyzate used to produce 1,3-propanediol in Example 10 was also used to produce ethanol by yeast fermentation. This hydrolyzate was used as a source of fermentable sugar for conversion to ethanol by wild-type *Saccharomyces cerevisiae* in shake flasks. The hydrolyzate was used at 10% (v/v) strength, with the balance being aqueous medium consisting of 10 g/L yeast extract, and 20 g/L peptone. Yeast were cultured in 50 mL of medium in a 250 mL baffled flask. The cultures were incubated at 30 °C with 250 rpm shaking for 24 hours. The amount of ethanol produced was measured by HPLC as described in Example 9, and results from duplicate flasks are listed in Table 13 below.

Table 13: Substrate utilization and product formation by fermentation with yeast.

	Broth at time zero	Flask 1, 24 hr	Flask 2, 24 hr
Glucose (g/L)	13.9	1.3	0.9
Ethanol (g/L)	0	4.1	4.3
Glucose use	0	91%	94%

20

Example 16

Lactic Acid Production by Lactobacillus Fermentation on Hydrolyzate from Very Low Ammonia-Pretreated and Saccharified Cob Biomass

25 The same hydrolyzate used to produce 1,3-propanediol in Example 10 was also used to produce lactic acid by fermentation with *Lactobacillus brevis* in shake flasks. The hydrolyzate was used at 10% (v/v), with the balance being aqueous medium consisting of 5 g/L yeast extract, 10 g/L peptone, 2 g/L ammonium citrate, 5 g/L sodium acetate, 0.1 g/L MgSO₄,

0.05 g/L MnSO_4 and 2 g/L K_2HPO_4 and 1 g/L Tween. The *Lactobacillus* was cultured in 50 mL broth in 250 mL baffled flasks. Duplicate cultures were incubated at 34 °C with 150 rpm shaking for 24 hours. The amount of lactic acid produced was measured by HPLC as described in Example 10 and is listed in Table 14. The two Flask 2 samples are duplicate assays of the same culture.

Table 14: Substrate utilization and product formation by fermentation with *Lactobacillus brevis*

	Broth at time zero	Flask 1, 24 hr	Flask 2, 24 hr	Flask 2, 24 hr
Glucose (g/L)	25.1	4.6	3.9	3.3
Lactic acid (g/L)	0	8.8	6.2	6.4
Glucose use	0	82%	84%	87%

10

Example 17

Cob Pretreatment at Higher Dry Biomass Concentration with Very Low Ammonia

Whole corn cobs were processed with a jaw crusher (2.2 kW motor) with a jaw spacing of approximately 0.95 cm, followed by a delumper (1.5 kW motor, Franklin Miller Inc., Livingston, NJ), followed by screening with a Sweco screen equipped with a 1.9 cm U.S. Standard screen. Approximately 805 g fractured cobs were loaded into the PEHReactor. Moisture content in the cobs was approximately 7%. The atmosphere in the reactor vessel was flushed 5 times with nitrogen prior to loading. The reactor, with no attrition media, was preheated to 75°C before the start of the experiment, without rotation. When the temperature within the reactor vessel stabilized at 75°C the rolling mechanism in the incubator was turned on and the rotation adjusted to 19 rpm. The appropriate amount of dilute ammonium hydroxide solution to give an ammonia concentration of 6 g ammonia/100 g dry weight of biomass and a solids concentration of 50 g dry weight of biomass/100 g total weight of biomass-ammonia mixture was then pumped into the reactor. Ethanol at 1 g/100 g dry weight of

25

biomass was also added to the solution. The ammonia solution was pumped through a heated loop in a water bath heated to ~75°C, fabricated using a 2-gal Parr reactor. The heated dilute ammonium hydroxide solution was injected via an injection lance into the reactor vessel and
5 sprayed on the fractured cobs rotating and tumbling in the reactor. The reactor was maintained at 75°C for 2 hr while turning at 19 rpm. At the end of that time, a vacuum (approximately 85 kPa) was applied to the reactor vessel for 30 minutes to remove ammonia and drop the temperature of the contents of the reactor to approximately 50°C. Carbon
10 dioxide was then injected into the reactor to relieve the vacuum and the reactor was pressurized to 103 kPa gauge pressure CO₂ and held at pressure for 30 min at 50°C.

Following this, the reactor was depressurized, opened and attrition media were added. The pH of the contents was adjusted to approximately
15 5.5 by injecting 1 M citric acid buffer at pH 4.8 using the injection lance, to increase the citric acid buffer strength to ~75 mM, plus adding citric acid monohydrate. Not all of the ammonia was stripped off in the vacuum step nor neutralized with CO₂. The citric acid buffer was injected into the reactor following heating to 50°C and then the contents was allowed to
20 equilibrate by incubating the reactor at 50°C and 19 rpm for 1 hour. Injection of the citric acid buffer while rotating the reactor using the injection lance allowed for a more even spraying and distribution of the buffer on the pretreated cob particles. The reactor was removed from the incubator, opened, and the pH of a sample determined. If the pH was
25 above 5.5, then additional solid citric acid monohydrate was added and the reactor was incubated with mixing at 50°C for an additional hour. This process was repeated until the pH was approximately 5.5. Once the desired pH was reached, 12.9 mg/g cellulose Spezyme CP (Genencor) and 5 mg active protein /g cellulose enzyme consortium consisting of β-
30 glucosidase, xylanase, β-xylosidase and arabinofuranosidase were loaded into the reactor. The reactor remained in the incubator at 50°C and 19 rpm for 72 hr. Following this pretreatment and saccharification, monomer

5 Example 18
Cob Pretreatment at Higher Solids Concentration with Very Low Ammonia
and Alternate Conditions

46

Following this, the reactor was depressurized, opened and the pH of the contents was adjusted to approximately 5.5 by injecting 1 M citric acid buffer, pH 4.8, into which citric acid monohydrate was added and dissolved. The citric acid buffer was injected into the reactor following
5 heating to 50°C and then the contents was allowed to equilibrate by incubating the reactor at 50°C and 19 rpm for 1 hour. Injection of the citric acid buffer while rotating the reactor using the injection lance allowed for a more even spraying and distribution of the buffer on the pretreated cob particles. The reactor was removed from the incubator, opened, and the
10 pH of a sample determined. If the pH was above 5.5, then additional solid citric acid monohydrate was added and the reactor was incubated with mixing at 50°C for an additional hour. This process was repeated until the pH was approximately 5.5. Once the desired pH was reached, 12.9 mg/g cellulose Spezyme CP (Genencor) and 5 mg active protein/g cellulose
15 enzyme consortium consisting of β -glucosidase, xylanase, β -xylosidase and arabinofuranosidase were loaded into the reactor. The reactor remained in the incubator at 50°C and 19 rpm for 72 hr. Following this pretreatment and saccharification, monomer glucose yield was 50.7% and monomer xylose yield was 35.7%. Total glucose and xylose yields were
20 71.7% and 89.8%, respectively.

Example 19

Pretreatment of Cobs with Very Low Ammonia and Additional Base

Whole corn cobs were processed with a jaw crusher (2.2 kW motor)
25 with a jaw spacing of approximately 0.95 cm, followed by a delumper (1.5 kW motor, Franklin Miller Inc.), followed by screening with a Sweco screen equipped with a 1.9 cm U.S. Standard screen. Approximately 460 g fractured cobs were loaded into the PEHReactor. Moisture content in the cobs was approximately 7%. The reactor was preheated to 95°C before
30 the start of the experiment, without rotation. A vacuum (approximately 85 kPa) was applied to the reactor vessel before the start and the vessel was sealed off. When the temperature within the vessel re-stabilized at 95°C the rolling mechanism in the incubator was turned on and the rotation was

adjusted to 19 rpm. The appropriate amount of ammonium hydroxide solution to give an ammonia concentration of 3.2 g ammonia/100g dry weight of biomass and NaOH to give a concentration of 1.9 g NaOH/100 g dry weight of biomass while maintaining a solids concentration of 30 g dry weight of biomass/100 g total weight of biomass-ammonia mixture was then pumped into the reactor. The ammonia and additional base solution was pumped through a heated loop in a boiling water bath fabricated using a 2-gal Parr reactor. The heated dilute ammonium hydroxide solution was injected via an injection lance into the reactor vessel and sprayed on the fractured cobs rotating and tumbling in the reactor. Following injection, the vacuum on the vessel was relieved to atmospheric pressure. The reactor was maintained at 95°C 30 min, then the temperature was lowered to 85°C where it was maintained for 4 hr. At the end of that time, a vacuum (approximately 85 kPa) was applied to the reactor vessel for 30 minutes to remove ammonia and drop the temperature of the contents of the reactor to approximately 50°C. Carbon dioxide was then injected into the reactor to relieve the vacuum and the reactor was pressurized to 103 kPa gauge pressure and held at pressure for 30 min at 50°C.

Following this, the reactor was depressurized, opened and the pH of the contents was adjusted to approximately 5.5 by injecting approximately 75 ml of 1 M citric acid buffer, pH 4.8, into which citric acid monohydrate was added and dissolved. The citric acid buffer was injected into the reactor following heating to 50°C and the contents was then allowed to equilibrate by incubating the reactor at 50°C and 19 rpm for 1 hour. Injection of the citric acid buffer while rotating the reactor using the injection lance allowed for a more even spraying and distribution of the buffer on the pretreated cob particles. The reactor was removed from the incubator, opened, and the pH of a sample determined. If the pH was above 5.5, then additional solid citric acid monohydrate was added and the reactor was incubated with mixing at 50°C for an additional hour. This process was repeated until the pH was approximately 5.5. Once the desired pH was reached, 28.4 mg/g

cellulose Spezyme CP (Genencor) and 28.4 mg/g cellulose Multifect were loaded into the reactor. The reactor remained in the incubator at 50°C and 19 rpm for 72 hr. Following this pretreatment and saccharification, monomer glucose yield was 56.1% and
5 monomer xylose yield was 39.5%. Total glucose and xylose yields were 82.8% and 84.2%, respectively. These values are the averages of 2 experiments.

Example 20

Room Temperature and Very Low Ammonia Pretreatment

10 Whole corn cobs were processed with a jaw crusher (2.2 kW motor) with a jaw spacing of approximately 0.95 cm, followed by a delumper (1.5 kW motor, Franklin Miller Inc.), followed by screening with a Sweco screen equipped with a 1.9 cm U.S. Standard screen. Approximately 460 g fractured cobs were loaded into the PEHReactor. Moisture content in the
15 cobs was approximately 7%. Twenty-two ceramic attrition cylinders (3.2 cm diameter x 3.2 cm long; E. R. Advanced Ceramics, East Palestine, OH) were also added to the reactor. A vacuum (approximately 85 kPa) was applied to the reactor vessel before the start and the vessel was sealed off. When the temperature within the reactor re-stabilized at room
20 temperature (22-26°C) the rolling mechanism in the incubator was turned on and rotation was adjusted to 19 rpm. The appropriate amount of dilute ammonium hydroxide solution to give an ammonia concentration of 4 g ammonia/100g dry weight of biomass and while maintaining a solids concentration of 30 g dry weight of biomass/total weight of biomass-
25 ammonia mixture was then pumped into the reactor. The dilute ammonium hydroxide solution was injected via an injection lance into the reactor vessel and sprayed on the fractured cobs rotating and tumbling in the reactor. Following injection, the vacuum on each vessel was relieved to atmospheric pressure. The reactor was maintained at room temperature
30 (22-26°C) for 24 hr. At the end of that time, a vacuum (approximately 81 kPa) was applied to the reaction vessel for 30 minutes to remove ammonia. Carbon dioxide was then injected into the reactor to relieve the

vacuum and the reactor was pressurized to 103 kPa gauge pressure with CO₂ and held at pressure for 30 min at room temperature.

Following this, the reactor was depressurized, opened and the pH of the contents was adjusted to approximately 5.5 by adding citric acid monohydrate following heating to 50°C, and then allowed to equilibrate by incubating the reactor at 50°C and 19 rpm. The reactor was removed from the incubator, opened, and the pH of a sample determined. If the pH was above 5.5, then additional solid citric acid monohydrate was added and the reactor was incubated with mixing at 50°C. This process was repeated until the pH was approximately 5.5. Once the desired pH was reached, 12.9 mg/g cellulose Spezyme CP (Genencor) and 5 mg active protein /g cellulose enzyme consortium consisting of β -glucosidase, xylanase, β -xylosidase and arabinofuranosidase were loaded into the reactor. The reactor remained in the incubator at 50°C and 19 rpm for 72 hr. Following this pretreatment and saccharification, monomer glucose yield was 41.7% and the monomer xylose yield was 25.4%. Total glucose and xylose yields were 50.1% and 53.2%, respectively. These values were the averages of 2 experiments.

CLAIMS

1. A method for treating biomass to produce fermentable sugars comprising:
 - a) contacting biomass with an aqueous solution comprising ammonia to form a biomass-aqueous ammonia mixture, wherein the ammonia is present at a concentration at least sufficient to maintain alkaline pH of the biomass-aqueous ammonia mixture but wherein said ammonia is present at less than 12 weight percent relative to dry weight of biomass, and further wherein the dry weight of biomass is at a solids concentration of at least 15 weight percent relative to the weight of the biomass-aqueous ammonia mixture, to produce a pretreated biomass product; and
 - b) contacting the product of step a) with a saccharification enzyme consortium under suitable conditions,to produce fermentable sugars.
2. The method of Claim 1 wherein the pH of the biomass-aqueous ammonia mixture is greater than 8.
3. The method of Claim 1 wherein vacuum is applied to the biomass prior to contacting the biomass with an aqueous solution comprising ammonia.
4. The method of Claim 1 wherein said dry weight of biomass is at a solids concentration of from at least 15% to 80%.
5. The method of Claim 4 wherein said dry weight of biomass is at a solids concentration of from at least 15% to 60%.
6. The method of Claim 1 wherein said ammonia is present at less than 10 weight percent relative to dry weight of biomass.
7. The method of Claim 6 wherein said ammonia is present at 6% or less weight percent relative to dry weight of biomass.

8. The method of Claim 1 wherein biomass is bioenergy crops, agricultural residues, municipal solid waste, industrial solid waste, yard waste, wood or forestry waste.
9. The method of Claim 1 wherein biomass is switchgrass, waste paper, sludge from paper manufacture, corn grain, corn cobs, corn husks, corn stover, grasses, wheat, wheat straw, hay, barley, barley straw, rice straw, sugar cane bagasse, sorghum, soy, components obtained from processing of grains, trees, branches, roots, leaves, wood chips, sawdust, shrubs and bushes, vegetables, fruits, flowers or animal manure.
10. The method of Claim 9 wherein biomass is corn cobs, corn stover, corn husks, sugar cane bagasse, sawdust, switchgrass, wheat straw, hay, barely straw, rice straw, or grasses.
11. The method of Claim 10 wherein biomass is corn cobs, corn stover, sawdust, or sugar cane bagasse.
12. The method of Claim 1 wherein ammonia is ammonia gas, ammonium hydroxide, urea, or combinations thereof.
13. The method of Claim 1 wherein said aqueous solution comprising ammonia further comprises at least one additional base.
14. The method of Claim 13 wherein said at least one base is sodium hydroxide, sodium carbonate, potassium hydroxide, potassium carbonate, calcium hydroxide or calcium carbonate.
15. The method of Claim 1 wherein step a) is carried out at a temperature of from 4 °C to 200 °C.
16. The method of Claim 15 wherein step a) is carried out at a temperature of from 75 °C to 150 °C.
17. The method of Claim 16 wherein step a) is carried out at a temperature of from greater than 90 °C to 150 °C.

18. The method of Claim 1 wherein step a) is carried out for a period of time of up to 25 hours.
19. The method of Claim 18 wherein step a) is carried out for a period of time of up to 8 hours.
20. The method of Claim 1 or Claim 2 wherein at least a portion of the ammonia of step a) is removed prior to step b).
21. The method of Claim 1 wherein ammonia from step a) is recycled.
22. The method of Claim 1 wherein the contacting of step b) is at a dry weight of biomass concentration of at least 15%.
23. The method of Claim 1 wherein step a), step b) or step a) and step b) are repeated at least one time.
24. The method of Claim 1 further comprising adding at least one plasticizer, softening agent or combination thereof in step a).
25. The method of Claim 24 wherein said at least one plasticizer, softening agent or combination thereof is polyols, esters of polyols, glycol ethers, acetamide, ethanol, or ethanolamines.
26. The method of Claim 1, further comprising applying energy before or during step a), before or during step b), or a combination thereof.
27. The method of Claim 26 wherein said energy is milling, crushing, grinding, shredding, chopping, disk refining, ultrasound or microwave.
28. The method of Claim 1, wherein carbon dioxide from fermentation is used to adjust the pH of the pretreatment mixture prior to saccharification.
29. The method of Claim 1 wherein said saccharification enzyme consortium comprises at least one glycosidase.
30. The method of Claim 1 wherein said saccharification enzyme consortium comprises at least one enzyme, wherein the enzyme is cellulose-hydrolyzing

glycosidases, hemicellulose-hydrolyzing glycosidases, starch-hydrolyzing glycosidases, peptidases, lipases, ligninases or feruloyl esterases.

31. The method of Claim 1 wherein said saccharification enzyme consortium comprises at least one enzyme wherein the enzyme is cellulases, endoglucanases, exoglucanases, cellobiohydrolases, β -glucosidases, xylanases, endoxylanases, exoxylanases, β -xylosidases, arabinoxylanases, mannases, galactases, pectinases, glucuronidases, amylases, α -amylases, β -amylases, glucoamylases, α -glucosidases, or isoamylases.

32. The method of Claim 1 wherein step b) is performed at a temperature of from 15 °C to 100 °C and at a pH of from 2 to 11.

Figure 1

