




(86) Date de dépôt PCT/PCT Filing Date: 2016/02/03  
(87) Date publication PCT/PCT Publication Date: 2016/08/11  
(45) Date de délivrance/Issue Date: 2022/08/23  
(85) Entrée phase nationale/National Entry: 2017/07/14  
(86) N° demande PCT/PCT Application No.: IL 2016/050125  
(87) N° publication PCT/PCT Publication No.: 2016/125160  
(30) Priorité/Priority: 2015/02/05 (US62/112,343)

(51) Cl.Int./Int.Cl. A61F 2/24 (2006.01)  
(72) Inventeurs/Inventors:  
HARITON, ILIA, IL;  
HARARI, BOAZ, IL  
(73) Propriétaire/Owner:  
CARDIOVALVE LTD., IL  
(74) Agent: CHATTERJEE, ALAKANANDA

(54) Titre : VALVE PROTHETIQUE AVEC CADRES COUSSIANT AXIALEMENT  
(54) Title: PROSTHETIC VALVE WITH AXIALLY-SLIDING FRAMES



(57) Abrégé/Abstract:

A tubular portion (32) of a valve frame (30) circumscribes a longitudinal axis, and defines a lumen along the axis and a plurality of valve-frame coupling elements (31) disposed circumferentially around the axis. An outer frame (60): (a) comprises a ring (66) defined by a pattern of alternating peaks and troughs, the pattern having an amplitude, (b) comprises a plurality of legs (50), coupled to the ring at respective troughs, and (c) is shaped to define a plurality of outer-frame coupling elements (61), each coupled to the ring at a respective peak, and fixed with respect to a respective valve-frame coupling element. Compression of the tubular portion from an expanded state toward a compressed state reduces a circumferential distance between each of the outer-frame coupling elements and its adjacent outer-frame coupling elements, and increases the amplitude of the pattern of the ring.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2016/125160 A1

(43) International Publication Date  
11 August 2016 (11.08.2016)(51) International Patent Classification:  
*A61F 2/24 (2006.01)*(21) International Application Number:  
PCT/IL2016/050125(22) International Filing Date:  
3 February 2016 (03.02.2016)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
62/112,343 5 February 2015 (05.02.2015) US

(71) Applicant: MITRALTECH LTD. [IL/IL]; 3 Ariel Sharon Avenue, 60376 Or Yehuda (IL).

(72) Inventors: HARITON, Ilia; 14B Orvani Street, 30900 Zichron Yaakov (IL). HARARI, Boaz; 7/50 Derech Hamelech Street, 55900 Ganey Tikva (IL).

(74) Agents: COLB, Sanford T. et al.; SANFORD T. COLB &amp; CO., P.O. Box 2273, 76122 Rehovot (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,


BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: PROSTHETIC VALVE WITH AXIALLY-SLIDING FRAMES

**FIG. 4E**

**(57) Abstract:** A tubular portion (32) of a valve frame (30) circumscribes a longitudinal axis, and defines a lumen along the axis and a plurality of valve-frame coupling elements (31) disposed circumferentially around the axis. An outer frame (60): (a) comprises a ring (66) defined by a pattern of alternating peaks and troughs, the pattern having an amplitude, (b) comprises a plurality of legs (50), coupled to the ring at respective troughs, and (c) is shaped to define a plurality of outer-frame coupling elements (61), each coupled to the ring at a respective peak, and fixed with respect to a respective valve-frame coupling element. Compression of the tubular portion from an expanded state toward a compressed state reduces a circumferential distance between each of the outer-frame coupling elements and its adjacent outer-frame coupling elements, and increases the amplitude of the pattern of the ring.

## PROSTHETIC VALVE WITH AXIALLY-SLIDING FRAMES

### **FIELD OF THE INVENTION**

5 Some applications of the present invention relate in general to valve replacement. More specifically, some applications of the present invention relate to prosthetic valves for replacement of a cardiac valve.

### **BACKGROUND**

10 Ischemic heart disease causes regurgitation of a heart valve by the combination of ischemic dysfunction of the papillary muscles, and the dilatation of the ventricle that is present in ischemic heart disease, with the subsequent displacement of the papillary muscles and the dilatation of the valve annulus.

15 Dilation of the annulus of the valve prevents the valve leaflets from fully coaptting when the valve is closed. Regurgitation of blood from the ventricle into the atrium results in increased total stroke volume and decreased cardiac output, and ultimate weakening of the ventricle secondary to a volume overload and a pressure overload of the atrium.

### **SUMMARY OF THE INVENTION**

20 For some applications, an implant is provided having a tubular portion, an upstream support portion and one or more flanges. The implant is percutaneously deliverable to a native heart valve in a compressed state, and is expandable at the native valve. The implant and its delivery system facilitate causing the upstream support portion and the flanges to protrude radially outward from the tubular portion without expanding the tubular portion. Expansion of the tubular portion brings the upstream support portion and the flanges closer together, for securing the implant at the native valve by sandwiching tissue of the native 25 valve between the upstream support portion and the flanges.

There is therefore provided, in accordance with an application of the present invention, apparatus for use with a native valve that is disposed between an atrium and a ventricle of a heart of a subject, the apparatus including:

a valve frame, including a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the tubular portion defining a plurality of valve-frame coupling elements disposed circumferentially around the longitudinal axis;

5 a plurality of prosthetic leaflets, coupled to the frame, disposed within the lumen, and arranged to provide unidirectional flow of blood from an upstream end of the lumen to a downstream end of the lumen;

an outer frame:

10 including a ring defined by a pattern of alternating peaks and troughs, the peaks being longitudinally closer to the upstream end than to the downstream end, and the troughs being longitudinally closer to the downstream end than to the upstream end, and the pattern of the ring having an amplitude longitudinally between the peaks and the troughs,

15 including a plurality of legs, each of the legs coupled to the ring at a respective trough, and

shaped to define a plurality of outer-frame coupling elements, each of the outer-frame coupling elements (i) coupled to the ring at a respective peak, and (ii) fixed with respect to a respective valve-frame coupling element,

and:

20 the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

25 the fixation of the outer-frame coupling elements to the valve-frame coupling elements is such that compression of the tubular portion from the expanded state toward the compressed state such that the valve-frame coupling elements pull the outer-frame coupling elements radially inward: (i) reduces a circumferential distance between each of the outer-frame coupling elements and its adjacent outer-frame coupling elements, and (ii) increases the amplitude of the pattern of the ring.

In an application, the ring circumscribes the tubular portion.

30 In an application, the valve-frame coupling elements are disposed circumferentially around the longitudinal axis between the upstream end and the downstream end but not at the upstream end nor at the downstream end.

In an application, the upstream support portion includes one or more fabric pockets disposed circumferentially, each pocket of the one or more pockets having an opening that faces a downstream direction.

5 In an application, the outer frame is coupled to the valve frame only via the fixation of the outer-frame coupling elements to the respective valve-frame coupling elements.

In an application, the apparatus further includes an upstream support portion that includes a plurality of arms that extend radially from the tubular portion, and:

10 the upstream support portion has (i) a constrained-arm state, and (ii) a released-arm state in which the arms extend radially outward from the tubular portion,

each leg has a tissue-engaging flange that has (i) a constrained-flange state, and (ii) a released-flange state in which the flange extends radially outward from the tubular portion, and

15 the apparatus has an intermediate state in which (i) the tubular portion is in its compressed state, (ii) the upstream support portion is in its released-arm state, and (iii) the legs are in their released-flange state.

In an application:

the apparatus includes an implant that includes the valve frame, the leaflets, and the outer frame, and

20 the apparatus further includes a tool:

including a delivery capsule dimensioned (i) to house and retain the implant in a compressed state of the implant in which (a) the tubular portion is in its compressed state, (b) the upstream support portion is in its constrained-arm state, and (c) the legs are in their constrained-flange state, and (ii) to be advanced 25 percutaneously to the heart of the subject while the implant is housed and in its compressed state, and

operable from outside the subject to:

30 transition the implant from its compressed state into the intermediate state while retaining the tubular portion in its compressed state, and

subsequently, expand the tubular portion toward its expanded state.

In an application, the tool is operable from outside the subject to transition the implant from its compressed state into the intermediate state by (i) releasing the legs into

their released-flange state, while retaining the tubular portion in its compressed state, and (ii) subsequently, releasing the upstream support portion into its released-arm state, while retaining the tubular portion in its compressed state.

In an application, the tool is operable from outside the subject to transition the 5 implant from its compressed state into the intermediate state by (i) releasing the upstream support portion into its released-arm state, while retaining the tubular portion in its compressed state, and (ii) subsequently, releasing the legs into their released-flange state, while retaining the tubular portion in its compressed state.

In an application, the fixation of the outer-frame coupling elements to the valve- 10 frame coupling elements is such that, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state moves the flanges longitudinally away from the valve-frame coupling elements.

In an application, the fixation of the outer-frame coupling elements to the valve- 15 frame coupling elements is such that, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state reduces the amplitude of the pattern of the ring and passes the flanges between the arms.

In an application, the upstream support portion further includes a covering that 20 covers the arms to form an annular shape in the released-arm state, and, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state presses the flanges onto the covering.

In an application, in the compressed state of the tubular portion, a downstream end of each leg is longitudinally closer than the valve-frame coupling elements to the downstream end, and the flange of each leg is disposed longitudinally closer than the valve-frame coupling elements to the upstream end.

25 In an application, in the expanded state of the tubular portion, the downstream end of each leg is longitudinally closer than the valve-frame coupling elements to the downstream end, and the flange of each leg is disposed longitudinally closer than the valve-frame coupling elements to the upstream end.

30 There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve of a heart of a subject, the apparatus including an implant that includes:

a valve frame that includes a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the tubular portion having an upstream end, a downstream end, a longitudinal length therebetween, and a diameter transverse to the longitudinal axis;

5 a valve member, coupled to the tubular portion, disposed within the lumen, and arranged to provide unidirectional upstream-to-downstream flow of blood through the lumen;

an upstream support portion, coupled to the tubular portion; and

10 flange, and:

the implant has a first state and a second state,

in both the first state and the second state, (i) the upstream support portion extends radially outward from the tubular portion, and (ii) the tissue-engaging flange extends

15 radially outward from the tubular portion, and

the tubular portion, the upstream support portion, and the outer frame are arranged such that transitioning of the implant from the first state toward the second state:

increases the diameter of the tubular portion by a diameter-increase amount,

20 decreases the length of the tubular portion by a length-decrease amount, and

moves the flange a longitudinal distance toward or toward-and-beyond the upstream support portion, the distance being greater than the length-decrease amount.

25 In an application, the tubular portion, the upstream support portion, and the outer frame are arranged such that the longitudinal distance is more than 20 percent greater than the length-decrease amount.

30 In an application, the tubular portion, the upstream support portion, and the outer frame are arranged such that the longitudinal distance is more than 30 percent greater than the length-decrease amount.

In an application, the tubular portion, the upstream support portion, and the outer frame are arranged such that the longitudinal distance is more than 40 percent greater than the length-decrease amount.

There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve that is disposed between an atrium and a ventricle of a heart of a subject, the apparatus including:

5 a valve frame, including a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis;

a plurality of prosthetic leaflets, coupled to the frame, disposed within the lumen, and arranged to provide unidirectional flow of blood from an upstream end of the lumen to a downstream end of the lumen;

an outer frame, including:

10 a ring defined by a pattern of alternating peaks and troughs:

the peaks being longitudinally closer than the troughs to the upstream end,

15 the peaks being fixed to respective sites of the tubular portion at respective coupling points disposed circumferentially around the longitudinal axis, and

the pattern of the ring having an amplitude longitudinally between the peaks and the troughs; and

15 a plurality of legs, each of the legs coupled to the ring at a respective trough,

20 and:

the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

25 the fixation of the peaks to the respective sites of the tubular portion is such that compression of the tubular portion from the expanded state toward the compressed state such that the respective sites of the tubular portion pull the peaks radially inward via radially-inward tension on the coupling points: (i) reduces a circumferential distance between each of the coupling points and its adjacent coupling points, and (ii) increases the amplitude of the pattern of the ring.

30 In an application, the outer frame is coupled to the valve frame only via the fixation of the peaks to the respective sites of the tubular portion at the respective coupling points.

There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve that is disposed between an atrium and a ventricle of a heart of a subject, the apparatus including:

5 a valve frame, including a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the valve frame defining a plurality of valve-frame coupling elements disposed circumferentially around the longitudinal axis;

a plurality of prosthetic leaflets, coupled to the frame, disposed within the lumen, and arranged to provide unidirectional flow of blood from an upstream end of the lumen to a downstream end of the lumen;

10 an outer frame:

including a ring defined by a pattern of alternating peaks and troughs, the peaks being longitudinally closer to the upstream end than to the downstream end, and the troughs being longitudinally closer to the downstream end than to the upstream end, and the pattern of the ring having an amplitude longitudinally 15 between the peaks and the troughs,

including a plurality of legs, each of the legs coupled to the ring at a respective trough, and

shaped to define a plurality of outer-frame coupling elements, each of the outer-frame coupling elements (i) coupled to the ring at a respective peak, and (ii) 20 fixed with respect to a respective valve-frame coupling element,

and:

the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

25 the fixation of the outer-frame coupling elements with respect to the valve-frame coupling elements is such that compression of the tubular portion from the expanded state toward the compressed state (i) pulls the outer-frame coupling elements radially inward via radially-inward pulling of the valve-frame coupling elements on the outer-frame coupling elements, (ii) reduces a circumferential distance between each of the outer-frame 30 coupling elements and its adjacent outer-frame coupling elements, and (iii) increases the amplitude of the pattern of the ring, without increasing a radial gap between the valve frame and the ring by more than 1.5 mm.

In an application, the outer frame is coupled to the valve frame only via the fixation of the outer-frame coupling elements to the respective valve-frame coupling elements.

There is further provided, in accordance with an application of the present  
5 invention, apparatus for use with a native valve that is disposed between an atrium and a ventricle of a heart of a subject, the apparatus including:

a valve frame, including a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis;

10 a plurality of prosthetic leaflets, coupled to the frame, disposed within the lumen, and arranged to provide unidirectional flow of blood from an upstream end of the lumen to a downstream end of the lumen;

an outer frame, including:

a ring defined by a pattern of alternating peaks and troughs:

15 the peaks being longitudinally closer than the troughs to the upstream end,

the peaks being fixed to respective sites of the tubular portion at respective coupling points disposed circumferentially around the longitudinal axis, and

20 the pattern of the ring having an amplitude longitudinally between the peaks and the troughs; and

a plurality of legs, each of the legs coupled to the ring at a respective trough,

and:

25 the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

30 the fixation of the peaks to the respective sites of the tubular portion is such that compression of the tubular portion from the expanded state toward the compressed state (i) pulls the peaks radially inward via radially-inward pulling of the respective sites of the tubular portion on the peaks, (ii) reduces a circumferential distance between each of the coupling points and its adjacent coupling points, and (iii) increases the amplitude of the pattern of the ring, without increasing a radial gap between the valve frame and the ring by more than 1.5 mm.

In an application, the outer frame is coupled to the valve frame only via the fixation of the peaks to the respective sites of the tubular portion at the respective coupling points.

There is further provided, in accordance with an application of the present 5 invention, apparatus for use with a native valve disposed between an atrium and a ventricle of a heart of a subject, the apparatus including:

a valve frame, including a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the tubular portion having an upstream end, a downstream end, and defining a plurality of valve-frame coupling 10 elements disposed circumferentially around the longitudinal axis between the upstream end and the downstream end but not at the upstream end nor at the downstream end;

a plurality of prosthetic leaflets, disposed within the lumen, and arranged to provide unidirectional flow of blood through the lumen;

an outer frame:

15 including a ring defined by a pattern of alternating peaks and troughs, the peaks being longitudinally closer to the upstream end than to the downstream end, and the troughs being longitudinally closer to the downstream end than to the upstream end,

20 including a plurality of legs, each of the legs coupled to the ring at a respective trough, and

shaped to define a plurality of outer-frame coupling elements, each of the outer-frame coupling elements (i) coupled to the ring at a respective peak, and (ii) fixed with respect to a respective valve-frame coupling element at a respective coupling point,

25 and:

the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

30 expansion of the tubular portion from the compressed state toward the expanded state (i) increases a circumferential distance between each of the outer-frame coupling elements and its adjacent outer-frame coupling elements, and (ii) moves the plurality of legs in a longitudinally upstream direction with respect to the tubular portion.

In an application, the outer frame is coupled to the valve frame only via the fixation of the outer-frame coupling elements to the respective valve-frame coupling elements.

There is further provided, in accordance with an application of the present  
5 invention, apparatus for use with a native valve disposed between an atrium and a ventricle of a heart of a subject, the apparatus including:

a valve frame, including a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the tubular portion having an upstream end and a downstream end;

10 a plurality of prosthetic leaflets, disposed within the lumen, and arranged to provide unidirectional flow of blood through the lumen;

an outer frame, including:

a ring defined by a pattern of alternating peaks and troughs:

15 the peaks being longitudinally closer than the troughs to the upstream end,

the peaks being fixed to respective sites of the tubular portion at respective coupling points disposed circumferentially around the longitudinal axis between the upstream end and the downstream end but not at the upstream end nor the downstream end; and

20 a plurality of legs, each of the legs coupled to the ring at a respective trough,

and:

the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an  
25 expanded diameter that is greater than the compressed diameter, and

expansion of the tubular portion from the compressed state toward the expanded state (i) increases a circumferential distance between each of the coupling points and its adjacent coupling points, and (ii) moves the plurality of legs in a longitudinally upstream direction with respect to the tubular portion.

30 In an application, the outer frame is coupled to the valve frame only via the fixation of the peaks to the respective sites of the tubular portion at the respective coupling points.

There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve of a heart of a subject, the apparatus including:

5 a frame assembly, having an upstream end and a downstream end, and a central longitudinal axis therebetween, and including:

a valve frame, including:

a tubular portion having an upstream end and a downstream end, and shaped to define a lumen therebetween, and

10 an upstream support portion, extending from the upstream end of the tubular portion; and

at least one leg, coupled to the valve frame at a coupling point, and having a tissue-engaging flange; and

15 a valve member disposed within the lumen, and configured to facilitate one-way liquid flow through the lumen from the upstream end of the tubular portion to the downstream end of the tubular portion,

and the frame assembly:

has a compressed state, for percutaneous delivery to the heart, in which the tubular portion has a compressed diameter,

20 is biased to assume an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

is configured such that increasing the diameter of the tubular portion toward the expanded diameter causes longitudinal movement:

of the upstream support portion toward the coupling point, and

of the tissue-engaging flange away from the coupling point.

25 In an application:

the apparatus includes an implant that includes the frame assembly and the valve member, and

the apparatus further includes a tool:

30 including a delivery capsule dimensioned (i) to house and retain the implant in the compressed state, and (ii) to be advanced percutaneously to the heart of the subject while the implant is housed and in the compressed state, and

operable from outside the subject to facilitate an increase of the diameter of the tubular portion from the compressed diameter toward the expanded diameter such that the increase of the diameter actuates longitudinal movement:

of the upstream support portion toward the coupling point, and of the tissue-engaging flange away from the coupling point.

In an application, the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes longitudinal movement of the upstream end of the tubular portion toward the coupling point.

In an application, the coupling point is disposed closer to the downstream end of the frame assembly than are either the tissue-engaging flange or the upstream support portion.

10 In an application, in the expanded state of the frame assembly, the leg extends away from the central longitudinal axis.

In an application:

the expanded state of the frame assembly is a fully-expanded state of the frame assembly,

15 the leg is expandable into an expanded state of the leg, independently of increasing the diameter of the tubular portion, and

in the expanded state of the leg, the leg extends away from the central longitudinal axis.

In an application:

20 in the expanded state of the frame assembly, the leg extends away from the central longitudinal axis, and

in the compressed state of the frame assembly, the leg is generally parallel with the central longitudinal axis.

In an application, the frame assembly is configured such that the longitudinal movement of the tissue-engaging flange away from the coupling point is a translational movement of the tissue-engaging flange that does not include rotation of the tissue-engaging flange.

30 In an application, the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes 1-20 mm of longitudinal movement of the tissue-engaging flange away from the coupling point.

In an application, the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes 1-20 mm of longitudinal movement of the upstream support portion toward the coupling point.

5 In an application, the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state reduces a distance between the upstream support portion and the tissue-engaging flange by 5-30 mm.

In an application, the frame assembly is configured such that increasing the  
10 diameter of the tubular portion by expanding the frame assembly toward the expanded state moves the tissue-engaging flange longitudinally past the upstream support portion.

In an application:  
the tubular portion is defined by a plurality of cells of the valve frame, and  
increasing the diameter of the tubular portion by expanding the frame assembly  
15 toward the expanded state:

includes (i) increasing a width, orthogonal to the longitudinal axis of the frame assembly, of each cell, and (ii) reducing a height, parallel with the longitudinal axis of the frame assembly, of each cell, and  
causes longitudinal movement of the upstream support portion toward the  
20 coupling point by reducing a height, parallel with the longitudinal axis of the frame assembly, of the tubular portion, by reducing the height of each cell.

In an application, the leg is disposed on an outside of the tubular portion.  
In an application:  
the at least one leg includes a plurality of legs,  
25 the coupling point includes a plurality of coupling points, and  
the frame assembly includes a leg frame that circumscribes the tubular portion, includes the plurality of legs, and is coupled to the valve frame at the plurality of coupling points, such that the plurality of legs is distributed circumferentially around the tubular portion.

30 In an application, the plurality of coupling points is disposed circumferentially around the frame assembly on a transverse plane that is orthogonal to the longitudinal axis of the frame assembly.

In an application, the plurality of legs is coupled to the valve frame via a plurality of struts, each strut:

having a first end that is coupled to a leg of the plurality of legs, and a second end that is coupled to a coupling point of the plurality of coupling points,

5 in the compressed state of the frame assembly, being disposed at a first angle in which the first end is disposed closer to the downstream end of the frame assembly than is the second end, and

10 being deflectable with respect to the coupling point of the plurality of coupling points, such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes the strut to deflect to a second angle in which the first end is disposed further from the downstream end of the frame assembly than is the first end in the compressed state of the frame assembly.

15 In an application, the leg frame is structured such that each leg of the plurality of legs is coupled to two struts of the plurality of struts, and two struts of the plurality of struts are coupled to each coupling point of the plurality of coupling points.

In an application, the leg is coupled to the valve frame via a strut, the strut:

having a first end that is coupled to the leg, and a second end that is coupled to the coupling point,

20 in the compressed state of the frame assembly, being disposed at a first angle in which the first end is disposed closer to the downstream end of the frame assembly than is the second end, and

25 being deflectable with respect to the coupling point, such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes the strut to deflect to a second angle in which the first end is disposed further from the downstream end of the frame assembly than is the first end in the compressed state of the frame assembly.

In an application, the at least one leg includes at least a first leg and a second leg.

In an application, the first leg and the second leg are both coupled to the valve frame at the coupling point.

30 In an application, the first leg is coupled to the coupling point via a respective first strut, and the second leg is coupled to the coupling point via a respective second strut.

In an application, the first and second legs, the first and second struts, and the coupling point are arranged such that, in the expanded state of the frame assembly:

the coupling point is disposed, circumferentially with respect to the tubular portion, between the first strut and the second strut,

5 the first strut is disposed, circumferentially with respect to the tubular portion, between the coupling point and the first leg, and

the second strut is disposed, circumferentially with respect to the tubular portion, between the coupling point and the second leg.

In an application, the coupling point includes at least a first coupling point and a  
10 second coupling point.

In an application, the leg is coupled to the valve frame at the first coupling point and at the second coupling point.

In an application, the leg is coupled to the first coupling point via a respective first strut, and to the second coupling point via a respective second strut.

15 In an application, the first and second legs, the first and second struts, and the coupling point are arranged such that, in the expanded state of the frame assembly:

the leg is disposed, circumferentially with respect to the tubular portion, between the first strut and the second strut,

20 the first strut is disposed, circumferentially with respect to the tubular portion, between the leg and the first coupling point, and

the second strut is disposed, circumferentially with respect to the tubular portion, between the leg and the second coupling point.

In an application, in the expanded state of the frame assembly, the upstream support portion extends radially outward from the tubular portion.

25 In an application:

the expanded state of the frame assembly is a fully-expanded state of the frame assembly,

the upstream support portion is expandable into an expanded state of the upstream support portion, independently of increasing the diameter of the tubular portion, and

30 in the expanded state of the upstream support portion, the upstream support portion extends radially outward from the tubular portion.

In an application, in the compressed state of the frame assembly, the upstream support portion is generally tubular, collinear with the tubular portion, and disposed around the central longitudinal axis.

In an application, in the expanded state of the frame assembly, an inner region of 5 the upstream support portion extends radially outward from the tubular portion at a first angle with respect to the tubular portion, and an outer region of the upstream support portion extends, from the inner region of the upstream support portion, further radially outward from the tubular portion at a second angle with respect to the tubular portion, the second angle being smaller than the first angle.

10 There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve of a heart of a subject, the apparatus including:

a frame assembly, having an upstream end and a downstream end, and a central longitudinal axis therebetween, and including:

15 a valve frame, including:

a tubular portion having an upstream end and a downstream end, and shaped to define a lumen therebetween, and

an upstream support portion, extending from the upstream end of the tubular portion; and

20 at least one leg, coupled to the valve frame at a coupling point, and having a tissue-engaging flange; and

a valve member disposed within the lumen, and configured to facilitate one-way liquid flow through the lumen from the upstream end of the tubular portion to the downstream end of the tubular portion,

25 and the frame assembly:

has a compressed state, for percutaneous delivery to the heart, in which the tubular portion has a compressed diameter,

is biased to assume an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

30 is configured such that reducing the diameter of the tubular portion toward the compressed diameter causes longitudinal movement:

of the upstream support portion away from the coupling point, and

of the tissue-engaging flange toward the coupling point.

There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve of a heart of a subject, the apparatus including:

5 a frame assembly, having an upstream end and a downstream end, and a central longitudinal axis therebetween, including:

10 a valve frame, including:  
 a tubular portion having an upstream end and a downstream end, and shaped to define a lumen therebetween, and  
 an upstream support portion, extending from the upstream end of the tubular portion; and  
 15 at least one leg, coupled to the valve frame at a coupling point, and having a tissue-engaging flange; and  
 a valve member disposed within the lumen, and configured to facilitate one-way liquid flow through the lumen from the upstream end of the tubular portion to the downstream end of the tubular portion,  
 20 and the frame assembly:  
 has a compressed state, for percutaneous delivery to the heart,  
 is intracorporeally expandable into an expanded state in which a diameter of the tubular portion is greater than in the compressed state, and  
 is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes longitudinal movement of the tissue-engaging flange away from the coupling point.

25 There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve of a heart of a subject, the apparatus including:

30 a frame assembly, having an upstream end and a downstream end, and a central longitudinal axis therebetween, and including:  
 an inner frame including an inner-frame tubular portion that circumscribes the central longitudinal axis, has an upstream end and a downstream end, and defines a channel therebetween, the inner frame defining a plurality of inner-frame couplings disposed circumferentially at a longitudinal location of the inner frame,  
 an outer frame including an outer-frame tubular portion that coaxially circumscribes at least a portion of the inner-frame tubular portion, the outer frame

defining a plurality of outer-frame couplings disposed circumferentially at a longitudinal location of the outer frame, and

a plurality of connectors, each connector connecting a respective inner-frame coupling to a respective outer-frame coupling;

5 a liner, disposed over at least part of the inner-frame tubular portion; and

a plurality of prosthetic leaflets, coupled to the inner-frame tubular portion and disposed within the channel,

and:

the frame assembly: (i) is compressible by a radially-compressive force into a 10 compressed state in which the inner frame is in a compressed state thereof and the outer frame is in a compressed state thereof, (ii) is configured, upon removal of the radially-compressive force, to automatically expand into an expanded state thereof in which the inner frame is in an expanded state thereof and the outer frame is in an expanded state thereof,

15 in the expanded state of the frame assembly, the prosthetic leaflets are configured to facilitate one-way fluid flow, in a downstream direction, through the channel, and

the connection of the inner-frame couplings to the respective outer-frame couplings is such that expansion of the frame assembly from the compressed state to the expanded state causes the inner-frame tubular portion to slide longitudinally in a 20 downstream direction with respect to the outer-frame tubular portion.

There is further provided, in accordance with an application of the present invention, apparatus for use with a native valve disposed between an atrium and a ventricle of a heart of a subject, the apparatus including:

a tubular portion, having an upstream portion that includes an upstream end, and a 25 downstream portion that includes a downstream end, and shaped to define a lumen between the upstream portion and the downstream portion;

a plurality of prosthetic leaflets, disposed within the lumen, and arranged to provide unidirectional flow of blood from the upstream portion to the downstream portion;

an annular upstream support portion:

30 having an inner portion that extends radially outward from the upstream portion, and

including one or more fabric pockets disposed circumferentially around the inner portion, each pocket of the one or more pockets having an opening that faces a downstream direction.

In an application:

- 5 the upstream support portion includes (i) a plurality of arms that extend radially outward from the tubular portion, and (ii) a covering, disposed over the plurality of arms, each arm has (i) a radially-inner part at the inner portion of the upstream support portion, and (ii) a radially-outer part at the outer portion of the upstream support portion, at the inner portion of the upstream support portion, the covering is closely-fitted
- 10 between the radially-inner parts of the arms, and at the outer portion of the upstream support portion, the pockets are formed by the covering being loosely-fitted between the radially-outer parts of the arms.

In an application:

- 15 the upstream support portion includes (i) a plurality of arms that extend radially outward from the tubular portion, and (ii) a covering, disposed over the plurality of arms, each arm has (i) a radially-inner part at the inner portion of the upstream support portion, and (ii) a radially-outer part at the outer portion of the upstream support portion, the radially-outer part being more flexible than the radially-inner part.

In an application:

- 20 the upstream support portion includes (i) a plurality of arms that extend radially outward from the tubular portion, and (ii) a covering, disposed over the plurality of arms, each arm has (i) a radially-inner part at the inner portion of the upstream support portion, and (ii) a radially-outer part at the outer portion of the upstream support portion, at the outer portion of the upstream support portion, the pockets are formed by
- 25 each arm curving to form a hook shape.

In an application, each pocket is shaped and arranged to billow in response to perivalvular flow of blood in an upstream direction.

- 30 In an application, the apparatus is configured to be transluminally delivered to the heart, and implanted at the native valve by expansion of the apparatus, such that the upstream support portion is disposed in the atrium and the tubular portion extends from the upstream support portion into the ventricle, and each pocket is shaped and arranged such that perivalvular flow of blood in an upstream direction presses the pocket against tissue of the atrium.

There is further provided, in accordance with an application of the present invention, apparatus including:

a plurality of prosthetic valve leaflets; and

a frame assembly, including:

5 a tubular portion defined by a repeating pattern of cells, the tubular portion extending circumferentially around a longitudinal axis so as to define a longitudinal lumen, the prosthetic valve leaflets coupled to the inner frame and disposed within the lumen;

10 an outer frame, including a plurality of legs, distributed circumferentially around the tubular portion, each leg having a tissue-engaging flange;

an upstream support portion that includes a plurality of arms that extend radially outward from the tubular portion; and

15 a plurality of appendages, each having a first end that defines a coupling element via which the tubular portion is coupled to the outer frame, and a second end;

and the frame assembly defines a plurality of hubs, distributed circumferentially around the longitudinal axis on a plane that is transverse to the longitudinal axis, each hub defined by convergence and connection of, (i) two adjacent cells of the tubular portion, (ii) an arm of the plurality of arms, and (iii) an appendage of the plurality of appendages.

20 In an application, each hub has six radiating spokes, two of the six spokes being part of a first cell of the two adjacent cells, two of the six spokes being part of a second cell of the two adjacent cells, one of the six spokes being the arm, and one of the six spokes being the second end of the appendage.

In an application, the appendages are in-plane with the tubular portion.

25 In an application, the appendages are in-plane with the outer frame.

There is further provided, in accordance with an application of the present invention, a method for use with a native valve of a heart of a subject, the method including:

percutaneously advancing to heart, an implant:

30 including a valve frame, a valve member disposed within a lumen defined by the valve frame, and at least one leg, coupled to the valve frame at a coupling point, and

having an upstream end, a downstream end, and a central longitudinal axis therebetween;

positioning the implant within the heart such that a tissue-engaging flange of the leg is disposed downstream of the valve, and thereafter causing the flange to protrude 5 radially outward from the axis;

subsequently, while an upstream support portion of the valve frame is disposed upstream of the valve, causing the upstream support portion to protrude radially outward from the axis, such that tissue of the valve is disposed between the upstream support portion and the flange; and

10 subsequently, sandwiching the tissue between the upstream support portion and the flange by reducing a distance between the upstream support portion and the flange by causing longitudinal movement (i) of the upstream support portion toward the coupling point, and (ii) of the tissue-engaging flange away from the coupling point.

15 In an application, causing the longitudinal movement (i) of the upstream support portion toward the coupling point, and (ii) of the tissue-engaging flange away from the coupling point, includes causing the longitudinal movement by increasing a diameter of the lumen.

20 There is further provided, in accordance with an application of the present invention, a method for use with a native valve of a heart of a subject, the method including:

percutaneously advancing to heart, an implant:

including a valve frame, a valve member disposed within a lumen defined by the valve frame, and at least one leg, coupled to the valve frame at a coupling point, and

25 having an upstream end, a downstream end, and a central longitudinal axis therebetween;

positioning the implant within the heart such that an upstream support portion of the valve frame is disposed upstream of the valve, and thereafter causing the upstream support portion to protrude radially outward from the axis;

30 subsequently, while a tissue-engaging flange of the leg is disposed downstream of the valve, causing the tissue-engaging flange to protrude radially outward from the axis, such that tissue of the valve is disposed between the upstream support portion and the flange; and

subsequently, sandwiching the tissue between the upstream support portion and the flange by reducing a distance between the upstream support portion and the flange by causing longitudinal movement (i) of the upstream support portion toward the coupling point, and (ii) of the tissue-engaging flange away from the coupling point.

5 In an application, causing the longitudinal movement (i) of the upstream support portion toward the coupling point, and (ii) of the tissue-engaging flange away from the coupling point, includes causing the longitudinal movement by increasing a diameter of the lumen.

10 There is further provided, in accordance with an application of the present invention, a method for use with a native valve of a heart of a subject, the method including:

percutaneously advancing an implant to the heart, the implant:

having an upstream end, a downstream end, and a central longitudinal axis therebetween, and

15 including a tubular portion, an upstream support portion, and a plurality of tissue-engaging flanges;

positioning the implant within the heart such that the upstream support portion is disposed upstream of the valve,

20 positioning the implant within the heart such that the tissue-engaging flanges are disposed downstream of the valve,

without increasing a diameter of the tubular portion:

causing the upstream support portion to extend radially outward from the axis so as to have a first support-portion span, and

25 causing the flanges to extend radially outward from the axis so as to have a first flange span; and

subsequently, causing the upstream support portion and the flanges move toward each other by at least 5 mm by increasing a diameter of the tubular portion such that:

30 the upstream support portion extends radially outward so as to have a second support-portion span, the first support-portion span being at least 40 percent as great as the second support-portion span, and

the flanges extend radially outward so as to have a second flange span, the first flange span being at least 30 percent as great as the second flange span.

There is further provided, in accordance with an application of the present invention, a method for use with a native valve of a heart of a subject, the method including:

- percutaneously advancing an implant to the heart, the implant:
  - 5 having an upstream end, a downstream end, and a central longitudinal axis therebetween, and
    - including a tubular portion, an upstream support portion, and a plurality of tissue-engaging flanges;
    - positioning the implant within the heart such that the upstream support portion is
      - 10 disposed upstream of the valve,
      - positioning the implant within the heart such that the tissue-engaging flanges are disposed downstream of the valve,
      - without increasing a diameter of the tubular portion:
        - 15 causing the upstream support portion to extend radially outward from the axis, and
          - causing the flanges to extend radially outward from the axis so as to have a first flange span; and
          - subsequently, by increasing a diameter of the tubular portion:
            - 20 causing the upstream support portion and the flanges move toward each other by at least 5 mm,
            - causing the upstream support portion to move further radially outward from the axis, and
              - causing each flange of the plurality of flanges to translate radially outward so as to have a second flange span that is greater than the first flange span.

25 The present invention will be more fully understood from the following detailed description of applications thereof, taken together with the drawings, in which:

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figs. 1A-B and 2A-E are schematic illustrations of an implant for use with a native valve of a heart of a subject, in accordance with some applications of the invention;

30 Figs. 3A-C are schematic illustrations that show structural changes in a frame assembly during transitioning of the assembly between its compressed and expanded states, in accordance with some applications of the invention;

Figs. 4A-F are schematic illustrations of implantation of the implant at the native valve, in accordance with some applications of the invention;

Fig. 5 is a schematic illustration of a step in the implantation of the implant, in accordance with some applications of the invention;

5 Fig. 6 is a schematic illustration of the implant, in accordance with some applications of the invention;

Figs. 7A-B and 8A-B are schematic illustrations of frame assemblies of respective implants, in accordance with some applications of the invention; and

10 Figs. 9A-C are schematic illustrations of an implant comprising a frame assembly, in accordance with some applications of the invention.

### DETAILED DESCRIPTION OF EMBODIMENTS

Reference is made to Figs. 1A-B and 2A-E, which are schematic illustrations of an implant 20 for use with a native valve of a heart of a subject, in accordance with some applications of the invention. Implant 20 comprises a frame assembly 22 that has an upstream end 24, a downstream end 26, and a central longitudinal axis ax1 therebetween. Frame assembly 22 comprises a valve frame 30 that comprises a tubular portion 32 that has an upstream end 34 and a downstream end 36, and is shaped to define a lumen 38 through the tubular portion from the upstream end to the downstream end. Tubular portion 32 circumscribes axis ax1, and thereby defines lumen 38 along the axis. Valve frame 30 further comprises an upstream support portion 40, extending from upstream end 34 of tubular portion 32. Frame assembly 22 further comprises at least one leg 50, coupled to valve frame 30 at (e.g., via) a coupling point 52, and having a tissue-engaging flange 54.

25 Typically, and as described hereinbelow, leg 50 is part of an outer frame (or "leg frame") 60, and frames 30 and 60 define respective coupling elements 31 and 61, which are fixed with respect to each other at coupling points 52. Typically, frames 30 and 60 are coupled to each other only at coupling points 52 (e.g., only via the fixation of coupling elements 31 and 61 with respect to each other).

Implant 20 further comprises a valve member 58 (e.g., one or more prosthetic leaflets) disposed within lumen 38, and configured to facilitate one-way liquid flow through the lumen from upstream end 34 to downstream end 36 (e.g., thereby defining the orientation of the upstream and downstream ends of tubular portion 32). Fig. 1A shows

implant 20 in a fully-expanded state, in which frame assembly 22 is in a fully-expanded state. Fig. 1B shows an exploded view of frame assembly 22 in its fully-expanded state. Figs. 2A-E show respective states of implant 20, which will be discussed in more detail hereinbelow with respect to the implantation of the implant and the anatomy in which the 5 implant is implanted. Fig. 2A shows implant 20 in a compressed state (in which frame assembly 22 is in a compressed state), for percutaneous delivery of the implant to the heart of the subject. Typically, in the compressed state, leg 50 (including flange 54 thereof) is in a constrained-flange state in which the flange is generally parallel with axis ax1. Further typically, in the compressed state, upstream support portion 40 is generally 10 tubular, collinear with tubular portion 32 (e.g., extending collinearly from the tubular portion), and disposed around axis ax1.

Fig. 2B shows a state of implant 20 in which tissue-engaging flange 54 of each leg 50 extends radially away from axis ax1 (e.g., radially away from tubular portion 32). Fig. 2C shows a state of implant 20 in which upstream-support portion 40 extends radially 15 away from axis ax1 (and thereby radially away from tubular portion 32). Fig. 2D shows a state of implant 20 in which both flange 54 and portion 40 extend away from axis ax1. In the fully-expanded state (Figs. 1A-B) both upstream support portion 40 and flange 54 extend radially away from axis ax1. Typically, frame assembly 22 is biased (e.g., shape-set) to assume its fully-expanded state, which is shown in Fig. 2E. Transitioning of 20 implant 20 between the respective states is typically controlled by delivery apparatus, such as by constraining the implant in a compressed state within a delivery tube and/or against a control rod, and selectively releasing portions of the implant to allow them to expand.

In the compressed state of frame assembly 22, tubular portion 32 has a diameter d1, and in the expanded state, the tubular portion has a diameter d2 that is greater than 25 diameter d1. For some applications, diameter d1 is 4-15 mm, (e.g., 5-11 mm) and diameter d2 is 20-50 mm, (e.g., 23-33 mm). Frame assembly 22 is configured such that increasing the diameter of tubular portion 32 (e.g., from d1 to d2) causes longitudinal movement of flange 54 away from coupling point 52. In the same way, reducing the diameter of tubular portion 32 (e.g., from d2 to d1) causes longitudinal movement of 30 flange 54 toward coupling point 52. It is to be noted that the term "longitudinal movement" (including the specification and the claims) means movement parallel with central longitudinal axis ax1. Therefore longitudinal movement of flange 54 away from coupling point 52 means increasing a distance, measured parallel with longitudinal axis

ax1, between flange 54 and coupling point 52. An example of such a configuration is described in more detail with respect to Fig. 3A.

Thus, expansion of tubular portion 32 from its compressed state toward its expanded state (i) increases a circumferential distance between each of coupling points 52 and its adjacent coupling points (e.g., between each of outer-frame coupling elements 61 and its adjacent outer-frame coupling elements) (e.g., from d8 to d9), and (ii) moves legs 50 in a longitudinally upstream direction with respect to the tubular portion.

Typically, frame assembly 22 is configured such that increasing the diameter of tubular portion 32 also causes longitudinal movement of upstream support portion 40 toward coupling point 52, e.g., as described in more detail with respect to Figs. 3B-C. Typically, frame assembly 22 is configured such that increasing the diameter of tubular portion 32 also causes longitudinal movement of upstream end 34 of tubular portion 32 toward coupling point 52. In the same way, reducing the diameter of tubular portion 32 causes longitudinal movement of upstream end 34 away from coupling point 52.

15 For some applications, upstream support portion 40 comprises a plurality of arms 46 that each extends radially outward from tubular portion 32 (e.g., from upstream end 34 of the tubular portion). Arms 46 are typically flexible. For some such applications, arms 46 are coupled to tubular portion 32 such that each arm may deflect independently of adjacent arms during implantation (e.g., due to anatomical topography).

20 For some applications, upstream support portion 40 comprises a plurality of barbs 48 that extend out of a downstream surface of the upstream support portion. For example, each arm 46 may comprise one or more of barbs 48. Barbs 48 press into tissue upstream of the native valve (e.g., into the valve annulus), thereby inhibiting downstream movement of implant 20 (in addition to inhibition of downstream movement provided by the 25 geometry of upstream support portion 40).

One or more surfaces of frame assembly 22 are covered with a covering 23, which typically comprises a flexible sheet, such as a fabric, e.g., comprising polyester. Typically, covering 23 covers at least part of tubular portion 32, typically lining an inner surface of the tubular portion, and thereby defining lumen 38.

30 Further typically, upstream support portion 40 is covered with covering 23, e.g., extending between arms 46 to form an annular shape. It is hypothesized that this reduces a likelihood of paravalvular leakage. For such applications, excess covering 23 may be

provided between arms 46 of upstream support portion 40, so as to facilitate their independent movement. Although Fig. 1A shows covering 23 covering an upstream side of upstream support portion 40, the covering typically additionally (or alternatively) covers the downstream side of the upstream support portion. For example, covering 23 5 may extend over the tips of arms 46 and down the outside of the arms, or a separate piece of covering may be provided on the downstream side of the upstream support portion.

Alternatively, each arm 46 may be individually covered in a sleeve of covering 23, thereby facilitating independent movement of the arms.

For some applications, at least part of legs 50 (e.g., flanges thereof) is covered with 10 covering 23.

Typically, frame assembly 22 comprises a plurality of legs 50 (e.g., two or more legs, e.g., 2-16 legs, such as 4-12 legs, such as 6-12 legs), arranged circumferentially around valve frame 30 (e.g., around the outside of tubular portion 32). Typically, frame assembly 22 comprises a plurality of coupling points 52 at which the legs are coupled to 15 valve frame 30.

As described in more detail hereinbelow (e.g., with reference to Fig. 3A), each leg 50 is typically coupled to a coupling point 52 via a strut 70. For some applications, each leg 50 is coupled to a plurality of (e.g., two) coupling points 52 via a respective plurality of (e.g., two) struts 70. For some such applications, frame assembly 22 is arranged such 20 that, in the expanded state of the frame assembly, leg 50 is disposed, circumferentially with respect to tubular portion 32, between two struts, and each of the two struts are disposed, circumferentially with respect to the tubular portion, between the leg and a respective coupling point 52.

For some applications, a plurality of (e.g., two) legs are coupled to each coupling 25 point 52 via a respective plurality of (e.g., two) struts 70. For some such applications, frame assembly 22 is arranged such that, in the expanded state of the frame assembly, coupling point 52 is disposed, circumferentially with respect to tubular portion 32, between two struts 70, and each of the two struts are disposed, circumferentially with respect to the tubular portion, between the coupling point and a respective leg 50.

30 For some applications, frame assembly 22 comprises an outer frame (e.g., a leg frame) 60 that circumscribes tubular portion 32, comprises (or defines) the plurality of legs 50 and the plurality of struts 70, and is coupled to valve frame 30 at the plurality of

coupling points 52, such that the plurality of legs are distributed circumferentially around the tubular portion. For such applications, outer frame 60 comprises a ring 66 that is defined by a pattern of alternating peaks 64 and troughs 62, and that typically circumscribes tubular portion 32. For example, the ring may comprise struts 70, 5 extending between the peaks and troughs. Peaks 64 are longitudinally closer to upstream end 34 of tubular portion 32 than to downstream end 36, and troughs 62 are longitudinally closer to the downstream end than to the upstream end. (It is to be noted that throughout this patent application, including the specification and the claims, the term "longitudinally" means with respect to longitudinal axis ax1. For example, "longitudinally closer" means closer along axis ax1 (whether positioned on axis ax1 or lateral to axis ax1), and "longitudinal movement" means a change in position along axis ax1 (which may be in addition to movement toward or away from axis ax1).) Therefore, peaks 64 are closer than troughs 62 to upstream end 34, and troughs 62 are closer than peaks 64 to downstream end 36. For applications in which frame 60 comprises ring 66, each leg 50 is 10 coupled to the ring (or defined by frame 60) at a respective trough 62. 15

In the embodiment shown, the peaks and troughs are defined by ring 66 having a generally zig-zag shape. However, the scope of the invention includes ring 66 having another shape that defines peaks and troughs, such as a serpentine or sinusoid shape.

For applications in which frame assembly 22 has a plurality of coupling points 52, 20 the coupling points (and therefore coupling elements 31 and 61) are disposed circumferentially around the frame assembly (e.g., around axis ax1), typically on a transverse plane that is orthogonal to axis ax1. This transverse plane is illustrated by the position of section A-A in Fig. 2B. Alternatively, coupling points 52 may be disposed at different longitudinal heights of frame assembly 22, e.g., such that different flanges 54 are 25 positioned and/or moved differently to others. Typically, coupling points 52 (and therefore coupling elements 31 and 61) are disposed longitudinally between upstream end 24 and downstream end 26 of frame assembly 22, but not at either of these ends. Further typically, coupling points 52 are disposed longitudinally between upstream end 34 and downstream end 36 of tubular portion 32, but not at either of these ends. For example, the 30 coupling points may be more than 3 mm (e.g., 4-10 mm) both from end 34 and from end 36. It is hypothesized that this advantageously positions the coupling points at a part of tubular portion 32 that is more rigid than end 34 or end 36.

It is to be noted that leg 50 is typically expandable into its expanded state (e.g., a released-flange state) such that flange 54 extends away from axis ax1, independently of increasing the diameter of tubular portion 32 (e.g., as shown in Figs. 2B & 2D). Similarly, upstream support portion 40 is typically expandable into its expanded state (e.g., a released-arm state) such that it (e.g., arms 46 thereof) extends away from axis ax1, independently of increasing the diameter of tubular portion 32 (e.g., as shown in Fig. 2C & 2D). The state shown in Fig. 2D may be considered to be an intermediate state. Therefore, implant 20 is typically configured such that legs 50 (e.g., flanges 54 thereof) and upstream support portion 40 are expandable such that they both extend away from axis ax1, while retaining a distance d3 therebetween. This distance is subsequently reducible to a distance d4 by expanding tubular portion 32 (e.g., shown in Fig. 2E).

For some applications, while tubular portion 32 remains in its compressed state, flange 54 can extend away from axis ax1 over 40 percent (e.g., 40-80 percent, such as 40-70 percent) of the distance that it extends from the axis subsequent to the expansion of the tubular portion. For example, for applications in which implant 20 comprises a flange on opposing sides of the implant, a span d15 of the flanges while tubular portion 32 is in its compressed state may be at least 40 percent (e.g., 40-80 percent, such as 40-70 percent) as great as a span d16 of the flanges subsequent to the expansion of the tubular portion. For some applications, span d15 is greater than 15 mm and/or less than 50 mm (e.g., 20-30 mm). For some applications, span d16 is greater than 30 mm and/or less than 60 mm (e.g., 40-50 mm). It is to be noted that flange 54 is effectively fully expanded, with respect to other portions of leg 50 and/or with respect to tubular portion 32, before and after the expansion of the tubular portion.

Similarly, for some applications, while tubular portion 32 remains in its compressed state, upstream support portion 40 (e.g., arms 46) can extend away from axis ax1 over 30 percent (e.g., 30-70 percent) of the distance that it extends from the axis subsequent to the expansion of the tubular portion. That is, for some applications, a span d17 of the upstream support portion while tubular portion 32 is in its compressed state may be at least 30 percent (e.g., 30-70 percent) as great as a span d18 of the upstream support portion subsequent to the expansion of the tubular portion. For some applications, span d17 is greater than 16 mm (e.g., greater than 20 mm) and/or less than 50 mm (e.g., 30-40 mm). For some applications, span d18 is greater than 40 mm and/or less than 65 mm (e.g., 45-56 mm, such as 45-50 mm). It is to be noted that upstream support portion

40 is effectively fully expanded, with respect to tubular portion 32, before and after the expansion of the tubular portion.

It is to be noted that when tubular portion 32 is expanded, flanges 54 typically translate radially outward from span d15 to span d16 (e.g., without deflecting). Typically 5 upstream support portion 40 behaves similarly (e.g., arms 46 translated radially outward from span d17 to span d18, e.g., without deflecting). That is, an orientation of each flange 54 and/or each arm 46 with respect to tubular portion 32 and/or axis ax1 is typically the same in the state shown in Fig. 2D as it is in the state shown in Fig. 2E. Similarly, for some applications an orientation of each flange 54 with respect to upstream support 10 portion 40 (e.g., with respect to one or more arms 46 thereof) is the same before and after expansion of tubular portion 32.

For some applications, increasing the diameter of tubular portion 32 from d1 to d2 causes greater than 1 mm and/or less than 20 mm (e.g., 1-20 mm, such as 1-10 mm or 5-20 mm) of longitudinal movement of flange 54 away from coupling point 52. For some 15 applications, increasing the diameter of tubular portion 32 from d1 to d2 causes greater than 1 mm and/or less than 20 mm (e.g., 1-20 mm, such as 1-10 mm or 5-20 mm) of longitudinal movement of upstream support portion 40 toward coupling point 52. For some applications, distance d3 is 7-30 mm. For some applications, distance d4 is 0-15 mm (e.g., 2-15 mm). For some applications, increasing the diameter of tubular portion 32 20 from d1 to d2 reduces the distance between the upstream support portion and flanges 54 by more than 5 mm and/or less than 30 mm, such as 5-30 mm (e.g., 10-30 mm, such as 10-20 mm or 20-30 mm). For some applications, the difference between d3 and d4 is generally equal to the difference between d1 and d2. For some applications, the difference between d3 and d4 is more than 1.2 and/or less than 3 times (e.g., 1.5-2.5 times, such as 25 about 2 times) greater than the difference between d1 and d2.

For some applications, flanges 54 curve such that a tip of each flange is disposed at a shallower angle with respect to inner region 42 of upstream support portion 40, than are portions of leg 50 that are closer to downstream end 26 of frame assembly 22. For some such applications, a tip of each flange may be generally parallel with inner region 42. For 30 some such applications, while tubular portion 32 is in its expanded state, a tip portion 55 of each flange 54 that extends from the tip of the flange at least 2 mm along the flange, is disposed within 2 mm of upstream support portion 40. Thus, for some applications, while tubular portion 32 is in its expanded state, for at least 5 percent (e.g., 5-8 percent, or at

least 8 percent) of span 18 of upstream support portion 40, the upstream support portion is disposed within 2 mm of a flange 54.

For some applications, in the absence of any obstruction (such as tissue of the valve or covering 23) between flange 54 and upstream support portion 40, increasing the 5 diameter of tubular portion 32 from d1 to d2 causes the flange and the upstream support portion to move past each other (e.g., the flange may move between arms 46 of the upstream support portion), such that the flange is closer to the upstream end of implant 20 than is the upstream support portion, e.g., as shown hereinbelow for frame assemblies 122 and 222, *mutatis mutandis*. (For applications in which upstream support portion 40 is 10 covered by covering 23, flanges 54 typically don't pass the covering. For example, in the absence of any obstruction, flanges 54 may pass between arms 46, and press directly against covering 23.) It is hypothesized that for some applications this configuration applies greater force to the valve tissue being sandwiched, and thereby further facilitates anchoring of the implant. That is, for some applications, distance d3 is smaller than the 15 sum of distance d5 and a distance d14 (described with reference to Fig. 3C). For some applications, increasing the diameter of tubular portion 32 from d1 to d2 advantageously causes flanges 54 and upstream support portion 40 to move greater than 3 mm and/or less than 25 mm (e.g., greater than 5 mm and/or less than 15 mm, e.g., 5-10 mm, such as about 7 mm) with respect to each other (e.g., toward each other and then past each other).

20 For some applications, in the expanded state of frame assembly 22, upstream support portion 40 has an inner region (e.g., an inner ring) 42 that extends radially outward at a first angle with respect to axis ax1 (and typically with respect to tubular portion 32), and an outer region (e.g., an outer ring) 44 that extends, from the inner region, further radially outward from the tubular portion at a second angle with respect to the 25 tubular portion, the second angle being smaller than the first angle. For example, for some applications inner region 42 extends radially outward at an angle alpha\_1 of 60-120 degrees (e.g., 70-110 degrees) with respect to axis ax1, and outer region 44 extends radially outward at an angle alpha\_2 of 5-70 degrees (e.g., 10-60 degrees) with respect to axis ax1.

30 It is to be noted that angles alpha\_1 and alpha\_2 are measured between the respective region support portion 40, and the portion of axis ax1 that extends in an upstream direction from the level of frame assembly 22 at which the respective region begins to extend radially outward.

For some applications in which implant 20 is configured to be placed at an atrioventricular valve (e.g., a mitral valve or a tricuspid valve) of the subject, region 42 is configured to be placed against the upstream surface of the annulus of the atrioventricular valve, and region 44 is configured to be placed against the walls of the atrium upstream of 5 the valve.

For some applications, outer region 44 is more flexible than inner region 42. For example, and as shown, each arm 46 may have a different structure in region 44 than in region 42. It is hypothesized that the relative rigidity of region 42 provides resistance against ventricular migration of implant 20, while the relative flexibility of region 44 10 facilitates conformation of upstream support portion 40 to the atrial anatomy.

For some applications, two or more of arms 46 are connected by a connector (not shown), reducing the flexibility, and/or the independence of movement of the connected arms relative to each other. For some applications, arms 46 are connected in particular sectors of upstream support portion 40, thereby making these sectors more rigid than 15 sectors in which the arms are not connected. For example, a relatively rigid sector may be provided to be placed against the posterior portion of the mitral annulus, and a relatively flexible sector may be provided to be placed against the anterior side of the mitral annulus, so as to reduce forces applied by upstream support portion 40 on the aortic sinus.

For some applications, and as shown, coupling points 52 are disposed closer to 20 downstream end 26 of frame assembly 22 than are flanges 54, or is upstream support portion 40.

As described in more detail with respect to Figs. 4A-F, the movement of flange 54 away from coupling point 52 (and the typical movement of upstream support portion 40 toward the coupling point) facilitates the sandwiching of tissue of the native valve (e.g., 25 leaflet and/or annulus tissue) between the flange and the upstream support portion, thereby securing implant 20 at the native valve.

Typically, in the compressed state of tubular portion 32, a downstream end of each leg 50 is longitudinally closer than valve-frame coupling elements 31 to downstream end 36, and flange 54 of each leg is disposed longitudinally closer than the valve-frame 30 coupling elements to upstream end 34. Typically, this is also the case in the expanded state of tubular portion 32.

Figs. 3A-C show structural changes in frame assembly 22 during transitioning of the assembly between its compressed and expanded states, in accordance with some applications of the invention. Figs. 3A-C each show a portion of the frame assembly, the structural changes thereof being representative of the structural changes that occur in other portions of the frame assembly. Fig. 3A shows a leg 50 and struts 70 (e.g., a portion of outer frame 60), and illustrates the structural changes that occur around outer frame 60. Fig. 3B shows a portion of valve frame 30, and illustrates the structural changes that occur around the valve frame. Fig. 3C shows valve frame 30 as a whole. In each of Figs. 3A-C, state (A) illustrates the structure while frame assembly 22 (and in particular tubular portion 32) is in its compressed state, and state (B) illustrates the structure while the frame assembly (and in particular tubular portion 32) is in its expanded state.

Fig. 3A shows structural changes in the coupling of legs 50 to coupling point 52 (e.g., structural changes of outer frame 60) during the transitioning of frame assembly 22 (and in particular tubular portion 32) between its compressed and expanded states. Each leg 50 is coupled to valve frame 30 via at least one strut 70, which connects the leg to coupling point 52. Typically, each leg 50 is coupled to valve frame 30 via a plurality of struts 70. A first end 72 of each strut 70 is coupled to leg 50, and a second end 74 of each strut is coupled to a coupling point 52. As described hereinabove, for applications in which frame 60 comprises ring 66, each leg 50 is coupled to the ring at a respective trough 62. Ring 66 may comprise struts 70, extending between the peaks and troughs, with each first end 72 at (or close to) a trough 62, and each second end 74 at (or close to) a peak 64.

In the compressed state of frame assembly 22 (and in particular of tubular portion 32), each strut 70 is disposed at a first angle in which first end 72 is disposed closer than second end 74 to the downstream end of the frame assembly. Expansion of frame assembly 22 (and in particular of tubular portion 32) toward its expanded state causes strut 70 to deflect to a second angle. This deflection moves first end 72 away from the downstream end of frame assembly 22. That is, in the expanded state of frame assembly 22, first end 72 is further from the downstream end of the frame assembly than it is when the frame assembly is in its compressed state. This movement is shown as a distance  $d5$  between the position of end 72 in state (A) and its position in state (B). This movement causes the above-described movement of flanges 54 away from coupling points 52. As shown, flanges 54 typically move the same distance  $d5$  in response to expansion of frame assembly 22.

For applications in which outer frame 60 comprises ring 66, the pattern of alternating peaks and troughs may be described as having an amplitude longitudinally between the peaks and troughs, i.e., measured parallel with central longitudinal axis ax1 of frame assembly 22, and the transition between the compressed and expanded states may

5 be described as follows: In the compressed state of frame assembly 22 (and in particular of tubular portion 32), the pattern of ring 66 has an amplitude d20. In the expanded state frame assembly 22 (and in particular of tubular portion 32), the pattern of ring 66 has an amplitude d21 that is lower than amplitude d20. Because (i) it is at peaks 64 that ring 66

10 is coupled to valve frame 30 at coupling points 52, and (ii) it is at troughs 62 that ring 66 is coupled to legs 50, this reduction in the amplitude of the pattern of ring 66 moves legs 50 (e.g., flanges 54 thereof) longitudinally further from the downstream end of the frame assembly. The magnitude of this longitudinal movement (e.g., the difference between magnitudes d20 and d21) is equal to d5.

Typically, distance d5 is the same distance as the distance that flange 54 moves

15 away from coupling point 52 during expansion of the frame assembly. That is, a distance between flange 54 and the portion of leg 50 that is coupled to strut 70, typically remains constant during expansion of the frame assembly. For some applications, the longitudinal movement of flange 54 away from coupling point 52 is a translational movement (e.g., a movement that does not include rotation or deflection of the flange).

20 For some applications, a distance d6, measured parallel to axis ax1 of frame assembly 22, between coupling point 52 and first end 72 of strut 70 while assembly 22 is in its compressed state, is 3-15 mm. For some applications, a distance d7, measured parallel to axis ax1, between coupling point 52 and first end 72 of strut 70 while assembly 22 is in its expanded state, is 1-5 mm (e.g., 1-4 mm).

25 For some applications, amplitude d20 is 2-10 mm (e.g., 4-7 mm). For some applications, amplitude d21 is 4-9 mm (e.g., 5-7 mm).

For some applications, and as shown, in the expanded state, first end 72 of strut 70 is disposed closer to the downstream end of frame assembly 22 than is coupling point 52. For some applications, in the expanded state, first end 72 of strut 70 is disposed further

30 from the downstream end of frame assembly 22 than is coupling point 52.

For applications in which frame assembly 22 comprises a plurality of legs 50 and a plurality of coupling points 52 (e.g., for applications in which the frame assembly comprises outer frame 60) expansion of the frame assembly increases a circumferential

distance between adjacent coupling points 52, and an increase in a circumferential distance between adjacent legs 50. Fig. 3A shows such an increase in the circumferential distance between adjacent coupling points 52, from a circumferential distance d8 in the compressed state to a circumferential distance d9 in the expanded state. For some 5 applications, distance d8 is 1-6 mm. For some applications, distance d9 is 3-15 mm.

For some applications, in addition to being coupled via ring 66 (e.g., struts 70 thereof) legs 50 are also connected to each other via connectors 78. Connectors 78 allow the described movement of legs 50 during expansion of frame assembly 22, but typically stabilize legs 50 relative to each other while the frame assembly is in its expanded state. 10 For example, connectors 78 may bend and/or deflect during expansion of the frame assembly.

Figs. 3B-C show structural changes in valve frame 30 during the transitioning of frame assembly 22 between its compressed and expanded states. Tubular portion 32 of valve frame 30 is defined by a plurality of cells 80, which are defined by the repeating 15 pattern of the valve frame. When frame assembly 22 is expanded from its compressed state toward its expanded state, cells 80 (i) widen from a width d10 to a width d11 (measured orthogonal to axis ax1 of the frame assembly), and (ii) shorten from a height d12 to a height d13 (measured parallel to axis ax1 of the frame assembly). This shortening reduces the overall height (i.e., a longitudinal length between upstream end 34 20 and downstream end 36) of tubular portion 32 from a height d22 to a height d23, and thereby causes the above-described longitudinal movement of upstream support portion 40 toward coupling points 52 by a distance d14 (shown in Fig. 3C). For some applications, and as shown, coupling points 52 are disposed at the widest part of each cell.

Due to the configurations described herein, the distance by which flanges 54 move 25 with respect to (e.g., toward, or toward-and-beyond) upstream support portion 40 (e.g., arms 46 thereof), is typically greater than the reduction in the overall height of tubular portion 32 (e.g., more than 20 percent greater, such as more than 30 percent greater, such as more than 40 percent greater). That is, implant 20 comprises:

30 a valve frame (30) that comprises a tubular portion (32) that circumscribes a longitudinal axis (ax1) of the valve frame so as to define a lumen (38) along the axis, the tubular portion having an upstream end (34), a downstream end (36), a longitudinal length therebetween, and a diameter (e.g., d1 or d2) transverse to the longitudinal axis;

a valve member (58), coupled to the tubular portion, disposed within the lumen, and arranged to provide unidirectional upstream-to-downstream flow of blood through the lumen;

5 an upstream support portion (40), coupled to the tubular portion; and  
an outer frame (60), coupled to the tubular portion, and comprising a tissue-engaging flange (54),

wherein:

the implant has a first state (e.g., as shown in Fig. 2D and Fig. 4D) and a second state (e.g., as shown in Fig. 2E and Fig. 4E),

10 in both the first state and the second state, (i) the upstream support portion extends radially outward from the tubular portion, and (ii) the tissue-engaging flange extends radially outward from the tubular portion, and

15 the tubular portion, the upstream support portion, and the outer frame are arranged such that transitioning of the implant from the first state toward the second state:

increases the diameter of the tubular portion by a diameter-increase amount (e.g., the difference between d1 and d2),

decreases the length of the tubular portion by a length-decrease amount (e.g., the difference between d22 and d23), and

20 moves the flange a longitudinal distance with respect to (e.g., toward or toward-and-beyond) the upstream support portion (e.g., the difference between d3 and d4), this distance being greater than the length-decrease amount.

As shown in the figures, valve frame 30 is typically coupled to outer frame 60 by coupling between (i) a valve-frame coupling element 31 defined by valve frame 30, and 25 (ii) an outer-frame coupling element 61 defined by outer frame 60 (e.g., an outer-frame coupling element is coupled to end 74 of each strut). Typically, elements 31 and 61 are fixed with respect to each other. Each coupling point 52 is thereby typically defined as the point at which a valve-frame coupling element and a corresponding outer-frame coupling 30 element 61 are coupled (e.g., are fixed with respect to each other). For some applications, and as shown, elements 31 and 61 are eyelets configured to be coupled together by a connector, such as a pin or suture. For some applications, elements 31 and 61 are soldered or welded together.

Typically, and as shown, valve-frame coupling elements 31 are defined by tubular portion 32, and are disposed circumferentially around central longitudinal axis ax1. Outer-frame coupling elements 61 are coupled to ring 66 (or defined by frame 60, such as by ring 66) at respective peaks 64.

5 As shown (e.g., in Figs. 2A-E), valve frame 30 (e.g., tubular portion 32 thereof) and outer frame 60 (e.g., ring 66 thereof) are arranged in a close-fitting coaxial arrangement, in both the expanded and compressed states of frame assembly 22. Ignoring spaces due to the cellular structure of the frames, a radial gap d19 between valve frame 30 (e.g., tubular portion 32 thereof) and outer frame 60 (e.g., ring 66 thereof) is typically less  
10 than 2 mm (e.g., less than 1 mm), in both the compressed and expanded states, and during the transition therebetween. This is facilitated by the coupling between frames 30 and 60, and the behavior, described hereinabove, of frame 60 in response to changes in the diameter of tubular portion 32 (e.g., rather than solely due to delivery techniques and/or tools). For some applications, more than 50 percent (e.g., more than 60 percent) of ring 66  
15 is disposed within 2 mm of tubular portion 32 in both the compressed and expanded states, and during the transition therebetween. For some applications, more than 50 percent (e.g., more than 60 percent) of outer frame 60, except for flanges 54, is disposed within 2 mm of tubular portion 32 in both the compressed and expanded states, and during the transition therebetween.

20 The structural changes to frame assembly 22 (e.g., to outer frame 60 thereof) are described hereinabove as they occur during (e.g., as a result of) expansion of the frame assembly (in particular tubular portion 32 thereof). This is the natural way to describe these changes because, as described hereinbelow with respect to Figs. 4A-6, assembly 22 is in its compressed state during percutaneous delivery to the implant site, and is  
25 subsequently expanded. However, the nature of implant 20 may be further understood by describing structural changes that occur during compression of the frame assembly (e.g., a transition from the expanded state in Fig. 2E to the intermediate state in Fig. 2D), in particular tubular portion 32 thereof (including if tubular portion 32 were compressed by application of compressive force to the tubular portion, and not to frame 60 except via the  
30 tubular portion pulling frame 60 radially inward). Such descriptions may also be relevant because implant 20 is typically compressed (i.e., "crimped") soon before its percutaneous delivery, and therefore these changes may occur while implant 20 is in the care of the operating physician.

For some applications, the fixation of peaks 64 to respective sites of tubular portion 32 is such that compression of the tubular portion from its expanded state toward its compressed state such that the respective sites of the tubular portion pull the peaks radially inward via radially-inward tension on coupling points 52: (i) reduces a 5 circumferential distance between each of the coupling points and its adjacent coupling points (e.g., from d9 to d8), and (ii) increases the amplitude of the pattern of ring 66 (e.g., from d21 to d20).

For some applications, the fixation of outer-frame coupling elements 61 to valve-frame coupling elements 31 is such that compression of tubular portion 32 from its 10 expanded state toward its compressed state such that the valve-frame coupling elements pull the outer-frame coupling elements radially inward: (i) reduces a circumferential distance between each of the outer-frame coupling elements and its adjacent outer-frame coupling elements (e.g., from d9 to d8), and (ii) increases the amplitude of the pattern of ring 66 (e.g., from d21 to d20).

15 For some applications, the fixation of peaks 64 to the respective sites of tubular portion 32 is such that compression of the tubular portion from its expanded state toward its compressed state (i) pulls the peaks radially inward via radially-inward pulling of the respective sites of the tubular portion on the peaks, (ii) reduces a circumferential distance between each of coupling points 52 and its adjacent coupling points (e.g., from d9 to d8), 20 and (iii) increases the amplitude of the pattern of ring 66 (e.g., from d21 to d20), without increasing radial gap d19 between valve frame 30 (e.g., tubular portion 32 thereof) and the ring by more than 1.5 mm.

For some applications, the fixation of outer-frame coupling elements 61 with 25 respect to valve-frame coupling elements 31 is such that compression of tubular portion 32 from its expanded state toward its compressed state (i) pulls outer-frame coupling elements 61 radially inward via radially-inward pulling of valve-frame coupling elements 31 on outer-frame coupling elements 61, (ii) reduces a circumferential distance between each of the outer-frame coupling elements and its adjacent outer-frame coupling elements (e.g., from d9 to d8), and (iii) increases the amplitude of the pattern of ring 66 (e.g., from 30 d21 to d20), without increasing radial gap d19 between valve frame 30 (e.g., tubular portion 32 thereof) and the ring by more than 1.5 mm.

Reference is made to Figs. 4A-F, which are schematic illustrations of implantation of implant 20 at a native valve 10 of a heart 4 of a subject, in accordance with some

applications of the invention. Valve 10 is shown as a mitral valve of the subject, disposed between a left atrium 6 and a left ventricle 8 of the subject. However implant 20 may be implanted at another heart valve of the subject, *mutatis mutandis*. Similarly, although Figs. 4A-F show implant 20 being delivered transseptally via a sheath 88, the implant may 5 alternatively be delivered by any other suitable route, such as transatrially, or transapically.

Implant 20 is delivered, in its compressed state, to native valve 10 using a delivery tool 89 that is operable from outside the subject (Fig. 4A). Typically, implant 20 is delivered within a delivery capsule 90 of tool 89, which retains the implant in its 10 compressed state. A transseptal approach, such as a transfemoral approach, is shown. Typically, implant 20 is positioned such that at least flanges 54 are disposed downstream of the native valve (i.e., within ventricle 8). At this stage, frame assembly 22 of implant 20 is as shown in Fig. 2A.

Subsequently, flanges 54 are allowed to protrude radially outward, as described 15 hereinabove, e.g., by releasing them from capsule 90 (Fig. 4B). For example, and as shown, capsule 90 may comprise a distal capsule-portion 92 and a proximal capsule-portion 94, and the distal capsule-portion may be moved distally with respect to implant 20, so as to expose flanges 54. At this stage, frame assembly 22 of implant 20 is as shown in Fig. 2B.

20 Subsequently, implant 20 is moved upstream, such that upstream support portion 40, in its compressed state, is disposed upstream of leaflets 12 (i.e., within atrium 6). For some applications, the upstream movement of implant 20 causes flanges 54 to engage leaflets 12. However, because of the relatively large distance d3 provided by implant 20 (described hereinabove), for some applications it is not necessary to move the implant so 25 far upstream that flanges 54 tightly engage leaflets 12 and/or pull the leaflets upstream of the valve annulus. Upstream support portion 40 is then allowed to expand such that it protrudes radially outward, as described hereinabove, e.g., by releasing it from capsule 90 (Fig. 4D). For example, and as shown, proximal capsule-portion 94 may be moved proximally with respect to implant 20, so as to expose upstream support portion 40. At 30 this stage, frame assembly 22 of implant 20 is as shown in Fig. 2D, in which: (i) distance d3 exists between upstream support portion 40 and flanges 54, (ii) the flanges have span d15, (iii) the upstream support portion has span d17, and (iv) tubular portion 32 has diameter d1.

Typically, expansion of frame assembly 22 is inhibited by distal capsule-portion 92 (e.g., by inhibiting expansion of tubular portion 32), and/or by another portion of delivery tool 89 (e.g., a portion of the delivery tool that is disposed within lumen 38).

Subsequently, implant 20 is allowed to expand toward its expanded state, such that 5 tubular portion 32 widens to diameter  $d_2$ , and the distance between upstream support portion 40 and flanges 54 reduces to distance  $d_4$  (Fig. 4E). This sandwiches tissue of valve 10 (typically including annular tissue and/or leaflets 12) between upstream support portion 40 and flanges 54, thereby securing implant 20 at the valve. Fig. 4F shows delivery capsule 90 having been removed from the body of the subject, leaving implant 20 10 in place at valve 10.

As described hereinabove, implant 20 is configured such that when tubular portion 32 is expanded, flanges 54 and upstream support portion 40 move a relatively large distance toward each other. This enables distance  $d_3$  to be relatively large, while distance 15  $d_4$  is sufficiently small to provide effective anchoring. As also described hereinabove, implant 20 is configured such that flanges 54 and upstream support portion 40 can extend radially outward a relatively large distance while tubular portion 32 remains compressed. It is hypothesized that for some applications, these configurations (independently and/or 20 together) facilitate effective anchoring of implant 20, by facilitating placement of a relatively large proportion of valve tissue (e.g., leaflets 12) between the flanges and the upstream support portion prior to expanding tubular portion 32 and sandwiching the valve tissue.

It is further hypothesized that the relatively great radially-outward extension of flanges 54 and upstream support portion 40 prior to expansion of tubular portion 32, further facilitates the anchoring/sandwiching step by reducing radially-outward pushing of 25 the valve tissue (e.g., leaflets 12) during the expansion of the tubular portion, and thereby increasing the amount of valve tissue that is sandwiched.

It is yet further hypothesized that this configuration of implant 20 facilitates identifying correct positioning of the implant (i.e., with upstream support portion 40 upstream of leaflets 12 and flanges 54 downstream of the leaflets) prior to expanding 30 tubular portion 32 and sandwiching the valve tissue.

As shown in Fig. 1A, for some applications, in the expanded state of frame assembly 22, implant 20 defines a toroidal space 49 between flanges 54 and upstream support portion 40 (e.g., a space that is wider than distance  $d_4$ ). For example, space 49

may have a generally triangular cross-section. It is hypothesized that for some such applications, in addition to sandwiching tissue of the native valve between upstream support portion 40 and flanges 54 (e.g., the tips of the flanges), space 49 advantageously promotes tissue growth therewithin (e.g., between leaflet tissue and covering 23), which 5 over time further secures implant 20 within the native valve.

Reference is now made to Fig. 5, which is a schematic illustration of a step in the implantation of implant 20, in accordance with some applications of the invention. Whereas Figs. 4A-F show an implantation technique in which flanges 54 are expanded 10 prior to upstream support portion 40, for some applications the upstream support portion is expanded prior to the flanges. Fig. 5 shows a step in such an application.

Reference is again made to Figs. 2A-5. As noted hereinabove, implant 20 may be implanted by causing flanges 54 to radially protrude before causing upstream support portion 40 to radially protrude, or may be implanted by causing the upstream support portion to protrude before causing the flanges to protrude. For some applications, implant 15 20 is thereby configured to be deliverable in a downstream direction (e.g., transseptally, as shown, or transapically) or in an upstream direction (e.g., transapically or via the aortic valve). Thus, for some applications, an operating physician may decide which delivery route is preferable for a given application (e.g., for a given subject, and/or based on available equipment and/or expertise), and implant 20 is responsively prepared for the 20 chosen delivery route (e.g., by loading the implant into an appropriate delivery tool).

It is to be noted that for some applications, downstream delivery of implant 20 may be performed by expanding flanges 54 first (e.g., as shown in Figs. 4A-F) or by expanding upstream support portion 40 first (e.g., as shown in Fig. 5). Similarly, for some applications upstream delivery of implant 20 may be performed by upstream support 25 portion 40 first, or by expanding flanges 54 first.

Reference is now made to Fig. 6, which is a schematic illustration of implant 20, in the state and position shown in Fig. 4D, in accordance with some applications of the invention. For some applications, while implant 20 is in the state and position shown in Fig. 4D, leaflets 12 of valve 10 are able to move, at least in part in response to beating of 30 the heart. Frame (A) shows leaflets 12 during ventricular systole, and frame (B) shows the leaflets during ventricular diastole. For some such applications, blood is thereby able to flow from atrium 6 to ventricle 8, between leaflets 12 and implant 20. It is hypothesized that this advantageously facilitates a more relaxed implantation procedure, e.g., facilitating

retaining of implant 20 in this state and position for a duration of greater than 8 minutes. During this time, imaging techniques may be used to verify the position of implant 20, and/or positioning of leaflets 12 between upstream support portion 40 and flanges 54.

Reference is made to Figs. 7A-B and 8A-B, which are schematic illustrations of 5 frame assemblies 122 and 222 of respective implants, in accordance with some applications of the invention. Except where noted otherwise, frame assemblies 122 and 222 are typically identical to frame assembly 22, *mutatis mutandis*. Elements of frame assemblies 122 and 222 share the name of corresponding elements of frame assembly 22. Additionally, except where noted otherwise, the implants to which frame assemblies 122 10 and 222 belong are similar to implant 20, *mutatis mutandis*.

Frame assembly 122 comprises (i) a valve frame 130 that comprises a tubular portion 132 and an upstream support portion 140 that typically comprises a plurality of arms 146, and (ii) an outer frame (e.g., a leg frame) 160 that circumscribes the valve frame, and comprises a plurality of legs 150 that each comprise a tissue-engaging flange 154. Typically, outer frame 160 comprises a ring 166 to which legs 150 are coupled. Ring 166 is defined by a pattern of alternating peaks and troughs, the peaks being fixed to frame 130 at respective coupling points 152, e.g., as described hereinabove for frame assembly 22, *mutatis mutandis*. 15

Frame assembly 222 comprises (i) a valve frame 230 that comprises a tubular portion 232 and an upstream support portion 240 that typically comprises a plurality of arms 246, and (ii) an outer frame (e.g., a leg frame) 260 that circumscribes the valve frame, and comprises a plurality of legs 250 that each comprise a tissue-engaging flange 254. Typically, outer frame 260 comprises a ring 266 to which legs 250 are coupled. Ring 266 is defined by a pattern of alternating peaks and troughs, the peaks being fixed to frame 230 at respective coupling points 252, e.g., as described hereinabove for frame assembly 22, *mutatis mutandis*. 25

Whereas arms 46 of frame assembly 22 are shown as extending from upstream end 34 of tubular portion 32, arms 146 and 246 of frame assemblies 122 and 222, respectively, extend from sites further downstream. (This difference may also be made to frame 30 assembly 22, *mutatis mutandis*.) Tubular portions 32, 132 and 232 are each defined by a repeating pattern of cells that extends around the central longitudinal axis. Typically, and as shown, tubular portions 32, 132 and 232 are each defined by two stacked, tessellating rows of cells. In the expanded state of each tubular portion, these cells are typically

narrower at their upstream and downstream extremities than midway between these extremities. For example, and as shown, the cells may be roughly diamond or astroid in shape. In frame assembly 22, each arm 46 is attached to and extends from a site 35 that is at the upstream extremity of cells of the upstream row. In contrast, in frame assemblies 5 122 and 222, each arm 146 or 246 is attached to and extends from a site 135 (assembly 122) or 235 (assembly 222) that is at the connection between two adjacent cells of the upstream row (alternatively described as being at the upstream extremity of cells of the downstream row).

It is hypothesized by the inventors that this lower position of the arms, while 10 maintaining the length of the lumen of the tubular portion, advantageously reduces the distance that the tubular portion (i.e., the downstream end thereof) extends into the ventricle of the subject, and thereby reduces a likelihood of inhibiting blood flow out of the ventricle through the left ventricular outflow tract. It is further hypothesized that this 15 position of the arms reduces radial compression of the tubular portion by movement of the heart, due to greater rigidity of the tubular portion at sites 135 and 235 (which is supported by two adjacent cells) than at site 35 (which is supported by only one cell).

As shown, in the expanded state of frame assemblies 22, 122 and 222, the legs (50, 150 and 250, respectively) are circumferentially staggered with the arms of the upstream support portion (46, 146 and 246, respectively). This allows the legs to move in an 20 upstream direction between the arms during expansion of the tubular portion (32, 132 and 232, respectively), facilitating application of greater sandwiching force on tissue of the native valve. The lower position of the arms of assemblies 122 and 222 includes circumferentially shifting the position of the arms by the width of half a cell. In order to 25 maintain the circumferential staggering of the arms and legs, rings 166 and 266 (and thereby legs 150 and 250) are circumferentially shifted correspondingly. As a result, whereas the peaks of ring 66 generally align with connections between adjacent cells of the downstream row of cells of tubular portion 32 (and are fixed to these sites), the peaks of rings 166 and 266 are generally aligned midway between these sites (i.e., at spaces of the cellular structure of the tubular portion). An appendages 168 (for assembly 122) or 30 268 (for assembly 222) facilitate fixing of the peak with respect to the tubular structure.

For assembly 122, appendages 168 are defined by valve frame 130 (e.g., by tubular portion 132 thereof) and extend (in a downstream direction) to the peaks of ring 166, to which they are fixed. For example, each appendage 168 may define a valve-frame

coupling element 131 that is fixed to a respective outer-frame coupling element 161 defined by outer frame 260. Typically, appendages 168 extend from sites 135. Typically, appendages 168 are integral with tubular portion 132 and/or in-plane with the tubular portion (e.g., are part of its tubular shape).

5 For assembly 222, appendages 268 are defined by outer frame 260, and extend (e.g., in an upstream direction) from the peaks of ring 266. Typically, appendages 268 extend to sites 235, to which they are fixed. For example, each appendage 268 may define an outer-frame coupling element 261 that is fixed to a respective valve-frame coupling element 231 defined by valve frame 230 (e.g., by tubular portion 232 thereof). Typically, 10 appendages 268 are integral with outer frame 260 and/or in-plane with adjacent portions of outer frame 260, such as ring 266.

Therefore, frame assembly 122 defines a hub at site 135, and frame assembly 222 defines a hub at site 235. For some applications, apparatus therefore comprises:

15 a plurality of prosthetic valve leaflets; and  
 a frame assembly, comprising:  
 a tubular portion (132 or 232) defined by a repeating pattern of cells, the tubular portion extending circumferentially around longitudinal axis ax1 so as to define a longitudinal lumen, the prosthetic valve leaflets coupled to the inner frame and disposed within the lumen;  
 20 an outer frame (160 or 260), comprising a plurality of legs (150 or 250), distributed circumferentially around the tubular portion, each leg having a tissue-engaging flange (154 or 254);  
 an upstream support portion (140 or 240) that comprises a plurality of arms (146 or 246) that extend radially outward from the tubular portion;  
 25 and  
 a plurality of appendages (168 or 268), each having a first end that defines a coupling element (161 or 261) via which the tubular portion is coupled to the outer frame, and a second end;  
 wherein the frame assembly defines a plurality of hubs (135 or 235), distributed circumferentially around the longitudinal axis on a plane that is transverse to longitudinal axis ax1, each hub defined by convergence and connection of, (i) two adjacent cells of the tubular portion, (ii) an arm of the plurality of arms, and (iii) an appendage of the plurality of appendages.

Reference is made to Figs. 9A-C, which are schematic illustrations of an implant 320 comprising a frame assembly 322, in accordance with some applications of the invention. Except where noted otherwise, frame assembly 322 is identical to frame assembly 122, and implant 300 is identical to the implant to which frame assembly 122 belongs, *mutatis mutandis*. Fig. 9A is a side-view of implant 320, and Fig. 9B is an isometric bottom-view of the implant.

Frame assembly 122 comprises (i) a valve frame 330 that comprises a tubular portion 332 and an upstream support portion 340 that typically comprises a plurality of arms 346, and (ii) an outer frame (e.g., a leg frame) 360 that circumscribes the valve frame, and comprises a plurality of legs 350 that each comprise a tissue-engaging flange 354. Typically, outer frame 360 comprises a ring 366 to which legs 350 are coupled. Ring 366 is defined by a pattern of alternating peaks and troughs, the peaks being fixed to frame 330 at respective coupling points 352, e.g., as described hereinabove for frame assembly 22 and/or frame assembly 122, *mutatis mutandis*.

Frame assembly 322 comprises an annular upstream support portion 340 that has an inner portion 342 that extends radially outward from the upstream portion (e.g., the upstream end) of tubular portion 332. Upstream support portion 340 further comprises one or more fabric pockets 344 disposed circumferentially around inner portion 342, each pocket of the one or more pockets having an opening that faces a downstream direction (i.e., generally toward the downstream end of implant 320). In the figures, upstream support portion 340 has a single toroidal pocket 344 that extends circumferentially around inner portion 342.

Typically, a covering 323 (e.g., similar to covering 23, described hereinabove, *mutatis mutandis*) is disposed over arms 346, thereby forming pocket 344. Further typically, arms 346 are shaped to form pocket 344 from covering 323. For example, and as shown, arms 346 may curve to form a hook-shape.

For some applications, portion 340 has a plurality of separate pockets 344, e.g., separated at arms 346. For some such applications, covering 323 is loosely-fitted (e.g., baggy) between radially-outward parts of arms 346, e.g., compared to inner portion 342, in which the covering is more closely-fitted between radially-inward parts of the arms.

Fig. 9C shows implant 320 implanted at native valve 10. Pocket 344 is typically shaped and arranged to billow in response to perivalvular flow 302 of blood in an upstream direction. If ventricular systole forces blood in ventricle 8 between implant 320

and native valve 10, that blood inflates pocket 344 and presses it (e.g., covering 323 and/or the radially-outward part of arm 346) against tissue of atrium 6 (e.g., against the atrial wall), thereby increasing sealing responsively. It is hypothesized by the inventors that the shape and orientation of pocket 344 (e.g., the hook-shape of arms 346) facilitates 5 this pressing radially-outward in response to the pocket's receipt of upstream-flowing blood.

Pocket(s) 344 may be used in combination with any of the implants described herein, mutatis mutandis.

Reference is again made to Figs. 1A-9C. It is to be noted that unless specifically 10 stated otherwise, the term "radially outward" (e.g., used to describe upstream support portion 40 and flanges 54) means portions of the element are disposed progressively further outward from a central point (such as longitudinal axis ax1 or tubular portion 32), but does not necessarily mean disposed at 90 degrees with respect to longitudinal axis ax1. For example, flanges 54 may extend radially outward at 90 degrees with respect to 15 longitudinal axis ax1, but may alternatively extend radially outward at a shallower angle with respect to the longitudinal axis.

It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove. Rather, the scope of the present invention includes both combinations and subcombinations of the various 20 features described hereinabove, as well as variations and modifications thereof that are not in the prior art, which would occur to persons skilled in the art upon reading the foregoing description.

## CLAIMS

1. Apparatus for use with a native valve of a heart of a subject, the apparatus comprising an implant that comprises:

a valve frame that comprises a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the tubular portion having an upstream end, a downstream end, a longitudinal length therebetween, and a diameter transverse to the longitudinal axis;

a valve member, coupled to the tubular portion, disposed within the lumen, and arranged to provide unidirectional upstream-to-downstream flow of blood through the lumen;

an upstream support portion, coupled to the tubular portion; and

an outer frame, coupled to the tubular portion, and comprising a tissue-engaging flange, wherein:

the implant has a first state and a second state,

in both the first state and the second state, (i) the upstream support portion extends radially outward from the tubular portion, and (ii) the tissue-engaging flange extends radially outward from the tubular portion, and

the tubular portion, the upstream support portion, and the outer frame are arranged such that transitioning of the implant from the first state toward the second state:

increases the diameter of the tubular portion by a diameter-increase amount,

decreases the length of the tubular portion by a length-decrease amount, and

moves the flange a longitudinal distance toward or toward-and-beyond the upstream support portion, the distance being greater than the length-decrease amount.

2. The apparatus according to claim 1, wherein the tubular portion, the upstream support portion, and the outer frame are arranged such that the longitudinal distance is more than 20 percent greater than the length-decrease amount.

3. The apparatus according to claim 2, wherein the tubular portion, the upstream support portion, and the outer frame are arranged such that the longitudinal distance is more than 30 percent greater than the length-decrease amount.

4. The apparatus according to claim 3, wherein the tubular portion, the upstream support portion, and the outer frame are arranged such that the longitudinal distance is more than 40 percent greater than the length-decrease amount.

5. Apparatus for use with a native valve of a heart of a subject, the apparatus comprising:  
a frame assembly, having an upstream end and a downstream end, and a central longitudinal axis therebetween, and comprising:

a valve frame, comprising:

a tubular portion having an upstream end and a downstream end, and shaped to define a lumen therebetween, and

an upstream support portion, extending from the upstream end of the tubular portion; and

at least one leg, coupled to the valve frame at a coupling point, and having a tissue-engaging flange; and

a valve member disposed within the lumen, and configured to facilitate one-way liquid flow through the lumen from the upstream end of the tubular portion to the downstream end of the tubular portion,

wherein the frame assembly:

has a compressed state, for percutaneous delivery to the heart, in which the tubular portion has a compressed diameter and in which the at least one tissue-engaging flange has a constrained-flange state,

is biased to assume an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter and in which the at least one tissue-engaging flange has a released-flange state in which the flange extends radially outward from the tubular portion, and

is configured such that in a transition from the compressed state to the expanded state of the frame assembly, increasing the diameter of the tubular portion toward the expanded diameter causes longitudinal movement:

of the upstream support portion toward the coupling point, and  
of the tissue-engaging flange away from the coupling point.

6. The apparatus according to claim 5, wherein:

the apparatus comprises an implant that comprises the frame assembly and the valve member, and

the apparatus further comprises a tool:

comprising a delivery capsule dimensioned (i) to house and retain the implant in the compressed state, and (ii) to be advanced percutaneously to the heart of the subject while the implant is housed and in the compressed state, and

operable from outside the subject to facilitate an increase of the diameter of the tubular portion from the compressed diameter toward the expanded diameter such that the increase of the diameter actuates longitudinal movement:

of the upstream support portion toward the coupling point, and

of the tissue-engaging flange away from the coupling point.

7. The apparatus according to claim 5, wherein the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes longitudinal movement of the upstream end of the tubular portion toward the coupling point.

8. The apparatus according to claim 5, wherein the coupling point is disposed closer to the downstream end of the frame assembly than are either the tissue-engaging flange or the upstream support portion.

9. The apparatus according to claim 5, wherein:

in the expanded state of the frame assembly, the leg extends away from the central longitudinal axis, and

in the compressed state of the frame assembly, the leg is generally parallel with the central longitudinal axis.

10. The apparatus according to claim 5, wherein the frame assembly is configured such that the longitudinal movement of the tissue-engaging flange away from the coupling point is a

translational movement of the tissue-engaging flange that does not include rotation of the tissue-engaging flange.

11. The apparatus according to claim 5, wherein the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes 1-20 mm of longitudinal movement of the tissue-engaging flange away from the coupling point.

12. The apparatus according to claim 5, wherein the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes 1-20 mm of longitudinal movement of the upstream support portion toward the coupling point.

13. The apparatus according to claim 5, wherein the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state reduces a distance between the upstream support portion and the tissue-engaging flange by 5-30 mm.

14. The apparatus according to claim 5, wherein the frame assembly is configured such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state moves the tissue-engaging flange longitudinally past the upstream support portion.

15. The apparatus according to claim 5, wherein:

the tubular portion is defined by a plurality of cells of the valve frame, and

increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state:

comprises (i) increasing a width, orthogonal to the longitudinal axis of the frame assembly, of each cell, and (ii) reducing a height, parallel with the longitudinal axis of the frame assembly, of each cell, and

causes longitudinal movement of the upstream support portion toward the coupling point by reducing a height, parallel with the longitudinal axis of the frame assembly, of the tubular portion, by reducing the height of each cell.

16. The apparatus according to claim 5, wherein the leg is disposed on an outside of the tubular portion.

17. The apparatus according to any one of claims 5-16, wherein:  
the at least one leg comprises a plurality of legs,  
the coupling point comprises a plurality of coupling points, and  
the frame assembly comprises a leg frame that circumscribes the tubular portion, comprises the plurality of legs, and is coupled to the valve frame at the plurality of coupling points, such that the plurality of legs is distributed circumferentially around the tubular portion.

18. The apparatus according to claim 17, wherein the plurality of coupling points is disposed circumferentially around the frame assembly on a transverse plane that is orthogonal to the longitudinal axis of the frame assembly.

19. The apparatus according to claim 17, wherein the plurality of legs is coupled to the valve frame via a plurality of struts, each strut:

having a first end that is coupled to a leg of the plurality of legs, and a second end that is coupled to a coupling point of the plurality of coupling points,

in the compressed state of the frame assembly, being disposed at a first angle in which the first end is disposed closer to the downstream end of the frame assembly than is the second end, and

being deflectable with respect to the coupling point of the plurality of coupling points, such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes the strut to deflect to a second angle in which the first end is disposed further from the downstream end of the frame assembly than is the first end in the compressed state of the frame assembly.

20. The apparatus according to claim 19, wherein the leg frame is structured such that each leg of the plurality of legs is coupled to two struts of the plurality of struts, and two struts of the plurality of struts are coupled to each coupling point of the plurality of coupling points.

21. The apparatus according to any one of claims 5-16, wherein the leg is coupled to the valve frame via a strut, the strut:

having a first end that is coupled to the leg, and a second end that is coupled to the coupling point,

in the compressed state of the frame assembly, being disposed at a first angle in which the first end is disposed closer to the downstream end of the frame assembly than is the second end, and

being deflectable with respect to the coupling point, such that increasing the diameter of the tubular portion by expanding the frame assembly toward the expanded state causes the strut to deflect to a second angle in which the first end is disposed further from the downstream end of the frame assembly than is the first end in the compressed state of the frame assembly.

22. The apparatus according to claim 21, wherein the at least one leg comprises at least a first leg and a second leg.

23. The apparatus according to claim 22, wherein the first leg and the second leg are both coupled to the valve frame at the coupling point.

24. The apparatus according to claim 22, wherein the first leg is coupled to the coupling point via a respective first strut, and the second leg is coupled to the coupling point via a respective second strut.

25. The apparatus according to claim 24, wherein the first and second legs, the first and second struts, and the coupling point are arranged such that, in the expanded state of the frame assembly:

the coupling point is disposed, circumferentially with respect to the tubular portion, between the first strut and the second strut,

the first strut is disposed, circumferentially with respect to the tubular portion, between the coupling point and the first leg, and

the second strut is disposed, circumferentially with respect to the tubular portion, between the coupling point and the second leg.

26. The apparatus according to claim 21, wherein the coupling point comprises at least a first coupling point and a second coupling point.

27. The apparatus according to claim 26, wherein the leg is coupled to the valve frame at the first coupling point and at the second coupling point.

28. The apparatus according to claim 26, wherein the leg is coupled to the first coupling point via a respective first strut, and to the second coupling point via a respective second strut.

29. The apparatus according to claim 28, wherein the leg, the first and second struts, and the coupling point are arranged such that, in the expanded state of the frame assembly:

the leg is disposed, circumferentially with respect to the tubular portion, between the first strut and the second strut,

the first strut is disposed, circumferentially with respect to the tubular portion, between the leg and the first coupling point, and

the second strut is disposed, circumferentially with respect to the tubular portion, between the leg and the second coupling point.

30. The apparatus according to any one of claims 5-16, wherein in the expanded state of the frame assembly, the upstream support portion extends radially outward from the tubular portion.

31. The apparatus according to claim 30, wherein:

the expanded state of the frame assembly is a fully-expanded state of the frame assembly,

the upstream support portion is expandable into an expanded state of the upstream support portion, independently of increasing the diameter of the tubular portion, and

in the expanded state of the upstream support portion, the upstream support portion extends radially outward from the tubular portion.

32. The apparatus according to claim 30, wherein in the compressed state of the frame assembly, the upstream support portion is generally tubular, collinear with the tubular portion, and disposed around the central longitudinal axis.

33. The apparatus according to claim 30, wherein in the expanded state of the frame assembly, an inner region of the upstream support portion extends radially outward from the tubular portion at a first angle with respect to the tubular portion, and an outer region of the upstream support portion extends, from the inner region of the upstream support portion, further radially outward from the tubular portion at a second angle with respect to the tubular portion, the second angle being smaller than the first angle.

34. Apparatus for use with a native valve of a heart of a subject, the apparatus comprising:  
a frame assembly, having an upstream end and a downstream end, and a central longitudinal axis therebetween, and comprising:

a valve frame, comprising:

a tubular portion having an upstream end and a downstream end, and shaped to define a lumen therebetween, and

an upstream support portion, extending from the upstream end of the tubular portion; and

at least one leg, coupled to the valve frame at a coupling point, and having a tissue-engaging flange; and

a valve member disposed within the lumen, and configured to facilitate one-way liquid flow through the lumen from the upstream end of the tubular portion to the downstream end of the tubular portion,

wherein the frame assembly:

has a compressed state, for percutaneous delivery to the heart, in which the tubular portion has a compressed diameter and in which the at least one tissue-engaging flange has a constrained-flange state,

is biased to assume an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter and in which the at least one tissue-engaging flange has a released-flange state in which the flange extends radially outward from the tubular portion, and

is configured such that in a transition from the expanded state to the compressed state of the frame assembly, reducing the diameter of the tubular portion toward the compressed diameter causes longitudinal movement:

of the upstream support portion away from the coupling point, and  
of the tissue-engaging flange toward the coupling point.

35. Apparatus for use with a native valve of a heart of a subject, the apparatus comprising:

a frame assembly, having an upstream end and a downstream end, and a central longitudinal axis therebetween, comprising:

a valve frame, comprising:

a tubular portion having an upstream end and a downstream end, and shaped to define a lumen therebetween, and

an upstream support portion, extending from the upstream end of the tubular portion; and

at least one leg, coupled to the valve frame at a coupling point, and having a tissue-engaging flange; and

a valve member disposed within the lumen, and configured to facilitate one-way liquid flow through the lumen from the upstream end of the tubular portion to the downstream end of the tubular portion,

wherein the frame assembly:

has a compressed state, for percutaneous delivery to the heart, in which the tubular portion has a compressed diameter and in which the at least one tissue-engaging flange has a constrained-flange state,

is intracorporeally expandable into an expanded state in which a diameter of the tubular portion is greater than in the compressed state and in which the at least one tissue-engaging flange has a released-flange state in which the flange extends radially outward from the tubular portion, and

is configured such that increasing the diameter of the tubular portion by expanding the frame assembly from the compressed state to the expanded state causes longitudinal movement of the tissue-engaging flange away from the coupling point.

36. Apparatus for use with a native valve that is disposed between an atrium and a ventricle of a heart of a subject, the apparatus comprising:

a valve frame, comprising a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the tubular portion defining a plurality of valve-frame coupling elements disposed circumferentially around the longitudinal axis;

a plurality of prosthetic leaflets, coupled to the frame, disposed within the lumen, and arranged to provide unidirectional flow of blood from an upstream end of the lumen to a downstream end of the lumen; and

an outer frame:

comprising a ring defined by a pattern of alternating peaks and troughs, the peaks being longitudinally closer to the upstream end than to the downstream end, and the troughs being longitudinally closer to the downstream end than to the upstream end, and the pattern of the ring having an amplitude longitudinally between the peaks and the troughs,

comprising a plurality of legs, each of the legs coupled to the ring at a respective trough, and having a tissue-engaging flange that protrudes radially away from the axis, and

shaped to define a plurality of outer-frame coupling elements, each of the outer-frame coupling elements (i) coupled to the ring, and (ii) fixed with respect to a respective valve-frame coupling element,

wherein:

the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter, and

the fixation of the outer-frame coupling elements to the valve-frame coupling elements is such that compression of the tubular portion from the expanded state toward the compressed state such that the valve-frame coupling elements pull the outer-frame coupling elements radially inward: (i) reduces a circumferential distance between each of the legs and its adjacent legs, and (ii) increases the amplitude of the pattern of the ring.

37. The apparatus according to claim 36, wherein the ring circumscribes the tubular portion.

38. The apparatus according to claim 36, wherein the valve-frame coupling elements are disposed circumferentially around the longitudinal axis between the upstream end and the downstream end but not at the upstream end nor at the downstream end.

39. The apparatus according to claim 36, wherein the outer frame is coupled to the valve frame only via the fixation of the outer-frame coupling elements to the respective valve-frame coupling elements.

40. The apparatus according to claim 36, further comprising an upstream support portion that comprises a plurality of arms that extend radially from the tubular portion, wherein:

the upstream support portion has (i) a constrained-arm state, and (ii) a released-arm state in which the arms extend radially outward from the tubular portion,

each leg has a tissue-engaging flange that has (i) a constrained-flange state, and (ii) a released-flange state in which the flange extends radially outward from the tubular portion, and

the apparatus has an intermediate state in which (i) the tubular portion is in its compressed state, (ii) the upstream support portion is in its released-arm state, and (iii) the legs are in their released-flange state.

41. The apparatus according to claim 40, wherein the upstream support portion comprises one or more fabric pockets disposed circumferentially, each pocket of the one or more pockets having an opening that faces a downstream direction.

42. The apparatus according to claim 40, wherein:

the apparatus comprises an implant that comprises the valve frame, the leaflets, and the outer frame, and

the apparatus further comprises a tool:

comprising a delivery capsule dimensioned (i) to house and retain the implant in a compressed state of the implant in which (a) the tubular portion is in its compressed state, (b) the upstream support portion is in its constrained-arm state, and (c) the legs are in their

constrained-flange state, and (ii) to be advanced percutaneously to the heart of the subject while the implant is housed and in its compressed state, and

operable from outside the subject to:

transition the implant from its compressed state into the intermediate state while retaining the tubular portion in its compressed state, and

subsequently, expand the tubular portion toward its expanded state.

43. The apparatus according to claim 42, wherein the tool is operable from outside the subject to transition the implant from its compressed state into the intermediate state by (i) releasing the legs into their released-flange state, while retaining the tubular portion in its compressed state, and (ii) subsequently, releasing the upstream support portion into its released-arm state, while retaining the tubular portion in its compressed state.

44. The apparatus according to claim 42, wherein the tool is operable from outside the subject to transition the implant from its compressed state into the intermediate state by (i) releasing the upstream support portion into its released-arm state, while retaining the tubular portion in its compressed state, and (ii) subsequently, releasing the legs into their released-flange state, while retaining the tubular portion in its compressed state.

45. The apparatus according to claim 40, wherein the fixation of the outer-frame coupling elements to the valve-frame coupling elements is such that, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state moves the flanges longitudinally away from the valve-frame coupling elements.

46. The apparatus according to claim 40, wherein the fixation of the outer-frame coupling elements to the valve-frame coupling elements is such that, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state reduces the amplitude of the pattern of the ring and passes the flanges between the arms.

47. The apparatus according to claim 46, wherein the upstream support portion further comprises a covering that covers the arms to form an annular shape in the released-arm state, and

wherein, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state presses the flanges onto the covering.

48. The apparatus according to claim 36, wherein in the compressed state of the tubular portion, a downstream end of each leg is longitudinally closer than the valve-frame coupling elements to the downstream end, and the flange of each leg is disposed longitudinally closer than the valve-frame coupling elements to the upstream end.

49. The apparatus according to claim 48, wherein in the expanded state of the tubular portion, the downstream end of each leg is longitudinally closer than the valve-frame coupling elements to the downstream end, and the flange of each leg is disposed longitudinally closer than the valve-frame coupling elements to the upstream end.

50. Apparatus for use with a native valve that is disposed between an atrium and a ventricle of a heart of a subject, the apparatus comprising:

a valve frame, comprising a tubular portion that circumscribes a longitudinal axis of the valve frame so as to define a lumen along the axis, the tubular portion defining a plurality of valve-frame coupling elements disposed circumferentially around the longitudinal axis;

a plurality of prosthetic leaflets, coupled to the frame, disposed within the lumen, and arranged to provide unidirectional flow of blood from an upstream end of the lumen to a downstream end of the lumen;

an outer frame:

comprising a ring defined by a pattern of alternating peaks and troughs, the peaks being longitudinally closer to the upstream end than to the downstream end, and the troughs being longitudinally closer to the downstream end than to the upstream end, and the pattern of the ring having an amplitude longitudinally between the peaks and the troughs,

comprising a plurality of legs, each of the legs coupled to the ring at a respective trough, and having a tissue-engaging flange that protrudes radially away from the axis, and

shaped to define a plurality of outer-frame coupling elements, each of the outer-frame coupling elements (i) coupled to the ring, and (ii) fixed with respect to a respective valve-frame coupling element; and

an upstream support portion that comprises a plurality of arms that extend radially from the tubular portion,

wherein:

the tubular portion has (i) a compressed state in which the tubular portion has a compressed diameter, and (ii) an expanded state in which the tubular portion has an expanded diameter that is greater than the compressed diameter,

the fixation of the outer-frame coupling elements to the valve-frame coupling elements is such that compression of the tubular portion from the expanded state toward the compressed state such that the valve-frame coupling elements pull the outer-frame coupling elements radially inward: (i) reduces a circumferential distance between each of the outer-frame coupling elements and its adjacent outer-frame coupling elements, and (ii) increases the amplitude of the pattern of the ring,

the upstream support portion has (i) a constrained-arm state, and (ii) a released-arm state in which the arms extend radially outward from the tubular portion,

each leg has a tissue-engaging flange that has (i) a constrained-flange state, and (ii) a released-flange state in which the flange extends radially outward from the tubular portion, and

the apparatus has an intermediate state in which (i) the tubular portion is in its compressed state, (ii) the upstream support portion is in its released-arm state, and (iii) the legs are in their released-flange state.

51. The apparatus according to claim 50, wherein:

the apparatus comprises an implant that comprises the valve frame, the leaflets, and the outer frame, and

the apparatus further comprises a tool:

comprising a delivery capsule dimensioned (i) to house and retain the implant in a compressed state of the implant in which (a) the tubular portion is in its compressed state, (b) the upstream support portion is in its constrained-arm state, and (c) the legs are in their constrained-flange state, and (ii) to be advanced percutaneously to the heart of the subject while the implant is housed and in its compressed state, and

operable from outside the subject to:

transition the implant from its compressed state into the intermediate state while retaining the tubular portion in its compressed state, and subsequently, expand the tubular portion toward its expanded state.

52. The apparatus according to claim 51, wherein the tool is operable from outside the subject to transition the implant from its compressed state into the intermediate state by (i) releasing the legs into their released-flange state, while retaining the tubular portion in its compressed state, and (ii) subsequently, releasing the upstream support portion into its released-arm state, while retaining the tubular portion in its compressed state.

53. The apparatus according to claim 51, wherein the tool is operable from outside the subject to transition the implant from its compressed state into the intermediate state by (i) releasing the upstream support portion into its released-arm state, while retaining the tubular portion in its compressed state, and (ii) subsequently, releasing the legs into their released-flange state, while retaining the tubular portion in its compressed state.

54. The apparatus according to claim 50, wherein the fixation of the outer-frame coupling elements to the valve-frame coupling elements is such that, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state moves the flanges longitudinally away from the valve-frame coupling elements.

55. The apparatus according to claim 50, wherein the fixation of the outer-frame coupling elements to the valve-frame coupling elements is such that, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state reduces the amplitude of the pattern of the ring and passes the flanges between the arms.

56. The apparatus according to claim 55, wherein the upstream support portion further comprises a covering that covers the arms to form an annular shape in the released-arm state, and wherein, when the apparatus is in its intermediate state, expansion of the tubular portion from its compressed state toward its expanded state presses the flanges onto the covering.

1/15

FIG. 1B





FIG. 1A

2/15

FIG. 2A





FIG. 2B




3/15

FIG. 2C


FIG. 2D

FIG. 2E




4/15

FIG. 3A




5/15

FIG. 3B






6/15

Fig. 3C



7/15

**FIG. 4B****FIG. 4A**

8/15

FIG. 4C





FIG. 4D



9/15

FIG. 4F







FIG. 4E




10/15

FIG. 5



11/15

FIG. 6



12/15

FIG. 7A





FIG. 7B



13/15

FIG. 8A






FIG. 8B



14/15



15/15




FIG. 9C

