



(86) Date de dépôt PCT/PCT Filing Date: 2014/09/11
(87) Date publication PCT/PCT Publication Date: 2015/03/19
(85) Entrée phase nationale/National Entry: 2016/03/09
(86) N° demande PCT/PCT Application No.: JP 2014/074754
(87) N° publication PCT/PCT Publication No.: 2015/037744
(30) Priorités/Priorities: 2013/09/12 (JP2013-188917);
2014/09/09 (JP2014-183708)

(51) Cl.Int./Int.Cl. *G03G 21/18* (2006.01),
G03G 15/00 (2006.01), *G03G 21/16* (2006.01)


(71) Demandeur/Applicant:
CANON KABUSHIKI KAISHA, JP

(72) Inventeurs/Inventors:
KAMOSHIDA, SHIGEMI, JP;
ARIMITSU, TAKESHI, JP;
KOISHI, ISAO, JP;
NIKAWA, YUSUKE, JP

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : CARTOUCHE ET MODULE DE TAMBOUR POUR APPAREIL DE FORMATION D'IMAGE
ELECTROPHOTOGRAPHIQUE

(54) Title: CARTRIDGE AND DRUM UNIT FOR ELECTROPHOTOGRAPHIC IMAGE FORMING APPARATUS



AA S10 cross section

(57) Abrégé/Abstract:

This cartridge, which can be installed in a printer, is provided with a coupling guide that comes into contact with a coupling and guides a coupling member. A cartridge case has a hole for exposing a free end of the coupling to the outside of the cartridge, and a



(57) **Abrégé(suite)/Abstract(continued):**

retracting part disposed downstream from the hole in the installation direction of the cartridge. When installing the cartridge in an apparatus body, the coupling guide enters the retracting part into which the coupling member has retracted.

[ABSTRACT]:

A cartridge mountable to a printer, said printer including a coupling guide contactable to a coupling of the cartridge to guide the coupling member. A case of the cartridge is provided with a hole for exposing a free end portion of the coupling to an outside of the cartridge, and a retracted portion provided in downstream of the hole with respect to the mounting direction of the cartridge. When the cartridge is mounted to a main assembly of the printer, the coupling guide enters the retracted portion from which the coupling member has retracted.

DESCRIPTION

[TITLE OF THE INVENTION] CARTRIDGE AND DRUM UNIT FOR
ELECTROPHOTOGRAPHIC IMAGE FORMING APPARATUS

5

[TECHNICAL FIELD]

[0001] The present invention relates to a cartridge and a drum unit usable for an electrophotographic type image forming apparatus such as a laser beam printer.

10

[BACKGROUND ART]

[0002] In the field of the electrophotographic type image forming apparatus, the structure is known in which elements such as a photosensitive drum and a developing roller as rotatable members contributable for image formation are unified as a cartridge which is detachably mountable to a main assembly of the image forming apparatus (main assembly). Here, in order to rotate the photosensitive drum in the cartridge, it is desirable to transmit a driving force thereto from the main assembly. It is known, for this purpose, to transmit the driving force through engagement between a coupling member of the cartridge and a driving force transmitting portion such as a drive pin of the main assembly side of the apparatus.

[0003] In some types of image forming apparatuses, a cartridge is demountable in a predetermined direction substantial perpendicular to a rotational axis of the photosensitive drum. In a known main assembly, the drive pin of the main assembly is moved in the rotational axis direction by an opening and closing operation of a cover of the main assembly. More particularly, a patent specification 1 discloses a structure in which a coupling member provided at an end portion of the photosensitive drum is pivotably relative to the rotational axis

25

of the photosensitive drum. With this structure, the coupling member provided on the cartridge is engaged with the drive pin provided in the main assembly, by which the driving force is capable of being transmitted from the main assembly to the cartridge, as is known.

5

[Prior art reference] Japanese Laid-open Patent Application 2008-233867.

[SUMMARY OF THE INVENTION]

[0004] The present invention provides a further improvement of the above-described prior-art.

10

[0005] According to an aspect of the present invention, there is provided a cartridge mountable to a main assembly of an electrophotographic image forming apparatus, said coupling member comprising a pivotable coupling member, wherein the main assembly including a rotatable engaging portion for engaging with said coupling member, and a coupling guide, positioned downstream of a rotational axis of the engaging portion with respect to a mounting direction of said cartridge, for being contacted by said coupling member pivoted relative to the rotational axis of the engaging portion to guide said coupling member to be parallel with the rotational axis of the engaging portion, said cartridge being mountable to the main assembly in the mounting direction substantially perpendicular to the rotational axis of the engaging portion, said cartridge comprising a frame; a rotatable member for carrying a developer; and a rotatable force receiving member for receiving a rotational force to be transmitted to said rotatable member; said coupling member including a free end portion having a receiving portion for receiving the rotational force from the engaging portion and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion to said force receiving member, said

15

20

25

frame including a hole portion for exposing said free end portion to an outside of said frame, and a receiving portion, provided in a downstream of said hole portion with respect to the mounting direction, for receiving said coupling member when said coupling member is inclined toward a downstream side with respect to the mounting direction and for receiving said coupling guide in place of said coupling member with engagement of said coupling member with the engaging portion.

[0006] According to another aspect of the present invention, there is provided a drum unit dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion rotatably provided in the main assembly, wherein a rotatable coupling member is mountable to said drum unit, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided with a through-hole, wherein said coupling member is mountable to said drum unit by holding opposite end portions of a shaft penetrating the through-hole, said drum unit comprising a cylinder having a photosensitive layer; and a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member, an annular groove portion in said accommodating portion outside with respect to a radial direction of said cylinder, and a holding portion for holding the opposite end portions of the shaft penetrating said through-hole, wherein said groove portion and said holding portion overlap along a rotational axis direction of said cylinder.

[BRIEF DESCRIPTION OF THE DRAWINGS]**[0007]**

Figure 1 is a sectional view of a main assembly of the image forming apparatus and a cartridge, according to an embodiment of the present invention.

5 Figure 2 is a sectional view of the cartridge according to the embodiment of the present invention.

Figure 3 is an exploded perspective view of the cartridge according to the embodiment.

10 Figure 4 is an illustration of behavior in the mounting and demounting of the cartridge relative to the main assembly, according to the embodiment of the present invention.

Figure 5 is an illustrations of behavior in the mounting and demounting of the cartridge relative to the main assembly with a pivoting action of the coupling member, according to the embodiment of the present invention.

15 Figure 6 is an illustration of the coupling member according to the embodiment.

Figure 7 is an illustration of a clearance space of the coupling member according to this embodiment.

20 Figure 8 is an illustration of a drum unit according to the embodiment of the present invention.

Figure 9 is an illustration of behavior in assembling of the drum unit into a cleaning unit.

Figure 10 is there exploded view of the driving side flange unit according to the embodiment of the present invention.

25 Figure 11 is a perspective view and a sectional view of a driving side flange unit according to the embodiment.

Figure 12 is an illustration of an assembling method of the driving

side flange unit, according to the embodiment.

Figure 13 is an illustration of a bearing member, according to the embodiment.

5 Figure 14 is an illustration of a bearing member, according to the embodiment.

Figure 15 is an illustration of a behavior of the pivoting of the coupling member relative to an axis L1, in this embodiment.

Figure 16 is a perspective view of a driving portion of a main assembly according to the embodiment of the present invention.

10 Figure 17 is an exploded view of the driving portion of the main assembly according to the embodiment of the present invention.

Figure 18 is an illustration of a driving portion of the main assembly according to the embodiment of the present invention.

15 Figure 19 is an illustration illustrating the state in the process of mounting the cartridge to the main assembly according to the embodiment of the present invention.

Figure 20 is an illustration illustrating the state in the process of mounting the cartridge to the main assembly according to the embodiment of the present invention.

20 Figure 21 is an illustration illustrating the state in which the mounting of the cartridge to the main assembly of the apparatus has completed, in the embodiment of the present invention.

Figure 22 is an illustration of a coupling guide in the embodiment of the present invention.

25 Figure 23 is an illustration of dismounting of the cartridge from the main assembly in the embodiment of the present invention.

Figure 24 is an illustration of dismounting of the cartridge from the

main assembly in the embodiment of the present invention.

Figure 25 is an illustration illustrating the state in the process of mounting the cartridge to the main assembly according to the embodiment of the present invention.

5 Figure 26 illustrates the coupling member and an engaging portion of a main assembly side in the embodiment of the present invention.

Figure 27 is an illustration of release operations between the coupling member and the main assembly side engaging portion when the cartridge according to the embodiment of the present invention is mounted to and
10 dismounted from the main assembly.

Figure 28 is an illustration of a coupling guide according to the embodiment of the present invention.

Figure 29 illustrates a coupling member and a drive pin in the embodiment of the present invention.

15 Figure 30 is an illustration of the cartridge and the coupling guide in the embodiment of the present invention.

Figure 31 is an illustration of a bearing member, according to an embodiment.

20 Figure 32 is an illustration of a bearing member, according to an embodiment.

Figure 33 is an illustration of a bearing member, according to an embodiment.

[EMBODIMENTS FORCARRYING OUT THE INVENTION]

25 [0008] Referring to the accompanying drawings, the embodiments of the present invention will be described.

[0009] Here, an electrophotographic image forming apparatus is an image

forming apparatus using an electrophotographic type process. In the electrophotographic type process, an electrostatic image formed on a photosensitive member is developed toner. The developing system may be a one-component developing system, two-component developing system, dry type development or another system. An electrophotographic photosensitive drum comprises a drum configuration cylinder and a photosensitive layer thereon, usable with an electrophotographic type image forming apparatus.

5 [0010] A process means includes a charging roller, a developing roller and so on, which are actable on the photosensitive drum, for image formation. A process cartridge these cartridge including the photosensitive member or process means (cleaning blade, developing roller or the like) relating to the image formation. In the embodiment, a process cartridge comprises the photosensitive drum, the charging roller, the developing roller and the cleaning blade as a unit.

10 [0011] More particularly, it is a laser beam printer of the electrophotographic type widely usable as a multifunction machine, a facsimile machine, a printer or the like. Reference numeral or characters in the following descriptions are for referring to the drawings and do not limit the structure of the present invention. The dimensions or the like in the following descriptions are to clarify the relationships and do not limit the structure of the present invention.

15 [0012] A longitudinal direction of the process cartridge in the following description is a direction substantially perpendicular to a direction in which the process cartridge is mounted to the main assembly of the electrophotographic image forming apparatus. A longitudinal direction of the process cartridge is a direction parallel with a rotational axis of the electrophotographic photosensitive drum (direction crossing with a sheet feeding direction). A side of the process cartridge in the longitudinal direction thereof where the photosensitive drum receive a rotational force from the main assembly of the image forming apparatus

20

25

is a driving side (driven side), and the opposite side is a non-driving side. In the following description, an upper part (upper side) is on the basis of the direction of gravity in the state that the image forming apparatus is installed, unless otherwise be described, and the opposite side is a lower part (lower side).

5

<Embodiment 1>

[0013] In the following, the laser beam printer according to this embodiment will be described in conjunction with the accompanying drawings. The cartridge in this embodiment comprises a photosensitive drum as a photosensitive member (image bearing member, rotatable member), and process means including a developing roller, a charging roller and a cleaning blade as a unit (process cartridge). The cartridge is detachably mountable to the main assembly. The cartridge is provided therein with a rotatable member (gear, photosensitive drum, flange, developing roller) which is rotatable by a rotational force from the main assembly. Ad among them, a member for carrying and feeding a toner image is called carrying member.

10

15

20

25

30

35

40

45

50

55

60

65

70

75

80

85

90

95

100

105

110

115

120

125

130

135

140

145

150

155

160

165

170

175

180

185

190

195

200

205

210

215

220

225

230

235

240

245

250

255

260

265

270

275

280

285

290

295

300

305

310

315

320

325

330

335

340

345

350

355

360

365

370

375

380

385

390

395

400

405

410

415

420

425

430

435

440

445

450

455

460

465

470

475

480

485

490

495

500

505

510

515

520

525

530

535

540

545

550

555

560

565

570

575

580

585

590

595

600

605

610

615

620

625

630

635

640

645

650

655

660

665

670

675

680

685

690

695

700

705

710

715

720

725

730

735

740

745

750

755

760

765

770

775

780

785

790

795

800

805

810

815

820

825

830

835

840

845

850

855

860

865

870

875

880

885

890

895

900

905

910

915

920

925

930

935

940

945

950

955

960

965

970

975

980

985

990

995

1000

1005

1010

1015

1020

1025

1030

1035

1040

1045

1050

1055

1060

1065

1070

1075

1080

1085

1090

1095

1100

1105

1110

1115

1120

1125

1130

1135

1140

1145

1150

1155

1160

1165

1170

1175

1180

1185

1190

1195

1200

1205

1210

1215

1220

1225

1230

1235

1240

1245

1250

1255

1260

1265

1270

1275

1280

1285

1290

1295

1300

1305

1310

1315

1320

1325

1330

1335

1340

1345

1350

1355

1360

1365

1370

1375

1380

1385

1390

1395

1400

1405

1410

1415

1420

1425

1430

1435

1440

1445

1450

1455

1460

1465

1470

1475

1480

1485

1490

1495

1500

1505

1510

1515

1520

1525

1530

1535

1540

1545

1550

1555

1560

1565

1570

1575

1580

1585

1590

1595

1600

1605

1610

1615

1620

1625

1630

1635

1640

1645

1650

1655

1660

1665

1670

1675

1680

1685

1690

1695

1700

1705

1710

1715

1720

1725

1730

1735

1740

1745

1750

1755

1760

1765

1770

1775

1780

1785

1790

1795

1800

1805

1810

1815

1820

1825

1830

1835

1840

1845

1

process cartridge B.

[0017] Referring to Figure 1, the structure of the laser beam printer is an electrophotographic image forming apparatus will be described.

[0018] The electrophotographic image forming apparatus shown in Figure 1 is a laser beam printer which uses electrophotographic technique and relative to a main assembly of which the process cartridge B is mountable and dismountable. When the process cartridge B is mounted to the apparatus main assembly A, the process cartridge B is disposed below a laser scanner unit 3 as exposure means (exposure device), with respect to the direction of gravity.

[0019] Below the process cartridge B, a sheet tray 4 accommodating sheets P (recording materials) on which images are formed by the image forming apparatus.

[0020] Furthermore, the apparatus main assembly A comprises a pick-up roller 5a, a feeding roller pair 5b, a feeding roller pair 5c, a transfer guide 6, a transfer roller 7, a feeding guide 8, a fixing device 9, a discharging roller pair 10 and a discharging tray 11, arranged in the order named from an upstream side along a sheet feeding direction X1. The fixing device 9 as fixing means comprises a heating roller 9a and a pressing roller 9b.

[0021] Referring to Figures 1 and 2, the image forming process will be described.

[0022] In response to a print starting signal, a rotatable photosensitive drum 62 (drum 62) is rotated at a predetermined peripheral speed (process speed) in an arrow R.

[0023] A charging roller 66 supplied with a bias voltage is contacted to an outer peripheral surface of the drum 62 to electrically charge the outer peripheral surface of the drum 62 uniformly.

[0024] The laser scanner unit 3 as exposure means outputs a laser beam L

modulated in accordance with image information inputted to the laser beam printer. The laser beam L passes through an exposure window 74 provided in an upper surface of the process cartridge B and scanningly impinges on the outer peripheral surface of the drum 62. By this, a part on the charged photosensitive member is electrically discharged so that an electrostatic image (electrostatic latent image) is formed in the surface of the photosensitive drum.

5 [0025] On the other hand, as shown in Figure 2, in a developing unit 20 as a developing device, a developer (toner T) in a toner chamber 29 is stirred and fed by a rotation of a feeding screw 43 as a feeding member into a toner supply chamber 28.

[0026] The toner T as the developer is carried on a surface of a developing roller 32 as developing means (process means, rotatable member) by a magnetic force of a magnet roller 34 (fixed magnet). The developing roller 32 functions as a rotatable member for carrying and feeding the developer into a developing zone to develop an electrostatic image formed on the photosensitive member.

15 The toner T which is to be fed into the developing zone is regulated in a layer thickness on the peripheral surface of the developing roller 3, by a developing blade 42. The toner T is triboelectrically charged between the developing roller 32 and the developing blade 42.

20 [0027] The electrostatic image formed on the drum 62 is developed (visualized) by the toner T for carried on the surface of the developing roller. The drum 66 rotates in the direction of an arrow R, carrying a toner image provided by the development,

[0028] As shown in Figure 1, in timed relation with the output of the laser beam, the sheet P is fed out of the sheet tray 4 disposed in the lower portion of the apparatus main assembly A, the pick-up roller 5a, the feeding roller pair 5b and the feeding roller pair 5c.

25

[0029] The sheet P is supplied into a transfer position (transfer nip) which is between the drum 62 and the transfer roller 7, along the transfer guide 6. In the transfer position, the toner image is sequentially transferred from the drum 62 as the image bearing member onto the sheet P as the recording material.

5 [0030] The sheet P having the transferred toner image is separated from the drum 62 as the image bearing member and is fed to the fixing device 9 along the feeding guide 8. The sheet P passes through a fixing nip formed between the heating roller 9a and the pressing roller 9b in the fixing device 9. In the fixing nip, the unfixed toner image on the sheet P is pressed and heated so that it is fixed
10 on the sheet P. Thereafter, the sheet P having the fixed toner image is fed by the discharging roller pair 10 and is discharged onto the discharging tray 11.

[0031] On the other hand, as shown in Figure 2, on the surface of the drum 62 after the toner T is transferred onto the sheet, untransferred toner which has now been transferred onto the sheet remains on the drum surface. The untransferred
15 toner is removed by a cleaning blade 77 contacting to the peripheral surface of the drum 62. By this, the toner remaining on the drum 62 is removed, and the cleaned drum 62 is charged again to be used for the next image forming process. The toner (untransferred toner) removed from the drum 62 is stored in a residual toner chamber 71b of a cleaning unit 60.

20 [0032] In this case, the charging roller 66, the developing roller 32 and the cleaning blade 77 function as process means acting on the drum 62. In the image forming apparatus of this embodiment, the untransferred toner is removed by the cleaning blade, but the present invention is applicable to a type (cleanerless type) In which the untransferred toner is adjusted in the electric
25 charge and then collected simultaneously with the development by the developing device. In the cleanerless type, an assistance charging member (auxiliary charging brush or the like) for adjusting the electric charge of the untransferred

toner also functions as the process means.

2. Structure of process cartridge

[0033] Referring to Figures 2 and 3, the structure of the process cartridge B will
5 be described in detail.

[0034] Figure 3 is an exploded perspective view of the process cartridge B as
the cartridge. A frame of the process cartridge can be disassembled into a
plurality of units. In this embodiment, the process cartridge B comprises two
units, namely the cleaning unit 60 and the developing unit 20. In this
10 embodiment, the cleaning unit 60 including the drum 62 is connected with the
developing unit 20 by two connection pins 75, but the present invention is not
limited to such a case, and for example, three unit structure may be employed.
The present invention is also applicable to such a case in which the units are not
connected with coupling members such as pins, but a part of the units is
15 exchangeable.

[0035] The cleaning unit 60 comprises a cleaning frame 71, the drum 62, the
charging roller 66, the cleaning blade 77 and so on. A driving side end portion
of the drum (cylinder) 62 as the rotatable member is provided with a coupling
member 86 (coupling) as a driving force transmitting part. To the drum 62 as
20 the rotatable member, a driving force is transmitted from the main assembly
through the coupling member 86 (coupling). In other words, the coupling
member 86 (coupling) as a drive transmission part is provided at the end portion
(driven side end portion) where the drum 62 is driven by the apparatus main
assembly A.

25 [0036] As shown in Figure 3, the drum 62 (photosensitive drum) as the
rotatable member is rotatable about a rotational axis L1 (axis L1) as the drum axis
(rotational axis of the drum 62). The coupling member 86 as the driving force

transmission member is rotatable about a rotational axis L2 (axis L2) as the coupling axis (rotational axis of the coupling). The coupling member 86 as the drive transmission member (driving force transmitting part) is inclinable (pivotable) relative to the drum 62. In other words, the axis L2 is inclinable
5 relative to the axis L1, as will be described in detail hereinafter.

[0037] On the other hand, the developing unit 20 comprises a toner accommodating container 21, a closing member 22, a developing container 23, a first side member 26L (driving side), a second side member 26R (non-driving side), a developing blade 42, a developing roller 32 and a magnet roller 34. The
10 toner container 21 contains toner T as the developer in this provided with a feeding screw 43 (stirring sheet) as a feeding member for feeding the toner. The developing unit 20 is provided with a spring (coil spring 46 in this embodiment) as an urging member for applying an urging force to regulate an attitude of the developing unit 20 and the cleaning unit 60 relative to each other. Furthermore,
15 the cleaning unit 60 and the developing unit 20 are rotatably connected with each other by connection pins 75 (connection pins, pins) as connecting members to constitute the process cartridge B.

[0038] More specifically, arm portions 23aL, 23aR provided opposite end portions of the developing container 23 with respect to the longitudinal direction
20 of the developing unit 20 (axial direction of the developing roller 32) is provided at free end portions rotation holes 23bL and 23bR. The rotation holes 23bL, 23bR are in parallel with the axis of the developing roller 32.

[0039] Longitudinal opposite end portions of the cleaning frame 71 which is a frame (casing) of the cleaning unit are provided with respective holes 71a for
25 receiving the connection pins 75. The arm portions 23aL and 23aR are aligned with a predetermined position of the cleaning frame 71, and the connection pins 75 are inserted through the rotation holes 23bL and 23bR and the holes 71a. By

this, the cleaning unit 60 and the developing unit 20 are connected with each other rotatably about the connection pins 75 as the connecting members.

[0040] At this time, the coil spring 46 as the urging member mounted to the base portion of each of the arm portions 23aL and 23aR abuts to the cleaning
5 frame 71, so that the developing unit 20 is urged to the cleaning unit 60 about the connection pin 75.

[0041] By this, the developing roller 32 as the process means is assuredly urged toward the drum 62 as the rotatable member. Opposite end portions of the developing roller 32 are provided with respective ring configuration spacers
10 (unshown) as gap holding members, by which the developing roller 32 is spaced from the drum 62 by a predetermined gap.

3. Mounting and dismounting of process cartridge

[0042] Referring to Figures 4 and 5, the description will be made as to the
15 operation of mounting and dismounting of the process cartridge B relative to the apparatus main assembly A.

[0043] Figure 4 is an illustration of mounting and demounting of the process cartridge B relative to the apparatus main assembly A. Part (a) of Figure 4 is a perspective view as seen from the non-driving side, and part (b) is a perspective
20 view as seen from the driving side. The driving side is a longitudinal end portion where the coupling member 86 of the process cartridge B is provided.

[0044] The apparatus main assembly A is provided with a rotatably door 13. Figure 4 shows the main assembly in a state that the door 13 is open.

[0045] Inside the apparatus main assembly A is provided with a drive head 14
25 as a main assembly side engaging portion and a guiding member 12 as a guiding mechanism. The drive head 14 is a drive transmission mechanism of the main assembly side for transmitting the driving force to the cartridge mounted thereto

through engagement with the coupling member 86 of the cartridge. By the rotation of the drive head 14 after the engagement, the rotational force can be transmitted to the cartridge. The drive head 14 can be deemed as a main assembly side coupling in the sense that it is engaged with the coupling of the process cartridge B to transmit the driving force. The drive head 14 as the main assembly side engaging portion is rotatably supported by the apparatus main assembly A. The drive head 14 includes a drive shaft 14a as a shaft portion, a drive pins 14b as an applying portions for applying the rotational force ((b3) of Figure 5). In this embodiment, it is in the form of a drive pin, another structure can be employed, for example, a projection (projection) or projections projecting from the drive shaft 14a outwardly in a radial direction, and the driving force is transmitted from the surface of the projection to the cartridge. As a further alternative, a drive pin 14a may be press-fitted into the hole provided in the drive shaft 14a, and then is welded. In (b1) to (b4) of Figure 5, hatched portions indicate cut surfaces. The same applies to the subsequent drawings.

[0046] The guiding member 12 is a main assembly side guiding member for guiding the process cartridge B in the apparatus main assembly A. The guiding member 12 may be a plate-like member provided with a guiding groove or a member for guiding the process cartridge B at the lower surface of the process cartridge B while supporting it.

[0047] Referring to Figure 5, the description will be made as to the process of mounting and dismounting of the process cartridge B relative to the apparatus main assembly A, while the coupling member 86 while the driving force transmitting part is inclining (pivoting, swing, whirling).

[0048] Figure 5 is an illustration of the mounting and dismounting of the process cartridge B relative to the main assembly A while the driving force transmitting part is inclining (pivoting, swing, whirling). Parts (a1) to (a4) of

Figure 5 are enlarged views of the coupling member 86 and the parts therearound as seen from the driving side toward the non-driving side. Parts (b1) of Figure 5 is a sectional view (S1 sectional view) taken along a line S1 - S1 of (a1) of Figure 5. Similarly, (b2), (b3) and (b4) of Figure 5 are sectional views (S1 sectional
5 views) taken along lines S1 - S1 of (a2), (a3) and (a4) of Figure 5.

[0049] The process cartridge B is mounted to the apparatus main assembly A in the process from (a1) to (a4) of Figure 5, and the (a4) of Figure 5 shows the state in which the mounting of the process cartridge B to the apparatus main assembly A is completed. In Figure 5, the guiding member 12 and the drive head 14 as
10 the parts of the apparatus main assembly A are shown, and the other members are parts of the process cartridge B.

[0050] An arrow X2 and an arrow X3 in Figure 5 are substantially perpendicular to a rotational axis L3 of the drive head 14. The direction indicated by the arrow X2 will be called X2 direction, and the direction indicated by the arrow X3 will be called X3 direction. Similarly, the X2 direction and the
15 X3 direction are substantially perpendicular to the axis L1 of the drum 62 of the process cartridge. In Figure 5, the direction indicated by the arrow X2 is a direction in which the process cartridge B is mounted to the apparatus main assembly A (downstream with respect to the cartridge mounting direction). In
20 the direction indicated by the arrow X3 is a direction in which the process cartridge B is dismounted from the main assembly (upstream with respect to the cartridge mounting direction). A mounting and dismounting direction contains the directions indicated by the arrow X2 and the arrow X3. The mounting and the dismounting are carried out in the respective directions. The directions may
25 be described by the upstream with respect to the mounting direction, the downstream with respect to the mounting direction, the upstream with respect to the dismounting direction or the downstream with respect to the dismounting

direction depending on the convenience of the explanation.

[0051] As shown in Figure 5, the process cartridge B is provided with a spring as an urging member (elastic member). In this embodiment, the spring is a twisting spring 91 (twisted coil spring, kick spring). The torsion coil spring 91
5 urges the coupling member such that a free end portion 86a of the coupling member is inclined toward the drive head 14. In other words, it urges the coupling member 86 such that in the mounting process of the process cartridge B, the free end portion 86a is inclined toward the downstream with respect to the mounting direction perpendicular to the rotational axis of the drive head 14.
10 The process cartridge B advances into the apparatus main assembly A with this attitude (state) of the free end portion 86a of the coupling member 86 inclining toward the drive head 14 (detailed description will be made hereinafter).

[0052] In the rotational axis of drum 62 is the axis L1, the rotational axis of the coupling member 86 is the axis L2, and the rotational axis of the drive head 14
15 functioning main assembly side engaging portion is the axis L3. As shown in (b1) to (b3) of Figure 5, the axis L2 is inclined relative to the axis L1 and the axis L3. The rotational axis of the drive head 14 is substantially coaxial with the rotational axis of the drive shaft 14a. A driving side flange 87 is provided at an end portion of the drum 62 and is rotatable integrally with the drum 62, and
20 therefore, the rotational axis of the driving side flange 87 is coaxial with the rotational axis of the drum 62.

[0053] When the process cartridge B is inserted to an extent shown in (a3) and (b3) of Figure 5, the coupling member 86 contacts to the drive head 14. In the example of (b3) of Figure 5, the drive pin 14b as the rotational force applying
25 portion is contacted by a standing-by portion 86k1 of the coupling member. By the contact, the position (inclination) of the coupling member 86 is regulated, so that the amount of the inclination (pivoting) of the axis L2 relative to the axis L1

(axis L3) gradually decreases.

[0054] In this embodiment, the drive pin 14b as the applying portion is contacted by the standing-by portion 86k1 of the coupling member. However, depending on the phases of the coupling member 86 and the drive head 14 in the rotational moving direction, the portion where the coupling member 86 and the drive head 14 contact to each other is different. Therefore, the contact positions in this embodiment is not limiting to the present invention. It will suffice if a portion of the free end portion 86a of the coupling member (the detailed will be described hereinafter) contacts to a portion of the drive head 14.

10 [0055] When the process cartridge B is inserted to the mounting completion position, the axis L2 is substantially coaxial with the axis L1 (axis L3) as shown in parts (a4) and (b4) of Figure 5. In other words, the rotational axes of the coupling member 86, the drive head 14 and the driving side flange 87 are all substantially coaxial.

15 [0056] By the engagement of the coupling member 86 provided in the process cartridge B with the drive head 14 as the main assembly side engaging portion in this manner, the transmission of the rotational force is enabled from the main assembly to the cartridge. When the process cartridge B is dismounted from the apparatus main assembly A, the process is the reciprocal, that is, from the state of
20 (a4) and (b4) toward the state of (a1) and (b1) in Figure 5. Similarly to the mounting operation, the coupling member 86 inclines relative to the axis L1, so that the coupling member 86 is disengaged from the drive head 14 as the main assembly side engaging portion. That is, the process cartridge B is moved in the X3 direction opposite from the X2 direction substantially perpendicularly to the
25 rotational axis L3 of the drive head 14, and the coupling member 86 disengages from the drive head 14.

[0057] The movement of the process cartridge B in the X2 direction or X3

direction may occur only in the neighborhood of the mounting completion position. In another position other than the mounting completion position, the process cartridge B may move in any direction. In other words, it will suffice if a track of movement of the cartridge immediately before the engagement or
5 disengagement of the coupling member 86 relative to the drive head 14 is the predetermined direction which is substantially perpendicular to the rotational axis L3 of the drive head 14.

4. Coupling member

10 [0058] Referring to Figure 6, the coupling member 86 will be described. As regards the rotational direction, the clockwise direction may be called right-handed rotational direction, and the counterclockwise direction may be called left-handed rotational direction. A rotational moving direction R in Figure 6 is counterclockwise direction when the cartridge is seen from the driving side
15 toward the non-driving side.

[0059] For the purpose of better explanation, an imaginary line will drawn on a planar view, and an imaginary plane will be drawn on a perspective view.

When a plurality of imaginary lines are to be used, first imaginary line, second imaginary line, third imaginary line or the like will be used. Similarly, when a
20 plurality of imaginary planes are to be used, first imaginary plane, second imaginary plane, third imaginary plane or the like will be used. An inside of the cartridge (inward direction of the cartridge) and an outside of the cartridge (outward of direction of the cartridge) are based on the frame of the cartridge, unless otherwise mentioned.

25 [0060] Part (a) of Figure 6 is a side view of the coupling member 86. Part (b) of Figure 6 is a S2 sectional view of the coupling member 86 along a line S2 - S2 of part (a) of Figure 6. Part (b) of Figure 6 shows the coupling with the drive

head 14 as the main assembly side engaging portion without cutting.

[0061] Part (c) of Figure 6 illustrates a state in which the coupling member 86 is engaged with the drive head 14. It is a view of the coupling member 86 and the drive head 14 as seen in the direction indicated by an arrow V1 of part (a) of Figure 6 from the outside of the driving side end portion (end surface) of the cartridge and the drive head 14. Part (d) of Figure 6 is a perspective view of the coupling member 86. Part (e) of Figure 6 illustrates a neighborhood of a free end portion 86a (which will be described hereinafter), as seen in the direction along the receiving portions 86e1 and 86e2 for receiving the rotational force (a direction V2 in part (c) of Figure 6).

[0062] As shown in Figure 6, the coupling member 86 mainly comprises three portions. Briefly, it comprises two end portions and a portion therebetween.

[0063] A first portion is a free end portion 86a engageable with the drive head 14 as the main assembly side engaging portion to receive the rotational force from the drive head 14. The free end portion 86a includes an opening 86m expanding toward the driving side.

[0064] A second portion is a substantially spherical connecting portion 86c (accommodated portion). The connecting portion 86c is pivotably held (connected) by a driving side flange 87 which is a force receiving member. One end portion side of the drum (cylinder end portion) is provided with a driving side flange 87, and the other end portion side is provided with a non-driving side flange 64.

[0065] The first portion can be deemed as including the one end portion side of the coupling member, and the second portion can be deemed as including the other end portion side of the coupling member. The second portion can be deemed as including a rotational center when the coupling member rotates (pivots) in the state that the coupling member is held by the driving side flange 87.

[0066] A third portion is an interconnecting portion 86 g connecting the free end portion 86a and the connecting portion 86c with each other.

[0067] Here, a maximum rotation diameter $\phi Z2$ of the interconnecting portion 86 g is smaller than a maximum rotation diameter $\phi Z3$ of the connecting portion 86c ($\phi Z2 < \phi Z3$), and is smaller than a maximum rotation diameter $\phi Z1$ of the free end portion 86a ($\phi Z2 < \phi Z1$). In other words, a diameter of at least a part of the interconnecting portion 86 g is smaller than a diameter of a maximum diameter portion of the connecting portion. In addition, a diameter of at least a part of the interconnecting portion 86 g is smaller than a diameter of a maximum diameter portion of the free end portion 86a. These diameters are the maximum diameters about the rotational axis of the coupling member, and they are the maximum diameters of imaginary circles of the respective cross-sectional portions of the coupling member on an imaginary flat plane perpendicular to the rotational axis of the coupling member.

[0068] The maximum rotation diameter $\phi Z3$ of the connecting portion 86c is larger than the maximum rotation diameter of the free end portion 86a ($\phi Z3 > \phi Z1$). With such relationships, when the coupling member 86 is inserted into a hole having a diameter not less than $\phi Z1$ and not more than $\phi Z3$ from the free end portion 86a side, the coupling member 86 does not penetrate throughout the hole. For this reason, when and after a unit including the coupling member 86 is assembled up, the coupling member is prevented from the unit in which the coupling member is inserted. In this embodiment, the maximum rotation diameter $\phi Z1$ of the free end portion 86a is larger than the maximum rotation diameter $\phi Z2$ of the interconnecting portion 86 g and is smaller than the maximum rotation diameter $\phi Z3$ of the connecting portion 86c ($\phi Z3 > \phi Z1 > \phi Z2$).

[0069] These maximum rotation diameters $\phi Z1$, $\phi Z2$ and $\phi Z3$ can be measured

as shown in part (a) of Figure 6. More particularly, the diameters of the respective portions of the coupling member are measured in longitudinal sections including the rotational axis of the coupling member, and the maximum measurements of the respective portions are the maximum diameters. The
5 diameters may be based on a three dimensional view shape provided by the rotation of the coupling member about the rotational axis thereof. More particularly, with respect to each of the portions, a point furthest from the rotational axis in the radial direction is determined. A track of the point when the point is revolved about the rotational axis of the coupling member is used as
10 an imaginary circle, and the diameter of the imaginary circle is deemed as the maximum rotation diameter of the portion.

[0070] As shown in part (b) of Figure 6, the opening 86m includes a conical shape receiving surface 86f as an expanding portion expanding toward the drive head 14 in the state that the coupling member 86 is mounted to the apparatus
15 main assembly A. The receiving surface 86f is provided by the member having an outer peripheral surface at the free end portion, and a recess 86z is formed in the free end portion by the receiving surface 86f projecting outwardly. The recess 86z includes an opening 86m (opening) in a side opposite from the drum 62 (cylinder) with respect to the axis L2.

20 [0071] As shown in parts (a) and (c), on a circumference extending about the axis L2 at the extreme end portion of the free end portion 86a, there are provided two claw portions 86d1 and 86d2 at point symmetry positions with respect to the axis L2. Standing-by portions 86k1 and 86k2 are provided circumferentially between claw portions 86d1 and 86d2. In this embodiment, a pair of projections
25 are provided, but only one such a projection may be provided. In such a case, the standing-by portion is that portion between the downstream side of the projection and the upstream side of the projection with respect to the clockwise

direction. The standing-by portions are the spaces required for the drive pins 14b of the drive head 14 provided in the apparatus main assembly A to wait without contacting the claw portions 86d. The spaces are greater than the diameters of the drive pin 14b as the applying portion for applying the rotational
5 force.

[0072] The spaces function as plays when the cartridge is mounted to the apparatus main assembly A. In the radial direction of the coupling member 86, the recess 86z is inside the claw portions 86d1 and 86d2. A width of the claw portion 86d in the diametrical direction is substantially equivalent to a width of
10 the standing-by portion.

[0073] As shown in part (c) of Figure 6, when the transmission of the rotational force from the drive head 14 to the coupling member 86 is awaited, the drive pins 14b for applying the rotational force are in the standing-by portions 86k1 and 86k2, respectively (preparatory position or stand-by position). Furthermore, in
15 part (d) of Figure 6, in upstream sides of the claw portions 86d1 and 86d2 with respect to a rotational direction indicated by a arrow R, there are provided receiving portions 86e1 and 86e2 for receiving a rotational force in a direction crossing with the R direction (part (a) of Figure 6), respectively. The R
direction in the Figure is the direction in which the coupling rotates in the image
20 formation as a result of receiving the driving force from the drive head 14 of the main assembly.

[0074] The drive head 14 for transmitting the drive into process cartridge B and the drive pins 14b constitutes a drive transmission mechanism. A member may have a plurality of functions, depending on the configuration of the drive head.
25 In such a case, a surface of a member actually contacting and transmitting the drive is the member constituting the drive transmission mechanism.

[0075] In the state that the coupling member 86 is engaged with the drive head

14 and the drive head 14 is rotating, the surfaces of the drive pins 14b of the main assembly side contact side surfaces of the receiving portions 86e1 and 86e2 of the coupling member 86. By this, the rotational force is transmitted from the drive head 14 as the main assembly side engaging portion to the coupling member 86 as the drive transmission part.

[0076] In the base portions of the receiving portions 86e1 and 86e2, there are provided undercuts (clearance spaces) 86n1 and 86n2 concaved from the standing-by portions 86k1 and 86k2 toward the connecting portion 86c.

Referring to Figure 7, the undercuts 86n1 and 86n2 will be described in detail.

10 Part (b) of Figure 7 is a S3 section of part (a) of Figure 7.

[0077] Figure 7 shows a state in which the coupling member 86 is inclined along the drive pins 14b for applying the rotational force, from the state in which the drive pins 14b contact the receiving portions 86e1 and 86e2. As shown in Figure 7, the undercuts 86n1 and 86n2 are provided to avoid interference between the standing-by portions 86k1 and 86k2 and the drive pins 14b when the coupling member 86 is inclined in the state that the receiving portions 86e1 and 86e2 and the drive pins 14b are in contact with each other. Therefore, when the entirety of the standing-by portions 86k1 and 86k2 are cut up toward the connecting portion 86c, or when the drive pins 14b are shortened, the undercut may not be provided. However, in this embodiment, the undercuts 86n1 and 86n2 are provided taking into account that if the entirety of the standing-by portions 86k1 and 86k2 are cut toward the connecting portion 86c, the rigidity of the coupling member 86 may lower.

[0078] As shown in part (c) of Figure 6, in order to stabilize the rotational torque transmitted to the coupling member 86, the receiving portions 86e1 and 86e2 are preferably provided at the point symmetry positions with respect to the axis L2. By doing so, a rotational force transmission radius is constant, and

therefore, the rotational torque transmitted to the coupling member 86 is stabilized. In addition, in order to stabilize the position of the coupling member 86 receiving the rotational force, it is preferable that the receiving portions 86e1 and 86e2 are disposed the diametrically opposite positions (180° opposing).

5 Particularly in the case that no flange around the receiving portion and the standing-by portion at the free end portion, as in this embodiment, it is preferable that the number of the receiving portions is two. In the case of an annular flange extending around the outer periphery of the receiving portion, the receiving portions are not exposed when seen from a radially outward position along the
10 rotational axis. Therefore, the receiving portions are relatively easily protected during transportation of the cartridge, irrespective of the attitude of the coupling member. However, with the structure in which the receiving portions is not seen from the outside along the rotational axis of the coupling member by the provision of the flange, the flange tends to interfere with the engaging portion.

15 [0079] As shown in parts (d) and (e) of Figure 6, in order to stabilize the position of the coupling member 86 receiving the rotational force, it is desirable that the receiving portions 86e1 and 86e2 are inclined at a angle θ_3 relative to the axis L2 so that the free end portions approach to the axis L2. This is because, as shown in part (b) of Figure 6, by the rotational torque transmitted to the coupling
20 member 86, the coupling member 86 is attracted toward the drive head 14 as in the main assembly side engaging portion. By this, the conical shape receiving surface 86f contacts the spherical surface portion 14c of the drive head 14, by which the position of the coupling member 86 is further stabilized.

[0080] In this embodiment, the number of the claw portions 86d1 and 86d2 is
25 two, but this number is not restrictive to the present invention and may be different as long as the drive pins 14b can enter the standing-by portions 86k1 and 86k2. However, because of the necessity of the drive pins 14b entering the

standing-by portions, the increase of the number of the claw portions may require reduction of the claw portions per se (width in the circumferential direction in part (c) of Figure 6). In such a case, it is preferable that two (a pair of) projections are provided as in this embodiment.

5 [0081] Furthermore, the receiving portions 86e1 and 86e2 may be provided radially inside the receiving surface 86f. Or, the receiving portions 86e1 and 86e2 may be provided at positions radially outside the receiving surface 86f with respect to the axis L2. However, in this embodiment, the driving force from the drive head 14 is received by the side surfaces of the claw portions 86d1, 86d2
10 projected from the receiving surface 86f in the direction away from the drum 62 along the rotational axis. Therefore, the claw portions 86d1 and 86d2, of the free end portion 86a, for receiving the driving force from the apparatus main assembly are exposed. If an annular flange is provided surrounding the projections (claws), the flange will interfere with a part therearound when the coupling
15 member 86 is inclined, and therefore, the inclinable angle of the coupling member 86 is restricted. In addition, the provision of the annular flange may require that the parts therearound are disposed so as not to interfere, with the result of the upsizing of the cartridge B.

Therefore, the structure not having a portion other than the driving
20 force receiving positions (claw portions 86d1, 86d2 in this embodiment) is contributable to the downsizing of the cartridge B (and main assembly A). On the other hand, without the flange surrounding the projections, the liability that the projections are conducted by the other parts during transportation increases. However, as will be described hereinafter, by
25 urging the coupling member 86 by a spring, the claw portions 86d1 and 86d2 can be accommodating within a most outer configuration portion of the bearing member 76. By this, the possibility of the damage of the claw portions 86d1,

86d2 during the transportation can be reduced.

[0082] In this embodiment, the projection amount Z15 of the claw portions 86d1 and 86d2 from the standing-by portions 86k1 and 86k2 is 4 mm. This amount is preferable in order to assuredly engaging the claw portions 86d1 and 86d2 with the drive pins 14b without interference of the standing-by portions 86k1 and 86k2 with the drive pins 14b, but may be another depending on the part accuracy. However, if the standing-by portions 86k1 and 86k2 are too far from the drive pin 14b, the formation when the drive is transmitted to the coupling member 86 may increase. On the other hand, if the projection amount of the claw portions 86d1 and 86d2 is increased, the cartridge B and/or the apparatus main assembly A may be upsized. Therefore, the projection amount Z15 is preferably in the range not less than 3 mm and not more than 5 mm.

[0083] In this embodiment, a length of the free end portion 86a in the direction of the axis L1 is approx. 6 mm. Therefore, the length of a base portion (portion other than the claw portions 86d1 and 86d2) of the free end portion 86a is approx. 2 mm, and as a result, the length of the claw portions 86d1 and 86d2 in the direction of the axis L1 is longer than the length of the base portion (portion other than the claw portions 86d1 and 86d2).

An inner diameter $\phi Z4$ of the receiving portions 86e1 and 86e2 is larger than the maximum rotation diameter $\phi Z2$ of the interconnecting portion 86g. In this embodiment, $\phi Z4$ is larger than $\phi Z2$ by 2 mm.

[0084] As shown in Figure 6, the connecting portion 86c comprises a substantial spherical shape 86c1 having a pivoting center C substantially on the axis L2, arcuate surface portions 86q1 and 86q2, and a hole portion 86b.

[0085] The maximum rotation diameter $\phi Z3$ of the connecting portion 86c is larger than the maximum rotation diameter $\phi Z1$ of the free end portion 86a. In this embodiment, $\phi Z3$ is larger than $\phi Z1$ by 1 mm. As for the spherical portion,

a substantial diameter may be compared, and if it is partly cut for the convenience of molding, a diameter of an imaginary sphere may be compared. The arcuate surface portions 86q1 and 86q2 are on an arcuate plane provided by extending an arcuate configuration having the same diameter as the interconnecting portion

5 86g. The hole portion 86b is a through-hole extending in the direction perpendicular to the axis L2. The through-hole 86b includes a first inclination-regulated portions 86p1 and 86p2 and transmitting portions 86b1 and 86b2 parallel with the axis L2.

[0086] The first inclination-regulated portions 86p1 and 86p2 have flat surface
10 configurations equidistant from the center C of the spherical 86c1 ($Z9=Z9$). The transmitting portions 86b1 and 86b2 have flat surface configurations equidistant from the center C of the spherical 86c1 ($Z8=Z8$). A diameter of the pin 88 pivotably supporting the coupling member 86 through the hole portion 86b is 2 mm. Therefore, the coupling member 86 is inclinable if Z9 exceeds 1 mm.

15 When Z8 is 1 mm, the pin 88 can pass through the hole portion, and if Z8 exceeds 1 mm, the coupling member 86 is rotatable about the axis L1 by a predetermined amount.

[0087] The end portions, with respect to the direction perpendicular to the axis L2, of the hole portion 86b of the first inclination-regulated portions 86p1, 86p2
20 extend to outer edges of the arcuate surface portions 86q1 and 86q2. The end portions, with respect to the direction perpendicular to axis L2, of the hole portion 86b of the transmitting portions 86b1, 86b2 extend to the outer edge of the spherical 86c1.

[0088] In addition, as shown in Figure 6, interconnecting portion 86 g has a
25 cylindrical shape connecting the free end portion 86a and the connecting portion 86c, and is a columnar (or cylindrical) shaft portion extending substantially along the axis L2.

[0089] The material of the coupling member 86 in this embodiment may be resin material such as polyacetal, polycarbonate, PPS, liquid crystal polymer. The resin material may contain glass fibers, carbon fibers or the like, or metal inserted therein, so as to enhance the rigidity. In addition, the entirety of the coupling member 86 is made of metal or the like. In this embodiment, metal is used which is preferable from the standpoint of downsizing of the coupling. More particularly, it is made of zinc die-cast alloy. A part of the spherical surface of the connecting portion 86c is cut out at the portion close to the interconnecting portion 86 g in the free end side 86a. In addition, the configuration of the coupling member is so designed that the total length including the first to third portions is not more than approx. 21 mm. A length from the pivoting center C to the free end portion engaging with the main assembly drive pin measured in the longitudinal direction is not more than 15 mm. With the decrease of the distance from the center of the pivoting of the coupling member, the distance through which the coupling retracts from the drive pins when the coupling inclines by the same angle decreases. In other words, if the coupling member is shortened for the purpose of downsizing of the cartridge, it is necessary to increase the pivotable angle required to escape from the drive pin. The free end portion 86a, the connecting portion 86c, and the interconnecting portion 86 g may be integrally molded, or may be provided by connecting different parts. In the state that the photosensitive drum, the coupling member and the flange supporting the coupling member is taken out of the cartridge, the coupling member is inclinable in any inclining directions.

25 5. Structure of drum unit

[0090] Referring to Figures 8 and 9, the structure of the photosensitive drum unit U1 (drum unit U1) will be described.

[0091] Figure 8 is an illustration of the drum unit U1, in which part (a) is a perspective view as seen from the driving side, part (b) is a perspective view as seen from the non-driving side, and part (c) is an exploded perspective view. Figure 9 is an illustration of assembling the drum unit U1 with the cleaning unit

5 60.

[0092] As shown in Figure 8, the drum 62, the drum unit U1 comprises a driving side flange unit U2 for receiving the rotational force from the coupling member, the non-driving side flange 64 and a grounding plate 65. The drum 62 as the rotatable member comprises an electroconductive member of aluminum or the like and a surface photosensitive layer thereon. The drum 62 may be hollow or solid.

10

[0093] The driving side flange unit U2 as a force receiving member to which the rotational force is transmitted from the coupling member is provided at the driving side end portion of the drum 62. More particularly, as shown in part (c) of Figure 8, in the driving side flange unit U2, a fixed portion 87b of the driving side flange 87 which is a force receiving member is engaged in an opening 62a1 at the end of the drum 62 and is fixed to the drum 62 by bonding and/or clamping or the like. When the driving side flange 87 rotates, the drum 62 also rotates integrally therewith. The driving side flange 87 is fixed to the drum 62 such that

15

20 a rotational axis as a flange axis of the driving side flange 87 substantially coaxial with the axis L1 of the drum 62.

[0094] Here, the substantial co-axial means the completely co-axial and approximately coaxial in which they are slightly deviated due to the manufacturing tolerances of the parts. The same applies to the following descriptions.

25

[0095] Similarly, the non-driving side flange 64 is provided at the non-driving side end portion of the drum 62 substantially coaxially with the drum 62. In this

embodiment, the non-driving side flange 64 is made of resin material. As shown in part (c) of Figure 8, the non-driving side flange 64 is fixed to the opening 62a2 at the longitudinal end portion of the drum 62 by bonding and/or clamping or the like. The non-driving side flange 64 is provided with an
5 electroconductive grounding plate 65 (main metal). The grounding plate 65 is in contact with the inner surface of the drum 62 and is electrically connected with the apparatus main assembly A.

[0096] As shown in Figure 9, the drum unit U1 is supported by the cleaning unit 60.

10 [0097] In the non-driving side of the drum unit U1, a shaft receiving portion 64a (part (b) of Figure 8) of the non-driving side flange 64 is rotatably supported by the drum shaft 78. The drum shaft 78 is press-fitted into the supporting portion 71b provided in the non-driving side of the cleaning frame 71.

[0098] On the other hand, as shown in Figure 9, in the driving side of the drum
15 unit U1, there is provided a bearing member 76 for contacting and supporting the flange unit U2. A wall surface (plate-like portion) 76h as a base portion (fixed portion) of the bearing member 76 is fixed to the cleaning frame 71 by screws 90. In other words, the bearing member 76 is fixed to the cleaning frame 71 by the screws. The driving side flange 87 is supported by the cleaning frame 71 and
20 the bearing member 76 (the bearing member 76 will be described hereinafter. The supporting member is provided with projections inside and outside of the cartridge, respectively with respect to a reference surface which is a plate-like portion 76h of the bearing member 76. The bearing member 76 which is the supporting member is a part of the frame of the cartridge, and therefore, the
25 projection from the bearing member 76 can be deemed as a frame projection (projection). Similarly, the projection (first projection) for receiving the urging force from the main assembly A and the projection (second projection) for mounting

the spring can be deemed as projections extending from the frame, because the bearing member 76 is mounted to the body of the cartridge frame. In order to assure the strength or in view of shrinkage in the resin material molding, the bearing member 76 and the cartridge frame may be provided with a rib, a groove and/or a lightening recess provided at a position not described.

[0099] In this embodiment, the bearing member 76 is fixed to the cleaning frame 71 by screws 90, but it may be fixed by bonding or by melted resin material. The cleaning frame 71 and the bearing member 76 may be made integral.

6. Driving side flange unit

[0100] Referring to Figures 10, 11 and 12, the structure of the driving side flange unit U2 will be described.

[0101] Figure 10 is an exploded perspective view of the driving side flange unit U2, in which part (a) is a view as seen from the driving side, and part (b) is a view as seen from the non-driving side. Figure 11 is an illustration of the driving side flange unit U2, in which part (a) is a perspective view of the driving side flange unit U2, part (b) is a sectional view taken along S4 - S4 of part (a) of Figure 11, part (c) is a sectional view taken along S5 - S5 of part (a) of Figure 11. Figure 12 is an illustration of an assembling method for the driving side flange unit U2.

[0102] As shown in Figures 10 and 11, the driving side flange unit U2 comprises the coupling member 86, the pin 88 (shaft), the driving side flange 87, a closing member 89 as the regulating member. The coupling member 86 is engageable with the drive head 14 to receive the rotational force. The pin 88 has a substantially circular column configuration (or cylindrical), and extends in the direction substantially perpendicular to the axis L1. The pin 88 receives the

rotational force from the coupling member 86 to transmit the rotational force to the driving side flange 87. The pin 88 as the shaft portion is provided with a rotation regulating portion for limiting rotation of the coupling member in the rotational moving direction by contacting a part of the through-hole in order to transmit the through engagement with the through-hole of the coupling member. It is also provided with a pivoting regulating portion for limiting pivoting of the coupling member by contacting a part of the penetrating shaft in order to limit the pivoting of the pin 88 and the coupling member 86.

[0103] The driving side flange 87 receives the driving force from the pin 88 to transmit the rotational force to the drum 62. The closing member 89 as a regulating member functions to prevent disengagement of the coupling member 86 and the pin 88 for the driving side flange 87. By this, the coupling member 86 is capable of taking various attitudes relative to the driving side flange 87. In other words, the coupling member 86 is held pivotably about a pivoting center, so as to take a first attitude, a second attitude which is different from the first attitude or the like. As for the free end portion of the coupling member, it can take various positions (a position, a second position different from the first position).

[0104] As described in the foregoing, the driving side flange unit U2 comprises a plurality of members, and the driving side flange 87 as a first member and the closing member 89 as a second member are unified into a flange. The driving side flange 87 functions both to receive the drive from the pin 88 and to transmit the drive to the drum 62. On the contrary, the closing member 89 substantially out of contact to the inside of the drum and supports the pin 88 together with the driving side flange 87.

[0105] Referring to Figure 10, the constituent elements will be described.

[0106] As described hereinbefore, the coupling member 86 includes the free

end portion 86a and the connecting portion 86c (accommodated portion). The connecting portion 86c is provided with a through hole portion 86b. The inside (inner wall) of the hole portion 86b has transmitting portions 86b1 and 86b2 for transmitting the rotational force to the pin 88. The inside (inner wall) of the hole portion 86b is also provided with first inclination-regulated portions 86p1 and 86p2 as inclination-regulated portions for being contacted by the pin 88 to limit the inclination amount of the coupling member 86 (also part (b2) of Figure 15). A part of the peripheral surface of the pin 88 as the shaft portion functions as the inclination regulating portion (first inclination regulating portion).

10 The driving side flange 87 includes the fixed portion 87b, a first cylindrical portion 87j, an annular groove portion 87p and a second cylindrical portion 87h. The fixed portion 87b is fixed to the drum 62 to transmit the driving force by contacting to the inner surface of the cylinder of the drum 62. The second cylindrical portion 87h is provided inside the first cylindrical portion 15 87j in the radial direction, and the annular groove portion 87p is provided between the first cylindrical portion 87j and the second cylindrical portion 87h. The first cylindrical portion 87j is provided with a gear portion (helical gear) 87c on the radially outside, and is provided with a supported portion 87d on the radially inside (annular groove portion 87p side). The gear portion 87c is 20 preferably a helical gear from the standpoint of drive transmission property, but a spur gear is usable. The second cylindrical portion 87h of the driving side flange 87 is hollow configuration and has a cavity as an accommodating portion 87i therein. The accommodating portion 87i accommodates the connecting portion 86c of the coupling member 86. In the driving side of the 25 accommodating portion 87i, there is provided a conical portion 87k as the disengagement prevention portion (overhang portion) for limiting disengagement of the coupling member 86 toward the driving side, by contacting to the

connecting portion 86c. More particularly, the conical portion 87k contacts to the outer periphery of the connecting portion 86c of the coupling member 86 to prevented the disengagement of the coupling member. More specifically, the conical portion 87k contacts to the substantially spherical portion of the

5 connecting portion 86c to prevent the disengagement of the coupling member 86. Therefore, the minimum inner diameter of the conical portion 87k is smaller than the inner diameter of the accommodating portion 87i. In other words, the conical portion 87k overhangs from the inner surface of the accommodating portion 87i toward the axis center of the coupling member (hollow portion side)

10 to contact to the peripheral surface of the connecting portion 86c to prevent the disengagement.

[0107] In this embodiment, the conical portion 87k as a center shaft coaxial with the axis L1, but may be a spherical surface or a crossing with the axis L1. The driving side of the conical portion 87k is provided with an opening 87m for

15 projecting the free end portion 86a of the coupling member 86, and the diameter of the opening 87m ($\phi Z10$) is larger than the maximum rotation diameter $\phi Z1$ of the free end portion 86a. In a further driving side of the opening 87m, there is provided a second inclination regulating portion 87n as another inclination regulating portion contacting to the outer periphery of the coupling member 86

20 when the coupling member 86 is inclined (pivoted). More particularly, the second inclination regulating portion 87n contacts to the interconnecting portion 86 g as a second inclination-regulated portion when the coupling member 86 is inclined. A gear portion 87c transmits the rotational force to the developing roller 32. The supported portion 87d is supported by a supporting portion 76a of

25 the bearing member 76 (supporting member) and is provided on the back side of the gear 87c with respect to the thickness direction thereof. They are coaxial with the axis L1 of the drum 62.

[0108] The structure is such that when the coupling member 86 contacts the first inclination regulating portion an inclination angle is smaller than when the coupling member 86 contacts the second inclination regulating portion, as will be described hereinafter.

5 [0109] The accommodating portion 87i inside the second cylindrical portion 87h is provided with a pair of groove portions 87e (recesses) extending in parallel with the axis L1, at 180° away from each other about the axis L1. The groove portion 87e opens toward the fixed portion 87b in the direction of the axis L1 of the driving side flange 87 and continues to the hollow portion 87i in the
10 diametrical direction. The bottom portion of the groove portion 87e is provided with a retaining portion 87f which is a surface perpendicular to the axis L1. The recess 87e is provided with a pair of receiving portions 87g for receiving the rotational force from the pin 88, as will be described hereinafter. (at least a part of) the groove portion 87e and (at least a part of) the annular groove portion 87p
15 overlap with each other in the axis L1 direction (part (b) of Figure 12).

Therefore, the driving side flange 87 can be downsized.

[0110] The closing member 89 as the regulating member is provided with a conical base portion 89a, a hole portion 89c provided in the base portion 89a, and a pair of projected portions 89b at positions approx. 180° away from each other
20 about the axis of the base portion. The projected portion 89b includes a longitudinal direction regulating portion 89b1 at a free end with respect to axis L1 direction.

[0111] In this embodiment, the driving side flange 87 is a molded resin material manufactured by injection molding, and the material thereof is polyacetal,
25 polycarbonate or the like. The driving side flange 87 may be made of metal, depending on the load torque. In this embodiment, the driving side flange 87 is provided with a gear portion 87c for transmitting the rotational force to the

developing roller 32. However, the rotation of the developing roller 32 by be effected not through the driving side flange 87. In such a case, the gear portion 87c may be omitted. The gear portion 87c is provided in the driving side flange 87 as in this embodiment, it is preferable that the gear portion 87c is integrally
5 molded together with the driving side flange 87.

[0112] Referring to Figures 13 and 14, the bearing member 76 will be described in detail. Figure 13 is an illustration showing only the bearing member 76 and parts therearound of the cleaning unit U1. Part (a) of Figure 13 is a perspective view as seen from the driving side. Part (b) of Figure 13 is a sectional view
10 taken along a line S61 - S61 of part (a) of Figure 13, part (c) of Figure 13 and part (d) of Figure 13 are perspective views. Part (e) of Figure 13 is a sectional view taken along a line S62 - S62 of part (a) of Figure 13. Figure 14 is a perspective view of the bearing member 76, part (a) of Figure 14 is a view as seen from the driving side, and part (b) of Figure 14 a view as seen from the non-driving side
15 and also shows the driving side flange 87 for convenience of explanation. Part (c) of Figure 14 is a sectional view taken along S71 plane of part (b) of Figure 14.

[0113] As shown in Figure 14, the bearing member 76 mainly comprises a plate-like portion 76h, a first projected portion 76j projecting from plate-like portion 76h in one direction (driving side), a supporting portion 76a as a second
20 projected portion projecting from the plate-like portion 76h in the other direction (non-driving side). The bearing member 76 further comprises a cut-away portion 76k as a retracted portion (receiving portion). The cut-away portion 76k as the retracted portion (receiving portion) is recessed from a reference surface of the bearing member 76, and in this embodiment, it is a groove portion extending
25 toward the downstream side with respect to the mounting direction. The recess is preferably in the form of a groove from the standpoint of assuring the rigid of the bearing member 76, but the shape is not limited to this example. The recess

from the reference surface is called retracted portion because it permits the coupling member to incline and retract, thus preventing interference between the coupling and the main assembly side drive pin. In other words, the recess from the reference surface is the receiving portion. This is because the inclined coupling member enters the recessed portion. A coupling guide of the main assembly side which will be described hereinafter is capable of entering the recess. It is not necessary that whole of the coupling member and/or the coupling guide enters the recess, but at least a part there of may enter. Therefore, the recess provided in the cartridge frame is a space for permitting retraction of the coupling and is a receiving portion for receiving the coupling member or the like.

[0114] More specifically, it will suffice if the coupling member inclining toward the downstream with respect to the mounting direction cartridge inclines (retracts) more than toward the directions, and the recess may have an expanding shape. The shape of the retracted portion (receiving portion) is not limited to a groove, but it will suffice if it is a recess extending toward the downstream beyond the rotational axis of the flange, with respect to the cartridge mounting direction. The first projected portion 76j is provided in a radially inside portion with a hollow portion 76i for accommodating the coupling member 86, and the hollow portion 76i is spatially connected with the cut-away portion 76k the cut-away portion 76j1 provided in a part of the first projected portion 76j. The cut-away portion 76k as the retracted portion is provided downstream of the hollow portion 76i with respect to the mounting direction (X2) of the process cartridge B. Thus, when the cartridge is mounted to the main assembly, the coupling member 86 is retractable (greatly pivotable) into the cut-away portion 76k as the retracted portion.

[0115] In addition, the cylindrical supporting portion 76a enters the annular

groove portion 87p of the driving side flange 87 to rotatably support the supported portion 87d.

[0116] Moreover, the first projected portion 76j is provided with a cylindrical portion 76d and a spring receiving portion 76e which function as a guided portion
 5 and a first positioned portion when the process cartridge B is mounted to the apparatus main assembly A. At a free end side of the cut-away portion 76k with respect to the mounting direction (X2), a free end portion 76f functioning as a second positioned portion is provided. The cylindrical portion 76d and the free end portion 76f and disposed at the positions different in the direction of the axis
 10 L1 with the plate-like portion 76h and the cut-away portion 76k therebetween, and have concentric arcuate configurations having different diameters.

[0117] In this embodiment, the first cylindrical portion 87j, the annular groove portion 87p, the second cylindrical portion 87h and the groove portion 87e are overlapping in the direction of the axis L1. Therefore, the supporting portion
 15 76a of the bearing member 76 entering the annular groove portion 87p, the pin 88, the 86c1 of the coupling member 86 and the gear portion 87c are overlapping in the direction of the axis L1. As described hereinbefore, the bearing member 76 is provided with the cut-away portion 76k recessed toward the non-driving side beyond the plate-like portion 76h, and when the coupling member 86 is inclined
 20 (pivoted), a part of the coupling member 86 is accommodated in the cut-away portion 76k. With this structure of the parts around the coupling member 86, the inclination (pivoting) amount of the coupling member 86 can be made large assuredly, while reducing the amount of the projection of the bearing member 76 and/or the coupling member 86 toward the driving side as compared with the gear
 25 portion 87c. Here, overlapping means that when parts of an object are projected on an imaginary line, the parts are overlapped. In other words, an imaginary plane (reference plane) is determined, on which the parts are projected, and if the

projected parts are overlapped on the imaginary plane, the parts are overlapped.

[0118] As shown in part (e) of Figure 13, when the coupling member 86 inclines toward the cut-away portion 76k, the most outer configuration of the first projected portion 76j in the direction of the axis L1 is outside of the (claw portions 86d1, 86d2) of the coupling member 86. By this, the risk that the claw portions 86d1 and 86d2 of the coupling member 86 collide against the other part during the transportation can be reduced.

[0119] In this embodiment, the developing roller 32 pushes the drum 62 in the direction indicated by an arrow X7, as described hereinbefore. That is, the drum unit U1 urged toward the cut-away portion 76k. The cut-away portion side supporting portion 76aR of the supporting portion 76a supporting (the driving side flange 87 of) the drum unit U1 is provided with the cut-away portion 76k. The supporting portion 76aL in the opposite side not having the cut-away portion 76k has a higher rigidity than that of the cut-away portion side supporting portion 76aR. Therefore, in this embodiment, the supported portion 87d is provided on the back side of the gear portion 87c with respect to the thickness direction to receive the inner surface of the driving side flange 87. By doing so, the drum unit U1 is substantially supported by the opposite side supporting portion 76aL. That is, the cut-away portion side supporting portion 76aR having a less rigidity receive a smaller load so that the supporting portion 76a is not easily deformed.

[0120] As shown in Figure 13, the torsion coil spring 91 as the urging means (urging member) is provided at a position which is in the disengagement side Of the axis L1 of the driving side flange 87 with respect to the mounting and demounting direction of the coupling member 86 and which is below the axis L1. The torsion coil spring 91 includes a cylindrical coil portion 91c, a first arm 91a extending from the coil portion 91c and a second arm 91b (first end portion, second end portion). By the coil portion 91c being supported (locked) by a

spring hook portion 76g, the spring is mounted to the bearing member 76. The spring hook portion 76 g has a cylindrical portion which is taller than the coil portion 91c to prevent the torsion coil spring 91 from disengaging from the spring hook portion 76g. The spring hook portion 76 g has a portion having a

5 substantially D-like configuration, and the projection penetrates the coil portion 91c, by which the torsion coil spring 91 is mounted to the cartridge. In the state that the torsion coil spring 91 is mounted, diameter of the coil portion 91 is larger than the diameter of the spring hood portion 76g. The spring hook portion 76 g projects from the longitudinal end portion of the cartridge frame toward an

10 outside of the cartridge along the rotational axis direction of the driving side flange.

[0121] The first arm 91a of the torsion coil spring 91 contacts a spring receiving portion 76n of the bearing member 76, and the second arm 91b thereof contacts a connection 86 g or a spring receiving portion 86h of the coupling

15 member 86. By this, the torsion coil spring 91 urges by an urging force F1 such that the free end portion 86a of the coupling member 86 faces cut-away portion 76k side. A width Z11 of the cut-away portion 76k is larger than the diameter $\phi Z1$ of the free end portion 86a of the coupling member 86, and therefore, the free end portion 86a has latitude of movement up and down directions. The coil

20 portion 91c of the torsion coil spring 91 is below the axis L1, and therefore, the free end portion 86a and coupling member 86 is urged downwardly by the urging force F1 and the gravity. By this, the axis L2 of the coupling member 86 inclines toward the cut-away portion 76k relative to the axis L1, and the free end portion 86a inclines to contact to the lower surface 76k1. In this embodiment,

25 the free end portion 86a takes a position below the axis L1 by the urging force F1 of the torsion coil spring 91. As will be described hereinafter in conjunction with Figure 23, the coupling member 86 is inclined so that the free end portion

86a thereof takes the position lower than the axis L1.

[0122] As described above, the free end portion 86a of the coupling member 86 is inclined in the direction of approaching to the drive head 14, by the torsion coil spring 91. Depending on the mounting direction X2, the direction of gravity, the weight of the coupling member 86 or the like, the free end portion 86a of the coupling member 86 is directed in the X2 direction due to the weight of the coupling member. In such a case, the coupling member 86 may be directed toward the desired direction using the gravity without provision of the torsion coil spring 91 as the urging means (urging member). The coupling member 86 of this embodiment is urged by the torsion coil spring 91 to contact to the lower side surface of the cut-away portion 76k in the form of a groove. By this, the coupling member is sandwiched by the torsion coil spring and the lower side surface of the groove so that the attitude of the coupling member is stabilized. By properly arranging the torsion coil spring 91, for example, the coupling member may be contacted to the upper part surface of the cut-away portion 76k in the form of the groove configuration. However, the coupling attitude can be stabilized more in the case of using the gravity than in the case of using the urging force of the spring against the gravity.

[0123] Referring to Figure 11, the description will be made as to the supporting method and connecting method of the constituent parts.

[0124] The position of the pin 88 in the longitudinal direction of the drum 62 (axis L1) is limited by the retaining portion 87f and the longitudinal direction regulating portion 89b1, and the position thereof in the rotational moving direction (R direction) of the drum 62 is limited by the receiving portion 87g. The pin 88 penetrates the hole portion 86b of the coupling member 86. The play between the hole portion 86b and the pin 88 is set so as to permit pivoting of the coupling member 86. With such a structure, the coupling member 86 is capable

of inclining (pivoting, swing, whirling) in any directions relative to the driving side flange 87.

[0125] By the connecting portion 86c of the coupling member 86 contacting to the accommodating portion 87i, the movement of the driving side flange 87 in the radial direction is limited. By the connecting portion 86c contacting to the base portion 89a of the closing member 89, the movement from the driving side toward the non-driving side is limited. Furthermore, by the contact between the spherical 86c1 and the conical portion 87k of the driving side flange 87, the movement of the coupling member 86 from the non-driving side toward the driving side is limited. By the contact between the pin 88 and the transmitting portions 86b1, 86b2, the movement of the coupling member 86 in the rotational moving direction (R direction) is limited. By this, the coupling member 86 is connected with the driving side flange 87 and the pin 88.

[0126] Here, as shown in part (d) of Figure 11, a width Z12 of the hole portion 86b is larger than the diameter ϕ Z13 of the pin 88. By doing so, the coupling member 86 and the pin 88 are connected with each other with a play in the rotational moving direction (R direction) of the drum 62, and therefore, the coupling member 86 can rotate through a predetermined amount about the axis L.

[0127] As described above, the position of the coupling member 86 in the axis L1 direction is limited by the contact to the base portion 89a or conical portion 87k, but because of the tolerances of parts, the coupling member 86 is made movable in the axis L1 direction through a small distance.

[0128] Referring to Figure 12, an assembling method of the driving side flange unit U2 will be described.

[0129] As shown in part (a) Figure 12, the pin 88 is inserted into the through hole portion 86b of the coupling member 86.

[0130] Then, as shown in part (a) of Figure 12, the pin 88 and the coupling

member 86 are inserted into the accommodating portion 87i (along the axis L1) with the phase of the pin 88 matching the pair of groove portions 87e of the driving side flange 87.

[0131] As shown in part (b) of Figure 12, the pair of projected portions 89b of the closing member 89 as the regulating member is inserted into the pair of groove portions 87e, and in this state, the closing member 89 is fixed to the driving side flange 87 by welding or bonding.

[0132] In this embodiment, the diameter $\phi Z1$ of the free end portion 86a of the coupling member 86 is smaller than the diameter $\phi Z10$ of the opening 87m. By this, the coupling member 86, the pin 88 and the closing member 89 can all be assembled into the driving side, and therefore, the assembling is easy. In addition, the diameter $\phi Z3$ of the connecting portion 86c is smaller than the diameter of the opening 87m, by which the spherical surface portion 86c1 and the conical portion 87k can be contacted with each other. By this, the disengagement of the coupling member 86 toward the driving side can be prevented, and the coupling member 86 can be held with high precision. Because of the relationship of $\phi Z1 (< \phi Z10) < \phi Z3$, the driving side flange unit U2 can be easily assembled, and the position of the coupling member 86 can be maintained with high precision.

20

7. Inclining (pivoting) operation of coupling

[0133] Referring to Figure 15, the inclining (pivoting) operation of the coupling member 86 will be described.

[0134] Figure 15 is an illustration of inclination (pivoting) of the coupling member 86 (including the axis L2) relative to the axis L1. Parts (a1) and (a2) of Figure 15 is a perspective view of the process cartridge B in the state in that the coupling member 86 is inclined (pivoted). Part (b1) of Figure 15 is a sectional

25

view taken along a line S7 - S7 of (a1) of Figure 15. Part (b2) of Figure 15 is a sectional view taken along a line S8 - S8 of (a2) of Figure 15.

[0135] Referring to Figure 15, the inclination (pivoting) of the coupling member 86 about the center of the sphere of the connecting portion 86c will be described.

[0136] As shown in (a1) and (b1) of Figure 15, the coupling member 86 is capable of inclining about the axis of the pin 88 about the center of the sphere of the connecting portion 86c relative to the axis L1. More specifically, the coupling member 86 is capable of inclining (pivoting) to such an extent that the second inclination-regulated portion (a part interconnecting portion 86g) contacts to the second inclination regulating portion 87n of the driving side flange 87. Here, the inclination (pivoting) angle relative to the axis L1 is a second inclination angle θ_2 (second inclination amount, second angle). The phase relation between the hole portion 86b and the claw portions 86d1, 86d2 are selected such that any one of the claw portion 86d1 and the claw portion 86d2 takes a leading position with respect to the direction in which the coupling member 86 inclines (arrow X7 direction) when the coupling member 86 inclines about the axis of the pin 88. More particularly, the hole portion 86b and the claw portions 86d1, 86d2 are disposed such that the free end 86d11 of the claw portion 86d1 is not less than 59° and not more than 77° relative to an imaginary line penetrating through the center of the hole portion 86b (θ_6 and θ_7) in part (e) of Figure 11). The angles θ_6 and θ_7 are not limited to the examples, and preferably in the range not less than approx. 55° and not more than approx. 125° . With such a structure, when one of the claw portions 86d1, 86d2 is in a leading position with respect to the inclination of the coupling member 86, the pin 88 takes a large angle position (not less than approx. 55° and not more than approx. 125°) relative to the direction of inclination of the coupling member 86. Then,

the coupling member 86 can incline to the second inclination amount or the amount close thereto, that is, it can incline to a larger amount than the first inclination amount which will be described hereinafter. Thus, the free end 86d11 can be retracted greatly in the axis L1 direction.

5 [0137] As shown in (a2) and (b2) of Figure 15, the coupling member 86 is capable of inclining (pivoting) relative to the axis L1 about the center of the sphere of the connecting portion 86c around the axis perpendicular to the axis of the pin 88 to a extent that the first inclination-regulated portions 86p1 and 86p2 contact to the pin 88. Because of the above-described phase relation between
10 the hole portion 86b (pin 88) and the claw portions 86d1, 86d2, the coupling member 86 inclines (pivots) about an axis perpendicular to the axis of the pin 88. At this time, the claw portions 86d1 and 86d2 are in the positions which are opposed to each other across the direction (arrow X8 direction) of the inclination of the coupling member 86. The inclination (pivoting) angle relative to the axis
15 L1 is a first inclination angle θ_1 (first inclination amount, first angle). In this embodiment, the coupling member 86, the driving side flange 87 and the pin 88 are constructed such that first inclination angle $\theta_1 <$ second inclination angle θ_2 is satisfied, for the reasons which will be described hereinafter with Figure 25.

[0138] By combination of the inclination (pivoting) about the axis of the pin 88
20 and the inclination (pivoting) about the axis perpendicular to the axis of the pin 88, the coupling member 86 is capable of inclining (pivoting) in a direction different from those described above. Because the inclination (pivoting) in any directions are provided by the combination, the inclination (pivoting) angle in any direction is not less than first inclination angle θ_1 and not more than second
25 inclination angle θ_2 . In other words, the coupling is pivotable not less than the first inclination angle θ_1 (first pivoting angle) and the second inclination angle (second pivoting angle)

[0139] In this manner, the coupling member 86 can incline (pivot) relative to the axis L1 substantially all directions. In other words, the coupling member 86 can incline (pivot) relative to the axis L1 in any directions. That is, the coupling member 86 can swing relative to the axis L1 in any directions. Further, the
5 coupling member 86 can whirl relative to the axis L1 in any directions. Here, the whirling of the coupling member 86 is revolving of the inclined (pivoted) axis L2 around the axis L1.

[0140] As described above, the arcuate surface portions 86q1 and 86q2 determine the first inclination angle θ_1 , and the interconnecting portion 86 g has a
10 dimension determining the second inclination angle θ_2 . Therefore, the diameters of the interconnecting portion 86 g and the arcuate surface portions 86q1 and 86q2 may be different from each other, although they are the same in this embodiment.

15 8. Driving portion of the apparatus main assembly

[0141] Referring to Figure 16 toward Figure 18, a structure of the cartridge driving portion of the apparatus main assembly A will be described.

[0142] Figure 16 is a perspective view of the driving portion of the apparatus main assembly A (neighborhood of the drive head 14 of part (a) of Figure 4), as
20 seen from an upstream inside of the apparatus main assembly A with respect to the mounting direction (X2 direction) of the process cartridge B. Figure 17 is an exploded perspective view of the driving portion, part (a) of Figure 18 is a partly enlarged view of the driving portion, and part (b) of Figure 18 is a sectional view taken along a cutting plane S9 - S9 of part (a) of Figure 18.

25 [0143] The cartridge driving portion comprises a drive head 14 as the main assembly side engaging portion, a first side plate 350, a holder 300, a driving gear 355 and so on.

[0144] As shown in part (b) of Figure 18, a driving shaft 14a of the drive head 14 as the main assembly side engaging portion is non-rotatably fixed to the driving gear 355 by a means (unshown). Therefore, when the driving gear 355 rotates, the drive head 14 as the main assembly side engaging portion also rotates.

5 The driving shaft 14a is rotatably supported by a supporting portion 300a of the holder 300 and a bearing 354 at the respective end portions.

[0145] As shown in part (b) of Figures 17 and 18, a motor 352 as the driving source is mounted to a second side plate 351, and the rotation shaft thereof is provided with a pinion gear 353. The pinion gear 353 is engaged with the driving gear 355. Therefore, when the motor 352 rotates, the driving gear 355 rotates, and the drive head 14 as the main assembly side engaging portion also rotates. The second side plate 351 and the holder 300 are fixed to the first side plate 350.

[0146] As shown in Figures 16 and 17, the guiding member 12 as the guiding mechanism includes a first guiding member 12a and a second guiding member 12b for guiding the mounting of the process cartridge B. At a terminal end of the first guiding member 12a with respect to the cartridge mounting direction (X2 direction), a mounting end portion 12c perpendicular to the X2 direction is provided. The guiding member 12 is also fixed to the first side plate 350.

20 [0147] As shown in Figures 17 and 18, the holder 300 is provided with the supporting portion 300a for rotatably supporting the driving shaft 14a of the drive head 14 as the main assembly side engaging portion, and a coupling guide 300b. The coupling guide 300b is positioned downstream of the supporting portion 300a with respect to the mounting direction (X2 direction) of the process cartridge B (rear side of the main assembly), and is provided with an interconnecting portion 300b1 and a guide portion 300b2. Here, the interconnecting portion 300b1 has an arcuate configuration of a diameter $\phi Z5$

25

about the axis L3, in which the diameter $\phi Z5$ is selected so as to be larger than the maximum rotation diameter $\phi Z2$ of the free end portion 86a of the coupling member 86. A free end of the guide portion 300b2 has an arcuate configuration of a diameter $\phi Z6$ about the axis L3. The diameter $\phi Z6$ is determined relative to the interconnecting portion 86 g of the coupling member 86 so as to provide a predetermined gap S therebetween. The predetermined gap S is provided to prevent interference between the interconnecting portion 86 g and the guide portion 300b2 in consideration of tolerances or the like, when the process cartridge B is rotated (which will be described hereinafter with Figure 22).

9. Mounting of process cartridge to apparatus main assembly

[0148] Referring to Figure 19 to Figure 22, mounting of the process cartridge B to the apparatus main assembly A will be described. In Figures 19 and, the parts other than those required for the description of the mounting operation are omitted.

[0149] Part (a) of Figures 19, 20 and 21 is a view of the apparatus main assembly A as seen from outside in the driving side. Part (b) of Figure 21 is a perspective view in the state shown in part (a) of Figure 21. Figure 22 is an illustration of details of the neighborhood of the coupling member 86 at the time when the mounting of the process cartridge B to the apparatus main assembly A is completed. In Figure 22, the apparatus main assembly A is shown as having a drive head 14 as the main assembly side engaging portion, a coupling guide 300b of the holder 300, and the guiding member 12, and the other parts are members of the process cartridge B.

[0150] In (a1) of the Figure 22, the process cartridge B is in the mounting completed position, and the coupling member 86 is inclined (pivoted). In (a2) of Figure 22, the process cartridge B is in the mounting completed position, and

the axis L2 of the coupling member 86 is substantially coaxial with the axis L3 of the drive head 14 as the main assembly side engaging portion. Part (a3) of Figure 22, is an illustration of a relationship between the coupling member 86 and the coupling guide 300b at the time when the coupling member 86 is inclined
5 (pivoted). Parts (b1) to (b3) of Figure 22 are sectional views taken along lines S10 - S10 of (a1) to (a3) of Figure 22, respectively.

[0151] As shown in Figure 19, the guiding member 12 as the apparatus main assembly A guiding mechanism is provided with pulling spring 356 as an urging member (elastic member). The pulling spring 356 is rotatably supported on a
10 rotational shaft 320c of the guiding member 12, and the position thereof is limited by stoppers 12d and 12e. An operating portion 356a of the pulling spring 356 is urged in the direction of an arrow J in Figure 19.

[0152] As shown in Figure 19, when the process cartridge B is mounted to the apparatus main assembly A, it is inserted so that a first arcuate portion 76d of the
15 process cartridge B moves along the first guiding member 12a, and a rotation stopper boss 71c of the process cartridge B moves along the second guiding member 12b. The first arcuate portion 76d of the process cartridge contacts the guide groove of the main assembly side, and at this time, the coupling member 86 is inclined toward the downstream of the mounting direction (X2 direction) by
20 the torsion coil spring 91 as the urging member (elastic member). Here, the coupling member 86 is covered by the first arcuate portion 76d of the bearing member 76. By this, the process cartridge B can be inserted to a neighborhood of the mounting completed position in the state, without interference with any parts of the apparatus main assembly A in the insertion path for the process
25 cartridge B.

[0153] As shown in Figure 20, when the process cartridge B is further inserted in the arrow X2 direction in the Figure, the spring receiving portion 76e of the

process cartridge B is brought into contact to the operating portion 356a of the pulling spring 356. By this, the operating portion 356a elastically deforms in an arrow H direction in the Figure.

[0154] Thereafter, the process cartridge B is mounted to a predetermined
5 position (mounting completed position) (Figure 21). At this time, the first arcuate portion 76d of the process cartridge B contacts the first guiding member 12a of the guiding member 12, and the leading end portion 76f with respect to the mounting direction contacts to the mounting end portion 12c. Similarly, a rotation stopper boss 71c of the process cartridge B contacts to a positioning
10 surface 12h of the guiding member 12 as the guiding mechanism. In this manner, the position of the process cartridge B relative to the apparatus main assembly A is determined.

[0155] At this time, the operating portion 356a of the pulling spring 356 presses the spring receiving portion 76e of the process cartridge B in the arrow J direction
15 in the Figure to assure the contact between the first arcuate portion 76d and the first guiding member 12a and the contact between the leading end portion 76f and the mounting end portion 12c. By this, the process cartridge B is correctly positioned relative to the apparatus main assembly A.

[0156] When the process cartridge B is mounted to the apparatus main
20 assembly A, the coupling member 86 is engaged with the drive head 14 as the main assembly side engaging portion (Figure 5) as described hereinbefore, so that the mounting of the process cartridge B to the main assembly is completed.

[0157] As shown in (a1) and (b1) of Figure 22, even when the mounting of the process cartridge B is completed, the coupling member 86 tends to incline (pivot)
25 in the mounting direction (X2 direction) by the torsion coil spring 91. In other words, even after the completion of the mounting, the torsion coil spring 91 continues to apply the urging force to the coupling member 86 (substantially

toward the downstream with respect to the cartridge mounting direction). At this time, the interconnecting portion 86 g contact the guide portion 300b2 of coupling guide 300b so that the inclination (pivoting) of the coupling member 86 is limited. By limiting the inclination amount of the coupling member 86, the claw portions 86d1 and 86d2 simultaneously contact the drive pin 14b of the drive head 14. More particularly, the claw portions are disposed at substantially point symmetry positions about the rotation axis of the coupling member. When the rotational force is transmitted to the coupling member 86 in this state, the axis L2 of the coupling member 86 is substantially aligned with the axis L3 of the drive head 14 by a couple of forces and the contact between the spherical surface portion 14c and the conical portion 86f, as shown in (a2) and (b2) of Figure 22. And, the above-described gap S is provided between the interconnecting portion 86 g and the guide portion 300b2, so that the coupling member 86 can be rotated stably.

[0158] When the inclination (pivoting) of the coupling member 86 is not limited, one of the claw portions 86d1 and 86d2 constituting the pair may not contact the drive pin 14b. In such a case, the above-described couple of forces is not supplied with the result of incapability of aligning the axis L2 of the coupling member 86 with the axis L3 of the drive head 14.

The coupling guide 300b1 does not interfere with the coupling member 86 in the mounting and demounting process of the process cartridge B even when the coupling member 86 is in a inclined (pivoted) state. To accomplish this, the coupling guide 300b is provided in a non-driving side of the free end portion 86a ((a3) and (b3) of Figure 22). The cut-away portion 76k of the bearing member 76 is further recessed to the non-driving side of the guide portion 300b2 so as to avoid the interference with the guide portion 300b2. In addition, the width Z11 of the cut-away portion 76k of the bearing member 76

measured in the direction perpendicular to the line S10 - S10 is larger than the width Z14 of the coupling guide 300b. By this, the size of the cartridge can be reduced while suppressing interference between the coupling guide and the cartridge.

5 [0159] In this embodiment, the inclination (pivoting) of the coupling member 86 by the torsion coil spring 91 is limited by the coupling guide 300b. However, as described above, the inclination (pivoting) of the coupling member 86 may be effected by another means other than the torsion coil spring 91. For example, when the coupling member 86 inclines by the weight thereof, the coupling guide
10 300b may be disposed at a lower side. As described above, the coupling guide 300b may be provided at a position where the inclination (pivoting) of the coupling member 86 is limited in the mounting of the process cartridge B.

10. Engagement and disengagement of coupling in dismounting operation of
15 process cartridge.

[0160] Referring to Figure 24, the dismounting of the process cartridge B from the apparatus main assembly A from the mounting completed position of the process cartridge B while the coupling member 86 is disengaging from the drive head 14 as the main assembly side engaging portion will be described.

20 [0161] The description will be made as to an example of this embodiment, in which the claw portions 86d1 and 86d2 of the coupling member 86 are in the upstream and downstream positions, respectively, with respect to the dismounting direction, as shown in Figure 24. In this embodiment, in this state, the phase relation between the hole portion 86b penetrated by the pin 88 and the claw
25 portions 86d1 and 86d2 is such that the axis of the pin 88 is substantially perpendicular to the dismounting direction (X3 direction). Part (a1) of Figure 24 shows a state from which the disengagement of the coupling member 86 from

the main assembly A occurs at the time of the dismounting of the process cartridge B from the apparatus main assembly A. Parts (a1) to (a4) of Figure 24 are perspective views as seen from an outside in the driving side, parts (b1) to (b4) of Figure 24 are sectional views taken along lines (a1) to (a4) of Figure 24, respectively. In Figure 24, similar to Figure 22, the apparatus main assembly A is shown as having a drive head 14 as the main assembly side engaging portion, a coupling guide 300b of the holder 300, and the guiding member 320, and the other parts are members of the process cartridge B.

[0162] The process cartridge B is moved in the dismounting direction (X3 direction) from the state shown in parts (a1) and (b1) in which the coupling member 86 is engaged with the drive head 14. Then, as shown in (a2) and (b2) of Figure 24, the (axis L2 of) the coupling member 86 is inclined (pivoted) relative to the axis L1 and in the axis L3, while the process cartridge B move in the dismounting direction (X3 direction). At this time, the amount of the inclination (pivoting) of the coupling member 86 is determined by the contact of the free end portion 86a to the parts of the drive head 14 (the drive shaft 14a, the drive pin 14b, the spherical surface portion 14c and the free end portion 14d).

[0163] When the process cartridge B is further moved in the dismounting direction (X3 direction), the coupling member 86 is disengaged from the drive head 14 as the main assembly side engaging portion, as shown in (a3) and (b3) of Figure 24. The coupling member 86 is urged by the torsion coil spring 91 as the urging means (urging member), by which it is further inclined (pivoted). The inclination angle of the coupling member 86 urged by the torsion coil spring as the urging member is larger than the inclination angle in the direction other than the urged direction.

[0164] By the contact between the second inclination regulating portion 87n and in the interconnecting portion 86 g the inclination (pivoting) of the coupling

member 86 is limited. The maximum rotation diameter $\phi Z2$ of the interconnecting portion 86 g and the second inclination angle $\theta 2$ are determined so that the coupling member 86 can incline (pivot) to such an extent that the upstream claw portion 86d1 with respect to the dismounting direction can be positioned in the non-driving side beyond the free end portion 14d of the drive head 14. By doing so, as shown in (a4) and (b4) of Figure 24, the process cartridge B can be dismounted from the apparatus main assembly A while the coupling member 86 is disengaging from the drive head 14 as the main assembly side engaging portion.

[0165] In the case that the claw portions 86d1 and 86d2 are in the phase other than that described above, the coupling member 86 circumvents the parts of the drive head 14 as the main assembly side engaging portion by the inclination (pivoting) and/or the above-described whirling, or by a combination of these motions. By the circumventing motion, the coupling member 86 can be disengaged from the drive head 14 as the main assembly side engaging portion. As shown in (a1) and (b1) of Figure 23, in the case that the axial direction of the drive pin 14b and the dismounting direction (X3 direction) are substantially perpendicular to each other, the inclination occurs such that the free end portion 86b direct away from the dismounting direction (X2 direction), so that the claw portion 86d1 dodges the drive pin 14b in the non-driving side direction. Or, when the claw portions 86d1 and 86d2 are opposed to each other interposing the dismounting direction (X3 direction) as shown in (a2) and (b2) of Figure 23, the inclination (pivoting) occurs such that the free end portion 86a moves in the direction (X6 direction) parallel with the axial direction of the drive pin 14b. By this, the claw portion 86d1 can dodge the drive pin 14b in the direction indicated by the arrow X6. In such a case, it is necessary that the free end portion 86a is moved to below the axis L3 and the axis L1, and therefore, the position of the

lower surface 76k1 of the bearing member 76 is determined as described above, and the direction of the urging force of the torsion coil spring 91 is determined so that the free end portion 86a is directed downward. Here, the lower, below and downward are not necessarily limited to those on the basis of the direction of gravity. More particularly, it will suffice if the free end portion 86a is movable in the direction necessary for the claw portion 86d1 placed in the downstream side with respect to the mounting direction (upstream side with respect to the dismounting direction) to dodge the drive pin 14b. Therefore, in the case that the rotational moving direction R of the drum 62 is opposite to that of this embodiment, the claw portion placed in the downstream side with respect to the mounting direction is in the upper side, and therefore, the direction in which the free end portion 86a is to move is upward. Therefore, in the case that the claw portions 86d1 and 86d2 are placed in the upper and lower positions across the mounting direction X2 of the coupling member 86, it is preferable that the free end portion 86a is movable toward the claw portion with which the direction of the rotational force received from the drive pin 14b is codirectional with the mounting direction. In the two examples shown in Figure 23, the inclination (pivoting) angle required before the release of the coupling member 86 from the drive head 14 as the main assembly side engaging portion may be smaller than the second inclination angle θ_2 shown in Figure 24. In this embodiment, in the case shown in (a2) and (b2) of Figure 23, the phase relation between the hole portion 86b of the coupling member 86 and the claw portions 86d1 and 86d2 is determined such that the inclination (pivoting) angle is the first inclination angle θ_1 . Part (b1) of Figure 23 is a sectional view taking along a line S11 - S11 of (a1) of Figure 23. Part (b2) of Figure 23 is a sectional view taking along a line S11 - S11 of (a2) of Figure 23.

[0166] Dimensions of the parts in this embodiment will be described.

[0167] As shown in Figure 6, the diameter of the free end portion 86a is $\phi Z1$, the diameter of the interconnecting portion 86 g is $\phi Z2$, the sphere diameter of the substantially spherical connecting portion 86c is $\phi Z3$, and rotation diameters of the claw portions 86d1 and 86d2 are $\phi Z4$. In addition, the diameter of the spherical of the free end of the drive head 14 as the main assembly side engaging portion is $S\phi Z7$, and the length of the drive pin 14b is $Z5$. Furthermore, as shown in (b1) and (b2) of Figure 15, the inclinable (pivotable) amount (second inclination angle) of the coupling member 86 about the axis of the pin 88 is $\theta 2$, and the inclinable (pivotable) amount (first inclination angle) thereof about the axis perpendicular to the axis of the pin 88 is $\theta 1$. The gap between the interconnecting portion 86 g and the guide portion 300b2 at the time when the axis L2 and the axis L3 are substantially coaxial is S.

[0168] In this embodiment, $\phi Z1=10$ mm, $\phi Z2=5$ mm, $\phi Z3=11$ mm, $\phi Z4=7$ mm, $Z5=8.6$ mm, $S\phi Z7=6$ mm, $\theta 1=30^\circ$, $\theta 2=40^\circ$ and $S=0.15$ mm.

[0169] These dimensions are examples and are not restrictive to the present invention, if the similar operations are possible. More specifically, it will suffice if $\theta 1$ and $\theta 2$ are not less than approx. 20° and not more than approx. 60° . Preferably, they are not less than 25° and not more than 45° . Further preferably, $\theta 1 < \theta 2$ is satisfied, and $\theta 1$ is not less than approx. 20° and not more than approx. 35° , and $\theta 2$ is not less than approx. 30° and not more than approx. 60° . The difference between $\theta 1$ and $\theta 2$ is not less than approx. 3° and not more than approx. 20° , and preferably, it is not less than approx. 5° and not more than approx. 15° . It will be considered to design the angles $\theta 1$ and $\theta 2$ such that as shown in Figure 25, when the cartridge B is mounted, the leading portion (which will be described hereinafter) is positioned in the non-driving side beyond the free end portion 14d of the drive head 14 and in the driving side beyond the guide portion 300b2. With such design, the coupling 86 can be properly engaged with

the drive head 14. The free end portion is the leading end portion 86d11 of the claw portion 86d1 when the inclination angle of the coupling member 86 is the second inclination angle θ_2 , and it is the standing-by portion 86k1 wherein the inclination angle of the coupling member 86 is the first inclination angle θ_1 .

5 Because the standing-by portion 86k1 is closer to the rotation axis C than the leading end portion 86d11, and therefore, if first inclination angle $\theta_1 <$ second inclination angle θ_2 is satisfied, the position of the leading end portion in the axis L1 direction when the coupling member 86 is inclined can be made the similar. By this, it is unnecessary to widen the gap between the drive head 14 and the
10 guide portion 300b2, so that the apparatus main assembly A and/or the cartridge B can be downsized.

[0170] By satisfying $\phi Z1 < \phi Z3$, the assembling is easy as in this embodiment. Furthermore, by satisfying $\phi Z1 < \phi Z10 < \phi Z3$ taking into account the minimum diameter $\phi Z10$ of the conical portion 87k as the disengagement prevention
15 portion (overhang portion, disengagement preventing portion), the position of the coupling member 86 in the driving side flange unit U2 can be determined with high precision.

[0171] According to this embodiment, the conventional cartridge which can be dismounted to the outside of the main assembly after being moved in the
20 predetermined direction substantially perpendicular to the rotational axis of the main assembly side engaging portion can be further improved.

<Embodiment 2>

[0172] This embodiment will be described in conjunction with the
25 accompanying drawings. In this embodiment, the structures of the parts other than a free end portion 286a of a coupling member 286, a drive head 214 and a coupling guide 400b are similar to those of the first embodiment, and therefore,

the description of such other parts is omitted by assigning the same reference numerals as in the first embodiment. Even if the same reference numerals are assigned, the parts may be partly modified so as to match the structure of this embodiment.

5 [0173] Figure 26 is an illustration of the coupling member 286 and the drive head 214 as the main assembly side engaging portion. Part (a) of Figure 26 is a side view, part (b) of Figure 26 is a perspective view, part (c) of Figure 26 is a sectional view taken along a line S21 - S21 of part (a) of Figure 26. Part (d) of Figure 26 is a sectional view taken along a line S22 - S22 of part (a) of Figure 26,
10 the line S22 - S22 being perpendicular to a receiving portion 286e1 and passing through the center of a drive pin 214b as the applying portion.

[0174] As shown in Figure 26, the configurations of the claw portions 286d1 and 286d2 of the coupling member 286 is different from those of the first embodiment. The claw portions 286d1, 286d2 have respective flat internal wall
15 surfaces 286s1, 286s2 facing toward the axis L2, and a widths Z21 of the receiving portions 286e1, 286e2 in the diametrical direction is larger than those of Embodiment 1. More particularly, as compared with Embodiment 1, the widths of the claw portions 286d1, 286d2 in the diametrical direction are larger. A diameter $\phi Z22$ of an inscribed circle of the internal wall surfaces 286s1, 286s2
20 about the axis L2 is larger than the diameter $\phi Z7$ of the driving shaft 214a of the drive head 214. Here, an amount of overlapping between the drive pins 214b1, 214b2 and the receiving portions 286e1, 286e2 in part (d) of Figure 26 in the axial direction of the drive pins 214b1, 214b2 (direction perpendicular to the axis L2 (L3)) is called engagement amount Z23.

25 [0175] On the other hand, the drive head 214 is provided at a base portion of the drive pin 214b with a receiving spherical surface portion 214c and a recess 214e recessed from the drive shaft 214a in a downstream side of the drive pin

214b with respect to the rotational moving direction (R direction).

[0176] Referring to Figure 27, engaging and disengaging operations between the coupling member 286 and the drive head 214 when the process cartridge B is mounted to and dismounted from the apparatus main assembly A will be described in detail. The operation peculiar to this embodiment will be described. This is when the phase of the drive pins 214b1 and 214b2 is deviated from the dismounting direction (X3 direction) of the cartridge B by a predetermined amount θ_4 , for example by $\theta_4=60^\circ$ which case will be described.

[0177] Figure 27 is an illustration of the operation of the coupling member 286 when the cartridge B is dismounted from the apparatus main assembly A. Parts (a1) to (a4) of Figure 27 are views as seen from the outside in the driving side of the main assembly A, illustrating the dismounting of the process cartridge B from the apparatus main assembly A, in this order. Parts (b1) to (b4) of Figure 27 are sectional views taken along lines S23 - S23 of (a1) to (a4) of Figure 27 seen from the bottom. For better illustration, the coupling member 286, the drive head 214 and the pin 88 are not sectional views.

[0178] As shown in (a1) of Figure 27, when the process cartridge B is dismounted from the apparatus main assembly A, the cartridge B is first in the mounting completed position in the apparatus main assembly A in which the coupling member 286 is engaged with the drive head 214. In many cases, the process cartridge B is dismounted from the apparatus main assembly A after a series of image forming operations it is completed. At this time, the receiving portions 286e1 and 286e2 of the coupling member are contacted to the drive pins 214b1 and 214b2, respectively.

[0179] From the state, the cartridge B is moved in the dismounting direction (X3 direction the, and shown in (a2) and (b2) of Figure 27. The cartridge B is moved in the dismounting direction (X3 direction) while the axis L2 of the

coupling member 286 is inclining relative to the axis L1 of the driving side flange 87 and the axis L3 of the drive head 214. At this time, the claw portion 286d1 (receiving portion 286e1) in the downstream side of the drive pin 214b1 with respect to the dismounting direction (X3 direction) keeps in contact with the drive pin 214b1.

[0180] The cartridge B is further moved in the dismounting direction (X3 direction), as shown in (a3) and (b3) of Figure 27. Then, the axis L2 further inclines (pivots) so that a first inclination-regulated portions 286p1 and 286p2 (unshown) and the pin 88 as the first inclination regulating portion contact to each other, or the second inclination regulating portion 87n and the interconnecting portion 286 g as the second inclination-regulated portion contact to each other, similarly to the first embodiment. By this, the inclination (pivoting) of the coupling member 286 is limited. In the case of the phase ($\theta=60^\circ$) of the drive pin 214b and the claw portions 286d1 and 286d2 shown in Figure 27, the claw portion 286d1 (receiving portion 286e1) may not move to the non-driving side of the drive pin 214b but may keep the contact state. This is because the movement distances of the claw portions 286d1 and 286d2 toward the non-driving side by the inclination (pivoting) of the axis L2 is small.

[0181] At this time, since the drive head 214 is provided with the cut-away portion 214e, the coupling member 286 inclines (pivots) in the direction of an arrow X5 so that the claw portions 286d1 and 286d2 move along the drive pins 214b and 214b2.

[0182] As shown in (a4) and (b4) of Figure 27, the coupling member 286 further inclines (pivots) in the direction of the arrow X5 by the claw portion 286d2 entering the cut-away portion 214e. By the inclination (pivoting) of the coupling member 286, the contact between the claw portion 286d1 and the drive pin 214b1 is released in the direction of the arrow X5. By this, the process

cartridge B can be dismounted from the apparatus main assembly A.

[0183] In this embodiment, as compared with Embodiment 1, the widths Z21 of the receiving portions 286e1 and 286e2 are larger. More specifically, the width of the base portion is approx. 1.5 mm. With such a structure, the engagement amount Z23 (part (d) of Figure 26) between the drive pin 214b1, 214b2 and in the receiving portion 286e1, 286e2 in the axial direction of the drive pin 214b is larger than that in Embodiment 1. By this, the engagement between the pair of applying portions and the pair of receiving portions is assured so that stabilized transmission is accomplished irrespective of variation of the part accuracy or the like. By increasing the width of the base portion of the receiving portion, the driving force transmission can be stabilized, but if it is too large, the interference with the drive head may occur with the result of adverse affect. Therefore, it is preferable that in an imaginary flat plane perpendicular to the rotational axis of the coupling member and including the receiving portion for receiving the driving force from the engaging portion, a angle between the rotational axis and the line connecting the end portions of the projections is not less than approx. 10° and not more than approx. 30°. Taking into account the rigidity for the reception of the drive, the width of the base portion is 1.0 mm or larger.

[0184] The cut-away portion 214e is desired to be enough to permit disengagement between the coupling member 286 and the drive head 214 even when the engagement amount Z23 is larger than the gap between the inner diameter ϕ Z24 of the claw portion and the diameter ϕ Z27 of the cylindrical portion of the drive head 214. Therefore, it is provided so as to permit large inclination (pivoting) of the coupling member 86 in the direction of the arrow X5. Here, the large inclination means that the claw portions 286d1 and 286d2 can move toward the drive pins 214b1 and 214b2 through a distance larger than the engagement amount Z23.

[0185] Referring to Figure 28, the structure of the coupling guide 400b in this embodiment will be described. The structure of the coupling guide 400b is similar to that of Embodiment 1, but the gap S2 between the interconnecting portion 286 g of the coupling member 286 and the coupling guide 400b is
5 different from that of first embodiment.

[0186] Figure 28 is an illustration of the coupling guide 400b and (a1) (b1) of Figure 28 shows the state in which the cartridge B is mounted to the apparatus main assembly A, and the axis L2 of the coupling member 286 keeps inclined (pivoted). Parts (a2) and (b2) of Figure 28 shows the state in which the axis L2
10 is aligned with the axis L1 and the axis L3. Part (b1) of Figure 28 is a sectional view taking along a line S24 - S24 of (a1) of Figure 28. Part (b2) of Figure 28 is a sectional view taking along a line S24 - S24 of (a2) of Figure 28.

[0187] As shown in (a1) and (b1) of Figure 28, the coupling guide 400b is capable of limiting the inclination (pivoting) of the coupling member 286 so that
15 the engagement between the drive pin 214b and the claw portion 286d1 is kept even when the coupling member 286 is inclined (pivoted). In this embodiment, as described hereinbefore, the engagement amount Z23 is larger than that in Embodiment 1. In this embodiment, the gap S2 in (b2) of Figure 28 is larger than the gap S in Embodiment 1 ((b2) of Figure 22). Despite such conditions,
20 the engagement between the drive pin 214b1 and the receiving portion 286e1 can be kept to properly transmit the rotation even when the inclination (pivoting) of the coupling member 86 increases. In this manner, the gap S2 can be made larger than in Embodiment 1, and therefore, the dimensional accuracy of the interconnecting portion 286 g and/or the guide portion 400b2 can be eased.

[0188] As described above, the engagement amount Z23 between the drive pin 214b1, 214b2 and in the claw portion 286d1, 286d2 is increased, and the drive
25 head 214 is provided with the cut-away portion 214e. By doing so, when the

cartridge B is dismounted from the apparatus main assembly A, the engagement between the coupling member 286 and the drive head 214 can be released. In addition, with the structure of this embodiment, the gap S2 between the coupling guide 400b and the interconnecting portion 286 g can be increased as compared with Embodiment 1, by which the required part accuracy can be eased.

<Embodiment 3>

[0189] A third embodiment of the present invention will be described. Figure 29 is an illustration of a coupling member 386 and a drive head 314 as the main assembly side engaging portion. Figure 30 is an illustration of a R configuration portion 386g1 and shows a state in which the cartridge B is mounted to the apparatus main assembly A. Figure 31 is an illustration of a bearing member 387 and the coupling member 386 and is a perspective view and a sectional view.

The coupling member 386 is provided with lightening portions 386c2 - 386c9 in a connecting portion 386c as is different from Embodiment 1 and Embodiment 2. A diameter of an interconnecting portion 386 g is small, and a thickness defined by a spring receiving portion 386h and a receiving surface 386f is small. By this, the material can be saved.

[0190] In providing the lightening portions 386c2 - 386c9, it is preferable that the spherical 386c1 remains evenly along the circumferential direction. In this embodiment, the connecting portion 386c is construct in such that the void of the spherical portion 386c1 provided by the lightening portions 386c2 - 386c9 and the hole portion 386b is less than continuously 90°. The spherical portion may be substantially spherical in consideration of the lightening and/or manufacturing variation or the like. With the above-described structure of the connecting portion 386c, the position of the coupling member 86 in the driving side flange unit U32 can be stabilized. Particularly, the position of the coupling member

can be stabilized at the position of the line S14 - S14 supported by the accommodating portion 87i and at the position opposing to the conical portion 87k and the base portion 89a, as shown in part (c) of Figure 29.

An arcuate surface portion 386q1 and an arcuate surface portion 386q2
5 have diameters different from each other.

As shown in Figure 30, a R (rounded) configuration 386g1 is provided between the interconnecting portion 386 g and the spring receiving portion 386h. As described hereinbefore, in the driving side flange unit U32, there is provided a play for permitting small amount of movement of the coupling member 386 in
10 the axis L1 direction. When the coupling member 386a shifts to the non-driving side within the range of the play, the engagement amount Z38 between the drive pin 314b and the claw portion 386d1, 386d2 in the axis L1 direction decreases. Here, the engagement amount Z38 is a distance in the axis L3 direction between the center point of the arcuate configuration of the drive pin 314b and the free
15 end of the claw portion 386d1. In addition, when the coupling member 386 inclines to the extent that the interconnecting portion 386 g and a guide portion 330b2 of the coupling guide 330b contact to each other, the engagement amount Z38 between the drive pin 314b and in the claw portion 386d1, 386d2 decreases with the possible result of adverse affect to the driving force transmission.

20 However, by the provision of the R configuration portion 386g1, the free end of the guide portion 330b2 of the coupling guide 330b is contacted by the R configuration portion 386g1 when the coupling member 386 shifts toward the non-driving side. By this, as compared with the case in which the interconnecting portion 86 g contacts to the guide portion 300b2 as in
25 Embodiment 1, the inclination of the coupling member 386 can be reduced. Therefore, the provision of the R configuration portion 386g1 is effective to prevent simultaneous occurrences of the decrease of the engagement amount Z38

attributable to the shifting of the coupling member 386 toward the non-driving side and the reduction of the engagement amount Z38 attributable to the inclination of the coupling member 386. The R configuration portion 386g1 is not limited to the arcuate configuration, but may be a conical surface

5 configuration with the similar effects.

[0191] As shown in Figure 29, in this embodiment, the claw portions 386d1 and 386d2 have flat surface at the free end portions, thus increasing the thickness in the circumferential direction, by which the deformation of the claw portions 386d1 and 386d2 during the drive transmission is reduced. In addition, in order
10 to define the portion pressed by the torsion coil spring 91, the spring receiving portion 386h is provided with a spring receiving groove 386h1 (part (d) of Figure 30, too). The portion contacting the second arm 91b of the spring 91 is regulated, and by applying a lubricant there, the sliding between the second arm 91b and the coupling member 386 it is effected with grease always in existing
15 therebetween, and therefore, the scraping of these members and the sliding noise can be reduced. The coupling member 386 is made of metal, and the torsion coil spring 91 is made of metal, too. In the state that the coupling member 386 is being rotated by the driving force received from the main assembly side engaging portion 314, the torsion coil spring 91 continues to apply the urging
20 force to the coupling member. Therefore, during the image forming operation, the sliding occurs between metal members, and in order to reduce the influence thereof, it is preferable to provide lubricant at least between the coupling member 386 and the torsion coil spring 91.

[0192] On the other hand, as shown in part (b) of Figure 29, the drive pin 314b
25 of the main assembly side engaging portion 314 is not necessarily a circular column configuration member. The diameter $\phi Z36$ of the spherical surface portion 314c is larger than the diameter $\phi Z6$ of the spherical surface portion 14c

and the diameter $\phi Z37$ of the driving shaft 314a in Embodiment 1, because it is contacted to a receiving surface 386f which is thinner than in Embodiment 1. For the purpose of sliding engagement (and disengagement) with the coupling member 386, a taper 314e1 is provided at a stepped portion minute between the cut-away portion 314e and the driving shaft 314a.

The diameter of the free end of the guide portion 330b2 of the coupling guide 330b shown in Figure 30 is smaller than that of Embodiment 1 because the diameter of the interconnecting portion 386 g is smaller than that of Embodiment 1.

Referring to Figure 31, the bearing member 376 will be described in detail. As shown in Figure 31 a width Z32 of a cut-away portion 376k of the bearing member 376 is larger than the diameter $\phi Z31$ of the free end portion 386a, so that the free end portion 386a directs downward relative to the mounting direction X2 and axis L1, similarly to Embodiment 1. On the other hand, a plate-like portion 376h is provided at the position closer to the driving side than in Embodiment 1. Therefore, when the coupling member 386 inclines, the outsidemost circumference ($\phi Z31$ part) of the free end portion 386a contacts a lower surface 376k1 of the cut-away portion 376k. By this, the downward inclination of the coupling member 386 is limited irrespective of the inclination angle of the coupling member 386, and therefore, the engagement with the main assembly side engaging portion 314b is further stabilized. (in Embodiment 1, the conical spring receiving portion 87h contacts the lower surface 76k1, and therefore, the amount of the downward inclination of the coupling member 86 is different depending on the inclination angle of the coupling member 86).

[0193] A spring hook portion 376 g comprises a retaining portion 376g1, an insertion opening 376g2 and a supporting portion 376g3. The insertion opening 376g2 and the supporting portion 376g3 are connected with each other by a

tapered portion 376g4 so that the spring 91 can be smoothly slipped in the direction of an arrow X10. The most outer diameter Z33 of the retaining portion 376g1 and the insertion opening 376g2 and the most outer diameter of the supporting portion 376g3 are smaller than the inner diameter ϕ Z35 of the coil portion 91c of the spring 91. With the above-described structure of the spring hook portion 376g, the coil portion 91c can be easily slipped around the spring hook portion 376g, and the movement of the coil portion 91c in the direction of disengagement from the retaining portion 376g1 by the supporting portion 376g3 can be suppressed. By this, the possibility of the disengagement of the spring 91 from the spring hook portion 376 g can be reduced. The spring hook portion 376 g does not project beyond the first projected portion 376j outwardly (driving side), so that the possibility of the damage of the spring hook portion 376 g during the transportation is reduced.

[0194] In this embodiment, it is preferable that the retaining portion 376g1 is disposed in the side opposite from the spring hook portion 376 g across the coupling member 386 (lower left side in part (a) of Figure 31).

[0195] To described briefly, a reaction force received by the torsion coil spring 91 (a resultant force of a force F91a received by the first arm 91a and a force F91b received by the second arm 91b) directs toward the coupling member 386 side (upper right side in part (a) of Figure 31). By this, the coil portion 91c shifts toward the coupling member 386. Therefore, the above-described position of the retaining portion 376 g is effective to assure that the mounting property of the torsion coil spring 91 the prevention of the disengagement thereof. Furthermore, in this embodiment, as shown in part (c) of Figure 31, when the coupling member 386 is inclined so as to be close to the coil portion 91c side, the first arm and the second arm are substantially parallel with each other. Therefore, the force F91a and the force F91b are canceled, and therefore, the

reaction force received by the torsion coil spring 91 is reduced. In this manner, the force F91 does not direct toward the retaining portion 376g1, by which the possibility of the disengagement of the torsion coil spring 91 from the spring hook portion 376 g is reduced.

5 [0196] The bearing member 376 is provided with a contact prevention rib 376j5 and a contact prevention surface 376j2 in order to prevent contact of the coupling member 386 to the coil portion 91c. By this, even when the coupling member 386 inclines close to the coil portion 91c, the coupling member 386 contacts to the contact prevention rib 376j5, the contact prevention surface 376j2, so that the
10 contact of the free end portion 386a to the coil portion 91c is prevented. By this, the possibility of the disengagement of the coil portion 91c from the retaining portion 376g1 can be suppressed.

[0197] Furthermore, radially inside of the first projected portion 376j, a space 376j4 is provided to permit movement of the second arm of the spring 91. Here,
15 the second arm 91b has such a length that an arm portion 91b1 of the second arm 91b can be always contacted to the spring receiving portion 386h (Figure 29) of the coupling member 386. By doing so, the contact of the free end 91b2 of the second arm to the spring receiving portion 386h can be prevented.

[0198] In this embodiment, the disengagement prevention of the torsion coil
20 spring 91 it is effected by the configuration of the spring hook portion 376g, but may be effected using application of silicon bond or hot melt. Alternatively, another resin material member may be used for the prevention of the disengagement.

25 <Embodiment 4>

[0199] Referring to Figure 32, another structure of driving side flange unit and a bearing member supporting it in this embodiment will be described. In this

embodiment, the other parts of other than the driving side flange unit and the bearing member are the same as in the first embodiment, and the descriptions thereof is omitted by assigning that the same reference numerals. Even if the same reference numerals are assigned, the parts may be partly modified so as to match the structure of this embodiment.

[0200] As shown in Figure 32, in this embodiment, a first projected portion 476j of the bearing member 476 is divided into upper and lower parts. The assembling property of the torsion coil spring 91 relative to the spring hook portion 476 g using a tool or assembling device is improved because the neighborhood structure parts are less. In Embodiment 1, the supporting portion 76a as the second projected portion is projected from the plate-like portion 76h toward the non-driving side, it is possible that a supporting portion 476a is provided inside a hollow portion 476i, as shown in parts (c) and (d) of Figure 32. In such a case, the supported portion 487d of the driving side flange 487 is preferably provided on a second cylindrical portion 487h as long as the inclination (pivoting) of the coupling member 86 is not influenced. In this case, there is no second projected portion (supporting portion 76a) in the annular groove portion 87p, and therefore, it is unnecessary for the driving side flange 487 is provided with an annular groove portion 487p. Or, even if an annular groove portion 487p is provided from the standpoint of convenience in the resin material molding, it is possible that a first cylindrical portion 487j and the second cylindrical portion 487h are connected using rib configuration portions 487p1 - 487p4 to suppress the formation of the time when the drive is transmitted to the driving side flange 487.

<Embodiment 5>

[0201] Referring to Figure 33, a further structure of driving side flange unit and

a bearing member supporting it in this embodiment will be described. In this embodiment, the other parts of other than the driving side flange unit and the bearing member are the same as in the first embodiment, and the descriptions thereof is omitted by assigning that the same reference numerals. Even if the
5 same reference numerals are assigned, the parts may be partly modified so as to match the structure of this embodiment.

[0202] As shown in Figure 33, a cut-away portion 576k of the bearing member 576 in this embodiment is different from that in Embodiment 1. In Embodiment 1, the cut-away portion 76k has been in the form of a groove recessing from the
10 plate-like portion 76h toward the non-driving side and extending in parallel with the mounting direction X2. The cut-away portion 576k of the bearing member 576 is common with that of Embodiment 1 in that it is recessed from the plate-like portion 576h toward the non-driving side, but the groove -like configuration is not inevitable. It will suffice if the recess from the plate-like portion 576h is
15 enough to provide a space for permitting inclination of the coupling member 86, and a lower surface 576k1 is capable of limiting the position of the coupling member 86 (free end portion 86a) in the vertical direction.

[0203] In Embodiment 1, the supported portion 87d is provided on an inner circumference of the first cylindrical portion 87j of the driving side flange 87, but
20 in this embodiment, the outer peripheral surface of the second cylindrical portion 587h is used as the supported portion 587d. In one of the bearing members 576, a supporting portion 576a as the second projected portion enters a groove portion 587p to support the supported portion 587d. The second cylindrical portion 587h is projected more toward the driving side than the first cylindrical portion
25 587j, and therefore, by the provision of the supported portion 587d on the second cylindrical portion 587, the supporting length in the axis L1 direction can be increased as compared with the case in which the supported portion is provided

on the first cylindrical portion 587j.

(Other embodiments)

[0204] In the foregoing embodiments, the coupling member is accommodated
5 in the flange unit of the photosensitive drum, but this is not inevitable, and it will
suffice if the drive is received by the cartridge through the coupling member.
More particularly, the structure may be that a developing roller is rotated through
a coupling member. The present invention is suitably applicable to a developing
cartridge not comprising a photosensitive drum in which the rotational force is
10 transmitted from the main assembly side engaging portion to the developing
roller. In such a case, the coupling member 86 transmits the rotational force to
the developing roller 32 as the rotatable member in place of the photosensitive
drum.

[0205] The present invention is applicable to the structure in which the driving
15 force is transmitted to the photosensitive drum only. In the foregoing
embodiments, the driving side flange 87 as the force receiving member is fixed to
a longitudinal end portion of the drum 62 which is the rotatable member, the
driving side flange 87 may be an independent part not fixed thereto. For
example, it may be a gear member with which the driving force is transmitted to
20 the drum 62 and/or to the developing roller 32 through a gear connection.

[0206] In the foregoing embodiments, the cartridge B is for forming
monochromatic images. However, this is not inevitable. The structures and
concept of the above-described embodiments are suitably applicable to a
cartridge for forming multi-color images (two-color images, or full-color images,
25 for example) using a plurality of developing means.

[0207] A mounting-and-demounting path of the cartridge B relative to the
apparatus main assembly A may be a linear path, a combination of linear paths or

curved path, and the structures of the above-described embodiments can be used in such cases.

[INDUSTRIAL APPLICABILITY]

- 5 [0208] The structures of the foregoing embodiments can be applied to a cartridge usable with an electrophotographic image forming apparatus and a drive transmission device for them.

[Reference numerals]

- 10 3: laser scanner unit (exposure means, exposure device)
 7: transfer roller
 9: fixing device (fixing means)
 12: guiding member (guiding mechanism).
 12a: first guiding member
 15 12b: second guiding member
 13: opening and closing door
 14: drive head (main assembly side engaging portion)
 14a: drive shaft (shaft portion)
 14b: drive pin (applying portion)
 20 20: developing unit
 21: toner accommodating container
 22: closing member
 23: developing container
 32: developing roller (developing means, process means, rotatable
 25 member)
 60: cleaning unit
 62: photosensitive drum (photosensitive member, rotatable member)

- 64: non-driving side flange
- 66: charging roller (charging means, process means)
- 71: cleaning frame
- 74: exposure window
- 5 75: coupling member
- 76: bearing member (supporting member)
- 76b: guide portion
- 76d: first arcuate portion
- 76f: second arcuate portion
- 10 77: cleaning blade (removing means, process means)
- 78: drum shaft
- 86: coupling member
- 86a: free end portion (cartridge side engaging portion)
- 86b1: transmitting portion
- 15 86p1, 86p2: first inclination (pivoting) regulated portion
- 86 connecting portion (accommodated portion)
- 86d1, 86d2: projection
- 86e1, 86e2: receiving portion
- 86f: receiving surface
- 20 86g: interconnecting portion
- 86h: spring receiving portion
- 86k1, 86k2: standing-by portion
- 86m: opening
- 86z: recess
- 25 87: driving side flange (force receiving member).
- 87b: fixed portion
- 87d: supported portion

- 87e: hole portion
- 87f: retaining portion
- 87g: receiving portion
- 87k: conical portion
- 5 87m: opening
- 87n: second inclination regulating portion
- 87i: accommodating portion
- 88: pin (shaft portion, shaft)
- 89: closing member (regulating member)
- 10 90: screw (fastening means, fixing means)
- A: main assembly of electrophotographic image forming apparatus
(apparatus main assembly)
- B: process cartridge (cartridge)
- T: toner (developer)
- 15 P: sheet (sheet material, recording material)
- R: rotational moving direction
- S: gap
- U1: photosensitive drum unit (drum unit)
- U2: driving side flange unit (flange unit)
- 20 L1 you, rotational axis of electrophotographic photosensitive drum
- L2 rotational axis: of coupling member
- L3: rotational axis of main assembly side engaging portion
- $\theta 1$: inclination angle (first angle)
- $\theta 2$: inclination angle (second angle)

C l a i m s:

1. A cartridge mountable to a main assembly of an electrophotographic image forming apparatus, said coupling member comprising a pivotable coupling member, wherein the main assembly including a rotatable engaging portion for engaging with said coupling member, and a coupling guide, positioned downstream of a rotational axis of the engaging portion with respect to a mounting direction of said cartridge, for being contacted by said coupling member pivoted relative to the rotational axis of the engaging portion to guide said coupling member to be parallel with the rotational axis of the engaging portion, said cartridge being mountable to the main assembly in the mounting direction substantially perpendicular to the rotational axis of the engaging portion, said cartridge comprising:
- a frame;
 - a rotatable member for carrying a developer; and
 - a rotatable force receiving member for receiving a rotational force to be transmitted to said rotatable member;
- said coupling member including a free end portion having a receiving portion for receiving the rotational force from the engaging portion and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion to said force receiving member,
- said frame including,
 - a hole portion for exposing said free end portion to an outside of said frame, and
 - a receiving portion, provided in a downstream of said hole portion with respect to the mounting direction, for receiving said coupling member when said coupling member is inclined toward a downstream side with respect to the

mounting direction and for receiving said coupling guide in place of said coupling member with engagement of said coupling member with the engaging portion.

5 2. A cartridge according to Claim 1, wherein said receiving portion includes a groove portion provided in said frame and extending from said hole portion toward downstream with respect to the cartridge mounting direction.

10 3. A cartridge according to Claim 1, wherein said receiving portion includes a groove portion provided in said frame, and a side surface of said groove portion does not contact the coupling guide which is entering.

15 4. A cartridge according to Claim 1, wherein said receiving portion includes a groove portion provided in said frame, and said coupling member enters said groove portion by inclining.

20 5. A cartridge according to Claim 1, wherein said receiving portion includes a groove portion provided in said frame, wherein a width measured in a direction perpendicular to the mounting direction of said groove portion is larger than a diameter of said free end portion of said coupling member.

25 6. A cartridge according to any one of Claims 1 - 5, wherein an inclinable angle of said coupling member toward said receiving portion is larger than an inclinable angle of said coupling member in another direction.

7. A cartridge according to any one of Claims 1 - 6, wherein in a state that said coupling member receives the rotational force from the engaging portion, said

coupling member is out of contact with said coupling guide.

8. A cartridge according to any one of Claims 1 - 7, wherein in a state that said cartridge is mounted to the main assembly, hole portion said coupling guide
5 overlaps with each other.

9. A cartridge according to any one of Claims 1 - 8, further comprising an urging member for urging said coupling member so as to incline said free end portion toward said receiving portion.
10

10. A cartridge according to Claim 1, wherein said receiving portion includes a groove portion provided in said frame, and said cartridge further comprises an urging member for urging said coupling member so as to incline said free end portion toward said receiving portion, wherein said coupling member urged by
15 said urging member is regulated in an attitude thereof by contact to a side surface of said groove portion.

11. A cartridge according to any one of Claims 1 - 2, wherein said frame further includes a projection projecting outwardly of said cartridge beyond said receiving portion, above said hole portion with respect to a direction of gravity.
20

12. A cartridge according to Claim 11, wherein in a state that said cartridge is mounted to the main assembly, projection receive an urging force from the main assembly.
25

13. A cartridge according to any one of Claims 1 - 12, wherein said coupling member is provided with a through-hole penetrating said connecting portion and

a shaft portion penetrating said through-hole to receive the rotational force from the transmitting portion, wherein opposite end portions thereof are supported by said force receiving member.

- 5 14. A cartridge according to any one of claims 1 - 13, wherein said free end portion is provided with two projections having said receiving portions disposed at substantially point symmetry positions with respect to the rotational axis of said coupling member, and wherein a inclinable angle of said coupling member in the mounting direction in a state that an imaginary line connecting said two
10 projections is perpendicular to the mounting direction when said cartridge is moved relative to the main assembly in the mounting direction is smaller than an inclinable angle in the mounting direction in a state that an imaginary line connecting said two projections is parallel with the mounting direction when said cartridge is moved relative to the main assembly in the mounting direction.

15

15. A cartridge according to any one of Claims 1 - 14, wherein said free end portion is provided with a projection having a receiving portion, and said receiving portion is exposed as seen from an outside with respect to a radial direction perpendicular to a rotational moving direction of said coupling member.

20

16. A cartridge according to any one of Claims 1 - 15, wherein said coupling member is rotatable toward the downstream with respect to the mounting direction by not less than approx. 20°.

- 25 17. A cartridge according to any one of Claims 1 - 16, wherein said rotatable member is a photosensitive member.

18. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a dismounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

- 5 a rotatable member for carrying a developer; and
- a rotatable coupling member including a free end portion having projections, said coupling member being pivotable relative to a rotational axis of said rotatable member,
- wherein a number of said projections that have receiving portions for
- 10 receiving a rotational force from the engaging portion is two, and said receiving portions of said two projections are disposed at substantially point symmetry positions with respect to the rotational axis of said coupling member, wherein a first inclinable angle of said coupling member in a direction opposite the mounting direction in a state that an imaginary line connecting said two
- 15 projections is perpendicular to the mounting direction when said cartridge is moved relative to the main assembly in the dismounting direction is smaller than a second inclinable angle in the opposite direction in a state that an imaginary line connecting said two projections is parallel with the dismounting direction when said cartridge is moved relative to the main assembly in the dismounting direction.

20

19. A cartridge according to Claim 18, wherein the first angle and the second angle are not less than approx. 20°.

20. A cartridge according to claim 18 or 19, wherein a difference between the

25 first angle and the second angle is not less than approx. 3° and not more than approx. 20°.

21. A cartridge according to any one of claims 18 - 20, further comprising a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is provided with an accommodating portion therein, and said coupling member
5 includes a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion to said force receiving member, and wherein at least a part of said connecting portion is accommodating in said accommodating portion.

10 22. A cartridge according to Claim 21, wherein said connecting portion is provided with a through-hole penetrating said connecting portion, and a shaft portion penetrating said through-hole and capable of receiving the rotational force from said transmitting portion.

15 23. A cartridge according to Claim 22, wherein an angle formed between said shaft portion and the imaginary line is not less than approx. 55° and not more than approx. 125° .

24. A cartridge according to any one of Claims 18 - 23, further comprising an
20 urging member for urging said coupling member so as to direct said free end portion in the opposite direction.

25. A cartridge according to any one of Claims 18 - 24, wherein an angle
formed between two lines connecting the rotation axis and opposite end portions
25 of said projections in an imaginary plane perpendicular to the rotational axis of said coupling member and including a receiving portion for receiving a driving force from the engaging portion is not less than approx. 10° and not more than

approx. 30°.

26. A cartridge according to any one of Claims 18 - 25, wherein the number of said projections is only two.

5

27. A cartridge according to any one of Claims 18 - 26, wherein said free end portion is provided with a projection having a receiving portion, and said receiving portion is exposed as seen from an outside with respect to a radial direction perpendicular to a rotational moving direction of said coupling member.

10

28. A cartridge according to any one of Claims 18 - 27, wherein the main assembly includes a coupling guide, positioned downstream of a rotational axis of the engaging portion with respect to a mounting direction of said cartridge, for being contacted by said coupling member pivoted relative to the rotational axis of the engaging portion to guide said coupling member to be parallel with the rotational axis of the engaging portion,

15

said cartridge further comprising a receiving portion capable of receiving said coupling member which is inclined, wherein when said cartridge is mounted to the main assembly, the coupling guide enters said receiving portion.

20

29. A cartridge according to any one of Claims 18 - 28, wherein said rotatable member is a photosensitive member.

30. A cartridge mountable to a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a mounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

25

a rotatable member for carrying a developer; and

a rotatable coupling member including a free end portion having projections, said coupling member being pivotable relative to a rotational axis of said rotatable member,

5 wherein a number of said projections that have receiving portions for receiving a rotational force from the engaging portion is two, and said receiving portions of said two projections are disposed at substantially point symmetry positions with respect to the rotational axis of said coupling member, wherein a first inclinable angle of said coupling member toward a downstream side with respect to the mounting direction in a state that an imaginary line connecting said
10 two projections is perpendicular to the mounting direction is smaller than a second inclinable angle toward a downstream side with respect to the mounting direction in a state that an imaginary line connecting said two projections is parallel with the mounting direction.

15

31. A cartridge according to Claim 30, wherein the first angle and the second angle are not less than approx. 20°.

32. A cartridge according to claim 30 or 31, wherein a difference between the
20 first angle and the second angle is not less than approx. 3° and not more than approx. 20°.

33. A cartridge according to any one of claims 30 - 32, further comprising a rotatable force receiving member for receiving the rotational force to be
25 transmitted to said rotatable member, wherein said force receiving member is provided with an accommodating portion therein, and said coupling member includes a connecting portion having a transmitting portion for transmitting the

rotational force received by said receiving portion to said force receiving member, and wherein at least a part of said connecting portion is accommodating in said accommodating portion.

5 34. A cartridge according to Claim 33, wherein a shaft portion penetrating said through-hole and capable of receiving the rotational force from said transmitting portion.

35. A cartridge according to Claim 34, wherein an angle formed between said
10 shaft portion and the imaginary line is not less than approx. 55° and not more than approx. 125° .

36. A cartridge according to any one of Claims 30 - 35, further comprising an urging member for urging said coupling member so as to direct said free end
15 portion in the opposite direction.

37. A cartridge according to any one of Claims 30 - 36, wherein an angle formed between two lines connecting the rotation axis and end portions of said projections in an imaginary plane perpendicular to the rotational axis of said
20 coupling member and including a receiving portion for receiving a driving force from the engaging portion is not less than approx. 10° and not more than approx. 30° .

38. A cartridge according to any one of Claims 30 - 37, wherein the number of
25 said projections is only two.

39. A cartridge according to any one of Claims 30 - 38, wherein said projection

is provided so as to expose said receiving portion without protection.

40. A cartridge according to any one of Claims 30 - 39, wherein the main assembly includes a coupling guide, positioned downstream of a rotational axis of the engaging portion with respect to a mounting direction of said cartridge, for
5 being contacted by said coupling member pivoted relative to the rotational axis of the engaging portion to guide said coupling member to be parallel with the rotational axis of the engaging portion,

said cartridge further comprising a receiving portion capable of
10 receiving said coupling member which is inclined, wherein said coupling guide enters said receiving portion in response to said coupling member retracting from said receiving portion and engaging with the engaging portion.

41. A cartridge according to Claim 40, wherein in a state that said coupling
15 member receives the rotational force from the engaging portion, said coupling member is out of contact with the coupling guide.

42. A cartridge according to any one of Claims 30 - 41, wherein said rotatable member is a photosensitive member.

20

43. A cartridge mountable to a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a mounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

25

a rotatable member for carrying a developer; and

a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is

provided with an accommodating portion therein;

a coupling member including a free end portion having a receiving portion for receiving the rotational force from the engaging portion, a connecting portion at least a part of which is accommodated in said accommodating portion
5 and which is provided with a through-hole, said coupling member being pivotable relative to the rotational axis of said force receiving member; and

a shaft portion penetrating said through-hole to transmit the rotational force from said coupling member to said force receiving member,

wherein when an axis of said shaft portion is parallel with the
10 mounting direction, said coupling member when inclining toward a downstream side with respect to the mounting direction is limited in the inclination thereof by said shaft portion contacting to said through-hole, and

wherein when the axis of said shaft portion is perpendicular to the mounting direction, said coupling member when inclining toward a downstream
15 side with respect to the mounting direction is limited in the inclination thereof by said coupling member contacting to said force receiving member.

44. A cartridge according to Claim 43, wherein an inclination angle of said coupling member relative to the rotational axis of said force receiving member at
20 the time when the inclination of said coupling member is limited by the contact of said shaft portion to said through-hole is smaller than an inclination angle of said coupling member relative to the rotational axis of said force receiving member at the time when the inclination of said coupling member is limited by the contact of the coupling member to said force receiving member.

25

45. A cartridge according to claim 43 or 44, further comprising a frame, wherein said frame is provided with a hole portion for exposing said free end

portion to an outside of said frame, and a receiving portion provided at the position downstream of said hole portion with respect to the mounting direction, said receiving portion is capable of receiving said coupling member which is inclined.

5

46. A cartridge according to Claim 45, wherein a pivoting angle of said coupling member when the pivoting of said coupling member is limited by the contact of said coupling member to said force receiving member is a maximum, when said coupling member inclines toward said receiving portion.

10

47. A cartridge according to claim 45 or 46, further comprising an urging member for urging said coupling member toward said receiving portion.

15

48. A cartridge according to Claim 47, wherein said urging member includes a torsion coil spring which is disengageably engaged with said supporting member.

20

49. A cartridge according to any one of Claims 43 -48, wherein an angle when the inclination of said coupling member limited by the contact of said coupling member to a part of said force receiving member is larger than an angle when the inclination of said coupling member is limited by the contact of said shaft portion to said through-hole.

25

50. A cartridge according to any one of Claims 43 - 49, wherein said free end portion is provided with a projection extending in a direction of the rotational axis of said coupling member, and a number of said projections that have receiving portions for receiving a rotational force from the engaging portion is two, and wherein said receiving portions of said two projections are disposed at

substantially point symmetry positions with respect to the rotational axis of said coupling member, and when an imaginary line connecting said two projections is parallel with the mounting direction, the inclination of said coupling member is limited by contacting to a part of said force receiving member.

5

51. A cartridge according to any one of Claims 43 - 49, wherein said free end portion is provided with a projection extending in a direction of the rotational axis of said coupling member, and a number of said projections that have receiving portions for receiving a rotational force from the engaging portion is two, and wherein said receiving portions of said two projections are disposed at substantially point symmetry positions with respect to the rotational axis of said coupling member, and when an imaginary line connecting said two projections is perpendicular to the mounting direction, the inclination of said coupling member is limited by said shaft portion contacting to said through-hole.

10
15

52. A cartridge according to any one of Claims 43 - 51, wherein an angle formed between two lines connecting the rotation axis and end portions of said projections in an imaginary plane perpendicular to the rotational axis of said coupling member and including a receiving portion for receiving a driving force from the engaging portion is not less than approx. 10° and not more than approx. 30°.

20

53. A cartridge according to any one of Claims 43 - 52, wherein said force receiving member includes a disengagement preventing portion for preventing disengagement of said coupling member by contacting to an outer periphery of said connecting portion.

25

54. A cartridge according to any one of Claims 43 - 53, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

5 55. A cartridge according to any one of Claims 43 - 54, wherein said rotatable member is a photosensitive member.

56. A cartridge mountable to a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a mounting direction
10 substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

a frame;

a rotatable photosensitive member;

a rotatable coupling member have a rotational axis which is pivotable
15 relative to a rotational axis of said photosensitive member;

an urging member contacted to said coupling member to urge a free end portion of said coupling member toward a downstream side with respect to the mounting direction;

a first projection provided on said frame to receive an urging force
20 from the main assembly in a state that said cartridge is mounted to the main assembly; and

a second projection projecting from the same surface of said frame from which said first projection projects, outwardly along the rotational axis to mount said urging member, said first projection projects more outwardly than
25 said second projection.

57. A cartridge according to Claim 56, wherein said frame is provided with a

hole portion for exposing said free end portion to an outside of said frame, and wherein said first projection provided above said hole portion with respect to a direction of gravity in a state that said cartridges mounted to the main assembly.

- 5 58. A cartridge according to Claim 56, wherein said frame is provided with a hole portion for exposing said free end portion to an outside of said frame, and wherein said second projection is provided below said hole portion with respect to a direction of gravity in a state that said cartridge is mounted to the main assembly.

10

59. A cartridge according to any one of Claims 56 - 58, wherein said urging member includes a torsion coil spring having a coil portion engaged with said second projection.

- 15 60. A cartridge according to Claim 59, wherein a portion of said second projection for supporting said coil portion has a D-shaped cross-section, and a side remote from the rotation axis of said coupling member is a linear part of the D-shape.

- 20 61. A cartridge according to Claim 56, wherein said frame is provided with a hole portion for exposing said free end portion to an outside of said frame, a receiving portion, provided at a position downstream of said hole portion, for receiving said coupling member which is inclined.

- 25 62. A cartridge according to any one of Claims 56 - 61, wherein a number of said projections that have receiving portions for receiving a rotational force from the engaging portion is two, and in a state that the rotational axis of said coupling

member is parallel with the rotational axis of said photosensitive member, the projections of said free end portion are projected more outwardly of said frame than said first projection.

5 63. A cartridge according to any one of Claims 56 - 61, wherein a number of said projections that have receiving portions for receiving a rotational force from the engaging portion is two, and in a state that said coupling member is urged by said urging member such that the rotational axis of said coupling member is inclined relative to the rotational axis of said photosensitive member, said first
10 projection is projected more outwardly of said frame than downstream one of projections of said free end portion with respect to the mounting direction.

64. A cartridge according to any one of Claims 56 - 61, wherein a number of said projections that have receiving portions for receiving a rotational force from
15 the engaging portion is two, and said receiving portion of said two projections are disposed at substantially point symmetry positions with respect to the rotational axis of said coupling member, wherein a first inclinable angle of said coupling member toward a downstream side with respect to the mounting direction in a state that an imaginary line connecting said two projections is perpendicular to
20 the mounting direction is smaller than a second inclinable angle toward a downstream side with respect to the mounting direction in a state that an imaginary line connecting said two projections is parallel with the mounting direction.

25 65. A cartridge according to any one of Claims 56 - 64, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

66. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a dismounting direction substantially perpendicular to a rotational axis of the engaging portion,
5 said cartridge comprising:

a rotatable member for carrying a developer;

a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is provided with an accommodating portion therein;

10 a rotatable coupling member including a free end portion having a receiving portion for receiving a rotational force from the engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion to said force receiving member, wherein at least a part of said coupling member is accommodated in said accommodating
15 portion so that the rotational axis of said coupling member is pivotable relative to a rotational axis of said force receiving member in the manner that said receiving portion is disengaged from the engaging portion with movement of said cartridge in the dismounting direction, and wherein said coupling member is provided with a through-hole penetrating through said connecting portion; and

20 a shaft portion penetrating through said through-hole and capable of receiving the rotational force from said transmitting portion,

wherein opposite end portions of said shaft portion are supported by said force receiving member, and a maximum rotation diameter about the rotational axis of said coupling member in said connecting portion is larger than a
25 maximum rotation diameter of said coupling member about the rotational axis in said free end portion.

67. A cartridge according to Claim 66, wherein said shaft portion is provided with the inclination regulating portion for limiting the inclination of said coupling member by contacting to said through-hole when the rotational axis of said coupling member inclines relative to said force receiving member.

5

68. A cartridge according to Claims 66 or 67, wherein said force receiving member includes a disengagement preventing portion for preventing disengagement of said coupling member by contacting to an outer periphery of said connecting portion.

10

69. A cartridge according to any one of Claims 66 - 88, wherein said connecting portion has a substantially spherical shape having a center at a pivoting center of said coupling member.

15

70. A cartridge according to Claim 69, wherein said disengagement preventing portion limits a substantially spherical shape portion of the connecting portion.

20

71. A cartridge according to any one of claims 66 - 70, further comprising an urging member contacting said coupling member to urge said free end portion to a downstream side with respect to the mounting direction.

25

72. A cartridge according to Claim 66 - 71, wherein an inclination angle of said coupling member relative to the rotational axis of said force receiving member when the inclination of said coupling member is limited by said shaft portion contacting to said through-hole is smaller than an inclination angle of said coupling member relative to the rotational axis of said force receiving member when the inclination of said coupling member is limited by said coupling member

contacting to said force receiving member.

73. A cartridge according to Claim 66 - 72, wherein said coupling member includes an interconnecting portion between said free end portion and said
5 connecting portion, wherein a diameter of said interconnecting portion is small and then diameters of said free end portion and said connecting portion.

74. A cartridge according to any one of Claims 66 - 73, wherein said coupling member is capable of inclining toward a downstream with respect to the
10 mounting direction by not less than approx. 20°.

75. A cartridge according to any one of Claims 66 - 74, wherein said rotatable member is a photosensitive member.

15 76. A cartridge mountable to a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a mounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

a frame;

20 a rotatable member for carrying a developer; and

a rotatable coupling member including a free end portion having projections, said coupling member being pivotable relative to a rotational axis of said rotatable member, wherein a number of said projections that have receiving portions for receiving a rotational force from the engaging portion is two, and
25 said receiving portions of said two projections are disposed at substantially point symmetry positions with respect to the rotational axis of said coupling member;

a first projection provided on said frame to receive an urging force

from the main assembly in a state that said cartridge is mounted to the main assembly; and

an urging member contacting said coupling member to urge said free end portion toward a downstream side with respect to the mounting direction,

5 wherein when the rotational axis of said coupling member is parallel with the rotational axis of said rotatable member, at least parts of the two projections of said free end portion is more outside of said frame than said first projection in a direction of the rotational axis of said rotatable member, and

wherein all of at least one of said projections of said coupling member
10 urged and inclined by said urging member are more inside than said first projection in the rotational axis of said rotatable member.

77. A cartridge according to Claim 76, further comprising a second projection projecting from the same surface of said frame from which said first projection
15 projects to support said urging member, wherein said first projection projects more outwardly of said frame than said second projection.

78. A cartridge according to Claim 77, wherein said urging member includes a torsion coil spring having a coil portion engaged with said second projection.

20

79. A cartridge according to any one of claims 76 - 78, further comprising a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is provided with an accommodating portion therein, and said coupling member
25 includes a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion to said force receiving member, and wherein at least a part of said connecting portion is accommodating in said

accommodating portion.

80. A cartridge according to Claim 79, wherein said connecting portion is provided with a through-hole penetrating said connecting portion, and a shaft
5 portion penetrating said through-hole and capable of receiving the rotational force from said transmitting portion.

81. A cartridge according to any one of Claims 76 - 80, wherein an imaginary line connecting two projections having the receiving portions is perpendicular to
10 the mounting direction, the two projections of said coupling member inclined toward a downstream with respect to the mounting direction are inside said frame.

82. A cartridge according to any one of Claims 76 - 81, wherein the main assembly includes a coupling guide, positioned downstream of a rotational axis of
15 the engaging portion with respect to a mounting direction of said cartridge, for being contacted by said coupling member pivoted relative to the rotational axis of the engaging portion to guide said coupling member to be parallel with the rotational axis of the engaging portion,

Said cartridge further comprising a receiving portion for receiving
20 said coupling member which is inclined, wherein said coupling member retracts from said receiving portion and said coupling guide enters said receiving portion, with said coupling member engaging with the engaging portion.

83. A cartridge according to Claim 82, wherein said frame is provided with a
25 hole portion for exposing said free end portion to an outside of said frame, and said receiving portion is provided with downstream of said hole portion with respect to the mounting direction.

84. A cartridge according to any one of Claims 76 - 83, wherein said free end portion is provided with a projection having a receiving portion, and said receiving portion is exposed as seen from an outside with respect to a radial direction perpendicular to a rotational moving direction of said coupling member.

85. A cartridge according to any one of Claims 76 - 84, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

10

86. A cartridge according to any one of Claims 76 - 85, wherein said rotatable member is a photosensitive member.

87. A cartridge usable with a main assembly of an electrophotographic image forming apparatus, the main assembly including a rotatable engaging portion, a coupling guide provided in a rear side of a rotational axis said engaging portion, said cartridge being mountable to said main assembly by moving in a mounting direction substantially perpendicular to the rotational axis of the engaging portion, said cartridge comprising:

20

a frame;

a rotatable member;

a coupling member which has a free end portion having a projection and which is rotatable about a rotational axis thereof pivotable relative to the rotational axis of said rotatable member, wherein an inclination of said coupling member at the time when it is completely mounted to the main assembly is capable of being limited by said coupling guide,

25

wherein said frame is provided with a hole portion for exposing said

free end portion to an outside of said frame, a receiving portion which is provided downstream of said hole portion with respect to the mounting direction, wherein said free end portion of said coupling member inclined toward a downstream side with respect to the mounting direction enters receiving portion, and the coupling
5 guide enters said receiving portion in place of said free end portion with said coupling member engaging with the engaging portion, said frame is further provided with a limiting portion projected more outside than said receiving portion in the rotational axis direction of said rotatable member; and
an urging member for urging said coupling member to said limiting
10 portion so as to cause said free end portion to enter said receiving portion.

88. A cartridge according to Claim 87, wherein said coupling guide is positioned downstream of a rotational axis of the engaging portion with respect to a mounting direction of said cartridge and is contacted by said coupling member
15 pivoted relative to the rotational axis of the engaging portion to guide said coupling member to be parallel with the rotational axis of the engaging portion, and wherein when said cartridge is mounted to the main assembly, said coupling member inclined by said urging member contacts the coupling guide entering said receiving portion.

20

89. A cartridge according to Claim 87 or 88, wherein said receiving portion includes a groove portion provided in said frame, and said groove portion extends from said hole portion toward a downstream with respect to the mounting direction.

25

90. A cartridge according to any one of Claims 87 - 89, wherein an inclinable of said coupling member is larger direction said retracted portion than direction

another direction.

91. A cartridge according to Claim 88, wherein said receiving portion includes a groove portion provided in said frame, and a side surface of said groove portion
5 does not contact the coupling guide which is entering.

92. A cartridge according to Claim 87, wherein said receiving portion includes a groove portion provided in said frame, and a pivoting angle of said coupling member is limited by being urged by said urging member to contact to a lower
10 side surface of said groove portion with respect to a direction of gravity.

93. A cartridge according to any one of claims 88 - 91, wherein in a state that said coupling member receive a rotational force from said engaging portion, said coupling member is contacted by said urging member, and does not contact to
15 said coupling guide.

94. A cartridge according to any one of claims 87 - 93, wherein said free end portion includes two projections having said receiving portions, wherein the projections are disposed such that said receiving portions are at substantially
20 point symmetry positions with respect to the rotational axis of said coupling member, and wherein when said cartridge moves in the mounting direction relative to the main assembly, a pivotable angle of said coupling member in a direction opposite the mounting direction when an imaginary line connecting said two projections is perpendicular to the mounting direction is smaller than a
25 pivotable angle of said coupling member in the opposite direction when the imaginary line is parallel with the mounting direction.

95. A cartridge according to any one of Claims 87 - 94, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

5 96. A cartridge according to any one of Claims 87 - 95, wherein said rotatable member is a photosensitive member.

97. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a dismounting
10 direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

a rotatable member for carrying a developer; and

a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, said force receiving member being
15 provided with an accommodating portion inside thereof and a gear portion outside thereof;

a rotatable coupling member including a free end portion having a receiving portion for receiving the rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the
20 rotational force received by said receiving portion to said force receiving member, wherein at least a part of said coupling member is accommodated in said accommodating portion so that the rotational axis of said coupling member is pivotable relative to a rotational axis of said force receiving member in the manner that said receiving portion is disengaged from the engaging portion with
25 movement of said cartridge in the dismounting direction, and wherein said coupling member is provided with a through-hole penetrating through said connecting portion;

a shaft portion penetrating through said through-hole and capable of receiving the rotational force from said transmitting portion; and

a supporting member having a supporting portion rotatably supporting said force receiving member,

5 wherein opposite end portions of said shaft portion are supported by said force receiving member, an imaginary flat plane perpendicular to the rotational axis of said force receiving member, an imaginary flat plane is across said shaft portion, said supporting portion and said gear portion.

10 98. A cartridge according to Claim 97, wherein said supporting member includes a first projection for receiving an urging force when said cartridge is mounted to said main assembly, wherein an imaginary flat plane perpendicular to the rotational axis of said force receiving member and including said shaft portion, said supporting portion and said gear portion is not across said first projection.

15 99. A cartridge according to claim 97 or 98, further comprising an urging member for urging said coupling member toward a downstream side with respect to the mounting direction, said supporting member includes a second projection for supporting said urging member, wherein an imaginary flat plane perpendicular to the rotational axis of said force receiving member and including
20 said shaft portion, said supporting portion and said gear portion is not across said second projection.

100. A cartridge according to any one of claims 97 - 99, wherein said
25 supporting member is provided with a hole portion for exposing said free end portion to an outside of said cartridge, a receiving portion, provided downstream of said hole portion with respect to the mounting direction, for receiving said

coupling member which is inclined.

101. A cartridge according to Claim 100, wherein said receiving portion includes a groove portion provided in said supporting member.

5

102. A cartridge according to claim 101, further comprising an urging member for urging said coupling member toward a downstream side with respect to the mounting direction,

a pivoting angle of said coupling member is limited by being urged by said urging member to contact to a lower side surface of said groove portion with respect to a direction of gravity.

10

103. A cartridge according to Claim 97, further comprising a torsion coil spring for urging said coupling member toward a downstream side with respect to the mounting direction, wherein said supporting member is provided with a second projection for supporting a coil portion of said torsion coil spring, and an arm extending from an outside portion of the coil portion of said torsion coil spring is engaged with said supporting member, and an arm extending from an inside portion of the coil portion of said torsion coil spring is contacted to said coupling member.

15

20

104. A cartridge according to Claim 97, further comprising a torsion coil spring for urging said coupling member toward a downstream side with respect to the mounting direction, wherein said supporting member is provided with a first projection for receiving an urging force from the main assembly in a state that said cartridge is mounted to the main assembly and a second projection for supporting a coil portion of said torsion coil spring, and wherein said first

25

projection is projected more outwardly than said second projection in the direction of rotational axis of said rotatable member.

105. A cartridge according to any one of Claims 97 - 104, wherein said force
5 receiving member includes a disengagement preventing portion for preventing disengagement of said coupling member by contacting to an outer periphery of said connecting portion.

106. A cartridge according to Claim 105, wherein said connecting portion has a
10 substantially spherical shape about a pivoting center of said coupling member.

107. A cartridge according to Claim 106, wherein said disengagement
preventing portion limits a substantially spherical shape portion of the connecting
portion.

15

108. A cartridge according to any one of Claims 97 - 107, wherein said force
receiving member is provided with an annular groove portion between said
accommodating portion and said gear portion in an outer surface of said cartridge.

20 109. A cartridge according to any one of Claims 43 - 53, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

110. A cartridge according to any one of Claims 1 - 16, wherein said rotatable
25 member is a photosensitive member.

111. A cartridge dismountable from a main assembly of an electrophotographic

image forming apparatus including a rotatable engaging portion, in a dismounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

a rotatable member for carrying a developer; and

5 a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is provided with an accommodating portion therein;

a coupling member pivotable relative to a rotational axis of said force receiving member, said coupling member including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and
10 a connecting portion at least a part of which is accommodated in said accommodating portion; and

a supporting member having a supporting portion rotatably supporting said force receiving member,

15 wherein said force receiving member is provided with an annular groove portion in an outside surface of said cartridge, and a supporting portion of said supporting member contacts a side surface of said groove which is radially outward of said force receiving member and rotatably supports said force receiving member, wherein said connecting portion is inside of said groove in a
20 radial direction of said transmission member.

112. A cartridge according to any one of Claims 111, wherein said coupling member is provided with a through-hole penetrating said connecting portion and a shaft portion penetrating said through-hole to receive the rotational force from
25 the transmitting portion, wherein opposite end portions thereof are supported by said force receiving member, wherein said shaft portion and a side surface of said groove overlaps with each other.

113. A cartridge according to any one of Claims 111, wherein said coupling member is provided with a through-hole penetrating said connecting portion and a shaft portion penetrating said through-hole to receive the rotational force from the transmitting portion, wherein opposite end portions thereof are supported by said force receiving member, wherein said shaft portion and said supporting portion overlaps with each other.

114. A cartridge according to any one of Claims 111 - 113, wherein said force receiving member includes a gear portion which is outside of said groove portion in a radial direction of said force receiving member.

115. A cartridge according to Claim 114, wherein a pivoting center at the time when coupling member inclines relative to said force receiving member overlaps with said gear portion.

116. A cartridge according to any one of Claims 111 - 115, wherein said force receiving member includes a disengagement preventing portion for preventing disengagement of said coupling member by contacting to an outer periphery of said connecting portion.

117. A cartridge according to any one of Claims 111 - 116, wherein said force receiving member is provided with a hole portion for exposing said free end portion to an outside of said cartridge, and a receiving portion, provided downstream of said hole portion with respect to the mounting direction, for receiving said coupling member.

118. A cartridge according to any one of the claims 111 - 117, further comprising a torsion coil spring for urging said coupling member toward a downstream side with respect to the mounting direction, wherein said supporting member is provided with a second projection for supporting a coil portion of said torsion coil spring, and an arm extending from an outside portion of the coil portion of said torsion coil spring is engaged with said supporting member, and an arm extending from the inside portion of the coil portion of said torsion coil spring is contacted to said coupling member.

119. A cartridge according to any one of claims 111 - 117, further comprising a torsion coil spring for urging said coupling member toward a downstream side with respect to the mounting direction, wherein said supporting member is provided with a first projection for receiving an urging force from the main assembly in a state that said cartridge is mounted to the main assembly, wherein said supporting member is provided with a second projection for supporting a coil portion of said torsion coil spring, and wherein said first projection is projected more outwardly than said second projection in the direction of rotational axis of said rotatable member.

120. A cartridge according to any one of Claims 111 - 119, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

121. A cartridge according to any one of Claims 111 - 120, wherein said rotatable member is a photosensitive member.

122. A cartridge mountable to a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a mounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

- 5 a rotatable member for carrying a developer; and
- a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is provided with an accommodating portion therein;
- a coupling member pivotable relative to a rotational axis of said
- 10 rotatable member, said coupling member including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a transmitting portion for transmitting the rotational force received by said receiving portion to said force receiving member;
- a supporting member having a supporting portion rotatably supporting
- 15 said force receiving member; and
- an urging member contacting said coupling member to urge said free end portion of said coupling member toward a downstream side with respect to the mounting direction,
- wherein said supporting member is provided with a retracted portion
- 20 by which an inclinable angle of said coupling member in a direction urged by said urging member is a maximum.

123. A cartridge according to Claim 122, wherein a width of said retracted portion measured in a direction perpendicular to the mounting direction is larger

25 than a diameter of said free end portion.

124. A cartridge according to claim 122 or 123, wherein said coupling member

includes an interconnecting portion between said free end portion and said connecting portion, said interconnecting portion having a diameter smaller than those of said free end portion and said connecting portion, and a width of said retracted portion measured in the mounting direction is larger than the diameter of interconnecting portion of said coupling member.

125. A cartridge according to any one of the claims 122 - 124, wherein in a state that said cartridge is mounted to the main assembly, said retracted portion is downstream of said engaging portion with respect to the mounting direction of said cartridge.

126. A cartridge according to any one of the claims 122 - 125, further comprising a through-hole penetrating said connecting portion and a shaft portion penetrating through the through-hole and capable of receiving the rotational force from said transmitting portion, wherein in a case that an axis of said shaft portion is perpendicular to an inclining direction of said coupling member when said coupling member is inclined toward said retracted portion by said urging member, the inclination of said coupling member is limited by contacting to a part of said force receiving member.

127. A cartridge according to any one of the claims 122 - 125, further comprising a through-hole penetrating said connecting portion and a shaft portion penetrating through the through-hole and capable of receiving the rotational force from said transmitting portion, wherein in a case that an axis of said shaft portion is parallel with an inclining direction of said coupling member when said coupling member is inclined toward said retracted portion by said urging member, the inclination of said coupling member is limited by contact between said

through-hole and said shaft portion.

128. A cartridge according to any one of the claims 122 - 125, further comprising a through-hole penetrating said connecting portion and a shaft portion
5 penetrating through the through-hole and capable of receiving the rotational force from said transmitting portion, wherein an angle of the inclination limited by said coupling member contacting the part of said force receiving member is larger than a angle of inclination limited by the contact between said through-hole and said shaft portion.

10

129. A cartridge according to any one of Claims 122 - 128, wherein said force receiving member includes a disengagement preventing portion for preventing disengagement of said coupling member by contacting to an outer periphery of said connecting portion.

15

130. A cartridge according to any one of Claims 122 - 129, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

20 131. A cartridge according to any one of Claims 122 - 130, wherein said rotatable member is a photosensitive member.

132. A cartridge mountable to a main assembly of an electrophotographic
25 image forming apparatus including a rotatable engaging portion, in a mounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

a rotatable member for carrying a developer; and

a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is provided with an accommodating portion therein;

5 a rotatable coupling member including a free end portion having a receiving portion for receiving a rotational force from the engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion to said force receiving member, wherein at least a part of said coupling member is accommodated in said accommodating
10 portion so that the rotational axis of said coupling member is pivotable relative to a rotational axis of said force receiving member, and wherein said coupling member is provided with a through-hole penetrating through said connecting portion; and

a shaft portion penetrating through said through-hole and capable of
15 receiving the rotational force from said transmitting portion,

wherein said shaft portion is supported by said force receiving member at the opposite end portions, and said cartridge further comprising an urging member contacting said coupling member to urge said free end portion of said coupling member toward a downstream side with respect to the mounting
20 direction.

133. A cartridge according to Claim 132, further comprising a supporting portion rotatably supporting said force receiving member, and a supporting member having a first projection for receiving an urging force when said
25 cartridge is mounted to the main assembly.

134. A cartridge according to Claim 132, wherein said urging member includes

a torsion coil spring, a supporting portion rotatably supporting said force receiving member, a second projection engaging with a coil portion of said torsion coil spring.

5 135. A cartridge according to Claim 134, wherein an arm extending from an outside portion of the coil portion of said torsion coil spring is engaged with said supporting member, and an arm extending from the inside portion of the coil portion of said torsion coil spring is contacted to said coupling member.

10 136. A cartridge according to Claim 132, further comprising a supporting member including a supporting portion rotatably supporting said force receiving member, a hole portion for exposing said free end portion to a outside of said cartridge, and a retracted portion to which said coupling member is capable of retracting, said retracted portion being provided downstream of said hole portion
15 with respect to the mounting direction.

137. A cartridge according to Claim 132, further comprising a supporting member having a supporting portion rotatably supporting said force receiving member, wherein said force receiving member is provided with an annular
20 groove portion in an outside surface of said cartridge, and said supporting portion of said supporting member contacts a side surface of said groove which is outside radially of said force receiving member.

138. A cartridge according to any one of Claims 132 - 137, wherein said force
25 receiving member includes a disengagement preventing portion for preventing disengagement of said coupling member by contacting to an outer periphery of said connecting portion.

139. A cartridge according to any one of Claims 132 - 138, wherein said free end portion is provided with projections extending in the direction of the rotational axis of the coupling member, and a number of the projections having
5 receiving portions for receiving the rotational force from said engaging portion is two, and such projections are provided at substantially point symmetry positions with respect to the rotational axis of the coupling member.

140. A cartridge according to Claim 139, wherein when an imaginary line
10 connecting said two projections is parallel with the mounting direction, the inclination of said coupling member is limited by contacting to a part of said force receiving member.

141. A cartridge according to any one of Claims 132 - 140, wherein said
15 coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

142. A cartridge according to any one of Claims 132 - 141, wherein said
20 rotatable member is a photosensitive member.

143. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus including a rotatable engaging portion, in a dismounting direction substantially perpendicular to a rotational axis of the engaging portion, said cartridge comprising:

25 a rotatable member for carrying a developer; and
a rotatable force receiving member for receiving the rotational force to be transmitted to said rotatable member, wherein said force receiving member is

provided with an accommodating portion therein;

a rotatable coupling member including a free end portion having a receiving portion for receiving a rotational force from the engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational
5 force received by said receiving portion to said force receiving member, wherein at least a part of said coupling member is accommodated in said accommodating portion so that the rotational axis of said coupling member is pivotable relative to a rotational axis of said force receiving member, and wherein said coupling member is provided with a through-hole penetrating through said connecting
10 portion; and

a shaft portion penetrating through said through-hole and capable of receiving the rotational force from said transmitting portion,

wherein said shaft portion is supported by said force receiving member at opposite end portions thereof, and said force receiving member
15 includes a disengagement preventing portion for preventing disengagement of said coupling member.

144. A cartridge according to Claim 143, further comprising a supporting member including a supporting portion rotatably supporting said force receiving
20 member, and a first projection for receiving an urging force when said cartridge is mounted to the main assembly.

145. A cartridge according to Claim 143, further comprising a torsion coil spring urging said coupling member toward an upstream side with respect to the
25 dismounting direction, and a supporting member including a supporting portion rotatably supporting said force receiving member and a second projection engaging with a coil portion of said torsion coil spring.

146. A cartridge according to Claim 145, wherein an arm extending from an outside portion of the coil portion of said torsion coil spring is engaged with said supporting member, and an arm extending from an inside portion of the coil
5 portion of said torsion coil spring is contacted to said coupling member.

147. A cartridge according to Claim 143, further comprising a supporting member including a supporting portion rotatably supporting said force receiving member, a hole portion for exposing said free end portion to an outside of said
10 cartridge, and a retracted portion to which said coupling member is capable of retracting, said retracted portion being provided downstream of said hole portion with respect to the mounting direction.

148. A cartridge according to Claim 143, further comprising a supporting
15 member having a supporting portion rotatably supporting said force receiving member, wherein said force receiving member is provided with an annular groove portion in an outside surface of said cartridge, and wherein a supporting portion of said supporting member contacts a side surface of said groove radially outside of said force receiving member to rotatably support said force receiving
20 member.

149. A cartridge according to any one of Claims 143 - 148, wherein said coupling member is capable of inclining toward a downstream with respect to the mounting direction by not less than approx. 20°.

25

150. A cartridge according to any one of Claims 143 - 149, wherein said rotatable member is a photosensitive member.

151. A cartridge comprising:

a frame;

a rotatable carrying member for carrying a developer;

5 a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and
movable between a first position in which the rotational axis of said coupling
member is coaxial with the axis of said rotatable member and a second position in
which the rotational axis of said coupling member is inclined relative to the
10 rotational axis of said rotatable member; and

an urging member urging said coupling member toward the second
position;

wherein said frame includes a retracted portion for permitting the
inclination of said coupling member in a direction urged by said urging member
15 at an inclination angle larger than an inclination angle of said coupling member in
another direction other than the urged direction.

152. A cartridge comprising:

a frame;

20 a rotatable carrying member for carrying a developer;

a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and
including a first portion provided with a through-hole and a second portion
remoter from said rotatable member than said first portion, said coupling member
25 being movable between a first position in which the rotational axis of said
coupling member is coaxial with the axis of said rotatable member and a second
position in which the rotational axis of said coupling member is inclined relative

to the rotational axis of said rotatable member;

a shaft portion penetrating said through-hole and having opposite end portions supported by said rotatable member; and

an urging member urging said coupling member toward the second
5 position.

153. A cartridge comprising:

a frame;

a rotatable carrying member for carrying a developer;

10 a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and

including a first portion provided with a through-hole and a second portion

remoter from said rotatable member than said first portion, said coupling member being movable between a first position in which the rotational axis of said

15 coupling member is coaxial with the axis of said rotatable member and a second position in which the rotational axis of said coupling member is inclined relative to the rotational axis of said rotatable member; and

a shaft portion penetrating said through-hole and having opposite end portions supported by said rotatable member,

20 wherein said rotatable member is provided with a disengagement preventing portion contactable to the first portion to prevent disengagement of said coupling member.

154. A cartridge comprising:

25 a frame;

a rotatable carrying member for carrying a developer;

a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and including a first portion provided with a through-hole and a second portion remoter from said rotatable member than said first portion, said coupling member being movable between a first position in which the rotational axis of said
5 coupling member is coaxial with the axis of said rotatable member and a second position in which the rotational axis of said coupling member is inclined relative to the rotational axis of said rotatable member; and

a shaft portion penetrating said through-hole and having opposite end portions supported by said rotatable member,

10 wherein when the rotational axis of said coupling member is inclined relative to an axis of said shaft portion, said shaft portion contacts said through-hole to limit the inclination of said coupling member, and

wherein the rotational axis of said coupling member is inclined relative to a direction perpendicular to an axis of said shaft portion, said frame
15 contacts to said coupling to limit the inclination of said coupling member in a case.

155. A cartridge comprising:

a frame;
20 a rotatable carrying member for carrying a developer;
a rotatable member rotatably supported by said frame;
a coupling member rotatable about a rotational axis thereof and including a first portion provided with a through-hole and a second portion remoter from said rotatable member than said first portion, said coupling member
25 being movable between a first position in which the rotational axis of said coupling member is coaxial with the axis of said rotatable member and a second position in which the rotational axis of said coupling member is inclined relative

to the rotational axis of said rotatable member;

a shaft portion penetrating said through-hole and having opposite end portions supported by said rotatable member; and

an angle formed between the rotational axis of said coupling member
5 and the rotational axis of said rotatable member when the inclination of said coupling member is limited by contact between said coupling member and said frame is larger than an angle formed between the rotational axis of said coupling member and the rotational axis of said rotatable member when the inclination of said coupling member is limited by contact between said shaft portion and said
10 through-hole.

156. A cartridge comprising:

a frame;

a rotatable carrying member for carrying a developer;

15 a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and

including a first portion provided with a through-hole and a second portion
remoter from said rotatable member than said first portion, said coupling member
being movable between a first position in which the rotational axis of said
20 coupling member is coaxial with the axis of said rotatable member and a second
position in which the rotational axis of said coupling member is inclined relative
to the rotational axis of said rotatable member; and

a shaft portion penetrating said through-hole and having opposite end portions supported by said rotatable member,

25 wherein said rotatable member is provided with a gear portion at an outer periphery thereof, and a portion where said frame rotatably supports said rotatable member and at least a part of said gear portion are overlapped along the

direction of the rotational axis of said rotatable member.

157. A cartridge comprising:

a frame;

5 a rotatable carrying member for carrying a developer;

a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and

including a first portion provided with a through-hole and a second portion

remoter from said rotatable member than said first portion, said coupling member

10 being movable between a first position in which the rotational axis of said

coupling member is coaxial with the axis of said rotatable member and a second

position in which the rotational axis of said coupling member is inclined relative

to the rotational axis of said rotatable member; and

a shaft portion penetrating said through-hole and having opposite end

15 portions supported by said rotatable member;

wherein said shaft portion includes an inclination regulating portion

contactable to said through-hole to limit the inclination of said coupling member,

and a rotation regulating portion contactable to said through-hole to limit rotation

of said coupling member when said coupling member rotates about the rotational

20 axis, and

wherein an angle through which said coupling member is inclinable in

a first imaginary plane including the rotational axis of said rotatable member and

an axis of said shaft portion is larger than an angle through which said coupling

member is inclinable in a second imaginary plane perpendicular to the first

25 imaginary plane.

158. A cartridge comprising:

a frame;
 a rotatable carrying member for carrying a developer;
 a rotatable member rotatably supported by said frame;
 a coupling member rotatable about a rotational axis thereof and
 5 including a first portion provided with a through-hole and a second portion
 remoter from said rotatable member than said first portion, said coupling member
 being movable between a first position in which the rotational axis of said
 coupling member is coaxial with the axis of said rotatable member and a second
 position in which the rotational axis of said coupling member is inclined relative
 10 to the rotational axis of said rotatable member; and

a shaft portion penetrating said through-hole and having opposite end
 portions supported by said rotatable member;

wherein said rotatable member includes a first member having a
 disengagement preventing portion for preventing disengagement of said coupling
 15 member by movement in a direction away from said carrying member, and a
 second member connected with said first member, and opposite end portions of
 said shaft portion are supported by said first member and said second member.

159. A cartridge comprising:

20 a frame;
 a rotatable carrying member for carrying a developer;
 a rotatable member provided with a gear portion at an outer periphery
 thereof and rotatably supported by said frame; and
 a coupling member rotatable about a rotational axis thereof and
 25 movable between a first position in which the rotational axis of said coupling
 member is coaxial with the axis of said rotatable member and a second position in
 which the rotational axis of said coupling member is inclined relative to the

rotational axis of said rotatable member;

wherein said rotatable member includes an accommodating portion for accommodating a part of said coupling member, and said rotatable member is provided with an annular groove portion in an outside surface of said cartridge in
5 a direction of the rotational axis of said rotatable member between said gear portion and said accommodating portion.

160. A cartridge comprising:

a frame;
10 a rotatable carrying member for carrying a developer;
a rotatable member rotatably supported by said frame;
a coupling member rotatable about a rotational axis thereof and
including a first portion provided with a through-hole, a second portion remoter
from said rotatable member than said first portion, and a projection projecting
15 from said second portion, said coupling member being movable between a first
position in which the rotational axis of said coupling member is coaxial with the
axis of said rotatable member and a second position in which the rotational axis
of said coupling member is inclined relative to the rotational axis of said rotatable
member;
20 a shaft portion penetrating said through-hole and having opposite end
portions supported by said rotatable member; and
a frame projection projecting from an end surface of said frame in a
side where said coupling member is provided outwardly of said frame,
wherein in a state that the rotational axis of said coupling member is
25 inclined relative to the rotational axis of said rotatable member and the inclination
of said coupling member is limited by contact between said shaft portion and said
through-hole, said projection is more inside than said frame projection in a

direction of the rotational axis of said rotatable member.

161. A cartridge comprising:

a frame;

5 a rotatable carrying member for carrying a developer;

a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and

including a first portion provided with a through-hole, a second portion remoter

from said rotatable member than said first portion, and a projection projecting

10 from said second portion, said coupling member being movable between a first

position in which the rotational axis of said coupling member is coaxial with the

axis of said rotatable member and a second position in which the rotational axis

of said coupling member is inclined relative to the rotational axis of said rotatable
member;

15 a shaft portion penetrating said through-hole and having opposite end

portions supported by said rotatable member; and

a frame projection projecting from an end surface of said frame in a
side where said coupling member is provided outwardly of said frame,

20 wherein in a state that coupling member is in the first position, said
projection of said coupling member is in a more outside position than said frame
projection in a direction of the rotational axis of said rotatable member.

162. A cartridge comprising:

a frame;

25 a rotatable carrying member for carrying a developer;

a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and

including a first portion provided with a through-hole, a second portion remoter from said rotatable member than said first portion, and a third portion remoter from said rotatable member than said second portion and having a projection, said coupling member being movable between a first position in which the rotational axis of said coupling member is coaxial with the axis of said rotatable member and a second position in which the rotational axis of said coupling member is inclined relative to the rotational axis of said rotatable member;

a shaft portion penetrating said through-hole and having opposite end portions supported by said rotatable member; and

a maximum rotation diameter of said coupling member in said first portion around the rotational axis is larger than a maximum rotation diameter of said coupling member in said third portion around the rotational axis.

163. A cartridge comprising:

a frame;

a rotatable carrying member for carrying a developer;

a rotatable member rotatably supported by said frame;

a coupling member rotatable about a rotational axis thereof and movable between a first position in which the rotational axis of said coupling member is coaxial with the axis of said rotatable member and a second position in which the rotational axis of said coupling member is inclined relative to the rotational axis of said rotatable member;

an urging member for urging said coupling member toward the second position; and

a supporting member including a frame projection projecting from an end surface in a side of said frame where said coupling member is provided and a mounting projection for mounting said urging member on the same surface as

said frame projection,

wherein said frame projection projects to a more outside of cartridge than said mounting projection.

5 164. A cartridge comprising:

a frame;

a photosensitive drum;

a developing roller for developing a latent image formed on the photosensitive drum;

10 a flange mounted to an end portion of said photosensitive drum; and

a coupling member pivotably held by said flange,

wherein said frame is provided with a hole portion for exposing said coupling member to an outside of cartridge, and a groove portion provided in a surface provided with said hole portion and continuously extending from said hole portion in the direction away from the rotation axis of said developing roller.

165. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion rotatably provided in the main assembly, wherein a rotatable coupling member is mountable to said cartridge, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided with a through-hole, wherein said coupling member is mountable to said cartridge by holding opposite end portions of a shaft penetrating the through-hole, said cartridge comprising:

a frame;

a cylinder having a photosensitive layer;
a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member; and
5 a bearing member mounted to said frame and having a supporting portion for rotatably supporting said flange,
wherein said flange includes a holding portion for holding the opposite end portions of the shaft penetrating said through-hole, and a disengagement preventing portion for limiting disengagement of the coupling
10 member by contact to an outer periphery of the connecting portion.

166. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion rotatably provided in the
15 main assembly, wherein a rotatable coupling member is mountable to said cartridge, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, wherein said coupling member is mountable to said cartridge
20 by holding opposite end portions of a shaft penetrating the through-hole, said cartridge comprising:

a frame;
a cylinder having a photosensitive layer;
a flange mounted to an end portion of said cylinder, said flange being
25 provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member; and
a bearing member mounted to said frame and having a supporting

portion for rotatably supporting said flange,

wherein said flange is provided with an annular groove portion in said accommodating portion outside with respect to a radial direction of said flange, and said supporting portion contacts an outside side surface of said groove portion with respect to a radial direction of said flange.

167. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion rotatably provided in the main assembly, wherein a rotatable coupling member is mountable to said cartridge, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided with a through-hole, wherein said coupling member is mountable to said cartridge by holding opposite end portions of a shaft penetrating the through-hole, said cartridge comprising:

a cylinder having a photosensitive layer; and

a flange mounted to an end portion of said cylinder and including an accommodating portion capable of accommodating the connecting portion and pivotably holding the coupling member, a holding portion holding opposite end portions of the shaft penetrating the through-hole,

wherein when the coupling member held by said holding portion is inclined to an axial direction, the inclination of the coupling member is limited by contact between the through-hole and the shaft, and when the coupling member is inclined to a direction perpendicular to the axial direction, said flange contacts to the coupling member to regulate the inclination of the coupling member.

168. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion rotatably provided in the main assembly, wherein a rotatable coupling member is mountable to said cartridge, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided with a through-hole, wherein said coupling member is mountable to said cartridge by holding opposite end portions of a shaft penetrating the through-hole, said cartridge comprising:

- a frame;
- a cylinder having a photosensitive layer;
- a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member; and
- a bearing member mounted to said frame and having a supporting portion for rotatably supporting said flange,

wherein said bearing member includes a first projection for receiving an urging force from the main assembly in a state that said cartridge is mounted to the main assembly and a second projection for mounting a coil portion of a torsion coil spring, said second projection projecting from the same surface of said frame as the first projection outwardly along a rotational axis direction of said cylinder, and

wherein said first projection projects more outwardly of the cartridge than said second projection.

169. A cartridge dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion rotatably provided in the main assembly, wherein a rotatable coupling member is mountable to said cartridge, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided with a through-hole, wherein said coupling member is mountable to said cartridge by holding opposite end portions of a shaft penetrating the through-hole, said cartridge comprising:

- a frame;
- a cylinder having a photosensitive layer;
- 15 a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member; and
- a bearing member mounted to said frame and having a supporting portion for rotatably supporting said flange,
- 20 wherein said flange is provided with a holding portion for holding opposite end portions of the shaft penetrating the through-hole and a gear portion for transmitting a driving force, wherein said holding portion, said supporting portion and said gear portion overlap along the rotational axis of said flange.

25 170. A cartridge usable with a main assembly of the electrophotographic image forming apparatus, said apparatus including an rotatable engaging portion and a coupling guide provided in a rear side of a rotational axis of said engaging

portion, said cartridge being mountable to the main assembly by moving in a mounting direction substantially perpendicular to a rotational axis of said engaging portion, wherein a coupling member is mountable to said cartridge, said cartridge comprising:

- 5 a frame;
- a cylinder having a photosensitive layer;
- a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member; and
- 10 a bearing member mounted to said frame and having a supporting portion for rotatably supporting said flange,
- wherein said bearing member is provided with a hole portion for exposing a free end portion to an outside, and a groove portion continuously extending from said hole portion toward a downstream side with respect to the
- 15 mounting direction.

171. A drum unit dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion

20 rotatably provided in the main assembly, wherein a rotatable coupling member is mountable to said drum unit, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided

25 with a through-hole, wherein said coupling member is mountable to said drum unit by holding opposite end portions of a shaft penetrating the through-hole, said drum unit comprising:

a cylinder having a photosensitive layer; and

a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member, an
5 annular groove portion in said accommodating portion outside with respect to a radial direction of said cylinder, and a holding portion for holding the opposite end portions of the shaft penetrating said through-hole,

wherein said groove portion and said holding portion overlap along a rotational axis direction of said cylinder.

10

172. A drum unit dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion rotatably provided in the main assembly, wherein a rotatable coupling member is
15 mountable to said drum unit, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided with a through-hole, wherein said coupling member is mountable to said drum
20 unit by holding opposite end portions of a shaft penetrating the through-hole, said drum unit comprising:

a cylinder having a photosensitive layer; and

a flange mounted to an end portion of said cylinder and including an accommodating portion capable of accommodating the connecting portion and
25 pivotably holding the coupling member, a holding portion holding opposite end portions of the shaft penetrating the through-hole;

wherein when the coupling member held by said holding portion is

inclined to an axial direction, the inclination of the coupling member is limited by contact between the through-hole and the shaft, and

wherein said flange includes a limiting portion contactable to coupling member to limit an inclination of coupling member when the coupling member
5 inclines in a direction perpendicular to the axial direction.

173. A drum unit dismountable from a main assembly of an electrophotographic image forming apparatus by moving in a predetermined direction substantially perpendicular to a rotational axis of an engaging portion
10 rotatably provided in the main assembly, wherein a rotatable coupling member is mountable to said drum unit, the coupling including a free end portion having a receiving portion for receiving a rotational force from said engaging portion, and a connecting portion having a transmitting portion for transmitting the rotational force received by said receiving portion, said connecting portion being provided
15 with a through-hole, wherein said coupling member is mountable to said drum unit by holding opposite end portions of a shaft penetrating the through-hole, said drum unit comprising:

a cylinder having a photosensitive layer; and

a flange mounted to an end portion of said cylinder, said flange being
20 provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member, a holding portion for holding the opposite end portions of the shaft penetrating said through-hole, and a disengagement preventing portion for preventing disengagement of the coupling member by contact to the connecting portion of
25 coupling member.

174. A drum unit to which a coupling member is capable of being mounted by

holding opposite end portions of a shaft penetrating through a through-hole of a connecting portion of the coupling member, said drum unit comprising:

a cylinder having a photosensitive layer; and

a flange mounted to an end portion of said cylinder, said flange being
5 provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member, an annular groove portion provided in an outside of said accommodating portion outside with respect to a radial direction of said cylinder, and a holding portion for holding the opposite end portions of the shaft penetrating said through-hole,
10 wherein said groove portion and said holding portion overlap along a rotational axis direction of said cylinder.

175. A drum unit to which a coupling member is capable of being mounted by holding opposite end portions of a shaft penetrating through a through-hole of a connecting portion of the coupling member, said drum unit comprising:

a cylinder having a photosensitive layer; and

a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member, and a
20 holding portion for holding the opposite end portions of the shaft penetrating said through-hole,

wherein when a rotational axis of the coupling member held in said accommodating portion is inclined toward an axial direction of the held by said holding portion, the inclination of the coupling member is limited by the shaft
25 contacting to the through-hole, and

wherein said flange is provided with a limiting portion contactable to the coupling member to limit the inclination of the coupling member.

176. A drum unit to which a coupling member is capable of being mounted by holding opposite end portions of a shaft penetrating through a through-hole of a connecting portion of the coupling member, said drum unit comprising:

- 5 a cylinder having a photosensitive layer; and
- a flange mounted to an end portion of said cylinder, said flange being provided with an accommodating portion capable of accommodating the connecting portion and capable of pivotably holding coupling member, a holding portion for holding the opposite end portions of the shaft penetrating said
- 10 through-hole, and a disengagement preventing portion for preventing disengagement of the coupling member by contact to the connecting portion of coupling member.

177. A drum unit comprising:

- 15 a cylinder having a photosensitive layer;
- a flange for receiving a rotational force to be transmitted to said cylinder, said flange including an accommodating portion in an inside thereof and being mounted to an end portion of said cylinder;
- a coupling member including a first portion at least a part of which is
- 20 accommodated in said accommodating portion and which is provided with a through-hole, and a second portion remoter from said cylinder than said first portion, said coupling member being rotatable about a rotational axis, and said coupling member being movable between a first position in which the rotational axis of said coupling member is coaxial with the axis of said flange and a second
- 25 position in which the rotational axis of said coupling member is inclined relative to the rotational axis of said flange; and
- a shaft portion penetrating said through-hole,

wherein said flange includes a holding portion holding opposite end portions of the shaft portion, and a disengagement preventing portion for preventing disengagement of said coupling member by contacting to said first portion.

5

178. A drum unit comprising:

a cylinder having a photosensitive layer;

a flange for receiving a rotational force to be transmitted to said cylinder, said flange including an accommodating portion in an inside thereof and
10 being mounted to an end portion of said cylinder;

a coupling member including a first portion at least a part of which is accommodated in said accommodating portion and which is provided with a through-hole, a second portion remoter from said cylinder than said first portion, said coupling member being rotatable about a rotational axis, and said coupling
15 member being movable between a first position in which the rotational axis of said coupling member is coaxial with the axis of said flange and a second position in which the rotational axis of said coupling member is inclined relative to the rotational axis of said flange; and

a shaft portion penetrating said through-hole,

20 wherein when a rotational axis of the coupling member is inclined toward an axial direction of the held by said holding portion, the inclination of the coupling member is limited by the shaft contacting to the through-hole, and

wherein said flange includes a holding portion holding opposite end portions of the shaft portion, and a regulating portion contactable to the coupling
25 to limit the inclination of the coupling member when the rotational axis of said coupling member is inclined toward a direction perpendicular to an axis of the shaft portion.

179. A drum unit comprising:

a cylinder having a photosensitive layer;

a flange for receiving a rotational force to be transmitted to said
5 cylinder, said flange including an accommodating portion in an inside thereof and
being mounted to an end portion of said cylinder;

a coupling member including a first portion at least a part of which is
accommodated in said accommodating portion and which is provided with a
through-hole, a second portion remoter from said cylinder than said first portion,
10 said coupling member being rotatable about a rotational axis, and said coupling
member being movable between a first position in which the rotational axis of
said coupling member is coaxial with the axis of said flange and a second
position in which the rotational axis of said coupling member is inclined relative
to the rotational axis of said flange; and

15 a shaft portion penetrating said through-hole,

wherein said flange includes a first member having a disengagement
preventing portion for preventing disengagement of said coupling member by
moving away from said cylinder, and a second member connecting with said first
member, and opposite end portions of the shaft portion are supported by said first
20 member and said second member, respectively.

180. A drum unit comprising:

a cylinder having a photosensitive layer;

a flange for receiving a rotational force to be transmitted to said
25 cylinder, said flange including an accommodating portion in an inside thereof and
being mounted to an end portion of said cylinder;

a coupling member including a first portion at least a part of which is

accommodated in said accommodating portion and which is provided with a through-hole, a second portion remoter from said cylinder than said first portion, and a third portion remoter from said cylinder than said second portion and provided with a projection, said coupling member being rotatable about a rotational axis, and said coupling member being movable between a first position in which the rotational axis of said coupling member is coaxial with the axis of said flange and a second position in which the rotational axis of said coupling member is inclined relative to the rotational axis of said flange; and

a shaft portion penetrating said through-hole,
 wherein said flange includes a holding portion for holding opposite end portions of the shaft portion, and a maximum rotation diameter of said coupling member around the rotational axis in the first portion of said coupling member is larger than a maximum rotation diameter of said coupling member around the rotational axis in said third portion.

15

181. A force receiving member mountable to an end portion of a cylindrical portion of a photosensitive cylinder, said force receiving member comprising:

a first cylindrical portion provided radially outside;
 a second cylindrical portion provided radially inside relative to said first cylindrical portion; and

20

a second cylindrical portion having an inside hollow portion and a recess connecting with said hollow portion in a radial direction and opening toward the cylinder along a rotational axis of said force receiving member, and an annular groove portion provided between said first cylindrical portion and said second cylindrical portion,

25

wherein said first cylindrical portion, said annular groove portion and said recess overlap in a rotational axis direction of said force receiving member.

182. A force receiving member according to Claim 181, wherein said first cylindrical portion includes a gear.

5 183. A force receiving member according to Claim 182, wherein said gear is a helical gear along said force receiving member.

184. A force receiving member according to Claim 181, wherein said second cylindrical portion includes an overhang portion projecting toward said hollow
10 portion along said force receiving member.

185. A force receiving member according to Claim 181, wherein said second cylindrical portion includes a projection projecting radially outwardly.

15 186. A flange unit mountable to an end portion of a cylindrical portion of a photosensitive cylinder, said flange unit comprising:

a shaft portion; and

a force receiving member including a first cylindrical portion provided radially outside, a second cylindrical portion having an inside hollow portion and
20 a recess connecting with said hollow portion in a radial direction and accommodating the shaft portion, and an annular groove portion provided between said first cylindrical portion and said second cylindrical portion,

wherein said first cylindrical portion, said annular groove portion and said recess overlap in a rotational axis direction of said force receiving member.

25

187. A flange unit mountable to an end portion of a cylindrical portion of a photosensitive cylinder, said flange unit comprising:

a shaft portion; and

a force receiving member including a first cylindrical portion provided radially outside; a second cylindrical portion having an inside hollow portion and a recess connecting with said hollow portion in a radial direction, and an annular
5 groove portion provided between said first cylindrical portion and said second cylindrical portion, and a regulating member having a regulating portion,

wherein said shaft portion is held by said recess and said regulating portion, and said first cylindrical portion and said annular groove portion overlap in the rotational axis direction of said force receiving member.

10

188. A cartridge according to Claim 10, wherein an attitude of said coupling member is regulated by contacting to a lower side surface of said groove portion with respect to a direction of gravity.

15




Fig. 1

2/32




Fig. 2

3/32




Fig. 3

4/32





Fig. 4

5/32




Fig. 5

6/32




Fig. 6

7/32




Fig. 7

8/32




Fig. 8

9/32




Fig. 9

10/32





Fig. 10

11/32




Fig. 11






Fig. 12



14/32




Fig. 14

15/32




Fig. 15

16/32




Fig. 16

17/32




Fig. 17

18/32





Fig. 18

19/32




Fig. 19




Fig. 20

20/32





Fig. 21




Fig. 22

22/32







Fig. 23




Fig. 24

24/32





Fig. 25

25/32




Fig. 26

26/32




Fig. 27

27/32




Fig. 28





Fig. 29

29/32



30/32




Fig. 31

31/32




Fig. 32




Fig. 33

