




(86) Date de dépôt PCT/PCT Filing Date: 2018/01/08
(87) Date publication PCT/PCT Publication Date: 2018/11/29
(45) Date de délivrance/Issue Date: 2022/08/16
(85) Entrée phase nationale/National Entry: 2019/09/12
(86) N° demande PCT/PCT Application No.: CN 2018/071730
(87) N° publication PCT/PCT Publication No.: 2018/214517
(30) Priorité/Priority: 2017/05/25 (CN2017103788528)

(51) Cl.Int./Int.Cl. *E05F 3/06* (2006.01),
E05F 3/20 (2006.01)
(72) Inventeurs/Inventors:
LIANG, YELIN, CN;
LAO, QINGJUN, CN;
ZHU, HAIHUI, CN
(73) Propriétaire/Owner:
LIANG, PEILING, CN
(74) Agent: BROUILLETTE LEGAL INC.

(54) Titre : CHARNIERE DE PORTE A FONCTION D'AMORTISSEMENT
(54) Title: DOOR HINGE HAVING BUFFERING FUNCTION



(57) Abrégé/Abstract:

Disclosed is a door hinge having a buffering function, including: a casing (1) within which a damper (3) is disposed in an axially movable manner, an end portion of a piston rod at the front end of the damper (3) being fixedly connected to the casing (1); a hinge cup (10); a linking member A (5) with a right end rotatably disposed inside the casing (1) via a first rotating shaft (4) and a left end rotatably connected to the hinge cup (10) via a third rotating shaft; and a connecting member B (8) with a right end rotatably disposed inside the casing (1) via a second rotating shaft (7) and a left end rotatably connected to the hinge cup (10) via a fourth rotating shaft. The end portion at the right end of the linking member A (5) or the connecting member B (8) is disposed corresponding to the rear end of the damper (8). The moving direction of the damper (3) is same as that of the linking member A (5) or the connecting member B (8), which greatly extends the stroke of the linking member A (5) or the connecting member B (8), thus achieving a better technical effect of buffering.

ABSTRACT

Disclosed is a door hinge having a buffering function, including: a casing (1) within which a damper (3) is disposed in an axially movable manner, an end portion of a piston rod at the front end of the damper (3) being fixedly connected to the casing (1); a hinge cup (10); a linking member A (5) with a right end rotatably disposed inside the casing (1) via a first rotating shaft (4) and a left end rotatably connected to the hinge cup (10) via a third rotating shaft; and a connecting member B (8) with a right end rotatably disposed inside the casing (1) via a second rotating shaft (7) and a left end rotatably connected to the hinge cup (10) via a fourth rotating shaft. The end portion at the right end of the linking member A (5) or the connecting member B (8) is disposed corresponding to the rear end of the damper (8). The moving direction of the damper (3) is same as that of the linking member A (5) or the connecting member B (8), which greatly extends the stroke of the linking member A (5) or the connecting member B (8), thus achieving a better technical effect of buffering.

DOOR HINGE HAVING BUFFERING FUNCTION

FIELD

The disclosure relates to the field of door hinge technologies, and more particularly, to a door hinge having a buffering function.

BACKGROUND

The wide application of door hinges is well known. Although it is relatively traditional hardware, it has also undergone a technological development process. A more primitive door hinge, such as a loose-leaf, is set such that it has no buffering effect when a door is opened and closed, resulting in that the door collides with walls and other objects, which has a poor use effect.

In order to effectively solve the technical problem above, a door hinge having a buffering function has emerged at the right moment. For example, the Chinese invention patent with the application publication number CN105604423A discloses a door hinge having a buffering function, which includes a casing, a buffering shaft and a first torsion spring. The buffering shaft, with a buffering block arranged thereon, is rotatably disposed in the casing. The first torsion spring is sleeved on the buffering shaft, with one end of the first torsion spring abutted against the casing and the other end of the first torsion spring abutted against the buffering block on the buffering shaft. The prior art further includes a second torsion spring, a linking member and a second rotating shaft. The linking member has one end rotationally connected to a hinge cup via the other shaft of the U-shaped rotating shaft and the other end rotationally disposed in the casing via the second rotating shaft. An end portion of the buffering block may be abutted with the linking member. The prior art above achieves the buffering effect by cooperation of the linking member and the buffering block, which effectively solves the technical problem of the traditional technologies. However, the prior art still has the technical defects as follows. The buffering block rotates with the buffering shaft as a center, thus the linking member has a short stroke when the buffering block is abutted with the linking member, resulting in a yet poor buffering effect.

Therefore, there still has a room for improvement in the prior art.

SUMMARY

The disclosure is intended to provide a door hinge having a buffering function, which

has the advantages of reasonable structural disposition, good buffering effect and the like.

In order to achieve the objects above, the following technical solutions are adopted in the disclosure.

The door hinge having a buffering function according to the disclosure includes: a casing in which a damper is disposed in an axially movable manner, an end portion of a piston rod at a front end of the damper being fixedly connected to the casing; a hinge cup; a linking member A with a right end rotatably disposed in the casing via a first rotating shaft and a left end rotatably connected to the hinge cup via a third rotating shaft; and a connecting member B with a right end rotatably disposed inside the casing via a second rotating shaft and a left end of the connecting member B rotatably connected to the hinge cup via a fourth rotating shaft, the second rotating shaft being sleeved with a torsion spring with one end fixed to or abutted against the fourth rotating shaft and the other end abutted against the casing, one of an end portion at the right end of the linking member A and an end portion at a right end of the connecting member B being disposed corresponding to a rear end of the damper.

The casing is provided with a positioning block at an inner wall at both front and rear sides, two sliding slots are formed between two positioning blocks and a top wall of the casing, and the damper is disposed, by both sides of the damper, in the two sliding slots in an axially slidable manner.

The damper is provided with a positioning slider at both sides, and the damper is in slide fit with the two sliding slots correspondingly via the positioning slider at both sides.

The casing is internally and fixedly provided with a positioning shaft, the end portion of the piston rod of the damper is provided with a hook, and the hook is hung on the positioning shaft for positioning.

A top portion of the casing is provided with a downwardly extending clamping piece, the end portion of the piston rod of the damper is provided with a clamping slot, and the clamping slot is clamped on the clamping piece for positioning.

An end portion at the rear end of the damper is provided with a stopper, the end portion at the right end of the linking member A is provided with a driving member corresponding to the stopper.

The driving member is a pushing block or a lifting hook.

An end portion at the rear end of the damper is provided with an inclined surface, the

end portion at the right end of the connecting member B is provided with a driving member corresponding to the inclined surface.

The driving member is a pushing block matched with the inclined surface.

One of the end portion at the right end of the linking member A or the end portion at the right end of the connecting member B is provided with the driving member, and the end portion at the rear end of the damper is hinged with the driving member.

The positioning block is an inwardly bent folding piece or bulge punched and inwardly stamped at front and rear sides of the casing respectively.

The third rotating shaft and the fourth rotating shaft are integrally formed into a U-shaped rotating shaft.

Beneficial effects

According to the disclosure, the damper is disposed in the casing in an axially movable manner, and the end portion of the piston rod at the front end of the damper is fixedly connected to the casing; and the end portion at the right end of the linking member A or the end portion at the right end of the connecting member B is disposed corresponding to the rear end of the damper. The damper of the disclosure has the same moving direction as the linking member A or the connecting member B, which greatly extends a stroke of the linking member A or a stroke of the connecting member B, thus achieving a better buffering technical effect.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a decomposed structure diagram of a first embodiment of the disclosure;

Fig. 2 is an overall structure diagram of the first embodiment of the disclosure;

Fig. 3 is a sectional view of A-A in Fig. 2;

Fig. 4 is a sectional view of B-B in Fig. 2;

Fig. 5 is a structure diagram of the first embodiment of the disclosure without a casing and a connecting member;

Fig. 6 is a decomposed structure diagram of another implementation of the first embodiment of the disclosure;

Fig. 7 is a decomposed structure diagram of a second embodiment of the disclosure; and

Fig. 8 is an assembly structure diagram of partial components according to the second

embodiment of the disclosure.

In the drawings: 1 refers to casing; 2 refers to positioning shaft; 3 refers to damper; 4 refers to first rotating shaft; 5 refers to linking member A; 6 refers to torsion spring; 7 refers to second rotating shaft; 8 refers to connecting member B; 9 refers to U-shaped rotating shaft; 10 refers to hinge cup; 11 refers to positioning block; 12 refers to sliding slot; 13 refers to clamping piece; 14 refers to driving member; 31 refers to positioning slider; 32 refers to hook; 33 refers to stopper; 34 refers to clamping slot; and 35 refers to inclined surface.

DETAILED DESCRIPTION OF THE EMBODIMENTS

The technical solutions of the disclosure are further described below with reference to the drawings.

Embodiment 1

As shown in Fig. 1 to Fig. 6, a door hinge having a buffering function according to the disclosure includes a casing 1, a hinge cup 10, a linking member A 5 and a connecting member B 8, wherein a damper 3 is disposed in the casing 1 in an axially movable manner, an end portion of a piston rod at a front end of the damper 3 is fixedly connected to the casing 1. Above are the main components of the disclosure, and form a basic structure of the disclosure.

A right end of the linking member A 5 is rotatably disposed in the casing 1 via a first rotating shaft 4, while a left end of the linking member A 5 is rotatably connected to the hinge cup 10 via a third rotating shaft. A right end of the connecting member B 8 is rotatably disposed inside the casing 1 via a second rotating shaft 7, while a left end of the connecting member B 8 is rotatably connected to the hinge cup 10 via a fourth rotating shaft.

A torsion spring 6 is sleeved on the second rotating shaft 7, one end of the torsion spring 6 is fixed to or abutted against the fourth rotating shaft, and the other end of the torsion spring 6 is abutted against the casing 1. An end portion at the right end of the linking member A 5 is disposed corresponding to a rear end of the damper 3.

In particular, in order to improve an integration level of products and simplify assembly procedures, the third rotating shaft and the fourth rotating shaft may be integrally formed into a U-shaped rotating shaft 9.

The casing 1 and the hinge cup 10 are respectively fixed on a door and a doorframe

during use. When the door is opened, the end portion at the right end of the linking member A 5 drives the damper 3 to move rightward to achieve a better buffering effect. When the door is closed, the torsion spring 6 is compressed, and the damper 3 moves leftward along with the linking member A 5 to achieve a better buffering effect. According to the disclosure, directions in which the linking member A 5 and the damper 3 move are in the same straight line, which has a large stroke, and compared with the prior art, has a better buffering effect.

The damper 3 is disposed in the casing 1 in an axially movable manner, specifically inner walls at front and rear sides of the casing 1 are respectively provided with a positioning block 11, two sliding slots 12 are formed between the two positioning blocks 11 and a top wall of the casing 1, and two sides of the damper 3 are disposed in the corresponding two sliding slots 12 in an axially slidable manner. In order to improve operability and flexibility, the two sides of the damper 3 are respectively provided with a positioning slider 31, and the damper 3 is in slide fit with the two sliding slots 12 correspondingly via the positioning sliders 31 on the two sides. In this way, it is simple in structure, greatly reduces the manufacturing cost, and facilitates the assembly and disassembly of the damper 3 at the same time, and the maintenance is simple and convenient, and has low cost.

It is worth mentioning that the positioning blocks 11 are inwardly bent folding pieces or bulges punched and inwardly stamped at front and rear sides of the casing 1 respectively. The structure so formed greatly simplifies the product structure, improves the operation reliability of products, and effectively reduces the cost.

An end portion of a piston rod at a front end of the damper 3 is fixedly connected to the casing 1, and specifically, two different implementations are used in the embodiment.

The first implementation is that: the casing 1 is internally and fixedly provided with a positioning shaft 2, the end portion of the piston rod of the damper 3 is provided with a hook 32, and the hook 32 is hung on the positioning shaft 2 for positioning.

The second implementation is that: a top portion of the casing 1 is provided with a downwardly extending clamping piece 13, the end portion of the piston rod of the damper 3 is provided with a clamping slot 34, and the clamping slot 34 is clamped on the clamping piece 13 for positioning.

In both implementations above, the end portion of the piston rod of the damper 3 is

detachably connected to the casing 1, which facilitates the assembly and disassembly of the damper 3, so that the maintenance is simple and convenient, and has the low cost.

An end portion at the rear end of the damper 3 is provided with a stopper 33, the end portion at the right end of the linking member A 5 is provided with a driving member 14 corresponding to the stopper 33. Regarding the corresponding relationship between the driving member 14 and the stopper 33, the embodiment may have three structures: 1. the driving member 14 is a pushing block and is disposed to be abutted with the stopper 33 to drive the damper 3 to move; 2. the driving member 14 is a lifting hook that can effectively hook the stopper 33 to drive the damper 3 to move; and 3. the driving member 14 is hinged with the stopper 33 to drive the damper 3 to move.

Embodiment II

Other structures of the embodiment are the same as those of the first embodiment, and will not be described again, except that the driving member 14 is disposed at the end portion at the right end of the connecting member B 8, and the damper 3 is driven by the driving member 14 to move axially through the rotation of the connecting member B 8.

Specifically, an end portion at the rear end of the damper 3 is provided with an inclined surface 35, the end portion at the right end of the connecting member B 8 is provided with a driving member 14 (a pushing block) corresponding to the inclined surface 35.

Specifically, the driving member 14 in the embodiment can be abutted and matched with the inclined surface 35, or the driving member 14 can also be hinged with the end portion at the rear end of the damper 3.

The embodiment also has a certain difference in technical effect from the first embodiment, a torsion spring 6 is sleeved on the second rotating shaft 7 of the connecting member B 8, and meanwhile, the end portion at the right end of the connecting member B 8 is provided with the driving member 14 corresponding to the damper 3, and when the door is opened or closed, the torsion spring 6 cooperates with the damper 3 more directly, thus having a better buffering effect.

The foregoing above is only the preferred embodiments of the disclosure. Therefore, all equivalent changes or modifications made according to the structure, features and principles described in the patent application scope of the disclosure shall all fall within the patent application scope of the disclosure.

CLAIMS

1. A door hinge having a buffering function, comprising:

a casing (1) in which a damper (3) is disposed in an axially movable manner, an end portion of a piston rod at a front end of the damper (3) being fixedly connected to the casing (1),

a hinge cup (10),

a linking member A (5) with a right end rotatably disposed in the casing (1) via a first rotating shaft (4) and a left end rotatably connected to the hinge cup (10) via a third rotating shaft, and

a connecting member B (8) with a right end rotatably disposed inside the casing (1) via a second rotating shaft (7) and a left end of the connecting member B (8) rotatably connected to the hinge cup (10) via a fourth rotating shaft, the second rotating shaft (7) being sleeved with a torsion spring (6) with one end fixed to or abutted against the fourth rotating shaft and the other end abutted against the casing (1), one of an end portion at the right end of the linking member A (5) and an end portion at a right end of the connecting member B (8) being disposed corresponding to a rear end of the damper (3);

wherein an end portion at the rear end of the damper (3) is provided with a stopper (33), the end portion at the right end of the linking member A (5) is provided with a driving member (14) corresponding to the stopper (33) and abutting against the stopper (33) of the damper (3) for driving the damper (3) to move.

2. The door hinge having a buffering function according to claim 1, wherein the casing (1) is provided with a positioning block (11) at an inner wall at both front and rear sides, two sliding slots (12) are formed between two positioning blocks (11) and a top wall of the casing (1), and the damper (3) is disposed, by both sides of the damper (3), in the two sliding slots (12) in an axially slidable manner.

3. The door hinge having a buffering function according to claim 2, wherein the damper (3) is provided with a positioning slider (31) at both sides, and the damper (3) is in slide fit with the two sliding slots (12) correspondingly via the positioning slider (31) at both sides.

4. The door hinge having a buffering function according to claim 1, wherein the casing (1) is internally and fixedly provided with a positioning shaft (2), the end portion of the piston rod of the damper (3) is provided with a hook (32), and the hook (32) is hung on

CLAIMS

the positioning shaft (2) for positioning.

5. The door hinge having a buffering function according to claim 1, wherein a top portion of the casing (1) is provided with a downwardly extending clamping piece (13), the end portion of the piston rod of the damper (3) is provided with a clamping slot (34), and the clamping slot (34) is clamped on the clamping piece (13) for positioning.

6. The door hinge having a buffering function according to claim 1, wherein the driving member (14) is a pushing block or a lifting hook which protrudes upwardly towards the damper (3).

7. The door hinge having a buffering function according to claim 1, wherein an end portion at the rear end of the damper (3) is provided with an inclined surface (35), the end portion at the right end of the connecting member B (8) is provided with a driving member (14) corresponding to the inclined surface (35).

8. The door hinge having a buffering function according to claim 7, wherein the driving member (14) is a pushing block matched with the inclined surface (35).

9. The door hinge having a buffering function according to claim 1, wherein one of the end portion at the right end of the linking member A (5) and the end portion at the right end of the connecting member B (8) is provided with a driving member (14), and the end portion at the rear end of the damper (3) is hinged with the driving member (14).

10. The door hinge having a buffering function according to claim 2, wherein the positioning block (11) is an inwardly bent folding piece or bulge punched and inwardly stamped at front and rear sides of the casing (1) respectively.

11. The door hinge having a buffering function according to claim 1, wherein the third rotating shaft and the fourth rotating shaft are integrally formed into a U-shaped rotating shaft (9).

1 / 4




Fig.1




Fig.2

2 / 4




Fig.3




Fig.4

3 / 4




Fig.5




Fig.6

4 / 4




Fig.7




Fig.8

