

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2016/030457 A1

(43) International Publication Date

3 March 2016 (03.03.2016)

WIPO | PCT

(51) International Patent Classification:

A61B 19/00 (2006.01) A61B 17/29 (2006.01)

(21) International Application Number:

PCT/EP2015/069628

(22) International Filing Date:

27 August 2015 (27.08.2015)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

14182381.5 27 August 2014 (27.08.2014) EP

(71) Applicant: STEERABLE INSTRUMENTS BVBA [BE/BE]; Poortakkerstraat 9c, B-9051 Sint-Denijs-Westrem (BE).

(72) Inventors: DEWAELE, Frank; Pruijnenbosstraat 13, B-9840 De Pinte (BE). MABILDE, Cyriel; Wallestraat 39, B-9700 Oudenaarde (BE). BLANCKAERT, Bart; Peperstraat F1, B-9900 Eeklo (BE). KALMAR, Alain; Gelukstraat 20, B-9000 Gent (BE). MAENE, Lieven; Zeedijk 681, bus 61, B-8300 Knokke (BE).

(74) Agents: GYI, Jeffrey Ivan et al.; De Clercq & Partners, E. Gevaertdreef 10a, 9830 Sint-Martens-Latem (BE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: TORQUE-TRANSMITTING STEERING MECHANISM FOR A STEERABLE TOOL




FIG. 20

(57) Abstract: A mechanical transmission system, MTS (100), for a steerable tool (500) which steerable tool (500) has a proximal end (20) and distal end (40) and comprises a shaft region (532), a bendable proximal part, BPP (534) that is omnidirectionally moveable, and a bendable distal part, BDP, (530) that is omnidirectionally moveable and moves responsive to movement of the BPP (534), which MTS (100) comprises a plurality of longitudinal members, LM (110) each having a proximal (20) and distal end (40), arranged in a longitudinal direction around a fictive tube (120), and has a corresponding transmission shaft region, TSR (132), transmission bendable proximal part, TBPP (134) and transmission bendable distal part, TBDP (130), wherein a plane section (114) of at least one LM (110) demonstrates an anisotropic area moment of inertia, and the majority of the LMs (110) are each axially rotationally constrained at 1 or more constraining points along the TBDP (130) or along the TSR (132) wherein the LMs are longitudinally slidable with respect to each discrete constraining point, and the MTS (100) is configured such that the BDP (530) tip is axially rotatable in a bent position by a complementary rotation of the BPP (534).

WO 2016/030457 A1

**TORQUE-TRANSMITTING STEERING MECHANISM FOR A STEERABLE TOOL****Background to the invention**

Since the 1980s, open surgery has been largely replaced by an endoscopic approach, whereby long-shaft instruments are inserted through trocars in a gas-extended abdomen.

- 5 Such laparoscopic surgery, known for its validated benefits of shorter hospitalization times, less post-operative pain, and earlier recovery, is more demanding for the surgeon.

A disadvantage of endoscopic surgery is reduced dexterity. This is mainly because of the fulcrum effect and the absence of wrist like movements at the tip of the instrument. Awareness of this disadvantage increases as more complex endoscopic procedures and 10 single-port surgeries, characterised by "sword fighting" of the instruments, are performed.

The fulcrum effect involves pivoting of the long-shaft instruments at the level of the trocar (pivot point) inserted in the abdomen. A movement of the handle to the left is translated as a movement to the right at the effector (e.g. a pair of scissors), and *vice versa*. Surgeons are able to quickly adapt to these inverted movements.

- 15 The lack of wrist-like movements is more difficult to overcome. A state-of-the-art solution is provided by the Da Vinci robot (Intuitive Surgical) where movements of the surgeons' hands at the console are transferred to fluent movements at the instruments' tip. This solution is expensive, leading to the development of cheaper hand instruments with an omni-directional articulated tip.

- 20 Much of the surgical challenge is attributable to the reduced dexterity. A conventional rigid laparoscopic instrument offers only 4 degrees of freedom (rotation, up/down angulations, left/right angulations, in/out movements). To overcome this restriction in movements, various designs for steerable instruments have been developed:

- 25 1. In its simplest form, an articulated instrument comprises a pre-bent flexible tube, that is slidably unsheathed from a rigid straight tube. This tip can only bend in one direction (uni-directional articulated instrument) and can only withstand a limited amount of lateral force.

- 30 2. More advanced alternatives are instruments that allow bending movements of the tip in one plane e.g. left to right and *vice versa*. Because of the nature of the construction, a mostly stable tip is created. These bi-directional instruments need to be navigated to a point of interest by bending into one direction and then by turning the whole instrument around its own axis. This lacks intuitiveness.

3. True wrist movements are only possible with omni-directional systems. The omnidirectional articulated instrument consists mainly of a proximal and distal end, a distal

bending part, a shaft region extending from the distal bending part, and optionally a proximal bending part. Movement of the proximal end is transferred to a movement at the distal end. Examples are described in US Patent Number: 7,410,483 (FIG. 11), and US Patent Number: 8,105,350 (FIG. 15).

- 5 Akin to robotic surgery, omni-directional articulated instruments provide up to 7 degrees of freedom (axial rotation and deflection of the tip in two planes are added to the 4 DOF of conventional rigid instruments). A combination of up/down and left/right movements at the proximal side allows any point at the distal effector side to be reached without the need for a rotation around its own axis. The increased maneuverability, however, is at the price of  
10 a significant decrease in tip stability. To solve this, hybrid solutions such as the Kymerax® system (Terumo) and Jaimy® system (EndoControl) compensate by using powerful electrical servo motors to restore the tip stability.

Omni-directional articulated instruments offer, in comparison to robotic systems, the advantages of low costs and tactile feedback.

- 15 The wrist of a surgical articulated instrument must be stable *i.e.* exhibit sufficient resistance the application of external forces. It has recently been studied by Chang Wook Jeong (Chang *et al.* Insufficient Joint Forces of First Generation Articulating Instruments for Laparoendoscopic Single-Site Surgery, Surgical Innovation 2012). He calculated that the instruments' wrist ideally withstands a minimal lateral force of 20N to be useful.  
20 This stability can be achieved by increasing the instruments' diameter, increasing the number, section of the steering wires, reducing the length of the wrist or by using stiffer material. However, where the desire for reduced invasiveness requires a minimised diameter, comprises are needed with existing technologies.

In surgery, perhaps the most important feature is rotational stability. The ability to transmit  
25 rotary motion from the shaft over the instruments' wrist to the end effector. For instance, the movement of throwing a suture in backhand cutting position requires an instrument that is bent over about 70° and still allows a rotary movement of the needle holder to protrude tissues with the round needle.

A surgical instrument is considered omni-directional if using the orientation of the shaft as  
30 a reference, the bendable distal end part can move freely within a full cone angle. Typically a ball and socket joint is used. This is a 3 DOF joint that allows movements such as pitch (up-down), roll (left-right) and yaw (rotation). In order to allow rotary motion to be transmitted the rotational movement in the joint is ideally be constrained, for instance, using a pin and groove. An arcuate groove is provided in the socket and extends in a

plane passing generally through the center of the ball and receives a pin which it is pivotally connected to the adjacent side of the ball. Another way is the use of a faceted ball and socket. The facets and edges block the axial rotation, however they reduce the angulation of some lateral orientations.

- 5 There are numerous ways in which a concatenation of revolute joints can be assembled to mimic the behaviour of a ball and socket joint. For instance, a universal joint is like a ball and socket joint, except it is constrained by one degree of rotational freedom. Two fork axes are joined together by a cross, the cross maintains these axes at 90 degrees, so if torque is applied to axis 1, axis 2 will rotate. A universal joint is equivalent to a hinge-2
- 10 10 joint where the hinge-2's axes are perpendicular to each other, and with a perfectly rigid connection in place. In articulated surgical instruments or articulated endovascular catheters, a universal joint is often achieved by a concatenation of flexible hinges that are oriented 90° to each other.

15 Omni-direction movement can be achieved using a kinematic chain that is an assembly of tandemly arranged links. A link is a rigid body which possesses points for attachment to other links. In human physiology, links can be seen as discs, vertebrae, or bones. A joint is a connection between links. A kinematic pair is a combination of two links with a joint in between. A kinematic chain is an assembly of links and joints. The instruments' wrist is the kinematic chain between shaft and end effector.

20 An interesting observation is that although the rotational freedom between two links is constrained, a kinematic chain containing such links can be forced into a configuration so that first and last links are rotated in respect of each other. When as all links and joints remain on one line, the rotary motion is transmitted without slack, and the first and last link maintain the same orientation. However, when the kinematic chain follows a spiral path a 25 significant rotation between first and last link may occur. Omni-directional instruments based on a concatenation of (flexible) revolute joints are also prone to this phenomenon. In the case of surgical instruments this results in a rotation between shaft and end bendable distal part. In surgery this loss of revolute transmission is highly undesirable.

30 One solution in the art to reduce the 'spiral kinematic chain effect' is to reduce the number of links. US 2012/0220831 describes a multi-disc wrist joint with only 5 links and 4 joints. They claim that the tool has no singularity in roll, pitch or yaw. So the movements are smooth. This is true for robotic applications where every joint can be controlled individually. Additionally, corrections are easily made by means of appropriate inverse kinematics implemented in the computer controller. Using hand controlled instruments,

the joints are hard to control especially if individual joints need to bent over 45°. They become 'notchy' and difficult to turn when operated at extreme angles.

The aim of the present invention is to provide a mechanical transmission system for a steerable instrument that overcomes one or more of the problems in the prior art.

## 5 Some embodiments of the invention

According to a first embodiment, the present invention relates to a mechanical transmission system, MTS (100), for a steerable tool (500) which steerable tool (500) has a proximal end (20) and distal end (40) and comprises a shaft region (532), a bendable proximal part, BPP (534) that is omnidirectionally moveable, and a bendable distal part, BDP, (530) that is omnidirectionally moveable and moves responsive to movement of the BPP (534), which MTS (100) comprises a plurality of longitudinal members, LM (110) each having a proximal (20) and distal end (40), arranged in a longitudinal direction around a fictive tube (120), and has a corresponding transmission shaft region, TSR (132), transmission bendable proximal part, TBPP (134) and transmission bendable distal part, TBDP (130), wherein a plane section (114) of at least one LM (110) demonstrates an anisotropic area moment of inertia, and the majority of the LMs (110) are each axially rotationally constrained at 1 or more constraining points along the TBDP (130) or along the TSR (132) wherein the LMs are longitudinally slidable with respect to each discrete constraining point, and the MTS (100) is configured such that the BDP (530) tip is axially 10 rotationable in a bent position by a complementary rotation of the BPP (534).

At least one constraining point disposed along the TSR (132) may be provided in the distal half of the TSR (132), preferably in 10% of the TSR (132) total length located at the distal end of the TSR (132) and at least one other constraining point disposed along the TSR (132) may be provided in the proximal half of the TSR (132), preferably in 10% of the 15 TSR (132) total length located at the proximal end of the TSR (132). Said the majority of the LMs (110) may be each further axially rotationally constrained at 1 or more constraining points along the TBPP (134). The MTS (100) may further be provided with one or more LM guides (300, 305, 350) each configured to axially rotationally constrain said majority of the LMs (110) at the constraining points. Each LM guide may be further 20 configured to maintain said majority of the LMs (110) at an essentially constant circumferential position on the fictive tube (120) at the constraining points. The MTS (100) may be provided with at least 2 LM guides (300, 305, 350) in the TBDP (130) and at least 2 LM guides in the TBPP (134). The LM guide (300, 305, 350) may comprise a body 25 provided with a plurality of discrete channels (310) arranged around the fictive tube (320, 120) configured to axially rotationally constrain said majority of the LMs (110) at the 30 35

constraining point, and to maintain the LMs (110) at an essentially constant circumferential position on the fictive tube (120) at the constraining point. A channel (310) may be configured to axially rotationally constrain an LM (110) in the TDBP or TBPP contains a profile in transverse cross-section that complements the plane section (114) of the LM.

5 The LM guides (300) in the TDBP (130) and TDPP (134) may be articulated LM guides (305, 305', 305'') respectively tandemly arranged, and mutually articulated, thereby supporting bending of the LMs (110) in the DBP (130) and PBP (134) respectively. The articulated LM guides (305, 305', 305'') may be in pairwise mutual contact through a pivot joint that comprises a ball and socket joint. Yawing between adjacent articulated LM 10 guides may be limited to provide an essentially fixed mutual rotational alignment of the discrete constraining points along the fictive tube. The LM guides (300) in the TSR (132) may be fixed LM guides (350, 350', 350'') and rotationally fixed with respect to each other to reduce the flexibility of TSR (132) compared with the flexibility of the TDBP (130) or 15 TBPP (134). The plane section of the LM may be a rectangular, letter "I", or circular segment profile, optionally wherein one or more of the profile corners are pointed or rounded-off. The BDP (530) and BPP (534) may be at least partially curveable. According 20 to a second embodiment, the present invention relates to a steerable tool (500) comprising an MTS (100) as defined herein.

Another embodiment of the invention relates to a mechanical transmission system, MTS

25 (100), for a steerable tool (500) which steerable tool (500) has a proximal end (20) and distal end (40) and comprises a bendable distal part, BDP, (530) that moves omnidirectionally, responsive to actuation of the MTS (100) at the proximal end (20), which MTS (100) comprises a plurality of longitudinal members, LM (110) each having a proximal (20) and distal end (40), arranged in a longitudinal direction around a fictive tube 20, and has a corresponding transmission bendable distal part, TDBP (130), wherein a plane section of at least one, optionally each and every LM (110) demonstrates an anisotropic area moment of inertia, and the majority, preferably all, of the plurality of LMs (110) are each axially rotationally constrained in the transmission bendable distal part (130).

30 The anisotropy may be with respect to mutually perpendicular axes (116, 118) that intersect at a centroid of the plane section (114) of the LM (110), and wherein the axis (116) around which the LM (110) has the higher area moment of inertia is oriented in a direction towards a central axis (A-A') of the fictive tube (120). The axis (116) may intersect the central axis (A-A') of the fictive tube (120) or diverge from the central axis (A- 35 A') of the fictive tube (120) by adopting an angle (alpha) of up to 60 deg compared with an

imaginary line draw (115) between the central (A-A') axis and the centroid (111) of the plane section. The plane section (114) may be present in the transmission bendable distal part (130). The number of LMs (110) may be at least three or four. The plane section (114) of the LM may have a rectangular, letter "I", or circular segment profile, optionally

5 wherein one or more of the profile corners are pointed or rounded-off.

The MTS (100) may be further provided with one or more LM guides (300, 350) configured to maintain the LMs (110) at an essentially constant circumferential position on the fictive tube (120) and to axially rotationally constrain said majority of the LMs (110) in the TBDP (130). The LM guide (300, 305, 350) may comprise a body provided with a plurality of

10 discrete channels (310) arranged around the fictive tube (320, 120) configured to maintain the LMs (110) at the essentially constant circumferential position on the fictive tube (120) and to axially rotationally constrain said majority of the LMs (110) in the TBDP (310). A channel (310) configured to axially rotationally constrain an LM (110) in the TBDP may contain a profile in transverse cross-section that complements the plane section (114) of 15 the LM. Some of the LM guides (300) may be articulated LM guides (305, 305', 305'') tandemly arranged in the TBDP (130), and mutually articulated, thereby supporting bending of the LMs (110) in the DBP (130). The articulated LM guides (305, 305', 305'') may be in pairwise mutual contact through a pivot joint. Some of the LM guides (300) may be fixed LM guides (350, 350', 350'') that are arranged in a transmission shaft region, TSR

20 (132), adjacent to the TBDP (130), and are rotationally fixed with respect to each other.

The MTS (100) may further comprise a transmission bendable proximal part, TBPP (134), for omnidirectional actuation by the user, that induces the omnidirectional movement response of the TBDP (130).

Another embodiment of the invention relates to a steerable tool (500) comprising an MTS 25 (100) as defined herein. The BDP (530) may be configured for movement in at least two different intersecting planes responsive to actuation of the MTS (100) at the proximal end (20), wherein the steerable tool (500) is further provided with an end effector (540) at the distal end of the BDP (530), and the MTS (100) is configured such that the end effector (540) is rotationally fixed in relation to the BDP (530), and the end effector is rotatable 30 when the BDP (530) is in a bent position by a complementary rotation of the proximal bending part (202). The end effector may be rotationally fixed in relation to the BDP by means of a lockable element configured to allow rotational adjustment of and to rotationally fix the end effector (540) in rotational relation to the BDP (530).

35 **Brief description of the Figures**

**FIG. 1** depicts an isometric view of a mechanical transmission system (MTS) of the invention in isolation in a linear configuration.

**FIG. 2** depicts the MTS of **FIG. 1** in which the transmission bendable distal part (TBDP) is bent, and the transmission shaft region (TSR) remains in the same straight configuration.

5 **FIG. 3** depicts two intersecting axes on a plane section that is a planar transverse cross-section of the longitudinal member (LM) at position 112 in **FIG. 1**, which cross-section has an "I"-shaped profile.

**FIG. 4** depicts an outer view of an MTS of the invention disposed with a plurality of fixed LM guides and a plurality of articulated LM guides.

10 **FIG. 5** depicts the MTS of **FIG. 4**, in which TBPP has been actuated by bending, the movement transmitted to the TBDP.

**FIG. 6** depicts a semi-circular transverse cross-section (*i.e.* plane section) of an LM.

**FIG. 7** depicts a rectangular transverse cross-section (*i.e.* plane section) of an LM.

**FIG. 8** depicts an "I" transverse cross-section (*i.e.* plane section) of an LM.

15 **FIG. 9** depicts a rounded-edged rectangular transverse cross-section (*i.e.* plane section) of an LM.

**FIG. 10** depicts a race-track transverse cross-section (*i.e.* plane section) of an LM.

**FIG. 11** depicts a side view of a mechanical transmission means, not of the invention, in which the longitudinal members each have a circular plane sections.

20 **FIG. 12** depicts a side view of a MTS of the invention, in which the LMs each have "I"-shaped plane sections.

**FIG. 13** is an isometric view of a mechanical transmission means not of the invention, in which the longitudinal members each have a circular plane sections, demonstrating the undesirable twisting of longitudinal members.

25 **FIG. 14** is an isometric view of a MTS of **FIG. 11** and of the invention, in which the LM each have an "I"-shaped plane section demonstrating a significantly lesser twisting of LMs in the TBDP.

**FIG. 15** is a side view of an MTS of **FIG. 14** and of the invention, showing an isolated single LM.

30 **FIG. 16** is a side view of an MTS showing different bending radii of LMs disposed in the TBDP of the MTS.

**FIG. 17** is a plan view of an LM guide that is disc shaped.

**FIG. 18** is a side view of a LM guide that is an articulated LM guide.

**FIG. 19** shows an isometric view of a steerable tool incorporating an MTS of the invention.

**FIG. 20** is an isometric view of a MTS **100** of the invention provided with 4 LMs maintained

5 in radial position with a plurality of fixed and articulated LM guides.

**FIG. 21A** shows a bendable distal part of a mechanical transmission means, not of the invention disposed with circularly-profiled longitudinal members.

**FIG. 21B** shows the bendable distal part of a mechanical transmission means of **FIG. 21A** and not of the invention, in the undesirable and stable spiral kinematic chain state.

10 **FIG. 22** shows two exemplary orientations of a LM guide channel and of the LM present therein.

**FIGs. 22A** and **B** show two exemplary orientations of a LM present in an LM guide channel.

15 **FIG. 23** illustrates discrete constraining points in essentially fixed mutual rotational alignment along the fictive tube.

### **Detailed description of invention**

Before the present method used in the invention is described, it is to be understood that this invention is not limited to particular methods, components, or devices described, as 20 such methods, components, and devices may, of course, vary. It is also to be understood that the terminology used herein is not intended to be limiting, since the scope of the present invention will be limited only by the appended claims.

As used herein, the singular forms "a", "an", and "the" include both singular and plural referents unless the context clearly dictates otherwise.

25 The terms "comprising", "comprises" and "comprised of" as used herein are synonymous with "including", "includes" or "containing", "contains", and are inclusive or open-ended and do not exclude additional, non-recited members, elements or method steps. The terms "comprising", "comprises" and "comprised of" also include the term "consisting of".

30 The recitation of numerical ranges by endpoints includes all numbers and fractions subsumed within the respective ranges, as well as the recited endpoints.

The term "about" as used herein when referring to a measurable value such as a parameter, an amount, a temporal duration, and the like, is meant to encompass variations of +/-10% or less, preferably +/-5% or less, more preferably +/-1% or less, and still more preferably +/-0.1% or less of and from the specified value, insofar such

5 variations are appropriate to perform in the disclosed invention. It is to be understood that the value to which the modifier "about" refers is itself also specifically, and preferably, disclosed.

Unless otherwise defined, all terms used in disclosing the invention, including technical and scientific terms, have the meaning as commonly understood by one of ordinary skill in

10 the art to which this invention belongs. By means of further guidance, definitions for the terms used in the description are included to better appreciate the teaching of the present invention. All publications referenced herein are incorporated by reference thereto. All United States patents and patent applications referenced herein are incorporated by reference herein in their entirety including the drawings.

15 Reference throughout this specification to "one embodiment" or "an embodiment" means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, appearances of the phrases "in one embodiment" or "in an embodiment" in various places throughout this specification are not necessarily all referring to the same embodiment, but 20 may. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner, as would be apparent to a person skilled in the art from this disclosure, in one or more embodiments. Furthermore, while some embodiments described herein include some but not other features included in other embodiments, combinations of features of different embodiments are meant to be within the scope of the 25 invention, and form different embodiments, as would be understood by those in the art. For example, in the following claims, any of the claimed embodiments can be used in any combination.

The terms "distal" and "proximal" are used through the specification, and are terms generally understood in the field to mean towards (proximal) or away (distal) from the 30 surgeon's side of the apparatus. Thus, "proximal" means towards the surgeon's side and, therefore, away from the patient's side. Conversely, "distal" means towards the patient's side and, therefore, away from the surgeon's side.

The present invention relates to a mechanical transmission system (MTS) for a steerable tool. The steerable tool is preferably longitudinal, meaning it is longer in one direction. It

does necessarily not imply the steerable tool is linear, though a linear (straight) steerable tool is within the scope of the invention. The steerable tool may be straight or curved, for instance, having a C- or S-shape shaft region.

- Typically, a steerable tool has a proximal end and distal end and comprises a bendable distal part (BDP), sometimes known as a wrist, that moves responsive to actuation of the MTS at the proximal end. Actuation of the MTS at the proximal end induces a movement response in the BDP. The steerable tool is also provided with a shaft region (SR), that may be essentially rigid or semi-rigid, one end of which is disposed with the BDP. The shaft region is longitudinal, meaning it is longer in one direction. It does necessarily not imply the shaft region is linear, though a linear (straight) shaft is within the scope of the invention. The shaft region may be straight or curved, for instance, having a C- or S-shape. To control BDP, steering wires which are known as longitudinal members (LMs) are used in the MTS. They control the BDP by pulling or pushing. The MTS comprises a plurality of longitudinal members (LM) each having a proximal end and a distal end, arranged in a longitudinal direction around a fictive tube. At least one of the LMs contains a region, in which a plane section thereof has an anisotropic second moment of inertia with respect to two intersecting axes. The tip (distal terminal end) of the BDP should be able to move with equal ease in any direction *i.e.* there is no singularity. The movement response is proportion to the degree of actuation.
- The shaft region (SR) is preferably essentially rigid or semi-rigid, or may be flexible and become rigid or semi-rigid when co-operating with a rigid or semi-rigid exotube or outer tube. The shaft region is adjacent to the BDP. The shaft region may contact the BDP. The steerable tool may further be provided with a bendable proximal part (BPP) at the proximal end of the steerable tool. The BPP is adjacent to the shaft region *i.e.* the shaft region is disposed between the BDP and BPP. The shaft region may contact the BPP. Movement of the BPP actuates the MTS at the proximal end and induces a movement response in the BDP. Movement of BPP in different radial directions and to different bending degrees is transmitted using the MTS to the BDP, and results in a corresponding change in radial direction and/or degree of bending of the BDP. The steerable tool may be actuated at the proximal end using an electromechanical device connected directly to the MTS, for instance to two or more of the LMs, or each and every LM. Typically the LMs in the shaft region would be actuated. In such case, the tool may be devoid of a BPP. Alternatively, robotic control may be realised by using an electromechanical device to actuate the BPP. The electromechanical device may be, for instance, a servo motor. Coupling to an electromechanical device would facilitate direct integration into a surgical robot.

The movement response of the BDP may be:

- a change in degree of bending within a plane parallel to and contacting a central longitudinal axis of and extending from the shaft region,

- a change direction of the bend within a plane perpendicular to and contacting a central

5 longitudinal axis of and extending from the shaft region.

The combination of movements the steerable tool allows would normally facilitate a rotation of the shaft region that could be transmitted to BDP at its tip while the BDP is in a bent position. However, the inventors have found that the tip of BDP does not rotate synchronously with the shaft region. There is a “dead-zone”, backlash or play where

10 torque applied at the proximal end and transmitted through the shaft region does not result in a rotation of the BDP tip, particularly when it is in a bent position.

The steerable tool may be a surgical instrument, such as, for instance, a laparoscopic instrument or an endovascular catheter. The invention can be used in an articulated instrument such as but not limiting to endovascular applications, surgical instruments,

15 robotic tele-operated medical robotics or hand-held surgical tools and industrial applications.

The BDP is configured to move omni-directionally *i.e.* in any radial direction. BDP is preferably configured to move in any radial direction (about 360° with respect to central longitudinal axis (**A'-A**) of the shaft region). The BDP is preferably configured to move in

20 at least two different planes (e.g. 3, 4, 5, 6, 7, 8 or more) disposed parallel to and contacting a central longitudinal axis (**A'-A**) of the shaft region. Preferably, the BDP is configured to move in an infinite number of different planes disposed parallel to and contacting a central longitudinal axis (**A'-A**) of the shaft region. The BDP bending is typically at least partially a curve *i.e.* the BDP is curvable. By curve, it is meant there is a

25 smooth bending rather than angular bending as is commonly understood in the art. A curve typically contains for at least a portion of its length a continuously changing (e.g. increasing or decreasing) gradient, compared with an angular bend that typically exhibits a constant gradient or a discrete and singular change of gradient, for instance, at a hinge joint. It is appreciated that the BDP may biased in a straight configuration and actuation

30 induces curvature therein. Alternatively, the BDP may biased in a curve and actuation induces additional or less curvature therein.

Similarly, the BPP, where present, is configured to move omni-directionally *i.e.* in any radial direction. BPP is preferably configured to move in any radial direction (about 360° with respect to central longitudinal axis (**A'-A**) of the shaft region). MTS is preferably

configured to move the BPP in at least 8 different directions. The BPP is preferably configured to move in at least two different planes (e.g. 3, 4, 5, 6, 7, 8 or more) disposed parallel to and contacting a central longitudinal axis (**A'-A**) of the shaft region. Preferably, the BPP is configured to move in an infinite number of different planes disposed parallel to

- 5 and contacting a central longitudinal axis of the shaft region. The BPP bending is typically at least partially a curve *i.e.* the BPP is curvable. By curve, it is meant there is a smooth bending rather than angular bending as is commonly understood in the art. A curve typically contains for at least a portion of its length a continuously changing (e.g. increasing or decreasing) gradient, compared with an angular bend that typically exhibits a  
10 constant gradient or a discrete and singular change of gradient, for instance, at a hinge joint. It is appreciated that the BPP may biased in a straight configuration and actuation induces curvature therein. Alternatively, the BPP may biased in a curve and actuation induces additional or less curvature therein.

The steerable tool may be provided with an end effector such as grip, pliers, cutting

- 15 scissors and the like. The end effector is provided at the distal end of the steerable tool.

Furthermore it may be possible to rotate the distal tip of the instrument about its own axis

*i.e.* axially even in a bent status. Accordingly, the MTS may be configured such that BDP (or TBDP) tip is axially rotationable in a bent position by a complementary rotation of the BPP (or TBPP). The steerable tool may be provided with an end effector at the distal end

- 20 of the BDP wherein the MTS is configured such that the end effector is rotationally fixed in relation to the BDP, and the end effector is rotatable when the BDP is in a bent position, by a complementary rotation of the BPP. The end effector may be rotationally fixed in relation to the BDP by means of a lockable element configured to allow rotational adjustment of and to rotationally fix the end effector in rotational relation to the BDP.

- 25 The MTS as described herein has a proximal end and distal end. The distal end is provided with a transmission bendable distal part (TBDP) that moves responsive to actuation of the MTS at the proximal end, and which moves the BDP of the steerable tool. The TBDP corresponds in position with the BDP. The proximal end may be provided with a transmission bendable proximal part (TBPP). Movements by the user of the BPP of the  
30 steerable tool are transferred to the TBPP. The TBDP corresponds in position with the BPP. The TBPP actuates the MTS at the proximal end and induces the movement response of the TBDP that is transferred to the BDP of the steerable tool.

The MTS is also provided with a transmission shaft region (TSR) to be disposed within the corresponding shaft region of the steerable tool. The TSR is preferably essentially rigid or

semi-rigid, or may become rigid or semi-rigid when co-operating with a rigid or semi-rigid exotube or outer tube.

The MTS may be actuated at the proximal end using an electromechanical device connected directly to the MTS, for instance to two or more of the LMs, or each and every

5 LM. Typically the LMs in the LM shaft region would be actuated. In such case, the tool may be devoid of a TBPP. Alternatively, robotic control may be realised by using an electromechanical device to actuate the BPP. The electromechanical device may be, for instance, a servo motor. This would facilitate direct integration into a surgical robot.

The MTS is preferably configured to move the BDP omni-directionally. MTS is preferably

10 configured to move the BDP in any direction (about 360° with respect to central longitudinal axis (**A'-A**) of the TSR). MTS is preferably configured to move the BDP in at least 8 different directions. The MTS may be configured to move the BDP in at least two different planes (e.g. 3, 4, 5, 6, 7, 8 or more) disposed parallel to and contacting a central longitudinal axis (**A'-A**) of the TSR. Preferably, MTS is configured to move the BDP in an 15 infinite number of different planes disposed parallel to and contacting a central longitudinal axis (**A'-A**) of the transmission shaft region.

The TBDP is configured to move omni-directionally *i.e.* in any radial direction. TBDP is preferably configured to move in any radial direction (about 360° with respect to central longitudinal axis (**A'-A**) of the shaft region). The TBDP is preferably configured to move in

20 at least two different planes (e.g. 3, 4, 5, 6, 7, 8 or more) disposed parallel to and contacting a central longitudinal axis (**A'-A**) of the shaft region. Preferably, the TBDP is configured to move in an infinite number of different planes disposed parallel to and contacting a central longitudinal axis (**A'-A**) of the shaft region. The TBDP bending is typically at least partially a curve *i.e.* the TBDP is curvable. By curve, it is meant there is a 25 smooth bending rather than angular bending as is commonly understood in the art. A curve typically contains for at least a portion of its length a continuously changing (e.g. increasing or decreasing) gradient, compared with an angular bend that typically exhibits a constant gradient or a discrete and singular change of gradient, for instance, at a hinge joint. It is appreciated that the TBDP may biased in a straight configuration and actuation 30 induces curvature therein. Alternatively, the TBDP may biased in a curve and actuation induces additional or less curvature therein.

The TBPP is configured to move omni-directionally *i.e.* in any radial direction. TBPP is preferably configured to move in any radial direction (about 360° with respect to central longitudinal axis (**A'-A**) of the shaft region). The TBPP is preferably configured to move in

at least two different planes (e.g. 3, 4, 5, 6, 7, 8 or more) disposed parallel to and contacting a central longitudinal axis (A'-A) of the shaft region. Preferably, the TBPP is configured to move in an infinite number of different planes disposed parallel to and contacting a central longitudinal axis (A'-A) of the shaft region. The TBPP bending is

- 5 typically at least partially a curve i.e. the TBPP is curvable. By curve, it is meant there is a smooth bending rather than angular bending as is commonly understood in the art. A curve typically contains for at least a portion of its length a continuously changing (e.g. increasing or decreasing) gradient, compared with an angular bend that typically exhibits a constant gradient or a discrete and singular change of gradient, for instance, at a hinge joint. It is appreciated that the TBPP may be biased in a straight configuration and actuation induces curvature therein. Alternatively, the TBPP may be biased in a curve and actuation induces additional or less curvature therein.
- 10

Furthermore it may be possible to rotate the distal tip of the instrument about its own axis even in a bent status. The MTS may be provided with an end effector at the distal end of

- 15 the TBDP wherein the MTS is configured such that the end effector is rotationally fixed in relation to the TBDP, and the end effector is rotatable when the TBDP is in a bent position, by a complementary rotation of the TBPP. The end effector may be rotationally fixed in relation to the TBDP by means of a lockable element configured to allow rotational adjustment of and to rotationally fix the end effector in rotational relation to the TBDP.

- 20 The MTS comprises a plurality of longitudinal members (LMs) each having a proximal end and a distal end, arranged in a longitudinal direction around a fictive tube. The fictive tube is a geometric shape around which the LMs are aligned. It is preferably longitudinal. It preferably has a circular transverse-cross section, a transverse cross-section being essentially perpendicular to a longitudinal axis. A central axis (A'-A) of the fictive tube is preferably coaxial with a central axis of the steerable tool. The fictive tube is preferably cylindrical. The fictive tube has a diameter that is smaller than the diameter of the steerable tool at the corresponding position.
- 25

The LM as described herein has a proximal end and distal end. The distal end is provided with a LM bendable distal part (LMBDP) to be disposed in the TBDP of the MTS. The LM is provided with a LM shaft region (LMSR) to be disposed in the corresponding TSR of the MTS. The LMSR is proximal to and adjacent to the LMBDP. The proximal end may be provided with a LM bendable proximal part (LMBPP) to be disposed in the TBPP of the MTS.

The distal ends of the LMs are maintained in fixed relation to each other in the MTS. The distal ends of the LMs, more preferably the distal terminal ends of the LMs, may be connected to a distal LM fixation element. Preferably, the distal LM fixation element maintains the LMs at their respective circumferential positions, for instance, it may maintain the distal terminal ends of the LMs in an annular ring. The distal LM fixation element may be, for instance, a disc or annulus disposed at the distal end of the MTS.

Similarly, the proximal ends of the LMs, more preferably the proximal terminal ends of the LMs, may be maintained in fixed relation to each other in the MTS. The proximal ends of the LMs may be connected to a proximal LM fixation element. Preferably, the proximal LM fixation element maintains the LMs at their respective circumferential positions, for instance, it may maintain the proximal terminal ends of the LMs in an annular ring. The proximal LM fixation element may be a disc or annulus disposed at the proximal end of the MTS.

The LMs are slidable relative to each other, to the extent that movement is restricted by said LM fixation element(s). The application of force - pushing and/or pulling - at the proximal end of the MTS is transmitted via the LMs along the LMSR to the LMBDP which in turn causes movement of the TBPP e.g. by pulling or pushing the aforementioned fixation element(s). The number of LMs in an MTS may be at least two, for instance, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 13, 14, 15, 16, 17, 18, 19, or 20, or more. For omnidirectional steering, it is preferred that at least 4, more preferably at least 6 or 8 LMs are present.

Dimensions of an LM can may depend on the diameter and length of the eventual steerable tool, and on the number of LMs utilised. As a general guidance, an LM may have a thickness in one direction of 40  $\mu\text{m}$ , 50  $\mu\text{m}$ , 60  $\mu\text{m}$ , 80  $\mu\text{m}$ , 100  $\mu\text{m}$ , 200  $\mu\text{m}$ , 200  $\mu\text{m}$ , 400  $\mu\text{m}$  or 500  $\mu\text{m}$ , or a value in the range between any two of the aforementioned values. An LM may have a width of 80  $\mu\text{m}$ , 100  $\mu\text{m}$ , 120  $\mu\text{m}$ , 140  $\mu\text{m}$ , 160  $\mu\text{m}$ , 180  $\mu\text{m}$ , 200  $\mu\text{m}$ , 300  $\mu\text{m}$ , 400  $\mu\text{m}$ , 500  $\mu\text{m}$ , 600  $\mu\text{m}$ , 700  $\mu\text{m}$ , 800  $\mu\text{m}$ , 900  $\mu\text{m}$ , 1000  $\mu\text{m}$ , 1100  $\mu\text{m}$ , 1200  $\mu\text{m}$ , 1300  $\mu\text{m}$ , 1400  $\mu\text{m}$ , or 1500  $\mu\text{m}$  or a value in the range between any two of the aforementioned values. The skilled person would understand how to select a suitable thickness and width according to the diameter of the MTS.. For a 10 mm diameter MTS, the preferred thickness is 280  $\mu\text{m}$  to 320  $\mu\text{m}$ , preferably about 300  $\mu\text{m}$ , and the preferred width is 480  $\mu\text{m}$  to 520  $\mu\text{m}$ , preferably about width 500  $\mu\text{m}$  in the LMBDP, LMSR and optionally LMBPP. The length of the MTS will depend on the length of the steerable tool and its application. The above preferred dimensions apply to MTS of 37-40 cm in length.

The LMs may be made from any suitable material having the appropriate tensile and compression properties and can be deduced by the person skilled in the art. Examples include stainless steel or nitinol, beta titanium, spring steel, or polymer.

The LM may be made from a single strand of a material e.g. a single strip of stainless

5 steel. Alternatively, it may be made from multiple strands of material tandemly connected.

The LMs are longitudinally arranged around the fictive tube. The LMs may be distributed evenly around the fictive tube e.g. the distance between adjacent LMs may be essentially the same. The LMs may be distributed symmetrically around the fictive tube e.g. there may be a plane of symmetry about a longitudinal-cross section of the fictive tube. The LMs may

10 be distributed unevenly around the fictive tube e.g. the distance between at least two pairs of adjacent LMs may be different.

The LM is preferably disposed essentially along the length of the MTS, and of the steerable tool. It spans the TBDP and extends into the TSR, and the TBPP where present.

The LMs are preferably arranged such that their longitudinal axes are mutually parallel.

15 The LMs are preferably arranged such that their longitudinal axes are parallel to a longitudinal axis (**A-A'**) of the fictive tube. The LMs are preferably arranged such that their longitudinal axes are parallel to a longitudinal axis of the longitudinal steerable tool.

At least one plane section of the LM demonstrates an anisotropic area moment of inertia.

20 A plane section is typically a transverse cross-section perpendicular to the longitudinal central (z) axis of an LM (see **FIG. 3**). The anisotropy is with respect to mutually perpendicular axes (x, y) that intersect at a centroid of the plane section, and which axes form a plane that is parallel to and lies on the plane section. The centroid is understood to be the geometric centre of the plane section, more specifically of the outer profile of the plane section. When the plane section has an essentially rectangular profile, the x and y

25 axes are aligned parallel to the straight edges of the rectangle, the x-axis being aligned such that the area moment of inertia in respect of the x-axis is the greatest. When the plane section has an irregular profile, the x-axis is aligned such that the area moment of inertia is greatest with respect to the x-axis. Preferably the ratio of the area moment of inertia ( $I_r$ ) with respect to an x-axis ( $I_x$ ) and a y-axis ( $I_y$ ) ( $I_x/I_y$ ) which intersect a centroid of a plane section of the LM is greater than 1, or is about 1.1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, or 20 or more, or a value in the range 30 between any two of the aforementioned values. As a general guidance,  $I_r$  may be between 1.1 and 4, preferably between 2 and 3 for an invasive surgical instrument which

the inventors have found provides a stable TDBP that is resistant to torque, while being amenable to bending, and stills avoids the undesirable spiral kinematic chain state.

The at least one plane section may be in the LMBDP. Preferably, the LMBDP demonstrates the anisotropic property at multiple plane sections, preferably at the majority of, or substantially all positions along the length of the LMBDP. Preferably, the LMBPP demonstrates the anisotropic property at multiple plane sections, preferably at the majority of, or substantially all positions along the length of the LMBPP. Preferably, the LMSR demonstrates the anisotropic property at multiple plane sections, preferably at the majority of, or substantially all positions along the length of the LMSR. According to one aspect, 10 the LMBDP, and 1 to 10 % of the length of the TSR from its distal end demonstrate the anisotropic property at the majority of, or substantially all plane sections therein. Where in the LMBPP is also present, the LMBDP, and 1 to 10 % of the length of the TSR from its distal end, the LMBPP, and 1 to 10 % of the length of the TSR from its proximal end, demonstrate the anisotropic property at the majority of, or substantially all plane sections 15 therein.

The LM is preferably orientated in the MTS or steerable tool such that the axis (typically the x-axis) having the higher area moment of inertia extends towards the central (A-A') axis of the fictive tube of the MTS, or of the steerable tool. While such axis extends towards the central (A-A') axis, it may or may not intersect the central A-A' axis. It may 20 diverge from the central axis, for instance, the x-axis may adopt an angle (alpha) of 10 deg, 20 deg or 30 deg, up to 60 deg compared with an imaginary line draw between the central (A-A') axis of the fictive tube of the MTS and the centroid of the plane section (see 25 **FIG. 22**). In other words the LM is preferably orientated such that the axis (typically the y-axis) having the lower area moment of inertia essentially faces the central (A-A') axis of the fictive circle of the MTS, or of the steerable tool.

Exemplary profiles (outer shape) of the planar transverse cross-section that demonstrate the aforementioned anisotropic area moment of inertia include rectangular, letter "I", circular segment (e.g. semicircle, quarter circle etc). One or more, preferably all of the corners of the profiles may be pointed (e.g. square) or rounded-off. In the case of a 30 rectangular LM, the radius of an edge may be up to 10 %, 20 %, 30 %, 40 % or 50 % of length of the shorter side of rectangle. Typically, it will be 10 $\mu$ m, 20 $\mu$ m, or 30 $\mu$ m or more, for instance, between 10  $\mu$ m and 200  $\mu$ m.

The area moment of inertia is also known as the second moment of inertia, moment of inertia of plane area, polar moment of area or second area moment. For a LM of uniform

material, the anisotropic property is determined essentially by the outer shape of the plane section. It can be calculated from the geometry of the plane section using techniques well known in the art. For instance,  $I_x$  and  $I_y$  can be calculated using Eqs 1 and Eqs 2, where  $x$ , and  $y$  are the coordinates of the differential element of  $dA$ , and  $A$  is the area of the plane section,  $x$  and  $y$ -axes intersect at a centroid of the plane section.

5  $I_x = \int y^2 dA$  [Eq 1]

$I_y = \int x^2 dA$  [Eq 2]

An LM having an isotropic area moment of inertia would facilitate omnidirectional movement at the TBDP and TBPP, since the LM needs to be able to bend in all directions,

10 not only in respect of circumferentially opposing actuating LMs (anterior and posterior LMs) that apply a pulling or pushing force that bends at the TBDP, but in respect of those LMs arranged between the actuating LMs - *i.e.* the lateral LMs. An LM having an isotropic area moment of inertia would reduce resistance to bending of these lateral LMs, and hence is preferred in the art. Contrary to this, the inventors have found that the MTS tolerates LMs having an anisotropic area moment of inertia, and which require more force to bend lateral LMs in the TBDP and TBPP because they bend over a larger radius compared with the LMs located on the inside of the bend (see **FIG. 16**).

Additionally, the inventors have found that axial rotation of the TSR is transmitted synchronously to the TBDP when LMs having an anisotropic area moment of inertia are employed. This is less the case when LMs having an isotropic area moment of inertia are used, which can result in a rotational lag - also known as backlash or play - before movements are transmitted to the tip of the TBDP. For instance, where a mechanical transmission means contains longitudinal members that have a circular transverse profile, an axial rotation of the end effector in respect of the shaft results in a torsion of the individual longitudinal members, that in turn means a torque applied to the steerable tool at one end is not transmitted to the other end, since said torque is absorbed by said circular-profiled longitudinal members (see, for instance **FIG. 13**). A counter torque force is induced that is inverse-linearly proportional to the length of torsion. In case of a steerable tool with a distal bendable part of 20 mm and a shaft region of 400 mm, a 45° torsion of the circular-profile longitudinal members will be spread over a distance of 420 mm, allowing significant backlash or play. The surgeon must apply additional torque before the slack is taken up.

For the same mechanical transmission system, but where anisotropic LMs are used, there is reduced torsion in the individual LMs, since the anisotropy provides each LM with an

enhanced resistance against twisting. This effect is enhanced when combined with LM guides, mentioned below, that constrain each LM to prevent or reduce axial rotation. Hence, the amount of backlash is reduced.

In a preferred aspect, the majority, preferably all of the LMs in the plurality of LMs are

- 5 each axially rotationally constrained at 1 or more constraining points (or regions) along the longitudinal axis of the fictive tube of the MTS.

Preferably, there is at least one 1 constraining point present along the TBDP or along the

TSR. The at least one constraining point disposed along the TSR may be provided in the distal half of the TSR, preferably in 25% or 10% of the TSR total length located at the

- 10 distal end of the TSR, optionally at the distal tip of the TSR. Constraining point or points disposed along the TSR may be confined to the distal half of the TSR, preferably in 25% or 10% of the TSR total length located at the distal end of the TSR, optionally at the distal tip of the TSR. Preferably, there are at least 2 constraining points, at least 1 disposed along the TSR, and at least 1, 2, 3 or 4 disposed along the TBDP.

- 15 Preferably, there is at least one 1 constraining point present along the TBPP or along the TSR. The at least 1 constraining point disposed along the TSR may be provided in the proximal half of the TSR, preferably in 25% or 10% of the TSR total length located at the proximal end of the TSR, optionally at the proximal tip of the TSR. Constraining point or points disposed along the TSR may be confined to the proximal half of the TSR, preferably in 25% or 10% of the TSR total length located at the proximal end of the TSR, optionally at the proximal tip of the TSR. Preferably, there are at least 2 constraining points, at least 1 disposed along the TSR and at least 1, 2, 3 or 4 disposed along the TBPP.

There may be at least 4 constraining points, at least 1 disposed along the TBDP, at least 1

- 25 disposed along the TSR in the distal half of the TSR, preferably in 25% or 10% of the TSR total length located at the distal end of the TSR, optionally at the distal tip of the TSR, at least 1 disposed along the TBPP, and at least 1 disposed along the TSR in the proximal half of the TSR, preferably in 25% or 10% of the TSR total length located at the proximal end of the TSR, optionally at the proximal tip of the TSR,

- 30 In the TBDP or BDP (or TBPP or BPP), the constraining points are discrete. By discrete it is meant they are spatially separated in the direction of the central longitudinal (**A-A'**) axis of the fictive tube. The discrete constraining points are spatially separated in the direction of the central longitudinal (**A-A'**) axis of the fictive tube in the TBDP or BDP or TBPP (or BPP where present).

In the TSR or SR constraining points may or may not be discrete. When not discrete they may be provided, for instance, as a continuous longitudinal channel in the direction of the central longitudinal (**A-A'**) axis of the fictive tube in the TSR or SR.

It is appreciated that the aforementioned constraining is different from any constraining

5 effect provided by the LM fixation element; the LM fixation element fixes the position of LM and does not allow the LMs to slide relative to each other (e.g. **FIG. 12**, distal LM fixation element **113**).

For the plurality of LMs, it allows the LM to be slidable with respect each other at each of

10 said constraining points. As described later below, a constraining point may be provided

15 by an LM guide, in particular an articulated LM guide in TBDP or BDP (and in the TBDP or BDP where present) or a fixed LM guide in the SR or TSR.

It is a further aspect that the constraining points may be in essentially fixed mutual rotational alignment; they are in essentially mutually fixed axial rotational alignment along the fictive tube. By essentially mutual fixed rotational alignment or essentially fixed mutual

15 axial rotational alignment, it is meant that the axial (**A-A'**) rotation angle between adjacent (neighbouring) constraining points along the fictive tube is essentially fixed or limited. For a plurality of constraining points arranged longitudinally along the fictive tube, the radial

20 angle of the LM with respect the central longitudinal axis (**A-A'**) of the fictive tube remains the same at each constraining point in an actuated or unactuated state. The constraining

25 points may be in essentially fixed alignment when no working load is applied to the MTS or to the steerable tool.

According to one aspect of the invention, the constraining points are in essentially fixed mutual rotational alignment such that a radial line intersecting a discrete constraining point at the distal terminal end of a TBDP shows a deviation angle, epsilon, of no more than 30

25 deg, preferably 25 deg along the longitudinal axis of the fictive tube compared with that of a constraining point at the proximal terminal end of a TBDP or in the TSR at the distal end

(see **FIG. 23** e.g. **I-A cf I-E**). The radial line radiates from and is perpendicular to the central longitudinal axis (**A-A'**) of the fictive tube. For the constraining points in question (e.g. a channel) the point of intersection is the same to enable a comparison.

30 According to one aspect of the invention, the constraining points are in essentially fixed mutual rotational alignment such that a radial line intersecting a discrete constraining point at the proximal terminal end of a TBPP shows a deviation angle, epsilon, of no more than

30 deg, preferably 25 deg along the longitudinal axis of the fictive tube compared with that of a constraining point at the distal terminal end of a TBPP or in the TSR at the proximal

end. The radial line radiates from and is perpendicular to the central longitudinal axis (**A-A'**) of the fictive tube. For the constraining points in question (e.g. a channel) the point of intersection is the same to enable a comparison.

According to another aspect, a radial line intersecting a discrete constraining point shows

- 5 a deviation angle, epsilon, of no more than 10 deg, preferably 5 deg compared with that of an adjacent (nearest neighbour) discrete constraining point along the longitudinal axis of the fictive tube (e.g. **FIGs. 23. I-C cf I-D**). The radial line radiates from and is perpendicular to the central longitudinal axis (**A-A'**) of the fictive tube. Between adjacent discrete constraining points (e.g. a channel) the point of intersection is the same to enable
- 10 a comparison. Besides the discrete constraining points in the TBDP or BDP (and in the TBPP or BPP where present) being mutually essentially axially rotational fixed along the fictive tube, they may be essentially axially rotational fixed with respect to constraining points in the SR or TSR.

An essentially fixed mutual rotational alignment in the TBDP or BDP (and in the TBPP or

- 15 BPP where present) may be provided, for instance, by the presence of the LM's which limit the amount of rotation between adjacent LM guides.

An essentially fixed mutual rotational alignment in the TBDP or BDP (and in the TBPP or BPP where present) may be provided, for instance, by articulated LM guides wherein yawing between adjacent articulated LM guides is limited or prevented as described later

- 20 below.

An essentially fixed mutual rotational alignment in the SR or TSR is provided, for instance, by fixed LM guides wherein yawing between adjacent fixed LM guides is limited or prevented as described later below.

The discrete constraining points TBDP or BDP (and in the TBPP or BPP where present)

- 25 being in essentially fixed mutual rotational alignment may further contribute to the reduction in backlash.

The obtained joint stiffness in the DBP is largely dependent on the anisotropic area moment of inertia ( $I_y$ ) of the LMs. Other factors can influence the stiffness, including the elastic modulus, shear modulus, the number of LMs, the distance of the LM to the central axis of the MTS, length of the LM section, the polar moment of inertia.

The counter-acting force is proportional to the area moment of inertia ( $I$ ). The inertia is

related to the length of the long side of the planar section of the LM to the third power.

This explains why the use of, for instance, an "I"-shape profile LM with a long and short

side is advantageous. The long side of the plane section gives rise to a higher area moment of inertia in comparison to a standard round steering wire for the same cross section area. We call this the 'ruler' effect. Such a ruler can be easily bent in one direction. However in the other direction it is highly stiff. It is the latter stiffness that is used to block axial rotation deformations, and reduce backlash in the system.

Due to the profile of an LM, it cannot freely rotate at the constraining points; once the LM contacts a wall of a channel (e.g. **FIG. 22B**), rotation is prevented and a second effect comes into action, namely twisting of the strip around the z-axis (see **FIG. 3**). The torsional constant (measure of resistance against torsion) is called the polar moment of

10 inertia, and equals to the sum of  $I_x$  and  $I_y$  (second moments of inertia, measure of resistance against bending). There is a third effect arising when an LM in only x-direction

hits the wall of the LM guide (**FIG. 22A**, with LM for instance moved to the left so it touches the wall of the LM guide). This condition is met very quickly as the LM guide is positioned near the outer surface of the instrument, at a radial distance which is much

15 larger than the thickness of the LM. The LM guide bends over its most bent resistive side (anisotropic moment of inertia) (see FIG 14, 110). The torsional constant for this effect depends on:  $I_y$ , radius of instrument (distance of the center of the LM to the central axis of the instrument) squared and inversely to the length of the LM (distance between 2 constraining points) squared. Because the distance between the constraining points is of

20 the same order compared to the radius of the instrument, and because the  $I_y$  is high due to the anisotropy and because the radius is large compared to the dimensions of the cross section of the LM, this third effect is very important. It tends to be much larger than the second effect, which explains the advantage of the anisotropic feature of the LM.

A rectangular-profiled LM with a thickness of 300 $\mu\text{m}$  and a width of 530 $\mu\text{m}$ , for instance,

25 has the same cross-sectional area as a round wire of diameter 437 $\mu\text{m}$ . However the area moment of inertia over the elongated side (oriented parallel to the circumference of the instrument) of the rectangular strip is twice the area moment of inertia of the round wire resulting in a double increase in rotational stiffness TBPP or the BPP ( $300 \times 530 = \pi \times 218^2$ ) ( $I_{530} = 300 \times 530^3 / 12$ ) ( $I_{437} = 437^4 \times \pi / 64$ ).

30 Not only does the anisotropic area moment of inertia reduce axial rotation and hence backlash, it also reduces the formation of a spiral kinematic chain within the LMBDP (and hence the TBDP and BDP) or within the LMBPP (and hence the TBPP and BPP). The spiral kinematic chain is an undesirable configuration in the LMBDP or the LMBPP in which articulated LM-guides, despite being mutually rotationally constrained, adopt a 35 mechanically stable configuration in which the proximal-most LM-guide is revolute offset

compared with the distal-most LM-guide (see **FIGs. 21A** and **21B**). Such stable configuration is realised when the LM-guides constitute a kinematic chain that follows a spiral path. Omni-directional instruments based on a concatenation of articulated LM-guide are all prone to this phenomenon. In the case of surgical instruments this results in

- 5 a rotation between shaft and end bendable distal part. In surgery this loss of revolute transmission is highly undesirable. The present inventors have found that LMs having an anisotropic area moment of inertia avoid the formation of this stable configuration. The effect is enhanced when the constraining points in the SR (TSR) and TBDP (BDP) and in the TBDP or BDP where present) are in essentially fixed mutual rotational alignment.
- 10 The LMs at the inside and the outside of a turn of a bent TBPP or BPP and which are the principal LMs involved in the transmission of force, bend over the axis with the smallest area moment of inertia. The side-disposed or lateral LMs, not involved not directly involved in the transmission of force, have to bend over the stiffer axis (see **FIG. 12**). In the case of a 10 mm diameter TBPP or BPP bent at 90° deflection the inner bending
- 15 radius can be 5 mm while the bending radius in the middle will be 10 mm. Hence, the unfavorable bending over the elongated side of the anisotropic LM can be compensated by an increased bending radius.

The MTS may be provided with a plurality (e.g. 2 to 30, 3 to 20) of LM guides configured to support and maintain the arrangement of LMs around the fictive tube. In particular, the

20 plurality of LM guides maintain the majority of, preferably all of the LMs at a constant circumferential position on the fictive tube. By maintaining a constant circumferential position, it is meant that a radial angle adopted by an LM with respect to a central longitudinal axis (A-A') of the fictive tube is essentially constant and that the radial distance of an LM from the central longitudinal axis (A-A') of the fictive tube is essentially

25 constant. The LM guide is configured to maintain the essentially constant circumferential position in an actuated or unactuated state.

In particular, the plurality of LM guides may axially rotationally constrain the majority of, preferably all of the LMs, in particular at the TBDP (and TBPP where present), but also at the TSR. By axially rotationally constraining an LM it is meant that rotation of an LM around its longitudinal (axial) axis is constrained, for instance, at a constraining point. The

30 LM guide is configured to maintain the essentially constant axial rotational angle in an actuated or unactuated state. An axial rotational angle, beta, (see **FIGs 22A** and **22B**) refers to an angle adopted by a plane section of the LM, for instance within the constraining point. A plane section is typically a transverse cross-section perpendicular to

35 the longitudinal central (z) axis of an LM (see **FIG. 22A** and **B**). The axial rotational angle,

beta, is with respect to an x-axis of mutually perpendicular axes (x, y) that intersect at a centroid of the plane section, and which axis form a plane that is parallel to and lies on the plane section. The centroid is understood to be the geometric centre of the plane section, more specifically of the outer profile of the plane section. When the plane section has an

- 5 essentially rectangular profile, the x and y axes are aligned parallel to the straight edges of the rectangle, the x-axis being aligned such that the area moment of inertia in respect of the x-axis is the greatest. When the plane section has an irregular profile, the x-axis is aligned such that the area moment of inertia is greatest with respect to the x-axis. Beta is a change in angle of x-axis (e.g.  $x'$  compared with  $x$  in **FIG. 22B**). For an essentially  
10 constant axial rotational angle *i.e.* where the LM is axially rotationally constrained, beta, typically has a deviation of between  $\pm 45$  deg.

An LM guide in the BDP/TBDP (and BPP/TBPP where present) contains the aforementioned discrete constraining point for an LM to axially rotationally constrain an LM and to further maintain the LM at an essentially constant circumferential position on  
15 the fictive tube, wherein LMs are longitudinally slidable with respect to each discrete constraining point. For the plurality of LM, it allows the LM to be slidable with respect each other at each of said discrete constraining points.

Similarly, an LM guide in the shaft region or TSR contains the aforementioned discrete constraining point for an LM to axially rotationally constrain an LM and to further maintain

- 20 the LM at an essentially constant circumferential position on the fictive tube, wherein LMs are longitudinally slidable with respect to each discrete constraining point. For the plurality of LM, it allows the LM to be slidable with respect each other at each of said discrete constraining points.

Some LM guides ("articulated LM guides" herein) may be articulated with respect to each  
25 other, particularly mutually pivoted, thereby supporting bending of the LMs, akin to a wrist joint. Articulated LM guides may be disposed in the TBDP and in the TBPP where present, corresponding to the BDP and the BPP of the steerable tool. An articulated LM guide may be articulated at one or both sides.

One or more LM guide ("fixed LM guides" herein) may be rotationally fixed with respect to each other, thereby maintaining a fixed (non-bending) path of the LM. They may be rotationally fixed with respect to each other to reduce the flexibility of TSR compared with the flexibility of the TBDP. The rotation fixation prevent mutual rotation in any of the three axes (e.g. rolling, pitching and yawing). Fixed LM guides may be disposed in the TSR,

corresponding to the SR of the steerable tool, giving rise to an essentially rigid or semi-rigid TSR.

As mentioned above, the TSR may become rigid or semi-rigid when co-operating with a rigid or semi-rigid exotube or outer tube. In other words, the TSR may be flexible. Rigidly

- 5 may be applied by inserting the TSR into a rigid or semi-rigid tube, or by clamping a rigid or semi-rigid tube around the TSR. Hence, articulated LM guides may be disposed in the TSR, corresponding to the SR of the steerable tool.

An LM guide comprises a body having a distal side and a proximal side, and an outer edge or surface connecting the distal and proximal sides.

- 10 For an articulated LM guide, the body is preferable substantially disc-shaped as shown, for instance, in **FIG. 18**. The disc may be disposed at a distal side with a socket and at a proximal side with a protrusion (e.g. ball) for engagement with a socket of an adjacent LM guide. Adjacent articulated LM guides hence form a ball and socket joint for mutual pivoting. As a general guidance for instruments such as surgical instruments, a disc may 15 have a diameter of 0.1 cm, 0.2 cm, 0.3 cm, 0.4 cm, 0.5 cm, 0.6 cm, 0.8 cm, 1 cm, 1.2 cm, 1.4 cm, 1.6 cm, 1.8 cm, 2 cm or more, or a value between any two of the aforementioned values, preferably between 0.2 cm and 1.6 cm. The disc, excluding protrusions may have a thickness of 0.02 cm, 0.15 cm, 0.2 cm, 0.4 cm, or a value between any two of the aforementioned values, preferably between 0.1 mm and 0.2 mm.

- 20 For a fixed LM guide, the body is preferable substantially cylindrically shaped, the ends of the cylinder being the distal and proximal sides. As a general guidance for instruments such as surgical instruments, a cylinder may have a diameter of 0.1 cm, 0.2 cm, 0.3 cm, 0.4 cm, 0.5 cm, 0.6 cm, 0.8 cm, 1 cm, 1.2 cm, 1.4 cm, 1.6 cm, 1.8 cm, 2 cm or more, or a value between any two of the aforementioned values, preferably between 0.2 cm and 1.6 25 cm. The diameter of the articulated LM guide and the fixed LM guide may be the same.

- The length of the cylinder may be, for instance, 0.5 cm, 0.6 cm, 0.8 cm, 1 cm, 2 cm, 3 cm or more, or a value between any two of the aforementioned values, preferably between 1 cm and 3 cm. While it is preferred that a plurality of tandemly arranged, fixed LM guides is present, it is within the scope of the invention that a single, long fixed LM guide is 30 disposed in the TSR, corresponding to the SR of the steerable tool.

Preferably, the body of the LM guide, either articulated or fixed is a one-piece element, e.g. is formed by moulding or machining as one piece, avoiding the assembly of a plurality of elements.

The body is provided with an arrangement of two or more, e.g. 2, 3, 4, 5 channels. The number of channels can depend on the size of the instrument; 18 to 40 channels or more is foreseen. A channel comprises a void space in the body of articulated LM guide. A channel passes from the distal side to the proximal side of the body. A channel preferably 5 has a central axis from the distal side to the proximal side of the body that is parallel to the central axis of the LM guide. A channel can accommodate one, two, or more LMs, preferably only one LM. A channel acts as a constraining point. A channel is dimensioned to constrain the LM, in particular to prevent radial movement with respect to the central axis of the body. A channel is dimensioned to constrain the LM, in particular to prevent 10 axial rotation, *i.e.* about the LM central (z) axis. Each channel is further configured to maintain the LM at an essentially constant circumferential position on the fictive tube. A channel is dimensioned to facilitate longitudinal slidable movement of the LM therethrough. The channels may be arranged around a fictive tube. Said fictive tube corresponds with the fictive tube of the MTS. The channels are mutually spatially 15 separated. A channel may contain a transverse profile that complements the profile of the LM to be accommodated. A transverse profile is perpendicular to the central axis of the channel. For instance, where the LM has a rectangular profile, the channel may contain a rectangular profile. It is appreciated that the channel profile need not precisely mirror the profile of the LM, for instance a race-track LM profile may be engaged by a rectangular 20 channel.

The plurality of LM guides are tandemly arranged *i.e.* distal side of one LM guide faces the proximal side of an adjacent LM guide. An example of tandemly-arranged articulated LM guides is shown in **FIG. 20**. The tandem arrangement of articulated LM guides serve to constrain the LMs at a number of discrete constraining positions along the longitudinal 25 axis of the fictive tube of the MTS. There may be 2 or more (e.g. 3, 4, 5, 6, 7, 8, 9 or 10 or more) tandemly-arranged articulated LM guides providing 2 or more (e.g. 3, 4, 5, 6, 7, 8, 9 or 10 or more) discrete constraining points. Preferably there are 7 or more tandemly-arranged articulated LM guides providing 7 or more discrete constraining points.

The plurality of articulated LM guides are mutually (pairwise) articulated. Preferably, the 30 plurality of articulated LM guides are in mutual (pairwise) contact. It is preferred that the relative rotation of adjacent articulated LM guides (*i.e.* yawing or axial rotation between adjacent articulated LM guides) is prevented or limited. Prevention or limiting of yawing allows the discrete constraining points to be in essentially fixed mutual rotational alignment along the fictive tube. According to one aspect, a radial line intersecting a 35 discrete constraining point (e.g. a channel) of one articulated LM guide shows a deviation

angle,  $\epsilon$ , of no more than 10 deg, preferably 5 deg compared with that of an adjacent articulated LM guide (see **FIGs. 23**). The radial line radiates from and is perpendicular to the central longitudinal axis (**A-A'**) of the fictive tube. Between adjacent LM guides the point of intersection with the discrete constraining point (e.g. a channel) is the same to enable a comparison.

Preferably, an articulated LM guide contacts an adjacent (neighbouring) LM guide using a pivot joint, such as a ball-and-socket type joint. There may be one ball-and-socket type joint per pair of articulated LM guide. The pivot joint allows pivoting of an articulated LM guide with respect to an adjacent articulated LM guide. The pivot joint may allow two

degrees of freedom of movement with respect to an adjacent articulated LM guide *i.e.* roll and pitch. The pivot joint may allow some relative rotation of adjacent articulated LM guides (*i.e.* yawing or axial rotation between adjacent articulated LM guides). Prevention or limiting of yawing is preferred but is not necessarily a requirement in view that the use

of LMs having an anisotropic area moment of inertia prevents the rotational slack as mentioned earlier, however, it is also within the scope of the invention. It is preferred that the pivot joint may not allow relative rotation of adjacent articulated LM guides (*i.e.* yawing or axial rotation between adjacent articulated LM guides). Prevention or limiting of yawing can be achieved for instance, using a rotation limiter that might be a protrusion fixed on the body of one articulated LM guide that is received by a recess fixed on the body of an

adjacent articulated LM guide (as shown, for instance, in **FIG. 18**); coupling prevents axial rotation of one LM guide relative to the adjacent LM guide.

A plurality of fixed LM guides are mutually (pairwise) in fixed relation. They are preferably in fixed rotational relation. They are preferably in fixed distance relation. Preferably, the plurality of fixed LM guides are in mutual (pairwise) contact. A plurality of fixed LM guides

is configured to reduce the flexibility of TSR compared with the flexibility of the TBDP.

As with adjacent articulated LM guides, relative rotation of adjacent fixed LM guides (*i.e.* yawing or axial rotation between adjacent fixed LM guides) is prevented. Prevention of yawing allows the discrete constraining points to be in essentially fixed mutual rotational alignment along the fictive tube.

The plurality of LM guides are tandemly arranged such the circularly-arranged channels are in alignment, and each can receive one (or optionally two or more) LMs.

Preferably, the articulated LM guide is substantially disc-shaped, is provided with 10 - 20 channels each configured to accommodate only one LM, each channel containing a

rectangular profile, the long side of the rectangle oriented to face a central axis of the LM guide, the channels being arranged around a fictive circle.

Preferably, the fixed LM guide is substantially cylindrically-shaped, is provided with 10 - 20

channels each configured to accommodate only one LM, each channel containing a

5 rectangular profile, the long side of the rectangle oriented to face a central axis of the LM guide, the channels being arranged around a fictive circle.

Each channel is configured to constrain the LM to reduce or prevent axial rotation, and to maintain its radial position with respect to a central LM guide axis (**A-A'**).

The MTS may be provided with an end effector, and configured such that the end effector

10 is rotationally fixed in relation to the LMBDP, and the end effector is rotatable when the

LMBDP is in a bent position, by a complementary rotation of the LMBPP. Hence, the

steerable tool may be configured such that the end effector is rotationally fixed in relation

to the BDP and the end effector is rotatable when the BDP is in a bent position, by a

complementary rotation of the BPP. The rotationally fixed effector end may be realised by

15 a permanent attachment to the tip of the LMBDP or BDP, for instance by welding or

adhesive. Alternatively, the rotationally fixed end effector may be realised by a lockable

revolute attachment to the tip of the LMBDP or BDP, in which the end effector is

rotationally fixed in relation when the end effector is locked in position.

Reference is made in the description below to the drawings which exemplify particular

20 embodiments of the invention; they are not at all intended to be limiting. It will be

understood that the skilled person may adapt the device and substitute components and

features according to the common practices of the skilled artisan.

**FIG. 1** depicts a mechanical transmission system (MTS) of the invention **100** shown in isolation having a proximal end **20** and a distal end **40**, and a central longitudinal axis **A-A'**.

25 The MTS **100** comprising a plurality (i.e. 4) of longitudinal members (LMs) **110** arranged longitudinally and dispersed evenly around a fictive longitudinal tube **120** having a cylindrical shape. The MTS **110** contains a transmission bendable distal part (TBDP)

**130** and a transmission shaft region (TSR) **132** that is essentially rigid or semi-rigid in the

shaft region of the steerable tool, or that is maintained rigid or semi-rigid in the shaft

30 region of the steerable tool by co-operating with an exotube.

**FIG. 2** depicts the MTS **100** of **FIG. 1** in which the TBDP **130** is bent, and the TSR **132** remains in the same straight configuration.

**FIG. 3** depicts two intersecting axes **116** (x-axis), **118** (y-axis) on a plane section **114** that is a planar transverse cross-section of the LM **110** at position **112** in **FIG. 1**, which cross-section has an "I"-shaped profile. The axes intersect at a point **111** that is a centroid of the profile (outer shape) of the planar transverse cross-section **114**. The axes **116**, **118** are mutually perpendicular. The axis **116** around which the LM has the higher area moment of inertia (x-axis, **116**) is oriented such that it is essentially radial to the central (**A**-**A'**) axis of the MTS. A z-axis **119** is also indicated that is perpendicular to both the x-axis **116**, y-axis **118**.

**FIG. 4** depicts an outer view of an MTS **100** of the invention, having a proximal **20** and distal end **40**, and transmission bendable distal part (TBDP) **130**, a transmission shaft region (TSR) **132** and a transmission bendable proximal part (TBPP) **134**. The transmission shaft region (TSR) **132** is disposed with a plurality of fixed LM guides **350**, **350'**, **350''** each providing constraining points for axial rotational of the LM wherein each LM is longitudinally slidable with respect to each LM guide **350**, **350'**, **350''**. The TBDP **130** and TBPP **134** are disposed with a plurality of articulated LM guides **305**, **305'**, **305''**, **305a**, **305a'**, **305a''** each providing a discrete constraining point for axial rotational of the LM wherein each LM is longitudinally slidable with respect to each LM guide **305**, **305'**, **305''**, **305a**, **305a'**, **305a''**.

**FIG. 5** depicts the MTS **100** of **FIG. 4**, in which TBPP **134** has been actuated by bending, the movement transmitted to the TBDP **130** along the TSR **132** by the MTS, which TBDP **130** bends responsively.

**FIG. 6** depicts a semi-circular transverse cross-section (i.e. plane section **114**) of an LM, and intersecting x- and y-axes about which moments of inertia are measured, which axes are centred at point **111** that is the centroid of the cross-section. The ratio  $I_x/I_y = 3.57$ , which is calculated according to Eq 1 and Eq 2.

**FIG. 7** depicts a rectangular transverse cross-section (i.e. plane section **114**) of an LM, and intersecting x- and y-axes about which moments of inertia are measured, which axes are centred at point **111** that is the centroid of the cross-section. The ratio  $I_x/I_y = 4$ , which is calculated according to Eq 1 and Eq 2.

**FIG. 8** depicts an "I" transverse cross-section (i.e. plane section **114**) of an LM, and intersecting x- and y-axes about which moments of inertia are measured, which axes are centred at point **111** that is the centroid of the cross-section. The ratio  $I_x/I_y = 9.2$ , which is calculated according to Eq 1 and Eq 2.

**FIG. 9** depicts a rounded-edged rectangular transverse cross-section (i.e. plane section **114**) of an LM, and intersecting x- and y-axes about which moments of inertia are measured, which axes are centred at point **111** that is the centroid of the cross-section. The ratio  $I_x/I_y = 4$ , which is calculated according to Eq 1 and Eq 2.

5 **FIG. 10** depicts a race-track transverse cross-section (i.e. plane section **114**) of an LM, and intersecting x- and y-axes about which moments of inertia are measured, which axes are centred at point **111** that is the centroid of the cross-section. The ratio  $I_x/I_y = 4$ , which is calculated according to Eq 1 and Eq 2.

10 **FIG. 11** depicts a side view of a mechanical transmission means **50**, not of the invention, having a proximal end **20** and a distal **40** end, and formed using longitudinal members **52**, **52'**, **52''** connected at the distal end to a distal longitudinal members fixation element **55**. The transmission shaft region is provided with a fixed longitudinal member guide **64**. Transverse cross-sections of the longitudinal members **52**, **52'**, **52''** are each depicted having a circular plane sections **56**, **56'**, **56''**. Bending of each of the longitudinal members 15 **52**, **52'**, **52''** is apparently facilitated by the circularly-profiled longitudinal members having an isotropic area moment of inertia, particularly in respect of those longitudinal members e.g. **52** that are peripheral to the longitudinal members **52'**, **52''** actuating the bending movement. Hence, all the longitudinal members **52**, **52'**, **52''** bend with equal resistance, despite each longitudinal member e.g. **52**, **52'**, **52''** bending in a different relative direction 20 (see direction of arrow **58**, **58'**, **58''**, compared with an orientation marker **60**, **60'**, **60''**).

25 **FIG. 12** depicts a side view of a MTS **100** of the invention, having a proximal end **20** and a distal **40** end, and formed using LMs **110**, **110**, **110''** connected at the distal end to a distal LM fixation element **113**. The transmission shaft region (TSR) is provided with a fixed LM guide **350**. Plane sections **114**, **114'**, **114''** of the LM **110**, **110**, **110''** are depicted with "I"-shaped profiles. Bending of each of the LM **110**, **110**, **110''** is surprisingly not hindered by the "I"-shaped -profiled LMs having plane sections with an anisotropic area moment of inertia, particularly in respect of those LMs e.g. **110** that are peripheral to the longitudinal members **110'**, **110''** actuating the bending movement. Hence, all the longitudinal members **110**, **110'**, **110''** bend without buckling or twisting, despite each longitudinal member e.g. **110**, **110'**, **110''** bending in a different relative direction (see direction of arrow **158**, **158'**, **158''**), and despite the peripheral longitudinal members e.g. **110**, bending in a direction that has a greater area moment of inertia. 30

**FIG. 13** is a schematic view of a mechanical transmission means **50** of **FIG. 11** and not of the invention, demonstrating the twisting of longitudinal members **52**, **52'**, **52''** in a distal

bendable part **64** when torque **62** is applied to a shaft region **66**. Each of the longitudinal members **52**, **52'**, **52''** has a circular profile and thus an isotropic area moment of inertia. Hence, the use of circular longitudinal members introduces a backlash in the transmission of torque through the shaft region **66** and to the bendable distal part **64**.

5 **FIG. 14** is a schematic view of a MTS **100** of **FIG. 11** and of the invention, demonstrating a significantly lesser twisting of LMs **110**, **110'**, **110''** in the transmission bendable distal part (TBDP) **130** when torque **162** is applied to the TSR **132**. Each of the longitudinal members **110**, **110'**, **110''** has an "I"-shaped plane section, and thus an anisotropic area moment of inertia. Hence, the use of "I"-profiled LMs reduces or removes backlash in the  
10 transmission of torque through the LM shaft region **132** and to the TBDP **130**.

**FIG. 15** is a schematic view of an MTS **100** of **FIG. 14** and of the invention, showing an isolated single LM **110**. It shows the application of force **(164)** to the LM **110** and its resistance to bending, attributable to the anisotropic area moment of inertia.

15 **FIG. 16** shows the different bending radii of anterior **110''**, posterior **110'** and lateral **110** LMs disposed in the MTS **100** in the TBDP **130**. The bending radius **117a** is smaller for the anterior LM **110''** located on the inside the bend, compared with the bending radius **117b** of the lateral LM **110**, which lateral LM **110** is stiffer in the bending direction owing to the anisotropic area moment of inertia of the LM **110**.

20 **FIG. 17** is a plan view of an LM guide **300** that is disc shaped. The LM guide **300** has a body **302** disposed with 4 separate channels **310**, arranged around a fictive tube **320**. The fictive tube **320** corresponds with the fictive tube **120** in **FIG. 1**. Each channel **310** constrains a LM **110**. Each channel is regarded as a discrete constraining point.

25 **FIG. 18** is a side view of a LM guide **300** that is an articulated LM guide **305** having a disc shaped, and a distal side **40** and a proximal side **20**. The articulated LM guide **300** has a body **302** comprising at the distal side **40**, one component of the pair of components that forms a pivot joint that is a dome protrusion **330**, akin to the ball of a ball and socket joint. It further comprises at the proximal side **20**, the other component of the pair of components that forms a pivot joint that is a reciprocating recess **340**, akin to the socket of a ball and socket joint. Further indicated is a pair of rotation limiters **(332, 332')** fixedly  
30 connected to the dome protrusion **330**, which are radial protrusions from said dome protrusion **330**. These couple with a pair reciprocating slots **340, 340'** fixedly connected to the receiving recess **340** of an adjacent articulated LM guide (not shown), to prevent mutual axial rotation of adjacent articulated LM guides. Each articulated LM guide contains a discrete constraining point (i.e. a channel) and the pair of rotation limiters

provide an essentially fixed mutual rotational alignment of the discrete constraining point along the fictive tube. **FIG. 19** shows a steerable tool **500** incorporating an MTS of the invention. The steerable tool **500** has a proximal **20** and distal **40** end. The distal end **40** is provided with an end effector (**540**) that is a gripper, while the proximal end **20** is provided with a handle **550** to steer the tube and to control the gripper. Also indicated are the bendable distal part (BDP) **530**, the shaft region (SR) **532** and the bendable proximal part (BPP) **534**.

**FIG. 20** is schematic view of a MTS **100** of the invention having a proximal end **20** and a distal end **40**, provided with 4 LMs **110** arranged around a fictive tube, maintained in position with a plurality of articulated LM guides **305**, **305'**, **305''** in the TBDP **130** each provided with a plurality of aligned channels. One of a complementary pair of elements (domed protrusion **330**) of a pivot joint is indicated in the distal most LM guide **300''**. The TSR **132** contains a plurality of tandemly-arranged fixed LM guide **350**, **350'**, **350''** that maintain the position of the LMs **110** in the TSR **130**.

**FIG. 21A** shows a bendable distal part of a mechanical transmission means **50**, not of the invention, having a proximal **20** and distal end **40**. The mechanical transmission means **50** is disposed with circularly-profiled longitudinal members **52**, **52'**, **52''** each having an isotropic second area moment of inertia, which longitudinal members **52**, **52'**, **52''** are constrained in a radial and circumferential position by a plurality of articulated longitudinal member guides **54**, **54'**, **54''**. Adjacent articulated longitudinal member guides **54**, **54'**, **54''** are prevented from mutual axial rotation due to the presence of rotation limiters (not indicated) on each longitudinal member guide **54**, **54'**, **54''**.

**FIG. 21B** shows the bendable distal part of a mechanical transmission means **50** of **FIG. 21A** and not of the invention, that has entered the undesirable and stable spiral kinematic chain state whereby the circularly-profiled longitudinal members **52**, **52'**, **52''** at the proximal end **20** are twisted relative to the distal end **40** despite the presence of rotation limiters.

**FIG. 22** shows two exemplary orientations of a longitudinal member **110a**, **110b** present in an LM guide channel **310** or **310'** wherein the x-axis of a plane section **114** of one longitudinal member **110b** is shown to diverge from an imaginary line **115** draw between the central (**A-A'**) axis and the centroid **111** of the plane section **114** by angle alpha when constrained by LM guide channel **310'**. The other longitudinal member **110a** shows no such divergence *i.e.* alpha is zero when constrained by LM guide channel **310**.

**FIG. 22A** and **22B** illustrate an angle beta that is a change in an axial rotational angle of an LM **110**. **FIG 22A** represents a starting orientation of an axis (x), and **FIG. 22B** represent the axis (x') at one of the limits of rotation within a channel **310**. For an essentially constant axial rotational angle of an LM **110** i.e. where the LM is axially 5 rotationally constrained at a discrete constraining point, angle beta deviates between certain limits.

**FIG. 23 I** and **II** illustrate a TDBP (**130**) disposed with a plurality of articulated LM guides (**305B** to **E**) and a central longitudinal axis (**A-A'**) of the fictive tube and a TSR (**132**) disposed with a fixed LM guides (**305A**). In **I**, the TDBP (**130**) is straight (unactuated), and 10 in **II**, the TDBP (**130**) is curved (actuated). **FIG. 23 Y** and **X** show schematic plan views of separate LM guides to illustrate the deviation angle, epsilon. **FIG. 23A** shows the radial line (**312X**) of one LM guide (**305X**) projecting from the central longitudinal axis (**A-A'**) of the fictive tube and intersecting its channel **310X**, **FIG. 23Y** shows the radial line (**312Y**) of another LM guide (**305X**) intersecting its channel **310X**. X and Y are the LM guides 15 between which epsilon is to be measured. For instance, where epsilon is a measure of deviation angle between two adjacent articulated LM guides, X may be I-C and Y may be I-D. Where epsilon is a measure of deviation angle between a proximal-most articulated LM-guide and a distal-most articulated LM-guide in the TDBP (**130**), X may be I-B and Y may be I-E. Where epsilon is a measure of deviation angle between the fixed LM guide in 20 the TSR (**132**) and a distal-most articulated LM-guide, X may be I-A and Y may be I-E.

The angular difference between the radial lines (**312A** and **312X**) of these respective LM guides, the deviation angle, is indicated as epsilon. **FIGs 23 I-A** to **I-E** are schematic plan views of the separate LM guides of **FIG. 23** wherein there is no deviation (epsilon is zero) between adjacent LM guides, and when the TDBP (**130**) is straight (unactuated). **FIGs 23 II-A** to **II-E** are schematic plan views of the separate LM guides of **FIG. 23-II** wherein there is no deviation (epsilon is zero) between adjacent LM guides, and when the TDBP (**130**) is curved (bend).

**CLAIMS**




1. A mechanical transmission system, MTS (100), for a steerable tool (500) which steerable tool (500) has a proximal end (20) and distal end (40) and comprises a shaft region (532), a bendable proximal part, BPP (534) that is omnidirectionally moveable, and a bendable distal part, BDP, (530) that is omnidirectionally moveable and moves responsive to movement of the BPP (534), which MTS (100) comprises a plurality of longitudinal members, LM (110) each having a proximal (20) and distal end (40), arranged in a longitudinal direction around a fictive tube (120), and has a corresponding transmission shaft region, TSR (132), transmission bendable proximal part, TBPP (134) and transmission bendable distal part, TBDP (130), wherein a plane section (114) of at least one LM (110) demonstrates an anisotropic area moment of inertia, and the majority of the LMs (110) are each axially rotationally constrained at 1 or more constraining points along the TBDP (130) or along the TSR (132) wherein the LMs are longitudinally slidable with respect to each discrete constraining point, and the MTS (100) is configured such that the BDP (530) tip is axially rotationable in a bent position by a complementary rotation of the BPP (534).  
2. The MTS (100) according to claim 1, wherein the at least one constraining point disposed along the TSR (132) is provided in the distal half of the TSR (132), preferably in 10% of the TSR (132) total length located at the distal end of the TSR (132) and at least one other constraining point disposed along the TSR (132) is provided in the proximal half of the TSR (132), preferably in 10% of the TSR (132) total length located at the proximal end of the TSR (132)..  
3. The MTS (100) according to claim 1 or 2 wherein said the majority of the LMs (110) are each further axially rotationally constrained at 1 or more constraining points along the TBPP (134).  
4. The MTS (100) according to any of claims 1 to 3, further provided with one or more LM guides (300, 305, 350) each configured to axially rotationally constrain said majority of the LMs (110) at the constraining points.  
5. The MTS (100) according to any of claims 1 to 4, wherein each LM guide is further configured to maintain said majority of the LMs (110) at an essentially constant circumferential position on the fictive tube (120) at the constraining points.

6. The MTS (**100**) according to any of claims 1 to 5, provided with at least 2 LM guides (**300, 305, 350**) in the TBDP (**130**) and at least 2 LM guides in the TBPP (**134**).
- 5 7. The MTS (**100**) according to any of claims 4 to 6, wherein the LM guide (**300, 305, 350**) comprises a body provided with a plurality of discrete channels (**310**) arranged around the fictive tube (**320, 120**) configured to axially rotationally constrain said majority of the LMs (**110**) at the constraining point, and to maintain the LMs (**110**) at an essentially constant circumferential position on the fictive tube (**120**) at the constraining point.
- 10 8. The MTS (**100**) according to claim 7, wherein a channel (**310**) configured to axially rotationally constrain an LM (**110**) in the TBDP or TBPP contains a profile in transverse cross-section that complements the plane section (**114**) of the LM.
- 15 9. The MTS (**100**) according to any of claims 4 to 8, wherein the LM guides (**300**) in the TBDP (**130**) and TDPP (**134**) are articulated LM guides (**305, 305', 305''**) respectively tandemly arranged, and mutually articulated, thereby supporting bending of the LMs (**110**) in the DBP (**130**) and PBP (**134**) respectively.
- 20 10. The MTS (**100**) according to claim 9, wherein the articulated LM guides (**305, 305', 305''**) are in pairwise mutual contact through a pivot joint that comprises a ball and socket joint.
- 25 11. The MTS (**100**) according to claim 9 or 10, wherein yawing between adjacent articulated LM guides is limited to provide an essentially fixed mutual rotational alignment of the discrete constraining points along the fictive tube.
- 30 12. The MTS (**100**) according to any of claims 4 to 11, wherein the LM guides (**300**) in the TSR (**132**) are fixed LM guides (**350, 350', 350''**) and are rotationally fixed with respect to each other to reduce the flexibility of TSR (**132**) compared with the flexibility of the TBDP (**130**) or TBPP (**134**).
- 35 14. The MTS (**100**) according to any of the previous claims, wherein the plane section of the LM has rectangular, letter "I", or circular segment profile, optionally wherein one or more of the profile corners are pointed or rounded-off.

15. A mechanical transmission system, MTS (**100**) according to any of the previous claims, wherein the BDP (**530**) and BPP (**534**) are at least partially curveable.

5 16. A steerable tool (**500**) comprising an MTS (**100**) as defined in any of the previous claims.

1 / 8



2 / 8




FIG. 4




FIG. 5




FIG. 6

FIG. 7

FIG. 8

FIG. 9

FIG. 10

3 / 8




FIG. 11








FIG. 12




4 / 8





5 / 8

**FIG. 15****FIG. 16**

6 / 8



7 / 8



8 / 8




FIG. 22




FIG. 22A










FIG. 22B

FIG. 23



# INTERNATIONAL SEARCH REPORT

International application No  
PCT/EP2015/069628

**A. CLASSIFICATION OF SUBJECT MATTER**  
INV. A61B19/00 A61B17/29  
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2010/160736 A1 (PADGET MARTIN [US] ET AL) 24 June 2010 (2010-06-24) paragraph [0068] - paragraph [0072] paragraph [0076] - paragraph [0077] paragraph [0080] - paragraph [0084] figures 1-3,10,11 ----- US 2008/300462 A1 (INTOCCIA ALFRED P [US] ET AL) 4 December 2008 (2008-12-04) paragraph [0047] - paragraph [0048] paragraph [0079] - paragraph [0083] figures 1,3,18-23 ----- US 2007/038230 A1 (STONE KEVIN T [US] ET AL) 15 February 2007 (2007-02-15) paragraph [0035] - paragraph [0039] figures 1,10 ----- -/-	1-12, 14-16
A		1-12, 14-16
A		1-12, 14-16

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance  
"E" earlier application or patent but published on or after the international filing date  
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  
"O" document referring to an oral disclosure, use, exhibition or other means  
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
8 October 2015	21/10/2015

Name and mailing address of the ISA/  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040,  
Fax: (+31-70) 340-3046

Authorized officer

Ebbinghaus, M

## INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2015/069628

## C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2007/156119 A1 (WALLACE DANIEL T [US] ET AL) 5 July 2007 (2007-07-05) paragraph [0062] - paragraph [0064] figures 1-3D -----	1-12, 14-16
A	US 2013/253481 A1 (DEWAELÉ FRANK [BE] ET AL) 26 September 2013 (2013-09-26) paragraph [0088] - paragraph [0147] figures 3,4,17-19 -----	1-12, 14-16
A	US 2014/052061 A1 (WEISSHAUPT DIETER [DE] ET AL) 20 February 2014 (2014-02-20) paragraph [0084] - paragraph [0095] paragraph [0103] - paragraph [0108] paragraph [0126] - paragraph [0127] figures 1,2,4A,6B -----	1-12, 14-16

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2015/069628

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
US 2010160736	A1	24-06-2010	AU 2007257754 A1		21-12-2007
			AU 2011202493 A1		16-06-2011
			CA 2622731 A1		21-12-2007
			EP 2024259 A2		18-02-2009
			JP 4731606 B2		27-07-2011
			JP 2009506804 A		19-02-2009
			US 2008221393 A1		11-09-2008
			US 2010160736 A1		24-06-2010
			WO 2007146842 A2		21-12-2007
<hr/>					
US 2008300462	A1	04-12-2008	CA 2684705 A1		11-12-2008
			EP 2152139 A2		17-02-2010
			JP 5362708 B2		11-12-2013
			JP 2010528714 A		26-08-2010
			US 2008300462 A1		04-12-2008
			WO 2008150767 A2		11-12-2008
<hr/>					
US 2007038230	A1	15-02-2007	NONE		
<hr/>					
US 2007156119	A1	05-07-2007	AT 547992 T		15-03-2012
			AU 2002322374 B2		26-10-2006
			CA 2451824 A1		09-01-2003
			EP 1408846 A2		21-04-2004
			JP 4347043 B2		21-10-2009
			JP 2005507679 A		24-03-2005
			US 2003018323 A1		23-01-2003
			US 2004162547 A1		19-08-2004
			US 2007156119 A1		05-07-2007
			WO 03001987 A2		09-01-2003
<hr/>					
US 2013253481	A1	26-09-2013	CN 101938933 A		05-01-2011
			CN 103654694 A		26-03-2014
			EP 2259710 A2		15-12-2010
			EP 2664270 A1		20-11-2013
			JP 5409655 B2		05-02-2014
			JP 2011510773 A		07-04-2011
			US 2011004157 A1		06-01-2011
			US 2013253481 A1		26-09-2013
			WO 2009098244 A2		13-08-2009
<hr/>					
US 2014052061	A1	20-02-2014	AU 2012242103 A1		10-10-2013
			CN 103476322 A		25-12-2013
			DE 102011001973 A1		18-10-2012
			EP 2696741 A2		19-02-2014
			JP 2014511734 A		19-05-2014
			US 2014052061 A1		20-02-2014
			WO 2012139869 A2		18-10-2012