



(51) International Patent Classification:
F02M 61/04 (2006.01) *F02M 61/12* (2006.01)

(21) International Application Number:
PCT/EP2011/050104

(22) International Filing Date:
5 January 2011 (05.01.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10152677.0 4 February 2010 (04.02.2010) EP

(71) Applicant (for all designated States except US): **DELPHI TECHNOLOGIES HOLDING S.À.R.L.** [LU/LU];
Avenue de Luxembourg, L-4940 Bascharage (LU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CROSSLEY, Stephen** [GB/GB]; 14 Ashcroft Road, Wainscott Kent ME3 8GS (GB). **LIMMER, Andrew** [GB/GB]; Church House, The Street, Bury St Edmunds Suffolk IP29 4PA (GB). **HACKETT, Mervyn** [GB/GB]; 10 Canon Pugh Drive, Sudbury Suffolk CO10 0UX (GB).

(74) Agent: **GREGORY, John**; Courteney Road, Gillingham Kent ME8 0RU (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: NEEDLE FOR NEEDLE VALVE




Figure 2

(57) Abstract: A needle for use in a needle valve, such as the needle valve of a fuel injector, comprises a tip section (2), a first guide section (1a) and a second guide section (3). The tip section (2a) has a needle tip. The first guide section (1a) is remote from the needle tip. The second guide section comprises a tube, wherein the first guide section (1a) and the tip section (2a) are comprised in an integrated inner needle component (7) extending through the tube (3). A method of manufacturing such a needle is also described.

NEEDLE FOR NEEDLE VALVE

TECHNICAL FIELD

- 5 The invention relates to a needle for a needle valve. In aspects, the invention relates to needle valves suitable for use in an injector system, particularly for a common rail fuel injector system.

BACKGROUND TO THE INVENTION

- 10 Needle valves are used in a variety of applications where dosing of fluid is required. A needle-shaped component is able to move within a valve body, with the needle tip adapted to rest on a seat at a nozzle tip of the valve body. Nozzle apertures are provided at the nozzle tip. The nozzle apertures are blocked when the needle tip rests on the seat. When the needle is forced away from the seat – for example, by
15 hydraulic pressure within the valve – then fluid flow may take place. The needle will restrict flow unless the needle tip is moved some distance away from the seat, so this design of valve is suitable for precise dosing of fluid. A context in which such valves are regularly used is that of a fuel injector, such as the fuel injector of a common rail fuel injector system.

20

- A needle valve for a fuel injector needs to meet a number of performance criteria: it needs to withstand a range of operating pressures, it needs sufficient structural strength and good resistance to wear to allow it to operate reliably over a good operating life, and it should be easy and cheap to manufacture and use. It is
25 desirable to provide a needle valve that will perform better than conventional needle valves in respect of these performance criteria, particularly in respect of a fuel injector for use in a common rail fuel injector system for a diesel engine.

- Developments on conventional needle valves are taught, for example, by
30 US2009/0179166, DE 19503224 and WO 2004/106726. These all teach new designs of needle valves for use in gasoline injectors for specific technical purposes. US 2008/018101, published after the priority date of the present application, describes a number of multi-part needle designs for use in needle valves.

- 35 SUMMARY OF THE INVENTION

According to the present invention, there is provided a needle for use in a needle valve, the needle comprising: a tip section having a needle tip; a first guide section

remote from the needle tip; and a second guide section comprising a tube, wherein the first guide section and the tip section are comprised in an integrated inner needle component extending through the tube.

- 5 This arrangement allows for a needle to be produced which is functionally effective but is also much lighter than a conventional valve needle, as the second guide section in the form of a tube will, with the right materials choice, be rigid and have good structural strength, while also being sufficiently light that the overall weight of the needle (and hence of the needle valve) may be substantially reduced.

10

Forming the first guide section and the tip section as sections of an integrated inner needle component is advantageous where greater structural strength is required but it is desirable to reduce the needle weight as compared to a conventional valve needle.

15

Advantageously, the tube is a metal tube. This provides effective structural strength and performance at the high temperatures present in a diesel fuel injector, and the manufacture of this component is straightforward and inexpensive.

- 20 Preferably the second guide section is retained over the tip section by a first interference fit, and advantageously the second guide section is retained over the first guide section by a second interference fit. This allows for easy and effective assembly of the needle component. In this arrangement, it is preferable if the first interference fit is tighter than the second interference fit.

25

An end of the tube associated with the first guide section may be formed as a spring seat for a biasing spring of a needle valve. This simplifies the manufacture of individual components and avoids the introduction of a recess.

- 30 The tube preferably has a plurality of apertures between connections to the needle tip section and the first guide section to allow fluid flow within the tube section. This is desirable to balance pressure in the needle valve, and will not have an effect on flow if the apertures are holes of sufficient size (for example 1.5mm in diameter or greater). It may be desired to affect flow properties by establishing a pressure
35 gradient within the needle valve, in which case smaller apertures may be used. In one arrangement, at least the apertures in the vicinity of the connection to the needle tip section are holes or slots sized to prevent substantially spherical particles of

0.15mm diameter passing therethrough. This is effective to prevent debris reaching the nozzle apertures of a needle valve in which the needle is used.

5 In some arrangements, one or both of the tip section and first guide section is recessed to form a seat for the second guide section when the relevant section is engaged with the second guide section. This defines the connection regions between components effectively, and ensures accurate component alignment.

10 In one aspect, the invention provides a needle valve containing a needle as described above.

In another aspect, the invention provides a fuel injector containing such a needle valve.

15 In a further aspect, the invention provides a method of manufacturing a needle for a needle valve, comprising: forming an integrated component comprising a needle tip section and a first guide section for the needle; forming a tube to form a second guide section; and fixing the second guide section both to the needle tip section and to the first guide section.

20 Advantageously, the tube is a metal tube and forming the tube comprises swaging the metal tube.

25 Preferably, fixing the second guide section to the needle tip section and the first guide section comprises press fitting the second guide section both on to the needle tip section to form a first interference fit and on to the first guide section to form a second interference fit.

30 In this way, a needle of the type described above can be formed cheaply and efficiently using a novel combination of conventional machining and assembly processes.

BRIEF DESCRIPTION OF THE DRAWINGS

35 The invention will now be described, by way of example only, by reference to the following drawings in which:

Figure 1 shows a prior art fuel injector system using a needle valve;

Figure 2 shows a first embodiment of a needle for a needle valve;

Figures 3A and 3B show second and third embodiments of a needle for a needle valve; and

Figure 4 shows the needle of Figure 3B installed in a needle valve.

5

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The needle and needle valve to be described below are suitable for use in an injector system, and in particular to a common rail fuel injector system. An existing common rail fuel injector system in which the needle and needle valve to be described may be used will now be discussed with reference to Figure 1. This system is particularly suitable where diesel is the fuel used.

10

Benefits of common rail fuel injectors include minimal engine warm-up time, lower engine noise and lower emissions, as compared to other known systems. Typically, a common rail fuel system includes a common pressure accumulator, called the "rail", which is mounted along the engine block and fed by a high pressure pump. The pressure level of the rail is electronically regulated by a combination of metering on the supply pump and fuel discharge by a high-pressure regulator (when fitted). The pressure accumulator operates independently of engine speed or load, so that high injection pressure can be produced at low speeds if required. A series of injectors are connected to the rail, and each is opened and closed, such as by means of a solenoid valve or piezoelectric actuator, as directed by the engine control unit (ECU), which opens each injector electronically.

15

20

One form of conventional common rail fuel injector is shown by way of example in Figure 1. It comprises a nozzle needle (26) slidable within a bore formed in a nozzle body (22) and engageable with a seating (21) at the free end of the bore to control delivery of fuel from the bore to a combustion chamber via one or more outlets (24) adjacent the free end. The bore includes a region towards the nozzle end of a diameter similar to the diameter of the needle (26) so that the bore acts as guide for the sliding movement of the needle. The bore also includes a region of enlarged diameter defining a gallery (30) for receiving fuel under pressure from a fuel supply passage (102).

30

The nozzle body (22) abuts a piston housing (40) that includes a bore (46) for receiving and guiding a projection that cooperates with, or extends from, the nozzle

35

needle (26). A piston spring (29) acts upon a spring abutment surface formed by an extended diameter region (27) to urge the needle (26) towards the seating (21).

5 In the described example, the fuel supply passage (102) extends through a main body (140) of the injector and the piston housing (40) for conveying pressurised fuel to the fuel gallery (30) in the bore of the nozzle body (22). The fuel gallery (30) also communicates, continuously, with a restricted outlet passage (50), that allows fuel to be in communication with the supply passage (102) when the pin (104) is in the de-energised state. In the energised state of the pin (104), fuel is allowed to return to a
10 relatively low pressure fuel reservoir. The outlet fuel passage (50) is generally shaped to restrict the rate at which fuel can flow from the fuel gallery (30).

Control of the fuel pressure within the injector is achieved using an electromagnetic actuator (100) that acts by way of a coil winding (108) which pulls an armature (114)
15 against the force of a spring (106) to lift a pin (104) off its associated valve seat (118). This allows the fuel to "spill" across the valve seat (118) and hence causes the fuel pressure within the outlet passage (51) immediately above the needle (26) to fall to an intermediate pressure, below rail pressure but above back leak pressure. The resultant force imbalance on the nozzle needle (26) due to the difference between
20 rail and intermediate pressures causes the nozzle needle (26) to rise thereby initiating an injection.

The needle to be described below is particularly suitable for use as the needle (26) in the common rail fuel injector of Figure 1. It will be understood that the above
25 described fuel injector is but one of many variations that are possible, and the needle described below is not limited to use in a fuel injector, let alone to use in a fuel injector having all of the features mentioned above.

A first embodiment of a needle for a needle valve is shown in Figure 2. The needle
30 has a tip section (2) comprising a needle tip, a first guide section (1) remote from the needle tip, and a second guide section in the form of a tube (3).

The needle has a first guide section in the form of an upper guide (1) that is adapted to be received in a bore of the valve body (such as bore (46) in the Figure 1 arrangement). Pressure on the end surface (33) of the upper guide (1) drives the
35 needle towards closure. In the arrangement shown, the upper guide (1) has a narrow guide section (31) and a main body section (32) of greater diameter. A step

(34) is formed between the narrow guide section (31) and the main body section (32) – this step acts as a seat for a spring (not shown, though an equivalent arrangement is shown in Figure 4) to bias the needle towards valve closure. For a needle valve for use in a fuel injector, a typical diameter G for the narrow guide section (31) could be 2mm, and a typical diameter D for the main body section (32) could be 4mm. In different designs of needle valve, G may be chosen to lie in the range of 1.5mm to 5mm, and D may be chosen to lie in the range 2mm to 6mm.

The tip section (2) is a discrete component, formed separately from the upper guide (1). While the upper guide (1) will typically be made of steel, the tip section (2) need not be – while it may be made from steel, it may also be made of a ceramic (such as silicon nitride, or zirconium oxide stabilized by magnesium oxide) where more suitable to the conditions experienced by the needle tip. The needle tip is adapted to form a sealing engagement against a valve body in the normal manner for a needle valve, for example as shown in the exemplary use in Figure 1. In a needle for use in the needle valve of a fuel injector, a suitable overall length L for the needle may be 60mm. In different designs of needle valve, L may be chosen to lie in the range 40mm to 100mm – in other designs, an even greater length of needle may be used.

The tip section (2) and the upper guide (1) are both retained within a tube (3), which forms a second guide section. At one end of the tube (3), the tube's inner surface forms a first interference fit (6) with an outer surface of the tip section (2). At the other end of the tube (3), the tube's inner surface forms a second interference fit (5) with the outer surface of the main body section (32) of the upper guide (1). In the region of the interference fit (5, 6), the tip section (2) and the upper guide (1) are recessed from the end up to a seat position, so that when the fit is made between the components, the tube (3) abuts with the seat formed on the tip section (2) and the upper guide (1). The size difference between the diameter of the tube and the larger diameter of the component to which the tube is fitted will typically be from 2 to 50µm, depending on the operating parameters for the needle valve of which the needle is to be a part.

The tube (3) provides the only connection between the tip section (2) and the upper guide (1). The structural strength of the tube form means that if the tube (3) is made of a suitable material and at a suitable thickness, it will be sufficiently stiff and strong that the needle valve will function within its operating parameters, but it will also be very light. The tube (3) will typically be made of a suitable steel, and may have a wall

thickness of approximately 0.5mm – the wall thickness may in practice be chosen to provide an appropriate combination of rigidity and weight.

As the second guide is in the form of a hollow tube (3), it is possible for the fuel or other fluid dosed through the needle valve to flow through it. This may be desirable to prevent unnecessary pressures on the tube, and even (as discussed below) in some arrangements to protect the valve aperture area. In Figure 2, the tube (3) is provided with a fuel inlet hole (4) near to the mounting on the upper guide (1) and with a fuel outlet hole (8) near to the mounting on the needle tip. These holes (4, 8) should be sufficiently large in size (for example 1.5mm in diameter) if they are not intended to restrict the flow and create a pressure difference within the needle itself. In some embodiments, these holes may indeed be used to restrict flow and so affect the properties of a needle valve itself – in this case, the holes will be calibrated relative to the valve nozzle to achieve desired flow properties.

The components of the needle can be manufactured separately, and the needle assembled from the separate components. The upper guide (1) is a conventional machined part. The tip section (2) may similarly be a conventional machined part, or may be formed by any process appropriate to the material used to form it and the dimensions and tolerances required. The tube (3) requires at least one change in diameter between different parts of the tube. An effective way to do this and also to retain structural strength is to form the tube (3) by swaging (restricting the diameter of part of a tube by forcing it through an appropriately sized die). In the Figure 2 arrangement, the tube (3) may be formed into its desired shape by swaging at the needle tip end. The holes (4, 8) in the tube (3) may be formed by conventional machining processes.

The tip section (2) and the upper guide (1) are then press fitted into the appropriate ends of the tube (3) to form the needle as shown in Figure 2. The formation of recesses and seats in the interference fit regions of the tip section (2) and the upper guide (1) assists in ensuring that this press fitting achieves intended results in a replicable fashion.

Needles according to second and third embodiments are shown in Figures 3A and 3B respectively. The needles of Figures 3A and Figures 3B are examples of a variant to the Figure 2 design – in this variant, the tip section (2a) and the upper guide section (1a) are not discrete components but are instead parts of an of an

integrated inner needle component (7). This approach may provide greater axial strength and torsion resistance, as the axial load is shared between the inner needle component (7) and the tube (3). With this arrangement, the thickness of the inner needle component (7) can be reduced substantially beyond that of a conventional
5 needle, as the rigidity of the needle is enhanced by the presence of the tube (3). The diameter of the inner needle component may be between 1mm and 4mm for needle valves of the type described above, depending on the axial load to be supported.

Figure 3A shows a needle with a tube (3) adapted to form interference fits with both
10 the needle tip section (2a) and the upper guide section (1a) of the inner needle component (7). Most of the axial load in this arrangement is taken by the inner needle component (7), with the tube (3) taking some axial load and increasing the overall rigidity of the arrangement. As the tube (3) takes significantly less axial load than in the Figure 2 arrangement, less load needs to be supported by the two
15 interference fits. In the arrangement shown in Figure 3A, this allows the recess and seat arrangement used in Figure 2 to be abandoned, with the interference fits not positively located on the inner needle component. If desired, a recess and seat arrangement of the type used in Figure 2 could be used in the Figure 3A arrangement (and similarly in the Figure 3B arrangement) to define the interference
20 length more clearly. Alternatives to a recess and seat arrangement could also be used for this purpose at one or both interference fits – diameter changes to the inner needle component (7) could be used, or grooves could be made in one of the components in the interference fit regions.

25 The third embodiment shown in Figure 3B is another example of the design shown in Figure 3A, but with different dimensions – the inner needle component 7 is shorter than for the second embodiment, and the needle is thus shorter overall. The length of the upper guide section (1a) and the needle tip section (2a) is constrained by their function, so in this case their length is unaffected and the length of tube (3) reduced
30 along with the inner needle component (7).

The third embodiment uses differently sized holes (9, 10) in the tube to achieve different functional results. In this case small holes (0.025mm to 0.15mm in diameter) are used to allow flow inside the tube (3). These holes will restrict flow
35 (and so a greater number of holes may be required to achieve desired flow properties), but will prevent debris from reaching the injection holes in the nozzle tip of the needle valve. These need not be circular holes – the holes may be shaped as

desired to achieve particular fluid flow effects. For example, narrow slots (with widths as indicated above, but with greater length) may be used instead with the same function – these will allow more flow, while still having the same ability to block roughly spherical debris.

5

As the inner needle component (7) is a single component making an interference fit with the tube (3) at two different points, the second and third embodiments use a different construction of tube (3). At the upper guide end, the diameter of the tube (3) is reduced significantly by swaging – while the diameter of the inner needle component (7) is increased in the upper guide section (1a), it is still proportionally less than the diameter of the main body section of the upper guide in the first embodiment. This arrangement allows for easier creation of the interference fits, as discussed below.

10

15 The tube (3) is also modified in the second and third embodiments to provide another feature which simplifies the overall design. At the upper guide end of the tube (3), further away from the needle tip than the interference fit with the upper guide section (1a), the tube (3) is flared outwards to form a spring seat (35), replicating the function of the spring seat (34) in the first embodiment. This arrangement allows for simpler machining of the inner needle component (7) and prevents the creation of a recess that may act as a stress concentrator, and hence as a source of weakness in the needle as a whole.

20

Assembly of the needle of the second and third embodiments is slightly different from the assembly of the needle of the first embodiment. The inner needle component (7) may be manufactured using conventional machining processes and may be machined as a single component. The tube (3) may still be produced from conventional steel tube by swaging, but the swaging process at the upper guide end will be slightly more complex – a double swaging process may be used to produce the constriction and spring seat, or a single swaging process may be used with an appropriately designed bit or mandrel (or combination). The press fit of the inner needle component (7) into the tube (3) will be carried out by insertion of the needle tip section (2a) into the upper guide end of the tube (3). Sensors on the assembly used for this press fitting process may be used to determine load against displacement to ensure correct placement and tightness of the interference fits. In this arrangement, it is desirable for the second interference fit (5) to the upper guide section (1a) to be less tight than the first interference fit (6) to the needle tip section

25

30

35

(2a). The diameter of the second interference fit (5) should also be greater than that of the first interference fit (6) to allow effective assembly. On assembly, the second interference fit will start to be made first, and the first interference fit made on further insertion of the inner needle component (7). This arrangement allows both
5 interference fits to be checked for tightness on assembly.

In other embodiments, other connection methods (such as laser welding) may be used to provide connection between components rather than use of interference fits. This will generally complicate manufacture by adding additional steps, though it may
10 be desirable where operating parameters required of a particular needle design cannot easily be met by use of interference fits.

Figure 4 shows the needle of Figure 3A fitted into a complete needle valve. As can be seen, the spring (11) rests on the spring seat formed by the end of the tube (3),
15 and the needle tip section (2a) of the inner needle component (7) is seated on the nozzle section of the valve, such that when seated, fluid cannot pass through the nozzle apertures, but when there is sufficient hydraulic pressure in the gallery to lift the needle tip away from the seat, fluid is dosed through the needle apertures. The first and third embodiments will fit within a complete needle valve in essentially the
20 same way – the use of the second embodiment here is simply an example of a complete needle valve using a needle according to embodiments as described here. The person skilled in the art will also readily see how the needle valve of Figure 4 may be used in the fuel injector of Figure 1. The use of such a needle, and such a needle valve, provides a number of practical advantages – lighter components,
25 effective control of nozzle properties, and simple machining and construction. The person skilled in the art will also readily appreciate how changes may be made to the embodiments of Figures 2, 3A and 3B to provide further embodiments of the present invention.

CLAIMS

1. A needle for use in a needle valve, the needle comprising:
5 a tip section (2a) having a needle tip;
a first guide section (1a) remote from the needle tip; and
a second guide section comprising a tube (3),
wherein the first guide section (1a) and the tip section (2a) are comprised in an
integrated inner needle component (7) extending through the tube (3).
10
2. A needle as claimed in claim 1, wherein the tube (3) is a metal tube.
3. A needle as claimed in claim 1 or claim 2, wherein the second guide section
is retained over the tip section (2, 2a) by a first interference fit (6).
15
4. A needle as claimed in any preceding claim, wherein the second guide
section is retained over the first guide section (1, 1a) by a second interference fit (5).
5. A needle as claimed in claim 3, wherein the second guide section is retained
20 over the first guide section (1, 1a) by a second interference fit (5) and wherein the
first interference fit (6) is tighter than the second interference fit (5).
6. A needle as claimed in any preceding claim, wherein an end of the tube (3)
associated with the first guide section (1a) is formed as a spring seat (35) for a
25 biasing spring of a needle valve.
7. A needle as claimed in any preceding claim, wherein the tube (3) has a
plurality of apertures (4, 8, 9, 10) between its connection with the first guide section
(1a) and the tip section (2a) to allow fluid flow within the tube (3).
30
8. A needle as claimed in claim 7, wherein at least the apertures (9) in the
vicinity of the connection with the tip section (2a) are holes or slots sized to prevent
substantially spherical particles of 0.15mm diameter passing therethrough.
- 35 9. A needle as claimed in any preceding claim, wherein one or both of the tip
section (2) and first guide section (1) is recessed to form a seat for the second guide
section when the relevant section is engaged with the second guide section.

10. A needle valve containing a needle as claimed in any preceding claim.

11. A fuel injector containing a needle valve as claimed in claim 10.

5

12. A method of manufacturing a needle for a needle valve, comprising:
forming an integrated component (7) comprising a needle tip section (2a) and
a first guide section (1a) for the needle;

forming a tube (3) to form a second guide section; and

10 fixing the second guide section both to the needle tip section (2a) and to the
first guide section (1a).

13. A method as claimed in claim 12, wherein the tube (3) is a metal tube and
forming the tube comprises swaging the metal tube.

15

14. A method as claimed in claim 12 or claim 13, wherein fixing the second guide
section to the needle tip section (2a) and the first guide section (1a) comprises press
fitting the second guide section both on to the needle tip section (2a) to form a first
interference fit (6) and on to the first guide section (1a) to form a second interference

20 fit (5).




Figure 1




Figure 2




Figure 3A




Figure 3B




Figure 4

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2011/050104

A. CLASSIFICATION OF SUBJECT MATTER

INV. F02M61/04 F02M61/12
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

F02M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y,P	WO 2010/018024 A1 (BOSCH GMBH ROBERT [DE]; KUEGLER THOMAS [DE]; KRASEMANN MARKUS [DE]; OP) 18 February 2010 (2010-02-18)	1-4, 7-12,14
A,P	page 9, line 8 - line 15; figure 6 page 9, line 30 - page 10, line 20; figures 8,9 figure 10	5,6,13
Y	----- WO 96/00348 A1 (BOSCH GMBH ROBERT [DE]; ROMANN PETER [DE]; REITER FERDINAND [DE]; MAIE) 4 January 1996 (1996-01-04)	1-4, 7-12,14
A	page 11, line 29 - page 12, line 20; figures 7-10	5,6,13
X	----- US 2005/072865 A1 (GOTO MORIYASU [JP] ET AL) 7 April 2005 (2005-04-07)	1
A	paragraph [0061]; figure 12 -----	12



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 March 2011

Date of mailing of the international search report

10/03/2011

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Kolland, Ulrich

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2011/050104

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2010018024 A1	18-02-2010	DE 102008041165 A1	18-02-2010
WO 9600348 A1	04-01-1996	DE 4421881 A1	04-01-1996
US 2005072865 A1	07-04-2005	CN 1603608 A	06-04-2005
		DE 102004045970 A1	18-08-2005
		JP 3891974 B2	14-03-2007
		JP 2005106018 A	21-04-2005
