



(51) International Patent Classification:

A61F 2/76 (2006.01) A61M 31/00 (2006.01)  
A61F 2/04 (2006.01) A61M 35/00 (2006.01)

(21) International Application Number:

PCT/US20 12/056968

(22) International Filing Date:

24 September 2012 (24.09.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/538,723 23 September 2011 (23.09.2011) US

(71) Applicant (for all designated States except US): **PULMONX, INC.** [US/US]; 700 Chesapeake Drive, Redwood City, CA 94063 (US).

(72) Inventors; and

(71) Applicants (for US only): **OLIVERA, Ryan** [US/US]; 5874 Valle Vista Court, Granite Bay, CA 95746 (US). **NGUYEN, Hoang** [US/US]; 2914 Glen Darby Court, San Jose, CA 95148 (US).

(74) Agents: **HESLIN, James, M.** et al; Wilson Sonsini Goodrich & Rosati, 650 Page Mill Road, Palo Alto, CA 94304-1050 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: IMPLANT LOADING DEVICE AND SYSTEM




FIG. 2B

(57) Abstract: Devices, methods, and systems are provided for loading an implantable device into a container. One aspect of the loading system contains a loader element with a loading tunnel that is configured to gradually contract an implantable device into a compressed state of reduced size relative to an expanded state as the implantable device travels through the loading tunnel.

WO 2013/044267 A1

## **IMPLANT LOADING DEVICE AND SYSTEM**

### **CROSS-REFERENCES TO RELATED APPLICATIONS**

[0001] This application claims the benefit of Provisional Application No. 61/538,723 (Attorney Docket No. 20920-740.102), filed September 23, 2011, the full disclosure of which is incorporated herein by reference. This application is also a continuation-in-part application of U.S. Patent Application No. 12/820,393 (Attorney Docket No. 20920-740.301), filed on June 22, 2010, which is a continuation application of U.S. Patent Number 7,771,472 (Attorney Docket No. 20920-740.201), filed on November 18, 2005, which claims the benefit and priority of U.S. Provisional Application No. 60/630,399 (Attorney Docket No. 20920-704.101), filed on November 19, 2004, all of which are incorporated herein by reference.

### **FIELD OF THE INVENTION**

[0002] Present embodiments relate generally to devices, methods, and systems for loading an implantable device into a container.

### **DESCRIPTION OF THE RELATED ART**

[0003] Pulmonary diseases, such as chronic obstructive pulmonary disease, (COPD), reduce the ability of one or both lungs to fully expel air during the exhalation phase of the breathing cycle. Such diseases are accompanied by chronic or recurrent obstruction to air flow within the lung. Because of the increase in environmental pollutants, cigarette smoking, and other noxious exposures, the incidence of COPD has increased dramatically in the last few decades and now ranks as a major cause of activity-restricting or bed-confining disability in the United States. COPD can include such disorders as chronic bronchitis, bronchiectasis, asthma, and emphysema.

[0004] It is known that emphysema and other pulmonary diseases reduce the ability of one or both lungs to fully expel air during the exhalation phase of the breathing cycle. One of the effects of such diseases is that the diseased lung tissue is less elastic than healthy lung tissue, which is one factor that prevents full exhalation of air. During breathing, the diseased portion of the lung does not fully recoil due to the diseased (e.g., emphysematic) lung tissue being less elastic than healthy tissue. Consequently, the diseased lung tissue exerts a relatively low driving force, which results in the diseased lung expelling less air volume than a healthy lung. The reduced air volume

exerts less force on the airway, which allows the airway to close before all air has been expelled, another factor that prevents full exhalation.

[0005] The problem is further compounded by the diseased, less elastic tissue that surrounds the very narrow airways that lead to the alveoli, which are the air sacs where oxygen-carbon dioxide exchange occurs. The diseased tissue has less tone than healthy tissue and is typically unable to maintain the narrow airways open until the end of the exhalation cycle. This traps air in the lungs and exacerbates the already-inefficient breathing cycle. The trapped air causes the tissue to become hyper-expanded and no longer able to effect efficient oxygen-carbon dioxide exchange.

[0006] In addition, hyper-expanded, diseased lung tissue occupies more of the pleural space than healthy lung tissue. In most cases, a portion of the lung is diseased while the remaining part is relatively healthy and, therefore, still able to efficiently carry out oxygen exchange. By taking up more of the pleural space, the hyper-expanded lung tissue reduces the amount of space available to accommodate the healthy, functioning lung tissue. As a result, the hyper-expanded lung tissue causes inefficient breathing due to its own reduced functionality and because it adversely affects the functionality of adjacent healthy tissue.

[0007] Some recent treatments include the use of devices that isolate a diseased region of the lung in order to reduce the volume of the diseased region, such as by collapsing the diseased lung region. According to such treatments, a delivery catheter is used to implant one or more implantable devices in airways feeding a diseased region of the lung to regulate fluid flow to the diseased lung region in order to fluidly isolate the region of the lung. These implanted implantable devices can be, for example, one-way valves that allow flow in the exhalation direction only, occluders or plugs that prevent flow in either direction, or two-way valves that control flow in both directions.

[0008] The implantable device is radially compressed into a contracted size for loading into the delivery catheter or a container associated with the catheter. It can be difficult to properly compress the implantable device to a size small enough to fit in the delivery catheter. Thus, there is a need for devices for properly compressing and loading an implantable device into a container.

### SUMMARY

[0009] Present disclosure relates to aspects of devices, methods, and systems for loading an implantable device into a container.

[0010] In one aspect, an embodiment of a loading system comprises a loader element with a loading tunnel that is configured to gradually contract an implantable device into a compressed state of reduced size relative to an expanded state as the implantable device travels through the loading tunnel. The loading system further comprises a puller element that is removably attached to the implantable device via a suture, wherein the puller element pulls the implantable device through the loading tunnel. In one aspect, the puller element automatically releases the suture after the implantable device contracts into the compressed state.

[0011] In one aspect, a loading system further comprises a rotator that is disposed on the puller element that is configured to be removably attached to a portion of the suture, wherein a rotation of the rotator causes the suture to detach from the rotator. In another aspect, the rotator may be disposed on the loader element.

[0012] In another aspect, the loading system further comprises a plunger element, wherein the plunger element comprises an elongated portion that is configured to push the implantable device through the loading tunnel. In one aspect, the plunger element is configured to push the implantable device into a delivery catheter.

[0013] In another aspect, the loading tunnel of the loading system comprises a funnel housing that defines an internal, funnel-shaped loading cavity.

[0014] In yet another aspect, the loading tunnel of the loading system further defines an internal transfer cavity that communicates with the loading cavity. In one aspect, the transfer cavity is sized to receive the implantable device from the loading cavity and retain the implantable device in the compressed state.

[0015] In yet another aspect, the loading tunnel of the loading system further defines a container cavity that communicates with the transfer cavity. In one aspect, the container cavity is sized to receive a container that receives the implantable device in the compressed state.

[0016] In one aspect, the implantable device is a pulmonary implant that is configured to be placed within a lung region. In another aspect, the container is a housing of a delivery catheter that is configured to receive the compressed implantable device.

[0017] In yet another aspect, an embodiment of the loading system further comprises a tension element that is configured to communicate a force to the loading tunnel. Additionally or

optionally, an aspect of the loading system comprises a container locking element that is configured to secure and align the container with the loader element.

[0018] This and other aspects of the present disclosure are described herein.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0019] Present embodiments have other advantages and features which will be more readily apparent from the following detailed description and the appended claims, when taken in conjunction with the accompanying drawings, in which:

[0020] FIG. 1A shows one embodiment of a loading system where various elements of the loading system are connected;

[0021] FIG. 1B shows one embodiment of a loading system where the various elements are separated;

[0022] FIGS. 2A-2B show two different views of the various components of one embodiment of the loader element and the puller element;

[0023] FIG. 2C shows one embodiment of a suture attachment element disposed on the puller element;

[0024] FIG. 3 is a flow diagram illustrating an exemplary operation of one embodiment of the loading system;

[0025] FIGS. 4A-4C show various steps of an exemplary operation of one embodiment of the loading system;

[0026] FIGS. 5A-5B illustrate an embodiment of the loading system comprising a catheter locking element;

[0027] FIGS. 6A-6C illustrate an alternative embodiment of the loading system.

### **DETAILED DESCRIPTION**

[0028] Although the detailed description contains many specifics, these should not be construed as limiting the scope of the disclosure but merely as illustrating different examples and aspects of the disclosure. It should be appreciated that the scope of the disclosure includes other embodiments not discussed herein. Various other modifications, changes and variations which will be apparent to those skilled in the art may be made in the arrangement, operation and details of the method, device, and system of the present embodiments disclosed herein without departing from the spirit and scope of the disclosure as described here.

**[0029]** Throughout the specification and claims, the following terms take the meanings explicitly associated herein unless the context clearly dictates otherwise. The meaning of "a", "an", and "the" include plural references. The meaning of "in" includes "in" and "on." Referring to the drawings, like numbers indicate like parts throughout the views. Additionally, a reference to the singular includes a reference to the plural unless otherwise stated or inconsistent with the disclosure herein.

**[0030]** The word "exemplary" is used herein to mean "serving as an example, instance, or illustration." Any implementation described herein as "exemplary" is not necessarily to be construed as advantageous over other implementations.

**[0031]** Disclosed herein are methods, devices and systems for loading an implantable device into a delivery device for delivering the apparatus to a body region, such as a bronchial passageway.

**[0032]** Throughout this disclosure, reference is made to the term "implantable device". As used herein, the term "implantable device" refers to various collapsible and/or self-expanding implant including implants configured to maintain openings in vascular, urinary, biliary, esophageal, and renal tracts, and vena cava filters. Furthermore, it is contemplated that the implantable device may be various pulmonary implants configured to be placed within a lung region to treat pulmonary disorders including but limited to flow restrictive devices such as valves including one-way valves that allow flow in the exhalation direction only, occluders or plugs that prevent flow in either direction, or two-way valves that control flow in both directions.

**[0033]** In one embodiment, present disclosure describes devices, systems, and methods for loading a collapsible pulmonary implant into a delivery system, such as a delivery catheter, in preparation for delivering the implant into a lung region such as the pulmonary airways of a patient. In one embodiment, collapsible pulmonary implants are made of memory-shape materials, such as Nitinol, and are compressed to enable delivery through relatively small and curved bodily pathways to the lung region. In one embodiment, delivery devices, such as catheters, retain the collapsed pulmonary implants in a radially compressed state for delivery to the treatment site, where the implant is released into the lung region and regains its non-compressed shape. The present embodiments disclose various aspects of loading devices that collapse such implants and optionally insert them into a container such as a delivery catheter.

**[0034]** FIGS. 1A and 1B show two perspective views of one embodiment of a loading system **100** for compressing an implantable device such as a pulmonary implant and optionally for inserting the implantable device into a housing of the delivery catheter. As seen in FIGS 1A and

IB, one embodiment of the loading system **100** comprises a loader element **110**, a puller element **120**, and a plunger element **130**. The plunger element **130** comprises an elongated portion **131** and optionally comprises a locking element **132** whereby the locking element **132** is configured to be inserted into the loader element **110** and the puller element **120** such that the loading system **100** may be configured, at least before the loading operation, as an inter-connected discrete unit. Alternatively, the loader element **110** and the puller element **120** may be secured through other locking or securing means and the plunger element **130** may be a separate unit.

[0035] Referring now to FIGS 2A -2D, where various components of one embodiment of the loader element **110** and the puller element **120** are shown. As described in detail below, the loader element **110** is used to compress a collapsible implantable device **140** to a size that can fit into a container, such as a housing of the delivery catheter. Additionally and optionally the loader element **110** is configured to facilitate the alignment of the compressed implantable device **140** with a container, such as a housing of the delivery catheter. As seen in FIG. 2, the loader element **110** comprises a loading tunnel **112** disposed longitudinally within the loader housing **111**. In one embodiment, the loading tunnel **112** may comprise three regions, including a funnel-shaped loading region **112a**, a container region **112b**, and a catheter region **112c**. The loading region **112a** of the loading tunnel **112** gradually reduces in diameter moving in a rearward direction from the front opening **110a** toward the rear opening **110b** of the loader element **110** so as to provide the loading region **112a** with a funnel shape. The housing region **112b** has a shape that substantially conforms to the outer shape of the catheter housing or configured to receive a portion of the catheter so that the catheter housing may be inserted into and/or aligned with the housing region **112c**. The catheter region **112c** is shaped to receive the housing of the delivery catheter. Additionally and optionally, the loading tunnel **112** may be connected to a tension element **113** exemplarily shown as a spring that is configured to apply a force to the loading tunnel towards the front opening **110a**.

[0036] Referring now to the puller element **120**, which in one embodiment may comprise a substantially cylindrical hollow body. The puller element **120** comprises a pin **121** disposed on the hollow body or it may be suspended within the hollow body. The puller element **120** further comprises a moveable rotator **122** that is configured to rotate along the pin **121**. As seen in FIG. 2B, in one embodiment, the rotator **122** may comprise a body that is configured to connect to the pin **121**, a first tine **122a** and a second tine **122b**, whereby the first tine **122a** is longer than the second tine **122b**. In one embodiment, one or both tines may be substantially triangular in shape

such that the base of the tines that is connected to the body of the rotator is larger than the tip of the tines. Alternatively, the tines may assume various other configurations. Furthermore, it is contemplated that the rotator may comprise a single tine.

[0037] The loader element **110** further comprises a rotator track that is configured to accommodate the rotator **122**. The rotator **122** is received by the tack disposed on the loader element **110** such that the rotator **122** resides within the rotator track when the loader element **110** and the puller element **120** are connected. The rotator track is further configured to allow the rotator **122** to slide along the rotator track during the loading operation, when the puller element **120** is moved away from the loader element **110**.

[0038] As seen in FIG. 2C, the loading system **100** further comprises at least one flexible element that is configured to connect the puller element **120** and the implantable device **140**. The flexible element may be a wire or suture, such as polypropylene monofilament suture. In one embodiment, the suture **150** is affixed to the puller element **120** by one or more adhesives configured to bond the suture **150** to the puller element **120**. Alternatively or additionally, the second end of the suture **150** may be affixed to the puller element **120** by fastening, tying, or looping the suture **150** to the puller element **120**. It is contemplated that the puller element **120** comprises a suture attachment element **123** that is configured to receive the second portion of the suture **150** and enables and/or facilitates affixing the suture **150** to the puller element **120**. In one embodiment, the suture attachment element **123** may comprise an attachment anchor **123a** where the suture **150** may be attached to the attachment anchor **123a** by fastening, tying, and/or looping around the attachment anchor **123a**. The attachment element **123** may further comprise a receiving track configured to receive the suture **150** and may comprise slots where adhesives may be applied to affix the suture **150** to the puller element **120**.

[0039] In one embodiment, the suture **150** is configured as a suture loop that is removably attached to the implantable device **140** by threading the loop through a portion of the implantable device **140** as described in co-pending U.S. App. Ser. No. 12/820,393. The suture loop is further removably attached to the rotator **122** such that the suture loop resides between the first and second tines of the rotator **122**.

[0040] Referring now to FIG. 3, which is a flow diagram that illustrates exemplary steps of operating one embodiment of the loading system. Aspects of the steps described herein are also illustrated in FIGS 4A-4C as well as FIGS 1A-1B. In one embodiment, as seen in FIG. 1A, the loading system **100** comprising a loader element **110**, a pulling element **120**, and a plunger

element **130** are mated to form a discrete unit. It is further noted that the implantable device **140** is placed within loading region **112a** of the loading tunnel **112** and attached to the suture **150** prior to the loading operation.

[0041] At step **201**, the loader element **110**, puller element **120**, and the plunger element **130** are unlocked. In an embodiment, where the loading system **100** is configured as a discrete unit, the locking element **132** is released by removing the plunger element **130** from the puller element **120** and the loader element **110**. Alternatively, the loader element **110** and the puller element **120** may be locked or secured through other means, and it is contemplated that during step **201** that such lock means is released thus enabling the loader element **110** and the puller element **120** to be separated.

[0042] At step **202**, the implantable device **140** is pulled through the loading region **112a** of the loading tunnel thereby causing the implantable device **140** to transition from an expanded state to a compressed state. The puller element **120** is pulled or moved away from the loader element **110**. As the puller element **120** is moved away from the loader element **110**, the suture **150** attached to the implantable device **140** and the puller element **120** pulls the implantable device **140** through the loading region **112a** towards the container region **112b** of the loading tunnel **112**. As this happens, the funnel shape of the loading region **112a** causes the implantable device **140** to be gradually compressed such that the diameter of the implantable device **140** is gradually reduced as the implantable device **140** moves toward and into the container region **112b**. In one embodiment, the walls of the loading tunnel **112** provide an equally balanced compressive force around the entire circumference of the implantable device **140** as the implantable device moves through the loading tunnel **112**. This reduces the likelihood of deforming the implantable device **140** during compression. Concurrent to the pulling of the implantable device **140**, the rotator which is removably attached to the suture **150** is configured to move or slide away from the loader device **110** along the rotator track disposed on the loader device **110**.

[0043] At step **203**, and as seen in FIG. 4A, the puller element **120** is sufficiently pulled or moved away from the loader element **110** causing the implantable device **140** to be pulled into the container region **112b** of the loading tunnel **112**. Furthermore, the movement of the puller element **110** in conjunction with the resulting suture tension causes the rotator to move sufficiently away from the loader element **110** such that that the rotator exits the track.

Thereafter, the suture tension due to the continued pulling of the puller element **120** causes the rotator **122** to rotate along the pin. The rotation of rotator **122** causes the rotator **122** to transition

from a first position (while rotator was inside the rotator track) to a second position (after the rotator exits the rotator track) and/or causes the orientation of the rotator tines to change. The rotation and/or the subsequent transition of the rotator **122** cause the suture **150** that was attached to the rotator **122** to detach from the rotator **122**. For example, the portion of the suture **150** that was attached to the rotator **122** between the first and second tines **122a** and **122b** may slide off due to the rotation thus detaching the suture **150** from the rotator **122**.

[0044] At step **204**, the puller element **120** is further pulled or moved away from the loader element **110** causing a complete separation of the puller element **120** and the loader element. The suture **150** is attached to the puller element **120** while it is detached from the implantable device **140**. Specifically, after the detachment of the suture **150** from the rotator **122**, the suture **150** is drawn through and exits the implantable device **140** and thereby detaching the suture **150** from the implantable device **140**.

[0045] At step **205**, and as seen in FIG. 4B, a portion of the delivery catheter **160** is placed into the loader element **110**, such that the portion of the delivery catheter **160** is inserted into and/or aligned with the catheter region **112c** of the loading tunnel **112**. Optionally, prior to placing the delivery catheter **160** into the loader element **110**, the loader tunnel **112** is first pushed towards the rear opening **110a** and thereby compressing the tension element **113**. Thereafter, a portion of the delivery catheter **160** is placed into the loader element **110** as described above and the loading tunnel **112** is released. The compressed tension element **113** thereby applies a force that pushes the loading tunnel **112** towards the front opening **110b**; this force may be advantageous since it may ease the alignment of the delivery catheter **160** with the catheter region **112c** of the loading tunnel **112** by pushing the loading tunnel **112** towards the delivery catheter **160**.

[0046] At step **206**, and as seen in FIG. 4C, after the portion of the delivery catheter **160** is placed into and/or substantially aligned with the loader element **110**, the plunger element **130** is used to push the implantable device **140** into the delivery catheter **160**. In one embodiment, the elongated portion **131** of the plunger element **130** is inserted into the loading tunnel **112** through the rear opening **110b** of the loader element **110**, thereafter, the elongated portion **131** forces the implantable device **140** that resides in the container region of the loading tunnel **112** into the delivery catheter **160**. Thereafter, the delivery catheter containing the implantable device is removed from the loader element **110**.

[0047] An alternative embodiment of a loading system is shown in FIGS. 5A and 5B. As seen FIG. 5A, an embodiment of a loading system **300** comprises a loader element **310**, a puller

element **320**, and a plunger element (not shown). The loader element **310** comprises a front opening **310a** and a rear opening **310b**. The loader element **310** further comprises a loading tunnel **311** that is held in place or suspended within the housing element **310** by a tunnel mount **312**. The loading tunnel **311** may comprise a loading region, a container region, and the catheter region similar to the configuration as described above. An optional first tension element **313** is disposed within the housing element **310** that applies a tension to the loading tunnel **311** and/or the tunnel mount **312**.

[0048] As seen in FIGS. 5A and 5B, in one embodiment, a catheter locking element **340** comprises a first opening **341** and a second opening **342** is movably disposed within the loader element **310**. The area of the first opening **341** is configured to accommodate a delivery catheter **350** while facilitates in placing and/or securing the delivery catheter **350** such that the catheter is substantially aligned with the loading tunnel **312**. The second opening **342** is configured with a larger area than the first opening **341** to facilitate the insertion and/or removal of the delivery catheter **350** from the loader element **310**. The first opening **341** and the second opening **342** are connected via a channel, wherein the channel is configured to accommodate the delivery catheter **350** such that the delivery catheter **350** may transition from the first opening **341** to the second opening **342** and vice-versa. In one embodiment, the catheter locking element **340** is disposed on top of a second tension element **314** within the housing element **310**.

[0049] Prior to the loading operation, as seen in FIG. 5A, the second tension element **314** is compressed by the catheter locking element **340** by using a locking pin **315** that protrudes from the tunnel mount **312**. The locking pin **315** may be inserted into the first opening **341** of the catheter locking element **320** thereby causing the catheter locking element **340** to compress the second tension element **314** and substantially aligns the second opening **342** with the loading tunnel **311**.

[0050] The puller element **320** comprises a pin **321** and a moveable rotator **322** that is configured to rotate along the pin **321**. As seen in FIG. 2B, in one embodiment, the rotator **322** comprises a body that is configured to connect to the pin **321** and a tine **322a**. Alternatively, the rotator **322** may assume various other configurations such as the rotator previously described comprising multiple tines.

[0051] Additionally, the loading system **300** further comprises a suture that is affixed to a suture attachment element (not shown) on the puller element **320**. The suture may be configured as a

suture loop that is threaded through an implantable device **330** and removably attached to the rotator **322** as described above.

[0052] In an exemplary operation of the loading device **300**, the puller element **320** is pulled or moved away from the housing element **310** until the rotator **322** rotates to release the suture and consequently the suture is released from the implantable device **330**. Thereafter, a delivery catheter **350** is inserted into the loader element **310** through the second opening **342** of the catheter locking element **340**. Tension is then applied to the catheter **350** which causes the tunnel mount **312** to move towards the rear opening **310b** of the loader element **310**. The movement of the tunnel mount **312** causes the locking pin **315** to exit from the first opening **341** of the catheter locking element **340** thereby causing the second tension element **314** to transition from a compressed state to a relaxed state which moves the catheter locking element **340** away from the base of the second tension element **314**. The movement causes the first opening **341** of the catheter locking element **340** to align with the loading tunnel **311** and causes the delivery catheter **350** to exit the second opening **342** and transition through the channel into the first opening **341** as seen in FIG. 5B. Since the first opening **341** is configured with a smaller diameter than the second opening **342**, by aligning with the loading tunnel **311** and placing the catheter **350** in the first opening **341**, the catheter locking element **350** is configured to facilitate or aid in the stabilizing and/or the aligning of the catheter **350** with the loading tunnel **311**. Thereafter, the plunger element (not shown) is applied to push the implantable device **330** into the catheter **350**.

[0053] Thereafter, the plunger element is removed from the loader element **310**, and the catheter **350** is release from the catheter locking element **340** by applying tension to the second tension element **314** such that the catheter **350** transitions back into the second opening **342**, thereafter, the catheter **350** is removed from the loader element **310**.

[0054] In yet another embodiment, as seen in FIGS. 6A-C, one embodiment of a loading system **400** comprises a loader element **410**, puller element **420**, and the plunger element **430**. The loader element **410** comprises loading tunnel **411** comprising a loading region, container region, and a catheter region as described above. In one embodiment, the loader element **410** further comprises a tunnel mount **412**, a pin connected to the loader element **410** and a rotator **413** configured to rotate along the pin. A suture is affixed to the puller element and it is removably attached to implantable device **440** and the rotator **413** as described above. The loader element **410** further comprises a tension element **414** that is disposed between tunnel mount **412** and the

loading portion of the loading tunnel **411a**. The puller element **420** comprises a tunnel locking element **421** that is configured to secure the loading tunnel **411** when the puller element **420** and the loader element **410** are mated.

[0055] In an exemplary operation of the loading system **400**, as seen in FIG. 6B the loading element **410** and the plunger element **430** are initially mated. Likewise, the puller element **420** and the loader element **410** are initially connected. As seen in FIG. 6C, a delivery catheter is first placed into the loading system **400** through the puller element **420**. The puller element **420** is moved towards the plunger element **430**, and consequently, a tension is applied through the suture to pull the implantable device **440** from the loading portion into the housing portion of the loading tunnel **411**. Further movement of the puller element **420** causes the rotator **413** disposed on the loader element **410** to rotate and the suture is released from the rotator **413**. Thereafter, the suture is released from the implantable device **440**. Further movement of the puller element **420** towards plunger element **430** causes the elongated portion of the plunger element **430** to push the implantable device **440** into the delivery catheter **450**, thereafter, the loaded delivery catheter is removed from the loader element **410**.

[0056] Also provided are kits for use in practicing the subject methods, where the kits typically include one or more of the above system for loading an implantable device, as described above. In certain embodiments, the kits at least include a loader element. Kits may also include a plunger element, an implantable device, and/or a delivery catheter. Additional components may be included in the kit.

[0057] In addition to above-mentioned components, the subject kits typically further include instructions for using the components of the kit to practice the subject methods. The instructions for practicing the subject methods are generally recorded on a suitable recording medium. For example, the instructions may be printed on a substrate, such as paper or plastic, etc. As such, the instructions may be present in the kits as a package insert, in the labeling of the container of the kit or components thereof (i.e., associated with the packaging or subpackaging) etc. In other embodiments, the instructions are present as an electronic storage data file present on a suitable computer readable storage medium, e.g. CD-ROM, diskette, etc. In yet other embodiments, the actual instructions are not present in the kit, but means for obtaining the instructions from a remote source, e.g. via the internet, are provided. An example of this embodiment is a kit that includes a web address where the instructions can be viewed and/or from which the instructions

can be downloaded. As with the instructions, this means for obtaining the instructions is recorded on a suitable substrate

[0058] While the above is a complete description of various embodiments, any of a number of alternatives, modifications, and equivalents may be used in alternative embodiments. Therefore, the above description should not be taken as limiting the scope of the invention as it is defined by the appended claims.

**WHAT IS CLAIMED IS:**

1. A system for loading an implantable device into a container, comprising:  
a loading element comprising a loading tunnel configured to gradually contract an implantable device into a compressed state of reduced size relative to an expanded state as the implantable device travels through the loading tunnel; and  
a puller element that is removably attached to the implantable device via a suture, wherein the puller element pulls the implantable device through the loading tunnel;  
wherein the puller element automatically releases the suture after the implantable device contracts into the compressed state.
2. The system of claim 1, further comprising a rotator that is disposed on the puller element that is configured to be removably attached to a portion of the suture, wherein rotation of the rotator causes the suture to detach from the rotator.
3. The system of claim 1, further comprising a plunger element, wherein the plunger element comprises an elongated portion that is configured to push the implantable device through the loading tunnel.
4. The system of claim 3, wherein the plunger element is configured to push the implantable device into a delivery catheter.
5. The system of claim 1, wherein the loading tunnel is a funnel housing defining an internal, funnel-shaped loading cavity.
6. The system of claim 5, wherein the loading tunnel further defines an internal transfer cavity that communicates with the loading cavity, the transfer cavity sized to receive the implantable device from the loading cavity and retain the implantable device in the compressed state.
7. The system of claim 6, wherein the loading tunnel further defines a container cavity that communicates with the transfer cavity, the container cavity sized to receive a container that receives the implantable device in the compressed state.

8. The system of claim 1, wherein the implantable device is a pulmonary implant.

9. The system of claim 1, wherein the container is a delivery catheter that is configured to deliver the pulmonary implant to a lung region.

10. The system of claim 1, further comprising a tension element that is configured to communicate a force to the loading tunnel.

11. The system of claim 1, further comprising a container locking element that is configured to secure and align the container with the loader element.




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 2C

4 / 9




FIG. 3




FIG. 4A




FIG. 4B




FIG.4C




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG.6C

## INTERNATIONAL SEARCH REPORT

International application No.  
**PCT/US2012/056968****A. CLASSIFICATION OF SUBJECT MATTER****A61F 2/76(2006.01)i, A61F 2/04(2006.01)I, A61M 31/00(2006.01)I, A61M 35/00(2006.01)I**

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

A61F 2/76; B65D 81/18; A61B 17/00; A61F 2/04; A61M 16/00; A62B 9/06; A61F 2/84

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) &amp; Keywords: compress, load, implant

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 2006-0162731 Al (WONDKA, A. et al.) 27 July 2006 See abstract ; claim 18; paragraphs [0017] , [0028] , [0069] - [0074] ; figures 10B, 11A, and HE.	1,3-9 2,10,11
X Y A	US 2010-0292779 Al (STRAUBINGER, H. et al.) 18 November 2010 See abstract ; paragraphs [0114H0115] , [0145] , [0164] ; figure 1.	1,5-7 3,4,8,9 2,10,11
X Y A	wo 98-14120 Al (MEDTRONIC INSTENT ISRAEL LTD.) 9 April 1998 See abstract ; page 12, lines 13-21 ; page 17, line 17 ; page 18, lines 10, 15-19 ; figure 3.	1,5,7 3,4,8,9 2,10,11
A	US 2008-0221703 Al (QUE, L. et al.) 11 September 2008 See abstract ; paragraphs [0025] , [0027] , and [0031] ; figure 1f.	1-11

 Further documents are listed in the continuation of Box C. See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

26 FEBRUARY 2013 (26.02.2013)

Date of mailing of the international search report

**27 FEBRUARY 2013 (27.02.2013)**

Name and mailing address of the ISA/KR



Facsimile No. 82-42-472-7140

Authorized officer

HAN, In Ho

Telephone No. 82-42-481-3362



**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

**PCT/US2012/056968**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2006-0 162731 A 1	27 .07 .2006	EP 18 12098 A2 JP 2008-520360 A US 20 10-0175693 A1 Wo 2006-055692 A2	0 1.08 ,2007 19 .06 ,2008 15 .07 ,2010 26 .05 ,2006
US 2010-0292779 A 1	18 . 1 1.20 10	EP 2429460 A1 US 20 10-0292780 A1 wo 20 10- 130297 A1 wo 20 10- 130789 A1	2 1.03 ,2012 18 . 11,2010 18 . 11,2010 18 . 11,2010
wo 9814120 A 1	09 .04 . 1998	AU 4635297 A EP 0929260 A1 US 05725519 A	24. 04 , 1998 2 1.07 , 1999 10 .03 , 1998
US 2008-0221703 A 1	11.09 .2008	EP 2 120821 A2 JP 20 10-520803 A US 8 100959 B2 wo 2008- 1 12574 A2 wo 2008- 1 12574 A3	25 . 11,2009 17 .06 ,2010 24. 0 1,2012 18 .09 ,2008 30 . 10 ,2008