



(51) International Patent Classification:

A61F 5/44 (2006.01) A61F 5/445 (2006.01)
A61F 5/441 (2006.01)

(21) International Application Number:

PCT/GB2014/050212

(22) International Filing Date:

28 January 2014 (28.01.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1301858.5 1 February 2013 (01.02.2013) GB

(71) Applicant: **SALTS HEALTHCARE LIMITED**
[GB/GB]; Richard Street, Aston, Birmingham, West Midlands B7 4AA (GB).

(72) Inventors: **ARGENT, Peter**; Salts Healthcare Limited, Richard Street, Aston, Birmingham, West Midlands B7 4AA (GB). **WILTSHIRE, Neil**; Salts Healthcare Limited, Richard Street, Aston, Birmingham, West Midlands B7 4AA (GB).

(74) Agent: **FORRESTERS**; Rutland House, 148 Edmund Street, Birmingham, West Midlands B3 2JA (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: OSTOMY APPLIANCE




Figure 1

(57) Abstract: An ostomy appliance (10) having first (12) and second (14) walls connected to each other at or near their peripheries, the first wall having a stoma-receiving opening (16), and a waste collecting cavity defined between the first and second walls, wherein the second wall includes viewing portion (20) through which the stoma-receiving opening can be viewed.

Title: Ostomy appliance

5 Description of Invention

The invention relates to an ostomy appliance for collecting human waste. It should be understood that the invention can be utilised in drainable and non-drainable ostomy appliances. The invention is applicable to both one piece
10 and two piece ostomy appliances.

According to a first aspect of the invention, we provide an ostomy appliance having:-

first and second walls connected to each other at or near their
15 peripheries, the first wall having a stoma-receiving opening; and
a waste collecting cavity defined between the first and second walls,
wherein the second wall includes viewing portion through which the
stoma-receiving opening can be viewed.

20 Further features of the first aspect of the invention are set out in claims 2 to 26 appended hereto.

Embodiments of the invention will now be described by way of example only with reference to the accompanying drawings, of which:-

25

Figure 1 is a rear view of a first embodiment of an ostomy appliance in accordance with the present invention;

Figure 2 is a front view of a first embodiment of an ostomy appliance in
30 accordance with the present invention;

Figure 3 is a cross-sectional view through the plane D-D of figure 1;

Figure 4 is a cross-sectional view through the plane C-C of figure 1;

Figure 5 is a rear view of a second embodiment of an ostomy appliance in
5 accordance with the present invention;

Figure 6 is a front view of a second embodiment of an ostomy appliance in
accordance with the present invention;

10 Figure 7 is a cross-sectional view through the plane B-B of figure 5;

Figure 8 is a cross-sectional view through the plane A-A of figure 5;

Figure 9 is a plan view of a component part of the second embodiment of the
15 present invention; and

Figures 10 to 12 are side views of the component part of figure 9 in
progressive stages of manufacture.

20 Referring firstly to figures 1, 2, 3 and 4, these show a first embodiment of an
ostomy appliance in accordance with the present invention, shown generally at
10. The general construction of the ostomy appliance 10 is similar to those
well known in the art and in that sense it includes first 12 and second 14 walls
connected to each other at or near their peripheries, for example by heat
25 welding or using an adhesive. The walls 12, 14 are opaque other than where
indicated below. The ostomy appliance shown is a drainable appliance,
meaning that its contents can be emptied through an opening 11 between the
walls 12, 14.

30 The first wall 12 has a stoma-receiving opening 16 and is connected to a
generally circular flange 18 which is manufactured from the hydrocolloid

material, for adhering the appliance 10 to a user around their stoma. The first 12 and second 14 walls define a waste collecting cavity (seen more clearly in figure 4).

- 5 The ostomy appliance 10 in accordance with the present invention advantageously includes a viewing portion 20 in the second wall 14 thereof through which the stoma receiving opening 16, and thus the stoma, can be viewed by a user. In this embodiment the viewing portion 20 is generally circular although it should be appreciated that it could take many other forms
10 so long as it is possible for the user to view at least a significant portion of the stoma-receiving opening 16.

- In the present invention the viewing portion is a transparent portion of an upper part of the second wall 14 generally opposite the stoma receiving opening 16.
15 In more detail, as can be seen from figures 1, 3 and 4, the second wall 14 includes, in an upper region thereof, an aperture 22 which defines the viewing portion 20 through which the stoma-receiving opening can be seen. The aperture 22 is closed by a transparent additional wall 24 which is connected to an exterior surface of the second wall 14 at or near its peripheries 13, by a
20 linear connection region 25, and around the aperture 22 (e.g. further heat welds or adhesives).

- As best seen in figure 1 the appliance 10 includes two filters 30 which permit gas to escape from the space between the walls 14, 24 to atmosphere. Each
25 gas filter 30 is positioned on an internally facing surface of the wall 24 and is adhered thereto adjacent an aperture (e.g. a slit) 31 in the wall 24. As can be seen from figure 1 the appliance 10 also includes a pair of gas flow path openings 32 each of which is positioned in the upper region (i.e. that which is covered by the wall 24) of the wall 14 and serves to provide a gas flow path
30 between the main waste collecting cavity (between walls 12, 14) and the cavity between the walls 14 and 24.

Now referring to figures 5 to 8 these show a second embodiment of an ostomy appliance 10' in accordance with the present invention. Feature similar to those in the first embodiment have been given the same reference numeral with the addition of a prime (') symbol and this will not be described in any further detail with regard to this embodiment.

This embodiment differs from the first embodiment in the arrangement and construction of the viewing portion 20' and the gas filters 30'. Rather than the viewing portion 20' being a circular portion, in this embodiment it is an upper portion 14'b of the second wall 14'. This D-shaped portion 14'b of the wall 14' is transparent and thus it is possible for the user to view the stoma-receiving opening 16'. The remainder of the wall 14' is opaque as is the entire wall 12'.

In the ostomy appliance 10' the gas filters 30' are provided as part of a gas filter assembly 40' which in the present example forms an integral part of the second wall 14'. In other words the gas filter assembly 40' is connected to and positioned in between the upper 14'b and lower 14'a portions of the second wall 14'. The gas filter assembly 40' is therefore connected to the viewing portion 20'.

The gas filter assembly 40' defines, in the present example, two gas filter chambers, each chamber containing one gas filter 30'. It should be appreciated, however, that fewer or more gas filter chambers could be provided and the number of gas filters within each chamber can be more than one. In the present example, as will become apparent hereinafter, the gas filter chambers are spaced from each other by a portion of wall 29'.

Turning to figures 9 through 12, these show the gas filter assembly 40' in plan view (figure 9) and then in its progressive stages of manufacture (figures 10 through 12). As can be seen from figure 9 the gas assembly 40' is a

strip/sheet of material (identical or similar to the material used for the walls of the appliance 10' - it must be liquid and gas impermeable) and is generally rectangular. Each gas chamber is defined by a folded end portion 41' of the sheet. Positioned either side of the central wall portion 29' is a portion of the sheet onto which the folded portion 41' is folded. This portion of the sheet includes a gas flow path 32' which in this example is covered by a gas permeable membrane 33'. As can be seen from figures 11 and 12 remote portions 41' of the sheet are folded back towards the central wall portion 29' where they are then adhered to the remainder of the sheet at linear connection zones 27'. As seen in figure 12 this provides a gas filter assembly 40' including a pair of gas filter chambers which are spaced from each other by the wall portion 29'. This component part is then connected to the upper transparent portion 14'b of the second wall 14' at lateral weld line 26' and to the lower portion 14'A of the wall 14' at the linear lateral weld line 26'. The gas filter assembly 40' thus becomes an integral part of the second wall 14' whilst permitting waste gases to exit from the main cavity (between the walls 12', 14'), through the gas chambers and to atmosphere.

It will be appreciated that any of the features of the second embodiment can be incorporated into the first embodiment, and vice versa, without departing with the scope of the present invention.

When used in this specification and claims, the terms "comprises" and "comprising" and variations thereof mean that the specified features, steps or integers are included. The terms are not to be interpreted to exclude the presence of other features, steps or components.

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any

combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS

1. An ostomy appliance having:-
first and second walls connected to each other at or near their
5 peripheries, the first wall having a stoma-receiving opening; and
a waste collecting cavity defined between the first and second walls,
wherein the second wall includes viewing portion through which the
stoma-receiving opening can be viewed.
- 10 2. An ostomy appliance according to claim 1 wherein said viewing portion
is a transparent portion of the second wall opposite the stoma-receiving
opening.
- 15 3. An ostomy appliance according to claim 1 or claim 2 wherein the
second wall includes an opening through which the stoma-receiving opening
can be viewed
4. An ostomy appliance according to claim 3 wherein the opening in the
second wall is covered by a transparent material.
- 20 5. An ostomy appliance according to any preceding claim wherein an
upper part of the second wall opposite the stoma-receiving opening is
transparent and a lower part of the second wall is opaque.
- 25 6. An ostomy appliance according to claim 5 wherein the upper and lower
parts of the second wall are separate flexible sheets which are connected to
each other.
- 30 7. An ostomy appliance according to claim 6 wherein said connection
extends laterally across the appliance.

8. An ostomy appliance according to any preceding claim wherein the appliance includes an outlet positioned at a bottom thereof for permitting emptying of the waste collecting cavity, and wherein a portion of the second wall positioned adjacent the outlet is opaque.

5

9. An ostomy appliance according to any preceding claim wherein the appliance includes a further wall connected to the first and second walls at or near their peripheries, the further wall including an opening or a transparent portion which is substantially aligned with the viewing portion of the second wall.

10

10. An ostomy appliance according to any preceding claim wherein the appliance includes an intermediate wall positioned in between the first and second walls which includes an opening or a transparent portion which is substantially aligned with the viewing portion of the second wall.

15

11. An ostomy appliance according to claim 10 wherein the intermediate wall is connected to the second wall at a connection zone.

12. An ostomy appliance according to claim 11 wherein said connection zone is positioned around the viewing portion of the second wall.

20

13. An ostomy appliance according to claim 11 or claim 12 wherein said connection zone extends completely around the viewing portion of the second wall.

25

14. An ostomy appliance according to any one of claims 10 to 13 wherein the first and intermediate walls are substantially the same length and wherein the second wall is shorter in length than the first and intermediate walls.

30

15. An ostomy appliance according to any preceding claim wherein the appliance includes a further viewing portion through which a lower portion of the waste collecting cavity can be viewed.

5 16. An ostomy appliance according to any preceding claim wherein the appliance includes two or more viewing portions through which the stoma-receiving opening can be viewed.

10 17. An ostomy appliance according to any preceding claim wherein a gas flow path is provided from the waste collecting cavity through the second wall, and if present, an intermediate wall, to atmosphere.

18. An ostomy appliance according to any preceding claim wherein the gas flow path includes one or more gas vents in the wall(s) of the appliance.

15

19. An ostomy appliance according to any preceding claim wherein the or each gas vent includes or is covered by a filter.

20 20. An ostomy appliance according to any preceding claim wherein the appliance includes a gas filter assembly supporting one or more gas filters, wherein the assembly includes a pair of walls which are connected to each other, and wherein the gas filter assembly is connected to the viewing portion of the second wall.

25 21. An ostomy appliance according to claim 20 wherein the gas filter assembly forms an integral part of the second wall.

30 22. An ostomy appliance according to claim 20 or claim 21 wherein the gas filter assembly defines two gas filter chambers, each chamber containing at least one gas filter.

22. An ostomy appliance according to claim 21 wherein the gas filter chambers are spaced from each other, preferably by a portion of wall.

23. An ostomy appliance according to claim 20, claim 21 or claim 22
5 wherein the gas filter assembly is manufactured from a single sheet of material, with each gas chamber being defined by a folded portion of the sheet.

24. An ostomy appliance according to claim 23 wherein each folded portion
10 is folded towards a central region of the assembly.



25. An ostomy appliance according to claim 24 wherein a remote edge of each folded portion is connected to the remainder of the sheet to form the gas filter chamber.


15

26. An ostomy appliance according to claim 25 wherein the remote edge is heat welded in place.

27. An ostomy appliance substantially as hereinbefore described with
20 reference to and as shown in the accompanying drawings.

28. Any novel feature or novel combination of features described herein and/or in the accompanying drawings.





3 / 4




Figure 5




Figure 6

Figure 9




Figure 10



Figure 11



Figure 12



INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2014/050212

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F5/44 A61F5/441 A61F5/445
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 570 490 A (BERGER LEON) 16 March 1971 (1971-03-16) column 2, line 58 - column 4, line 27; figure 2	1-16,27, 28
X	----- US 2008/269699 A1 (O'TOOLE LOIS DIANE [US]) 30 October 2008 (2008-10-30) paragraph [0025]; figures 1,2	1-8
X	----- US 4 319 571 A (WINCHELL FRANK J) 16 March 1982 (1982-03-16) column 2, line 22 - line 24 column 5, line 26 - line 39; figures 1,10,11	1-8,15, 16
	----- -/--	

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 April 2014

Date of mailing of the international search report

17/04/2014

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Arjona López, G

INTERNATIONAL SEARCH REPORT

International application No

PCT/GB2014/050212

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2011/150936 A1 (COLOPLAST AS [DK]; SCHERTIGER LARS OLAV [DK]; TORSTENSEN JAN [DK]; LUT) 8 December 2011 (2011-12-08)	1,5-7, 9-14, 17-21, 24-26
Y	page 13, line 14 - page 14, line 1 page 26, line 9 - line 26; figures 1-3 -----	22,23
X	WO 2007/134608 A2 (COLOPLAST AS [DK]; CHRISTENSEN CLAUS BO VOEGE [DK]; KRAGH PETER [DK];) 29 November 2007 (2007-11-29)	1,2, 17-19
A	page 15, line 23 - page 16, line 5; figures 5,6 -----	9
X	US 3 780 739 A (FRANK M) 25 December 1973 (1973-12-25)	1,2,8
A	column 1, line 58 - column 3, line 22 column 5, line 2; figures 1,2,8 -----	10
Y	WO 2011/150937 A1 (COLOPLAST AS [DK]; LUTHER PREBEN [DK]; SCHERTIGER LARS OLAV [DK]; TORS) 8 December 2011 (2011-12-08) page 8, line 29 - page 9, line 14; figures 5,6 -----	22,23

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/GB2014/050212

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3570490	A	16-03-1971	NONE	
US 2008269699	A1	30-10-2008	NONE	
US 4319571	A	16-03-1982	NONE	
WO 2011150936	A1	08-12-2011	AU 2011260705 A1 CA 2801430 A1 CN 102933180 A EP 2575704 A1 JP 2013526989 A US 2013072886 A1 WO 2011150936 A1	13-12-2012 08-12-2011 13-02-2013 10-04-2013 27-06-2013 21-03-2013 08-12-2011
WO 2007134608	A2	29-11-2007	AU 2007252105 A1 BR PI0712258 A2 CA 2652748 A1 CN 101453966 A EP 2029070 A2 JP 2009537262 A RU 2008151160 A US 2009163883 A1 WO 2007134608 A2	29-11-2007 17-01-2012 29-11-2007 10-06-2009 04-03-2009 29-10-2009 27-06-2010 25-06-2009 29-11-2007
US 3780739	A	25-12-1973	NONE	
WO 2011150937	A1	08-12-2011	CN 102917673 A EP 2575705 A1 US 2013072885 A1 WO 2011150937 A1	06-02-2013 10-04-2013 21-03-2013 08-12-2011